

Oracle® Database Express Edition

2 Day Plus Locator Developer Guide

10g Release 2 (10.2)

B28004-01

February 2006

Provides a quick start to storing and querying spatial (location-based) data, using the Oracle Locator feature of Oracle Database Express Edition.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software—Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Contents

Preface	vii
Audience	vii
Documentation Accessibility	vii
Related Documents	viii
Conventions	viii
 1 Using Locator: Scenario and Examples	
Overview of Spatial Data	1-1
Scenario for Using Spatial Data	1-2
Using the SDO_GEOMETRY Object Type	1-5
Loading Customer and Store Information, Including Locations	1-7
Updating the Spatial Metadata	1-8
Creating Spatial Indexes	1-9
Querying Spatial Data	1-9
Running the Scenario Script	1-11
Using Non-Point Geometry Types	1-13
Polygon	1-14
Rectangle	1-15
Polygon with a Hole	1-16
Line String	1-18
Compound Line String	1-19
Compound Polygon	1-20
Several Geometry Types	1-22

Index

List of Examples

1-1	SQL Script for Customers and Stores Scenario.....	1-3
1-2	Inserting Customer and Store Records	1-7
1-3	Updating the Spatial Metadata	1-8
1-4	Creating the Spatial Indexes.....	1-9
1-5	Finding Closest Customers to a Store	1-9
1-6	Finding Closest Customers, Ordered by Distance from Store	1-10
1-7	Finding Customers Within 100 Miles of a Store	1-11
1-8	SQL Statement to Insert a Polygon.....	1-15
1-9	SQL Statement to Insert a Rectangle	1-16
1-10	SQL Statement to Insert a Polygon with a Hole.....	1-17
1-11	SQL Statement to Insert a Line String.....	1-19
1-12	SQL Statement to Insert a Compound Line String.....	1-20
1-13	SQL Statement to Insert a Compound Polygon	1-21
1-14	SQL Statements to Insert Various Geometries.....	1-22

List of Figures

1-1	Location Query and Results: Three Closest Customers, with Distance.....	1-13
1-2	Polygon.....	1-15
1-3	Rectangle	1-16
1-4	Polygon with a Hole	1-17
1-5	Line String.....	1-18
1-6	Compound Line String.....	1-19
1-7	Compound Polygon	1-21

Preface

This guide provides a quick start to using spatial (location-based) data with the Oracle Locator feature of Oracle Database Express Edition (Oracle Database XE).

Audience

This guide is intended for those who need to store and manage spatial data in the database. It assumes that you are familiar with the main concepts and techniques described in *Oracle Database Express Edition 2 Day Developer Guide*, and especially that you know how to create, upload, and run SQL scripts.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

Related Documents

For comprehensive information about developing applications using Oracle Database XE, see *Oracle Database Express Edition 2 Day Developer Guide*.

For detailed conceptual, usage, and reference information about Oracle Spatial and Oracle Locator, see *Oracle Spatial User's Guide and Reference*.

Oracle error message documentation is only available in HTML. If you only have access to the Oracle Documentation CD, you can browse the error messages by range. Once you find the specific range, use your browser's "find in page" feature to locate the specific message. When connected to the Internet, you can search for a specific error message using the error message search feature of the Oracle online documentation.

Printed documentation is available for sale in the Oracle Store at

<http://oraclestore.oracle.com/>

To download free release notes, installation documentation, white papers, or other collateral, go to the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

<http://www.oracle.com/technology/membership>

If you already have a user name and password for OTN, then you can go directly to the documentation section of the OTN Web site at

<http://www.oracle.com/technology/documentation>

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Using Locator: Scenario and Examples

This chapter describes how to manage spatial (location-based) data, using the Oracle Locator feature of Oracle Database Express Edition (Oracle Database XE). It develops an extended example that shows the major steps required to store and use spatial data, and it includes some common queries.

It assumes that you are familiar with the main concepts and techniques described in *Oracle Database Express Edition 2 Day Developer Guide*, and especially that you know how to create SQL scripts and how to use SQL*Plus to run SQL scripts.

Note: You cannot use the Express Edition SQL Commands or SQL Scripts features to run a SQL script or enter a SQL statement that creates or requires a spatial index. You *must* instead use SQL*Plus, such as by selecting **Run SQL Command Line** from the Express Edition menus, and connect as a database user that has the Create Table privilege.

This chapter includes the following major sections:

- ["Overview of Spatial Data"](#) on page 1-1
- ["Scenario for Using Spatial Data"](#) on page 1-2
- ["Using the SDO_GEOMETRY Object Type"](#) on page 1-5
- ["Loading Customer and Store Information, Including Locations"](#) on page 1-7
- ["Updating the Spatial Metadata"](#) on page 1-8
- ["Creating Spatial Indexes"](#) on page 1-9
- ["Querying Spatial Data"](#) on page 1-9
- ["Running the Scenario Script"](#) on page 1-11
- ["Using Non-Point Geometry Types"](#) on page 1-13

See Also:

- *Oracle Spatial User's Guide and Reference* for conceptual, usage, and reference information about Oracle Locator.

Overview of Spatial Data

Spatial data represents the essential location characteristics (typically longitude and latitude coordinates) of objects, which are also referred to as geometry objects and which include geometry types such as points, lines, and polygons. The location

characteristics are stored using a special data type, SDO_GEOMETRY. Once spatial data is stored in an Oracle database, it can be easily manipulated, retrieved, and related to all other data stored in the database.

Oracle Locator, a feature of all editions of Oracle Database 10g, provides an integrated set of functions and procedures to efficiently store, manage, query, and analyze spatial data in an Oracle database, using standard SQL. Oracle Locator is a subset of Oracle Spatial, which is included in Oracle Database Enterprise Edition, and which adds high-end spatial functionality, including functions such as buffer generation, spatial aggregates, area calculations, and more; linear referencing; coordinate systems transformations; geocoding; a routing engine; topology and network data models; and support for georeferenced raster (GeoRaster) data.

See Also:

- The Oracle Locator appendix in *Oracle Spatial User's Guide and Reference* for detailed information about which Oracle Spatial features are and are not supported for Oracle Locator.

Scenario for Using Spatial Data

Consider the following business scenario. A company has several major retail stores. It needs to locate its customers who are near a given store, to inform them of new advertising promotions. To locate its customers and perform location-based analysis, the company must store location data for both its customers and stores.

The CUSTOMERS table has the following definition. (An actual customers table would have more information, but the definition is simplified for this scenario.)

```
CREATE TABLE customers (  
    customer_id NUMBER,  
    last_name VARCHAR2(30),  
    first_name VARCHAR2(30),  
    street_address VARCHAR2(40),  
    city VARCHAR2(30),  
    state_province_code VARCHAR2(2),  
    postal_code VARCHAR2(9),  
    cust_geo_location SDO_GEOMETRY);
```

The STORES table has the following definition:

```
CREATE TABLE stores (  
    store_id NUMBER,  
    description VARCHAR2(100),  
    street_address VARCHAR2(40),  
    city VARCHAR2(30),  
    state_province_code VARCHAR2(2),  
    postal_code VARCHAR2(9),  
    store_geo_location SDO_GEOMETRY);
```

Each table contains a column (cust_geo_location and store_geo_location) of the Oracle Spatial and Locator data type, SDO_GEOMETRY (described in ["Using the SDO_GEOMETRY Object Type"](#) on page 1-5). In these tables, the SDO_GEOMETRY columns hold the geocoded location of each customer's residence and each store. These geocoded locations are stored as two-dimensional points, whose coordinates are the longitude and latitude values associated with the location. For example, longitude-latitude value pair of (-63.136, 52.4854) indicates the point at 63.136 degrees longitude west of the Greenwich prime meridian and 52.4854 degrees latitude north of the Equator.

Note: Oracle Locator does not provide support for geocoding, that is, creating point geometry objects from specified address data. Oracle Spatial does support geocoding, using the SDO_GCDR package. However, if you already have the longitude and latitude points associated with your desired locations, you can use Oracle Locator to store and use the spatial data.

If you want, you can use the following statements in [Example 1–1](#) to perform the operations in all examples associated with this customers and stores scenario. Many examples in the remaining sections use excerpts from these statements.

Example 1–1 SQL Script for Customers and Stores Scenario

```
-- Clean up from any previous running of this procedure.

DROP TABLE customers;
DROP TABLE stores;
DROP INDEX customers_sidx;
DROP INDEX stores_sidx;
DELETE FROM USER_SDO_GEOM_METADATA
  WHERE TABLE_NAME = 'CUSTOMERS' AND COLUMN_NAME = 'CUST_GEO_LOCATION';
DELETE FROM USER_SDO_GEOM_METADATA
  WHERE TABLE_NAME = 'STORES' AND COLUMN_NAME = 'STORE_GEO_LOCATION';

-- Create table for customer information.

CREATE TABLE customers (
  customer_id NUMBER,
  last_name VARCHAR2(30),
  first_name VARCHAR2(30),
  street_address VARCHAR2(40),
  city VARCHAR2(30),
  state_province_code VARCHAR2(2),
  postal_code VARCHAR2(9),
  cust_geo_location SDO_GEOMETRY);

-- Create table for store information.

CREATE TABLE stores (
  store_id NUMBER,
  description VARCHAR2(100),
  street_address VARCHAR2(40),
  city VARCHAR2(30),
  state_province_code VARCHAR2(2),
  postal_code VARCHAR2(9),
  store_geo_location SDO_GEOMETRY);

-- Insert customer data.

INSERT INTO customers VALUES
  (1001,'Nichols', 'Alexandra',
   '17 Maple Drive', 'Nashua', 'NH','03062',
   SDO_GEOMETRY(2001, 8307,
    SDO_POINT_TYPE (-71.48923,42.72347,NULL), NULL, NULL));

INSERT INTO customers VALUES
  (1002,'Harris', 'Melvin',
   '5543 Harrison Blvd', 'Reston', 'VA', '20190',
```

```
SDO_GEOMETRY(2001, 8307,
  SDO_POINT_TYPE(-70.120133,44.795766,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1003,'Chang', 'Marian',
'294 Main St', 'Concord', 'MA','01742',
SDO_GEOMETRY(2001, 8307,
  SDO_POINT_TYPE (-71.351,42.4598,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1004,'Williams', 'Thomas',
'84 Hayward Rd', 'Acton', 'MA','01720',
SDO_GEOMETRY(2001, 8307,
  SDO_POINT_TYPE (-71.4559,42.4748,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1005,'Rodriguez', 'Carla',
'9876 Pine Lane', 'Sudbury', 'MA','01776',
SDO_GEOMETRY(2001, 8307,
  SDO_POINT_TYPE (-71.4242,42.3826,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1006,'Adnani', 'Ramesh',
'1357 Appletree Ct', 'Falls Church', 'VA','22042 ',
SDO_GEOMETRY(2001, 8307,
  SDO_POINT_TYPE (-77.1745,38.88505,NULL),NULL,NULL));

-- Insert stores data.

INSERT INTO stores VALUES
(101,'Nashua megastore',
'123 Commercial Way', 'Nashua', 'NH','03062',
SDO_GEOMETRY(2001, 8307,
  SDO_POINT_TYPE (-71.49074,42.7229,NULL),NULL,NULL));

INSERT INTO stores VALUES
(102,'Reston store',
'99 Main Blvd', 'Reston', 'VA','22070',
SDO_GEOMETRY(2001, 8307,
  SDO_POINT_TYPE (-77.34511,38.9521,NULL),NULL,NULL));

-- Add metadata to spatial view USER_SDO_GEOM_METADATA.

INSERT INTO USER_SDO_GEOM_METADATA (TABLE_NAME, COLUMN_NAME, DIMINFO, SRID)
VALUES ('CUSTOMERS', 'CUST_GEO_LOCATION',
SDO_DIM_ARRAY
  (SDO_DIM_ELEMENT('LONG', -180.0, 180.0, 0.5),
  SDO_DIM_ELEMENT('LAT', -90.0, 90.0, 0.5)),
8307);

INSERT INTO USER_SDO_GEOM_METADATA (TABLE_NAME, COLUMN_NAME, DIMINFO, SRID)
VALUES ('STORES', 'STORE_GEO_LOCATION',
SDO_DIM_ARRAY
  (SDO_DIM_ELEMENT('LONG', -180.0, 180.0, 0.5),
  SDO_DIM_ELEMENT('LAT', -90.0, 90.0, 0.5)),
8307);

-- Create spatial indexes.

CREATE INDEX customers_sidx ON customers(cust_geo_location)
```

```

INDEXTYPE IS mdsys.spatial_index;

CREATE INDEX stores_sidx ON stores(store_geo_location)
INDEXTYPE IS mdsys.spatial_index;

-- Perform location-based queries.

-- Find the 3 closest customers to store_id = 101.

SELECT /*+ordered*/
  c.customer_id,
  c.first_name,
  c.last_name
FROM stores s,
  customers c
WHERE s.store_id = 101
AND sdo_nn (c.cust_geo_location, s.store_geo_location, 'sdo_num_res=3')
  = 'TRUE';

-- Find the 3 closest customers to store_id = 101, and
-- order the results by distance.

SELECT /*+ordered*/
  c.customer_id,
  c.first_name,
  c.last_name,
  sdo_nn_distance (1) distance
FROM stores s,
  customers c
WHERE s.store_id = 101
AND sdo_nn
  (c.cust_geo_location, s.store_geo_location, 'sdo_num_res=3', 1)
  = 'TRUE'
ORDER BY distance;

-- Find all the customers within 100 miles of store_id = 101

SELECT /*+ordered*/
  c.customer_id,
  c.first_name,
  c.last_name
FROM stores s,
  customers c
WHERE s.store_id = 101
AND sdo_within_distance (c.cust_geo_location,
  s.store_geo_location,
  'distance = 100 unit=MILE') = 'TRUE';

```

Using the SDO_GEOMETRY Object Type

This section introduces the SDO_GEOMETRY type, which you must use to store spatial data as geometry objects. It does not contain a detailed explanation, which is provided in *Oracle Spatial User's Guide and Reference*.

The geometric description of a spatial object is stored in a single row, in a single column of object type SDO_GEOMETRY in a user-defined table. Any table that has a column of type SDO_GEOMETRY must have another column, or set of columns, that defines a unique primary key for that table. The SDO_GEOMETRY type is defined as:

```
CREATE TYPE sdo_geometry AS OBJECT (
```

```
SDO_GTYPE NUMBER,  
SDO_SRID NUMBER,  
SDO_POINT SDO_POINT_TYPE,  
SDO_ELEM_INFO SDO_ELEM_INFO_ARRAY,  
SDO_ORDINATES SDO_ORDINATE_ARRAY);
```

The SDO_GTYPE attribute indicates the type of the geometry. The SDO_GTYPE value is 4 digits in the format *dltt*, where *d* identifies the number of dimensions (2, 3, or 4), *l* identifies the linear referencing measure dimension for a three-dimensional linear referencing system (LRS) geometry, and *tt* identifies the geometry type (00 through 07). (LRS geometries are not supported with Oracle Locator, so the *l* value must be 0.) Examples of SDO_GTYPE values include 2001 for a two-dimensional point, 2002 for a two-dimensional line string, and 2003 for a two-dimensional polygon.

The SDO_SRID attribute can be used to identify a coordinate system (spatial reference system) to be associated with the geometry. If SDO_SRID is null, no coordinate system is associated with the geometry. If SDO_SRID is not null, it must contain a value from the SRID column of the SDO_COORD_REF_SYS table, and this value must be inserted into the SRID column of the USER_SDO_GEOM_METADATA view. The SRID value 8307 is associated with the widely used WGS84 longitude/latitude coordinate system.

The SDO_POINT attribute is used only for point data, and it is defined using the SDO_POINT_TYPE object type, which has the attributes X, Y, and Z, all of type NUMBER. If the SDO_ELEM_INFO and SDO_ORDINATES arrays are both null, and the SDO_POINT attribute is non-null, then the X and Y values are considered to be the coordinates for a point geometry. Otherwise, the SDO_POINT attribute is ignored. You should store point geometries in the SDO_POINT attribute for optimal storage.

The SDO_ELEM_INFO attribute is defined using a varying length array of numbers. This attribute lets you know how to interpret the ordinates stored in the SDO_ORDINATES attribute. Each triplet set of numbers is interpreted as follows:

- SDO_STARTING_OFFSET -- Indicates the offset within the SDO_ORDINATES array where the first ordinate for this element is stored. Offset values start at 1 and not at 0. Thus, the first ordinate for the first element will be at SDO_GEOMETRY.SDO_ORDINATES(1). If there is a second element, its first ordinate will be at SDO_GEOMETRY.SDO_ORDINATES(*n*), where *n* reflects the position within the SDO_ORDINATE_ARRAY definition (for example, 19 for the 19th number).
- SDO_ETYPE -- Indicates the type of the element.
- SDO_INTERPRETATION -- Means one of two things, depending on whether or not SDO_ETYPE is a compound element. If the SDO_ETYPE is not a compound element (1, 2, 1003, or 2003), the interpretation attribute determines how the sequence of ordinates for this element is interpreted. For example, a line string or polygon boundary may be made up of a sequence of connected straight line segments or circular arcs. If SDO_ETYPE is a compound element (4, 1005, or 2005), this field specifies how many subsequent triplet values are part of the element.

The valid SDO_ETYPE and SDO_INTERPRETATION value pairs are described in detail in *Oracle Spatial User's Guide and Reference*.

The SDO_ORDINATES attribute is defined using a varying length array (1048576) of NUMBER type that stores the coordinate values that make up the boundary of a spatial object. This array must always be used in conjunction with the SDO_ELEM_INFO varying length array. The values in the array are ordered by dimension. For example, a polygon whose boundary has four two-dimensional points is stored as {X1, Y1, X2, Y2, X3, Y3, X4, Y4, X1, Y1}. The number of dimensions associated with each point is stored as metadata in the USER_SDO_GEOM_METADATA view.

The SDO_GEOMETRY constructor is used to create a geometry object. The examples in ["Using Non-Point Geometry Types"](#) on page 1-13 show the use of the SDO_GEOMETRY constructor to create many different kinds of geometry objects.

Loading Customer and Store Information, Including Locations

You will use transactional insert operations to add new customers and their locations to the CUSTOMERS table, and new stores and their locations into the STORES table. A location can be stored as a point in an SDO_GEOMETRY column in a table. The customer or store location is associated with longitude and latitude values on the Earth's surface (for example, -63.136, 52.4854). Oracle Locator requires that you place the longitude value before the latitude value.

[Example 1-2](#) inserts some rows into the CUSTOMERS and STORES tables. In the INSERT statements, the SDO_GEOMETRY constructor is used to insert the point location.

Example 1-2 Inserting Customer and Store Records

```
-- Insert customer data.

INSERT INTO customers VALUES
(1001,'Nichols', 'Alexandra',
'17 Maple Drive', 'Nashua', 'NH','03062',
SDO_GEOMETRY(2001, 8307,
SDO_POINT_TYPE (-71.48923,42.72347,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1002,'Harris', 'Melvin',
'5543 Harrison Blvd', 'Reston', 'VA', '20190',
SDO_GEOMETRY(2001, 8307,
SDO_POINT_TYPE (-70.120133,44.795766,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1003,'Chang', 'Marian',
'294 Main St', 'Concord', 'MA','01742',
SDO_GEOMETRY(2001, 8307,
SDO_POINT_TYPE (-71.351,42.4598,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1004,'Williams', 'Thomas',
'84 Hayward Rd', 'Acton', 'MA','01720',
SDO_GEOMETRY(2001, 8307,
SDO_POINT_TYPE (-71.4559,42.4748,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1005,'Rodriguez', 'Carla',
'9876 Pine Lane', 'Sudbury', 'MA','01776',
SDO_GEOMETRY(2001, 8307,
SDO_POINT_TYPE (-71.4242,42.3826,NULL), NULL, NULL));

INSERT INTO customers VALUES
(1006,'Adnani', 'Ramesh',
'1357 Appletree Ct', 'Falls Church', 'VA','22042 ',
SDO_GEOMETRY(2001, 8307,
SDO_POINT_TYPE (-77.1745,38.88505,NULL),NULL,NULL));

-- Insert stores data.
```

```

INSERT INTO stores VALUES
(101, 'Nashua megastore',
'123 Commercial Way', 'Nashua', 'NH', '03062',
SDO_GEOMETRY(2001, 8307,
SDO_POINT_TYPE (-71.49074, 42.7229, NULL), NULL, NULL));

INSERT INTO stores VALUES
(102, 'Reston store',
'99 Main Blvd', 'Reston', 'VA', '22070',
SDO_GEOMETRY(2001, 8307,
SDO_POINT_TYPE (-77.34511, 38.9521, NULL), NULL, NULL));

```

Updating the Spatial Metadata

For each spatial column (type SDO_GEOMETRY), you must insert an appropriate row into the USER_SDO_GEOM_METADATA view to reflect the dimensional information for the area in which the data is located. You must do this before creating spatial indexes (see ["Creating Spatial Indexes"](#) on page 1-9) on the spatial columns.

The USER_SDO_GEOM_METADATA view has the following definition:

```

(
TABLE_NAME    VARCHAR2(32),
COLUMN_NAME   VARCHAR2(32),
DIMINFO       SDO_DIM_ARRAY,
SRID          NUMBER
);

```

The DIMINFO column is a varying length array of an object type, ordered by dimension, and has one entry for each dimension. The SDO_DIM_ARRAY type is defined as follows:

```
Create Type SDO_DIM_ARRAY as VARRAY(4) of SDO_DIM_ELEMENT;
```

The SDO_DIM_ELEMENT type is defined as:

```
Create Type SDO_DIM_ELEMENT as OBJECT (
SDO_DIMNAME VARCHAR2(64),
SDO_LB NUMBER,
SDO_UB NUMBER,
SDO_TOLERANCE NUMBER);

```

The SDO_DIM_ARRAY instance is of size n if there are n dimensions. That is, DIMINFO contains 2 SDO_DIM_ELEMENT instances for two-dimensional geometries, 3 instances for three-dimensional geometries, and 4 instances for four-dimensional geometries. Each SDO_DIM_ELEMENT instance in the array must have valid (not null) values for the SDO_LB (lower bound), SDO_UB (upper bound), and SDO_TOLERANCE (tolerance) attributes.

Tolerance reflects the distance that two points can be apart and still be considered the same (for example, to accommodate rounding errors), and thus reflects the precision of the spatial data. The tolerance value must be a positive number greater than zero.

[Example 1-3](#) inserts rows into the USER_SDO_GEOM_METADATA view, with dimensional information for each spatial column. In both cases, the dimensional range is the entire Earth, and the coordinate system is the widely used WGS84 (longitude/latitude) system (spatial reference ID = 8307).

Example 1-3 Updating the Spatial Metadata

```
INSERT INTO USER_SDO_GEOM_METADATA (TABLE_NAME, COLUMN_NAME, DIMINFO, SRID)
```



```
VALUES ('CUSTOMERS', 'CUST_GEO_LOCATION',
      SDO_DIM_ARRAY
        (SDO_DIM_ELEMENT('LONG', -180.0, 180.0, 0.5),
         SDO_DIM_ELEMENT('LAT', -90.0, 90.0, 0.5)),
      8307);

INSERT INTO USER_SDO_GEOM_METADATA (TABLE_NAME, COLUMN_NAME, DIMINFO, SRID)
VALUES ('STORES', 'STORE_GEO_LOCATION',
      SDO_DIM_ARRAY
        (SDO_DIM_ELEMENT('LONG', -180.0, 180.0, 0.5),
         SDO_DIM_ELEMENT('LAT', -90.0, 90.0, 0.5)),
      8307);
```

In [Example 1–3](#), the longitude dimension of -180.0,180.0 and latitude dimension of -90.90 are required for geodetic data using the WGS84 coordinate system. The tolerance value of 0.5 means that any points less than one-half meter apart are considered to be the same point by any location-based operators or functions.

Creating Spatial Indexes

Spatial indexes are required for many queries that use Locator operators, and are important for performance for most spatial queries. Before you use spatial data for analysis or queries, create a spatial index on each spatial column. To create a spatial index, use the CREATE INDEX statement, and specify the INDEXTYPE IS MDSYS.SPATIAL_INDEX clause.

To create a spatial index, the database user must have the CREATE TABLE privilege.

[Example 1–4](#) creates spatial indexes on the CUSTOMERS.CUST_GEO_LOCATION and STORES.STORE_GEO_LOCATION columns.

Example 1–4 Creating the Spatial Indexes

```
CREATE INDEX customers_sidx ON customers(cust_geo_location)
INDEXTYPE IS mdsys.spatial_index;

CREATE INDEX stores_sidx ON stores(store_geo_location)
INDEXTYPE IS mdsys.spatial_index;
```

Querying Spatial Data

After you have created and populated spatial tables, updated the spatial metadata, and created spatial indexes, you can use Oracle Locator operator and functions to perform location-based queries. This section shows some queries to find the closest customers to a store and all customers within a specified distance of a store.

[Example 1–5](#) shows the SQL statement and the output for finding the three closest customers to the store with the STORE_ID value of 101. This example uses the SDO_NN ("nearest neighbors") operator.

Example 1–5 Finding Closest Customers to a Store

```
SELECT /*+ordered*/
      c.customer_id,
      c.first_name,
      c.last_name
FROM   stores s,
      customers c
WHERE  s.store_id = 101
```

```
AND sdo_nn (c.cust_geo_location, s.store_geo_location, 'sdo_num_res=3') = 'TRUE';
```

CUSTOMER_ID	FIRST_NAME	LAST_NAME
1001	Alexandra	Nichols
1003	Marian	Chang
1004	Thomas	Williams

In [Example 1-5](#):

- The `/*+ordered*/` hint is a hint to the optimizer, which ensures that the `STORES` table is searched first.
- The `SDO_NN` operator returns the `SDO_NUM_RES` value of the customers from the `CUSTOMERS` table who are closest to store 101. The first argument to `SDO_NN` (`c.cust_geo_location` in the example) is the column to search. The second argument to `SDO_NN` (`s.storeh_geo_location` in the example) is the location you want to find the neighbors nearest to. No assumptions should be made about the order of the returned results. For example, the first row returned is not guaranteed to be the customer closest to store 101. If two or more customers are an equal distance from the store, either of the customers may be returned on subsequent calls to `SDO_NN`.
- When you use the `SDO_NUM_RES` parameter, no other constraints are used in the `WHERE` clause. `SDO_NUM_RES` takes only proximity into account. For example, if you added a criterion to the `WHERE` clause because you wanted the five closest customers that resided in NY, and four of the five closest customers resided in NJ, the preceding query would return one row. This behavior is specific to the `SDO_NUM_RES` parameter, and its results may not be what you are looking for.

[Example 1-6](#) extends [Example 1-5](#) by showing the SQL statement and the output (reformatted for readability) for finding the three closest customers to the store with the `STORE_ID` value of 101, and ordering the results by distance (in meters) from the store. This example uses the `SDO_NN_DISTANCE` ancillary operator.

Example 1-6 Finding Closest Customers, Ordered by Distance from Store

```
SELECT /*+ordered*/
  c.customer_id,
  c.first_name,
  c.last_name,
  sdo_nn_distance (1) distance
FROM stores s,
  customers c
WHERE s.store_id = 101
AND sdo_nn
  (c.cust_geo_location, s.store_geo_location, 'sdo_num_res=3', 1) = 'TRUE'
ORDER BY distance;
```

CUSTOMER_ID	FIRST_NAME	LAST_NAME	DISTANCE
1001	Alexandra	Nichols	138.94486
1004	Thomas	Williams	27708.0946
1003	Marian	Chang	31396.4521

In [Example 1-6](#):

- The SDO_NN_DISTANCE operator is an ancillary operator to the SDO_NN operator; it can only be used within the SDO_NN operator. The argument for this operator is a number that matches the number specified as the last argument of SDO_NN; in this example it is 1. There is no hidden meaning to this argument; it is simply a tag. With SDO_NN_DISTANCE, you can order the results by distance and guarantee that the first row returned is the closest. If the data you are querying is stored as longitude and latitude, the default unit for SDO_NN_DISTANCE is meters.
- The SDO_NN operator also has a unit parameter that determines the unit of measurement returned by SDO_NN_DISTANCE; however, it is not used in this example.
- The ORDER BY distance clause ensures that the distances are returned in order, with the shortest distance first.

[Example 1–7](#) shows the SQL statement and the output for finding all customers within 100 miles of the store with the STORE_ID value of 101. This example uses the SDO_WITHIN_DISTANCE operator.

Example 1–7 Finding Customers Within 100 Miles of a Store

```
SELECT /*+ordered*/
  c.customer_id,
  c.first_name,
  c.last_name
FROM stores s,
  customers c
WHERE s.store_id = 101
AND sdo_within_distance (c.cust_geo_location,
  s.store_geo_location,
  'distance = 100 unit=MILE') = 'TRUE';
```

CUSTOMER_ID	FIRST_NAME	LAST_NAME
1005	Carla	Rodriguez
1004	Thomas	Williams
1003	Marian	Chang
1001	Alexandra	Nichols

In [Example 1–7](#):

- The SDO_WITHIN_DISTANCE operator returns the customers from the customers table that are within 100 miles of store 101. The first parameter to SDO_WITHIN_DISTANCE (c.cust_geo_location in the example) is the column to search. The second parameter (s.store_geo_location in the example) is the location from which you want to determine the distances. No assumptions should be made about the order of the returned results. For example, the first row returned is not guaranteed to be the customer closest to store 101.
- The distance keyword specifies the distance value (100 in this example).
- The unit keyword specifies the unit of measure for the distance keyword. The default unit is the unit of measure associated with the data. For longitude and latitude data, the default is meters; however, in this example it is miles.

Running the Scenario Script

You can create a SQL script that includes the operations described in preceding sections about the scenario for using spatial data: creating the tables, loading data into

the tables, updating the spatial metadata, creating the spatial indexes, and querying the spatial data. For example, you could create a script containing the statements in [Example 1-1](#) on page 1-3 to perform these operations for the sample scenario.

After you create the SQL script, you can test it by running it.

Note: You cannot use the Express Edition SQL Commands or SQL Scripts features to run a SQL script or enter a SQL statement that creates or requires a spatial index. You *must* instead use SQL*Plus, such as by selecting **Run SQL Command Line** from the Express Edition menus, and connect as a database user that has the Create Table privilege.

Follow these steps to run the SQL script:

1. On the Express Edition menus, select **Run SQL Command Line**. Specifically:
 - On Windows, from the **Start** menu, select **Programs** (or **All Programs**), then **Oracle Database 10g Express Edition**, then **Run SQL Command Line**.
 - On Linux, click the **Application** menu (on Gnome) or the **K** menu (on KDE), then point to **Oracle Database 10g Express Edition**, then **Run SQL Command Line**.
2. In the Run SQL Command Line window, connect to the Express Edition database as the user in whose schema you want to execute the SQL script. The following example connects as user `smith` with the password `jane`:

```
SQL> connect smith/jane
```


3. Use the SQL*Plus `@` ("at" sign) or `@@` (double "at" sign) command to specify the path and file name of the SQL script file. The following example (showing Windows syntax) runs a SQL script file named `locator_scenario.sql`:

```
SQL> @c:\my_scripts\locator_scenario
```

If you do not specify a file extension, `.sql` is assumed.

[Figure 1-1](#) shows the results of one of the queries in the scenario script shown in [Example 1-1](#). This query returns the three customers nearest to the store that has store ID 101, with the distance in meters of each customer's home from the store, and with the results ordered by distance from the store.

Figure 1–1 Location Query and Results: Three Closest Customers, with Distance



```

SQL> -- Find the 3 closest customers to store_id = 101, and
SQL> -- order the results by distance.
SQL>
SQL> SELECT /*+ordered*/
2      c.customer_id,
3      c.first_name,
4      c.last_name,
5      sdo_nn_distance (1) distance
6 FROM stores s,
7      customers c
8 WHERE s.store_id = 101
9 AND sdo_nn
10      (c.cust_geo_location, s.store_geo_location, 'sdo_num_res=3', 1)
11      = 'TRUE'
12 ORDER BY distance;

```

CUSTOMER_ID	FIRST_NAME	LAST_NAME	DISTANCE
1001	Alexandra	Nichols	138.94486
1004	Thomas	Williams	27708.0946
1003	Marian	Chang	31396.4521

```

SQL>

```

As shown in Figure 1–1, the results indicate that Alexandra Nichols lives about 139 meters from the store, Thomas Williams lives about 27.7 kilometers from the store, and Marian Chang lives about 31.4 kilometers from the store.

Using Non-Point Geometry Types

The examples so far in this chapter have shown point geometries, because the scenario involved the use of addresses that are represented as points. However, with Locator you can store and use many other types of geometries, such as lines (representing rivers, roads, pipelines, and so on) and polygons (representing any areas, such as counties, states, provinces, countries, and so on).

This section contains examples of creating non-point geometries. The examples include some explanation, but for detailed explanations of these geometry types, see *Oracle Spatial User's Guide and Reference*.

The examples do not use the WGS84 longitude/latitude coordinate system. Instead, they use a null coordinate system, which is not Earth-based and which reflects an arbitrary grid on a plane. All examples except those in "Several Geometry Types" on page 1-22 use a table named COLA_MARKETS. The following statements were used to create the COLA_MARKETS table, add its metadata to the USER_SDO_GEOMETRY view, and create a spatial index for its SDO_GEOMETRY column.

```

-- Create a table for cola (soft drink) markets in a
-- given geography (such as city or state).
-- Each row will be an area of interest for a specific
-- cola (for example, where the cola is most preferred
-- by residents, where the manufacturer believes the
-- cola has growth potential, and so on).

```


```
CREATE TABLE cola_markets (  
  mkt_id NUMBER PRIMARY KEY,  
  name VARCHAR2(32),  
  shape SDO_GEOMETRY);  
  
-----  
-- UPDATE METADATA VIEW --  
-----  
-- Update the USER_SDO_GEOM_METADATA view. This is required  
-- before the Spatial index can be created. Do this only once for each  
-- layer (that is, table-column combination; here: COLA_MARKETS and SHAPE).  
  
INSERT INTO user_sdo_geom_metadata  
  (TABLE_NAME,  
   COLUMN_NAME,  
   DIMINFO,  
   SRID)  
VALUES (  
  'cola_markets',  
  'shape',  
  SDO_DIM_ARRAY(  
    -- 20X20 grid  
    SDO_DIM_ELEMENT('X', 0, 20, 0.005),  
    SDO_DIM_ELEMENT('Y', 0, 20, 0.005)  
  ),  
  NULL -- SRID  
);  
  
-----  
-- CREATE THE SPATIAL INDEX --  
-----  
  
CREATE INDEX cola_spatial_idx  
  ON cola_markets(shape)  
  INDEXTYPE IS MDSYS.SPATIAL_INDEX;
```

This section contains the following subsections:

- ["Polygon" on page 1-14](#)
- ["Rectangle" on page 1-15](#)
- ["Polygon with a Hole" on page 1-16](#)
- ["Line String" on page 1-18](#)
- ["Compound Line String" on page 1-19](#)
- ["Compound Polygon" on page 1-20](#)
- ["Several Geometry Types" on page 1-22](#)

Polygon

[Figure 1–2](#) illustrates a polygon.

Figure 1–2 Polygon

In the SDO_GEOMETRY definition of the geometry illustrated in [Figure 1–2](#):

- SDO_GTYPE = 2003. The 2 indicates two-dimensional, and the 3 indicates a polygon.
- SDO_SRID = NULL.
- SDO_POINT = NULL.
- SDO_ELEM_INFO = (1,1003,1). The 1 in 1003 indicates an exterior polygon ring. The final 1 in 1,1003,1 indicates that this is a simple polygon whose vertices are connected by straight line segments, and you must specify coordinates for each vertex point, with the last set of coordinates being the same as the first set.
- SDO_ORDINATES = (5,1, 8,1, 8,6, 5,7, 5,1). These identify the vertices of the polygon, with the first and last coordinates the same. Because this is an exterior polygon ring (this simple polygon has no interior ring), the coordinates are in counterclockwise order.


[Example 1–8](#) shows a SQL statement that inserts the geometry illustrated in [Figure 1–2](#) into the database.

Example 1–8 SQL Statement to Insert a Polygon

```
INSERT INTO cola_markets VALUES(
  301,
  'polygon',
  SDO_GEOMETRY(
    2003, -- two-dimensional polygon
    NULL,
    NULL,
    SDO_ELEM_INFO_ARRAY(1,1003,1), -- one polygon (exterior polygon ring)
    SDO_ORDINATE_ARRAY(5,1, 8,1, 8,6, 5,7, 5,1)
  )
);
```

Rectangle

[Figure 1–3](#) illustrates a rectangle.

Figure 1–3 Rectangle

In the SDO_GEOMETRY definition of the geometry illustrated in [Figure 1–3](#):

- SDO_GTYPE = 2003. The 2 indicates two-dimensional, and the 3 indicates a polygon.
- SDO_SRID = NULL.
- SDO_POINT = NULL.
- SDO_ELEM_INFO = (1, 1003, 3). The final 3 in 1,1003,3 indicates that this is a rectangle. Because it is a rectangle, only two ordinates are specified in SDO_ORDINATES (lower-left and upper-right).
- SDO_ORDINATES = (1,1, 5,7). These identify the lower-left and upper-right ordinates of the rectangle.


[Example 1–9](#) shows a SQL statement that inserts the geometry illustrated in [Figure 1–3](#) into the database.

Example 1–9 SQL Statement to Insert a Rectangle

```
INSERT INTO cola_markets VALUES (
  302,
  'rectangle',
  SDO_GEOMETRY(
    2003, -- two-dimensional polygon
    NULL,
    NULL,
    SDO_ELEM_INFO_ARRAY(1,1003,3), -- one rectangle (1003 = exterior)
    SDO_ORDINATE_ARRAY(1,1, 5,7) -- only 2 points needed to
      -- define rectangle (lower left and upper right) with
      -- Cartesian-coordinate data
  )
);
```

Polygon with a Hole

[Figure 1–4](#) illustrates a polygon consisting of two elements: an exterior polygon ring and an interior polygon ring. The inner element in this example is treated as a void (a hole).

Figure 1–4 Polygon with a Hole

In the SDO_GEOMETRY definition of the geometry illustrated in [Figure 1–4](#):

- SDO_GTYPE = 2003. The 2 indicates two-dimensional, and the 3 indicates a polygon.
- SDO_SRID = NULL.
- SDO_POINT = NULL.
- SDO_ELEM_INFO = (1,1003,1, 19,2003,1). There are two triplet elements: 1,1003,1 and 19,2003,1.
1003 indicates that the element is an exterior polygon ring; 2003 indicates that the element is an interior polygon ring.
19 indicates that the second element (the interior polygon ring) ordinate specification starts at the 19th number in the SDO_ORDINATES array (that is, 7, meaning that the first point is 7,5).
- SDO_ORDINATES = (2,4, 4,3, 10,3, 13,5, 13,9, 11,13, 5,13, 2,11, 2,4, 7,5, 7,10, 10,10, 10,5, 7,5).
- The area (SDO_GEOM.AREA function) of the polygon is the area of the exterior polygon minus the area of the interior polygon. In this example, the area is 84 (99 - 15).
- The perimeter (SDO_GEOM.LENGTH function) of the polygon is the perimeter of the exterior polygon plus the perimeter of the interior polygon. In this example, the perimeter is 52.9193065 (36.9193065 + 16).

[Example 1–10](#) shows a SQL statement that inserts the geometry illustrated in [Figure 1–4](#) into the database.

Example 1–10 SQL Statement to Insert a Polygon with a Hole

```
INSERT INTO cola_markets VALUES (
  303,
  'polygon_with_hole',
  SDO_GEOMETRY(
    2003, -- two-dimensional polygon
```

```

NULL,
NULL,
SDO_ELEM_INFO_ARRAY(1,1003,1, 19,2003,1), -- polygon with hole
SDO_ORDINATE_ARRAY(2,4, 4,3, 10,3, 13,5, 13,9, 11,13, 5,13, 2,11, 2,4,
7,5, 7,10, 10,10, 10,5, 7,5)
)
);

```

An example of such a "polygon with a hole" might be a land mass (such as a country or an island) with a lake inside it. Of course, an actual land mass might have many such interior polygons: each one would require a triplet element in `SDO_ELEM_INFO`, plus the necessary ordinate specification.

Exterior and interior rings cannot be nested. For example, if a country has a lake and there is an island in the lake (and perhaps a lake on the island), a separate polygon must be defined for the island; the island cannot be defined as an interior polygon ring within the interior polygon ring of the lake.

In a **multipolygon** (polygon collection), rings must be grouped by polygon, and the first ring of each polygon must be the exterior ring. For example, consider a polygon collection that contains two polygons (A and B):

- Polygon A (one interior "hole"): exterior ring A0, interior ring A1
- Polygon B (two interior "holes"): exterior ring B0, interior ring B1, interior ring B2


The elements in `SDO_ELEM_INFO` and `SDO_ORDINATES` must be in one of the following orders (depending on whether you specify Polygon A or Polygon B first):

- A0, A1; B0, B1, B2
- B0, B1, B2; A0, A1

Line String

Figure 1–5 illustrates a line string made up of three straight line segments, starting at (3,2). Four points are required to represent this shape: (3,2), (4,6), (6,4), and (14,7).

Figure 1–5 Line String



In the SDO_GEOMETRY definition of the geometry illustrated in [Figure 1-5](#):

- SDO_GTYPE = 2002. The first 2 indicates two-dimensional, and the second 2 indicates one or more line segments.
- SDO_SRID = NULL.
- SDO_POINT = NULL.
- SDO_ELEM_INFO = (1,2,1). The 2,1 in 1,2,1 indicates a line string whose vertices are connected by straight line segments.
- SDO_ORDINATES = (3,2, 4,6, 6,4, 14,7).

[Example 1-11](#) shows a SQL statement that inserts the geometry illustrated in [Figure 1-5](#) into the database.


Example 1-11 SQL Statement to Insert a Line String

```
INSERT INTO cola_markets VALUES (
  304,
  'line_string',
  SDO_GEOMETRY(
    2002,
    NULL,
    NULL,
    SDO_ELEM_INFO_ARRAY(1,2,1), -- line string
    SDO_ORDINATE_ARRAY(3,2, 4,6, 6,4, 14,7)
  )
);
```

Compound Line String

[Figure 1-6](#) illustrates a crescent-shaped object represented as a compound line string made up of one straight line segment and one circular arc. Four points are required to represent this shape: points (10,10) and (10,14) describe the straight line segment, and points (10,14), (6,10), and (14,10) describe the circular arc.

Figure 1-6 Compound Line String



In the SDO_GEOMETRY definition of the geometry illustrated in [Figure 1-6](#):

- SDO_GTYPE = 2002. The first 2 indicates two-dimensional, and the second 2 indicates one or more line segments.
- SDO_SRID = NULL.
- SDO_POINT = NULL.
- SDO_ELEM_INFO = (1,4,2, 1,2,1, 3,2,2). There are three triplet elements: 1,4,2, 1,2,1, and 3,2,2.

The first triplet indicates that this element is a compound line string made up of two subelement line strings, which are described with the next two triplets.

The second triplet indicates that the line string is made up of straight line segments and that the ordinates for this line string start at offset 1. The end point of this line string is determined by the starting offset of the second line string, 3 in this instance.

The third triplet indicates that the second line string is made up of circular arcs with ordinates starting at offset 3. The end point of this line string is determined by the starting offset of the next element or the current length of the SDO_ORDINATES array, if this is the last element.

- SDO_ORDINATES = (10,10, 10,14, 6,10, 14,10).


[Example 1-12](#) shows a SQL statement that inserts the geometry illustrated in [Figure 1-6](#) into the database.

Example 1-12 SQL Statement to Insert a Compound Line String

```
INSERT INTO cola_markets VALUES(
  305,
  'compound_line_string',
  SDO_GEOMETRY(
    2002,
    NULL,
    NULL,
    SDO_ELEM_INFO_ARRAY(1,4,2, 1,2,1, 3,2,2), -- compound line string
    SDO_ORDINATE_ARRAY(10,10, 10,14, 6,10, 14,10)
  )
);
```

Compound Polygon

[Figure 1-7](#) illustrates an ice cream cone-shaped object represented as a compound polygon made up of one straight line segment and one circular arc. Five points are required to represent this shape: points (6,10), (10,1), and (14,10) describe one acute angle-shaped line string, and points (14,10), (10,14), and (6,10) describe the circular arc. The starting point of the line string and the ending point of the circular arc are the same point (6,10). The SDO_ELEM_INFO array contains three triplets for this compound line string. These triplets are {(1,1005,2), (1,2,1), (5,2,2)}.

Figure 1–7 Compound Polygon

In the SDO_GEOMETRY definition of the geometry illustrated in [Figure 1–7](#):

- SDO_GTYPE = 2003. The 2 indicates two-dimensional, and the 3 indicates a polygon.
- SDO_SRID = NULL.
- SDO_POINT = NULL.
- SDO_ELEM_INFO = (1,1005,2, 1,2,1, 5,2,2). There are three triplet elements: 1,1005,2, 1,2,1, and 5,2,2.

The first triplet indicates that this element is a compound polygon made up of two subelement line strings, which are described using the next two triplets.

The second triplet indicates that the first subelement line string is made up of straight line segments and that the ordinates for this line string start at offset 1. The end point of this line string is determined by the starting offset of the second line string, 5 in this instance. Because the vertices are two-dimensional, the coordinates for the end point of the first line string are at ordinates 5 and 6.

The third triplet indicates that the second subelement line string is made up of a circular arc with ordinates starting at offset 5. The end point of this line string is determined by the starting offset of the next element or the current length of the SDO_ORDINATES array, if this is the last element.

- SDO_ORDINATES = (6,10, 10,1, 14,10, 10,14, 6,10).

[Example 1–13](#) shows a SQL statement that inserts the geometry illustrated in [Figure 1–7](#) into the database.

Example 1–13 SQL Statement to Insert a Compound Polygon

```
INSERT INTO cola_markets VALUES (
  306,
  'compound_polygon',
  SDO_GEOMETRY(
    2003, -- two-dimensional polygon
    NULL,
```

```
        NULL,  
        SDO_ELEM_INFO_ARRAY(1,1005,2, 1,2,1, 5,2,2), -- compound polygon  
        SDO_ORDINATE_ARRAY(6,10, 10,1, 14,10, 10,14, 6,10)  
    )  
);
```

Several Geometry Types

Example 1–14 creates a table and inserts various geometries, including multipoints (point clusters), multipolygons, and collections. At the end, it calls the [SDO_GEOM.VALIDATE_GEOMETRY_WITH_CONTEXT](#) function to validate the inserted geometries. Note that some geometries are deliberately invalid, and their descriptions include the string `INVALID`.

Example 1–14 SQL Statements to Insert Various Geometries

```
CREATE TABLE t1 (  
    i NUMBER,  
    d VARCHAR2(50),  
    g SDO_GEOMETRY  
);  
INSERT INTO t1 (i, d, g)  
VALUES (  
    1,  
    'Line segment',  
    sdo_geometry (2002, null, null, sdo_elem_info_array (1,2,1),  
        sdo_ordinate_array (10,10, 20,10))  
);  
INSERT INTO t1 (i, d, g)  
VALUES (  
    2,  
    'Arc segment',  
    sdo_geometry (2002, null, null, sdo_elem_info_array (1,2,2),  
        sdo_ordinate_array (10,15, 15,20, 20,15))  
);  
INSERT INTO t1 (i, d, g)  
VALUES (  
    3,  
    'Line string',  
    sdo_geometry (2002, null, null, sdo_elem_info_array (1,2,1),  
        sdo_ordinate_array (10,25, 20,30, 25,25, 30,30))  
);  
INSERT INTO t1 (i, d, g)  
VALUES (  
    4,  
    'Arc string',  
    sdo_geometry (2002, null, null, sdo_elem_info_array (1,2,2),  
        sdo_ordinate_array (10,35, 15,40, 20,35, 25,30, 30,35))  
);  
INSERT INTO t1 (i, d, g)  
VALUES (  
    5,  
    'Compound line string',  
    sdo_geometry (2002, null, null,  
        sdo_elem_info_array (1,4,3, 1,2,1, 3,2,2, 7,2,1),  
        sdo_ordinate_array (10,45, 20,45, 23,48, 20,51, 10,51))  
);  
INSERT INTO t1 (i, d, g)  
VALUES (  
    6,
```

```

        'Closed line string',
        sdo_geometry (2002, null, null, sdo_elem_info_array (1,2,1),
            sdo_ordinate_array (10,55, 15,55, 20,60, 10,60, 10,55))
    );
INSERT INTO t1 (i, d, g)
VALUES (
    7,
    'Closed arc string',
    sdo_geometry (2002, null, null, sdo_elem_info_array (1,2,2),
        sdo_ordinate_array (15,65, 10,68, 15,70, 20,68, 15,65))
);
INSERT INTO t1 (i, d, g)
VALUES (
    8,
    'Closed mixed line',
    sdo_geometry (2002, null, null, sdo_elem_info_array (1,4,2, 1,2,1, 7,2,2),
        sdo_ordinate_array (10,78, 10,75, 20,75, 20,78, 15,80, 10,78))
);
INSERT INTO t1 (i, d, g)
VALUES (
    9,
    'Self-crossing line',
    sdo_geometry (2002, null, null, sdo_elem_info_array (1,2,1),
        sdo_ordinate_array (10,85, 20,90, 20,85, 10,90, 10,85))
);
INSERT INTO t1 (i, d, g)
VALUES (
    10,
    'Polygon',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,1003,1),
        sdo_ordinate_array (10,105, 15,105, 20,110, 10,110, 10,105))
);
INSERT INTO t1 (i, d, g)
VALUES (
    11,
    'Arc polygon',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,1003,2),
        sdo_ordinate_array (15,115, 20,118, 15,120, 10,118, 15,115))
);
INSERT INTO t1 (i, d, g)
VALUES (
    12,
    'Compound polygon',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,1005,2, 1,2,1, 7,2,2),
        sdo_ordinate_array (10,128, 10,125, 20,125, 20,128, 15,130, 10,128))
);
INSERT INTO t1 (i, d, g)
VALUES (
    13,
    'Rectangle',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,1003,3),
        sdo_ordinate_array (10,135, 20,140))
);
INSERT INTO t1 (i, d, g)
VALUES (
    14,
    'Circle',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,1003,4),
        sdo_ordinate_array (15,145, 10,150, 20,150))
);

```

```
INSERT INTO t1 (i, d, g)
VALUES (
    15,
    'Point cluster',
    sdo_geometry (2005, null, null, sdo_elem_info_array (1,1,3),
        sdo_ordinate_array (50,5, 55,7, 60,5))
);
INSERT INTO t1 (i, d, g)
VALUES (
    16,
    'Multipoint',
    sdo_geometry (2005, null, null, sdo_elem_info_array (1,1,1, 3,1,1, 5,1,1),
        sdo_ordinate_array (65,5, 70,7, 75,5))
);
INSERT INTO t1 (i, d, g)
VALUES (
    17,
    'Multiline',
    sdo_geometry (2006, null, null, sdo_elem_info_array (1,2,1, 5,2,1),
        sdo_ordinate_array (50,15, 55,15, 60,15, 65,15))
);
INSERT INTO t1 (i, d, g)
VALUES (
    18,
    'Multiline - crossing',
    sdo_geometry (2006, null, null, sdo_elem_info_array (1,2,1, 5,2,1),
        sdo_ordinate_array (50,22, 60,22, 55,20, 55,25))
);
INSERT INTO t1 (i, d, g)
VALUES (
    19,
    'Multiarc',
    sdo_geometry (2006, null, null, sdo_elem_info_array (1,2,2, 7,2,2),
        sdo_ordinate_array (50,35, 55,40, 60,35, 65,35, 70,30, 75,35))
);
INSERT INTO t1 (i, d, g)
VALUES (
    20,
    'Multiline - closed',
    sdo_geometry (2006, null, null, sdo_elem_info_array (1,2,1, 9,2,1),
        sdo_ordinate_array (50,55, 50,60, 55,58, 50,55, 56,58, 60,55, 60,60, 56,58))
);
INSERT INTO t1 (i, d, g)
VALUES (
    21,
    'Multiarc - touching',
    sdo_geometry (2006, null, null, sdo_elem_info_array (1,2,2, 7,2,2),
        sdo_ordinate_array (50,65, 50,70, 55,68, 55,68, 60,65, 60,70))
);
INSERT INTO t1 (i, d, g)
VALUES (
    22,
    'Multipolygon - disjoint',
    sdo_geometry (2007, null, null, sdo_elem_info_array (1,1003,1, 11,1003,3),
        sdo_ordinate_array (50,105, 55,105, 60,110, 50,110, 50,105, 62,108, 65,112))
);
INSERT INTO t1 (i, d, g)
VALUES (
    23,
    'Multipolygon - touching',
```



```

        sdo_geometry (2007, null, null, sdo_elem_info_array (1,1003,3, 5,1003,3),
            sdo_ordinate_array (50,115, 55,120, 55,120, 58,122))
    );
INSERT INTO t1 (i, d, g)
VALUES (
    24,
    'Multipolygon - tangent * INVALID 13351',
    sdo_geometry (2007, null, null, sdo_elem_info_array (1,1003,3, 5,1003,3),
        sdo_ordinate_array (50,125, 55,130, 55,128, 60,132))
);
INSERT INTO t1 (i, d, g)
VALUES (
    25,
    'Multipolygon - multi-touch',
    sdo_geometry (2007, null, null, sdo_elem_info_array (1,1003,1, 17,1003,1),
        sdo_ordinate_array (50,95, 55,95, 53,96, 55,97, 53,98, 55,99, 50,99, 50,95,
            55,100, 55,95, 60,95, 60,100, 55,100))
);
INSERT INTO t1 (i, d, g)
VALUES (
    26,
    'Polygon with void',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,1003,3, 5,2003,3),
        sdo_ordinate_array (50,135, 60,140, 51,136, 59,139))
);
INSERT INTO t1 (i, d, g)
VALUES (
    27,
    'Polygon with void - reverse',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,2003,3, 5,1003,3),
        sdo_ordinate_array (51,146, 59,149, 50,145, 60,150))
);
INSERT INTO t1 (i, d, g)
VALUES (
    28,
    'Crescent (straight lines) * INVALID 13349',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,1003,1),
        sdo_ordinate_array (10,175, 10,165, 20,165, 15,170, 25,170, 20,165,
            30,165, 30,175, 10,175))
);
INSERT INTO t1 (i, d, g)
VALUES (
    29,
    'Crescent (arcs) * INVALID 13349',
    sdo_geometry (2003, null, null, sdo_elem_info_array (1,1003,2),
        sdo_ordinate_array (14,180, 10,184, 14,188, 18,184, 14,180, 16,182,
            14,184, 12,182, 14,180))
);
INSERT INTO t1 (i, d, g)
VALUES (
    30,
    'Heterogeneous collection',
    sdo_geometry (2004, null, null, sdo_elem_info_array (1,1,1, 3,2,1, 7,1003,1),
        sdo_ordinate_array (10,5, 10,10, 20,10, 10,105, 15,105, 20,110, 10,110,
            10,105))
);
INSERT INTO t1 (i, d, g)
VALUES (
    31,
    'Polygon+void+island touch',

```

```
sdo_geometry (2007, null, null,  
  sdo_elem_info_array (1,1003,1, 11,2003,1, 31,1003,1),  
  sdo_ordinate_array (50,168, 50,160, 55,160, 55,168, 50,168, 51,167,  
    54,167, 54,161, 51,161, 51,162, 52,163, 51,164, 51,165, 51,166, 51,167,  
    52,166, 52,162, 53,162, 53,166, 52,166))  
);  
COMMIT;  
SELECT i, d, SDO_GEOM.VALIDATE_GEOMETRY_WITH_CONTEXT (g, 0.5) FROM t1;
```

Index

C

compound line string
 explanation and example, 1-19
compound polygon
 explanation and example, 1-20

D

dimension (in SDO_GTYPE), 1-6

E

ELEM_INFO (SDO_ELEM_INFO attribute), 1-6
ETYPE (SDO_ETYPE value), 1-6
exterior polygon ring, 1-16
exterior polygon rings, 1-16, 1-18

G

geometry types
 SDO_GTYPE, 1-6
GTYPE (SDO_GTYPE attribute), 1-6

I

indexing spatial data, 1-9
INTERPRETATION (SDO_INTERPRETATION
 value), 1-6
interior polygon ring, 1-16
interior polygon rings, 1-16, 1-18

L

line string
 compound
 explanation and example, 1-19
 explanation and example, 1-18
loading spatial data, 1-7
Locator
 description, 1-1
 using Oracle Locator with spatial data, 1-1

M

multipolygon, 1-18

O

Oracle Locator
 description, 1-1
 using with spatial data, 1-1

P

polygon
 compound
 explanation and example, 1-20
 explanation and example, 1-14
 exterior and interior rings, 1-16, 1-18
polygon collection, 1-18
polygon with hole
 explanation and example, 1-16

Q

querying spatial data, 1-9

R

rectangle
 explanation and example, 1-15

S

SDO_ELEM_INFO attribute, 1-6
SDO_ETYPE value, 1-6
SDO_GTYPE attribute, 1-6
SDO_INTERPRETATION value, 1-6
SDO_ORDINATES attribute, 1-6
SDO_POINT attribute, 1-6
SDO_SRID attribute, 1-6
SDO_STARTING_OFFSET value, 1-6
spatial data
 indexing, 1-9
 loading, 1-7
 overview, 1-1
 querying, 1-9
spatial indexes
 creating, 1-9
spatial metadata
 updating, 1-8
SQL*Plus
 running Locator scripts, 1-12

SRID
SDO_SRID attribute in SDO_GEOMETRY, 1-6

U

USER_SDO_GEOMETRY view
updating, 1-8