

# Oracle® Workshop for WebLogic

User Guide

Release 10.3

July 2008

ORACLE®

---

Product Title and BookTitle as a Variable (a variable, do not use legal marks such as TM or R), Release 10.3

Copyright © 2007, 2008, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

# Contents

- What's New in Workshop Version 10.3? . . . . . 1
  - Support for Java Enterprise Edition 5 . . . . . 1
  - Built on Eclipse 3.3.2 and Web Tools Platform 2.0.3 . . . . . 1
  - Supported by Windows Vista . . . . . 2
  - XMLBeans. . . . . 2
  - Workshop for WebLogic IDE Launcher . . . . . 2
- Location of Supported Platform Information. . . . . 2
- Known Limitations for Workshop 10.3 . . . . . 2



# Oracle Workshop for WebLogic Version 10.3 Release Notes

This document contains information on the following subjects:

- [What's New in Workshop Version 10.3?](#)
- [Location of Supported Platform Information](#)
- [Known Limitations for Workshop 10.3](#)

## What's New in Workshop Version 10.3?

### Support for Java Enterprise Edition 5

Workshop supports the following JEE5 technologies:

- Servlet 2.5
- JSP 2.1
- JSF 1.2
- JSTL 1.2
- EJB 3.0
- JAX-WS
- JAXB 2.0

### Built on Eclipse 3.3.2 and Web Tools Platform 2.0.3

Workshop version 10.3 is built on the Eclipse Platform, an open source framework that is now widely used for Java development. Workshop extends Eclipse 3.3.2 and the Web Tools Platform 2.0.3

## Supported by Windows Vista

Workshop version 10.3 is supported by Windows Vista.

## XMLBeans

Workshop version 10.3 supports XMLBeans 2.3.

## Workshop for WebLogic IDE Launcher

The WorkSpace Studio launcher has been discontinued. The Workshop for WebLogic IDE launcher is WORKSHOP\_HOME/workshop[.exe].

## Location of Supported Platform Information

For more information on platform support, including hardware and software requirements, see the [Supported Platforms](#) web site.

## Known Limitations for Workshop 10.3

[Table 1](#) lists the known limitations found in Workshop for WebLogic.

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3**

<b>Problem ID</b>	<b>Description</b>
<b>CR282777</b>	<p><b>The first time you run Project &gt; Clean after importing a project, Workshop for WebLogic may not clean all of the files from the .apt_src directory</b></p> <p>When a user imports a project including build directories such as .apt_src, all files in that directory might not get removed the first time a clean is performed. This only happens the first time, subsequent cleans correctly handle the generated directories.</p> <p><b>Platform:</b> All</p> <p><b>Workaround:</b> Manually delete the files in the .apt_src directory when performing a clean the first time after import. Once deleted, the new files that go into that directory are correctly handled by the clean action.</p>
<b>CR287585</b>	<p><b>When a web service or other artifact is in a web project that is part of more than one EAR, the Run on Server can produce the wrong URL.</b></p> <p>Using the Run on Server action on artifacts in a web project that is associated with multiple EARs in the workspace can launch the browser to the incorrect URL. That is, it will use the URL associated with the last EAR with which is was associated.</p> <p><b>Platforms:</b> All</p> <p><b>Workaround:</b> To workaround this issue, you can either</p> <ol style="list-style-type: none"> <li>close the EAR that is not to be used for the launch,</li> <li>remove the web project from the EAR that is not used for the launch, or</li> <li>manually update the URL in the browser to hit the correct EAR.</li> </ol>
<b>CR293197</b>	<p><b>Lost JVMTI events (especially breakpoints) when debugging with JRockit</b></p> <p>When debugging with the JRockit JVM you may experience performance problems and missed breakpoints.</p> <p><b>Platforms:</b> All</p> <p><b>Workaround:</b> Update to JRockit 5.0 R27.1 or later.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

Problem ID	Description
<b>CR294199</b>	<p data-bbox="243 383 1174 435"><b>Invocation of buffered Control methods will fail at runtime if deployed (via the IDE) to a server with more than one JMS Server</b></p> <p data-bbox="243 461 1174 696">The IDE will auto-deploy required Workshop libraries when deploying an application. The use of @MessageBuffer on Control methods creates a dependency on application-scoped JMS resources in the weblogic-controls library. If the weblogic-controls library is deployed (by the IDE) to a server with more than one JMS server, the library will deploy, but the application-scoped JMS resources will not be available. This is because the IDE depends on default sub-module targeting, and default sub-module targeting relies on the target containing exactly one JMS Server. A message similar to the following warns that there is an issue with the deployment:</p> <pre data-bbox="283 713 1174 895" style="margin-left: 40px;"> &lt;The JMS module named "WlwRuntimeAppScopedJMS" inside application "testLibWebApp" does not have a sub-deployment stanza named "WlwRuntimeAppScopedJMS". Without such a stanza no entities inside the module will be deployed, since the sub deployments inside of the sub-deployment stanza named "WlwRuntimeAppScopedJMS" control where JMS entities inside this module are targeted.&gt; </pre> <p data-bbox="243 913 1174 1025">Note that even though there is a warning message, the library is deployed to the server. This means that applications that are dependent on the library will also successfully deploy. However, invocation of buffered Control methods will fail at runtime with a message similar to the following:</p> <pre data-bbox="283 1043 1174 1121" style="margin-left: 40px;"> "Failed to invoke end componentFailed to invoke methodMessage buffering is not available - either the buffering MDB did not deploy or we are in a standalone WAR" </pre> <p data-bbox="243 1138 1174 1190">Note that this situation is most likely to occur when using domains that were not created with support for "Workshop for Weblogic Platform."</p> <p data-bbox="243 1208 397 1234"><b>Platforms:</b> All</p> <p data-bbox="243 1251 397 1277"><b>Workaround:</b></p> <p data-bbox="243 1286 1174 1338">Manually deploy the library using the weblogic.Deployer command. The form of the command is:</p> <pre data-bbox="243 1347 1174 1659" style="margin-left: 40px;"> java weblogic.Deployer   -username weblogic   -password weblogic   -adminurl t3://localhost:7001   -deploy   -name weblogic-controls-10.0   -source %WL_HOME%/common/deployable-libraries/weblogic-controls-10.0.ear   -targets cgServer   -submoduletargets cgJMSServer@WlwRuntimeAppScopedJMS@WseeJmsServer   -library -libspectver 10.0 </pre>



**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

Problem ID	Description
<b>CR301661</b>	<p data-bbox="314 388 928 418"><b>Buffered methods on ServiceControl may fail over JMS protocol</b></p> <p data-bbox="314 435 1228 517">Buffered operations on a ServiceControl must be void. However the Message Exchange Pattern (MEP) in the underlying WSDL can be either request/response (with an empty response), or oneway (a request with no response).</p> <p data-bbox="314 534 1228 616">In the case of a request/response MEP over JMS, the presence of @MessageBuffer will cause the request to deadlock and eventually timeout. The following warning message will generally be produced:</p> <pre data-bbox="354 638 1214 765"> Potential blocking operation {http://someNamespace}someOperation: a synchronous request/response invocation within a transaction using the JMS transport can cause deadlocks. Please refer to WebLogic documentation for details. </pre> <p data-bbox="314 782 848 808">The resulting error message will include text similar to:</p> <pre data-bbox="354 829 1228 878"> javax.xml.rpc.soap.SOAPFaultException: Failed to receive message java.io.IOException: Request timed out </pre> <p data-bbox="314 895 1018 921">Note: this only occurs when the transport protocol for the request is JMS.</p> <p data-bbox="314 939 458 965"><b>Platforms:</b> All</p> <p data-bbox="314 982 1228 1086"><b>Workaround:</b> If you can influence the design of the target JWS, having the JWS operation annotated with @Oneway will direct that the underlying MEP be oneway, and will avoid this situation. If you can not influence the design of the target JWS, then the workaround is to add the TransactionAttribute annotation to the ServiceControl operation:</p> <pre data-bbox="354 1107 1193 1190"> @MessageBuffer @TransactionAttribute(TransactionAttributeType.NOT_SUPPORTED) public void voidMethod(); </pre> <p data-bbox="314 1208 1228 1255">Note that the presence of the @TransactionAttribute will not change the transactional behavior of actions that occur within the calling application.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

Problem ID	Description
<b>CR304008</b>	<p data-bbox="243 383 1180 418"><b>Servlet 2.5 Implementation In WebLogic Server 10.0 Can Break 9.2 Beehive Applications</b></p> <p data-bbox="243 430 1180 552"><b>Description:</b> An issue may surface when a 9.2 Beehive application is deployed on WebLogic Server 10.0. The symptom with this scenario is a <code>java.lang.IllegalStateException</code> being thrown. The underlying issue is with the <code>javax.servlet.ServletException</code> which changed from Servlet 2.4 to Servlet 2.5.</p> <p data-bbox="243 557 1180 591"><b>Platforms:</b> WebLogic Server 10.0 or higher</p> <p data-bbox="243 597 1180 718"><b>Workaround:</b> Upgrade the application to use Beehive 10.0 libraries (which work with either Servlet 2.4 or Servlet 2.5). If the 9.2 application cannot be compiled in 10.0, then manually updating the deployment descriptors in the 9.2 application EAR to use the 10.0 Beehive libraries will resolve this issue. For example:</p> <p data-bbox="243 723 1180 758">For each <code>.war</code> in the 9.2 <code>.ear</code>, modify the following section of the <code>web-inf/weblogic.xml</code>:</p> <pre data-bbox="243 763 1180 911"> &lt;wls:library-ref&gt;   &lt;wls:library-name&gt;beehive-netui-1.0&lt;/wls:library-name&gt;   &lt;wls:specification-version&gt;1.0&lt;/wls:specification-version&gt;   &lt;wls:implementation-version&gt;1.0&lt;/wls:implementation-version&gt; &lt;/wls:library-ref&gt; </pre> <p data-bbox="243 921 1180 956">to look like:</p> <pre data-bbox="243 961 1180 1111"> &lt;wls:library-ref&gt;   &lt;wls:library-name&gt;beehive-netui-1.0.1-10.0&lt;/wls:library-name&gt;   &lt;wls:specification-version&gt;1.0&lt;/wls:specification-version&gt;   &lt;wls:implementation-version&gt;1.0.1.1&lt;/wls:implementation-version&gt; &lt;/wls:library-ref&gt; </pre>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

Problem ID	Description
<b>CR304502</b>	<p data-bbox="314 388 1201 449"><b>Users who upgrade an 8.x application to a 9.x/10.x application may experience issues when making multiple method calls to a JDBC control from a single page flow method</b></p> <p data-bbox="314 465 1231 557">Due to a change in transaction scope from page flows which has been documented in <a href="http://e-docs.bea.com/workshop/docs92/ws_platform/upgrading/conChangesDuringUpgrade.html">http://e-docs.bea.com/workshop/docs92/ws_platform/upgrading/conChangesDuringUpgrade.html</a></p> <p data-bbox="314 572 1231 598">See the section labeled: 'Controls are Not Automatically Run Within the Scope of a Transaction'</p> <p data-bbox="314 614 1231 756">Users who upgrade an 8.x application to a 9.x/10.x application may experience issues when making multiple method calls to a JDBC control from a single page flow method. The crux of the issue is that when the first call is made to the JDBC control a new transaction is created by our transaction interceptor. When that call returns the transaction is either committed or rolled back.</p> <p data-bbox="314 772 1231 855">On the next call to the JDBC control a new transaction is created, but the JDBC connection being used by the control cannot be used in another transaction (it has been associated as a resource of the first transaction).</p> <p data-bbox="314 871 1231 1013">The behavior in 8.x page flows was for the JDBC control to release its JDBC connection after each method invocation. The transaction scope for a control method being invoked from a page flow was to start a transaction at the beginning of the control method invocation, and end the transaction on the return of the method. If the control rolled back the transaction, all operations performed within that transaction would be rolled back as well.</p> <p data-bbox="314 1029 460 1055"><b>Platforms:</b> All</p> <p data-bbox="314 1060 857 1086"><b>Workaround:</b> There are several workarounds available:</p> <ol data-bbox="314 1102 1231 1260" style="list-style-type: none"> <li data-bbox="314 1102 1231 1185">1) If you do not want to use transactions (they were implicit in 8.x) the transaction interceptor annotations (inserted by the upgrader) can be removed from the control methods.</li> <li data-bbox="314 1208 1231 1260">2) If you want to use transactions, create a JTA transaction in the page flow method and either commit or rollback once the calls to the JDBC control are completed.</li> </ol>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

<b>Problem ID</b>	<b>Description</b>
<b>CR308749</b>	<p><b>Duplicate simple class names are not supported for web service controls with callbacks</b></p> <p>When multiple web service controls, with callbacks, have identical class names (ignoring package name) an error will occur in jwsc. This error will appear in the publish step in the ide, during the usable step in exported ant scripts, or when exporting an ear file from the ide. In previous versions of Workshop the exported ant scripts would incorrectly report that the assemble step had succeeded even though this condition was present. This was because the ant script did not attempt to run jwsc on garnered java files.</p> <p><b>Platforms:</b> All</p> <p><b>Workaround:</b> When using web service controls (ServiceControl) with callbacks make sure that each control file has a unique un-qualified class name. Differing the package name is not sufficient.</p>
<b>CR313306</b>	<p><b>Service control generation can produce incorrect callback method names</b></p> <p>Service control generation based on WSDL callbacks named with underscores and numbers can result in incorrect callback method names. This will occur if a lower case letter follows an underscore or number.</p> <p>For example, the following WSDL callback names:</p> <pre>a_b a4b</pre> <p>will result in the generation of the following callback method names:</p> <pre>a_B a4B</pre> <p>Note that the first character after a number or underscore has been capitalized.</p> <p>When the method is invoked, the following error will result.</p> <pre>javax.xml.rpc.JAXRPCException: SOAPFaultException - FaultCode [http://schemas.xmlsoap.org/soap/envelope/}Client] FaultString [Failed to get operation name from the incoming request]</pre> <p><b>Platforms:</b> 10.x</p> <p><b>Workaround:</b> Avoid callback method names with a lower case letter following an underscore or number.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

Problem ID	Description
<b>CR326326</b>	<p data-bbox="314 388 1197 449"><b>Workshop startup.jar cannot be used to run in headless mode on Linux unless an additional system property is defined</b></p> <p data-bbox="314 465 1228 522">The startup.jar provided with Workshop cannot be used to run in headless mode on Linux, unless the following system property is set to true:</p> <pre data-bbox="411 534 592 560">m7.disable.swt.init</pre> <p data-bbox="314 574 575 600"><b>Platforms:</b> Workshop 10.1</p> <p data-bbox="314 614 1228 696"><b>Workaround:</b> Launch workshop in headless mode with the system property m7.disable.swt.init set to true. Note that the DISPLAY system property must not be set for this workaround to succeed.</p>
<b>CR326466</b>	<p data-bbox="314 725 911 751"><b>Issue with Hibernate JPA deployment on Weblogic Server 10.0</b></p> <p data-bbox="314 767 1228 855">Hibernate JPA projects created in Workshop 10.1 or imported from Workshop Studio 3.x fail to deploy on Weblogic Server 10.0. The below workaround will help Hibernate JPA projects deploy but redeployment will require a server restart</p> <p data-bbox="314 869 666 895"><b>Platforms:</b> Workshop 10.1 and later</p> <p data-bbox="314 909 1193 935"><b>Workaround:</b> For EAR Projects - Modify weblogic-application.xml and add the following</p> <pre data-bbox="314 951 1032 1150">&lt;prefer-application-packages&gt;   &lt;package-name&gt;antlr.*&lt;/package-name&gt;   &lt;package-name&gt;org.apache.commons.*&lt;/package-name&gt;   &lt;package-name&gt;org.apache.oro.*&lt;/package-name&gt;   &lt;package-name&gt;oracle.*&lt;/package-name&gt; &lt;/prefer-application-packages&gt;</pre> <p data-bbox="314 1171 1013 1229">For Web Applications - Add the web project to an EAR and then modify weblogic-application.xml as described above.</p> <p data-bbox="314 1242 884 1269">Note: Redeployment of the project requires a server restart.</p>
<b>CR327602</b>	<p data-bbox="314 1295 985 1321"><b>After renaming project, old project is not undeployed from the server</b></p> <p data-bbox="314 1336 1228 1394">If you rename a project that belongs to an EAR, the previous project name will not be undeployed from WebLogic Server.</p> <p data-bbox="314 1407 575 1433"><b>Platforms:</b> Workshop 10.1</p> <p data-bbox="314 1447 1210 1494"><b>Workaround:</b> To remove the project from the server, undeploy and redeploy the application from WebLogic Server.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

<b>Problem ID</b>	<b>Description</b>
<b>CR327849</b>	<p><b>Problems deploying EJB project upgraded using command line upgrader</b></p> <p>You may encounter problems deploying an EJB project that has been upgraded using the command line upgrade tool upgradeStarter.</p> <p><b>Platforms:</b> Workshop 10.1</p> <p><b>Workaround:</b> Upgrade the project using the IDE instead of the command line tool. To upgrade using the Workshop IDE.</p>
<b>CR328406</b>	<p><b>Incomplete AppXRay database may be produced after upgrade</b></p> <p>After upgrade from Workshop version 8.1.x to 10.2 or migration from 9.2 through 10.0 to 10.2 the initial build of the upgraded application may produce an incomplete AppXRay database for web projects that have the AppXRay feature enabled. In this case the user may notice that the App Xaminer view does not show all dependencies correctly.</p> <p><b>Platforms:</b> Workshop 8.1 and later</p> <p><b>Workaround:</b> To correct this situation clean and rebuild the workspace (by selecting <b>Project &gt; Clean</b>).</p>
<b>CR334542</b>	<p><b>ExceptionInitializerError deploying web service on WebLogic Server 9.2</b></p> <p>When deploying a web service to pre-MP1 versions of WebLogic Server 9.2, you may encounter a ExceptionInitializerError.</p> <p><b>Platforms:</b> Workshop 10.2 and WebLogic Server 9.2</p> <p><b>Workaround:</b> Implement one of the following solutions:</p> <ol style="list-style-type: none"> <li>(1) Upgrade your WebLogic Server 9.2 installation to 9.2 MP1 or higher.</li> <li>(2) Or add the following flag to both the workSpaceStudio.ini file and WebLogic Server's start script for the VM.</li> </ol> <pre>-Dcom.sun.xml.namespace.QName.useCompatibleSerialVersionUID=1.0</pre>
<b>CR336597</b>	<p><b>Web application deployment descriptor graphical editor doesn't support &lt;resource-ref&gt; elements</b></p> <p>Workshop's graphical editor for deployment descriptors does not support &lt;resource-ref&gt; elements. The <b>Deployment Descriptor Elements</b> tree view (located above the source editor) and the <b>Outline</b> view do not support adding or editing &lt;resource-ref&gt; elements.</p> <p><b>Platforms:</b> All</p> <p><b>Workaround:</b> Use source view to add and edit &lt;resource-ref&gt; elements.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

<b>Problem ID</b>	<b>Description</b>
<b>CR340273</b>	<p><b>Filter dispatcher warnings from JSF webapp deploy</b></p> <p>The version of MyFaces bundled with Workshop logs warnings to the WebLogic Server console due to a bug in the MyFaces web.xml parser. This bug is tracked here:</p> <p><a href="http://issues.apache.org/jira/browse/MYFACES-1415">http://issues.apache.org/jira/browse/MYFACES-1415</a></p> <p>The warnings are harmless Oracle Workshop for WebLogic 10.3 Release Notes and result in no loss of functionality.</p> <p><b>Platforms:</b> All</p> <p><b>Workaround:</b> These warnings can be ignored.</p>
<b>CR342837</b>	<p><b>Some Workshop text fields do not support Ctrl+V paste</b></p> <p>In the presence of the WebLogic Portal Eclipse plugins, some of the Workshop text fields do not support the <b>Ctrl+V</b> paste operation.</p> <p><b>Platforms:</b> All</p> <p><b>Workaround:</b> Manually type text into these text fields.</p>
<b>CR342995</b>	<p><b>Linux: Workshop JSP design view does not support drag and drop</b></p> <p>On Linux, the Workshop JSP design view does not support drag and drop from the Design Palette.</p> <p><b>Platform:</b> Linux</p> <p><b>Workaround:</b> Drag-and-drop from the Design Palette onto the source view.</p>
<b>CR344306</b>	<p><b>Minimal support for JSP XML syntax</b></p> <p>The Workshop JSP designer does not support JSP's XML syntax and gives warnings when parsing XML JSPs. For example, use of an entity reference "&amp;amp;" for the character "&amp;" will report a warning in the Problems view that deployment is prevented.</p> <p><b>Platforms:</b> All</p> <p><b>Workaround:</b> These warnings can be ignored: JSP XML syntax does not hinder deployment of the application.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

<b>Problem ID</b>	<b>Description</b>
<b>CR350342</b>	<p><b>Projects upgraded from Workshop Studio 3.3 may require manual upgrade of Kodo license</b></p> <p>The Kodo license bundled with Workshop Studio 3.3 release has expired, so older applications which have the license file at &lt;Project_Home&gt;/src/license.bea need a manual upgrade.</p> <p><b>Platforms:</b> Applies to JPA/Kodo applications upgraded from Workshop Studio 3.3 to Workshop 10.1 and later.</p> <p><b>Workaround:</b></p> <p>Create a new project that supports JPA/Kodo. For details, see <a href="http://edocs.bea.com/wlw/docs101/guide/ormworkbench/conAddingEJB3Support.html">http://edocs.bea.com/wlw/docs101/guide/ormworkbench/conAddingEJB3Support.html</a></p> <p>Copy the license.bea file from the new project into the original project's src folder.</p>
<b>CR355189</b>	<p><b>Licensing concerns when Workshop Studio 10.2 and Workshop for WebLogic 10.2 are installed in same the BEA Home</b></p> <p>If a user has both Workshop for WebLogic 10.2 and Workshop Studio 10.2 installed in the same BEA_HOME and either the Workshop Studio trial or full license expires, all Workshop functionality (including both Workshop Studio and Workshop for WebLogic) will be unavailable.</p> <p><b>Platforms:</b> Workshop for Weblogic 10.2 and Workshop Studio 10.2.</p> <p><b>Workaround:</b> Uninstall Workshop Studio 10.2 by performing the following: Run uninstall, deselecting all components except Workshop Studio in the uninstall wizard. Launch the product again. The Workshop for WebLogic license will be used and Workshop for WebLogic functionality returns.</p>
<b>CR356110</b>	<p><b>Workshop closes console when the server fails to start</b></p> <p>When WebLogic Server fails to start in Workshop, the <b>Console</b> view may be closed making it difficult to monitor the errors associated with the failure to start.</p> <p><b>Platforms:</b> Workshop 10.2</p> <p><b>Workaround:</b> Follow the procedure below:</p> <ol style="list-style-type: none"> <li>1. In the <b>Server</b> view, double-click the server instance to open the <b>Server Overview</b>.</li> <li>2. In the section <b>Startup and Deployment</b>, uncheck <b>Launch WebLogic server in Eclipse Console</b>.</li> <li>3. Start WebLogic Server using the start up script located at &lt;domain_home&gt;\bin\startWebLogic.cmd .sh.</li> <li>4. To view the errors associated with the start up failure consult the command shell console output.</li> </ol>



**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

<b>Problem ID</b>	<b>Description</b>
<b>CR362046</b>	<p><b>WorkSpace Studio About Box may stop displaying plugin and configuration details after a BEA Product is removed from the BEA Home directory</b></p> <p>After uninstalling a BEA product from your BEA Home directory in which you have other products installed, the Plugin Details and Configuration Details buttons in the WorkSpace Studio IDE about box (<b>Help &gt; About BEA WorkSpace Studio</b>) may stop working. This is due to the fact that under some circumstances empty plugin directories may still be present after the plugins are removed and the IDE expects to locate, but can not find, plugin details in those directories.</p> <p><b>Platforms:</b> WorkSpace Studio 1.1</p> <p><b>Workaround:</b> Launch WorkSpace Studio with -clean.</p>
<b>CR365358</b>	<p><b>Error When Processing JAX-RPC Style Web Service Annotations Using JDK 6</b></p> <p>The following error occurs when JAX-RPC style web service annotations are processed by an Ant script generated with WebLogic Server 10.0 using JDK 6:</p> <pre>[apt] C:\mywebservice\JAXRPCService.java: Class: mywebservice.JAXRPCService contains mixed bindings. SOAPBinding.Style.RPC and SOAPBinding.Style.DOCUMENT cannot be mixed.</pre> <p><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p><b>Workaround:</b> Re-export the Ant script for the web service using Workshop 10.3 and reprocess. The Ant script export wizard is available by selecting <b>File &gt; Export &gt; Workshop Build Scripts &gt; Workshop Ant Scripts</b>.</p>
<b>CR367817</b>	<p><b>Error When Adding JAR to Web Module Through J2EE Module Dependencies Dialog</b></p> <p>The following error:</p> <pre>IWAE0010E An internal error occurred"</pre> <p>may occur if you attempt to add a JAR to a web module in the following way:</p> <ol style="list-style-type: none"> <li>1) Right-click the project in the <b>Project Explorer</b> view.</li> <li>2) Select <b>Properties</b>.</li> <li>3) Select on <b>J2EE Module Dependencies</b>.</li> <li>4) Click <b>Add Jars</b>.</li> <li>5) Select the target JAR.</li> <li>6) Click OK and click OK on the <b>Properties</b> dialog.</li> </ol> <p><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p><b>Workaround:</b> Add the JAR using the following dialog: right-click the project in the <b>Project Explorer</b> view and select <b>Properties &gt; Java Build Path</b>.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

Problem ID	Description
<b>CR370200</b>	<p data-bbox="243 383 1174 418"><b>Failure to Deploy Web Services Generated From WSDLs</b></p> <p data-bbox="243 430 1174 487">Web services generated from different WSDLs in a single JAX-WS project cannot be successfully deployed without manually modifying the deployment descriptors.</p> <p data-bbox="243 499 1174 557">Note that in a JAX-RPC project, you can simply add a WLS-specific annotation (i.e., WLHttpTransport). In a JAX-WS project, WLS-specific annotations are not supported.</p> <p data-bbox="243 569 1174 597"><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p data-bbox="243 602 1174 683"><b>Workaround:</b> Documentation on modifying the deployment descriptors is located in the <a href="#">WebLogic Web Service Deployment Descriptor Element Reference</a> (see the service-endpoint-address element).</p>
<b>CR370893</b>	<p data-bbox="243 701 1174 736"><b>Problems With Imported JSP Files With UTF-16LE Encoding</b></p> <p data-bbox="243 748 1174 805">After importing a JSP file with UTF-16LE encoding, Workshop sets the encoding to UTF-16, and, after editing and saving the file, the encoding will be reset to ISO-8859-1.</p> <p data-bbox="243 817 1174 845"><b>Platforms:</b> Workshop for WebLogic 10.2 and 10.3</p> <p data-bbox="243 850 1174 944"><b>Workaround:</b> Close the JSP file, right-click the target JSP file in the <b>Project view</b> and select <b>Properties</b>. On the <b>Resource</b> page, in the <b>Text file encoding</b> section, select <b>Other</b>, set the encoding to UTF-16LE and click <b>Ok</b>.</p>
<b>CR371257</b>	<p data-bbox="243 961 1174 996"><b>JAXB -&gt; XJC tool issue -&gt; resolving URIs like schemaLocation in folder selection</b></p> <p data-bbox="243 1008 1174 1100">When selecting a folder in the JAXB XJC wizard (<b>File &gt; New &gt; Other &gt; Web Services &gt; JAXB XJC Wizard</b>), binding file schema locations will not be resolved from the contents of the binding file. For example, if you have a folder that contains</p> <pre data-bbox="243 1112 395 1204">/folder   /binding.xjb   /foo.xsd</pre> <p data-bbox="243 1216 1174 1244">and the contents of the binding file contain the declaration</p> <pre data-bbox="243 1256 878 1279">&lt;jxb:bindings schemaLocation="foo.xsd" node="/xs:schema"&gt;</pre> <p data-bbox="243 1291 1174 1348">then selecting the /folder and running the wizard will result in the same error as running the wizard with only the binding file, i.e., it will not be able to locate foo.xsd.</p> <p data-bbox="243 1361 1174 1388"><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p data-bbox="243 1394 1174 1451"><b>Workaround:</b> If your JAXB binding file makes use of the schemaLocation attribute, ensure the schema specified is explicitly checked during file selection.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

<b>Problem ID</b>	<b>Description</b>
<b>CR372626</b>	<p><b>Web Services: Properties Editor Displays Incorrect Elements on Web Service Creation</b></p> <p>After opening a web service in a web service project configured using the facet set <b>Annotated Web Service Facets JAX-RPC (Recommended) (v10.3)</b>, the <b>Properties</b> view may display no elements or incorrect elements.</p> <p><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p><b>Workaround:</b> Refresh the <b>Properties</b> view by switching between the web service <b>Source View</b> and <b>Design View</b>.</p>
<b>CR373745</b>	<p><b>JBoss 4.2 &amp; 5.0 Fails to Suspend on a Breakpoint Using the Workshop JSP Editor</b></p> <p>When debugging JSP files running on JBoss 4.2 or 5.0, where your workspace contains two web projects each with index.jsp files with breakpoints set in them, the breakpoints may fail to suspend.</p> <p><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p><b>Workaround:</b> Set the breakpoint using the WTP JSP editor:</p> <ul style="list-style-type: none"> <li>- Close the <b>Workshop JSP Editor</b>.</li> <li>- Right click the JSP in the <b>Project Explorer</b> and select <b>Open With &gt; JSP Editor</b>.</li> <li>- Switch to the <b>Debug</b> perspective.</li> <li>- Select <b>Run &gt; Debug As &gt; Debug on Server</b>.</li> </ul>
<b>CR374069</b>	<p><b>Workshop Source Editor Does not Support Files with UTF-32(BE:0000 feff)/UTF-32(LE:fffe 0000) BOM</b></p> <p>Workshop for WebLogic 10.3 does not currently support saving JSP files with the following encodings:</p> <p style="padding-left: 40px;">UTF-32, big endian (0000 feff)</p> <p style="padding-left: 40px;">UTF-32, little endian (ffef 0000)</p> <p><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p><b>Workaround:</b> To view UTF-32BE and UTF-32LE encoded files in Source view, see the workaround for CR374070 below. However, the BOM is not preserved in the resulting saved artifact.</p>

**Table 1 Known Limitations in Oracle Workshop for WebLogic Version 10.3 (Continued)**

<b>Problem ID</b>	<b>Description</b>
<b>CR374070</b>	<p><b>Source View Incorrectly Displays UTF-16BE and UTF-32BE Encoded JSP Files</b></p> <p>After importing a JSP file with UTF-16BE or UTF-32BE encoding, the Source View may fail to display the page correctly.</p> <p><b>Platforms:</b> Workshop for WebLogic 10.2 and 10.3</p> <p><b>Workaround:</b> Close the JSP file, right-click the target JSP file in the <b>Project view</b> and select <b>Properties</b>. On the <b>Resource</b> page, in the <b>Text file encoding</b> section, select <b>Other</b>, set the encoding to UTF-16BE or UTF-32BE as appropriate and click <b>Ok</b>.</p>
<b>CR374342</b>	<p><b>IBM WebSphere 5 &amp; 6 Fails to Start in Debug Mode When Workshop is Started Using JRockit VM</b></p> <p>When IBM WebSphere 5 or 6 is started in debug mode when Workshop has been started using the JRockit VM, the following error will occur:</p> <pre>org.eclipse.core.runtime.CoreException: socket closed     at     com.m7.wide.eclipse.debugger.launch.WideSocketLaunchConnector.a     bort(WideSocketLaunchConnector.java:128) ...</pre> <p><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p><b>Workaround:</b> Switch the default JDK to the Sun JDK when developing with IBM Websphere app server. To switch the default JDK, change the -vm argument in the WORKSHOP_HOME/workshop.ini file.</p>
<b>CR374804</b>	<p><b>Tomcat server 4.1.x Fails to Start in Debug Mode Using JDK 1.4</b></p> <p>Workshop does not support Tomcat server version 4.1.x in debug mode when using JDK 1.4. When attempting to start server the following error occurs:</p> <pre>!ENTRY org.eclipse.wst.server.core 4 0 &lt;time_stamp&gt; !MESSAGE Timeout waiting for Tomcat v4.1 at localhost to start.</pre> <p><b>Platforms:</b> Workshop for WebLogic 10.3</p> <p><b>Workaround:</b> Switch to JDK 1.5. Note that you can switch the JDK version during server creation. Select <b>File &gt; New &gt; Server</b>. Select <b>Apache &gt; Tomcat v4.1 &gt; Next</b>. Use the <b>JRE</b> dropdown and the <b>Installed JREs</b> button to switch to JDK 1.5.</p>