

Schema Reference Manual

Sun™ ONE Messaging and Collaboration

Version 6.0

816-6710-10
December 2003

Copyright © 2003 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved. Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.sun.com/patents> and one or more additional patents or pending patent applications in the U.S. and in other countries. THIS PRODUCT CONTAINS CONFIDENTIAL INFORMATION AND TRADE SECRETS OF SUN MICROSYSTEMS, INC. USE, DISCLOSURE OR REPRODUCTION IS PROHIBITED WITHOUT THE PRIOR EXPRESS WRITTEN PERMISSION OF SUN MICROSYSTEMS, INC.

U.S. Government Rights - Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

This distribution may include materials developed by third parties.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and in other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, Java, Solaris, JDK, Java Naming and Directory Interface, JavaMail, JavaHelp, J2SE, iPlanet, the Duke logo, the Java Coffee Cup logo, the Solaris logo, the SunTone Certified logo and the Sun ONE logo are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon architecture developed by Sun Microsystems, Inc.

Legato and the Legato logo are registered trademarks, and Legato NetWorker, are trademarks or registered trademarks of Legato Systems, Inc. The Netscape Communications Corp logo is a trademark or registered trademark of Netscape Communications Corporation.

The OPEN LOOK and Sun(TM) Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

This product includes software developed by Computing Services at Carnegie Mellon University (<http://www.cmu.edu/computing/>).

Products covered by and information contained in this service manual are controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright © 2003 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, Etats-Unis. Tous droits réservés. Sun Microsystems, Inc. détient les droits de propriété intellectuelle relatifs à la technologie incorporée dans le produit qui est décrit dans ce document. En particulier, et ce sans limitation, ces droits de propriété intellectuelle peuvent inclure un ou plus des brevets américains listés à l'adresse <http://www.sun.com/patents> et un ou les brevets supplémentaires ou les applications de brevet en attente aux Etats - Unis et dans les autres pays. CE PRODUIT CONTIENT DES INFORMATIONS CONFIDENTIELLES ET DES SECRETS COMMERCIAUX DE SUN MICROSYSTEMS, INC. SON UTILISATION, SA DIVULGATION ET SA REPRODUCTION SONT INTERDITES SANS L'AUTORISATION EXPRESSE, ECRITE ET PREALABLE DE SUN MICROSYSTEMS, INC.

Cette distribution peut comprendre des composants développés par des tierces parties.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, Java, Solaris, JDK, Java Naming and Directory Interface, JavaMail, JavaHelp, J2SE, iPlanet, le logo Duke, le logo Java Coffee Cup, le logo Solaris, le logo SunTone Certified et le logo Sun[tm] ONE sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays.

Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

Le logo Netscape Communications Corp est une marque de fabrique ou une marque déposée de Netscape Communications Corporation.

L'interface d'utilisation graphique OPEN LOOK et Sun(TM) a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui, en outre, se conforment aux licences écrites de Sun.

Ce produit comprend du logiciel développé par Computing Services à Carnegie Mellon University (<http://www.cmu.edu/computing/>).

Les produits qui font l'objet de ce manuel d'entretien et les informations qu'il contient sont régis par la législation américaine en matière de contrôle des exportations et peuvent être soumis au droit d'autres pays dans le domaine des exportations et importations. Les utilisations finales, ou utilisateurs finaux, pour des armes nucléaires, des missiles, des armes biologiques et chimiques ou du nucléaire maritime, directement ou indirectement, sont strictement interdites. Les exportations ou réexportations vers des pays sous embargo des Etats-Unis, ou vers des entités figurant sur les listes d'exclusion d'exportation américaines, y compris, mais de manière non exclusive, la liste de personnes qui font objet d'un ordre de ne pas participer, d'une façon directe ou indirecte, aux exportations des produits ou des services qui sont régis par la législation américaine en matière de contrôle des exportations et la liste de ressortissants spécifiquement désignés, sont rigoureusement interdites.

LA DOCUMENTATION EST FOURNIE "EN L'ETAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFACON.

Contents

Who Should Read This Manual	13
What You Need to Know	14
How This Manual is Organized	14
Monospaced Font	15
Bold Monospaced Font	15
Italicized Font	15
Square or Straight Brackets	16
Command Line Prompts	16
Platform-specific Syntax	16
Where to Find Related Information	16
Messaging Server Documents	16
Calendar Server Documents	17
Where to Find This Manual Online	18
Related Third-Party Web Site References	18
 Chapter 1 Overview	 19
Data Model for Sun ONE LDAP Schema, v.2	19
Data Model for Sun ONE LDAP Schema, v.1	21
Sun ONE Messaging Server Schema Overview	22
Mail Recipient	23
Personal Address Book	24
Domains	25
Delegation of Management	26
Sun ONE Calendar Server Schema Overview	27
 Chapter 2 Object Classes	 31
List of Object Classes	31

Object Classes	32
domain	32
groupOfUniqueNames	33
icsAdministrator	34
icsCalendarDomain	35
icsCalendarDWPHost	35
icsCalendarGroup	36
icsCalendarResource	37
icsCalendarUser	37
inetAdmin	38
inetDomain	39
inetDomainAlias	40
inetDomainAuthInfo	40
inetLocalMailRecipient	41
inetMailAdministrator	42
inetMailGroup	43
inetMailUser	43
inetOrgPerson	44
inetResource	45
inetSubscriber	45
inetUser	46
ipUser	47
mailDomain	48
mailPublicFolder	49
msgVanityDomainUser	49
organization	50
organizationalUnit	50
pab	51
pabGroup	52
pabPerson	53
userPresenceProfile	53
 Chapter 3 Attributes	 55
List of Attributes	55
Attribute Definitions	61
adminRole	61
aliasedObjectName	62
businessCategory	63
calCalURI	63
calFBURL	64
cn	64
co	65
commonName (see cn)	66

countryName (see co)	66
dataSource	66
dateOfBirth	66
dc	67
description	67
domainUidSeparator	68
domOrgMaxUsers	69
domOrgNumUsers	70
facsimileTelephoneNumber	70
givenName	71
icsAdminRole	71
icsAlias	72
icsAllowedServiceAccess	72
icsAllowRights	73
icsAnonymousAllowWrite	75
icsAnonymousCalendar	76
icsAnonymousDefaultSet	76
icsAnonymousLogin	77
icsAnonymousSet	77
icsCalendar	78
icsCalendarOwned	78
icsCapacity	79
icsContact	79
icsDefaultAccess	80
icsDefaultSet	80
icsDomainAllowed	81
icsDomainNames	82
icsDomainNotAllowed	83
icsDWPBackEndHosts	84
icsDWPHost	85
icsExtended	85
icsExtendedDomainPrefs	86
icsExtendedGroupPrefs	87
icsExtendedResourcePrefs	88
icsExtendedUserPrefs	88
icsFirstDay	92
icsFreeBusy	92
icsGeo	93
icsMandatorySubscribed	93
icsMandatoryView	94
icsPartition	94
icsPreferredHost	95
icsQuota	96

icsRecurrenceBound	96
icsRecurrenceDate	97
icsRegularExpressions	97
icsSessionTimeout	98
icsSet	98
icsSourceHtml	100
icsStatus	100
icsSubscribed	102
icsTimezone	102
inetCanonicalDomainName	103
inetCoS	104
inetDomainBaseDN	105
inetDomainCertMap	106
inetDomainSearchFilter	106
inetDomainStatus	107
inetMailGroupStatus	109
inetResourceStatus	110
inetSubscriberAccountId	111
inetSubscriberChallenge	112
inetSubscriberResponse	112
inetUserHttpURL	113
inetUserStatus	113
mail	115
mailAccessProxyPreAuth	115
mailAccessProxyReplay	116
mailAdminRole	117
mailAllowedServiceAccess	117
mailAlternateAddress	120
mailAntiUBEService	121
mailAutoReplyMode	122
mailAutoReplySubject	123
mailAutoReplyText	123
mailAutoReplyTextInternal	124
mailAutoReplyTimeOut	124
mailClientAttachmentQuota	125
mailConversionTag	125
mailDeferProcessing	126
mailDeliveryFileURL	127
mailDeliveryOption	128
mailDomainAllowedServiceAccess	130
mailDomainCatchallAddress	132
mailDomainConversionTag	133
mailDomainDiskQuota	133

mailDomainMsgMaxBlocks	134
mailDomainMsgQuota	134
mailDomainReportAddress	135
mailDomainSieveRuleSource	136
mailDomainStatus	137
mailDomainWelcomeMessage	139
mailEquivalentAddress	139
mailFolderName	140
mailForwardingAddress	141
mailHost	141
mailMessageStore	142
mailMsgMaxBlocks	143
mailMsgQuota	143
mailProgramDeliveryInfo	144
mailPublicFolderDefaultRights	145
mailQuota	147
mailRejectText	148
mailRoutingAddress	149
mailRoutingHosts	149
mailRoutingSmartHost	150
mailSieveRuleSource	151
mailSMTPSubmitChannel	153
mailUserStatus	153
maxPabEntries	155
memberOf	155
memberOfPAB	156
memberOfPABGroup	156
memberURL	157
mgrpAddHeader	158
mgrpAllowedBroadcaster	158
mgrpAllowedDomain	159
mgrpAuthPassword	160
mgrpBroadcasterPolicy	161
mgrpDeliverTo	162
mgrpDisallowedBroadcaster	163
mgrpDisallowedDomain	164
mgrpErrorsTo	165
mgrpModerator	165
mgrpMsgMaxSize	166
mgrpMsgPrefixText	167
mgrpMsgRejectAction	168
mgrpMsgRejectText	169
mgrpMsgSuffixText	169

mgrpNoDuplicateChecks	170
mgrpRemoveHeader	170
mgrpRequestTo	171
mgrpRFC822MailMember	171
msgVanityDomain	172
multiLineDescription	173
nickName	173
nswcalDisallowAccess	174
nswmExtendedUserPrefs	174
o	175
objectClass	175
organizationName (see o)	176
organizationUnitName (see ou)	176
ou	176
owner	177
pabURI	177
parentOrganization	178
postalAddress	179
preferredLanguage	179
preferredMailHost	180
preferredMailMessageStore	181
seeAlso	182
sn	182
telephoneNumber	183
uid	183
un	184
uniqueMember	185
userId (see uid)	185
userPassword	185
vacationEndDate	186
vacationStartDate	187
 Chapter 4 Sun ONE Identity Server Classes and Attributes	 189
Object Classes	189
iplanet-am-managed-assignable-group	190
iplanet-am-managed-filtered-group	191
iplanet-am-managed-filtered-role	191
iplanet-am-managed-group	192
iplanet-am-managed-group-container	193
iplanet-am-managed-org-unit	193
iplanet-am-managed-people-container	194
iplanet-am-managed-person	195
iplanet-am-managed-role	195

iplanet-am-managed-static-group	196
iplanet-am-user-service	197
iPlanetPreferences	197
sunISManagedOrganization	198
sunManagedOrganization	199
sunNameSpace	199
sunServiceComponent	201
userPresenceProfile	201
Attributes	202
associatedDomain	203
inetGroupStatus	204
iplanet-am-group-subscribable	205
iplanet-am-modifiable-by	206
iplanet-am-role-aci-description	206
iplanet-am-role-aci-list	207
iplanet-am-role-any-options	208
iplanet-am-role-description	208
iplanet-am-role-managed-container-dn	209
iplanet-am-role-service-options	209
iplanet-am-role-type	210
iplanet-am-service-status	211
iplanet-am-static-group-dn	211
iplanet-am-user-account-life	211
iplanet-am-user-admin-start-dn	212
iplanet-am-user-alias-list	213
iplanet-am-user-auth-config	213
iplanet-am-user-auth-modules	214
iplanet-am-user-failure-url	214
iplanet-am-user-federation-info	215
iplanet-am-user-federation-info-key	215
iplanet-am-user-login-status	216
iplanet-am-user-password-reset-force-reset	217
iplanet-am-user-password-reset-options	217
iplanet-am-user-password-reset-passwordChanged	218
iplanet-am-user-password-reset-question-answer	218
iplanet-am-user-service-status	219
iplanet-am-user-success-url	219
preferredLocale	220
preferredTimeZone	220
sunAdditionalTemplates	221
sunKeyValue	221
sunNameSpaceUniqueAttrs	223
sunOrganizationAlias	223

sunOverrideTemplates	224
sunPreferredDomain	224
sunPreferredOrganization	225
sunRegisteredServiceName	226
sunServiceId	227
sunSmsPriority	228
sunXmlKeyValue	228

Chapter 5 iPlanet Delegated Administrator for Messaging Classes and Attributes 229

Object Classes	229
inetDomainOrg	230
inetMailGroupManagement	231
inetManagedGroup	231
nsManagedDept	232
nsManagedDeptAdminGroup	233
nsManagedDomain	233
nsManagedFamilyGroup	234
nsManagedISP	235
nsManagedMailList	235
nsManagedOrgUnit	236
nsManagedPerson	237
nsUniquenessDomain	237
Attributes	238
domainUidSeparator	239
domOrgMaxUsers	240
domOrgNumUsers	241
memberOfManagedGroup	241
mgmanAllowSubscribe	242
mgmanDenySubscribe	243
mgmanGoodbyeText	243
mgmanHidden	244
mgmanIntroText	244
mgmanJoinability	245
mgmanMemberVisibility	245
mgmanVisibility	247
mnggrpAdditionPolicy	247
mnggrpBillableUser	248
mnggrpCurrentUsers	248
mnggrpDeletionPolicy	249
mnggrpMailQuota	249
mnggrpMaxUsers	250
mnggrpStatus	250
mnggrpUserClassOfServices	251

nsDefaultMaxDeptSize	251
nsMaxDepts	252
nsMaxDomains	252
nsMaxMailLists	253
nsMaxUsers	254
nsNumDepts	254
nsNumDomains	255
nsNumMailLists	255
nsNumUsers	256
nsSearchFilter	257
nsdaCapability	257
nsdaDomain	258
nsdaModifiableBy	258
preferredMailMessageStore	259
 Appendix A General Information	 261
LDAP Overview	261
Attribute Syntax	262
Object Identifiers	262
Standard Time Zones	263
 Glossary	 271
 Index	 285

About This Manual

This manual serves as a reference for schema information for Sun™ Open Net Environment (ONE) Messaging and Collaboration products using LDAP, specifically Sun ONE Messaging Server and Sun ONE Calendar Server.

Topics covered in this chapter include:

- [Who Should Read This Manual](#)
- [What You Need to Know](#)
- [How This Manual is Organized](#)
- [Document Conventions](#)
- [Where to Find Related Information](#)
- [Where to Find This Manual Online](#)
- [Related Third-Party Web Site References](#)

Who Should Read This Manual

You should read this manual if you want to provision Sun ONE Messaging Server, or Sun ONE Calendar Server, using LDAP. The audience for this manual consists of:

- System architects who want to develop customized provisioning tools that interface between Messaging and Collaboration product entries in the LDAP directory and their existing source of users, groups, and domains information such as a company database or billing system.
- Site Administrators who want to know how to create domain, user, group, or resource entries using LDAP.

What You Need to Know

This manual assumes that you have a general understanding of the following:

- The Internet and the World Wide Web
- Sun ONE Administration Server
- Sun ONE Directory Server and LDAP
- Email and email concepts
- Calendar and calendar concepts
- Sun ONE Console
- RFC 2798, and RFC 2445

The RFC's may be found at the IETF web sites:

- <http://www.ietf.org/rfc/rfc2798.txt>
- <http://www.ietf.org/rfc/rfc2445.txt>
- ISO8601 DateTime Format

For a list of time zone names used with these products, see Appendix A, [Standard Time Zones](#).

In addition, you probably need to have a general understanding of either the two following products:

- iPlanet Delegated Administrator for Messaging, for use with Sun ONE LDAP Schema, v.1
- Sun ONE Identity Server, for use with Sun ONE LDAP Schema, v.2

How This Manual is Organized

This manual contains the following chapters and appendix:

- [About This Manual](#) (this chapter)
- [Chapter 1, "Overview"](#)
- [Chapter 2, "Object Classes"](#)
- [Chapter 3, "Attributes"](#)
- [Chapter 4, "Sun ONE Identity Server Classes and Attributes"](#)

- [Chapter 5, “iPlanet Delegated Administrator for Messaging Classes and Attributes”](#)
- [Appendix A, “General Information”](#)
- [Glossary](#)

Document Conventions

Monospaced Font

Monospaced font is used for any text that appears on the computer screen or text that you should type. It is also used for filenames, distinguished names, functions, and examples.

Bold Monospaced Font

Bold monospaced font is used to represent text within a code example that you should type. For example, you might see something like this:

```
./installer
```

In this example, `./installer` is what you would type at the command line.

Italicized Font

Italicized font is used to represent text that you enter using information that is unique to your installation (for example, variables). It is used for server paths and names.

For example, throughout this document you will see path references of the form:

msg_svr_base / . . .

The Messaging Server Base (*msg_svr_base*) represents the directory path in which you install the server. The default value of the *msg_svr_base* is `/opt/SUNWmsgsr`.

Square or Straight Brackets

Square (or straight) brackets [] are used to enclose optional parameters.

Command Line Prompts

Command line prompts (for example, % for a C-Shell, or \$ for a Korn or Bourne shell) are not displayed in the examples. Depending on which operating system you are using, you will see a variety of different command line prompts. However, you should enter the command as it appears in the document unless specifically noted otherwise.

Platform-specific Syntax

All paths specified in this manual are in UNIX® format. If you are using a Windows 2000-based Messaging and Collaboration, you should assume the Windows 2000 equivalent file paths whenever UNIX file paths are shown in this book.

Where to Find Related Information

In addition to this manual, Sun ONE Messaging Server, and Sun ONE Calendar Server come with supplementary information for administrators, end users and developers.

Messaging Server Documents

Use the following URL to see all the Messaging Server documentation:

http://docs.sun.com/coll/S1_MessagingServer_60

Listed below are the documents that are available:

- *Sun ONE Messaging Server Installation Guide*
- *Sun ONE Messaging Server Release Notes*
- *Sun ONE Messaging Server Administrator's Guide*
- *Sun ONE Messaging Server Reference Manual*

- *Sun ONE Messaging and Collaboration Schema Reference Manual*
- *Sun ONE Messaging Server Provisioning Guide*

If you are using Sun ONE LDAP Schema, v.1, use the Provisioning Guide found in the iPlanet Messaging Server 5.2 documents.

If you are using Sun ONE LDAP Schema v.2, use information found in the Sun Java Enterprise System documentation.

- *Sun ONE Messaging and Collaboration Event Notification Service Manual*
- *Sun ONE Messaging Server Messenger Express Customization Guide*
- *Sun ONE Messaging Server MTA Programmer's Reference Manual*

The Sun ONE Messaging Server product suite contains other products such as Sun ONE Console, Directory Server, and Administration Server. Documentation for these and other products can be found at the following URL:

<http://docs.sun.com/db/prod/sunone>

In addition to the software documentation, see the Sun ONE Messaging Server Software Forum for technical help on specific Messaging Server product questions. The forum can be found at the following URL:

<http://swforum.sun.com/jive/forum.jsp?forum=15>

Calendar Server Documents

Use the following URL to see all the Calendar Server documentation:

http://docs.sun.com/coll/S1_CalendarServer_60

The following documents are available:

- *Sun ONE Calendar Server Release Notes*
- *Sun ONE Calendar Server Installation Guide*
- *Sun ONE Calendar Server Administrator's Guide*
- *Sun ONE Calendar Server Programmer's Manual*
- *Sun ONE Messaging and Collaboration Schema Reference Manual*
- *Sun ONE Messaging and Collaboration Event Notification Service Manual*

Where to Find This Manual Online

You can find the *Sun ONE Messaging and Collaboration Schema Reference Manual* online in HTML and PDF formats.

To find this manual or other Sun ONE Messaging Server documentation, use the URL:

http://docs.sun.com/coll/S1_MessagingServer_60

Or, for this manual and other Sun ONE Calendar Server documentation, use the URL:

http://docs.sun.com/coll/S1_CalendarServer_60

Related Third-Party Web Site References

Third-party URLs are referenced in this document and provide additional, related information.

NOTE	Sun is not responsible for the availability of third-party Web sites mentioned in this document. Sun does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Sun will not be responsible or liable for any actual or alleged damage or loss caused by or in connection with the use of or reliance on any such content, goods, or services that are available on or through such sites or resources.
-------------	---

Overview

This chapter give an overview of Sun™ ONE Messaging and Collaboration schema. It contains the following sections:

- [Data Model for Sun ONE LDAP Schema, v.2](#)
- [Data Model for Sun ONE LDAP Schema, v.1](#)
- [Sun ONE Messaging Server Schema Overview](#)
- [Sun ONE Calendar Server Schema Overview](#)

Data Model for Sun ONE LDAP Schema, v.2

The basic data model of Sun ONE object classes is to extend LDAP entry *types* (for example, user, group, domain) created by *core object classes* by overlaying them with *shared classes* (object classes can be shared by more than one service) and *service-specific object classes* (classes specific to a certain type of server).

In addition, there are two ways to structure the LDAP data model: native mode (the preferred way) using only an Organization Tree, and compatibility (for backwards compatibility with earlier versions of Sun ONE or iPlanet™ LDAP based products) using both a DC Tree and an Organization Tree. Provisioning your LDAP differs depending on whether you chose the native or compatibility mode at installation time.

Use the Sun™ ONE Messaging and Collaboration User Management Utility (a command line utility) to add, modify and delete users, groups and domains.

For a discussion of the differences between the native and compatibility modes as regards LDAP data models, the *Sun Java™ Enterprise System Installation Guide*.

For more information on RFC 2798, RFC 2252, and internet standards, use the following URL:

<http://www.imc.org/rfcs.html>

Table 1-1 shows the core classes, shared classes and server specific classes for the three types of entries for native mode: domains, users and groups. Note that for Calendar Server, there is an additional type of entry for resources that need to be scheduled, such as conference rooms and equipment.

Note that while `userPresenceProfile` is not specifically a Messaging Server object class (it is used to store vacation start and end dates), Calendar Server does not use it at all.

This table also includes the classes used by Identity Server in these types of entries. Identity Server classes are shown in italicized font. Note that the object classes and attributes defined for Identity Server are subject to change. See the *Sun Java™ Enterprise System Installation Guide* for a discussion of provisioning concepts.

Table 1-1 Native Mode Entry types and Corresponding Object Classes

Types	Core Classes	Shared Classes	Server Specific Classes
Domain	organization domain <i>sunManagedOrganization</i> <i>sunNameSpace</i>		mailDomain icsCalendarDomain
User	person inetUser organizationalPerson inetOrgPerson	ipUser userPresenceProfile <i>iplanet-am-managed-person</i>	inetMailUser inetLocalMailRecipient
Group	groupOfUniqueNames <i>iplanet-am-managed-group</i>	<i>iplanet-am-managed-filtered-group</i> <i>iplanet-am-managed-assignable-group</i> <i>iplanet-am-managed-static-group</i>	inetMailGroup inetLocalRecipient
Resource	inetResource		icsCalendarResource

Table 1-2 shows the core classes, shared classes and server specific classes for the four types of entries for compatibility mode: DC Tree domains, Organization Tree domains, users and groups.

Note that for Calendar Server, there is an additional type of entry for resources that need to be scheduled, such as conference rooms and equipment. Also note that `userPresenceProfile` is used only by Messaging Server, even though it is not a messaging specific object class.

This table also includes the classes used by Identity Server in these types of entries.

Table 1-2 Compatibility Mode Entry types and Corresponding Object Classes

Types	Core Classes	Shared Classes	Server Specific Classes
DC Tree Domain	domain inetDomain		mailDomain icsCalendarDomain
Org Tree Domain	organization sunManagedOrganization sunNameSpace		
User	person inetUser organizationalPerson inetOrgPerson	ipUser userPresenceProfile iplanet-am-managed-person	inetMailUser inetLocalMailRecipient
Group	groupOfUniqueNames iplanet-am-managed-group	iplanet-am-managed-filtered-group iplanet-am-managed-assignable-group iplanet-am-managed-static-group	inetMailGroup inetLocalRecipient
Resource	inetResource		icsCalendarResource

Data Model for Sun ONE LDAP Schema, v.1

The basic data model of Sun ONE object classes is to extend LDAP entry *types* (for example, user, group, domain) created by *core object classes* by overlaying them with *shared classes* (object classes can be shared by more than one service) and *service-specific object classes* (classes specific to a certain type of server).

This model has an Organization Tree for holding user and group information and a Domain Component Tree (DC Tree) that holds the domain information.

This model is administered by the iPlanet Delegated Administrator for Messaging graphical user interface.

For more information on RFC 2798, RFC 2252, and internet standards, use the following URL:

<http://www.imc.org/rfcs.html>

Table 1-3 shows the core classes, shared classes and server specific classes for the four types of entries: DC Tree domains, Organization Tree domains, users and groups. Note that for Calendar Server, there is an additional type of entry for resources that need to be scheduled, such as conference rooms and equipment. This table also includes the marker classes used by Delegated Administrator.

Table 1-3 Two-DIT Entry types and Corresponding Object Classes

Types	Core Classes	Shared Classes	Server Specific Classes
DC Tree Domain	domain inetDomain		mailDomain nsManagedDomain icsCalendarDomain
Org Tree Domain	organization		nsManagedDomain
User	person inetUser organizationalPerson inetOrgPerson	ipUser userPresenceProfile	inetMailUser inetLocalMailRecipient nsManagedPerson
Group	groupOfUniqueNames		inetMailGroup inetLocalRecipient inetMailGroupManagement nsManagedMailingList
Family Account	inetManagedGroup		nsManagedDept
Resource	inetResource		icsCalendarResource

Sun ONE Messaging Server Schema Overview

The basic Sun ONE Messaging Server schema model is to extend LDAP entries created by structural object classes. Extensions are made to a base LDAP entry using auxiliary object classes. The extensions made for Sun ONE Messaging Server are defined in this manual.

For example, `inetOrgPerson` is the structural class used to make a base user entry. This user entry becomes an email user when overlaid by the auxiliary classes defined in this document. Similarly, `groupOfUniqueNames` is the structural class used to make a base group entry, which becomes an email distribution list when overlaid by the distribution list auxiliary object classes.

Sun ONE Messaging Server auxiliary object classes can be grouped by function into the following categories and subcategories:

- [Mail Recipient](#)
 - [Email Users](#)
 - [Email Groups](#) (Distribution Lists)
 - [Email Routing](#)
- [Personal Address Book](#)
 - [Personal Address Book](#)
 - [Personal Address Book Group](#)
 - [Personal Address Book Person](#)
- [Domains](#)
 - [Hosted Domain Entries](#)
 - [Domain Aliases](#)
 - [Domain Organizations](#)
- [Delegation of Management](#)
 - [Managed Group](#)
 - [Store Administrator](#)

Mail Recipient

There are two types of mail recipients: users and groups. Both user and group email use the `inetLocalMailRecipient` auxiliary object class for local mail routing attributes.

Email Users

LDAP entries created by `inetOrgPerson` can be enabled for messaging services by overlaying the entry with `inetUser`, `ipUser`, `inetMailUser`, `inetLocalMailRecipient`, and `userPresenceProfile`. Optionally, `inetSubscriber` may be used for holding subscriber type attributes for the user, but it is not required for creating messaging server users.

Email Groups

LDAP entries created by `groupOfUniqueNames` can be enabled for messaging services by overlaying the entry with `inetMailGroup`, `inetMailUser`, and `inetLocalMailRecipient`. These object classes define distribution lists and how they are to be used by the messaging server.

Email Routing

For email routing attributes, the messaging server uses the object class `inetLocalMailRecipient`.

Personal Address Book

LDAP entries created by `inetOrgPerson` can be enabled for personal address books by overlaying the entry with object classes `pab`, `pabGroup`, and `pabPerson`. The data model for personal address book entries is the address book (`pab`), which contains zero or more persons (`pabPerson`) and zero or more group (`pabGroup`) entries.

Personal Address Book

The personal address book (`pab` object class) contains zero or more `pabPerson` and zero or more `pabGroup` entries. All users and groups belong to the default personal address book called `All`.

Personal Address Book Group

The personal address book group object class, `pabGroup`, corresponds to a personal distribution list. A group belongs to zero or more personal address books. The link between groups and personal address books is established by `memberOfPAB`, a multi-valued attribute of `pabGroup`.

Personal Address Book Person

The personal address book user object class, `pabPerson`, is a user entry in a personal address book. A user (`pabPerson`) can belong to zero or more personal address book groups (`pabGroup`) and zero or more personal address books (`pab`).

The link between users and groups is established by `memberOfPABGroup`, a multi-valued attribute of `pabPerson`, which allows the user to belong to many groups. A user can also belong to many personal address books. This link is established by `memberOfPAB`, a multi-valued attribute of `pabPerson`.

Domains

Domain object classes are used to specify email-addressable organizations. These domains are known as hosted domains.

This section discusses the following:

- [Hosted Domain Entries](#)
- [Domain Aliases](#)
- [Domain Organizations](#)

Hosted Domain Entries

LDAP entries created by `domain` and `inetDomain` can be enabled for hosted domains using the object class `mailDomain`. There must be an instance of both `mailDomain`, and `inetDomain` for each hosted domain. Optionally, to hold attributes suitable for overriding the default behavior of `mailDomain` and for stored certmaps, `inetDomainAuthInfo` can be used.

For Sun ONE LDAP Schema v.2, each hosted domain entry must also carry the Sun ONE Identity Server marker class, `sunManagedOrganization` and its attribute, `sunPreferredDomain`. This is true in both native and compatibility modes. In addition, if the hosted domain is also to be a namespace, the domain entry must contain the `sunNameSpace` object class and `sunNameSpaceUniqueAttrs` attribute.

For Sun ONE LDAP Schema v.1, each hosted domain entry must carry the Delegated Administrator marker class `nsManagedDomain`.

Domain Aliases

A hosted domain can have aliases. In Sun ONE LDAP Schema v.1, and Sun ONE LDAP Schema v.2 compatibility mode, these aliases are separate nodes on the DC Tree, and depending on what type of aliasing is being one, can carry separate routing information. However, for Sun ONE LDAP Schema v.2 native mode, there is no DC Tree. All aliasing is handled by adding the `associatedDomain` attribute (which lists all the alias names) to the domain node. This means a loss of functionality for native mode. That is for native mode, there can not be separate domain information (and thus different mail routing) for alias domains.

For Sun ONE LDAP Schema v.2, compatibility mode, the DC Tree domain alias nodes are still present, and can be provisioned using the Sun ONE User Management Utility.

For the User Management Utility (`commadmin`), see the *Sun ONE Messaging and Collaboration User Management Utility Installation and Administration Guide*.

Domain Organizations

To support a managed domain organization in Sun ONE LDAP Schema v.1, the auxiliary object classes `inetDomainOrg` is used in conjunction with the structural class `organization`. A domain organization is usually created as a way of introducing hierarchy beneath a customer subtree and assigning administrators for that domain organization. The resulting structures are not domains. They are usually denoted with the attribute `organizationalUnit` (`ou`).

Sun ONE LDAP Schema v.2 does not support “domain organizations” as used by earlier versions of Messaging Server. Especially do not use `iplanet-am-managed-organizational-unit`, which despite its name, is treated exactly the same as a regular domain named by `sunManagedOrganization`. Since this organization is not a domain, and there is no marker class for this in Identity Server, if you want to use the “domain organization” concept in your Sun ONE Schema LDAP, v.2 directory, you must provision and manage these structures by directly writing LDAP entries (using `ldapmodify`).

Delegation of Management

Managed group object classes are used to specify arbitrary groupings of users or groups (and possibly other resources defined in the LDAP directory) so that management of these resources can be delegated to another user. Examples of such groupings are DNS domain boundaries, and departments.

Managed Group

Managed groups commonly have different rules for adding or deleting members. To enable policy differences in the administration of groups, an instance of the object class `inetOrgPerson`, with its associated policy attributes, must exist for each managed group.

Store Administrator

To define a group of administrators for domains, the object class `inetMailAdministrator` is used to grant members administrative privileges over users in the same domain where the group is defined.

Sun ONE Calendar Server Schema Overview

This section lists the Sun ONE Calendar Server object classes and their attributes.

Table 1-4 shows the calendar-specific object classes and their attributes. In addition, Sun ONE Calendar Server also uses one non-calendar object class, `inetResource`.

Table 1-4 Calendar-Specific Object Classes

Object Classes	Required Attributes	Allowed Attributes
<code>icsAdministrator</code> (not currently used)	N/A	<code>icsAdminRole</code> , <code>icsExtended</code> , <code>icsExtendedGroupPrefs</code>

Table 1-4 Calendar-Specific Object Classes *(Continued)*

Object Classes	Required Attributes	Allowed Attributes
icsCalendarDomain (not all attributes are currently used)	N/A	icsAllowedServiceAccess , icsAllowRights , icsAnonymousAllowWrite , icsAnonymousCalendar , icsAnonymousDefaultSet , icsAnonymousLogin , icsAnonymousSet , icsDefaultAccess , icsDomainAllowed , icsDomainNames , icsDomainNotAllowed , icsDWPBackEndHosts , icsExtended , icsExtendedDomainPrefs , icsMandatorySubscribed , icsMandatoryView , icsPreferredHost , icsQuota , icsRecurrenceBound , icsRecurrenceDate , icsSessionTimeout , icsSourceHtml , icsStatus , icsTimezone
icsCalendarDWPHost (not currently implemented)	N/A	cn , description , icsDomainNames , icsDWPHost , icsExtended , icsRegularExpressions , icsStatus
icsCalendarGroup (not currently implemented)	icsStatus	N/A
icsCalendarResource (not all attributes are currently used)	N/A	cn , icsAlias , icsCalendar , icsCapacity , icsContact , icsDWPHost , icsExtended , icsExtendedResourcePrefs , icsGeo , icsPartition , icsPreferredHost , icsQuota , icsStatus , icsTimezone , mailAlternateAddress , mail , uid

Table 1-4 Calendar-Specific Object Classes *(Continued)*

Object Classes	Required Attributes	Allowed Attributes
<code>icsCalendarUser</code> (not all attributes are currently used)	N/A	<code>cn</code> , <code>givenName</code> , <code>icsAllowedServiceAccess</code> , <code>icsCalendar</code> , <code>icsCalendarOwned</code> , <code>icsDefaultSet</code> , <code>icsDWPHost</code> , <code>icsExtended</code> , <code>icsExtendedUserPrefs</code> , <code>icsFirstDay</code> , <code>icsFreeBusy</code> , <code>icsGeo</code> , <code>icsPartition</code> , <code>icsPreferredHost</code> , <code>icsQuota</code> , <code>icsSet</code> , <code>icsStatus</code> , <code>icsSubscribed</code> , <code>icsTimezone</code> , <code>mail</code> , <code>mailAlternateAddress</code> , <code>nswcalDisallowAccess</code> , <code>preferredLanguage</code> , <code>sn</code> , <code>uid</code> , <code>userPassword</code>

Object Classes

This chapter describes LDAP object classes for Sun™ Open Net Environment (ONE) Messaging and Collaboration products. The objects are listed alphabetically.

Note that the object classes and attributes specific only to Sun ONE Identity Server are found in a separate chapter, [Chapter 4, “Sun ONE Identity Server Classes and Attributes.”](#)

Note also that the object classes and attributes specific only to iPlanet Delegated Administrator for Messaging are found in a separate chapter, [Chapter 5, “iPlanet Delegated Administrator for Messaging Classes and Attributes.”](#)

List of Object Classes

This chapter describes the following object classes:

- [“domain” on page 32](#)
- [“groupOfUniqueNames” on page 33](#)
- [“icsAdministrator” on page 34](#)
- [“icsCalendarDomain” on page 35](#)
- [“icsCalendarDWPHost” on page 35](#)
- [“icsCalendarGroup” on page 36](#)
- [“icsCalendarResource” on page 37](#)
- [“icsCalendarUser” on page 37](#)
- [“inetAdmin” on page 38](#)
- [“inetDomain” on page 39](#)

- “inetDomainAlias” on page 40
- “inetDomainAuthInfo” on page 40
- “inetLocalMailRecipient” on page 41
- “inetMailAdministrator” on page 42
- “inetMailGroup” on page 43
- “inetMailUser” on page 43
- “inetOrgPerson” on page 44
- “inetResource” on page 45
- “inetSubscriber” on page 45
- “inetUser” on page 46
- “ipUser” on page 47
- “mailDomain” on page 48
- “mailPublicFolder” on page 49
- “msgVanityDomainUser” on page 49
- “organization” on page 50
- “organizationalUnit” on page 50
- “pab” on page 51
- “pabGroup” on page 52
- “pabPerson” on page 53
- “userPresenceProfile” on page 53

Object Classes

domain

Supported by

iPlanet Messaging Server 5.0, iPlanet Calendar Server 5.1

Definition

Object class used to define entries that represent DNS domains.

This class can only be used with an entry that does not correspond to an organization, organizational unit, or other type of object for which an object class has been defined.

This is a core class for both Messaging and Calendar products.

Superior Class

top

Object Class Type

structural

OID

0.9.2342.19200300.100.4.13

Required Attributes

dc, [objectClass](#)

Allowed Attributes

associatedName, [businessCategory](#), [description](#), destinationIndicator, fax ([facsimileTelephoneNumber](#)), internationalIsdnNumber, localityName, manager, o ([organizationName](#) ([see o](#))), physicalDeliveryOfficeName, postOfficeBox, postalAddress, postalCode, preferredDeliveryMethod, registeredAddress, searchGuide, [seeAlso](#), st, street, [telephoneNumber](#), telexTerminalIdentifier, telexNumber, [userPassword](#), x121Address

groupOfUniqueNames

Supported by

iPlanet Messaging Server 5.0, iPlanet Calendar Server 5.1

Definition

Defines entries for a group of unique names. A static group entry must be extended by this class. (A group entry may also be extended by [inetUser](#).) Use roles to define dynamic groups. For information on roles, see the *Sun ONE Directory Server Administrator's Guide*.

Superior Class

top

Object Class Type

structural

OID

2.5.6.17

Required Attributes

[cn](#), [objectClass](#), [uniqueMember](#)

Allowed Attributes

[businessCategory](#), [description](#), [o](#), [ou](#), [owner](#), [seeAlso](#)

icsAdministrator

Supported by

Not currently used.

Definition

Specifies a calendar administrator. Must be used in conjunction with other object classes.

Superior Class**Object Class Type**

structural

OID

2.16.840.1.113730.3.2.145

Required Attributes

N/A

Allowed Attributes

[icsAdminRole](#), [icsExtended](#), [icsExtendedGroupPrefs](#)

icsCalendarDomain

Supported by

Sun ONE Calendar Server 5.1.1

Definition

Specifies a calendar domain. Must be used in conjunction with [inetDomain](#).

Superior Class

top

Object Class Type

structural

OID

1.3.6.1.4.1.42.2.27.9.2.4

Required Attributes

N/A

Allowed Attributes

The following attributes are currently used:

[icsAllowedServiceAccess](#), [icsAllowRights](#), [icsDefaultAccess](#),
[icsDomainNames](#), [icsExtendedDomainPrefs](#), [icsStatus](#), [icsTimezone](#)

The following attributes are reserved but not implemented for this object class:

[icsAnonymousAllowWrite](#), [icsAnonymousCalendar](#), [icsAnonymousDefaultSet](#),
[icsAnonymousLogin](#), [icsAnonymousSet](#), [icsDomainAllowed](#),
[icsDomainNotAllowed](#), [icsDWPBackEndHosts](#), [icsExtended](#),
[icsMandatorySubscribed](#), [icsMandatoryView](#), [icsPreferredHost](#), [icsQuota](#),
[icsRecurrenceBound](#), [icsRecurrenceDate](#), [icsSessionTimeout](#),
[icsSourceHtml](#),

icsCalendarDWPHost

Supported by

Sun ONE Calendar Server 5.1.1

Definition

Reserved; not implemented.

Contains configuration and other information specific to one DWP server. Each entry tracks which domain it serves. The domain names are used to scope searches.

Superior Class**Object Class Type**

structural

OID

1.3.6.1.4.1.42.2.27.9.2.1

Required Attributes

N/A

Allowed Attributes

`cn`, `description`, `icsDomainNames`, `icsDWPHost`, `icsExtended`,
`icsRegularExpressions`, `icsStatus`

icsCalendarGroup

Supported by

iPlanet Calendar Server 5.1

Definition

Reserved, not implemented.

Superior Class**Object Class Type**

structural

OID

1.3.6.1.4.1.42.2.27.9.2.5

Required Attributes

`icsStatus`

Allowed Attributes

N/A

icsCalendarResource

Supported by

iPlanet Calendar Server 5.1, Sun ONE Messaging and Collaboration User Management Utility 1.0

Modified in 5.1.1 – attributes added: `icsDWPHost`, `icsPartition`, `uid`

Definition

Specifies a calendar resource, such as a conference room or piece of equipment that must be scheduled. Must be used in conjunction with [inetResource](#). Not all attributes are currently used.

Sun ONE Identity Server 6.1 reserves this as a marker class for calendar resources but does not support calendar resources yet.

Superior Class

`inetResource`

Object Class Type

structural

OID

1.3.6.1.4.1.42.2.27.9.2.3

Required Attributes

N/A

Allowed Attributes

The following attributes are currently used:

`cn`, `description`, `icsCalendar`, `icsDWPHost`, `icsPartition`, `icsStatus`, `icsTimezone`, `mail`, `mailAlternateAddress`, `uid`

The following attributes are reserved but not implemented for this object class:

`icsAlias`, `icsCapacity`, `icsContact`, `icsExtended`, `icsExtendedResourcePrefs`, `icsGeo`, `icsPreferredHost`, `icsQuota`

icsCalendarUser

Supported by

iPlanet Calendar Server 5.1

Modified in 5.1.1 – attributes added: icsDWPHost, icsPartition

Definition

Specifies a calendar user, including the DWP host name.

Superior Class

top

Object Class Type

auxiliary

OID

1.3.6.1.4.1.42.2.27.9.2.2

Required Attributes

N/A

Allowed Attributes

These attributes are currently in use:

`cn`, `givenName`, `icsAllowedServiceAccess`, `icsCalendar`, `icsCalendarOwned`,
`icsDWPHosticsExtendedUserPrefs`, `icsFirstDay`, `icsPartition`, `icsSet`,
`icsStatus`, `icsSubscribed`, `icsTimezone`, `mail`, `mailAlternateAddress`,
`preferredLanguage`, `sn`, `uid`, `userPassword`

These attributes are reserved but not currently used:

`icsDefaultSet`, `icsExtended`, `icsFreeBusy`, `icsGeo`, `icsPreferredHost`,
`icsQuota`, `nswcalDisallowAccess`

inetAdmin

Supported by

iPlanet Messaging Server 5.0

Definition

Identifies administrator user or group.

Superior Class

top

Object Class Type

Auxiliary

OID

2.16.840.1.113730.3.2.112

Required Attributes[objectClass](#)**Allowed Attributes**[memberOf](#), [adminRole](#)

inetDomain

Supported by

iPlanet Messaging Server 5.0

Definition

Used in two-tree LDAP data models to extend the base entry created by `domain` in the DC Tree. It represents a hosted domain account and is used in conjunction with `mailDomain` and (optionally `inetDomainAuthInfo`) for creating a hosted domain node in the DC Tree suitable for mail services for the hosted organization. This object class must be used for all hosted domain entries in the DC Tree.

Sun ONE Identity Server uses this as a marker class for domains in the DC Tree.

Superior Class`top`**Object Class Type**

auxiliary

OID

2.16.840.1.113730.3.2.129

Required Attributes[inetDomainBaseDN](#)**Allowed Attributes**[inetDomainStatus](#)

inetDomainAlias

Supported by

iPlanet Messaging Server 5.0

Definition

Structural class for creating domain alias entries in the DC Tree for the compatibility mode LDAP data model. Entries may be created that point at other hosted domain objects. Such domain alias entries must be extended by this object class. Attribute [aliasedObjectName](#), inherited from the parent object class [alias](#) (see RFC 2256), holds the DN of the LDAP entry for which the node is an alias.

Use this object class when you want two identical domains with different names. If you want two domains that have different attribute settings, create two [inetDomain](#) entries and use the [inetCanonicalDomainName](#) attribute to decorate the domain to use for mail routing.

This object class is not used in the native mode LDAP data model. Instead, to show the aliases for a domain, the (Organization Tree) domain entry is extended by [sunManagedOrganization](#) and decorated with the [businessCategory](#) attribute.

Superior Class

[alias](#)

Object Class Type

structural

OID

2.16.840.1.113730.3.2.131

Required Attributes

[aliasedObjectName](#), [dc](#)

Allowed Attributes

N/A

inetDomainAuthInfo

Supported by

iPlanet Messaging Server 5.0

Definition

This object class is used to extend the `domain` entry with search filter, domain cert map, and a canonical domain name if more than one hosted domain refers to the same organization subtree.

Superior Class

`top`

Object Class Type

`auxiliary`

OID

2.16.840.1.113730.3.2.133

Required Attributes

N/A

Allowed Attributes

`domainUidSeparator`, `inetDomainSearchFilter`, `inetDomainCertMap`,
`inetCanonicalDomainName`

inetLocalMailRecipient

Supported by

iPlanet Messaging Server 5.0

Definition

Stores information that provides a way to designate an LDAP entry as one that represents a local (intra-organizational) email recipient, to specify the recipient's email address(es), and to provide routing information pertinent to the recipient. This is intended to support SMTP message transfer agents in routing RFC 822-based email within a private enterprise only, and is not to be used in the process of routing email across the public Internet.

Superior Class

`top`

Object Class Type

`auxiliary`

OID

2.16.840.1.113.730.3.2.147

Required Attributes

N/A

Allowed Attributes

[mail](#), [mailAlternateAddress](#), [mailHost](#), [mailRoutingAddress](#)

inetMailAdministrator

Supported by

iPlanet Messaging Server 5.0

Definition

LDAP group defined with `groupOfUniqueNames` can be overlaid with this object class. Members (listed in the attribute `uniqueMember`) of a group overlaid with this object class and where `mailAdminRole` is set to `storeAdmin` get IMAP proxyauth (proxy authentication) rights over all users in the same domain in which the group entry exists.

Superior Class

`top`

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.148

Required Attributes

N/A

Allowed Attributes

[mailAdminRole](#)

inetMailGroup

Supported by

iPlanet Messaging Server 5.0

Definition

Used to extend the base entry created by `groupOfUniqueNames` to define a group of mail recipients. `inetMailGroup` is used to store attributes of a mailing list. It is used in conjunction with `inetLocalMailRecipient` and `inetMailGroupManagement` (for mailing lists managed by the Delegated Administrator).

Superior Class

top

Object Class Type

auxiliary

OID

1.3.6.1.4.1.42.2.27.2.2.2

Required Attributes

N/A

Allowed Attributes

`dataSource`, `inetMailGroupStatus`, `mailConversionTag`,
`mailDeferProcessing`, `mailDeliveryFileURL`, `mailDeliveryOption`,
`mailEquivalentAddress`, `mailMsgMaxBlocks`, `mailProgramDeliveryInfo`,
`mailRejectText`, `memberURL`, `mgrpAddHeader`, `mgrpAllowedBroadcaster`,
`mgrpAllowedDomain`, `mgrpAuthPassword`, `mgrpBroadcasterPolicy`,
`mgrpDeliverTo`, `mgrpDisallowedBroadcaster`, `mgrpDisallowedDomain`,
`mgrpErrorsTo`, `mgrpModerator`, `mgrpMsgMaxSize`, `mgrpMsgPrefixText`,
`mgrpMsgRejectAction`, `mgrpMsgRejectText`, `mgrpMsgSuffixText`,
`mgrpNoDuplicateChecks`, `mgrpRemoveHeader`, `mgrpRFC822MailMember`,
`preferredLanguage`, `uniqueMember`

inetMailUser

Supported by

iPlanet Messaging Server 5.0

Definition

Used to extend the base entry created by `inetOrgPerson` to define a messaging service user. It represents a mail account and is used in conjunction with `inetUser` and `inetLocalMailRecipient`. Optionally, `inetSubscriber` may also be used for general account management purposes.

Superior Class

`top`

Object Class Type

`auxiliary`

OID

2.16.840.1.113730.3.2.146

Required Attributes

N/A

Allowed Attributes

`cn`, `dataSource`, `icsQuota`, `mailAllowedServiceAccess`, `mailAntiUBEService`, `mailAutoReplyMode`, `mailAutoReplySubject`, `mailAutoReplyTimeOut`, `mailAutoReplyText`, `mailAutoReplyTextInternal`, `mailConversionTag`, `mailDeferProcessing`, `mailDeliveryOption`, `mailEquivalentAddress`, `mailForwardingAddress`, `mailMessageStore`, `mailMsgMaxBlocks`, `mailMsgQuota`, `mailProgramDeliveryInfo`, `mailQuota`, `mailSieveRuleSource`, `mailSMTPSubmitChannel`, `mailUserStatus`, `nswmExtendedUserPrefs`

inetOrgPerson

Supported by

Specified here for reference only.

Definition

All user entries are created with this object class. Refer to the internet draft *The LDAP inetOrgPerson Object Class* for further details.

Superior Class

`organizationalPerson`

Object Class Type

`structural`

OID

2.16.840.1.113730.3.2.2

Required Attributes

N/A

Allowed Attributes[businessCategory](#), [givenName](#), [mail](#), [uid](#), [preferredLanguage](#)

inetResource

Supported by

iPlanet Calendar Server 5.1

Definition

Specifies a resource, which is defined as an object to which calendar services are provided. For example, a conference room, or a piece of equipment shared by many that needs to be scheduled.

Superior Class[top](#)**Object Class Type**

structural

OID

2.16.840.1.113730.3.2.142

Required Attributes[cn](#)**Allowed Attributes**[facsimileTelephoneNumber](#), [inetResourceStatus](#), [mail](#), [postalAddress](#), [telephoneNumber](#)

inetSubscriber

Supported by

iPlanet Messaging Server 5.0

Definition

Used to extend the base entry created by `inetOrgPerson` to define a user. It represents a subscriber account and may be used in conjunction with `inetUser`, `inetMailUser`, and `ipUser` for creating a mail account.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.134

Required Attributes

N/A

Allowed Attributes

`inetSubscriberAccountId`, `inetSubscriberChallenge`,
`inetSubscriberResponse`

inetUser

Supported by

iPlanet Messaging Server 5.0, Sun ONE Calendar Server 5.1.1

Definition

It represents a user account, or a resource (defined as any object to which services are provided) account, and is used in conjunction with `inetMailUser` and `ipUser` for creating a mail account. When creating user accounts, this object class extends the base entry created by `inetOrgPerson`.

This attribute can be used with `icsCalendarUser` for creating a calendar user account. (Note that `inetResource` is used by Calendar Server to create resource accounts.)

User and resource entries must be extended by this object class. Group entries may be extended with this class.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.130

Required Attributes

N/A.

Allowed Attributes

[inetUserHttpURL](#) (see note), [inetUserStatus](#), [memberOf](#) (see note), [uid](#), [userPassword](#)

NOTE

The attributes [inetUserHttpURL](#), and [memberOf](#) are deprecated for this object class and are likely to be removed from the class in future versions of Sun ONE schema.

ipUser

Supported by

iPlanet Messaging Server 5.0

Superior Class

top

Definition

Object class for services like mail and calendar. Used to extend the base entry created by [inetOrgPerson](#) and [inetUser](#). This object class holds the reference to the personal address book container and the class of service specifier.

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.135

Required Attributes

N/A

Allowed Attributes

[inetCoS](#), [memberOfPAB](#), [maxPabEntries](#), [pabURI](#)

mailDomain

Supported by

iPlanet Messaging Server 5.0

Definition

Auxiliary class used to extend the base entry created by `domain` and `inetDomain` for enabling messaging services for the hosted domain. It represents a hosted domain account with access to Messaging Service. This object class must be used for all hosted domain entries.

In the absence of the `mailPublicFolderDefaultRights` attribute for a `mailPublicFolder` entry, the presence of the attribute in the `mailDomain` entry allows administrators to specify the default rights to assign to the public folder.

Superior Class

`top`

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.151

Required Attributes

N/A

Allowed Attributes

[mailAccessProxyPreAuth](#), [mailAccessProxyReplay](#),
[mailClientAttachmentQuota](#), [mailDomainAllowedServiceAccess](#),
[mailDomainConversionTag](#), [mailDomainCatchallAddress](#),
[mailDomainDiskQuota](#), [mailDomainMsgMaxBlocks](#), [mailDomainMsgQuota](#),
[mailDomainReportAddress](#), [mailDomainSieveRuleSource](#), [mailDomainStatus](#),
[mailDomainWelcomeMessage](#), [mailPublicFolderDefaultRights](#),
[mailQuota](#), [mailRoutingHosts](#), [mailRoutingSmartHost](#), [preferredLanguage](#),
[preferredMailHost](#),

mailPublicFolder

Supported by

Sun ONE Messaging Server 6.0

Definition

Defines a public folder.

Superior Class

top

Object Class Type

structural

OID**Required Attributes**

[mailFolderName](#)

Allowed Attributes

[mailMessageStore](#), [mailPublicFolderDefaultRights](#), [mailDeliveryOption](#)

msgVanityDomainUser

Supported by

iPlanet Messaging Server 5.0

Definition

This object class and its attribute are deprecated in the current release, and may not be supported in future releases. Sites should stop using this feature and consider migrating current vanity domains to hosted domains.

Auxiliary class for supporting the notion of a vanity domain for messaging. Used to extend the base mail user entry to assign a vanity domain to the user.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.150

Required Attributes

N/A

Allowed Attributes

[msgVanityDomain](#)

organization

Supported by

iPlanet Messaging Server 5.0

Definition

Defines entries that represent organizations. An organization is generally assumed to be a large, relatively static grouping within a larger corporation or enterprise.

Superior Class

top

OID

2.5.6.4

Required Attributes

[objectClass](#), [o](#) (organizationName)

Allowed Attributes

[businessCategory](#), [description](#), [destinationIndicator](#),
[facsimileTelephoneNumber](#), [internationalIsdnNumber](#), [l](#) (localityName),
[physicalDeliveryOfficeName](#), [postalAddress](#), [postalCode](#), [postOfficeBox](#),
[preferredDeliveryMethod](#), [registeredAddress](#), [searchGuide](#), [seeAlso](#), [st](#),
[street](#), [telephoneNumber](#), [teletexTerminalIdentifier](#), [telexNumber](#),
[userPassword](#)

organizationalUnit

Supported by

iPlanet Messaging Server 5.0

Definition

Defines entries that represent organizations. An organization is generally assumed to be a large, relatively static grouping within a larger corporation or enterprise.

Superior Class

top

OID

2.5.6.5

Required Attributes

[objectClass](#), [ou](#)

Allowed Attributes

[businessCategory](#), [description](#), [destinationIndicator](#), [facsimileTelephoneNumber](#), [internationalIsdnNumber](#), [l](#) (localityName), [physicalDeliveryOfficeName](#), [postalAddress](#), [postalCode](#), [postOfficeBox](#), [preferredDeliveryMethod](#), [registeredAddress](#), [searchGuide](#), [seeAlso](#), [st](#), [street](#), [telephoneNumber](#), [teletexTerminalIdentifier](#), [telexNumber](#), [userPassword](#)

pab

Supported by

iPlanet Messaging Server 5.0

Definition

The data model used is as follows:

`pabPerson` is a user entry in the personal address book.

`pabGroup` is the group entry and corresponds to a personal distribution list. For example, the `pabGroup` “pab-notes” may contain `pabPersons` micky and john.

`pab` is the address book that contains zero or more `pabPerson` and zero or more `pabGroup` entries. This is the top level logical container. `pab` may contain `pabPerson` and/or `pabGroup`. A `pabPerson` may belong in zero or more `pabGroup` and zero or more `pab`.

pabPerson may belong to zero or more pabGroup entries. This link is established by memberOfPABGroup, a multi-valued attribute holding the DN of the pabGroup in which the pabPerson belongs. A pabPerson may also belong to many personal address book's. This link is established by having the DN of the pab listed as a value of the attribute memberOfPAB.

All users and groups belong in the default personal address book called “All.”

Superior Class

top

Object Class Type

structural

OID

2.16.840.1.113730.3.2.140

Required Attributes

cn

Allowed Attributes

description, un

pabGroup

Supported by

iPlanet Messaging Server 5.0

Definition

pabGroup is a group entry in a personal address book (pab) and corresponds to a personal distribution list. For example, the pabGroup “pab-notes” may contain pabPersons micky and john.

Superior Class

top

Object Class Type

structural

OID

2.16.840.1.113730.3.2.139

Required Attributes[cn](#)**Allowed Attributes**[description](#), [memberOfPAB](#), [nickName](#), [un](#)

pabPerson

Supported by

iPlanet Messaging Server 5.0

DefinitionA user entry in the personal address book ([pab](#)).**Superior Class**[inetOrgPerson](#)**Object Class Type**

structural

OID

2.16.840.1.113730.3.2.138

Required Attributes

N/A

Allowed Attributes[calCalURI](#), [calFBURL](#), [co](#), [dateOfBirth](#), [mailAlternateAddress](#), [memberOfPAB](#), [memberOfPABGroup](#), [nickName](#), [organizationName](#) (see [o](#)), [ou](#) ([organizationalUnitName](#)), [un](#)

userPresenceProfile

Supported by

iPlanet Messaging Server 5.0

Definition

Used to store the presence information for a user.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.136

Required Attributes

N/A

Allowed Attributes

[vacationEndDate](#), [vacationStartDate](#)

Attributes

This chapter describes attributes required or allowed by LDAP object classes for Sun™ Open Net Environment (ONE) Messaging and Collaboration products. The attributes are listed alphabetically.

Note that attributes used exclusively by Sun ONE Identity Server are covered in [Chapter 4, “Sun ONE Identity Server Classes and Attributes.”](#) Whereas, attributes used exclusively by iPlanet Delegated Administrator for Messaging are covered in [Chapter 5, “iPlanet Delegated Administrator for Messaging Classes and Attributes.”](#)

List of Attributes

This chapter describes the following attributes:

- “adminRole” on page 61
- “aliasedObjectName” on page 62
- “businessCategory” on page 63
- “calCalURI” on page 63
- “calFBURL” on page 64
- “cn” on page 64
- “co” on page 65
- “commonName (see cn)” on page 66
- “countryName (see co)” on page 66
- “dataSource” on page 66

- “dateOfBirth” on page 66
- “dc” on page 67
- “description” on page 67
- “facsimileTelephoneNumber” on page 70
- “givenName” on page 71
- “icsAdminRole” on page 71
- “icsAlias” on page 72
- “icsAllowedServiceAccess” on page 72
- “icsAllowRights” on page 73
- “icsAnonymousAllowWrite” on page 75
- “icsAnonymousCalendar” on page 76
- “icsAnonymousDefaultSet” on page 76
- “icsAnonymousLogin” on page 77
- “icsAnonymousSet” on page 77
- “icsCalendar” on page 78
- “icsCalendarOwned” on page 78
- “icsDefaultSet” on page 80
- “icsDomainAllowed” on page 81
- “icsDomainNames” on page 82
- “icsDomainNotAllowed” on page 83
- “icsDWPBackEndHosts” on page 84
- “icsDWPHost” on page 85
- “icsExtended” on page 85
- “icsExtendedDomainPrefs” on page 86
- “icsExtendedGroupPrefs” on page 87
- “icsExtendedResourcePrefs” on page 88
- “icsExtendedUserPrefs” on page 88

- “icsFirstDay” on page 92
- “icsFreeBusy” on page 92
- “icsGeo” on page 93
- “icsMandatorySubscribed” on page 93
- “icsMandatoryView” on page 94
- “icsPartition” on page 94
- “icsPreferredHost” on page 95
- “icsQuota” on page 96
- “icsRecurrenceBound” on page 96
- “icsRecurrenceDate” on page 97
- “icsRegularExpressions” on page 97
- “icsSessionTimeout” on page 98
- “icsSet” on page 98
- “icsSourceHtml” on page 100
- “icsStatus” on page 100
- “icsSubscribed” on page 102
- “icsTimezone” on page 102
- “inetCanonicalDomainName” on page 103
- “inetCoS” on page 104
- “inetDomainBaseDN” on page 105
- “inetDomainCertMap” on page 106
- “inetDomainSearchFilter” on page 106
- “inetDomainStatus” on page 107
- “inetMailGroupStatus” on page 109
- “inetResourceStatus” on page 110
- “inetSubscriberAccountId” on page 111
- “inetSubscriberChallenge” on page 112

- “inetSubscriberResponse” on page 112
- “inetUserHttpURL” on page 113
- “inetUserStatus” on page 113
- “mail” on page 115
- “mailAccessProxyPreAuth” on page 115
- “mailAccessProxyReplay” on page 116
- “mailAdminRole” on page 117
- “mailAllowedServiceAccess” on page 117
- “mailAlternateAddress” on page 120
- “mailAntiUBEService” on page 121
- “mailAutoReplyMode” on page 122
- “mailAutoReplySubject” on page 123
- “mailAutoReplyText” on page 123
- “mailAutoReplyTextInternal” on page 124
- “mailAutoReplyTimeOut” on page 124
- “mailClientAttachmentQuota” on page 125
- “mailConversionTag” on page 125
- “mailDeferProcessing” on page 126
- “mailDeliveryFileURL” on page 127
- “mailDeliveryOption” on page 128
- “mailDomainAllowedServiceAccess” on page 130
- “mailDomainCatchallAddress” on page 132
- “mailDomainConversionTag” on page 133
- “mailDomainDiskQuota” on page 133
- “mailDomainMsgMaxBlocks” on page 134
- “mailDomainMsgQuota” on page 134
- “mailDomainReportAddress” on page 135

- “mailDomainSieveRuleSource” on page 136
- “mailDomainStatus” on page 137
- “mailDomainWelcomeMessage” on page 139
- “mailEquivalentAddress” on page 139
- “mailFolderName” on page 140
- “mailForwardingAddress” on page 141
- “mailHost” on page 141
- “mailMessageStore” on page 142
- “mailMsgMaxBlocks” on page 143
- “mailMsgQuota” on page 143
- “mailProgramDeliveryInfo” on page 144
- “mailPublicFolderDefaultRights” on page 145
- “mailQuota” on page 147
- “mailRejectText” on page 148
- “mailRoutingAddress” on page 149
- “mailRoutingHosts” on page 149
- “mailRoutingSmartHost” on page 150
- “mailSieveRuleSource” on page 151
- “mailSMTPSubmitChannel” on page 153
- “mailUserStatus” on page 153
- “maxPabEntries” on page 155
- “memberOf” on page 155
- “memberOfPAB” on page 156
- “memberOfPAB” on page 156
- “memberOfPABGroup” on page 156
- “memberURL” on page 157
- “mgrpAddHeader” on page 158

- “mgrpAllowedBroadcaster” on page 158
- “mgrpAllowedDomain” on page 159
- “mgrpAuthPassword” on page 160
- “mgrpBroadcasterPolicy” on page 161
- “mgrpDeliverTo” on page 162
- “mgrpDisallowedBroadcaster” on page 163
- “mgrpDisallowedDomain” on page 164
- “mgrpErrorsTo” on page 165
- “mgrpModerator” on page 165
- “mgrpMsgMaxSize” on page 166
- “mgrpMsgPrefixText” on page 167
- “mgrpMsgRejectAction” on page 168
- “mgrpMsgRejectText” on page 169
- “mgrpMsgSuffixText” on page 169
- “mgrpNoDuplicateChecks” on page 170
- “mgrpRemoveHeader” on page 170
- “mgrpRequestTo” on page 171
- “mgrpRFC822MailMember” on page 171
- “msgVanityDomain” on page 172
- “msgVanityDomain” on page 172
- “multiLineDescription” on page 173
- “nickName” on page 173
- “nswmExtendedUserPrefs” on page 174
- “o” on page 175
- “objectClass” on page 175
- “organizationName (see o)” on page 176
- “organizationUnitName (see ou)” on page 176

- “ou” on page 176
- “owner” on page 177
- “pabURI” on page 177
- “parentOrganization” on page 178
- “postalAddress” on page 179
- “preferredLanguage” on page 179
- “preferredMailHost” on page 180
- “preferredMailMessageStore” on page 181
- “seeAlso” on page 182
- “sn” on page 182
- “telephoneNumber” on page 183
- “uid” on page 183
- “un” on page 184
- “uniqueMember” on page 185
- “userId (see uid)” on page 185
- “userPassword” on page 185
- “vacationEndDate” on page 186
- “vacationStartDate” on page 187

Attribute Definitions

adminRole

Origin

iPlanet Messaging Server 5.0

Syntax

cis

Object Classes

[inetAdmin](#)

Definition

Specifies the administrator role for this administrator entry.

Example

OID

2.16.840.1.113730.3.1.601

aliasedObjectName

Origin

iPlanet Messaging Server 5.0

Syntax

dn

Object Classes

[inetDomainAlias](#)

Definition

Used only in compatibility mode (with a DC Tree) for Sun ONE LDAP Schema v.2, not in native mode (no DC Tree).

Used by the directory server to identify alias entries in the directory. Contains the distinguished name of the entry for which it is an alias. The domain attribute values are taken only from the referenced domain. So that routing will be identical between these domains.

Example

aliasedObjectName: cn=jdoe,o=sesta.com

OID

2.5.4.1

businessCategory

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[groupOfUniqueNames](#), [organization](#), [organizationalUnit](#)

Definition

Identifies the type of business in which the entry is engaged. This should be a broad generalization such as is made at the corporate division level.

Example

`businessCategory:Engineering`

OID

2.5.4.15

calCalURI

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[pabPerson](#)

Definition

Contains URI to user's entire default calendar. For details see RFC 2739.

Example

Varies according to the version of calendar server implemented. For details see RFC 2739.

OID

1.2.840.113556.1.4.478

calFBURL

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[pabPerson](#)

Definition

URL to the user's default busy time data. For details see RFC 2739.

Example

Varies according to the version of calendar server implemented. For details see RFC 2739.

OID

1.2.840.113556.1.4.479

cn

Origin

iPlanet Calendar Server 5.1

Syntax

cis, single-valued

Object Classes

[icsCalendarResource](#), [icsCalendarUser](#), [inetResource](#)

Definition

For users, full name of person. For resources, a unique identifier. In either case, it may contain spaces and special characters. Abbreviation for `commonName`.

Example

For a user: `cn: John Doe.`

For a resource: `cn: Conference Room #3`

or

commonName: John Doe

commonName: Conference Room #3

OID

2.5.4.3

co

Origin

LDAP

Syntax

cis

Object Classes

[pabPerson](#)

Definition

Contains the name of a country, using a two character code. Abbreviation for countryName.

The attribute `friendlyCountryName` is used to spell out the actual country name.

Example

co:IE

or

countryName:IE

friendlyCountryName:Ireland

OID

2.5.4.4

commonName (see cn)

commonName (see cn)

countryName (see co)

dataSource

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailUser](#), [inetMailGroup](#)

Definition

Text field to store a tag or identifier. Value has no operational impact.

Example

```
dataSource:1.0
```

OID

2.16.840.1.113730.3.1.779

dateOfBirth

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[pabPerson](#)

Definition

Date of birth of the `pabPerson`. Format is: YYYYMMDD.

Example

dateOfBirth: 19740404
(date of birth on April 6, 1974.)

OID

2.16.840.1.113730.3.1.779

dc

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainAlias](#)

Definition

The domain component of the domain alias entry.

Example

dc=sesta

For example a domain alias entry DN might be:

dn: dc=sesta, dc=fr, o=internet.

OID

0.9.2342.19200300.100.1.25

description

Origin

LDAP

Syntax

cis, multi-valued

Object Classes

[icsCalendarDWPHost](#), [icsCalendarResource](#), [groupOfUniqueNames](#),
[inetOrgPerson](#), [organization](#), [organizationalUnit](#), [pab](#), [pabGroup](#),
[sunServiceComponent](#)

Definition

Provides a human readable description of the object. For people and organizations, this often includes their role or work assignment.

Example

description: Quality control inspector.

OID

2.5.4.13

domainUidSeparator

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainOrg](#)

Definition

This attribute is used only for Sun ONE LDAP Schema v.1.

This attribute is used by the messaging server to override the default mailbox (MB) home. When present, this attribute specifies that compound user identifications (UIDs) are used in this domain and this attribute specifies the separator. For instance, if + is the separator, the mailbox names in this domain are obtained by replacing the right most occurrence of + in the uid with @. To map an internal mailbox name to the UID, the right most occurrence of @ is replaced with a + in the mailbox name.

While substitution of an @ for the UID separator is sufficient to generate a mailbox name, this may not be the same as any of the user's actual email addresses.

NOTE Format of internal mailbox names is `uid@domain`, where “domain” is DNS domain mapping to the namespace. The only exception to this rule is mailbox names for users in default domain where only the `uid` is used to construct internal mailbox names. See `inetCanonicalDomainName` on how the default value of domain name used can be overridden in specific cases.

The MTA option used to override this attribute’s value is `LDAP_DOMAIN_ATTR_UID_SEPARATOR`.

Example

`domainUIDSeparator: #`

OID

`2.16.840.1.113730.3.1.702`

domOrgMaxUsers

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainOrg](#)

Definition

This attribute is used only for Sun ONE LDAP Schema v.1.

Maximum number of user entries in a domain organization.

Example

`domOrgMaxUser: 500`

OID

`2.16.840.1.113730.3.1.697`

domOrgNumUsers

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainOrg](#)

Definition

Number of current user entries in a domain organization.

Example

```
domOrgNumUsers: 345
```

OID

2.16.840.1.113730.3.1.698

facsimileTelephoneNumber

Origin

iPlanet Calendar Server 5.1

Syntax

tel, single-valued

Object Classes

[icsCalendarResource](#), [inetResource](#), [organization](#), [organizationalUnit](#)

Definition

Fax telephone number for resources.

Example

```
facsimileTelephoneNumber 1-800-555-1212
```

OID

2.5.4.23

givenName

Origin

LDAP

Syntax

cis

Object Classes

[icsCalendarUser](#)

Definition

Identifies the entry's given name, usually a person's first name.

Example

givenName: John

OID

2.5.4.42

icsAdminRole

Origin

iPlanet Calendar Server 5.1

Syntax

cis

Object Classes

[icsAdministrator](#)

Definition

Administrative calendar role that can be assigned to a group.

Example**OID**

2.16.840.1.113730.3.1.724

icsAlias

Origin

iPlanet Calendar Server 5.1

Syntax

cis, UTF8 encoded

Object Classes

[icsCalendarResource](#)

Definition

Alias associated with a resource. An alias can make a resource name easier for the end user to work with.

Example

The resource named “halleyscomet” can be aliased as “Halley’s Comet”.

```
icsAlias: Halley's Comet
```

OID

2.16.840.1.113730.3.1.725

icsAllowedServiceAccess

Origin

Sun ONE Calendar Server 6.0

Syntax

cis, single-valued

Object Classes

[icsCalendarDomain](#), [icsCalendarUser](#)

Definition

This attribute is used only if the [icsStatus](#) attribute is not set, or in other words, if icsStatus is set, this attribute is ignored.

Use this attribute to disallow calendar services to a user. As a default all users are allowed access with http, but if you specify this attribute as shown in the example, it disallows the user from receiving calendar access (user is disabled):

Any other setting, or absence of the attribute entirely, results in the user having access to http services (user is enabled).

Example

icsAllowedServiceAccess:http

OID

2.16.840.1.113730.3.1.726

icsAllowRights

Origin

iPlanet Calendar Server 5.1

Syntax

int, single valued

Object Classes

icsCalendarDomain

Definition

A numeric string used to hold bit fields, each corresponding to a set of rights. Each bit corresponds to a setting in the ics.conf file. After you have figured out the bit string settings you want, convert the bits to an integer.

If the property is set (1), the right is not allowed. If the bit is not set (0), the right is allowed.

If this attribute does not exist, the corresponding ics.conf default settings are used.

Table 3-1 defines the meaning of each bit position for bits 0-15:

Table 3-1 Bit Definitions and ics.conf Settings

Property Name and ics.conf Setting Name	Bit	Allows (0) or Disallows (1)
allowCalendarCreation service.wcap.allowcreatecalendars	0	Creation of calendars
allowCalendarDeletion service.wcap.allowdeletecalendars	1	Deletion of calendars

Table 3-1 Bit Definitions and ics.conf Settings

Property Name and ics.conf Setting Name	Bit	Allows (0) or Disallows (1)
allowPublicWritableCalendars service.wcap.allowpublicwriteablecalendars	2	Publicly writable calendars for users
N/A	3	Reserved. Defaults to 0
allowModifyUserPreferences service.admin.calmaster.wcap.allowgetmodifyuserprefs	4	Domain Administrator allowed to change user preferences
allowModifyPassword service.wcap.allowchangepassword	5	Users allowed to change their password
N/A	6	Reserved. Defaults to 0
N/A	7	Reserved. Defaults to 0
allowUserDoubleBook user.allow.doublebook	8	Double booking of user calendars
allowResourceDoubleBook resource.allow.doublebook	9	Double booking of resource calendars
allowSetCn service.wcap.allowsetprefs.cn	10	User preference cn modified by set_userprefs command
allowSetGivenName service.wcap.allowsetprefs.givenname	11	User preference givenname modified by set_userprefs command
allowSetGivenMail service.wcap.allowsetprefs.mail	12	User preference mail modified by set_userprefs command
allowSetPrefLang service.wcap.allowsetprefs.preferredlanguage	13	User preference preferredlanguage modified by set_userprefs command
allowSetSn service.wcap.allowsetprefs.sn	14	User preference sn modified by set_userprefs command
N/A	15–31	Reserved. Defaults to all 0

Example

If you decide that you want to disallow the following bits:

- publicly writable user calendars (bit 2),
- double booking of resources (bit 9),
- and modifying the given name (bit 11),

then your bit pattern would look like this:

```
'000000000000000000000000101000000100'
```

which you would convert into the integer 2564 so that:

```
icsAllowRights: 2564
```

OID

2.16.840.1.113730.3.1.727

icsAnonymousAllowWrite

Origin

iPlanet Calendar Server 5.1

Syntax

boolean (yes, no)

Object Classes

icsCalendarDomain

Definition

Specifies if anonymous users can write events in public calendars. The value comes from the `ics.conf` setting

service.wcap.anonymousallowpubliccalendarwrite.

Example

```
icsAnonymousAllowWrite: yes
```

OID

2.16.840.1.113730.3.1.728

icsAnonymousCalendar

Origin

iPlanet Calendar Server 5.1

Syntax

ces

Object Classes

[icsCalendarDomain](#)

Definition

Calendar ID for anonymous users. The value is taken from the `ics.conf` setting `calstore.anonymous.calid`.

Example

```
icsAnonymousCalendar: guest1
```

OID

2.16.840.1.113730.3.1.729

icsAnonymousDefaultSet

Origin

Not implemented.

Syntax

ces, UTF8 encoded

Object Classes

[icsCalendarDomain](#)

Definition

Default calendar set for anonymous users.

Example**OID**

2.16.840.1.113730.3.1.730

icsAnonymousLogin

Origin

iPlanet Calendar Server 5.1

Syntax

boolean (yes, no))

Object Classes

[icsCalendarDomain](#)

Definition

Specifies if anonymous login is allowed. Value is taken from the `ics.conf` file setting `service.http.allowanonymousLogin`.

Example

```
icsAnonymousLogin: yes
```

OID

2.16.840.1.113730.3.1.798

icsAnonymousSet

Origin

Not implemented.

Syntax

ces, UTF8 encoded

Object Classes

[icsCalendarDomain](#)

Definition

Reserved. Not implemented.

Default calendar set for anonymous users.

Example

OID

2.16.840.1.113730.3.1.732

icsCalendar

Origin

iPlanet Calendar Server 5.1

Syntax

ces, single-valued

Object Classes

[icsCalendarResource](#), [icsCalendarUser](#)

Definition

Default calendar for a user or resource. Required attribute. It is a policy of Calendar Server to construct calendar IDs based on the user's ID, since it is guaranteed to be unique.

Example

icsCalendar: jdoe

OID

2.16.840.1.113730.3.1.731

icsCalendarOwned

Origin

iPlanet Calendar Server 5.1

Syntax

ces, multi-valued

Object Classes

[icsCalendarUser](#)

Definition

Calendars owned by this user. Required attribute. Must be set with the user's default calendar value.

Example

icsCalendar: jdoe

OID

1.3.6.1.4.1.42.2.27.9.1.6

icsCapacity

Origin

Not implemented.

Syntax

int, single-valued

Object Classes**Definition**

Reserved, not implemented.

Example**OID**

2.16.840.1.113730.3.1.800

icsContact

Origin

Not implemented.

Syntax

cis, UTF8 encoded

Object Classes

[icsCalendarResource](#)

Definition

Reserved, not implemented.

Resource contact name.

Example

icsContact: John Doe jdoe@sesta.com

OID

2.16.840.1.113730.3.1.733

icsDefaultAccess

Origin

iPlanet Calendar Server 5.1

Syntax

cis, single valued

Object Classes**Definition**

Default access control string applied to the user's default calendar. For more information about access control, see "Access Control Entries" in the *Sun ONE Calendar Server Programmer's Manual*. If this attribute is not present, the value is taken from the `ics.conf` file setting `calstore.calendar.default.acl`.

Example

Granting the user both freebusy and scheduling permission for calendar components.

icsDefaultAccess: @sesta.com^c^sf^g

OID

2.16.840.1.113730.3.1.734

icsDefaultSet

Origin

iPlanet Calendar Server 5.1

Syntax

ces, single-valued

Object Classes[icsCalendarUser](#)**Definition**

User preference for what calendars to display at login. User's can specify any of their calendar sets (groups they have created) to be displayed at login instead of a single calendar.

Example

```
icsDefaultSet: MyCalendarGroup
```

OID

```
2.16.840.1.113730.3.1.735
```

icsDomainAllowed

Origin

Not implemented.

Syntax

cis, single-valued (see [mgrpAllowedDomain](#))

Object Classes[icsCalendarDomain](#)**Definition**

What domains are allowed. The value has the following format:

```
service-list:client-list
```

where *service-list* is a blank- or comma-separated list of one or more service names or wildcards, and *client-list* is a blank- or comma-separated list of one or more host names or addresses, patterns or wildcards.

The following are the explicit wildcards recognized by the system:

ALL	Always matches
LOCAL	Matches any host whose name does not contain a dot character.
UNKNOWN	Matches any host whose name or address are unknown. Use this with care.
KNOWN	Matches any host whose name and address are known. Use with care.
DNSSPOOFER	Matches any host whose name does not match its address.

There is one operator that can be used in the service-list and the client-list:

EXCEPT Matches anything that matches list 1 unless it matches anything in list 2.
The expected form: list1 EXCEPT list2. List1 and list2 are comma-separated.

You can use patterns to distinguish clients by the network address that they can connect to. For example: `service@host_pattern:client-list`.

The default value comes from `service.http.domainallowed` in the `ics.conf` file.

Example

Allow local access to anyone in the `sesta.com` domain.

```
icsDomainAllowed: ALL:sesta.com
```

OID

2.16.840.1.113730.3.1.736

icsDomainNames

Origin

iPlanet Calendar Server 5.1.1

Syntax

cis, multi-valued, ASCII

Object Classes

[icsCalendarDWPHost](#)

Definition

For cross-domain searching, each domain to be searched must be listed using this attribute.

Example

```
icsDomainNames: sesta.com
icsDomainNames: siroe.com
```

OID

1.3.6.1.4.1.42.2.27.9.1.3

icsDomainNotAllowed

Origin

iPlanet Calendar Server 5.1

Syntax

cis, single-valued (see [mgrpDisallowedDomain](#))

Object Classes

[icsCalendarDomain](#)

Definition

What domains are not allowed. The value has the following format:

service-list:client-list

where service-list is a blank- or comma-separated list of one or more service names or wildcards, and client-list is a blank- or comma-separated list of one or more host names or addresses, patterns or wildcards.

The following are the explicit wildcards recognized by the system:

ALL	Always matches
LOCAL	Matches any host whose name does not contain a dot character.
UNKNOWN	Matches any host whose name or address are unknown. Use this with care.
KNOWN	Matches host whose name and address are known. Use with care.
DNSSPOOFER	Matches any host whose name does not match its address.

There is one operator that can be used in the service-list and the client-list:

EXCEPT	Matches anything that matches list 1 unless it matches anything in list 2. The expected form: list1 EXCEPT list2. List1 and list2 are comma-separated.
--------	---

The value comes from `ics.conf` setting `service.http.domainnotallowed`.

Example 1

If you want to allow access to all but a selected few hosts, you can explicitly deny access as in the following example:

Deny access to anyone at the company22.com domain.

```
icsDomainNotAllowed: ALL:company22.com
```

In this instance, you would not need to have any specific `icsDomainAllowed` attributes.

Example 2

If you want to implement a no-access default, a single instance of this attribute will do it. This denies all service to all hosts, unless they are specifically permitted access by `icsDomainAllowed` attributes.

```
icsDomainNotAllowed: ALL:ALL
```

Example 3

The following example shows how to deny access to any unknown users.

```
icsDomainNotAllowed: ALL:UNKNOWN@ALL
```

OID

2.16.840.1.113730.3.1.737

icsDWPBackEndHosts

Origin

Sun ONE Calendar Server 5.1.1

Syntax

cis, multi-valued

Object Classes

[icsCalendarDomain](#)

Definition

The list of all possible back end hosts used for calendars found in this domain. This attribute is required if the calendar installation is using the [Database Wire Protocol \(DWP\)](#).

Example

```
icsDWPBackEndHosts: machine1
icsDWPBackEndHosts: machine2
```

OID

1.3.6.1.4.1.42.2.27.9.1.5

icsDWPHost

Origin

iPlanet Calendar Server 5.1.1

Syntax

cis, single-valued, ASCII

Object Classes[icsCalendarDWPHost](#), [icsCalendarResource](#), [icsCalendarUser](#)**Definition**

Stores a DWP host name so that the calendar ID can be resolved to the [Database Wire Protocol \(DWP\)](#) server that stores the calendar and its data. When the calendar database is distributed across several back end servers, the attribute value is the DNS name of user's back end host. Each user's entire calendar will be on a single back end server. Required if using the [Calendar Lookup Database \(CLD\)](#).

This attribute is required if the Calendar installation is using DWP to distribute calendar data across back end calendar data servers. If DWP is not being used, every user's calendar will be found on the same host as the calendar server. If an installation initially does not use DWP, but later switches to it, the calendar server will fill in this value based on the default DWP host name found in the domain entry. If there is no value or such entry (calendar server is not in hosted domain mode) then the value will be picked up from the `ics.conf` configuration file.

Example`icsDWPHost:calserv1`**OID**

1.3.6.1.4.1.42.2.27.9.1.1

icsExtended

Origin

Sun ONE Calendar Server 5.1.1

Syntax

cis, multi-valued

Object Classes

[icsCalendarDWPHost](#)

Definition

Extensions for calendar. Reserved.

Example

OID

2.16.840.1.113730.3.1.738

icsExtendedDomainPrefs

Origin

iPlanet Calendar Server 5.1

Syntax

cis, multi- valued

Object Classes

[icsCalendarDomain](#)

Definition

Preferences for calendar domains can be set using the properties found in [Table 3-2](#). Each attribute value is a property-value pair. The default settings for these properties are found in the domain server's `ics.conf` file. In the absence of this attribute, the `ics.conf` settings will be used.

Table 3-2 Domain Preferences

Property	Value	Description
allowProxyLogin	yes, no	Allow proxy login
calmasterAccessOverride	yes, no	Domain administrator can override access control
calmasterCred	string	Bind credentials (password) for user specified in <code>ics.conf</code> setting <code>service.admin.calmaster.userid</code>
calmasterUid	string	User ID for the domain administrator

Table 3-2 Domain Preferences *(Continued)*

Property	Value	Description
createLowerCase	yes, no	Make calendar name lowercase for creating new calendars and looking up calendars.
domainAccess	valid acl string	Access control string for domain. Used in cross domain searches.
fbIncludeDefCal	yes, no	User's default calendar included in freebusy calendar list.
filterPrivateEvents	yes, no	Filter the private and confidential events on queries to server.
resourceDefaultAcl	valid access string	Resource calendars' default ACL
setPublicRead	yes, no	Set default user calendars to public read and private write (yes), or private read and private write (no).
subIncludeDefCal	yes, no	User's default calendar included in subscribed calendar list
uiAllowAnyone	yes/no	Everybody ACL shows and can be used in the user interface.
uibaseURL	valid URL	Base server address. For example, <code>https://proxyserver/</code>
uiConfigFile	string	Specifies the configuration file for the user interface. (Allows items in the user interface to be turned off.)
uiProxyUrl	string	Proxy server address prepended in user interface JavaScript file. For example, <code>https://web_portal.com/</code>

Example

```
icsExtendedDomainPrefs: createLowerCase=yes

icsExtendedDomainPrefs:
domainAccess=@@d^a^slfrwd^g;anonymous^a^r^g;@^a^s^g
```

OID

```
2.16.840.1.113730.3.1.739
```

icsExtendedGroupPrefs

Origin

iPlanet Calendar Server 5.1

Syntax

cis

Object Classes

[icsAdministrator](#)

Definition

Extensions for calendar group preferences.Reserved.

Example**OID**

2.16.840.1.113730.3.1.740

icsExtendedResourcePrefs

Origin

Not implemented.

Syntax

cis

Object Classes**Definition**

Reserved, not implemented.

Example**OID**

2.16.840.1.113730.3.1.741

icsExtendedUserPrefs

Origin

iPlanet Calendar Server 5.1

Syntax

cis, multi-valued

Object Classes
[icsCalendarUser](#)

Definition
Extensions for calendar user preferences. The attribute value is a property-value pair. The following are the properties and their values

Table 3-3 Extended User Preferences

Properties	Values	Description
ceAllCalendarTZIDS	a standard time zone	Time zone TZID for this calendar.
ceClock	12, 24	Defines whether a 12- or 24-hour clock is used.
ceColorSet	pref_group1 pref_group2 pref_group3 pref_group4 pref_group7	Defines which of the five UI color schemes to use.
ceDateOrder	M/D/Y D/M/Y Y/M/D	Determines what order the three elements of a date (month (M), day (D), and year (Y)) are displayed.
ceDateSeparator	Any single printable character. For example: / or -	The single character used to delimit displayed date elements (M,D,Y). For example, a date can be displayed as: 12/22/2002.
ceDayHead	0–23	Start time hour (expressed as one of 24 hours in a day) for displaying calendar information.
ceDayTail	0–23	End time hour (expressed as one of 24 hours in a day) for displaying calendar information.
cdDefaultAgenda	unused	Not currently implemented.
cdDefaultAlarmEmail	email addresses separated by white space	Email Addresses event alarms sent to.
ceDefaultAlarmStart	P[unit count][unit type]	Amount of time before the event an alarm should be sent. Where <code>unit count</code> is any numeric value, and <code>unit type</code> is either M (minutes), H (hours), or D (days). For example: P10M
ceDefaultTZID	one of standard time zones For a list of time zones, see Standard Time Zones .	Time zone to use when a calendar does not have one assigned to it.

Table 3-3 Extended User Preferences *(Continued)*

Properties	Values	Description
ceDefaultView	dayview weekview monthview yearview groupview	View to be presented at log in. If this parameter is not present, overview is used as the default. (groupview is the Comparison view on the user interface)
ceExcludeSatSun	boolean (0, 1)	Calendars don't display if value=1. Default is value=0.
ceFontFace	One of these values: 1) Times New Roman, Times, serif 2) Courier New, Courier, monospace 3) PrimaSans BT, Verdana, sans-serif	Three choices of font face to be used in the user interface.
ceFontSizeDelta	pref_font_size_group_2 (normal) pref_font_size_group_1 (larger) pref_font_size_group_3 (smaller)	Defines three font sizes for the user interface. In the interface they are defined as: normal, larger, smaller.
ceGroupInviteAll	boolean (0, 1)	When creating an invitation while viewing a group, invite all calendars in the group when value=1; default is 1.
ceInterval	PT0H15M PT0H30M PT1H0M PT2H0M PT4H0M	Defines the time interval to be used when displaying calendar information. Intervals are: 15 min., 30 min., 1 hour, 2 hours, 4 hours.
ceNotifyEmail	any valid RFC 822 email address	Email address notifications are mailed to when the calendar receives an invitation to an event.
ceNotifyEnable	0, 1	Enables/disables email notifications being sent when the calendar receives an invitation to an event. 0 = do not send notifications 1 = send notifications
ceSingleCalendarTZID	any valid time zone For a list of valid time zones, see Standard Time Zones .	Lists the time zone assigned to this calendar. If the parameter is not sent, the default time zone is used. For example: America/Los_Angeles

Table 3-3 Extended User Preferences *(Continued)*

Properties	Values	Description
ceToolImage	0, 1	Toggle for the user interface display of icon images on the toolbar. 0 = do not display icons, 1 = display icons (default)
ceToolText	0, 1	Toggle for the user interface display of icon text on the toolbar. 0 = do not display text with the icon 1 = display text with the icon (default)

NOTE Regarding `ceToolImage` and `ceToolText`: the user interface only allows three possibilities for the toolbar: icons and text (attributes values 1, 1), icons only (attributes values 1, 0), and text only (attributes values 0, 1). It does not allow the user to turn off both icons and text (attributes values 0, 0).

Example

```
icsextendeduserprefs: ceClock=12
icsextendeduserprefs: ceColorSet=pref_group_1
icsextendeduserprefs: ceDateOrder=D/M/Y
icsextendeduserprefs: ceDateSeparator=/
icsextendeduserprefs: ceDayHead=10
icsextendeduserprefs: ceDayTail=17
icsextendeduserprefs: ceDefaultAlarmEmail=jdoe@sesta.com
icsextendeduserprefs: ceDefaultAlarmStart=P30H
icsextendeduserprefs: ceDefaultTZID=America/New_York
icsextendeduserprefs: ceDefaultView=groupview
icsextendeduserprefs: ceFontFace=PrimaSans BT,Verdana,sans-serif
icsextendeduserprefs: ceFontSizeDelta=pref_font_size_group_3
icsextendeduserprefs: ceInterval=PT2H0M
icsextendeduserprefs: ceNotifyEmail=jdoe@sesta.com
icsextendeduserprefs: ceNotifyEnable=0
icsextendeduserprefs: ceSingleCalendarTZID=America/Los_Angeles
```

```
icsextendeduserprefs: ceToolText=1
```

```
icsextendeduserprefs: ceToolImage=1
```

OID

2.16.840.1.113730.3.1.742

icsFirstDay

Origin

iPlanet Calendar Server 5.1

Syntax

cis, single-valued

Object Classes

[icsCalendarUser](#)

Definition

First day of the week to be displayed on user's calendar.

Range of values: 1–7, with 1 = Sunday, 2 = Monday, 3= Tuesday, 4 = Wednesday, 5 = Thursday, 6 = Friday, 7 = Saturday

Example

```
icsFirstDay: 1
```

OID

2.16.840.1.113730.3.1.743

icsFreeBusy

Origin

Not implemented.

Syntax

ces, single-valued

Object Classes**Definition**

Reserved, not implemented.

Example**OID**

2.16.840.1.113730.3.1.744

icsGeo

Origin

Not implemented.

Syntax

cis single-valued

Latitude; longitude

Object Classes**Definition**

Reserved, not implemented.

Geographical location of user or resource.

Example

This class exists only for compliance with the RFC spec and is not used.

OID

2.16.840.1.113730.3.1.745

icsMandatorySubscribed

Origin

iPlanet Calendar Server 5.1

Syntax

ces

Object Classes

[icsCalendarDomain](#)

Definition

The valid calendar IDs for mandatory subscribed calendars for all users in a domain.

Example

```
icsMandatorySubscribed: ConfRml@sesta.com:meetings
```

OID

2.16.840.1.113730.3.1.746

icsMandatoryView

Origin

iPlanet Calendar Server 5.1

Syntax

cis

Object Classes

[icsCalendarDomain](#)

Definition

The mandatory default view for all calendars in a domain. Views are: overview, day, week, month, year, comparison.

Example

```
icsMandatoryView: overview
```

OID

2.16.840.1.113730.3.1.747

icsPartition

Origin

Not implemented.

Syntax

cis, single-valued, ASCII

Object Classes

[icsCalendarResource](#), [icsCalendarUser](#)

Definition

Reserved. not implemented.

The name of the partition that holds a calendar database. There is no default value.

Example

```
icsPartition: partition1
```

OID

1.3.6.1.4.1.42.2.27.9.1.4

icsPreferredHost

Origin

Not implemented.

Syntax

cis, single-valued

Object Classes**Definition**

Reserved, not implemented.

Specifies the preferred host for this calendar. This attribute is used by clients to retrieve the front-end-host server name.

Example**OID**

2.16.840.1.113730.3.1.749

icsQuota

Origin

Not implemented.

Syntax

int, single-valued

Object Classes**Definition**

Reserved, not implemented.

Example**OID**

2.16.840.1.113730.3.1.748

icsRecurrenceBound

Origin

iPlanet Calendar Server 5.1

Syntax

int, single-valued

Object Classes

[icsCalendarDomain](#)

Definition

Maximum number of instances created for events and todos with infinite recurrence. The value is taken from the `ics.conf` setting `calstore.recurrence.bound`.

Example

```
icsRecurrenceBound: 60
```

OID

2.16.840.1.113730.3.1.750

icsRecurrenceDate

Origin

iPlanet Calendar Server 5.1

Syntax

cis, single-valued

Object Classes

[icsCalendarDomain](#)

Definition

An ISO8601 date/time string specifying the maximum date for events and todos with infinite recurrence.

Example

```
icsRecurrenceDate: 20300365T115959Z
```

OID

2.16.840.1.113730.3.1.751

icsRegularExpressions

Origin

iPlanet Calendar Server 5.1.1

Syntax

ces, multi-valued, UTF8

Object Classes

[icsCalendarDWPHost](#)

Definition

Stores regular expressions used to divide the LDAP database between servers.

Example

```
icsRegularExpressions: A-F,G-L,M-T,U-Z
```

A-F, G-L, M-T, U-Z are possible values for instances of this attribute and describe a database divided alphabetically between four servers.

icsSessionTimeout

OID

1.3.6.1.4.1.42.2.27.9.1.2

icsSessionTimeout

Origin

iPlanet Calendar Server 5.1

Syntax

int, single-valued

Object Classes

[icsCalendarDomain](#)

Definition

Number of seconds of inactivity before a user session is timed out. Read from `ics.conf` setting `service.http.idletimeout`.

Example

icsSessionTimeout: 600

OID

2.16.840.1.113730.3.1.752

icsSet

Origin

iPlanet Calendar Server 5.1

Syntax

cis, multi-valued

Object Classes

[icsAnonymousSet](#), [icsCalendarUser](#), [icsDefaultAnonymousSet](#)

Definition

Defines one group of calendars. End users create these groups for various tasks. Each group is represented by one icsSet attribute, that is, for every group the user creates there will be one icsSet attribute. For example, if the user has three groups defined, there will be three icsSet attributes.

The value for this attribute is a six-part string, with each part separated by a dollar sign (\$).

The following table shows the six parts of this attribute's value:

Table 3-4 Six Parts of the Attribute Value

Part	Required?	Description
name	Required	The display name of this group.
calendars	Required	A semi-colon-separated list of calendar IDs (calid) that comprise this group.
tzmode	Required	Three possible values: <code>default</code> , <code>inherit</code> , <code>specify</code> . The value that tells where the time zone for this group comes from. <code>default</code> – take user's default time zone <code>inherit</code> – take the time zone of the first calendar in the group <code>specify</code> – take the time zone from the <code>tz</code> value that follows.
tz	Not Required, unless <code>tzmode = specify</code>	A valid time zone for this group. For a list of acceptable values, see Standard Time Zones . Value is optional unless <code>tzmode = specify</code> , then it is required.
mergeInDayView	Required	A boolean (TRUE/FALSE). The value tells whether to display this group in the Day view (TRUE) or the Comparison view (FALSE)
description	Not Required	Character string. Optional description of the calendar.

Example

The value of this attribute should all be on one line or if you wish to break a line, start the next line with a single space or tab.

```
icsSet: name=GroupName$calendars=calid1;calid2;calid3$
      tzmode=specify$tz=America/Los_Angeles$mergeInDayView=FALSE$
      description=Example group of calendars.
```

OID

2.16.840.1.113730.3.1.753

icsSourceHtml

Origin
iPlanet Calendar Server 5.1

Syntax
ces, single-valued

Object Classes
[icsCalendarDomain](#)

Definition
The alternate location of all client HTML files. A directory path that is relative to the installed client HTML files. The default value comes from the `ics.conf` setting `service.http.uidir.path`.

[Table 3-5](#) lists the values for this attribute.

Table 3-5 Alternate Locations for Client HTML files.

Parameters	Value	Definition
sourceUrl	directory	Directory relative to executable, where all URL references to files are stored.
uiDirPath	directory	Directory containing the default client. If only WCAP access is allowed, value is "".
calHostname	hostname	HTTP host for retrieving HTML documents.

Example
`icsSourceHtml: calHostname=calhost1`

OID
2.16.840.1.113730.3.1.754

icsStatus

Origin
iPlanet Calendar Server 5.1

Syntax
cis, single-valued

Object Classes

[inetDomain](#)

Definition

This attribute must be set when assigning calendar services to a domain. The attribute describes the status of this domain’s calendar service. Calendar status, with one of the values specified in [Table 3-6](#):

Table 3-6 Calendar Status Values	
Status	Definition
active	Users and resources in this domain have access to calendar services.
inactive	No calendar services allowed for any users or resources in this domain, until the status is changed to active again. Calendars remain in the database and the LDAP entry remains.
deleted	<p>No calendar service allowed for any users or resources in this domain. It is marked for deletion. Calendars will be removed from the database and the LDAP attributes that control the calendar’s service will be removed.</p> <p>All the entries remain in the directory, but object classes having to do only with calendars for these users, resources and domains will be removed. For example, <code>icsCalendarUser</code>, <code>icsCalendarResource</code>, <code>icsCalendarDomain</code> will be removed. In addition all attributes with the <code>ics</code> prefix will be removed.</p> <p>For resources, it means that the resources associated with this object are to be removed from the calendar system, but the entry remains in the directory. For domains, all calendars associated with all the users and resources within that domain are to be removed.</p>

If this attribute is not set, the [icsAllowedServiceAccess](#) attribute is checked. If present and the value of that attribute is `http`, then calendar services are disabled for the user (the user status is `inactive`). If `icsAllowedServiceAccess` has any other value, or if both attributes are missing, then the default user status is `active`.

Calendar services evaluate the following status attributes in order:[inetDomainStatus](#), `icsStatus` (for `icsCalendarDomain`), either [inetResourceStatus](#) or [inetUserStatus](#), and `icsStatus` (for either `icsCalendarResource` or `icsCalendarUser`).

The rule is: the first of these attributes that is set to something other than `active` takes precedence over all the others.

Example

`icsStatus: active`

OID

2.16.840.1.113730.3.1.755

icsSubscribed

Origin

iPlanet Calendar Server 5.1

Syntax

ics, multi-valued

Object Classes

[icsCalendarUser](#)

Definition

List of calendars to which this user is subscribed. This includes all the calendars that the user owns, as well as any calendars owned by others to which the owner subscribes.

The value of this attribute is the calendar ID and optionally, the calendar name, with a dollar sign (\$) between them, when present.

Example

```
icsSubscribed: jdoe$MyHomeCalendar  
icsSubscribed: jsmith
```

OID

2.16.840.1.113730.3.1.756

icsTimezone

Origin

iPlanet Calendar Server 5.1

Syntax

cis

Object Classes

[icsCalendarResource](#), [icsCalendarUser](#)

Definition

The default time zone for this user or resource calendar if one is not explicitly assigned through their own user preferences (see [icsExtendedUserPrefs](#)). Specifically a valid time zone from the list found in “[Standard Time Zones](#)” on [page 263](#). The value is taken from the `ics.conf` setting `calstore.default.timezoneID`.

Example

```
icsTimezone: America/Chicago
```

OID

```
2.16.840.1.113730.3.1.757
```

inetCanonicalDomainName

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainAuthInfo](#)

Definition

Used both in Sun ONE LDAP Schema v.1 and compatibility mode for Sun ONE LDAP Schema v.2 (with a DC Tree). This attribute is a fully qualified domain name. For an explanation of native and compatibility mode LDAP structures, see the *Sun Java™ Enterprise System Installation Guide*.

In compatibility mode, if more than one DC node in a DC tree refers to the same organization node in the Organization tree, this attribute is used to specify the canonical domain name used by the mail processes to open users' mailboxes. (There can be only one canonical domain name per organization node, but there can be many DC nodes referring to the same organization node)

This attribute is not necessary if there is only one DC node referring to an organization node. If the attribute is missing, the DC node entry is taken for the canonical domain name.

If this attribute is missing and there are multiple DC nodes referring to the same organization node, the mail processes could possibly use the wrong domain name when trying to open users' mailboxes.

Using multiple domain nodes to point to the same organization node allows you to have different attribute settings (and therefore different routing) for each one. If you want to be sure the two domains have the same attribute settings (are routed identically), use [aliasedObjectName](#) on the duplicate node instead.

This attribute is not used for the Sun ONE LDAP Schema v.2 native mode LDAP data model.

Example

For the corporation `sesta.com`, if two DC nodes exist, `dc=sesta` and `dc=sesta2`, both referring to the organization node `o=sesta`, then you must specify one of them in the attribute:

```
inetCanonicalDomainName: sesta.com
```

Thus:

```
dn: dc=sesta,dc=com,o=internet
inetDomainBaseDN: o=sesta.com
inetCanonicalDomainName: sesta.com
```

```
dn: dc=sesta2,dc=com,o=internet
inetDomainBaseDN: o=sesta.com
```

OID

2.16.840.1.113730.3.1.701

inetCoS

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[ipUser](#)

Definition

(Organization tree domain) Specifies the name of the Class of Service (CoS) template supplying values for attributes in the user entry. The RDN of the CoS template is the value of this attribute. Attribute values provided by the template and any override rules are specified in the CoS definition. CoS definitions are

created by using the object class `cosDefinition`. The value of attribute `cosSpecifier` in CoS definition entry is set to `inetCoS`. Create CoS definitions and templates in the container `ou=CoS` in the subtree for that domain. See the *iPlanet Messaging Server 5.2 Provisioning Guide* for more information.

Example

`inetCoS: HallofFame`

OID

2.16.840.1.113730.3.1.706

inetDomainBaseDN

Origin

iPlanet Messaging Server 5.0

Syntax

dn, single-valued

Object Classes

`inetDomain`

Definition

This attribute decorates domain nodes on the DC Tree when in compatibility mode. It is not used for native mode Sun ONE LDAP Schema v.2.

The two domains, the alias and the referenced domain, can have different attribute values, such that routing will differ between the two. If you want to ensure routing is the same, the attribute values of both domains must be identical.

DN of the organization's subtree where all user/group entries are stored. This attribute points to a valid Organization subtree DN. Messaging Server components using the RFC 2247 search (compatibility mode) must resolve this DN in order to search for user and group entries that correspond to the hosted organization.

Example

`inetDomainBaseDN: o=sesta.com,o=siroe-isp.com`

OID

2.16.840.1.113730.3.1.690

inetDomainCertMap

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[inetDomainAuthInfo](#)

Definition

Reserved.

Example

TBD

OID

2.16.840.1.113730.3.1.700

inetDomainSearchFilter

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainAuthInfo](#)

Definition

LDAP search filter to use in search templates when performing a native mode search. The compatibility mode RFC 2247 algorithm search requires this attribute, but ignores its value.

Used during authentication to map login name in that domain to an LDAP entry.

The following variables can be used in constructing the filter:

- %U–Name part of the login name (that is, everything before the login separator stored in the servers configuration).

- %V-Domain part of the login string .

If this attribute is missing, it is equivalent to:

```
(&(objectclass=inetOrgPerson)(uid=%U))
```

Namespaces where users are provisioned with compound uids, such as uid=john_siroe.com, where john is the userID and siroe.com is the domain, would use a search filter of uid=%U_%V. This maps a login string of john@siroe.com (where @ is the login separator for the service) into a search request by the service for an entry's namespace of siroe.com, where uid=john_siroe.com.

An alternate example of using this attribute would be for sites wanting to log people in based on their employee identification. Assuming the attribute empID in user entries stores employee identifications, the search filter would be:

```
(&(objectclass=inetOrgPerson)(empID=%U)).
```

This attribute must return a unique match for valid users within the [inetDomainBaseDN](#) subtree. If this attribute is not set, the uid attribute must be unique in the inetDomainBaseDN subtree.

Example

```
inetDomainSearchFilter: uid=%U
```

OID

```
2.16.840.1.113730.3.1.699
```

inetDomainStatus

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomain](#)

Definition

Applications using a DC Tree as their entry point (RFC 2247 compliant compatibility mode LDAP data model) may choose to respect application specific status attributes, but must consume and respect this attribute on the affiliated physical node (Organization Tree). In other words, for compatibility mode, both the DC Tree and the Organization Tree contain this attribute and if the two attribute's values differ, the one on the Organization Tree will take precedence.

Specifies the global status of a domain for all services. The intent of this attribute is to allow the administrator to temporarily suspend and then reactivate access, or to permanently remove access, by the domain and all its users to all the services enabled for that domain.

This attribute takes one of three values. Supported values are:

Table 3-7 Status Attribute Values

Value	Description
active	Domain is active and users in the domain may use services enabled by the overlay of service-specific object classes and the service state as indicated by the particular status attribute for that service.
inactive	Domain is inactive. The account may not use any services granted by service-specific object classes. This state overrides individual service status set using the service's status attributes.
deleted	Domain is marked as deleted. The account may remain in this state within the directory for some time (pending purging of deleted users). Service requests for all users in a domain marked as deleted will return permanent failures.

A missing value implies status is active. An illegal value is treated as inactive.

There are four status attributes that mail services look at and which are evaluated in this order: inetDomainStatus, mailDomainStatus, inetUserStatus, and mailUserStatus. The rule is: the first of these attributes that is set to something other than active takes precedence over all the others.

Similarly, this attribute is used for calendar services when evaluating status. The status attributes used are: inetDomainStatus, icsStatus (of icsCalendarDomain), either inetResourceStatus or inetUserStatus, and icsStatus (of either icsCalendarResource or icsCalendarUser).

In addition, in compatibility mode, when this attribute decorates both the DC Tree and the Organization Tree, both attributes should agree. Administrators are responsible for keeping the two synchronized. If the two attributes do not have the same value, Messaging Server will use the value found in the Organization Tree, while some other legacy application might be using the DC Tree attribute only. This could cause unpredictable results.

For more information on native and compatibility mode LDAP schemes, see the *Sun Java™ Enterprise System Installation Guide*.

Example

```
inetDomainStatus: active
```

OID

```
2.16.840.1.113730.3.1.691
```

inetMailGroupStatus

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailGroup](#)

Definition

Current status of a mail group.

The following table lists the possible status values and gives a description of each:

active	Messages are delivered to the members of the mailing list.
inactive	Messages sent to the mailing list result in a transient failure.
deleted	Mailing list can be purged from the directory. Messages sent to the group return a permanent failure.

A missing value implies status is `active`. An illegal value is treated as `inactive`.

There are four status attributes that interact with each other: `inetDomainStatus`, `mailDomainStatus`, `inetGroupStatus`, and `inetMailGroupStatus`. These are considered in the order just given. The first one with a status of `active` takes precedence over the setting of all the others.

The MTA option `LDAP_GROUP_STATUS` can be used to specify a different attribute to be used for group status.

Example

`inetMailGroupStatus: active`

OID

2.16.840.1.113730.3.1.786

inetResourceStatus

Origin

iPlanet Calendar Server 5.1

Syntax

cis, single-valued

Object Classes

`inetResource`

Definition

This is a global status for resources. It holds the current status of the resource: `active`, `inactive`, or `deleted` for all services. It is used by Sun ONE Identity Server to manage resources. Status changes can be made to a resource's status using the `commcli` interface, or by directly changing the LDAP entry for the group.

The following table lists the attribute's values and their meanings:

Table 3-8 Status Attribute Values

Value	Description
active	The resource is active and it may be used in services enabled by the overlay of service-specific object classes and the service state as indicated by the particular status attribute for that service.
inactive	Resource is inactive. The resource may not be used in any services granted by service-specific object classes. This state overrides individual service status set using the service's status attributes.

Table 3-8 Status Attribute Values

Value	Description
deleted	Resource is marked as deleted. The resource may remain in this state within the directory for some time (pending purging of deleted resources). Service requests for all resources marked as deleted will return permanent failures.

There are several status attributes that are evaluated to determine status. They are evaluated in this order: `inetDomainStatus`, `icsStatus` (for `icsCalendarDomain`), `inetResourceStatus`, `icsStatus` (for `icsCalendarResource`). These are considered in the order just given. The first one with a status of `active` takes precedence over the setting of all the others.

Example

```
inetResourceStatus: active
```

OID

```
2.16.840.1.113730.3.1.758
```

inetSubscriberAccountId

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

`inetSubscriber`

Definition

A unique account ID used for billing purposes.

Example

```
inetSubscriberAccountId: A3560B0
```

OID

```
2.16.840.1.113730.3.1.694
```

inetSubscriberChallenge

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetSubscriber](#)

Definition

Attribute for storing the challenge phrase used to identify the subscriber. Used in conjunction with the `inetSubscriberResponse`.

Example

```
inetSubscriberChallenge=Mother's Maiden Name
```

OID

2.16.840.1.113730.3.1.695

inetSubscriberResponse

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetSubscriber](#)

Definition

Attribute for storing the response to the challenge phrase.

Example

```
inetSubscriberResponse=Mamasita
```

OID

2.16.840.1.113730.3.1.696

inetUserHttpURL

Origin

iPlanet Messaging Server 5.0, deprecated in Sun ONE Messaging Server 6.0

Syntax

cis, single-valued

Object Classes

[inetUser](#)

Definition

This attribute is deprecated for the user class `inetUser` starting in Sun ONE Messaging Server 6.0 and is likely to be removed from the object class in future versions of Sun ONE schema.

User's primary URL for publishing Web content. This is an informational attribute and may be used in phonebook-type applications. It is not intended to have any operational impact.

Example

`inetUserHttpURL: http://www.siroe.com/theotis`

OID

2.16.840.1.113730.3.1.693

inetUserStatus

Origin

iPlanet Messaging Server 5.0, Sun ONE Calendar Server 5.1.1

Syntax

cis, single-valued

Object Classes

[inetUser](#)

Definition

Specifies the status of a user's account with regard to global server access. This attribute enables the administrator to temporarily suspend, reactivate, or permanently remove access to all services for a user account.

The following table lists the values for this attribute:

Table 3-9 Status Attribute Values

Values	Description
active	The user account is active and the user can use all services enabled by the overlay of service-specific object classes and the service state as indicated by the particular status attribute for that service. For example, a user can use the email system if both mailUserStatus and inetDomainStatus are set to active.
inactive	The user account is inactive. The account cannot use any services granted by service-specific object classes. This state overrides individual service status set using the service's status attributes.
deleted	The account is marked as deleted. The account can remain in this state within the directory for some time (pending purging of deleted users). Service requests for a user marked as deleted must return permanent failures.

A missing value implies status is active. An illegal value is treated as inactive.

There are four status attributes that mail services look at and which are evaluated in this order: inetDomainStatus, mailDomainStatus, inetUserStatus, and mailUserStatus. The rule is: the first of these attributes that is set to something other than active takes precedence over all the others.

For calendar services, the attributes evaluated are: inetDomainStatus, icsStatus (for icsCalendarDomain), inetUserStatus, icsStatus (for icsCalendarUser).

When this attribute applies to a static group, defined using the inetUser object class, inactivating (disabling) the group only applies to the group itself and not the users in the group.

To disable the users of a group, create a dynamic group by assigning roles to the users, and then disable the role (which disables all users assigned to that role). For more information about roles, see the *Sun ONE Directory Server Administrator's Guide*.

The MTA option LDAP_USER_STATUS can be used to specify a different attribute to be used for user status.

Example

inetUserStatus=inactive

OID

2.16.840.1.113730.3.1.692

mail

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued (RFC 822 address)

Object Classes

[inetLocalMailRecipient](#), [icsCalendarResource](#), [icsCalendarUser](#)

Definition

Identifies a user's primary email address (the email address retrieved and displayed by white-pages lookup applications).

This attribute and `mailAlternateAddress`, are the default attributes used for reverse searches.

Example

`mail=jdoe@sesta.com`

OID

0.9.2342.19200300.100.1.3

mailAccessProxyPreAuth

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[mailDomain](#)

Definition

Attribute tells the MMP if the users in this domain have to be preauthenticated. Permitted values are `yes` or `no`.

Example

`mailAccessProxyPreAuth=yes`

OID

2.16.840.1.113730.3.1.769

mailAccessProxyReplay

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes[mailDomain](#)**Definition**

This attribute tells the Messaging Multiplexor how to reconstruct the login string when replaying the login sequence with the backend mail server. A missing attribute implies that the message access proxies construct the replay string based on the login name used by the client, the domain of the client, and the login separator used for this service. The `mailAccessProxyReplay` attribute overrides this default behavior when the message access proxy has a different backend server than Messaging and Collaboration.

The syntax is that of a login string, with the following substitutions:

- `%U`: Login name. That is, the name part of the login string, if it is a {name, domain} compound.
- `%V`: Domain part of the login string.
- `%[attr]`: The value of the LDAP user attribute.

Examples

1. If the client logs in as `hugo` and the domain associated with the server IP address used is `yoyo.com`, and `mailAccessProxyReplay=%U%V`, the replayed login string is `hugo@yoyo.com`.
2. If the client logs in as `hugo`, and the domain associated with the server IP address used is `yoyo.com`, and `mailAccessProxyReplay=%[surname]%V`, the replayed login string is the value of the surname attribute of the client.
3. If the client logs in as `hugo+yoyo.com`, and the login separator for the service used is `+`, and `mailAccessProxyReplay=%U%V`, the replayed login string is `hugo@yoyo.com`.

4. If the client logs in as `hugo`, and the domain associated with the server IP address used is `yoyo.com`, and `mailAccessProxyReplay` is not defined, and the login separator for the service used is `+`, the replayed login string is `hugo+yoyo.com`.

OID

2.16.840.1.113730.3.1.763

mailAdminRole

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes`inetMailAdministrator`**Definition**

Specifies the administrative role assigned to the members of the group. The only legal value for this attribute is `storeAdmin`. The object class that contains this attribute—`inetMailAdministrator`—is overlaid on a group entry to grant members of a group administrative privileges over part of the mail server. Currently the only privilege group members inherit are rights to perform proxy authentication for any user in the domain. These rights extend over users in the same domain as where the group is defined. To grant such privileges the attribute `mailAdminRole` must be set to the value `storeAdmin`.

Example`mailAdminRole: storeAdmin`**OID**

2.16.840.1.113730.3.1.780

mailAllowedServiceAccess

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailUser](#)

Definition

Stores access filters (rules). If no rules are specified, then user is allowed access to all services from all clients. Rules are separated by a dollar sign (\$). The rules are evaluated in this manner:

- Access is granted if the client information matches an allow filter for that service.
- Access is denied if the client information matches a deny filter for that service.
- If no match is made with any allow or deny filters, access is granted, except in the case where there are allow filters but no deny filters. In this case, a lack of match means access is denied.

For a full explanation of access filters and an alternate way to control access through the administration console or the `config` utility, see “Configuring Client Access to POP, IMAP, and HTTP Services” in the *Sun ONE Messaging Server Administrator’s Guide*.

Rule Syntax

`"+"` or `"-"` `service_list` `:` `client_list`

`+` (allow filter) means the services in the service list are being granted to the client list.

`-` (deny filter) means the services are being denied to the client list.

`service_list` is a comma separated list of services to which access is being granted or denied.

Legal service names are: `imap`, `imaps`, `pop`, `pops`, `smtp`, `smtps`, and `http`. Note that the MMP supports `imap`, `imaps`, `pop`, `pops`, and `smtp`. The backend supports `imap`, `pop`, `smtp`, and `http`.

`client_list` is a comma separated list of clients (domains) to which access is being granted or denied.

Wildcards can be substituted for the client list (domains). The following table shows the legal wildcards and gives a description of each:

Table 3-10 Wildcards

Wildcards	Description
ALL, *	The universal wildcard. Matches all names.
DNSSPOOFER	Matches any host whose DNS name does not match its own IP address.
KNOWN	Matches any host whose name and address are known. Use with care.
LOCAL	Matches any local host (one whose name does not contain a dot character). If your installation uses only canonical names, even local host names will contain dots and thus will not match this wildcard.
UNKNOWN	Matches any host whose name or address are unknown. Use this with care.

The following wildcards can be used for the service list: *, ALL.

Except Operator

The access control system supports a single operator, **EXCEPT**. You can use the **EXCEPT** operator to create exceptions to the patterns found in a rule's service list and client list. **EXCEPT** clauses can be nested. If there are multiple **EXCEPT** clauses in a rule, they are evaluated right to left.

The **EXCEPT** format is:

```
list1 EXCEPT list2
```

where **list1** is a comma separated list of services and **list2** is a comma separated lists of clients.

Example

This example shows a single rule with multiple services and a single wildcard for the client list.

```
mailAllowedServiceAccess: +imap,pop,http:*
```

This example shows multiple rules, but each rule is simplified to have only one service name and uses wildcards for the client list. (This is the most commonly used method of specifying access control in LDIF files.)

```
mailAllowedServiceAccess: +imap:ALL$+pop:ALL$+http:ALL
```

An example of how to disallow all services for a user is:

```
mailAllowedServiceAccess: -imap:*$-pop:*$-http:*
```

An example of a rule with an `EXCEPT` operator is:

```
mailAllowedServiceAccess: -ALL:ALL EXCEPT server1.sesta.com
```

This example denies access to all services for all clients except those on the host machine `server1.sesta.com`.

OID

2.16.840.1.113730.3.1.777

mailAlternateAddress

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[inetLocalMailRecipient](#), [pabPerson](#)

Definition

Alternate RFC 822 email address of this recipient. If the MTA receives mail with a “from” header with this email address, it rewrites the header with the value of the [mail](#) attribute and routes the email to that inbox. The [mailEquivalentAddress](#) attribute works similarly to route the email, but does not rewrite the header.

The local part of the address may be omitted to designate a user/group as the catchall address. A catchall domain address is an address that will receive mail to a specified domain if the MTA does not find an exact user address match with that domain.

This attribute, along with `mail`, are the default attributes used for reverse searches.

Example

```
mailAlternateAddress: jdoe@sesta.com
```

```
mailAlternateAddress: @sesta.com (catchall domain address)
```

OID

2.16.840.1.113730.3.1.13

mailAntiUBEService

Origin

iPlanet Messaging Server 5.2

Syntax

cis, multi-valued

Object Classes

`inetMailUser`, `mailDomain`

Definition

The string values given by this and other `optin` attributes are collected and passed to the filtering agent being used (for instance, Brightmail).

For Brightmail spam and virus checking, the interpretation of these strings is specified in the Brightmail configuration file. Brightmail uses the information from this attribute for its processing.

There are two Brightmail values:

- `spam` – When a spam message is found by the anti-UBE service, take the action specified in a system wide configuration option.
- `virus` - When a virus in a message is detected by the anti-UBE service, take the action specified in a system wide configuration option.

SpamAssasin, another filtering agent, does not use the actual value of the attribute; it can be set to anything.

While another attribute can be named in the `option.dat` setting for `LDAP_OPTIN`, it is not recommended. (For more information on Brightmail, see the *Sun ONE Messaging Server 6.0 Administrator's Guide*.)

To use this attribute to specify per user `optin` values, set the following in the `option.dat` file:

```
LDAP_OPTIN=mailAntiUBEService
```

To use the attribute to specify domain level `optin` values, set the following in the `option.dat` file:

```
LDAP_DOMAIN_ATTR_OPTIN=mailAntiUBEService
```

Example

```
mailAntiUBEService: virus
```

mailAutoReplyMode

mailAntiUBEService: spam

OID

mailAutoReplyMode

Origin

iPlanet Messaging Server 5.0 (for reply mode), iPlanet Messaging Server 5.2 patch 1 (for echo mode)

Syntax

cis, single-valued

Object Classes

[inetMailUser](#)

Definition

Specifies the autoreply mode for user mail account. This is one of several autoreply attributes used when autoreply is an active mail delivery option. The two modes for autoreply are:

- **echo** – Echo the original message with the added `mailAutoReplyText` or `mailAutoReplyTextInternal` to the original sender. This occurs only once a week per sender.

If you want the message to be echoed for each message from every sender regardless of how recently a previous reply was sent, set the `mailAutoReplyTimeOut` to 0, which will cause the reply message to be sent every time.

- **reply** – Send a fixed reply, contained in attributes `mailAutoReplyText` or `mailAutoReplyTextInternal`, to the original sender.

Example

mailAutoReplyMode: reply

OID

2.16.840.1.113730.3.1.14

mailAutoReplySubject

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailUser](#)

Definition

Subject text of auto-reply response. `$SUBJECT` can be used to insert the subject of the original message into the response.

Example

```
mailAutoreplySubject: I am on vacation
```

OID

2.16.840.1.113730.3.1.772

mailAutoReplyText

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailUser](#)

Definition

Auto-reply text sent to all senders except users in the recipient's domain. If not specified, external users receive no auto response.

Example

```
mailAutoreplyText: Please contact me later.
```

OID

2.16.840.1.113730.3.1.15

mailAutoReplyTextInternal

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailUser](#)

Definition

Auto-reply text sent to senders from the recipients domain. If not specified, then internal uses get the mail auto-reply text message.

Example

```
mailAutoreplyTextInternal: Please contact me later.
```

OID

2.16.840.1.113730.3.1.773

mailAutoReplyTimeOut

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes

[inetMailUser](#)

Definition

Duration, in hours, for successive auto-reply responses to any given mail sender. Used only when mailAutoReplyMode: reply. If the value is set to 0 for mailAutoReplyMode: echo then a response is sent back every time a message is received. Auto-reply responses are sent out only if the recipient is listed in the “to” or “cc:” of the original message.

Example

```
mailAutoreplyTimeout: 48
```

OID

2.16.840.1.113730.3.1.771

mailClientAttachmentQuota

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes[mailDomain](#)**Definition**

A positive integer value indicating the number of attachments the Messenger Express user can send per message in this domain. A value of -1 means no limit on attachments.

Example`mailClientAttachmentQuota: 12`**OID**

2.16.840.1.113730.3.1.768

mailConversionTag

Origin

iPlanet Messaging Server 5.2

Syntax

cis, multi-valued (ASCII string)

Object Classes`inetMailGroup, inetMailUser`**Definition**

Conversion tags attached to a message to this user or group. Tag specific conversion actions are specified in the MTA configuration.

The MTA option used to override this attribute is `LDAP_CONVERSION_TAG`.

Example

OID

mailDeferProcessing

Origin

iPlanet Messaging Server 5.2

Syntax

cis, single-valued (ASCII string)

Object Classes

`inetMailGroup`, `inetMailUser`

Definition

Controls whether or not address expansion of the current user or group entry is performed immediately (value is “No”), or deferred (value is “Yes”).

NOTE A different attribute (other than `mailDeferProcessing`) can be designated for this purpose in the MTA option `LDAP_REPROCESS`.

Deferral takes place if the value is “Yes” and the current source channel isn’t the reprocess channel. Deferral is accomplished by directing the user or group’s address to the reprocess channel. That is, the expansion of the alias is aborted and the original address (`user@domain`) is queued to the reprocess channel.

If this attribute does not exist, the setting of the deferred processing flag associated with delivery options processing is checked. If it is set, processing is deferred.

If it is not set, the default for users is to process immediately (as if the value of this attribute were “No”).

The default for groups (such as mailing lists) is controlled by the MTA option `DEFER_GROUP_PROCESSING`, which defaults to 1 (yes).

Best Practices Suggestions for Duplicate Message Problem

Getting duplicate copies of messages can happen. For example, if a user sends an email to both `addresseeA`, and `groupA` that contains `addresseeA`, and `DEFER_GROUP_PROCESSING=1` and this attribute is `No`, then the message immediately duplicates, such that `addresseeA` gets two copies, one that came directly, and one that took the deferred expansion hop through the `reprocess` channel for `groupA` to get expanded.

While disabling deferred group expansion would eliminate the duplicate, that's not a good idea if you have a lot of large groups. Using `expandlimit 1` can potentially cause unnecessary overhead on general, non-group, multi-recipient messages.

To minimize the effect of this situation, the following two solutions are best practices:

- For installations with only a few small groups, setting the default `DEFER_GROUP_PROCESSING=1`, and this attribute to `No`, gives you duplicates but also gives you two major benefits:
 - You don't have to bother running the `reprocess` channel, which makes a bit less overhead and a bit faster delivery.
 - The potential for eliminating duplicate addresses is increased.
- If your installation has many small groups and only a few large groups, then set `DEFER_GROUP_PROCESSING=0`, and this attribute to `Yes` for the few large groups.

Example

The default for mail users:

```
mailDeferProcessing: No
```

The default for mailing lists:

```
mailDeferProcessing: Yes
```

OID

TBD

mailDeliveryFileURL

Origin

iPlanet Messaging Server 5.0

Syntax

ces, single-valued

Object Classes

[inetMailGroup](#)

Definition

Fully qualified local path of file to which all messages sent to the mailing list are appended. Used in conjunction with `mailDeliveryOption: file`.

The MTA option used to override this attribute's value is `LDAP_PROGRAM_FILE`.

Example

`mailDeliveryFileURL: /home/dreamteam/mail_archive`

OID

2.16.840.1.113730.3.1.787

mailDeliveryOption

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[inetMailGroup](#), [inetMailUser](#)

Definition

Specifies delivery options for the mail recipient. One or more values are permitted on a user or group entry, supporting multiple delivery paths for inbound messages. Values will apply differently depending on whether the attribute is used in `inetMailGroup` or `inetMailUser`.

Note, that the `mailUserStatus` attribute is processed before this attribute. If `mailUserStatus` is set to hold, an internal flag is set so that when `mailDeliveryOption` is processed, the `mailUserStatus` hold overrides whatever delivery options are specified with `mailDeliveryOption`.

For users, delivery addresses are generated for each valid delivery option value.

Valid values are:

For users only (inetMailUser):

- **autoreply** – Specifies autoreply is turned on for the user. Messages on which the recipient is listed in the "To:" or "Cc:" header fields of the message are sent to the autoreply channel where an autoreply message is generated and sent to the original sender.
- **hold** – A recipient is temporarily halted from receiving messages. Note that unlike `mailUserStatus`, `hold` for this attribute does not disallow POP, IMAP and WebMail access. For this attribute, `hold` only halts delivery to the recipient's mailbox, but access is still allowed.
- **mailbox** – Deliver messages to the user's IMAP/POP store.
- **native or unix** – Deliver messages to the user's `/var/mail` store INBOX. The store is in Berkeley mailbox format. Messaging Server does not support `/var/mail` access. Users must use UNIX tools to access mail from the `/var/mail` store.

For groups only (inetMailGroup):

- **file** – Messages are appended to the file specified in the attribute `mailDeliveryFileURL`.
- **members** – Messages are sent to members of the mailing list. If missing, `default=members` is assumed.
- **members_offline** – To defer processing for this group, set the attribute to this value, and set the `option.dat` file option `DEFER_GROUP_PROCESSING` to zero (0).

Both users and groups:

These values are handled the same for both users and groups.

- **program** – Messages are delivered to a program, which is on the approved list of programs (specified in MTA's configuration). The name of the program is specified in the attribute `mailProgramdeliveryInfo`.
- **forward** – Specifies that messages will be forwarded. The forwarding address is specified in the attribute `mailForwardingAddress`. Note that when this value is set, `mailForwardingAddress` must be set to keep the mail system in sync.

The MTA option `DELIVERY_OPTIONS`, found in the `msg_svr_base/config/option.dat` file, defines how each of the previously listed values will be processed.

The MTA option used to override this attribute's value is `LDAP_DELIVERY_OPTION`.

Example

mailDeliveryOption: mailbox

OID

2.16.840.1.113730.3.1.16

mailDomainAllowedServiceAccess

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single valued

Object Classes

[mailDomain](#)

Definition

Stores access filters (rules). If no rules are specified, then domain is allowed access to all services from all clients. Rules are separated by a dollar sign (\$). The rules are evaluated in this manner:

- Access is granted if the client information matches an allow filter for that service.
- Access is denied if the client information matches a deny filter for that service.
- If no match is made with any allow or deny filters, access is granted, except in the case where there are allow filters but no deny filters. In this case, a lack of match means access is denied.

For a full explanation of access filters and an alternate way to control access through the administration console or the `config` utility, see “Configuring Client Access to POP, IMAP, and HTTP Services” in the *Sun ONE Messaging Server Administrator’s Guide*.

Rule Syntax

"+" or "-" <service_list> ":" <client_list>

+ (allow filter) means the service list services are being granted to the client list.

- (deny filter) means the services are being denied to the client list.

`service_list` is a comma separated list of services to which access is being granted or denied.

Legal service names are: `imap`, `imaps`, `pop`, `pops`, `smtp`, `smtps`, and `http`. Note that the MMP supports `imap`, `imaps`, `pop`, `pops`, and `smtp`. The backend supports `imap`, `pop`, `smtp`, and `http`.

`client_list` is a comma separated list of clients (domains) to which access is being granted or denied.

Wildcards can be substituted for the client list (domains). The following table shows the allowed wildcards and describes each of them:

Table 3-11 Wildcards

Wildcards	Meanings
ALL, *	The universal wildcard. Matches all names.
DNSSPOOFER	Matches any host whose DNS name does not match its own IP address.
KNOWN	Matches any host whose name and address are known. Use with care.
LOCAL	Matches any local host (one whose name does not contain a dot character). If your installation uses only canonical names, even local host names will contain dots and thus will not match this wildcard.
UNKNOWN	Matches any host whose name or address are unknown. Use this with care.

The following wildcards can be used for the service list: `*`, `ALL`.

Except Operator

The access control system supports a single operator, `EXCEPT`. You can use the `EXCEPT` operator to create exceptions to the patterns found in a rule's service list and client list. `EXCEPT` clauses can be nested. If there are multiple `EXCEPT` clauses in a rule, they are evaluated right to left.

The `EXCEPT` format is:

```
list 1 EXCEPT list 2
```

A list is a comma separated list of services or clients.

Example

This example shows a single rule with multiple services and a single wildcard for the client list.

```
mailDomainAllowedServiceAccess: +imap,pop,http:*
```

This example shows multiple rules, but each rule is simplified to have only one service name and uses wildcards for the client list.

```
mailDomainAllowedServiceAccess: +imap:ALL$+pop:ALL$+http:ALL
```

The second example is probably the most commonly used in Messaging Server LDIF files.

An example of a rule with an EXCEPT operator is:

```
mailDomainAllowedServiceAccess: -ALL:ALL EXCEPT server1.sesta.com
```

This example denies access to all services for all clients except those on the host machine `server1.sesta.com`.

OID

2.16.840.1.113730.3.1.764

mailDomainCatchallAddress

Origin

iPlanet Messaging Server 5.2

Syntax

cis, single-valued (RFC 822 mailbox)

Object Classes

[mailDomain](#)

Definition

Specifies an address to be substituted for any address in the domain that doesn't match any user or group in the domain.

The MTA option used to override this attribute's value is

`LDAP_DOMAIN_ATTR_CATCHALL_ADDRESS`.

Example

OID

TBD

mailDomainConversionTag

Origin

iPlanet Messaging Server 5.2

Syntax

cis, multi-valued (ASCII string)

Object Classes

[mailDomain](#)

Definition

One or more conversion tags attached to messages to any user in the domain. Tag specific conversion actions are specified in the MTA configuration.

The MTA option used to override this attribute's value is

LDAP_DOMAIN_ATTR_CONVERSION_TAG.

Example**OID**

TBD

mailDomainDiskQuota

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes

[mailDomain](#)

Definition

Used for internal monitoring only. Disk quota, for all users in the domain, in bytes. This is used in quota reporting tools and not used for enforcing domain wide quota restrictions.

Example

mailDomainDiskQuota: 50000000000

OID

2.16.840.1.113730.3.1.766

mailDomainMsgMaxBlocks

Origin

iPlanet Messaging Server 5.2

Syntax

int, single-valued

Object Classes

mailDomain

Definition

Imposes a size limit in units of MTA blocks on all messages sent to addresses in this domain. This limit doesn't apply to messages sent by users from this domain.

The value of this attribute is overridden by the value of [mailMsgMaxBlocks](#), if set.

The MTA option used to override this attribute's value is

LDAP_DOMAIN_ATTR_BLOCKLIMIT.

Example

OID

TBD

mailDomainMsgQuota

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes

[mailDomain](#)

Definition

Quota of number of messages permitted for all users in this domain. This is used in quota reporting tools and not for enforcing domain wide quota restrictions.

Example

mailDomainMsgQuota: 2000000

OID

2.16.840.1.113730.3.1.767

mailDomainReportAddress

Origin

iPlanet Messaging Server 5.2

Syntax

cis, single-valued (RFC 822 mailbox)

Object Classes

[mailDomain](#)

Definition

This value is used as the header From: address in DSNs reporting problems associated with recipient addresses in the domain. It is also used when reporting problems to users within the domain regarding errors associated with nonlocal addresses.

If this attribute is not set, the reporting address will default to “postmaster@domain.”

The MTA option used to override this attribute’s value is
LDAP_DOMAIN_ATTR_REPORT_ADDRESS.

Example**OID**

TBD

mailDomainSieveRuleSource

Origin

iPlanet Messaging Server 5.2

Syntax

cis, single-valued (RFC 3028 sieve filter)

Object Classes

[mailDomain](#)

Definition

SIEVE filters are not supported by iPlanet Delegated Administrator.

SIEVE filter for all users in the domain. There are two possible forms for the value of this attribute: a single value that contains the complete sieve script (RFC 3028 compliant), and multiple values, with each value containing a piece of the sieve script (not RFC 3028 compliant).

A script has the following form:

```
require ["fileinto", "reject"];
# $Rule Info: Order=(1-infinity, or 0 for disabled)
Template=(template-name) Name=(rule name)
if header :is "Sender" "owner-ietf-mta-filters@imc.org"
{ fileinto "filter"; # move to "filter" folder }
if header :is "Subject" "SPAM!"
{ delete }
```

Multi-valued Form

Multiple SIEVE scripts per user can be stored in LDAP. To enable the user interface to handle several smaller rules scripts, rather than one script containing all the domain's rules, this attribute takes multiple values (that is, multiple rules). The server looks at every rule in mailSieveRuleSource.

To provide ordering and possible user interface editing information, there is an optional SIEVE comment line in each rule. This line has the following format:

```
# $Rule Info: Order=(1-infinity, or 0 for disabled)
```


All rules that have a `Rule Info` line will be processed first by the Messaging Server. If `Order=0`, then this rule is not used in the SIEVE evaluation. Otherwise, the rules are processed in the order provided (1 having highest priority). To accommodate SIEVE rules that might not have been entered using the `Rule Info` extension, any other rules found are run by the server, in order received from LDAP after all rules with corresponding order values have been processed.

MTA Override Option

The MTA option that overrides this attribute's value is `LDAP_DOMAIN_ATTR_FILTER`.

Example

The following example is correctly formed, but Messaging Server ignores `discard` and `reject` text, and does not send a reject or discard reply message.

```
mailSieveRuleSource:
require ["fileinto", "reject", "redirect", "discard"]
if header :contains "Subject" "New Rules Suggestion"
    {redirect "rules@sesta.com" # Forward message }
if header :contains "Sender" "porn.com"
    {discard text:
Your message has been rejected. Please remove this address from your
mailing list.      # Reject message, send reply message.}
if size :over 1M
    { reject text:
Please do not send large attachments.
Put your file on a server and send the URL.
Thank you. # Discard message, send reply message.}
if header :contains "Sender" "domainadministrator@sesta.com"
    { fileinto complaints.refs # File message}
```

OID

TBD

mailDomainStatus

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

mailDomain

Definition

Current status of the mail domain. Can be one of the following values: active, inactive, deleted, or hold. This attribute is the mail service domain status. Missing value implies status is active. An illegal value is treated as inactive.

The following table lists the status values:

Table 3-12 Status Values

Value	Description
active	Mail service is marked as active for all users in this domain and all users in the domain that are marked active (see inetUserStatus and mailUserStatus for more information). However, any restrictions specified in mailAllowedServiceAccess and mailDomainAllowedServiceAccess still apply.
inactive	Mail service for all users in the domain is marked inactive. All user login attempts are rejected and messages sent to them get transient failure messages.
deleted	Mail domain is marked as deleted and will be removed during cleanup by the purge utility after the grace period is over. Mailboxes and user's mail service object classes are included in cleanup.
hold	Messages sent to all users in the domain are redirected to the hold channel. This value is typically used when users in the domain are being moved from one server to another without having to bounce messages back to the sender during the move. In this state, mailboxes can be moved without fear of any lost messages as all incoming messages are sent to the hold channel. Once the move is complete and the state has been changed from hold to active the messages are drained from the hold channel and sent to the MTAs where the user mailboxes now reside.
overquota	The MTA will not accept new messages for any users in the domain until this value is changed back to active.

There are four status attributes that mail services look at and which are evaluated in this order: inetDomainStatus, mailDomainStatus, inetUserStatus, and mailUserStatus. The rule is: the first of these attributes that is set to something other than active takes precedence over all the others.

The MTA option that overrides this attribute's values is LDAP_DOMAIN_ATTR_STATUS.

Example

mailDomainStatus: active

OID

2.16.840.1.113730.3.1.770

mailDomainWelcomeMessage

Origin

Sun ONE Messaging Server 6.0

Syntax

cis, single-valued

Object Classes

[mailDomain](#)

Definition

Welcome message sent to new users added to this domain. '\$\$' is a carriage return. BNF syntax of this attribute is:

```
value:: <subjectline>'$' [<opt_headers>] '$$' <body>
subjectline:: 'Subject:' [<TEXT>]
opt_headers:: <header_line>'$' [<opt_headers>]
header_line:: <header_name> ':' <TEXT>
header_name:: <TEXT>
body:: [<lines>]
lines:: <line>'$' [<lines>]
line:: <TEXT>
```

Example

```
mailDomainWelcomeMessage: Subject: Welcome!!$X-Endorsement: We're
good. $$Welcome to the mail system.
```

OID

2.16.840.1.113730.3.1.765

mailEquivalentAddress

Origin

iPlanet Messaging Server 5.2

Syntax

cis, multi-valued (RFC 822 addr-spec)

Object Classes

[inetMailGroup](#), [inetMailUser](#)

Definition

Equivalent to [mailAlternateAddress](#) in regard to mail routing, except with this attribute, the header doesn't get rewritten.

Note that `mailEquivalentAddress` is searched for when the system is deciding where to deliver messages, but it is not one of the attributes searched for when doing `REVERSE_URL` address reversal.

This attribute works only for direct LDAP mode, not with the deprecated `imsimta` `dirsync` option.

Example

```
mailEquivalentAddress: jdoe@sesta.com
```

```
mailEquivalentAddress: @sesta.com (catchall domain address)
```

OID

TBD

mailFolderName

Origin

Sun ONE Messaging Server 6.0

Syntax

cis, single-valued

Object Classes

[mailDomain](#), [mailPublicFolder](#)

Definition

This attribute specifies the name of a public folder.

Example

```
mailFolderName: Announcements
```

OID

mailForwardingAddress

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[inetMailUser](#)

Definition

This attribute stores one or more forwarding addresses for inbound messages. Addresses are specified in RFC 822 format. Messages are forwarded to the listed address when `mailDeliveryOption: forward` is set.

Note that both `mailDeiveryOption` and this attribute must be set in order to keep the mail system in sync.

Example

```
mailForwardingAddress: kokomo@sesta.com
```

OID

2.16.840.1.113730.3.1.17

mailHost

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetLocalMailRecipient](#)

Definition

For a user or group entry, the fully qualified host name of the MTA that is the final destination of messages sent to this recipient. To be deemed local, the user entry must have this attribute, and it must match either the `local.hostname` configuration attribute, or one of the names specified by the `local.imta.hostnamealiases` configuration attribute. Otherwise, a new source routed address is generated in the form: `@mailhost:user@domain` and will be processed through the rewrite rules.

If a user entry does not have this attribute, the generated address will use the `mailRoutingSmartHost` hostname associated with the domain `@smarthost:user@domain`. If the domain has no `mailRoutingSmartHost` attribute, the address is discarded and a 5xx error is reported.

If a group entry does not have this attribute, the group is processed locally.

The MTA option that overrides this attribute's value is `LDAP_MAILHOST`.

Example

```
mailHost: mail.siroe.com
```

OID

```
2.16.840.1.113730.3.1.18
```

mailMessageStore

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

`inetMailUser`

Definition

Specifies the message store partition name for the user. The mapping between the partition name and the file system location of the store is kept in the message store configuration. If not specified, the default store partition specified in the server configuration is used.

Example

```
mailMessageStore: secondary
```

OID
2.16.840.1.113730.3.1.19

mailMsgMaxBlocks

Origin
iPlanet Messaging Server 5.2

Syntax
int, single-valued

Object Classes
inetMailGroup, inetMailUser

Definition
The size in units of MTA blocks of the largest message that can be sent to this user or group. The limit doesn't apply to messages sent by the user.

If this attribute is set, it overrides the value of [mailDomainMsgMaxBlocks](#).

The MTA option that overrides the attribute's value is LDAP_BLOCKLIMIT.

Example

OID
TBD

mailMsgQuota

Origin
iPlanet Messaging Server 5.0

Syntax
int, single-valued

Object Classes
[inetMailUser](#)

Definition

Maximum number of messages permitted for a user is set with mailMsgQuota. This is a cumulative count for all folders in the store. Table 3-13 shows the special values and their meanings:

Table 3-13 mailMsgQuota Special Values

Value	Meaning
0	No mail messages allowed
-1	No limit on number of messages allowed
-2	Use system default quota (use of this value is being deprecated)

If this attribute is missing, the system default quota is used.

During server configuration, quota enforcement must be turned on for mailMsgQuota to take effect. Both soft and hard quotas can be set (See *Sun ONE Message Server Administrator's Guide*).

The MTA option override is LDAP_MESSAGE_QUOTA.

Example

mailMsgQuota: 2000

OID

2.16.840.1.113730.3.1.774

mailProgramDeliveryInfo

Origin

iPlanet Messaging Server 5.0

Syntax

ces, multi-valued

Object Classes

inetMailGroup, inetMailUser

Definition

Specifies one or more programs used for program delivery. These programs have to be on the approved list of programs that the messaging server is permitted to execute for a domain. The attribute value specifies a reference to a program. That reference is resolved from the approved list of programs. The resolved reference also provides the program parameters and execution permissions. Used in conjunction with the `mailDeliveryOption: program`.

The value of this attribute should be used as the value for the method name (-m value) when running `imsimta program`.

The program approval process is documented further in the *Sun ONE Messaging Server Administrator's Guide*.

The MTA option used to name a different attribute for this function is `LDAP_PROGRAM_INFO`.

Example

```
mailProgramDeliveryInfo: procmail
```

OID

2.16.840.1.113730.3.1.20

mailPublicFolderDefaultRights

Origin

Sun ONE Messaging Server 6.0

Syntax

cis, multi-valued

Object Classes

`mailPublicFolder`

Definition

Specifies the access control rights granted for this public folder. Each value of this attribute consists of two parts separated by a space. The two parts are: an identifier, as specified in RFC 2086, and a list of access rights (mod_rights) as follows in [Table 3-14](#).

Table 3-14 Access Rights for a Public Folder

Allowed Characters	Name	Actions Permitted
l	lookup	Mailbox is visible to LIST/LSUB commands.
r	read	SELECT the mailbox, perform CHECK, FETCH, PARTIAL, SEARCH, COPY from mailbox.
s	seen	Keep seen/unseen information across sessions. (STORE SEEN flag)
w	write	STORE flags other than SEEN and DELETED.
i	insert	Perform APPEND, COPY into mailbox.
p	post	Send mail to submission address for mailbox (not enforced by IMAP 4 itself).
c	create	CREATE new sub-mailboxes in any implementation-defined hierarchy.
d	delete	STORE DELETED flag, perform EXPUNGE.
a	administer	Perform SETACL.

Sun ONE Messaging Server’s IMAP ACL implementation also defines the following new identifier:

`anyone@domain`

where *domain* is a valid domain.

If the attribute is missing, the default rights specified in the mailPublicFolderDefaultRights attribute from the mailDomain object class will be applied. If mailDomain does not contain this attribute, the following default ACL is set when a public folder is first created:

`anyone@domain lrs`

where *domain* is a valid domain.

Group identifiers start with the prefix “group=”. Do not put the group identifier prefix on a userid. The message store’s user creation code checks for this.

Examples

```
mailPublicFolderDefaultRights: anyone@sesta.com lrs
```

```
mailPublicFolderDefaultRights: group: sales@sesta.com lrs
```

```
mailPublicFolderDefaultRights: john@sesta.com lrswid
```

OID

mailQuota

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes

[inetMailUser](#), [mailDomain](#)

Definition

Specifies, in bytes, the amount of disk space allowed for the user's mailbox. The numeric portion of the value is limited to 4294966272. For values approaching or exceeding four gigabytes, use the G suffix instead of specifying the full value as a number. Other valid suffixes are: K for kilobytes, M for megabytes, and G for gigabytes.

[Table 3-15](#) shows the special values for this attribute.

Table 3-15 mailQuota Special Values

Value	Meaning
0	No space allowed for user's mailbox
-1	No limit on space usage allowed
-2	Use system default quota (use of this value is being deprecated)

The quota value is limited to 4096G because the message store uses a 32 bit unsigned integer to store the quota value.

If the attribute is not specified, the system default quota is used. The system default is specified in the server configuration parameter `store.defaultmailboxquota`. Setting the configuration parameter `store.quotaenforcement` to 'on' causes the message store to enforce the quota.

NOTE `LDAP_DISK_QUOTA` is the MTA option used to specify a different attribute name for this function.

Example

`mailQuota: 4G`

or for the system default quota:

`mailQuota:`

OID

2.16.840.1.113730.3.1.21

mailRejectText

Origin

Sun ONE Messaging Server 5.2

Syntax

ces, multi-valued

Object Classes

[inetMailGroup](#)

Definition

The first line of text stored in the first value of this attribute is saved. This text is returned if any of the authentication attributes cause the message to be rejected. Since text can appear in SMTP responses, the value is limited to US-ASCII characters in order to comply with messaging standards.

NOTE `LDAP_REJECT_TEXT` is the MTA option used to specify a different attribute name for this function.

Example

OID
TBD

mailRoutingAddress

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single valued

Object Classes

[inetLocalMailRecipient](#)

Definition

Used together with [mailHost](#) to determine whether or not the address should be acted upon at this time or forwarded to another system.

NOTE

`LDAP_ROUTING_ADDRESS` is the MTA option used to specify a different attribute name for this function.

Example

OID
2.16.840.1.113730.3.1.24

mailRoutingHosts

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[mailDomain](#)

Definition

Fully qualified host name of the MTA responsible for making routing decisions for users in this (and all contained) domain(s). Unspecified attribute implies all MTAs must route messages for the users/groups of this (and contained) domain(s).

When a domain is found to be nonlocal, the use of this attribute depends on the value of the MTA option `ROUTE_TO_ROUTING_HOST`:

- If the value is zero (0), which is the default setting, the attribute was checked as part of the `$*` rewrite rule. With a nonlocal domain, the `$*` rewrite rule fails and no further use is made of this attribute's values. The remaining rewrite rules determine the handling of the domain.
- If the value of the option is one (1), then the first value of this attribute that the MTA receives is installed as the source route in the address. And, all addresses associated with the domain are routed to that host.

Since this attribute is multi-valued and the first value the MTA “sees” will be chosen when the option is set to 1, it might be tempting to assume that you can direct the order in which these mail hosts will be used; that is, you might assume you can do a sort of load balancing by ordering the various values of this attribute. But, LDAP does not guarantee that attribute value ordering is preserved, so the first value seen by the MTA might be any of the attribute's values, not necessarily the first one in the LDAP entry.

You can implement load balancing with a set of MX records for each of the routing host names. Do not attempt to do it with the ordering of this attribute's values.

`LDAP_DOMAIN_AATR_ROUTING_HOSTS` is the MTA option used to specify a different attribute name for this function.

Example

```
mailRoutingHosts: mail.siroe.com
```

OID

2.16.840.1.113730.3.1.759

mailRoutingSmartHost

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes[mailDomain](#)**Definition**

Fully qualified host name, or domain-literal IP address, of a mail server responsible for handling mail for users not found in the local directory. Messages sent to users not found in the messaging server's directory are forwarded to the mail server specified in this attribute. This is useful when making a transition from one mail system to another and all users have not yet been moved over to the messaging server directory. An empty or missing attribute implies the local MTA is responsible for routing and delivering all messages for users in that domain.

This attribute is used by the system only if the domain it cares about is listed in the attribute, otherwise, it is ignored.

NOTE

LDAP_DOMAIN_ATTR_SMARTHOST is the MTA option used to specify a different attribute name for this function.

Example

```
mailRoutingSmartHost: mail.siroe.com
```

```
mailRoutingSmartHost: 129.148.12.141
```

OID

```
2.16.840.1.113730.3.1.760
```

mailSieveRuleSource

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes[inetMailUser](#)**Definition**

SIEVE filters are not supported with iPlanet Delegated Administrator for Messaging. Use this with Sun ONE LDAP Schema v. 2 and Sun ONE Identity Server.

The attribute contains a [SIEVE](#) rule (RFC 3028 compliant) used to create a message filter script for a user entry. This attribute can be either single-valued, with the rule containing the complete SIEVE script, or multi-valued, with each rule containing an independently valid piece of the SIEVE script. When there are multiple values, the Web filter construction interface combines the rules into a single SIEVE script using an ordering parameter (Order) found in a #Rule Info: comment.

NOTE Note that when the value of Order is a negative number, the value is ignored, and the rule is processed with other unordered SIEVE rules for this entry, but when the value of Order is zero, the rule is disabled and not processed at all.

The script is applied when a message is ready to be enqueued to the delivery channel. Though the SIEVE script is created while the MTA is expanding aliases, it is not used until after the resulting delivery addresses have been expanded and are being sent to the `ims-ms`, `native`, `autoreply` or `pipe` channels.

A script has the following form:

```
require ["fileinto", "reject"];
# $Rule Info: Order=(1-infinity, or 0 for disabled)
Template=(template-name) Name=(rule name)
if header :is "Sender" "owner-ietf-mta-filters@imc.org"
{ fileinto "filter"; # move to "filter" folder }
if header :is "Subject" "SPAM!"
{ delete }
```

MTA Option

The MTA option used to name a different attribute for this function is `LDAP_FILTER`.

Example

```
mailSieveRuleSource:
require ["fileinto", "reject", "redirect", "discard"]
if header :contains "Subject" "New Rules Suggestion"
    { redirect "rules@sesta.com" # Forward message }
if header :contains "Sender" "porn.com"
    { discard text:
Your message has been rejected. Please remove this address from your
mailing list.      # Reject message, send reply message.}
if size :over 1M
    { reject text:
Please do not send me large attachments.
```



```
Put your file on a server and send me the URL.
Thank you. # Discard message, send reply message.}
if header :contains "Sender" "barkley@sesta.com"
    { fileinto complaints.refs # File message}
```

OID

2.16.840.1.113730.3.1.775

mailSMTPSubmitChannel

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes[inetMailUser](#)**Definition**

Most commonly, this attribute is a factor involved in setting up guaranteed message delivery, or in setting up other special classes of service. When defined, this attribute tells the MTA to consider the channel named by this attribute to be the effective submission channel, if the SMTP AUTH is successful.

Example

mailSMTPSubmitChannel: tcp_tas

OID

2.16.840.1.113730.3.1.776

mailUserStatus

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

inetMailUser

Definition

Stores one of the following mail user status (missing value implies status is inactive):

Table 3-16 Mail User Status

Status Value	Description
active	Normal state. If <code>inetUserStatus</code> is also active, then mail is processed as per the values stored in other user attributes (such as <code>mailDeliveryOption</code> , <code>mailSieveRuleSource</code> , and so on). If not set to <code>active</code> , the status from <code>inetUserStatus</code> takes precedence. Other status attributes taken into consideration are <code>inetDomainStatus</code> and <code>mailDomainStatus</code> . If the combination of <code>inetDomainStatus</code> and <code>mailDomainStatus</code> permits mail delivery and access for the domain, the user state is determined from <code>inetUserStatus</code> and <code>mailUserStatus</code> .
inactive	The user's mail account is inactive. A transient failure is returned to the sending MTA.
deleted	User's mail account is marked deleted. A permanent failure is returned to the sending MTA and the user's mail account is a candidate for cleanup by the purge utility. User access to mailbox is blocked.
hold	User's mail is sent to the hold queue and access to the mailbox over IMAP, POP, and HTTP is disallowed. MTA and Message Access Servers on the store server must comply with this requirement. This setting overrides any other <code>mailDeliveryOption</code> settings.
overquota	The MTA will not deliver mail to a mailbox with this status.

Missing value implies status is `active`. An illegal value is treated as `inactive`.

There are four status attributes that mail services look at and which are evaluated in this order: `inetDomainStatus`, `mailDomainStatus`, `inetUserStatus`, and `mailUserStatus`. The rule is: the first of these attributes that is set to something other than `active` takes precedence over all the others.

NOTE `LDAP_USER_STATUS` is the MTA option used to specify a different attribute name for this function.

Example

`mailUserStatus: active`

OID

2.16.840.1.113730.3.1.778

maxPabEntries

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes

[ipUser](#)

Definition

Specifies the maximum number of personal address book entries users are permitted to have in their personal address book store. A value of -1 implies there is no limit. If this attribute is not present then the system default specified in the personal address book configuration is used.

Example

```
maxPabEntries: 1000
```

OID

2.16.840.1.113730.3.1.705

memberOf

Origin

iPlanet Messaging Server 5.0, deprecated in Sun ONE Messaging Server 6.0 for [inetUser](#). Sun ONE Identity Server

Syntax

dn, multi-valued

Object Classes

[inetAdmin](#), [inetUser](#)

Definition

For Sun ONE LDAP Schema v.2, this attribute decorates [inetAdmin](#), and specifies the DN of an assignable dynamic group to which a user belongs. It is used as the default well-known filtered attribute used in conjunction with [mgrpDeliverTo](#) to search for assignable dynamic group members.

This attribute is deprecated for `inetUser` in Sun ONE Messaging Server 6.0 and is likely to be removed from the `inetUser` object class in future versions of Sun ONE schema.

For Sun ONE LDAP Schema v.1, this attribute specifies the DN of a mailing list to which a user belongs, indicating static group membership as a backpointer.

Example

`memberOf: cn=Administrators,ou=groups o=sesta.com,o=basedn`

OID

1.2.840.113556.1.2.102

memberOfPAB

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[pabPerson](#), [pabGroup](#)

Definition

The unique name (`un`) of the personal address book(s) in which this entry belongs.

Example

`memberOfPAB:addressbook122FA7`

OID

2.16.840.1.113730.3.1.718

memberOfPABGroup

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes[pabPerson](#)**Definition**

Unique name of the personal group(s) in which this user belongs.

Example

memberOfPabGroup:testgroup15577F2D

OID

2.16.840.1.113730.3.1.719

memberURL

Origin

iPlanet Messaging Server 5.2

Syntax

ces, multi-valued

Object Classes[inetMailGroup](#)**Definition**

A list of URLs, which, when expanded, provides a list of mailing list member addresses.

This is the preferred way to specify a dynamic mailing list. Alternately, you can use [mgrpDeliverTo](#).

The MTA option used to override this attribute's value is LDAP_GROUP_URL2.

Example

memberURL:ldap://cn=jdoes, o=sesta.com

OID

2.16.840.1.113730.3.1.198

mgrpAddHeader

Origin

Netscape Messaging Server

Syntax

ces, multi-valued

Object Classes

[inetMailGroup](#)

Definition

Each attribute value specifies a header field that is to be added to the message header if it is present.

For the MTA, the values of these attributes are headers, which are used to set header-trimming ADD options.

NOTE	LDAP_ADD_HEADER is the MTA option used to specify a different attribute name for this function.
-------------	---

Example

mgrpAddHeader:Reply-To: thisgroup@sesta.com

OID

2.16.840.1.113730.3.1.781

mgrpAllowedBroadcaster

Origin

iPlanet Messaging Server 5.0

Syntax

ces, multi-valued

Object Classes

[inetMailGroup](#)

Definition

Identifies mail users allowed to send messages to the mail group. The Messaging Server expects this attribute to contain either a distinguished name or an RFC822address using an LDAP URI or a mailto address (see example). If a distinguished name is used, it must represent a mailable entry or entries of type group or groupOfUniqueNames. (That is, the group entry must contain an email address in one of the following attributes: mail, mailAlternateAddress, mailEquivalentAddress.) If no instances of this attribute exist on the inetMailGroup entry, then there are no restrictions on who can send messages to the mail group unless the mgrpAllowedDomain and mgrpDisallowedDomain attributes are used.

If multi-valued, each URL is expanded into a list of addresses and each address is checked against the current envelope “from” address. The message is allowed if there is a match.

To specify that only the members of this group can post to the group, use the group name as the value of the attribute.

If none of the attribute values is a valid URL, or none of the members of the group specified in the attribute value have a valid URL, then the message will bounce.

NOTE

LDAP_AUTH_URL is the MTA option used to specify a different attribute name for this function.

Example

```
mgrpAllowedBroadcaster: ldap:///uid=bjensen,o=siroe.com
```

```
mgrpAllowedBroadcaster:mailto:group1@siroe.com
```

OID

```
2.16.840.1.113730.3.1.22
```

mgrpAllowedDomain

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes[inetMailGroup](#)**Definition**

Identifies domains (including subdomains) from which users are allowed to send messages to the mail group. If no instances of this attribute exist on the `inetMailGroup` entry, then there are no restrictions on who can send messages to the mail group unless the `mgrpAllowedBroadcaster`, `mgrpDisallowedBroadcaster`, and `mgrpDisallowedDomain` attributes are used.

NOTE

`LDAP_AUTH_DOMAIN` is the MTA option used to specify a different attribute name for this function.

Example

```
mgrpAllowedDomain:siroe.com
```

This matches any user sending from `*.siroe.com`.

OID

```
2.16.840.1.113730.3.1.23
```

mgrpAuthPassword

Origin

iPlanet Messaging Server 5.0

Syntax

ces, single-valued

Object Classes[inetMailGroup](#)**Definition**

Specifies a password needed to post to the list.

The presence of this attribute forces a reprocessing pass. As the message is enqueued to the reprocessing channel, the password is taken from the header and placed in the envelope. Then, while reprocessing, the password is taken from the envelope and checked against this attribute. Only passwords that are actually used are removed from the header field.

This allows for routing to the moderator in the event of a password failure.

NOTE `LDAP_AUTH_PASSWORD` is the MTA option used to specify a different attribute name for this function.

Example

OID
2.16.840.1.113730.3.1.783

mgrpBroadcasterPolicy

Origin
iPlanet Messaging Server 5.0

Syntax
cis, single-valued

Object Classes
[inetMailGroup](#)

Definition
Policy for determining allowed broadcaster. It specifies the level of authentication required to access the list of broadcaster addresses. The allowed values are:

- `AUTH_REQ`, `SMTP_AUTH_REQUIRED`
In order to post to the list, the sender must be authenticated using the SMTP `AUTH` command.
- `PASSWORD_REQUIRED`, `PASSWD_REQUIRED`, `PASSWD_REQ`
All values mean the password to the broadcaster list, specified by the `mgrpAuthPassword` attribute, must appear in an `Approved:` header field in the message.
- `NO_REQUIREMENTS`
This value means no special requirements apply.

NOTE `LDAP_AUTH_POLICY` is the MTA option used to specify a different attribute name for this function.

Example

`mgrpBroadcasterPolicy:AUTH_REQ`

OID

2.16.840.1.113730.3.1.3

mgrpDeliverTo

Origin

iPlanet Messaging Server 5.0

Syntax

ces, multi-valued

Object Classes

[inetMailGroup](#)

Definition

Used as an alternative method of specifying mail group membership. This can be used to create a dynamic mailing list.

The preferred attribute to use for specifying dynamic mail group is [memberURL](#).

The values of this attribute are a list of URLs, which, when expanded, provides mailing list member addresses.

Messaging Server expects this attribute to contain an LDAP URL using the format described in RFC 1959. Any entries returned by the resulting LDAP search are members of the mailing group. There is a hard limit on the length of the search filter of 1024 bytes.

NOTE `LDAP_GROUP_URL1` is the MTA option used to specify a different attribute name for this function.

Example

This example returns all users in the United States Accounting department for Sesta corporation.

```
mgrpDeliverTo: ldap:///ou=Accounting,o=Sesta,c=US??sub?
(&(objectClass=inetMailUser)(objectClass=inetOrgPerson))
```

OID

2.16.840.1.113730.3.1.25

mgrpDisallowedBroadcaster

Origin

iPlanet Messaging Server 5.0

Syntax

ces, multi-valued

Object Classes

[inetMailGroup](#)

Definition

Identifies mail users not allowed to send messages to the mail group. If no instances of this attribute exist on the `inetMailGroup` entry, then there are no restrictions on who can send messages to the mail group unless the `mgrpAllowedDomain` and `mgrpDisallowedDomain` attributes are used.

Messaging Server expects this attribute to contain either a distinguished name or an `RFC822address`. If a distinguished name is used, it must represent a mailable entry or entries of type `group` or `groupOfUniqueNames`. (That is, the group entry must contain an email address in one of the following attributes: `mail`, `mailAlternateAddress`, `mailEquivalentAddress`.) The distinguished name must be represented in the form of an LDAP URL as described in RFC 1959.

If multi-valued, each URL is expanded into a list of addresses and each address is checked against the current envelope “from” address. The message is disallowed if there is a match.

NOTE

`LDAP_CANT_URL` is the MTA option used to specify a different attribute name for this function.

Example

```
mgrpDisallowedBroadcaster: ldap:///uid=bjensen, o=sesta.com
```

```
mgrpDisallowedBroadcaster: mailto:sys50@sesta.com
```

OID

```
2.16.840.1.113730.3.1.785
```

mgrpDisallowedDomain

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[inetMailGroup](#)

Definition

Identifies domains from which users are not allowed to send messages to the mail group. This attribute is a private extension used by Messaging Server to manage mailing lists. If this attribute exists, then messages from listed domains are rejected. If no instances of this attribute exist on the [inetMailGroup](#) entry, then there are no restrictions on who can send messages to the mail group unless the [mgrpAllowedBroadcaster](#), [mgrpDisallowedBroadcaster](#), and [mgrpAllowedDomain](#) attributes are used.

NOTE

LDAP_CANT_DOMAIN is the MTA option used to specify a different attribute name for this function.

Example

```
mgrpDisallowedDomain:sesta.com
```

OID

```
2.16.840.1.113730.3.1.784
```

mgrpErrorsTo

Origin

iPlanet Messaging Server 5.0

Syntax

ces, single-valued

Object Classes

[inetMailGroup](#)

Definition

Recipient of error messages generated when messages are submitted to this list. Recipient's address can be specified using the `mailto` syntax, which includes an RFC 822 email address preceded by the keyword "mailto:" or simply an RFC 822 email address. Also supports LDAP URL syntax. However, if an LDAP URL is used, it must be one that produces a single address.

The envelope originator (`MAIL FROM`) address is set to the value of this attribute.

NOTE

`LDAP_ERRORS_TO` is the MTA option used to specify a different attribute name for this function.

Examples:

Example 1: `mgrpErrorsTo:mailto:jordan@siroe.com`

Example 2: `mgrpErrorsTo:`

`ldap:///uid=ofanning,ou=people,o=siroe.com,o=isp`

OID

2.16.840.1.113730.3.1.26

mgrpModerator

Origin

iPlanet Messaging Server 5.0

Syntax

ces, multi-valued

Object Classes[inetMailGroup](#)**Definition**

LDAP URI or `mailto` URL identifying the moderators allowed to submit messages to this list. Only those messages that are submitted by the moderator are sent to the members of this list. Messages submitted by others are forwarded to the moderators for approval and resubmitting.

The URLs given as the value of this attribute are expanded into a series of addresses, and then compared with the envelope “from” address. If there is a match, group processing continues. If there is no match, the value of this attribute becomes the group URL, any list of RFC 822 addresses or DN's associated with the group is cleared, the delivery options for the group are set to “members,” and there is no further group processing for the failed URL (subsequent group attributes are ignored).

NOTE

`LDAP_MODERATOR_URL` is the MTA option used to specify a different attribute name for this function.

Example

```
mgrpModerator: mailto:jordan@sesta.com
```

OID

2.16.840.1.113730.3.1.33

mgrpMsgMaxSize

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes[inetMailGroup](#)**Definition**

Maximum message size in bytes that can be sent to the group. Messaging Server expects zero or one instance of this attribute to exist for every `mailGroup` entry. If no entry exists, then no size limit is imposed on mail to the group.

This attribute is obsolete, but still supported for backwards compatibility. Use `mailMsgMaxBlocks` instead.

NOTE `LDAP_ATTR_MAXIMUM_MESSAGE_SIZE` is the MTA option used to specify a different attribute name for this function.

Example

`mgrpMsgMaxSize:8000`

OID

2.16.840.1.113730.3.1.3

mgrpMsgPrefixText

Origin

Not implemented.

Syntax

UTF-8 text, single-valued

Object Classes

[inetMailGroup](#)

Definition

Specifies the text to be added to the beginning of the message text. You must supply the formatting. That is, you must insert CRLF where they belong in the text.

NOTE `LDAP_PREFIX_TEXT` is the MTA option used to specify a different attribute name for this function.

Example

OID

TBD

mgrpMsgRejectAction

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailGroup](#)

Definition

Identifies the action to be taken when a email sent to a mail group is rejected. The Messaging Server may reject mail for the following reasons:

- It is received from an unauthorized domain (as defined by the `mgrpAllowedDomain` attribute).
- It is received from a mail address that is not a member of the `mgrpAllowedBroadcaster` attribute.
- It is larger than the size permitted on `mgrpMsgMaxSize`.

This attribute takes two values: `reply` and `toModerator`:

`reply` – The system produces an SMTP error, which is also the default if the attribute is not set. The text of the failure notice is stored in the [mgrpMsgRejectText](#) attribute.

`toModerator` – The mail is forwarded to the moderator for processing. The moderator is identified by the [mgrpModerator](#) attribute.

NOTE `LDAP_REJECT_ACTION` is the MTA option used to specify a different attribute name for this function.

Example

```
mgrpMsgRejectAction: reply
```

OID

2.16.840.1.113730.3.1.28

mgrpMsgRejectText

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailGroup](#)

Definition

Specifies the error text to use in the event of a group access failure. Because this text may appear in SMTP responses, this restricts the text to a single line of US-ASCII. This is implemented by reading only the first line of text in this attribute and using it only if it contains no 8-bit characters. (This is a limitation of the SMTP protocol.)

Example**OID**

2.16.840.1.113730.3.1.29

mgrpMsgSuffixText

Origin

Not implemented.

Syntax

UTF-8 text, single valued

Object Classes

[inetMailGroup](#)

Definition

Specifies the text to be appended to the text message. You must supply the formatting. That is, you must insert any CRLFs (carriage return, line feeds) that belong in the text.

NOTE

LDAP_SUFFIX_TEXT is the MTA option used to specify a different attribute name for this function.

Example

OID

TBD

mgrpNoDuplicateChecks

Origin

iPlanet Messaging Server 5.0, not implemented going forward for iPlanet Messaging Server 5.2

Syntax

cis, single-valued

Object Classes

[inetMailGroup](#)

Definition

This attribute is no longer supported. Duplicate checking is controlled by characteristics of the lists themselves. Some lists combine and some lists don't.

Old definition: Prevents Messaging Server from checking for duplicate delivery to members of the mail group. Prevents multiple deliveries if a user is on multiple lists. `No` means the system checks for duplicate delivery. `Yes` means the system does not check for duplicate delivery.

Example

```
mgrpNoDuplicateChecks: yes
```

OID

2.16.840.1.113730.3.1.789

mgrpRemoveHeader

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes[inetMailGroup](#)**Definition**

Each attribute value specifies a header field that is to be removed from the message header, if present.

Turns the headers specified into header trimming `MAXLINES=-1` options.

NOTE

`LDAP_REMOVE_HEADER` is the MTA option used to specify a different attribute name for this function.

Example**OID**

2.16.840.1.113730.3.1.801

mgrpRequestTo

This attribute has been removed from the schema. It is no longer supported. It only worked for dirsyntax mode, which was deprecated in iPlanet Messaging Server 5.2.

mgrpRFC822MailMember

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes[inetMailGroup](#)

Definition

Identifies recipients of mail sent to mail group. Mail sent to both this attribute and `uniqueMember` attributes are not members of the mixed-in `groupOfUniqueNames`. This attribute represents mail recipients that cannot be expressed as distinguished names, or who are to be sent mail from this group but who do not have the full privileges of a unique group member. Messaging Server expects this attribute to contain RFC 822 mail addresses. Generally used for group members who are not in the local directory.

For backwards compatibility, `rfc822MailMember` is also supported. You can use either one or the other of these attributes in any given group, but not both.

NOTE

`LDAP_GROUP_RFC822` is the MTA option used to specify a different attribute name for this function.

Example

`mgrpRFC822MailMember:bjensen@siroe.com`

OID

2.16.840.1.113730.3.1.30

msgVanityDomain

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[msgVanityDomainUser](#)

Definition

This attribute and the object class using it are deprecated in the current release, and may not be supported in future releases. Sites should stop using this feature and consider migrating current vanity domains to hosted domains.

Example**OID**

2.16.840.1.113730.3.1.799

multiLineDescription

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailUser](#)

Definition

Detailed description of the distribution list. A dollar sign (“\$”) creates a new line.

Example

```
multiLineDescription:People who like cats. $And are ambivalent  
about people.
```

OID

1.3.6.1.4.1.250.1.2

nickName

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[pabPerson](#), [pabGroup](#)

Definition

Identifies the short name used to locate a [pabPerson](#) or a [pabGroup](#) entry.

Example

```
nickname:Nick
```

OID

2.16.840.1.113730.3.1.720

nswcalDisallowAccess

Origin

Netscape™ Calendar Hosting Server

Syntax

cis, single

Object Classes

[icsCalendarUser](#)

Definition

Lists the calendar protocols not allowed to be used by this user.

Example

OID

2.16.840.1.113730.3.1.539

nswmExtendedUserPrefs

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[inetMailUser](#)

Definition

This attribute holds the pairs that define Messenger Express preferences such as sort order, Mail From address, and so on. Each instance of this attribute is the tuple *pref_name=pref_value*. This is a proprietary syntax and the example below is for illustrative purposes only.

Example

Example 1: nswmExtendedUserPrefs: meColorSet=4
 Example 2: nswmExtendedUserPrefs: meSort=r
 Example 3: nswmExtendedUserPrefs: meAutoSign=True
 Example 4: nswmExtendedUserPrefs: meSignature=Otis
 Fanning\$ofanning@sesta.com
 Example 5: nswmExtendedUserPrefs: meDraftFolder=Drafts

OID

2.16.840.1.113730.3.1.520

o**Origin**

iPlanet Messaging Server 5.0

Syntax

cis, single valued

Object Classes

[pabPerson](#)

Definition

Name of the user's company or organization. Abbreviation of `organizationName`.

Example

`organizationName:Company22 Incorporated`

or

`o:Company22 Incorporated`

OID

2.5.4.10

objectClass

Origin

iPlanet Messaging Server 5.0

organizationName (see o)

Syntax

cis

Object Classes

[inetAdmin](#), [organization](#)

Definition

Specifies the objects for this object class.

Example

objectClass:person

OID

2.5.4.0

organizationName (see o)

organizationUnitName (see ou)

ou

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single valued

Object Classes

[organizationalUnit](#), [pabPerson](#)

Definition

Name of the organization unit to which the user belongs. Abbreviation for organizationUnitName.

Example

organizationUnitName:docs

or

ou:docs

OID

2.16.840.1.113730.3.1.722

owner

Origin

iPlanet Messaging Server 5.0

Syntax

dn, single-valued

Object Classes

[inetOrgPerson](#)

Definition

Identifies the distinguished name (DN) of the person or group with administrative privileges over the entry.

Example

owner: cn=John Smith,o=Sesta,c=US

OID

2.5.4.32

pabURI

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[ipUser](#)

Definition

LDAP URI specifying the container of the personal address book entries for this user. It takes the following form: `ldap://server:port/container_dn`, where:

- *server* – Host name of the personal address book LDAP server.
- *port* – Port of the personal address book LDAP server.
- *container_dn* – DN of the subtree where all PAB entries for the user are created.

Example

pabURI:

`ldap://ldap.siroe.com:389/ou=ed,ou=people,o=sesta.com,o=isp,o=pab`

OID

2.16.840.1.113730.3.1.703

parentOrganization

Origin

Sun ONE Messaging Server 6.0, Sun ONE Calendar Server 6.0

Syntax

cis, single-valued

Object Classes

`sunManagedSubOrganization`

Definition

Specifies the logical parent of a suborganization. The value of this is the DN of the parent organization or parent suborganization.

Example

`parentOrganization:o=sesta,o=com,o=internet`

OID

postalAddress

Origin

LDAP

Syntax

cis

Object Classes

[icsCalendarResource](#), [organization](#), [organizationalUnit](#)

Definition

Identifies the entry's mailing address. This field is intended to include multiple lines. When represented in LDIF format, each line should be separated by a dollar sign (\$).

To represent an actual dollar sign (“\$”) or back slash (“\”) within this text, use the escaped hex values, \24 and \5c respectively. For example, to represent the string:

```
The dollar ($) value can be found
in the c:\cost file.
```

provide the string:

The dollar(\24) value can be found\$in the c:\5ccost file.

Example

```
postalAddress:123 Oak Street$Anytown, CA$90101
```

OID

2.5.4.16

preferredLanguage

Origin

iPlanet Messaging Server 5.0, iPlanet Calendar Server 5.1, Sun ONE Directory Server

Syntax

RFC 2798, cis, single-valued

Object Classes

`icsCalendarUser`, `inetMailGroup`, `inetOrgPerson`, `iPlanetPreferences`, `mailDomain`

Definition

Preferred written or spoken language for a person. The value for this attribute should conform to the syntax for HTTP Accept-Language header values.

Messaging Server uses this attribute to figure the locale. It does not use the locale specified with `iPlanetPreferences`.

Also used by Sun ONE Identity Server in user LDAP entries to store a user's preferred language. Note that only Sun ONE Identity Server uses the `iPlanetPreferences` object class to host this attribute.

[Table 3-17](#) lists the supported language strings:

Table 3-17 Language Strings for preferredLanguage Attribute

Language String	Language
de	German
en	English
es	Spanish
fr	French
ja	Japanese
ko	Korean
zh-CN	Chinese - People's Republic of China
zh-TW	Chinese - Taiwan

Example

`preferredLanguage:en`

OID

2.16.840.1.113730.3.1.39

preferredMailHost

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[mailDomain](#)

Definition

Used by Sun ONE Messaging Server Delegated Administrator with Sun ONE LDAP Schema v.1 only.

Used to set the `mailHost` attribute of newly created users and groups in this mail domain.

Example

`preferredMailHost:mail.siroe.com`

OID

2.16.840.1.113730.3.1.761

preferredMailMessageStore

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[mailDomain](#)

Definition

Used by Sun ONE Messaging Server Delegated Administrator for Sun ONE LDAP Schema v.1 only.

Used to set the `mailMessageStore` attribute of newly created users. If missing, Delegate Administrator leaves the `mailMessageStore` attribute empty and the access server assumes that the user's mailbox is in the default partition of the server instance.

Example

`preferredMailMessageStore: primary`

seeAlso

OID

2.16.840.1.113730.3.1.762

seeAlso

Origin

LDAP

Syntax

dn

Object Classes

[groupOfUniqueNames](#), [organization](#), [organizationalUnit](#)

Definition

Identifies another LDAP entry that may contain information related to this entry.

Example

seeAlso: cn=Quality Control

Inspectors,ou=manufacturing,o=Company22, c=US

OID

2.5.4.34

sn

Origin

LDAP

Syntax

cis

Object Classes

[icsCalendarUser](#)

Definition

Identifies the entry's surname, also referred to as last name or family name.

Example

surname:jones

OID

2.5.4.4

telephoneNumber

Origin

LDAP

Syntax

tel

Object Classes

domain, organization, organizationalUnit

Definition

Identifies the entry's phone number.

Example

telephoneNumber:800-555-1212

OID

2.5.4.20

uid

Origin

iPlanet Calendar Server 5.0, iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

icsCalendarResource, icsCalendarUser

Definition

Identifies the unique identifier for this user or resource within its relative namespace. All valid user and resource entries must have a `uid` attribute. Group entries may have a `uid`.

For Messaging Server, the `uid` is used to generate the user address to pass to the delivery channel. If a user entry does not have a `uid` attribute, the entry is ignored. If multiple `uid` attributes exist in an entry, only the first one is used. The MTA used to override this attribute's value is `LDAP_UID`.

Example

`uid:jdoe`

OID

0.9.2342.19200300.100.1.1

un**Origin**

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[pabPerson](#), [pabGroup](#), [pab](#)

Definition

Unique name assigned to PAB entry. This is also the naming attribute for entries created by this object class and is used to form the DN of all PAB entries, irrespective of the type (`pab`, `pabPerson`, or `pabGroup`).

Example

`un:Nick`

OID

2.16.840.1.113730.3.1.717

uniqueMember

Origin

iPlanet Messaging Server 5.0

Syntax

dn, multi-valued

Object Classes

[groupOfUniqueNames](#)

Definition

Identifies a member of a static group. Each member of the group is listed in the group's LDAP entry using this attribute.

Example

```
uniqueMember: uid=jdoe,ou=People,o=sesta.com,o=basedn  
uniqueMember: uid=rsmith,ou=People,o=sesta.com,o=basedn
```

OID

2.5.4.50

userId (see uid)

userPassword

Origin

iPlanet Messaging Server 5.0

Syntax

bin, single-valued

Even though RFC 2256 defines this attribute as multi-valued, for Sun ONE products, only one value is allowed.

Object Classes

[inetUser](#), [domain](#), [organization](#), [organizationalUnit](#)

Definition

This attribute identifies the entry's password and encryption method in the following format:

```
{encryption method}encrypted password
```

Transfer of cleartext passwords is strongly discouraged where the underlying transport service cannot guarantee confidentiality. Transfer of cleartext may result in disclosure of the password to unauthorized parties.

Example

```
userPassword:{sha}FTSLQhxXpA05
```

OID

2.5.4.35

vacationEndDate

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[userPresenceProfile](#)

Definition

Vacation end date and time. Date is in the following format: YYYYMMDDHHMMSSZ; where YYYY is the four digit year, MM is the two digit month, DD is the two digit day, HH is the two digit hour, and SS is the two digit second. Time is normalized to GMT. Z is the character Z.

When the current date falls outside the range of dates specified by the attributes vacationStartDate and vacationEndDate, then any delivery options (in the DELIVERY_OPTIONS list) prefixed with “^” are removed from the active set of options. For example, if one of the DELIVERY_OPTIONS is “^autoreply” and today's date falls outside the vacation date range, then the option is removed from the active options list. Otherwise, the autoreply delivery option is activated.

Example

```
vacationEndDate:20000220000000Z
```

OID

2.16.840.1.113730.3.1.708

vacationStartDate

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes[userPresenceProfile](#)**Definition**

Vacation start date and time. Date is in the following format: YYYYMMDDHHMMSSZ; where YYYY is the four digit year, MM is the two digit month, DD is the two digit day, HH is the two digit hour, and SS is the two digit second. Time is normalized to GMT. Z is the character z.

Example

vacationStartDate:20000215000000Z

OID

2.16.840.1.113730.3.1.707

vacationStartDate

Sun ONE Identity Server Classes and Attributes

This chapter describes LDAP object classes and attributes for Sun™ Open Net Environment (ONE) Identity Server implementing Sun ONE LDAP Schema v.2. The objects and attributes are listed alphabetically.

Note that the Identity Server schema is subject to change. To understand provisioning considerations, see the *Sun Java™ Enterprise System Installation Guide*.

The chapter is divided into two sections:

- [“Object Classes” on page 189](#)
- [“Attributes” on page 202](#)

Object Classes

This section describes the following Sun ONE Identity Server object classes:

- [“iplanet-am-managed-assignable-group” on page 190](#)
- [“iplanet-am-managed-filtered-group” on page 191](#)
- [“iplanet-am-managed-filtered-role” on page 191](#)
- [“iplanet-am-managed-group” on page 192](#)
- [“iplanet-am-managed-group-container” on page 193](#)
- [“iplanet-am-managed-org-unit” on page 193](#)
- [“iplanet-am-managed-people-container” on page 194](#)
- [“iplanet-am-managed-person” on page 195](#)

- “iplanet-am-managed-role” on page 195
- “iplanet-am-managed-static-group” on page 196
- “iplanet-am-user-service” on page 197
- “iPlanetPreferences” on page 197
- “sunISManagedOrganization” on page 198
- “sunManagedOrganization” on page 199
- “sunNameSpace” on page 199

iplanet-am-managed-assignable-group

Supported by

Sun ONE Identity Server

Definition

Specifies a dynamic group with a well-known attribute in the search filter. For Messaging Server, the well-known attribute is `memberOf`. The search filter is contained in the `mgrpDeliverTo` attribute.

Superior Class

`iplanet-am-managed-group`

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.182

Required Attributes

N/A

Allowed Attributes

Inherits attributes from superior class.

iplanet-am-managed-filtered-group

Supported by

Sun ONE Identity Server

Definition

Specifies a dynamic group which can be filtered on any attribute. The search filter is set in the `mgrpDeliverTo` attribute.

This group is not subscribable. Do not use `iplanet-am-group-subscribable` for a filtered dynamic group.

Superior Class

`iplanet-am-managed-group`

Object Class Type

`auxiliary`

OID

2.16.840.1.113730.3.2.181

Required Attributes

N/A

Allowed Attributes

Inherits attributes from superior class. Note that since this group can not be subscribed to, the `mail` attribute should not be used with it. If present, it will be ignored.

iplanet-am-managed-filtered-role

Supported by

Sun ONE Identity Server

Definition

Specifies the attributes necessary to define administrator roles and their ACIs. The list of all users assigned this role is a dynamic list; that is, the list can be retrieved only by performing a search filtered by the role name. For further information on roles, see the Sun ONE Identity Server documentation at:

<http://docs.sun.com>

Superior Class

[iplanet-am-managed-role](#)

Object Class Type

auxiliary

OID

1.3.6.1.4.1.42.2.27.9.2.74

Required Attributes

N/A

Allowed Attributes

This class inherits the attributes of its superior class, see [iplanet-am-managed-role](#).

iplanet-am-managed-group

Supported by

Sun ONE Identity Server

Definition

This is the superior class for the various types of groups: static, assignable dynamic, and filtered dynamic. (See [iplanet-am-managed-assignable-group](#), [iplanet-am-managed-filtered-group](#), [iplanet-am-managed-static-group](#).)

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.180

Required Attributes

N/A

Allowed Attributes

[mail](#), [inetGroupStatus](#)

iplanet-am-managed-group-container

Supported by

Sun ONE Identity Server

Definition

The Sun ONE Identity Server class that defines the groups container under each Sun ONE Messaging Server hosted domain.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.189

Required Attributes

N/A

Allowed Attributes

N/A

iplanet-am-managed-org-unit

Supported by

Sun ONE Identity Server

Definition

This class is used by Sun ONE Identity Server to manage organizational units. It uses the same attributes as `sunManagedOrganization` and for all intents and purposes functions as any other organization managed by Identity Server.

Do not use this class for the domain organizations, or people and group containers in Sun ONE Messaging Server. Even though the attribute that holds the container name is organizational unit (`ou`), the proper Identity Server class to use is either [iplanet-am-managed-group-container](#), or [iplanet-am-managed-people-container](#).

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.186

Required Attributes

N/A

Allowed Attributes

[businessCategory](#), [iplanet-am-service-status](#), [telephoneNumber](#),
[sunOverrideTemplates](#), [sunPreferredDomain](#), [seeAlso](#)

iplanet-am-managed-people-container

Supported by

Sun ONE Identity Server

Definition

The Sun ONE Identity Server class that defines the people container under each Sun ONE Messaging Server hosted domain.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.187

Required Attributes

N/A

Allowed Attributes

N/A

iplanet-am-managed-person

Supported by

Sun ONE Identity Server

Definition

Specifies sunONE Identity Server attributes used to manage users.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.184

Required Attributes

N/A

Allowed Attributes

[iplanet-am-modifiable-by](#), [iplanet-am-role-aci-description](#),
[iplanet-am-static-group-dn](#), [iplanet-am-user-account-life](#)

iplanet-am-managed-role

Supported by

Sun ONE Identity Server

Definition

Specifies the attributes necessary to define administrator roles and their ACIs. This is the superior class for [iplanet-am-managed-filtered-role](#).

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.179

Required Attributes

N/A

Allowed Attributes

`iplanet-am-role-aci-description`, `iplanet-am-role-aci-list`,
`iplanet-am-role-any-options`, `iplanet-am-role-description`,
`iplanet-am-role-managed-container-dn`,
`iplanet-am-role-service-options`, `iplanet-am-role-type`

iplanet-am-managed-static-group

Supported by

Sun ONE Identity Server

Definition

Defines a group in which there are members identified with the `uniqueMember` attribute. Each user named in those attributes has the `memberOf` attribute in their LDAP user entry.

Note that static groups can have dynamic members. In this case, the LDAP entry must also contain the `iplanet-am-managed-assignable-group` object class.

Superior Class

`iplanet-am-managed-group`

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.183

Required Attributes

N/A

Allowed Attributes

N/A (inherits from `iplanet-am-managed-group`)

iplanet-am-user-service

Supported by

Sun ONE Identity Server

Definition

This class contains the Sun ONE Identity Server attributes necessary to manage user accounts.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.176

Required Attributes

N/A

Allowed Attributes

`iplanet-am-user-account-life`, `iplanet-am-user-admin-start-dn`,
`iplanet-am-user-alias-list`, `iplanet-am-user-auth-config`,
`iplanet-am-user-auth-modules`, `iplanet-am-user-failure-url`,
`iplanet-am-user-federation-info`,
`iplanet-am-user-federation-info-key`, `iplanet-am-user-login-status`,
`iplanet-am-user-password-reset-force-reset`,
`iplanet-am-user-password-reset-options`,
`iplanet-am-user-password-reset-question-answer`,
`iplanet-am-user-service-status`, `iplanet-am-user-success-url`

iPlanetPreferences

Supported by

Sun ONE Directory Server

Definition

Used by Sun ONE Identity Server. While Sun ONE Messaging Server does not use this object class, it is necessary for Identity Server.

Attributes for this object class hold certain preferences for this user. Specifically, the preferred language, preferred locale, and preferred time zone.

Note: Sun ONE Messaging Server does not use this object class to define the preferred language. In addition, it does not use an attribute for locale; it infers the locale from the language. Messaging Server holds the `preferredLanguage` attribute in `inetOrgPerson`.

Superior Class

top

Object Class Type

auxiliary

OID**Required Attributes**

N/A

Allowed Attributes

`preferredLanguage`, `preferredLocale`, `preferredTimeZone`

sunISManagedOrganization

Supported by

Sun ONE Calendar Server 6.0, Sun ONE Messaging Server 6.0

Definition

For Sun ONE LDAP Schema v.2, this is a core class for both Messaging and Calendar products doing authentication with SSO. Every physical node must contain this class, including the root suffix.

The attribute holds the fully qualified login host name.

Superior Class

top

Object Class Type

auxiliary

OID

Required Attributes

N/A

Allowed Attributes[sunOrganizationAlias](#)

sunManagedOrganization

Supported by

Sun ONE Calendar Server 6.0, Sun ONE Messaging Server 6.0

Definition

This is a core class for both Messaging and Calendar products. Every physical node must contain this class.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.185

Required Attributes[inetDomainStatus](#)**Allowed Attributes**[sunPreferredDomain](#), [businessCategory](#), [sunPreferredOrganization](#), [telephoneNumber](#), [sunOverrideTemplates](#)

sunNameSpace

Supported by

Sun ONE Identity Server

Definition

Used for Sun ONE LDAP Schema v.2 only. Required to be present at the root of a subtree representing a namespace. Sun ONE Identity Server enforces the uniqueness attribute for namespaces.

Any organization or its subtree nodes can be designated as a namespace by extending the organization LDAP entry with this object class. Namespaces based on different unique attributes may overlap. That is, a subtree of a node designated as a namespace could also be its own namespace if the unique attributes are different. For example, the parent node could use `uid` to enforce uniqueness, while the child node uses the employee number.

This is a different paradigm than was used in Sun ONE LDAP Schema v.1, in which every domain was considered a unique namespace (using `uid` as the default unique attribute). For Sun ONE LDAP Schema v.2, all namespaces must be explicitly declared using this object class.

NOTE After Sun ONE Identity Server is installed, the root-suffix node contains this object class, but not its corresponding attribute. If you want to provision more than one unique namespace for your Sun ONE Messaging Server or Sun ONE Calendar Server installation, do not add `sunNameSpaceUniqueAttrs` to the root-suffix node.

For more information about namespaces, see the *Sun Java™ Enterprise System Installation Guide*.

Superior Class

top

Object Class Type

auxiliary

OID

1.3.6.1.4.1.42.2.27.9.2.29

Required Attributes

N/A

Allowed Attributes

[sunNameSpaceUniqueAttrs](#)

sunServiceComponent

Supported by

Sun ONE Calendar Server 6.0, Sun ONE Messaging Server 6.0

Definition

Templates are LDAP entries of this object class. Search templates are used to describe how applications should construct searches to send to the directory server in order to locate entries in the DIT.

The entry is named by its required `ou` attribute.

Superior Class

`top`

Object Class Type

`auxiliary`

OID

1.3.6.1.4.1.42.2.27.9.2.27

Required Attributes

`organizationalUnitName (ou)`

Allowed Attributes

`description`, `sunKeyValue`, `sunServiceId`, `sunSmsPriority`, `sunXmlKeyValue`

userPresenceProfile

Supported by

iPlanet Messaging Server 5.0

Definition

Used to store the presence information for a user.

Superior Class

`top`

Object Class Type

`auxiliary`

OID

2.16.840.1.113730.3.2.136

Required Attributes

N/A

Allowed Attributes

[vacationEndDate](#), [vacationStartDate](#)

Attributes

This section describes the following Sun ONE Identity Server attributes:

- [“associatedDomain”](#) on page 203
- [“inetGroupStatus”](#) on page 204
- [“mail”](#) on page 115
- [“iplanet-am-modifiable-by”](#) on page 206
- [“iplanet-am-role-aci-description”](#) on page 206
- [“iplanet-am-role-aci-list”](#) on page 207
- [“iplanet-am-role-any-options”](#) on page 208
- [“iplanet-am-role-description”](#) on page 208
- [“iplanet-am-role-managed-container-dn”](#) on page 209
- [“iplanet-am-role-service-options”](#) on page 209
- [“iplanet-am-role-type”](#) on page 210
- [“iplanet-am-service-status”](#) on page 211
- [“iplanet-am-static-group-dn”](#) on page 211
- [“iplanet-am-user-account-life”](#) on page 211
- [“iplanet-am-user-admin-start-dn”](#) on page 212
- [“iplanet-am-user-alias-list”](#) on page 213
- [“iplanet-am-user-auth-config”](#) on page 213
- [“iplanet-am-user-auth-modules”](#) on page 214

- “iplanet-am-user-failure-url” on page 214
- “iplanet-am-user-federation-info” on page 215
- “iplanet-am-user-federation-info-key” on page 215
- “iplanet-am-user-login-status” on page 216
- “iplanet-am-user-password-reset-force-reset” on page 217
- “iplanet-am-user-password-reset-options” on page 217
- “iplanet-am-user-password-reset-question-answer” on page 218
- “iplanet-am-user-service-status” on page 219
- “iplanet-am-user-success-url” on page 219
- “preferredLocale” on page 220
- “preferredTimeZone” on page 220
- “sunAdditionalTemplates” on page 221
- “sunKeyValue” on page 221
- “sunNameSpaceUniqueAttrs” on page 223
- “sunOrganizationAlias” on page 223
- “sunOverrideTemplates” on page 224
- “sunPreferredDomain” on page 224
- “sunPreferredOrganization” on page 225
- “sunRegisteredServiceName” on page 226
- “sunServiceId” on page 227
- “sunSmsPriority” on page 228
- “sunXmlKeyValue” on page 228

associatedDomain

Origin

Sun ONE LDAP Schema 2

Syntax

dn, multi-valued

Object Classes

inetDomain, sunManagedOrganization

Definition

Specifies the DNS domain name aliases used to lookup an organization entry.

Used when a domain subtree is being referenced by domain names in addition to the one specified in the attribute `sunPreferredDomain`.

Example

```
associatedDomain:qa.sesta.com
```

```
associatedDomain:eng.sesta.com
```

OID

inetGroupStatus

Origin

Sun ONE Identity Server

Syntax

cis, single-valued

Object Classes

[iplanet-am-managed-group](#)

Definition

This is a global status for groups and overrides the status found in `inetMailGroupStatus`. It holds the current status of the group: `active`, `inactive`, or `deleted` for all services. It is used by Sun ONE Identity Server to manage groups. Status changes can be made to a group's status using the `commcli` interface, or by directly changing the LDAP entry for the group.

The following table lists the attribute's values and their meanings:

Table 4-1 Status Attribute Values

Value	Description
active	The group is active and its users may use services enabled by the overlay of service-specific object classes and the service state as indicated by the particular status attribute for that service.
inactive	Group is inactive. The group users may not use any services granted by service-specific object classes. This state overrides individual service status set using the service's status attributes.
deleted	Group is marked as deleted. The group may remain in this state within the directory for some time (pending purging of deleted groups). Service requests for all groups marked as deleted will return permanent failures.

A missing value implies status is `active`. An illegal value is treated as `inactive`.

Example

```
inetGroupStatus: active
```

OID

```
1.3.6.1.4.1.42.2.27.9.1.588
```

iplanet-am-group-subscribable

Origin

Sun ONE Identity Server

Syntax

boolean, single-valued

Object Classes

[iplanet-am-managed-group](#)

Definition

Specifies if users can subscribe to the group. Boolean value: `true`, `false`. Default setting is `true`.

If the value is `true`, the group can be seen, searched for and subscribed to by end users. If the value is `false`, the group can be seen and searched for but can not be subscribed to by end users.

Filtered groups can not be subscribed to; this attribute is ignored if found on a filtered group.

Example

```
iplanet-am-group-subscribable: true
```

OID

2.16.840.1.113730.3.1.1085

iplanet-am-modifiable-by

Origin

Sun ONE Identity Server

Syntax

dn, multi-valued

Object Classes

[iplanet-am-managed-person](#)

Definition

This attribute lists the role-dn of the administrator who has access rights to modify this user entry. By default, the value is set to the role-dn of the administrator who created the account.

Example

For native mode (with domain nodes on the organization tree):

```
iplanet-am-modifiable-by: cn:Top-level Admin Role, o=sesta.com
```

For compatibility mode (with domain nodes on the DC Tree):

```
iplanet-am-modifiable-by: cn=Top-level Admin Role, dc=sesta, dc=com
```

OID

2.16.840.1.113730.3.1.1094

iplanet-am-role-aci-description

Origin

Sun ONE Identity Server

Syntax

string, multi-valued

Object Classes

[iplanet-am-managed-person](#)

Definition

Description of the ACI that belongs to this role.

Example**OID**

2.16.840.1.113730.3.1.1081

iplanet-am-role-aci-list

Origin

Sun ONE Identity Server

Syntax

string, multi-valued

Object Classes

[iplanet-am-managed-role](#)

Definition

The set of ACIs associated with this role. The format is a DN:ACI pair, where the DN of the entry is specified with its ACI. When deleting a role, this attribute allows for the ACIs associated with this role to be located and cleaned up properly.

Example

For native mode (with domain nodes on the organization tree):

```
iplanet-am-role-aci-list: o=sesta.com,o=basedn:aci:
(target="ldap:///o=sesta.com,o=basedn") (targetfilter=(!(|(nsroledn=cn=Top-level Admin Role,o=sesta.com,o=basedn)(nsroledn=cn=Top-level Help Desk Admin Role,o=sesta.com,o=basedn)))) (targetattr != "nsroledn") (version 3.0; acl "Organization Admin access allow"; allow (all) roledn = "ldap:///cn=myrole,o=sesta.com,o=basedn";)
```

For compatibility mode (with domain nodes on a DC Tree):

```
iplanet-am-role-aci-list: dc=sesta,dc=com:aci:  
(target="ldap:///dc=sesta,dc=com")(targetfilter=(!(|(nsroledn=cn=Top-level  
Admin Role,dc=sesta,dc=com)(nsroledn=cn=Top-level Help Desk Admin  
Role,dc=sesta,dc=com))))(targetattr != "nsroledn")(version 3.0; acl  
"Organization Admin access allow"; allow (all) roledn =  
"ldap:///cn=myrole,dc=sesta,dc=com";)
```

OID

2.16.840.1.113730.3.1.1082

iplanet-am-role-any-options

Origin

Sun ONE Identity Server

Syntax

string, multi-valued

Object Classes

[iplanet-am-managed-role](#)

Definition

Not currently used.

Example

OID

2.16.840.1.113730.3.1.1084

iplanet-am-role-description

Origin

Sun ONE Identity Server

Syntax

cis, multi-valued

Object Classes[iplanet-am-managed-role](#)**Definition**

An optional description of the role being defined.

Example

```
iplanet-am-role-description: Top Level Admin Role
```

OID

2.16.840.1.113730.3.1.1080

iplanet-am-role-managed-container-dn

Origin

Sun ONE Identity Server

Syntax

dn, multi-valued

Object Classes[iplanet-am-managed-role](#)**Definition**

Defines the container this role resides in.

Example

For example, if the role being defined administers the domain organization east:

```
iplanet-am-role-managed-container-dn: ou=east,o=sesta.com,o=basedn
```

OID

2.16.840.1.113730.3.1.977

iplanet-am-role-service-options

Origin

Sun ONE Identity Server

Syntax

string, multi-valued

Object Classes

[iplanet-am-managed-role](#)

Definition

Not currently used.

Example

OID

2.16.840.1.113730.3.1.1083

iplanet-am-role-type

Origin

Sun ONE Identity Server

Syntax

string, multi-valued

Object Classes

[iplanet-am-managed-role](#)

Definition

Defines the type of role. There are three values, as shown in the following table:

Role Value	Role Names
1	Top Level Admin Role
2	General Admin Role
3	User Role

Even though this attribute is defined as multi-valued string, it is implemented in Messaging Server as if it were a single-valued integer.

Example

iplanet-am-role-type: 1

OID

2.16.840.1.113730.3.1.1079

iplanet-am-service-status

This attribute is aliased to [sunRegisteredServiceName](#). Use that attribute instead.

iplanet-am-static-group-dn

Origin

Sun ONE Identity Server

Syntax

dn, multi-valued

Object Classes[iplanet-am-managed-group](#)**Definition**

Defines the DNs for the static groups this user belongs to.

Example

For native mode (with domain nodes on the organization tree):

```
iplanet-am-static-group-dn: cn=mygroup, ou=groups, o=sesta.com
```

For compatibility mode (with domain nodes on the DC Tree):

```
iplanet-am-static-group-dn: cn=mygroup, ou=groups, dc=sesta, dc=com
```

OID

2.16.840.1.113730.3.1.1094

iplanet-am-user-account-life

Origin

Sun ONE Identity Server

Syntax

date string, single-valued

Object Classes[iplanet-am-user-service](#)**Definition**

Specifies the account expiration date in the following format:

`yyyy/mm/dd hh:mm:ss`

where the first `mm` is for month, `dd` is for day, `yyyy` for full year (for example, 2005), `hh` is for the time stamp hour, the final `mm` is for the timestamp minutes, and `ss` is for the timestamp seconds.

If this attribute is present, the authentication service will disallow login if the current date has passed the specified account expiration date.

Example

`iplanet-am-user-account-life: 2040/12/31 23:59:59`

OID

2.16.840.1.113730.3.1.976

iplanet-am-user-admin-start-dn

Origin

Sun ONE Identity Server

Syntax

dn, single-valued

Object Classes[iplanet-am-user-service](#)**Definition**

Specifies the starting point node (DN) displayed in the starting view of the IS Console when this administrator logs in.

Example

`iplanet-am-user-admin-start-dn: ou=people, o=sesta.com, o=basedn`

OID

2.16.840.1.113730.3.1.1072

iplanet-am-user-alias-list

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Defines a list of aliases for the user.

Example

User jdoe could have an alias of jd, johnd, or jd123456.

```
iplanet-am-user-alias-list: jd
iplanet-am-user-alias-list: johnd
iplanet-am-user-alias-list: jd123456
```

OID

1.3.6.1.4.1.42.2.27.9.1.59

iplanet-am-user-auth-config

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Specifies the user authentication configuration method in an XML string. There is no default value.

Example

```
<AttributeValuePair><Value>com.sun.identity.authentication.modules.ldap.LD  
AP REQUIRED </Value></AttributeValuePair>
```

OID

1.3.6.1.4.1.42.2.27.9.1.58

iplanet-am-user-auth-modules

Origin

Sun ONE Identity Server

Syntax

string, multi-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Not currently used.

Example**OID**

2.16.840.1.113730.3.1.1071

iplanet-am-user-failure-url

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Defines the routing taken (URL user is redirected to) if the login fails. Any valid URL can be used.

Example**OID**

1.3.6.1.4.1.42.2.27.9.1.71

iplanet-am-user-federation-info

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

For Sun ONE Identity Server internal use only. Do not use.

Specifies the user account's Federation specific information. This is managed internally by Sun ONE Identity Server's Federation Management module to store user account's Federation related information, and should not be modified outside of that module.

Example**OID**

1.3.6.1.4.1.42.2.27.9.1.74

iplanet-am-user-federation-info-key

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes[iplanet-am-user-service](#)**Definition**

For Sun ONE Identity Server internal use only. Do not use.

Specifies the user account's Federation information key. This is managed internally by Sun ONE Identity Server's Federation Management module to store the user account's Federation information key, and should not be modified outside of that module.

Example**OID**

1.3.6.1.4.1.42.2.27.9.1.73

iplanet-am-user-login-status

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes[iplanet-am-user-service](#)**Definition**

Specifies the user status. It takes two values:

- *Active* - The user is allowed to authenticate through the Sun ONE Identity Server.
- *Inactive* - The user is not allowed to authenticate through the Sun ONE Identity Server.

Example**OID**

2.16.840.1.113730.3.1.1074

iplanet-am-user-password-reset-force-reset

Origin

Sun ONE Identity Server

Syntax

boolean, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Not currently used.

Specifies whether password will be forced to be reset. Values: `true`, `false`. Defaults to `false`.

Example**OID**

1.3.6.1.4.1.42.2.27.9.1.591

iplanet-am-user-password-reset-options

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Used internally by Sun ONE Identity Server's password reset module. Do not use. Any values assigned to this attribute will be ignored.

Example**OID**

1.3.6.1.4.1.42.2.27.9.1.589

iplanet-am-user-password-reset-passwordChanged

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Not used.

Example**OID**

1.3.6.1.4.1.42.2.27.9.1.592

iplanet-am-user-password-reset-question-answer

Origin

Sun ONE Identity Server

Syntax

string, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Password question and answer used to prompt user who has forgotten their password. The format is `question answer`.

Example

```
iplanet-am-user-password-reset-question-answer:  
favorite restaurant Outback
```

OID

1.3.6.1.4.1.42.2.27.9.1.590

iplanet-am-user-service-status

Origin

Sun ONE Identity Server

Syntax

dn, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Specifies the status of the user for various services.

Example**OID**

2.16.840.1.113730.3.1.1073

iplanet-am-user-success-url

Origin

Sun ONE Identity Server

Syntax

dn, single-valued

Object Classes

[iplanet-am-user-service](#)

Definition

Defines the routing taken (URL the user is directed) if the login succeeds. Any valid URL can be used.

Example**OID**

1.3.6.1.4.1.42.2.27.9.1.71

preferredLocale

Origin

Sun ONE Directory Server

Syntax

cis, single-valued

Object Classes

[iPlanetPreferences](#)

Definition

Used by Sun ONE Identity Server to store user preference for locale. The values accepted by this attribute are described in the Sun ONE Identity Server Administrator's Guide, chapter 18. Some additional information on locales is located in the Sun ONE Directory Server Reference Manual.

Example

```
preferredLocale:en-US
```

OID

2.16.840.1.113730.3.1.39

preferredTimeZone

Origin

Sun ONE Directory Server

Syntax

cis, single-valued

Object Classes

[iPlanetPreferences](#)

Definition

Used by Sun ONE Identity Server to store user preference for time zone. Supported time zone names can be found in the appendix under "[Standard Time Zones](#)" on [page 263](#).

Example

```
preferredTimeZone: America/Los Angeles
```

OID
TBD

sunAdditionalTemplates

Origin

Sun ONE Messaging Server 6.0, Sun ONE Calendar Server 6.0

Syntax

cis, multi-valued

Object Classes

inetDomain, sunManagedOrganization

Definition

Specifies relative DN (RDN) sequences, that is DNs that are relative to the organization entry. Values identify entries in the configuration templates part of the ou=services tree below this organization. These are additional templates beyond those specified in the global configuration templates. These are used to specify operations private to an organization.

This attribute must appear in the top entry for this organization.

Example

OID
1.3.6.1.4.1.42.2.27.9.1.76

sunKeyValue

Origin

Sun ONE Messaging Server 6.0, Sun ONE Calendar Server 6.0

Syntax

cis, multi-valued

Object Classes

[sunServiceComponent](#)

Definition

Each value is a “key=value” pair, where the key is the name of the XML element. table lists the keys for search templates.

Table 4-2 Search Template Keys

Key	Description
attrs	Attribute to retrieve from LDAP entry.
rfc2247Flag	Boolean (ture, false) that tells applications to use the RFC2247 algorithm for constructing the DN of the LDAP entry, instead of performing an LDAP search using the filter specified in the inetDomainSearchFilter attribute.
baseDN	If rfc2247Flag is set to true, and if this key is present, then it must be appended to the algorithmically constructed DN in order to get the DN of the target entry.

For more information on templates and the native and compatibility mode LDAP data models, see [Chapter 1, “Overview”](#).

Example

The following sunKeyValue attributes appear in the default search template for the native mode LDAP data model:

```
sunKeyValue: attrs=objectclass
sunKeyValue: attrs=ou
sunKeyValue: attrs=inetDomainStatus
```

The following sunKeyValue attributes appear in the default search template for compatibility mode (uses the RFC 2247 algorithm for constructing the search DN):

```
sunKeyValue: attrs=objectclass
sunKeyValue: attrs=ou
sunKeyValue: attrs=inetDomainStatus
sunKeyValue: rfc2247=true
sunKeyValue: baseDN=o=internet
```

OID

1.3.6.1.4.1.42.2.27.9.1.83

sunNameSpaceUniqueAttrs

Origin

Sun ONE Messaging Server 6.0, Sun ONE Calendar Server 6.0

Syntax

cis, multi-valued

Object Classes

[sunNameSpace](#)

Definition

Stores the name of an attribute required to be unique across all entries in the subtree.

This attribute allows namespace uniqueness to be enforced. For further explanation of namespaces, see the *Sun Java™ Enterprise System Installation Guide* and the object class description for `sunNameSpace`.

Example

```
sunNameSpaceUniqueAttrs:uid  
  
sunNameSpaceUniqueAttrs:c
```

OID

1.3.6.1.4.1.42.2.27.9.1.85

sunOrganizationAlias

Origin

Sun ONE Identity Server

Syntax

cis, single-valued

Object Classes

[userPresenceProfile](#)

Definition

Sun ONE Identity Server uses this attribute for authentication. It holds the fully qualified host name for the server the user is logging into.

The format is: *server.domain*.

Example

sunOrganizationAlias: seaside.siroe.com

OID

TBD

sunOverrideTemplates

Origin

Sun ONE Messaging Server 6.0, Sun ONE Calendar Server 6.0

Syntax

cis, multi-valued

Object Classes

inetDomain, sunManagedOrganization

Definition

Specifies relative DN (RDN) sequences, that is DNs that are relative to the organization entry. Values identify entries in the configuration templates part of the ou=services tree below this organization. These templates override global configuration templates for searches and other operations within this organization.

This attribute must appear in the top entry for this organization.

Example

OID

1.3.6.1.4.1.42.2.27.9.1.77

sunPreferredDomain

Origin

Sun ONE Messaging Server 6.0, Sun ONE Calendar Server 6.0

Syntax

cis, single-valued

Object Classes

`iplanet-am-managed-org-unit`, `sunManagedOrganization`

Definition

Specifies the DNS domain name used to lookup an organization entry when a unique matching organization is required.

When a value for this is available, provisioners should set it so as to enable applications to look up organizations using a domain name.

The domain name value of this attribute must be unique across all organizations in the directory, including the domains named in `associatedDomain`.

This attribute is for use with native mode data model LDAPs only; it must not be used in DC Tree nodes.

In the native mode LDAP data model, this attribute serves the same function as `inetCanonicalDomainName` used to in compatibility mode. If you are running in compatibility mode, do not use this attribute.

Example

`sunPreferredDomain:sesta.com`

OID

2.16.840.1.113730.3.1.1086

sunPreferredOrganization

Origin

Sun ONE Messaging Server 6.0, Sun ONE Calendar Server 6.0

Syntax

cis, single-valued

Object Classes

`iplanet-am-managed-org-unit`, `sunManagedOrganization`

Definition

Specifies the DNS name used to lookup an organization entry when a unique matching organization is required.

When a value for this is available, provisioners should set it so as to enable applications to look up organizations using the organization's name.

This attribute is for use with native mode data model LDAPs only; it must not be used in DC Tree nodes.

Example

sunPreferredOrganization:sesta.com

OID

1.3.6.1.4.1.42.2.27.9.1.75

sunRegisteredServiceName

Origin

Sun ONE Identity Server

Syntax

string, multi-valued

Object Classes

[iplanet-am-managed-org-unit](#), [sunManagedOrganization](#)

Definition

Defines the set of names of the registered services. The following services are defined for Messaging Server and Calendar Server:

Service Name	Description
DomainMailService	Mail service definition for domains.
DomainCalendarService	Calendar service definition for domains.
UserMailService	Mail service definition for users.
UserCalendarService	Calendar service definition for users.
GroupMailService	Mail service definition for groups.

For informational purposes: The following services are used by Sun ONE Identity Server for authentication with SSO (Single Sign-On). These services must be registered to the root suffix node. This step is done by Identity Server as part of its installation process. The services are:

- PlanetAMAuthService
- iPlanetAMAuthLDAPService

- iPlanetAMPolicyConfigService
- iPlanetAMAuthenticationDomainConfigService
- iPlanetAMProviderConfigService

Any one can create a new service and load it into Identity Server. For information on how to do this, see the Sun ONE Identity Server documentation at:

<http://docs.sun.com/>

Example

sunRegisteredServiceName: DomainMailService

OID

1.3.6.1.4.1.42.2.27.9.1.593

sunServiceId

Origin

Sun ONE Messaging Server 6.0, Sun ONE Calendar Server 6.0

Syntax

cis, single valued

Object Classes

[sunServiceComponent](#)

Definition

The kind of template being created. For search templates, the value is StructureUmsObjects. (At this time search templates are the only publicly defined template.)

Example

sunServiceId:StructureUmsObjects

OID

1.3.6.1.4.1.42.2.27.9.1.79

sunSmsPriority

Origin

Sun ONE Identity Server

Syntax

cis, single valued

Object Classes

[sunServiceComponent](#)

Definition

Stores the priority of the service with respect to its siblings.

Example

sunSmsPriority:

OID

1.3.6.1.4.1.42.2.27.9.1.81

sunXmlKeyValue

Origin

Sun ONE Identity Server

Syntax

cis, single valued

Object Classes

[sunServiceComponent](#)

Definition

Not currently used.

Example

OID

1.3.6.1.4.1.42.2.27.9.1.84

iPlanet Delegated Administrator for Messaging Classes and Attributes

This chapter describes LDAP object classes and attributes for iPlanet Delegated Administrator for Messaging implementing Sun ONE LDAP Schema v.1. The objects and attributes are listed alphabetically.

The chapter is divided into two sections:

- [“Object Classes” on page 229](#)
- [“Attributes” on page 238](#)

Object Classes

This chapter describes the following object classes used by Delegated Administrator and those object classes only used in Sun ONE LDAP Schema v.1.

- [“inetDomainOrg” on page 230](#)
- [“inetMailGroupManagement” on page 231](#)
- [“inetManagedGroup” on page 231](#)
- [“nsManagedDept” on page 232](#)
- [“nsManagedDeptAdminGroup” on page 233](#)
- [“nsManagedDomain” on page 233](#)
- [“nsManagedFamilyGroup” on page 234](#)
- [“nsManagedISP” on page 235](#)
- [“nsManagedMailList” on page 235](#)

- [“nsManagedOrgUnit” on page 236](#)
- [“nsManagedPerson” on page 237](#)
- [“nsUniquenessDomain” on page 237](#)

inetDomainOrg

Supported by

iPlanet Messaging Server 5.0

Definition

Used for Sun ONE LDAP Schema v.1. Auxiliary class for supporting a Sun ONE Delegated Manager for Messaging managed domain organization.

This object class is used in conjunction with the structural class `organization` to define a domain organization. A domain organization is usually created as a way of introducing hierarchy beneath a customer subtree and assigning administrators for that domain organization. To create a suborganization beneath the parent tree and designate a set of administrators for that suborganization, you would create a domain organization node by using `organizationalUnit` and `inetDomainOrg` object classes. For example, `siroe.com` could have a customer subtree with the DN:

```
ou=east,o=siroe.com,o=basedn.
```

How to provision a domain organization for Sun ONE LDAP Schema v.1 is described in the *iPlanet Messaging Server 5.2 Provisioning Guide*.

Superior Class

`top`

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.132

Required Attributes

N/A

Allowed Attributes

[domOrgMaxUsers](#), [domOrgNumUsers](#)

inetMailGroupManagement

Supported by

iPlanet Messaging Server 5.0

Definition

Used for Sun ONE LDAP Schema v.1 only. Used to extend the base entry created by `groupOfUniqueNames`. `inetMailGroupManagement` is used to store attributes for managing a distribution list by using Delegated Administrator for Messaging. This object class is used in conjunction with `inetMailGroup` and `inetLocalMailRecipient`. The attributes in this object class have no operational impact on the messaging server's MTA or message access/message store.

Superior Class

`top`

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.149

Required Attributes

N/A

Allowed Attributes

`mgrpAddHeader`, `mgmanDenySubscribe`, `mgmanGoodbyeText`, `mgmanHidden`, `mgmanIntroText`, `mgmanJoinability`, `mgmanMemberVisibility`, `mgmanVisibility`, `multiLineDescription`

inetManagedGroup

Supported by

iPlanet Messaging Server 5.0

Definition

Used to define a managed group. If a managed group is just a department or family group, then the structural class to use is `top`, but it can also be used to make a statically defined group (from `groupOfUniqueNames`) and make that a managed group.

Superior Class

top

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.137

Required Attributes

[cn](#)

Allowed Attributes

[description](#), [mnggrpAdditionPolicy](#), [mnggrpBillableUser](#),
[mnggrpCurrentUsers](#), [mnggrpDeletionPolicy](#), [mnggrpMailQuota](#),
[mnggrpMaxUsers](#), [mnggrpStatus](#), [mnggrpUserClassOfServices](#),
[nsdaModifiableBy](#), [owner](#)

nsManagedDept

Supported by

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Definition

This object class is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Stores information for a non-administrator group.

Superior Class

[groupOfUniqueNames](#)

Object Class Type

auxiliary

OID

2.16.840.1.113730.3.2.88

Required Attributes

N/A

Allowed Attributes

[nsMaxDepts](#), [nsMaxUsers](#), [nsNumDepts](#), [nsNumUsers](#), [nsdaModifiableBy](#), [owner](#)

nsManagedDeptAdminGroup

Supported by

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Definition

This object class is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Stores information for a group of administrators for iPlanet Delegated Administrator.

Superior Class

top

Object Class Type**OID**

2.16.840.1.113730.3.2.111

Required Attributes

[objectClass](#)

Allowed Attributes

N/A

nsManagedDomain

Supported by

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Definition

This object class is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Used only for versions of Messaging Server using iPlanet Delegated Administrator. It contains information necessary to administer domains.

Superior Class

top

Object Class Type**OID**

2.16.840.1.113730.3.2.86

Required Attributes

[objectClass](#)

Allowed Attributes

[nswcalDisallowAccess](#), [nsMaxDepts](#), [nsMaxDomains](#), [nsMaxMailLists](#), [nsMaxUsers](#), [nsNumDepts](#), [nsNumDomains](#), [nsNumMailLists](#), [nsNumUsers](#), [nsdaModifiableBy](#), [owner](#)

nsManagedFamilyGroup

Supported by

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2

Definition

This object class is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Stores information for a family group managed by a delegated administrator. The family group is like a Group, with a few differences. It was added primarily to support Delegated Administrator deployments using Sun Internet Message Service (SIMS) 4.0.

Superior Class

top

OID

2.16.840.1.113730.3.2.89

Required Attribute[objectClass](#)**Allowed Attributes**[nsMaxUsers](#), [nsNumUsers](#), [nsdaModifiableBy](#), [owner](#)

nsManagedISP

Supported by

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2

Definition

This object class is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Tracks the number of sub-organizations that can be created under this object.

Superior Class

top

OID

2.16.840.1.113730.3.2.85

Required Attribute[objectClass](#)**Allowed Attributes**[nsNumDomains](#)

nsManagedMailList

Supported by

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2

Definition

This object class is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Stores information for a mail list created by enabled users. A mail list must contain this object class in order to be managed by Delegated Administrator.

Superior Class

top

Object Class Type

OID

2.16.840.1.113730.3.2.90

Required Attributes

[objectClass](#)

Allowed Attributes

[nsMaxUsers](#), [nsNumUsers](#), [nsdaModifiableBy](#), [owner](#)

nsManagedOrgUnit

Supported by

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Definition

This object class is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Stores information for a Delegated Administrator managed organizational unit.

Superior Class

top

OID

2.16.840.1.113730.3.2.87

Required Attributes

[objectClass](#)

Allowed Attributes

[nsdaModifiableBy](#), [owner](#)

nsManagedPerson

Supported by

iPlanet Messaging Server 5.0; deprecated for Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2

Definition

This object class is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Stores information about a user. A user entry must contain this object class in order to be managed by Delegated Administrator.

Superior Class

top

Object Class Type

OID

2.16.840.1.113730.3.2.91

Required Attributes

[objectClass](#)

Allowed Attributes

[memberOf](#), [nsdaCapability](#), [nsdaDomain](#), [nsSearchFilter](#), [nsdaModifiableBy](#), [owner](#)

nsUniquenessDomain

Supported by

iPlanet Messaging Server 5.0; deprecated for Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2

Definition

Sun ONE LDAP Schema v.1 object class in support of Delegated Administrator for Messaging. If you are still using Sun ONE LDAP Schema v.1, then this object is still valid; otherwise it is deprecated.

This object class is a marker to identify the subtree where the uniqueness of `uid` should be enforced. The `uid` uniqueness plugin used this to determine the scope or sphere of influence for enforcing uniqueness.

Superior Class

`top`

OID

2.16.840.1.113730.3.2.115

Required Attributes

`objectClass`

Allowed Attributes

N/A

Attributes

- `domainUidSeparator` on page 239
- `domOrgMaxUsers` on page 240
- `domOrgNumUsers` on page 241
- `memberOfManagedGroup` on page 241
- `mgmanAllowSubscribe` on page 242
- `mgmanDenySubscribe` on page 243
- `mgmanGoodbyeText` on page 243
- `mgmanHidden` on page 244
- `mgmanIntroText` on page 244
- `mgmanJoinability` on page 245
- `mgmanMemberVisibility` on page 245
- `mgmanVisibility` on page 247
- `mnggrpAdditionPolicy` on page 247
- `mnggrpBillableUser` on page 248
- `mnggrpCurrentUsers` on page 248

- “mnggrpDeletionPolicy” on page 249
- “mnggrpMailQuota” on page 249
- “mnggrpMaxUsers” on page 250
- “mnggrpStatus” on page 250
- “mnggrpUserClassOfServices” on page 251
- “nsDefaultMaxDeptSize” on page 251
- “nsMaxDepts” on page 252
- “nsMaxDomains” on page 252
- “nsMaxMailLists” on page 253
- “nsMaxUsers” on page 254
- “nsNumDepts” on page 254
- “nsNumDomains” on page 255
- “nsNumMailLists” on page 255
- “nsNumUsers” on page 256
- “nsSearchFilter” on page 257
- “nsdaCapability” on page 257
- “nsdaDomain” on page 258
- “nsdaModifiableBy” on page 258
- “preferredMailMessageStore” on page 259

domainUidSeparator

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainOrg](#)

Definition

This attribute is used only for Sun ONE LDAP Schema v.1.

This attribute is used by the messaging server to override the default mailbox (MB) home. When present, this attribute specifies that compound user identifications (UIDs) are used in this domain and this attribute specifies the separator. For instance, if + is the separator, the mailbox names in this domain are obtained by replacing the right most occurrence of + in the uid with @. To map an internal mailbox name to the UID, the right most occurrence of @ is replaced with a + in the mailbox name.

While substitution of an @ for the UID separator is sufficient to generate a mailbox name, this may not be the same as any of the user's actual email addresses.

NOTE

Format of internal mailbox names is uid@domain, where "domain" is DNS domain mapping to the namespace. The only exception to this rule is mailbox names for users in default domain where only the uid is used to construct internal mailbox names. See [inetCanonicalDomainName](#) on how the default value of domain name used can be overridden in specific cases.

The MTA option used to override this attribute's value is

LDAP_DOMAIN_ATTR_UID_SEPARATOR.

Example

```
domainUIDSeparator: #
```

OID

2.16.840.1.113730.3.1.702

domOrgMaxUsers

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainOrg](#)

Definition

This attribute is used only for Sun ONE LDAP Schema v.1.

Maximum number of user entries in a domain organization.

Example

```
domOrgMaxUser: 500
```

OID

```
2.16.840.1.113730.3.1.697
```

domOrgNumUsers

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetDomainOrg](#)

Definition

Number of current user entries in a domain organization.

Example

```
domOrgNumUsers: 345
```

OID

```
2.16.840.1.113730.3.1.698
```

memberOfManagedGroup

Origin

iPlanet Messaging Server 5.0

Syntax

dn, single-valued

Object Classes[ipUser](#)**Definition**

Family accounts are not supported in Sun ONE LDAP Schema v.2. Use this only if you are using Sun ONE LDAP Schema v.1.

Specifies the DN of the family account of which this user is a member.

Example

```
memberOfManagedGroup: cn=Addams Family, ou=groups,o=sesta.com,o=isp
```

OID

2.16.840.1.113730.3.1.704

mgmanAllowSubscribe

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes[inetMailGroupManagement](#)**Definition**

Domain name(s) or email addresses of users allowed to subscribe to this mailing list.

Example

```
mgmanAllowSubscribe:sesta.com (Every user at sesta.com would be able to subscribe to the list.)
```

OID

2.16.840.1.113730.3.1.790

mgmanDenySubscribe

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[inetMailGroupManagement](#)

Definition

Domain name(s) or email addresses of users not allowed to subscribe to this list. The `mgmanDenySubscribe` attribute takes precedence over `mgmanAllowSubscribe`.

Example

`mgmanDenySubscribe:siroe.com`

OID

2.16.840.1.113730.3.1.791

mgmanGoodbyeText

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single valued

Object Classes

[inetMailGroupManagement](#)

Definition

Reserved.

Example

TBD.

OID

2.16.840.1.113730.3.1.797

mgmanHidden

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailGroupManagement](#)

Definition

Used with iPlanet Delegated Administrator for Messaging only.

A boolean flag specifying whether or not the group should appear in lists that are requested by people other than the group owners. A value of `true` corresponds with a hidden group, that is, the list is not visible. A value of `false` means that the list is visible. A missing value is the same as a value of `false`.

Example

```
mgmanHidden:true
```

OID

2.16.840.1.113730.3.1.792

mgmanIntroText

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailGroupManagement](#)

Definition

Reserved.

Example

TBD.

OID

2.16.840.1.113730.3.1.796

mgmanJoinability

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes[inetMailGroupManagement](#)**Definition**

Used for Sun ONE LDAP Schema v.1 only. Specifies who can subscribe to the group. The allowed values are ANYONE, ALL, and NONE (If this attribute is not specified, the default is NONE):

- ANYONE – Enables anyone to subscribe.
- ALL – Enables anyone authenticated to the directory (or Sun ONE Delegated Administrator for Messaging) to subscribe.
- NONE – Only owner can add members to a closed distribution list.

Example

mgmanJoinability:All

OID

2.16.840.1.113730.3.1.793

mgmanMemberVisibility

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailGroupManagement](#)

Definition

Only used in Sun ONE LDAP Schema v.1 with iPlanet Delegated Administrator for Messaging.

Defines who has rights to view the group membership list (expand the group). This attribute has the keyword values: none, all, true , anyone. No matter what the setting of this attribute, group owners always retain the right to view (and modify) membership.

However, if this attribute is checked in the case of group expansion as part of an SMTP EXPN command (that is, not as part of an administrative tool that can easily identify whether or not the client is the group owner), then a value of none ends up operating as if the list is unconditionally disabled. This is because SMTP doesn't provided a means of establishing a client's identity, such as "owner".

The following table lists the keywords and gives a description of each:

Table 5-1 Rights Keywords

Rights	Description
anyone	Enables anyone to expand the group (see the members in the mailing list). Also, the MTA returns the addresses of members when an EXPN is performed.
all or true	The user has to successfully authenticate to the directory (or iPlanet Delegated Administrator for Messaging) before expansion is allowed.
none	Expansion is not allowed.

Unrecognized values are interpreted as none.

If the attribute is not present, the MTA option EXPANDABLE_DEFAULT controls whether the expansion is allowed.

NOTE	LDAP_EXPANDABLE is the MTA option used to specify a different attribute name for this function.
-------------	---

Example

mgmanMemberVisibility:all

OID

2.16.840.1.113730.3.1.795

mgmanVisibility

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetMailGroupManagement](#)

Definition**Example****OID**

2.16.840.1.113730.3.1.794

mnggrpAdditionPolicy

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetOrgPerson](#)

Definition

Reserved.

Example

TBD.

OID

2.16.840.1.113730.3.1.710

mnggrpBillableUser

Origin

iPlanet Messaging Server 5.0

Syntax

dn, single-valued

Object Classes

[inetOrgPerson](#)

Definition

DN of the user who is responsible for paying the bills for this family account or group of users.

Example

```
mnggrpBillableUser: uid=John,ou=people,o=sesta.com,o=isp
```

OID

2.16.840.1.113730.3.1.711

mnggrpCurrentUsers

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes

[inetOrgPerson](#)

Definition

Current number of users allowed in the managed group. Intended for reporting purposes only. No operational impact.

Example

```
mnggrpCurrentUsers: 20
```

OID

2.16.840.1.113730.3.1.714

mnggrpDeletionPolicy

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single valued

Object Classes

[inetOrgPerson](#)

Definition

Reserved.

Example

TBD.

OID

2.16.840.1.113730.3.1.709

mnggrpMailQuota

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes

[inetOrgPerson](#)

Definition

Cumulative disk quota allowed for all users in the managed group. A value of -1 specifies that there is no limit on space used by users in the managed group. Intended for reporting purposes only. No operational impact.

Example

mnggrpMailQuota:-1

OID

2.16.840.1.113730.3.1.715

mnggrpMaxUsers

Origin

iPlanet Messaging Server 5.0

Syntax

int, single-valued

Object Classes

[inetOrgPerson](#)

Definition

Maximum number of users allowed in the managed group.

Example

30

OID

2.16.840.1.113730.3.1.713

mnggrpStatus

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes

[inetOrgPerson](#)

Definition

Reserved.

Example

TBD.

OID

2.16.840.1.113730.3.1.712

mnggrpUserClassOfServices

Origin

iPlanet Messaging Server 5.0

Syntax

cis, multi-valued

Object Classes

[inetOrgPerson](#)

Definition

Reserved.

Example

TBD.

OID

2.16.840.1.113730.3.1.716

nsDefaultMaxDeptSize

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single-valued

Object Classes

[nsManagedDomain](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Specifies the default size (in number of users) of a newly created department managed by Delegated Administrator.

Example

nsDefaultMaxDeptSize:20

OID

2.16.840.1.113730.3.1.562

nsMaxDepts

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single-valued

Object Classes

[organization](#), [nsManagedDomain](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Used with Delegated Administrator. Specifies the maximum number of group entries that can be created under this object.

Example

nsMaxDepts:200

OID

2.16.840.1.113730.3.1.557

nsMaxDomains

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single-valued

Object Classes

[nsManagedDomain](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

For use with Delegated Administrator. Specifies the maximum number of suborganizations allowed to be created under this object.

Example

```
nsMaxDomains:50
```

OID

```
2.16.840.1.113730.3.1.561
```

nsMaxMailLists

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single valued

Object Classes

[nsManagedDomain](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

For use with Delegated Administrator. Specifies the maximum number of mailing lists that can be created under this entry.

Example

```
nsMaxMailLists:200
```

OID

```
2.16.840.1.113730.3.1.559
```

nsMaxUsers

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single-valued

Object Classes

[organization](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

For use with Delegated Administrator. Specifies the maximum number of users that can be created under this entry.

Example

```
nsMaxUsers:750
```

OID

2.16.840.1.113730.3.1.555

nsNumDepts

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single-valued

Object Classes

[organization](#), [nsManagedDomain](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

For use with Delegated Administrator. Tracks the number of nested departments that exist under this object.

Example

nsNumDepts:35

OID

2.16.840.1.113730.3.1.556

nsNumDomains

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single-valued

Object Classes

[nsManagedDomain](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Used by Delegated Administrator. Tracks the number of suborganizations that exist under this object.

Example

nsNumDomains:5

OID

2.16.840.1.113730.3.1.560

nsNumMailLists

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single-valued

Object Classes

[nsManagedDomain](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Used by Delegated Administrator. Tracks the number of mail lists that exist under this object.

Example

```
nsNumMailLists:200
```

OID

2.16.840.1.113730.3.1.558

nsNumUsers

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

int, single-valued

Object Classes

[organization](#), [nsManagedDomain](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Tracks the number of users that can be created under this object.

Example

```
nsNumUsers:2000
```

OID

2.16.840.1.113730.3.1.554

| nsSearchFilter

Origin

Not currently used; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

cis, single-valued

Object Classes

[nsManagedPerson](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Reserved for future development for Delegated Administrator.

Example**OID**

2.16.840.1.113730.3.1.564

nsdaCapability

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

cis, single-valued

Object Classes

[nsManagedPerson](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Specifies whether a user can create a mail list. Supports Delegated Administrator.

Example

OID

2.16.840.1.113730.3.1.563

nsdaDomain

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

cis, single

Object Classes

[nsManagedPerson](#)

Definition

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Specifies the user's organization, for Delegated Administrator.

Example

OID

2.16.840.113730.3.1.600

nsdaModifiableBy

Origin

iPlanet Messaging Server 5.0; deprecated in Sun ONE Messaging Server 6.0 with Sun ONE LDAP Schema v.2.

Syntax

dn, single-valued

Object Classes[inetOrgPerson](#)**Definition**

This attribute is deprecated for Sun ONE LDAP Schema v.2, it is supported only for Sun ONE LDAP Schema v.1.

Used by Delegated Administrator. Specifies who has modify access to the object in which this attribute appears. DN of the administrator's group used with ACIs to grant rights to manage other groups.

Example

```
nsdaModifiableBy: cn=service administrators,ou=group,o=isp
```

OID

2.16.840.1.113730.3.1.565

preferredMailMessageStore

Origin

iPlanet Messaging Server 5.0

Syntax

cis, single-valued

Object Classes[mailDomain](#)**Definition**

Used by Sun ONE Messaging Server Delegated Administrator for Sun ONE LDAP Schema v.1 only.

Used to set the `mailMessageStore` attribute of newly created users. If missing, Delegate Administrator leaves the `mailMessageStore` attribute empty and the access server assumes that the user's mailbox is in the default partition of the server instance.

Example

```
preferredMailMessageStore: primary
```

OID

2.16.840.1.113730.3.1.762

preferredMailMessageStore

General Information

This appendix covers the following topics:

- [LDAP Overview](#)
- [Attribute Syntax](#)
- [Object Identifiers](#)
- [Standard Time Zones](#)

LDAP Overview

Sun™ Open Net Environment (ONE) Messaging Server and Sun™ ONE Calendar Server products include object classes and attributes defined by the Lightweight Directory Access Protocol (LDAP) and extensions to the standard LDAP schema that extend the basic functionality of LDAP.

Initially developed at the University of Michigan, LDAP is a lightweight version of the X.500 Directory Access Protocol. LDAP has become an Internet standard for directory services running over TCP/IP.

One or more LDAP servers contain the data that make up the LDAP directory. An LDAP directory stores information in object-oriented hierarchies of entries. Each entry is uniquely identified by a distinguished name, or DN. The DN consists of the comma-separated sequence of attributes and values that specify the unique location of an entry within the directory information tree. This provides a path of names tracing the entry back to the top of the directory hierarchy.

Attribute Syntax

Directory data is represented as attribute-value pairs. Any specific piece of information is associated with a descriptive attribute.

Each attribute has a corresponding syntax definition. The syntax definition describes the type of information provided by the attribute.

Table A-1 Syntax Types

Syntax Method	Abbreviation	Definition
Binary	bin	Attribute values are binary
Boolean	boolean	Two values possible: Yes or No, True or False, On or Off
Case Exact String	ces	Values are case sensitive
Case Ignore String	cis	Values are not case sensitive
Telephone	tel	Telephone numbers (identical to cis, but blanks and dashes (-) are ignored)
Distinguished Name	dn	Indicates values are DNs
Integer	int	Values are numbers
Operational	operational	Not displayed in search results

Required and allowed attributes for each object class are included in the object class listing.

Unless otherwise noted, attributes are assumed to be multi-valued, that is, more than one instance of the attribute can be specified. Attributes that are single-valued, that is, only one instance of the attribute can be specified, are noted as such in the Syntax heading, found in each attribute definition.

Object Identifiers

To meet LDAP and X.500 standards, all attributes and objects should have been assigned Object identifiers (OIDs). An OID is a sequence of integers, typically written as a dot-separated string. The OID identifies who first filed the name of the object or attribute with the standards committee.

In some cases, objects and attributes listed in this document do not have an OID assigned to them yet.

Standard Time Zones

The following two tables lists the time zones recognized by Calendar and Messaging Servers first in alphabetical order, and then by offset from Universal Time Constant (UTC).

Note that in some countries, like Israel, day-light savings time is not always observed every year. The decision is made year-by-year. Also, some individual states in the United States do not observe day-light savings time.

This means that some time offsets will not be accurate unless the definitions are updated as needed in the respective systems (see individual product documentation for information about adjusting time zone offsets).

The following table lists the time zones in alphabetical order.

Time Zone Name	Offset
Africa/Amman	+0300
Africa/Cairo	+0300
Africa/Casablanca	-0000
Africa/Johannesburg	+0200
Africa/Lagos	+0100
Africa/Tripoli	+0100
Africa/Windhoek	+0300
America/Adak	-0900
America/Anchorage	-0800
America/Buenos_Aires	-0300
America/Caracas	-0300
America/Chicago	-0500
America/Costa_Rica	-0600
America/Cuiaba	-0300
America/Denver	-0600
America/Godthab	-0200
America/Grand_Turk	-0400
America/Halifax	-0300
America/Havana	-0400
America/Indianapolis	-0500

Time Zone Name	Offset
America/Los_Angeles	-0700
America/Miquelon	-0200
America/New_York	-0400
America/Phoenix	-0700
America/Port-au-Prince	-0400
America/Santiago	-0300
America/Sao_Paulo	-0200
America/St_Johns	-0230
Asia/Alma-Ata	+0700
Asia/Anandyr	+1400
Asia/Aqtau	+0500
Asia/Aqtobe	+0600
Asia/Baku	+0500
Asia/Bangkok	+0700
Asia/Beirut	+0300
Asia/Bishkek	+0600
Asia/Calcutta	+0530
Asia/Dacca	+0600
Asia/Irkutsk	+0900
Asia/Jerusalem	+0300
Asia/Kabul	+0430
Asia/Kamchatka	+1300
Asia/Karachi	+0500
Asia/Katmandu	+0545
Asia/Krasnoyarsk	+0800
Asia/Magadan	+1200
Asia/Novosibirsk	+0700
Asia/Rangoon	+0630
Asia/Riyadh	+0300
Asia/Shanghai	+0800
Asia/Taipei	+0800

Time Zone Name	Offset
Asia/Tehran	+0400
Asia/Tokyo	+0900
Asia/Ulan_Bator	+0800
Asia/Vladivostok	+1100
Asia/Yakutsk	+1000
Asia/Yekaterinburg	+0600
Asia/Yerevan	+0400
Atlantic/Azores	-0000
Atlantic/Cape_Verde	-0100
Atlantic/South_Georgia	-0200
Atlantic/Stanley	-0300
Australia/Adelaide	+1030
Australia/Brisbane	+1000
Australia/Darwin	+0930
Australia/Hobart	+1100
Australia/Lord_Howe	+1100
Australia/Perth	+0800
Australia/Sydney	+1100
Europe/Bucharest	+0300
Europe/Istanbul	+0300
Europe/London	+0100
Europe/Minsk	+0300
Europe/Moscow	+0400
Europe/Paris	+0200
Europe/Riga	+0300
Europe/Samara	+0500
Europe/Simferopol	+0400
Europe/Warsaw	+0200
Pacific/Apia	-1100
Pacific/Auckland	+1300
Pacific/Chatham	+1345

Time Zone Name	Offset
Pacific/Easter	-0500
Pacific/Fiji	+1200
Pacific/Gambier	-0900
Pacific/Guadalcanal	+1100
Pacific/Honolulu	-1000
Pacific/Kiritimati	+1400
Pacific/Marquesas	-0930
Pacific/Norfolk	+1130
Pacific/Noumea	+1200
Pacific/Pitcairn	-0830
Pacific/Rarotonga	-0930
Pacific/Tongatapu	+1300

The following table lists the time zones by standard-time offset.

Offset	Time Zone Name
-1100	Pacific/Apia
-1000	Pacific/Honolulu
-0900	America/Adak
-0930	Pacific/Rarotonga
-0930	Pacific/Marquesas
-0900	Pacific/Gambier
-0830	Pacific/Pitcairn
-0800	America/Anchorage
-0700	America/Los_Angeles
-0700	America/Phoenix
-0600	America/Denver
-0600	America/Costa_Rica
-0500	America/Chicago
-0500	Pacific/Easter
-0500	America/Indianapolis

Offset	Time Zone Name
-0400	America/New_York
-0400	America/Havana
-0400	America/Port-au-Prince
-0400	America/Grand_Turk
-0300	America/Caracas
-0300	America/Cuiaba
-0300	America/Halifax
-0300	America/Santiago
-0300	Atlantic/Stanley
-0300	America/Buenos_Aires
-0230	America/St_Johns
-0200	America/Sao_Paulo
-0200	America/Miquelon
-0200	America/Godthab
-0200	Atlantic/South_Georgia
-0100	Atlantic/Cape_Verde
-0000	Atlantic/Azores
-0000	Africa/Casablanca
+0100	Europe/London
+0100	Africa/Lagos
+0100	Africa/Tripoli
+0200	Europe/Paris
+0200	Europe/Warsaw
+0200	Africa/Johannesburg
+0300	Europe/Bucharest
+0300	Europe/Istanbul
+0300	Africa/Cairo
+0300	Africa/Amman
+0300	Europe/Riga
+0300	Asia/Beirut
+0300	Africa/Windhoek

Offset	Time Zone Name
+0300	Europe/Minsk
+0300	Asia/Jerusalem
+0300	Asia/Riyadh
+0400	Europe/Simferopol
+0400	Europe/Moscow
+0400	Asia/Yerevan
+0400	Asia/Tehran
+0430	Asia/Kabul
+0500	Asia/Aqtau
+0500	Asia/Baku
+0500	Europe/Samara
+0500	Asia/Karachi
+0530	Asia/Calcutta
+0545	Asia/Katmandu
+0600	Asia/Aqtobe
+0600	Asia/Bishkek
+0600	Asia/Yekaterinburg
+0600	Asia/Dacca
+0630	Asia/Rangoon
+0700	Asia/Alma-Ata
+0700	Asia/Novosibirsk
+0700	Asia/Bangkok
+0800	Asia/Krasnoyarsk
+0800	Asia/Shanghai
+0800	Australia/Perth
+0800	Asia/Taipei
+0800	Asia/Ulan_Bator
+0900	Asia/Irkutsk
+0900	Asia/Tokyo
+0930	Australia/Darwin
+1000	Asia/Yakutsk

Offset	Time Zone Name
+1000	Australia/Brisbane
+1030	Australia/Adelaide
+1100	Australia/Sydney
+1100	Australia/Hobart
+1100	Asia/Vladivostok
+1100	Australia/Lord_Howe
+1100	Pacific/Guadalcanal
+1130	Pacific/Norfolk
+1200	Pacific/Noumea
+1200	Asia/Magadan
+1200	Pacific/Fiji
+1300	Pacific/Auckland
+1300	Asia/Kamchatka
+1300	Pacific/Tongatapu
+1345	Pacific/Chatham
+1400	Asia/Anandyr
+1400	Pacific/Kiritimati

Glossary

access control A method for controlling access to a server or to folders and files on a server.

Access Control Entry (ACE) A single item of information from an access control list. Also called access control information.

Access Control Information (ACI) See Access Control Entry. Information from an access control entry.

Access Control List (ACL) A set of data associated with a directory that defines the permissions that users and/or groups have for accessing it. Contains zero or more ACEs.

access control rules Rules specifying user permissions for a given set of directory entries or attributes.

access domain Limits access to certain Messaging Server operations from within a specified domain. For example, an access domain can be used to limit where mail for an account can be collected.

account Information that defines a specific user or user group. This information includes the user or group name, valid email address or addresses, and how and where email is delivered.

administration domain A region of administrative control. See also domain.

administration privileges A set of privileges that define a users administrative role.

administration server administrator User who has administrative privileges to start or stop a server even when there is no Directory Server connection. The administration server administrator has restricted server tasks (typically only Restart Server and Stop Server) for all servers in a local server group. When an administration server is installed, this administrator's entry is automatically created locally (this administrator is not a user in the user directory).

administrator A user with a defined set of administrative privileges. See also configuration administrator, Directory Manager, administration server administrator, server administrator, message store administrator, top-level administrator, domain administrator, organization administrator, family group administrator, mail list owner.

alias An alternate name of an email address.

allowed attributes The attributes that optionally can be present in entries using a particular object class, but are not required to be present. See also attributes, required attributes.

alternate address A secondary address for an account, generally a variation on the primary address. In some cases it is convenient to have more than one address for a single account.

attributes LDAP data is represented as attribute-value pairs. Any specific piece of information is associated with a descriptive attribute. See also allowed attributes, required attributes.

AUTH An SMTP command enabling an SMTP client to specify an authentication method to the server, perform an authentication protocol exchange, and, if necessary, negotiate a security layer for subsequent protocol interactions.

authentication (1) The process of proving the identity of a client user to a server or, (2) The process of proving the identity of the server to a client or another server.

base DN A distinguished name entry in the directory from which searches will occur. Also known as a search base. For example, `ou=people, o=siroe.com`.

bind DN A distinguished name used to authenticate to the Directory Server when performing an operation.

calendar identifier (calid) Identifies a calendar in the database. Must be A-Z, a-z, 0-9 (alphanumeric). A fully qualified calendar identifier consists of three parts, with the first two parts being optional: `uid` is the user's unique identifier in the authentication name space. `domain` is the domain to which the user belongs. `calid` is the local identifier for the calendar, where "local" means that it is unique within the `uid@domain` name space. The format is: `[uid]@[domain]:calid`

CNAME record A type of DNS record that maps a domain name alias to a domain name.

cn LDAP alias for common name.

CLI Command-Line Interface.

command-line interface Command that can be executed from the command line. Also called utility.

configuration administrator Person who has administrative privileges to manage servers and configuration directory data in the entire Sun™ ONE. The configuration administrator has unrestricted access to all resources in the Sun ONE topology. This is the only administrator who can assign server access to other administrators. The configuration administrator initially manages administrative configuration until the administrators group and its members are in place.

Configuration Directory Server A Directory Server that maintains configuration information for a server or set of servers.

data store A store that contains directory information, typically for an entire directory information tree.

DC Tree Domain Component tree. A directory information tree that mirrors the DNS network syntax. An example of a distinguished name in a DC Tree would be `cn=billbob,dc=bridge,dc=net,o=internet`.

Delegated Administrator for Messaging A set of interfaces (GUI and utilities) that allow domain administrators to add and modify users and groups to a hosted domain.

directory context The point in the directory tree information at which a search begins for entries used to authenticate a user and password for message store access. See also base DN.

directory entry A set of directory attributes and their values identified by its distinguished name. Each entry contains an object class attribute that specifies the kind of object the entry describes and defines the set of attributes it contains.

directory information tree The tree-like hierarchical structure in which directory entries are organized. Also called a DIT. DITs can be organized along the DNS (DC Trees) or Open Systems Interconnect networks (OSI trees).

directory lookup The process of searching the directory for information on a given user or resource, based on that user or resource's name or other characteristic.

Directory Manager User who has administrative privileges to the directory server database. Access control does not apply to this user (think of the directory manager as the directory's superuser).

directory schema The set of rules that defines the data that can be stored in the directory.

Directory Server The Sun ONE directory service based on LDAP. See also directory service, Lightweight Directory Access Protocol, Configuration Directory Server, User/Groups Directory Server.

directory service A logically centralized repository of information about people and resources within an organization. See also Lightweight Directory Access Protocol.

distinguished name The comma-separated sequence of attributes and values that specify the unique location of an entry within the directory information tree. Often abbreviated as DN.

DIT See directory information tree.

DN See distinguished name.

dn LDAP alias for distinguished name. See also distinguished name.

DNS See Domain Name System.

DNS alias A host name that the DNS server recognizes as pointing to a different host—specifically a DNS CNAME record. Machines always have one real name, but they can have one or more aliases. For example, `www.siroe.domain` might be an alias that points to a real machine called `realthing.siroe.domain` where the server currently exists.

DNS database A database of domain names (host names) and their corresponding IP addresses.

DNS domain A group of computers whose host names share a common suffix, the domain name. Syntactically, an Internet domain name consists of a sequence of names (labels) separated by periods (dots), for example, `corp.mktng.siroe.com`. See also **domain**.

domain Resources under control of a single computer system. See also administration domain, DNS domain, hosted domain, virtual domain.

domain name space The name space within which identifiers for users, resources and groups are unique. A given identifier can be used in different domains.

domain administrator User who has administrative privileges to create, modify, and delete mail users, mail lists, and family accounts in a hosted domain by using the Delegated Administrator for Messaging and Collaboration GUI or CLIs. By default, this user can act as a message store administrator for all messaging servers in the topology.

domain alias A domain entry that points to another domain. By using aliases, hosted domains can have several domain names.

domain hosting The ability to host one or more domains on a shared messaging server. For example, the domains `siroe.com` and `sesta.org` might both be hosted on the `siroe.net` mail server. Users send mail to and receive mail from the hosted domain—the name of the mail server does not appear in the email address.

domain name (1) A host name used in an email address. (2) A unique name that defines an administrative organization. Domains can contain other domains. Domain names are interpreted from right to left. For example, `siroe.com` is both the domain name of the Siroe Company and a subdomain of the top-level `com` domain. The `siroe.com` domain can be further divided into subdomains such as `corp.siroe.com`, and so on. See also host name, fully qualified domain name.

Domain Name System (DNS) A distributed name resolution software that allows computers to locate other computers on a network or the Internet by domain name. The system associates standard IP addresses with host names (such as `www.siroe.com`). Machines normally get this information from a DNS server. DNS servers provide a distributed, replicated, data query service for translating hostnames into Internet addresses. See also A record, MX record, CNAME record.

domain organization A subdomain below a hosted domain in the Organization Tree. Domain organizations are useful for companies that wish to organize their user and group entries along departmental lines.

dynamic group A mail group defined by an LDAP search URL. Users usually join the group by setting an LDAP attribute in their directory entry.

family group administrator User who has administrative privileges to add and remove family members in a family group. This user can grant family group administrative access to other members of group.

fully qualified domain name (FQDN) The unique name that identifies a specific Internet host. See also domain name.

group A group of LDAP mail entries that are organized under a distinguished name. Usually used as a mail list, but may also be used to grant certain administrative privileges to members of the group. See also dynamic group, static group.

GUI Graphical User Interface

host The machine on which one or more servers reside.

hosted domain An email domain that is outsourced by an ISP. That is, the ISP provides email domain hosting for an organization by operating and maintaining the email services for that organization. A hosted domain shares the same Messaging Server host with other hosted domains. In earlier LDAP-based email systems, a domain was supported by one or more email server hosts. With Messaging Server, many domains can be hosted on a single server. For each hosted domain, there is an LDAP entry that points to the user and group container for the domain. Hosted domains are also called virtual hosted domains or virtual domains. See also domain, virtual domain.

host name The name of a particular machine within a domain. The host name is the IP host name, which might be either a “short-form” host name (for example, mail) or a fully qualified host name. The fully qualified host name consists of two parts: the host name and the domain name. For example, mail.siroe.com is the machine mail in the domain siroe.com. Host names must be unique within their domains. Your organization can have multiple machines named mail, as long as the machines reside in different subdomains; for example, mail.corp.siroe.com and mail.field.siroe.com. Host names always map to a specific IP address. See also domain name, fully qualified domain name, IP address.

Identity Server (IS) The Sun ONE product responsible for implementing Sun ONE Schema, v.2. It is used for SSO authentication and contains administrative tools. The User Management Utility uses the IS SDK as the backend of its command line utilities.

INBOX The name reserved for a user’s default mailbox for mail delivery. INBOX is the only folder name that is case insensitive. For example: INBOX, Inbox, and inbox are all valid names for a users default mailbox.

Internet The name given to the worldwide network of networks that uses TCP/IP protocols.

Internet Protocol (IP) The basic network-layer protocol on which the Internet and intranets are based.

internet protocol address See IP address.

IP See Internet Protocol.

IP address A set of numbers, separated by dots, such as 198.93.93.10, that specifies the actual location of a machine on an intranet or the Internet. A 32-bit address assigned to hosts using TCP/IP.

knowledge information Part of the directory service infrastructure information. The directory server uses knowledge information to pass requests for information to other servers.

LDAP See Lightweight Directory Access Protocol.

LDAP Data Interchange Format (LDIF) The format used to represent Directory Server entries in text form.

LDAP filter A method of specifying a set of entries, based on the presence of a particular attribute or attribute value.

LDAP referrals An LDAP entry that consists of a symbolic link (referral) to another LDAP entry. An LDAP referral consists of an LDAP host and a distinguished name. LDAP referrals are often used to reference existing LDAP data so that this data does not have to be replicated. They are also used to maintain compatibility for programs that depend on a particular entry that may have been moved.

LDAP search string A string with replaceable parameters that defines the attributes used for directory searches. For example, an LDAP search string of "uid=%s" means that searches are based on the user ID attribute.

LDAP Server A software server that maintains an LDAP directory and services queries to the directory. The Sun ONE Directory Services are implementations of an LDAP Server.

LDBM LDAP Data Base Manager.

LDIF See LDAP Data Interchange Format.

Lightweight Directory Access Protocol (LDAP) Directory service protocol designed to run over TCP/IP and across multiple platforms. A simplification of the X.500 Directory Access Protocol (DAP) that allows a single point of management for storage, retrieval, and distribution of information, including user profiles, mail lists, and configuration data across Sun ONE servers. The Sun ONE Directory Server uses the LDAP protocol.

local part The part of an email address that identifies the recipient. See also domain part.

mailbox A place where messages are stored and viewed. See also folder.

mail list A list of email addresses to which a message can be sent by way of a mail list address. Sometimes called a group.

mail list owner A user who has administrative privileges to add members to and delete members from the mail list.

managed object A collection of configurable attributes, for example, a collection of attributes for the directory service.

master directory server The directory server that contains the data that will be replicated.

member A user or group who receives a copy of an email addressed to a mail list. See also mail list, expansion, moderator, and owner.

message quota A limit defining how much disk space a particular folder can consume.

Messaging Server administrator The administrator whose privileges include installation and administration of an Sun ONE Messaging Server instance.

name resolution The process of mapping an IP address to the corresponding name. See also DNS.

namespace The tree structure of an LDAP directory. See also directory information tree.

naming attribute The final attribute in a directory information tree distinguished name. See also relative distinguished name.

naming context A specific suffix of a directory information tree that is identified by its DN. In Sun ONE Directory Server, specific types of directory information are stored in naming contexts. For example, a naming context which stores all entries for marketing employees in the Siroe Corporation at the Boston office might be called `ou=mktg, ou=Boston, o=siroe, c=US`.

node An entry in the DIT.

object class A template specifying the kind of object the entry describes and the set of attributes it contains. For example, Sun ONE Directory Server specifies an `emailPerson` object class which has attributes such as `commonname`, `mail` (email address), `mailHost`, and `mailQuota`.

object identifier (OID) An OID is a sequence of integers, typically written as a dot-separated string. An OID is assigned to each attribute and object class to conform with the LDAP and X.500 standards.

OID See object identifier (OID).

organization administrator User who has administrative privileges to create, modify, and delete mail users and mail lists in an organization or suborganization by using the Delegated Administrator for Messaging and Collaboration GUI or CLIs.

OSI tree A directory information tree that mirrors the Open Systems Interconnect network syntax. An example of a distinguished name in an OSI tree would be `cn=billt,o=bridge,c=us`.

personal folder A folder that can be read only by the owner. See also shared folder.

port number A number that specifies an individual TCP/IP application on a host machine, providing a destination for transmitted data.

protocol A formal description of messages to be exchanged and rules to be followed for two or more systems to exchange information.

provisioning The process of adding, modifying or deleting entries in the Sun ONE Directory Server. These entries include users and groups and domain information.

RDN Relative distinguished name. The name of the actual entry itself, before the entry's ancestors have been appended to the string to form the full distinguished name.

referral A process by which the directory server returns an information request to the client that submitted it, with information about the Directory Service Agent (DSA) that the client should contact with the request. See also knowledge information.

relative distinguished name See RDN.

replica directory server The directory that will receive a copy of all or part of the data.

required attributes Attributes that must be present in entries using a particular object class. See also allowed attributes, attributes.

reverse DNS lookup The process of querying the DNS to resolve a numeric IP address into the equivalent fully qualified domain name.

RFC Request For Comments. The document series, begun in 1969, describes the Internet suite of protocols and related experiments. Not all (in fact very few) RFCs describe Internet standards, but all Internet standards are published as RFCs. See <http://www.imc.org/rfcs.html>.

root entry The top-level entry of the directory information tree (DIT) hierarchy.

schema Definitions, including structure and syntax, of the types of information that can be stored as entries in Sun ONE Directory Server. When information that does not match the schema is stored in the directory, clients attempting to access the directory might be unable to display the proper results.

search base See base DN.

server administrator Person who performs server management tasks. The server administrator provides restricted access to tasks for a particular server, depending upon task ACIs. The configuration administrator must assign user access to a server. Once a user has server access permissions, that user is a server administrator who can provide server access permissions to users.

shared folder A folder that can be read by more than one person. Shared folders have an owner who can specify read access to the folder and who can delete messages from the shared folder. The shared folder can also have a moderator who can edit, block, or forward incoming messages. Only IMAP folders can be shared. See also personal folder.

SIEVE A scripting language for filtering mail. Messaging and Collaboration supports the SIEVE rules as specified in RFC 3028 and in the relational extension to SIEVE found in RFC 3431.

SIMS Sun Internet Mail Server.

sn Aliased directory attribute for surname.

static group A mail group defined statically by enumerating each group member. See also dynamic group.

subdomain A portion of a domain. For example, in the domain name `corp.siroe.com`, `corp` is a subdomain of the domain `siroe.com`. See also host name, fully qualified domain name.

subnet The portion of an IP address that identifies a block of host IDs.

subordinate reference The naming context that is a child of the naming context held by your directory server. See also knowledge information.

synchronization The update of data by a master directory server to a replica directory server.

TCP See Transmission Control Protocol.

TCP/IP See Transmission Control Protocol/Internet Protocol.

top-level administrator User who has administrative privileges to create, modify, and delete mail users, mail lists, family accounts, and domains in an entire Messaging Server namespace by using the Delegated Administrator for Messaging and Collaboration GUI or CLIs. By default, this user can act as a message store administrator for all messaging servers in the topology.

Transmission Control Protocol (TCP) The basic transport protocol in the Internet protocol suite that provides reliable, connection-oriented stream service between two hosts.

Transmission Control Protocol/Internet Protocol (TCP/IP) The name given to the collection of network protocols used by the Internet protocol suite. The name refers to the two primary network protocols of the suite: TCP (Transmission Control Protocol), the transport layer protocol, and IP (Internet Protocol), the network layer protocol.

UID (1) User identification. A unique string identifying a user to a system. Also referred to as a userID. (2) Aliased directory attribute for userID (login name).

upper reference Indicates the directory server that holds the naming context above your directory server's naming context in the directory information tree (DIT).

user account An account for accessing a server, maintained as an entry on a directory server.

User/Groups Directory Server A Directory Server that maintains information about users and groups in an organization.

user entry or user profile Fields that describe information about each user, required and optional, examples are: distinguished name, full name, title, telephone number, pager number, login name, password, home directory, and so on.

user folders A user's email mailboxes.

User Management Utility The Sun ONE command line interface (`commadmin`) for adding, deleting and modifying users, groups and domains.

user quota The amount of space, configured by the system administrator, allocated to a user for email messages.

virtual domain (1) An ISP hosted domain. (2) A domain name added by the Messaging Multiplexor to a client's user ID for LDAP searching and for logging into a mailbox server. See also domain, hosted domain.

Index

A

- access
 - reactivate [113](#)
 - remove [113](#)
 - suspend [113](#)
- access filter
 - user [118](#), [130](#)
- access rights, public folder [145](#)
- account ID, billing [111](#)
- adminRole, attribute [61](#)
- aliasedObjectName, attribute [62](#)
- allowed broadcaster [158](#)
 - determining policy [161](#)
- allowed disk space [147](#)
- attachment quota [125](#)
- attribute syntax [262](#)
- attributes
 - definitions [61](#)
 - list of [55](#)
- audience [13](#)
- authentication [106](#)
- automatic response [123](#)
 - duration [124](#)
 - internal [124](#)
- autoreply [123](#), [129](#)
 - duration [124](#)
 - internal [124](#)

B

- billable user [248](#)
- billing, account ID [111](#)
- birthday attribute [66](#)
- businessCategory, attribute [63](#)

C

- calCalURI, attribute [63](#)
- calendar [63](#)
 - busy time data [64](#)
 - default URI [63](#)
- calendar groups [99](#)
- calFBURL, attribute [64](#)
- catchall address [120](#)
- challenge phrase [112](#)
 - response to [112](#)
- cn, attribute [64](#)
- co, attribute [65](#)
- commonName, attribute [66](#)
- countryName, attribute [66](#)

D

- daemon_list [131](#)
- dataSource, attribute [66](#)
- dateOfBirth, attribute [66](#)
- dc (domain component)
 - domain component node [103](#)
- dc (domain component), attribute [67](#)
- delivery paths [128](#)
- deny filter [118, 130](#)
- description, attribute [67](#)
- distinguished name (DN) [105](#)
 - administrator's group [259](#)
 - billable user [248](#)
 - family account [242](#)
 - forming, in PAB entries [184](#)
 - mailing list [156](#)
- distribution list
 - describing [173](#)
- document conventions [15](#)
- documentation
 - where to find Messaging Server
 - documentation [16](#)
- domain
 - primary [172](#)
 - vanity [172](#)
- domain access
 - reactivate [108](#)
 - remove [108](#)
 - suspend [108](#)
- domain alias entry [67](#)
 - domain component [67](#)
- domain component [67](#)
- domain name
 - multiple DC nodes [103](#)
- domain name (DN)
 - overriding [69, 240](#)
- domain suborganizations [26](#)
- domain, object class [32](#)
- domains, hosted [25](#)
- domainUIDSeparator, attribute [68, 239](#)
- domOrgMaxUsers, attribute [69, 240](#)
- domOrgNumUsers, attribute [70, 241](#)
- duplicate deliveries [170](#)

E

- echo [122](#)
- error message [165](#)

F

- facsimileTelephoneNumber, attribute [70](#)
- family group
 - manager [177](#)
- file
 - local path [128](#)
- filter
 - access [118, 130](#)
 - deny [118, 130](#)
- forwarded to
 - moderator [166](#)

G

- givenName, attribute [71](#)
- group
 - within organization [176](#)
- group membership
 - restrictions [245](#)
 - visibility [245](#)
- groupOfUniqueNames, object class [33](#)
- groups, calendar [99](#)

H

- host, defined [276](#)
- hosted domains [25](#)

I

- icsAdministrator, object class [34](#)

- icsAdminRole, attribute 71
- icsAlias, attribute 72
- icsAllowedServiceAccess, attribute 72
- icsAllowRights, attribute 73
- icsAnonymousAllowWrite, attribute 75
- icsAnonymousCalendar, attribute 76
- icsAnonymousDefaultSet, attribute 76
- icsAnonymousLogin, attribute 77
- icsAnonymousSet, attribute 77
- icsCalendar, attribute 78
- icsCalendarDomain, object class 35
- icsCalendarDWPHost, object class 35
- icsCalendarGroup object class 36
- icsCalendarOwned, attribute 78
- icsCalendarResource, object class 37
- icsCalendarUser, object class 37
- icsCapacity, attribute 79
- icsContact, attribute 79
- icsDefaultAccess, attribute 80
- icsDefaultSet, attribute 80
- icsDomainAllowed, attribute 81
- icsDomainNames, attribute 82
- icsDomainNotAllowed, attribute 83
- icsDWPBackEndHosts, attribute 84
- icsDWPHost, attribute 85
- icsExtended, attribute 85
- icsExtendedDomainPrefs, attribute 86
- icsExtendedGroupPrefs, attribute 87
- icsExtendedResourcePrefs, attribute 88
- icsExtendedUserPrefs, attribute 88
- icsFirstDay, attribute 92
- icsFreeBusy, attribute 92
- icsGeo, attribute 93
- icsMandatorySubscribed, attribute 93
- icsMandatoryView, attribute 94
- icsPartition, attribute 94
- icsPreferredHost, attribute 95
- icsQuota, attribute 96
- icsRecurrenceBound, attribute 96
- icsRecurrenceDate, attribute 97
- icsRegularExpressions, attribute 97
- icsSessionTimeout, attribute 98
- icsSet, attribute 98
- icsSourceHtml, attribute 100
- icsStatus, attribute 100
- icsSubscribed, attribute 102
- icsTimezone, attribute 102
- inetAdmin, object class 38
- inetCanonicalDomainName, attribute 103
- inetCOS (class of service), attribute
COS definitions 104
- inetDomain, object class 39
- inetDomainAlias, object class 40
- inetDomainAuthInfo, object class 40
- inetDomainBaseDN, attribute 105
- inetDomainCertMap 106
- inetDomainCertMap, attribute 106
- inetDomainOrg, object class 230
- inetDomainSearchFilter, attribute 106
- inetDomainStatus, attribute 107
- inetLocalMailRecipient, object class 41
- inetMailAdministrator, object class 42
- inetMailGroup
connection with mgrpDisallowedDomain 164
- inetMailGroup, object class 43
- inetMailGroupManagement, object class 231
- inetMailGroupStatus, attribute 109
- inetMailUser, object class 43
- inetManagedGroup, object class 231
- inetOrgPerson, object class 44
- inetResource, object class 45
- inetResourceStatus, attribute 110
- inetSubscriber, object class 45
- inetSubscriberAccountId 110
- inetSubscriberAccountId, attribute 111
- inetSubscriberChallenge, attribute 112
- inetSubscriberResponse, attribute 112
- inetUser, object class 46
- inetUserHttpURL, attribute 113
- inetUserStatus, attribute 113
- ipUser, object class 47

L

- language
 - preferred by user [179](#)
- LDAP overview [261](#)
- list of attributes [55](#)
- list of object classes
 - object classes
 - list of [31](#), [189](#), [229](#)
- local path [128](#)
- locale
 - preferred by user [220](#)
- login sequence, replaying [116](#)
- login string, reconstructing [116](#)

M

- mail group
 - message size received [166](#)
- mail group membership
 - alternative specification method [162](#)
 - restrictions [245](#)
 - visibility [245](#)
- mail group, allowed incoming mail
 - by domain [159](#)
 - by user [158](#)
- mail group, disallowed incoming mail
 - by domain [164](#)
 - by user [163](#)
- mail quota
 - managed group [249](#)
 - user [147](#)
- mail, attribute [115](#)
- mailAccessProxyPreAuth, attribute [115](#)
- mailAccessProxyReplay, attribute [116](#)
- mailAdminRole, attribute [117](#)
- mailAllowedServiceAccess
 - connection with mailDomainStatus [138](#)
- mailAllowedServiceAccess, attribute [117](#)
- mailAlternateAddress, attribute [120](#)
- mailAntiUBEService, attribute [121](#)
- mailAutoReplyMode, attribute
 - autoreply [122](#)
- mailAutoReplySubject, attribute [123](#)
- mailAutoReplyText
 - connection to mailAutoReplyMode [122](#)
- mailAutoReplyText, attribute [123](#)
- mailAutoReplyTextInternal, attribute [124](#)
- mailAutoReplyTimeOut, attribute [124](#)
- mailClientAttachmentQuota [125](#)
- mailClientAttachmentQuota, attribute [125](#)
- mailConversionTag, attribute [125](#)
- mailDeferProcessing, attribute [126](#)
- mailDeliveryFileURL, attribute [127](#)
- mailDeliveryOption [128](#)
 - mailDeliveryOption=forward [141](#)
 - mailDeliveryOption=program [145](#)
- mailDeliveryOption, attribute
 - mailDeliveryOption=file [128](#)
- mailDomain, object class [48](#)
- mailDomainAllowedServiceAccess
 - connection with mailDomainStatus [138](#)
- mailDomainAllowedServiceAccess, attribute [130](#)
- mailDomainMsgMaxBlocks, attribute [134](#)
- mailDomainMsgQuota [134](#)
- mailDomainMsgQuota, attribute [134](#)
- mailDomainStatus, attribute [137](#)
- mailDomainWelcomeMessage, attribute [139](#)
- mailEquivalentAddress, attribute [139](#)
- mailFolderName, attribute [140](#)
- mailForwardingAddress, attribute [141](#)
- mailHost
 - setting up [181](#)
- mailHost, attribute [141](#)
- mailing lists
 - allowed membership [242](#)
 - denied membership [243](#)
 - group appearance on [244](#)
- mailMessageStore
 - setting up [181](#), [259](#)
- mailMessageStore, attribute [142](#)
- mailMsgMaxBlocks, attribute [143](#)
- mailMsgQuota, attribute [143](#)
- mailProgramDeliveryInfo, attribute [144](#)
- mailPublicFolderDefaultRights, attribute [145](#)

- mailQuota [147](#)
- mailQuota, attribute [147](#)
- mailRejectText, attribute [148](#)
- mailRoutingAddress, attribute [149](#)
- mailRoutingHosts, attribute [149](#)
- mailRoutingSmartHost, attribute [150](#)
- mailSieveRuleSource, attribute [151](#)
- mailSMTPSubmitChannel, attribute [153](#)
- mailto syntax [165](#)
- mailUserStatus, attribute [153](#)
- managed group
 - billable user [248](#)
 - cumulative disk quota [249](#)
 - current status [250](#)
 - maximum users [250](#)
 - number of users [248](#)
- maximum message size allowed
 - to a group [166](#)
- maximum messages allowed
 - user [143](#)
- maximum pab entries allowed
 - user [155](#)
- maximum size message [143](#)
- maximum users allowed
 - domain [69](#), [240](#)
 - managed group [250](#)
- maxPabEntries, attribute [155](#)
- memberOf, attribute [155](#)
- memberOfManagedGroup, attribute [241](#)
- memberOfPAB, attribute [156](#)
- memberOfPABGroup, attribute [156](#)
- memberURL, attribute [157](#)
- message delivery, guaranteeing [153](#)
- message filtering, Sieve rules [152](#)
- message quota [134](#)
- message size
 - to mailGroup [166](#)
- message store
 - partition name [142](#)
- Messaging Server
 - documentation [16](#)
- mgmanAllowSubscribe, attribute [242](#)
- mgmanDenySubscribe, attribute [243](#)
- mgmanGoodbyeText, attribute [243](#)
- mgmanHidden, attribute [244](#)
- mgmanIntroText, attribute [244](#)
- mgmanJoinability, attribute [245](#)
- mgmanMemberVisibility, attribute [245](#)
- mgmanVisibility, attribute [247](#)
- mgrpAddHeader, attribute [158](#)
- mgrpAllowedBroadcaster, attribute [158](#)
- mgrpAllowedDomain, attribute [159](#)
- mgrpAuthPassword, attribute [160](#)
- mgrpBroadcasterPolicy, attribute [161](#)
- mgrpDeliverTo, attribute [162](#)
- mgrpDisallowedBroadcaster, attribute [163](#)
- mgrpDisallowedDomain, attribute [164](#)
- mgrpErrorsTo, attribute [165](#)
- mgrpModerator, attribute [165](#)
- mgrpMsgMaxSize, attribute [166](#)
- mgrpMsgPrefixText, attribute [167](#)
- mgrpMsgRejectAction, attribute [168](#)
- mgrpMsgRejectText, attribute [169](#)
- mgrpMsgSuffixText, attribute [169](#)
- mgrpNoDuplicateCheck, attribute [170](#)
- mgrpRemoveHeader, attribute [170](#)
- mgrpRFC822MailMember, attribute [171](#)
- mnggrpAdditionPolicy, attribute [247](#)
- mnggrpBillableUser, attribute [248](#)
- mnggrpCurrentUsers, attribute [248](#)
- mnggrpDeletionPolicy, attribute [249](#)
- mnggrpMailQuota, attribute [249](#)
- mnggrpMaxUsers, attribute [250](#)
- mnggrpStatus, attribute [250](#)
- mnggrpUserClassOfServices, attribute [251](#)
- moderator
 - messages forwarded to [166](#)
- msgVanityDomain, attribute [172](#)
- msgVanityDomainUser, object class [49](#)
- MTA
 - host name, final destination [142](#)
 - host name, user's domain [150](#)
- multiLineDescription, attribute [173](#)

N

nickName, attribute [173](#)
 nsdaCapability, attribute [257](#)
 nsdaDomain, attribute [258](#)
 nsdaModifiableBy, attribute [258](#)
 nsDefaultMaxDeptSize, attribute [251](#)
 nsManagedDept, object class [232](#)
 nsManagedDeptAdminGroup, object class [233](#)
 nsManagedDomain, object class [233](#)
 nsManagedFamilyGroup, object class [234](#)
 nsManagedISP, object class [235](#)
 nsManagedMailList, object class [235](#)
 nsManagedOrgUnit, object class [236](#)
 nsManagedPerson, object class [237](#)
 nsMaxDepts, attribute [252](#)
 nsMaxDomains, attribute [252](#)
 nsMaxMailingLists, attribute [253](#)
 nsMaxUsers, attribute [254](#)
 nsNumDepts, attribute [254](#)
 nsNumDomains, attribute [255](#)
 nsNumMailLists, attribute [255](#)
 nsNumUsers, attribute [256](#)
 nsSearchFilter, attribute [257](#)
 nsUniquenessDomain, object class [237](#)
 nswcalDisallowAccess, attribute [174](#)
 nswmExtendedUserPrefs, attribute [174](#)

O

o, attribute [175](#)
 object classes
 definitions [32](#)
 object identifiers [262](#)
 objectClass, attribute [175](#)
 OIDs [262](#)
 organization subtree [105](#)
 organization, object class [50](#)
 organizationalUnit, object class [50](#)
 organizationName, attribute [176](#)
 organizationUnitName [176](#)

organizationUnitName, attribute [176](#)
 ou (organizationUnitName), attribute [176](#)
 owner, attribute [177](#)

P

pab, object class [51](#)
 pabGroup, object class [52](#)
 pabPerson, object class [53](#)
 pabURI, attribute [177](#)
 personal address book (pab)
 container [178](#)
 maximum entries [155](#)
 unique name (un) of pab [156](#)
 unique name (un) of personal group(s) [156](#)
 postalAddress, attribute [179](#)
 preauthentication [115](#)
 preferredLanguage, attribute [179](#)
 preferredLocale, attribute [220](#)
 preferredMailHost, attribute [180](#)
 preferredMailMessageStore, attribute [181](#), [259](#)
 privileges, administrative [117](#)
 Program approval process [145](#)
 program delivery [144](#)
 proxy authentication [117](#)
 public folder access rights [145](#)

Q

quota [147](#)
 mailClientAttachmentQuota [125](#)
 mailDomainMsgQuota [134](#)
 mailMsgQuota [143](#)
 mnggrpMailQuota [249](#)
 quota reporting tools
 mailDomainMsgQuota [135](#)
 quotas
 hard [144](#)
 soft [144](#)

R

- references, resolved [145](#)
- RFC 1959 [163](#)
- RFC 2256 [40](#)
- RFC 2739 [63](#)
- RFC 2798 [179](#)
- RFC 822 [41](#), [163](#), [165](#)
 - mgrpRFC822MailMember [171](#)
- RFC1959 [162](#)
- RFC822 [159](#)
 - alternate email address [120](#)
- rights
 - to manage other groups [259](#)

S

- seeAlso, attribute [182](#)
- service- specific object classes [19](#), [21](#)
- service_list [118](#)
- shared classes [19](#), [21](#)
- sieve rule [151](#)
- Sieve rules, message filters [152](#)
- size limit on MTA blocks units [134](#)
- sn, attribute [182](#)
- standard time zones [263](#)
- status
 - internet domain [107](#)
 - internet mail group [109](#)
 - internet user [113](#)
 - mail domain [137](#)
 - mail user [153](#)
 - managed group [250](#)
- status attributes
 - interaction between [114](#), [138](#), [154](#)
- subject text [123](#)
- suborganizations [26](#)
- subscriber [112](#)
- subtree [105](#)
- sunKeyValue, attribute [221](#)
- sunManagedOrganization, object class [198](#), [199](#)
- sunNameSpace, object class [199](#)

- sunNameSpaceUniqueAttrs, attribute [223](#)
- sunServiceComponent, object class [201](#)
- sunServiceId, attribute [227](#)
- sunSmsPriority, attribute [228](#)
- sunXmlKeyValue, attribute [228](#)
- syntax, attributes [262](#)

T

- tag, program [66](#)
- telephoneNumber, attribute [183](#)
- time zones, list of valid [263](#)

U

- uid, attribute [183](#)
- un, attribute [184](#)
- unique name (un)
 - personal address book [156](#)
 - personal group [157](#)
- uniqueMember, attribute [185](#)
- user [70](#), [241](#)
- user identification, compound [68](#), [107](#), [239](#)
- user rules [151](#)
- userid, attribute [185](#)
- userPassword, attribute [185](#)
- userPresenceProfile, object class [53](#), [201](#)

V

- vacationEndDate, attribute [186](#)
- vacationStartDate, attribute [187](#)
- vanity domain
 - creating [172](#)

W

Web content

publishing [113](#)

white-pages lookup applications [115](#)

who should read [13](#)