



# **Sun Cluster Data Service for WebSphere Message Broker Guide for Solaris OS**



Sun Microsystems, Inc.  
4150 Network Circle  
Santa Clara, CA 95054  
U.S.A.

Part No: 819-3068-10  
December 2006, Revision A

Copyright 2006 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more U.S. patents or pending patent applications in the U.S. and in other countries.

U.S. Government Rights – Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

This distribution may include materials developed by third parties.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, the Solaris logo, the Java Coffee Cup logo, docs.sun.com, SunOS is a trademark or registered trademark of Sun Microsystems, Inc. in the United States and other countries. Java, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Products covered by and information contained in this publication are controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical or biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

---

Copyright 2006 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. Tous droits réservés.

Sun Microsystems, Inc. détient les droits de propriété intellectuelle relatifs à la technologie incorporée dans le produit qui est décrit dans ce document. En particulier, et ce sans limitation, ces droits de propriété intellectuelle peuvent inclure un ou plusieurs brevets américains ou des applications de brevet en attente aux États-Unis et dans d'autres pays.

Cette distribution peut comprendre des composants développés par des tierces personnes.

Certains composants de ce produit peuvent être dérivés du logiciel Berkeley BSD, licenciés par l'Université de Californie. UNIX est une marque déposée aux États-Unis et dans d'autres pays; elle est licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, le logo Solaris, le logo Java Coffee Cup, docs.sun.com, SunOS is a trademark or registered trademark of Sun Microsystems, Inc. in the United States and other countries. Java et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux États-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux États-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui, en outre, se conforment aux licences écrites de Sun.

Les produits qui font l'objet de cette publication et les informations qu'il contient sont régis par la législation américaine en matière de contrôle des exportations et peuvent être soumis au droit d'autres pays dans le domaine des exportations et importations. Les utilisations finales, ou utilisateurs finaux, pour des armes nucléaires, des missiles, des armes chimiques ou biologiques ou pour le nucléaire maritime, directement ou indirectement, sont strictement interdites. Les exportations ou réexportations vers des pays sous embargo des États-Unis, ou vers des entités figurant sur les listes d'exclusion d'exportation américaines, y compris, mais de manière non exclusive, la liste de personnes qui font objet d'un ordre de ne pas participer, d'une façon directe ou indirecte, aux exportations des produits ou des services qui sont régis par la législation américaine en matière de contrôle des exportations et la liste de ressortissants spécifiquement désignés, sont rigoureusement interdites.

LA DOCUMENTATION EST FOURNIE "EN L'ETAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFACON.

# Contents

---

<b>Preface</b> .....	5
<b>Installing and Configuring Sun Cluster HA for WebSphere Message Broker</b> .....	9
Sun Cluster HA for WebSphere Message Broker Overview .....	9
Overview of Installing and Configuring Sun Cluster HA for WebSphere Message Broker .....	10
Planning the Sun Cluster HA for WebSphere Message Broker Installation and Configuration .....	11
Configuration Restrictions .....	11
Configuration Requirements .....	14
Installing and Configuring WebSphere Message Broker .....	15
▼ How to Install and Configure WebSphere Message Broker .....	15
Verifying the Installation and Configuration of WebSphere Message Broker .....	19
▼ How to Verify the Installation and Configuration of WebSphere Message Broker .....	19
Installing the Sun Cluster HA for WebSphere Message Broker Packages .....	22
▼ How to Install the Sun Cluster HA for WebSphere Message Broker Packages .....	22
Registering and Configuring Sun Cluster HA for WebSphere Message Broker .....	24
▼ How to Register and Configure Sun Cluster HA for WebSphere Message Broker .....	24
Verifying the Sun Cluster HA for WebSphere Message Broker Installation and Configuration .....	28
▼ How to Verify the Sun Cluster HA for WebSphere Message Broker Installation and Configuration .....	29
Upgrading Sun Cluster HA for WebSphere Message Broker .....	29
▼ How to Upgrade to the New Version of Sun Cluster HA for WebSphere Message Broker .....	29
Understanding the Sun Cluster HA for WebSphere Message Broker Fault Monitor .....	30
Resource Properties .....	30
Probing Algorithm and Functionality .....	31
Debug Sun Cluster HA for WebSphere Message Broker .....	32
▼ How to turn on debug for Sun Cluster HA for WebSphere Message Broker .....	32
<b>A Deployment Example: Installing WebSphere Message Broker in Zones</b> .....	35
Target Cluster Configuration .....	35

Software Configuration .....	35
Assumptions .....	36
Installing and Configuring WebSphere Message Broker .....	36
▼ Example: Prepare the Cluster for WebSphere Message Broker .....	37
▼ Example: Configure zones z1 and z2 for WebSphere Message Broker .....	37
▼ Example: Install WebSphere Message Broker in the zones .....	38
▼ Example: Verify WebSphere Message Broker .....	41
▼ Example: Configure Cluster Resources for WebSphere Message Broker .....	45
▼ Example: Enable the WebSphere Message Broker Software to Run in the Cluster .....	45
▼ Example: Verify the Sun Cluster HA for WebSphere Message Broker Resource Group .....	47
<b>Index</b> .....	<b>49</b>

# Preface

---

*Sun Cluster Data Service for WebSphere Message Broker Guide for Solaris OS* explains how to install and configure Sun™ Cluster HA for WebSphere Message Broker on both SPARC® based systems and x86 based systems.

---

**Note** – This Sun Cluster release supports systems that use the SPARC and x86 families of processor architectures: UltraSPARC, SPARC64, and AMD64. In this document, the label x86 refers to systems that use the AMD64 family of processor architectures.

---

This document is intended for system administrators with extensive knowledge of Sun software and hardware. Do not use this document as a planning or presales guide. Before reading this document, you should have already determined your system requirements and purchased the appropriate equipment and software.

The instructions in this book assume knowledge of the Solaris™ Operating System (Solaris OS) and expertise with the volume-manager software that is used with Sun Cluster software.

---

**Note** – Sun Cluster software runs on two platforms, SPARC and x86. The information in this document pertains to both platforms unless otherwise specified in a special chapter, section, note, bulleted item, figure, table, or example.

---

## Using UNIX Commands

This document contains information about commands that are specific to installing and configuring Sun Cluster data services. The document does *not* contain comprehensive information about basic UNIX® commands and procedures, such as shutting down the system, booting the system, and configuring devices. Information about basic UNIX commands and procedures is available from the following sources:

- Online documentation for the Solaris Operating System
- Solaris Operating System man pages
- Other software documentation that you received with your system

## Typographic Conventions

The following table describes the typographic conventions that are used in this book.

TABLE P-1 Typographic Conventions

Typeface	Meaning	Example
<i>AaBbCc123</i>	The names of commands, files, and directories, and onscreen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. <code>machine_name%</code> you have mail.
<b>AaBbCc123</b>	What you type, contrasted with onscreen computer output	<code>machine_name%</code> <b>su</b> Password:
<i>aabcc123</i>	Placeholder: replace with a real name or value	The command to remove a file is <i>rm filename</i> .
<i>AaBbCc123</i>	Book titles, new terms, and terms to be emphasized	Read Chapter 6 in the <i>User's Guide</i> . <i>A cache</i> is a copy that is stored locally. Do <i>not</i> save the file. <b>Note:</b> Some emphasized items appear bold online.

## Shell Prompts in Command Examples

The following table shows the default UNIX system prompt and superuser prompt for the C shell, Bourne shell, and Korn shell.

TABLE P-2 Shell Prompts

Shell	Prompt
C shell	<code>machine_name%</code>
C shell for superuser	<code>machine_name#</code>
Bourne shell and Korn shell	<code>\$</code>
Bourne shell and Korn shell for superuser	<code>#</code>

## Related Documentation

Information about related Sun Cluster topics is available in the documentation that is listed in the following table. All Sun Cluster documentation is available at <http://docs.sun.com>.

Topic	Documentation
Data service administration	<i>Sun Cluster Data Services Planning and Administration Guide for Solaris OS</i> Individual data service guides
Concepts	<i>Sun Cluster Concepts Guide for Solaris OS</i>
Overview	<i>Sun Cluster Overview for Solaris OS</i>
Software installation	<i>Sun Cluster Software Installation Guide for Solaris OS</i>
System administration	<i>Sun Cluster System Administration Guide for Solaris OS</i>
Hardware administration	<i>Sun Cluster 3.1 - 3.2 Hardware Administration Manual for Solaris OS</i> Individual hardware administration guides
Data service development	<i>Sun Cluster Data Services Developer's Guide for Solaris OS</i>
Error messages	<i>Sun Cluster Error Messages Guide for Solaris OS</i>
Command and function reference	<i>Sun Cluster Reference Manual for Solaris OS</i>

For a complete list of Sun Cluster documentation, see the release notes for your release of Sun Cluster at <http://docs.sun.com>.

## Related Third-Party Web Site References

Third-party URLs that are referenced in this document provide additional related information.

---

**Note** – Sun is not responsible for the availability of third-party web sites mentioned in this document. Sun does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Sun will not be responsible or liable for any actual or alleged damage or loss caused or alleged to be caused by or in connection with use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

---

## Documentation, Support, and Training

The Sun web site provides information about the following additional resources:

- [Documentation](http://www.sun.com/documentation/) (<http://www.sun.com/documentation/>)
- [Support](http://www.sun.com/support/) (<http://www.sun.com/support/>)
- [Training](http://www.sun.com/training/) (<http://www.sun.com/training/>)

## Getting Help

If you have problems installing or using Sun Cluster, contact your service provider and provide the following information:

- Your name and email address (if available)
- Your company name, address, and phone number
- The model number and serial number of your systems
- The release number of the Solaris Operating System (for example, Solaris 10)
- The release number of Sun Cluster (for example, Sun Cluster 3.2)

Use the following commands to gather information about each node on your system for your service provider.

Command	Function
<code>prtconf -v</code>	Displays the size of the system memory and reports information about peripheral devices
<code>psrinfo -v</code>	Displays information about processors
<code>showrev -p</code>	Reports which patches are installed
<code>SPARC: prtdiag -v</code>	Displays system diagnostic information
<code>/usr/cluster/bin/clnode show-rev</code>	Displays Sun Cluster release and package version information

Also have available the contents of the `/var/adm/messages` file.



# Installing and Configuring Sun Cluster HA for WebSphere Message Broker

---

This chapter explains how to install and configure Sun Cluster HA for WebSphere Message Broker.

This chapter contains the following sections.

- “Sun Cluster HA for WebSphere Message Broker Overview” on page 9
- “Overview of Installing and Configuring Sun Cluster HA for WebSphere Message Broker” on page 10
- “Planning the Sun Cluster HA for WebSphere Message Broker Installation and Configuration” on page 11
- “Installing and Configuring WebSphere Message Broker” on page 15
- “Verifying the Installation and Configuration of WebSphere Message Broker” on page 19
- “Installing the Sun Cluster HA for WebSphere Message Broker Packages” on page 22
- “Registering and Configuring Sun Cluster HA for WebSphere Message Broker” on page 24
- “Verifying the Sun Cluster HA for WebSphere Message Broker Installation and Configuration” on page 28
- “Upgrading Sun Cluster HA for WebSphere Message Broker” on page 29
- “Understanding the Sun Cluster HA for WebSphere Message Broker Fault Monitor” on page 30
- “Debug Sun Cluster HA for WebSphere Message Broker” on page 32

## Sun Cluster HA for WebSphere Message Broker Overview

---

**Note** – Throughout this document the term zone reflects a non-global Solaris zone. The term global zone will remain.

---

The Sun Cluster HA for WebSphere Message Broker data service provides a mechanism for the orderly startup and shutdown, fault monitoring, and automatic failover of the WebSphere Message Broker service.

The following components can be protected by the Sun Cluster HA for WebSphere Message Broker data service within the global zone or whole root zone.

Broker  
 Configuration Manager  
 UserNameServer

## Overview of Installing and Configuring Sun Cluster HA for WebSphere Message Broker

The following table summarizes the tasks for installing and configuring Sun Cluster HA for WebSphere Message Broker and provides cross-references to detailed instructions for performing these tasks. Perform the tasks in the order that they are listed in the table.

**TABLE 1** Tasks for Installing and Configuring Sun Cluster HA for WebSphere Message Broker

Task	Instructions
Plan the installation	“Planning the Sun Cluster HA for WebSphere Message Broker Installation and Configuration” on page 11
Install and configure the WebSphere Message Broker software	“How to Install and Configure WebSphere Message Broker” on page 15
Verify the installation and configuration	“How to Verify the Installation and Configuration of WebSphere Message Broker” on page 19
Install Sun Cluster HA for WebSphere Message Broker packages	“How to Install the Sun Cluster HA for WebSphere Message Broker Packages” on page 22
Register and configure Sun Cluster HA for WebSphere Message Broker resources	“How to Register and Configure Sun Cluster HA for WebSphere Message Broker” on page 24
Verify the Sun Cluster HA for WebSphere Message Broker installation and configuration	“How to Verify the Sun Cluster HA for WebSphere Message Broker Installation and Configuration” on page 29
Upgrade the Sun Cluster HA for WebSphere Message Broker data service	“How to Upgrade to the New Version of Sun Cluster HA for WebSphere Message Broker” on page 29
Tune the Sun Cluster HA for WebSphere Message Broker fault monitor	“Understanding the Sun Cluster HA for WebSphere Message Broker Fault Monitor” on page 30
Debug Sun Cluster HA for WebSphere Message Broker	“How to turn on debug for Sun Cluster HA for WebSphere Message Broker” on page 32

# Planning the Sun Cluster HA for WebSphere Message Broker Installation and Configuration

This section contains the information you need to plan your Sun Cluster HA for WebSphere Message Broker installation and configuration.

## Configuration Restrictions

The configuration restrictions in the subsections that follow apply only to Sun Cluster HA for WebSphere Message Broker.



---

**Caution** – Your data service configuration might not be supported if you do not observe these restrictions.

---

### Restriction for the supported configurations of Sun Cluster HA for WebSphere Message Broker

The Sun Cluster HA for WebSphere Message Broker data service can only be configured as a failover service.

Single or multiple instances of WebSphere Message Broker can be deployed in the cluster.

WebSphere Message Broker can be deployed in the global zone or a whole root zone. See [“Restriction for multiple WebSphere Message Broker instances” on page 12](#) for more information about deploying in a zone.

The Sun Cluster HA for WebSphere Message Broker data service supports different versions of WebSphere Message Broker. Before proceeding with the installation of WebSphere Message Broker you must check that the Sun Cluster HA for WebSphere Message Broker data service has been verified against that version.

### Restriction for the location of WebSphere Message Broker files

The WebSphere Message Broker files are the data files used by the broker in `/var/mqs.i`. Within this document references will be made to the WebSphere Message Broker files which implies all of the contents of `/var/mqs.i`, unless specified otherwise.

These WebSphere Message Broker files needs to be placed on shared storage as either a cluster file system or a highly available local file system. However, this placement will depend on how WebSphere Message Broker is being deployed, if a single or multiple instances are being deployed, and if that deployment will be in the global zone or zones.

Refer to [Step 5](#) and [Step 6](#) in [“How to Install and Configure WebSphere Message Broker” on page 15](#) for a more information.

## Restriction for the WebSphere Message Broker additional software

WebSphere Message Broker requires WebSphere MQ and a database.

If you are installing WebSphere Business Integration Message Broker v5, the Sun Cluster HA for WebSphere Message Broker requires that the broker, queue manager and database are all registered within the same resource group. This implies that a remote database cannot be used for WebSphere Business Integration Message Broker v5.

This restriction is required because WebSphere Business Integration Message Broker v5 has very specific restart dependencies if the queue manager or database fails. More specifically, it is not possible for the cluster to manage the restart of a remote database that is outside of the cluster.

**Table 2** describes the restart dependencies that the WebSphere Business Integration Message Broker v5 software has on additional software.

**TABLE 2** WebSphere Business Integration Message Broker v5 restart dependencies

Failure	Intended Action	Actual Action
Broker	Broker Start	Sun Cluster Broker resource restarted
Broker Queue Manager	Broker Stop	Sun Cluster Queue Manager resource restarted
	Broker Queue Manager Start	Sun Cluster Broker resource restarted
	Broker Start	
Broker Database	Broker Stop	Sun Cluster Database resource restarted
	Broker Queue Manager Stop	Sun Cluster Queue Manager resource restarted
	Broker Database Start	Sun Cluster Broker resource restarted
	Broker Queue Manager Start	
	Broker Start	

If you are installing WebSphere Message Broker v6, the restart dependency for the broker database listed in **Table 2** is no longer required. This implies that a remote database can be used for WebSphere Message Broker v6. WebSphere Message Broker and WebSphere MQ are still required to be registered within the same resource group.

---

**Note** – The broker database needs to be available for WebSphere Message Broker v6 to fully initialize. Therefore if you are deploying a remote broker database you must consider the availability of the broker database and the impact that can have on the broker if the broker database is not available.

---

## Restriction for multiple WebSphere Message Broker instances

The Sun Cluster HA for WebSphere Message Broker data service can support multiple WebSphere Message Broker instances, potentially with different versions.

If you intend to deploy multiple WebSphere Message Broker instances you will need to consider how you deploy WebSphere Message Broker in the global zone or whole root zones.

The purpose of the following discussion is to help you decide how to use the global zone or whole root zones to deploy multiple WebSphere Message Broker instances and then to determine what `NodeList` entries are required.

The `NodeList` entry is used when the resource group is defined using the `clresourcegroup` command. The Sun Cluster HA for WebSphere Message Broker *must* use the same resource group that is used for the WebSphere MQ and database resources.

You must therefore determine how the WebSphere Message Broker will be deployed in the cluster *before* the WebSphere MQ resource group is created so that you can specify the appropriate `NodeList` entry.

Within these examples:

- There are two nodes within the cluster, `node1` and `node2`.
- Both nodes have two zones named `z1` and `z2`.
- Each example listed simply shows the required `NodeList` property value, via the `-n` parameter, which is used when creating a failover resource group.
- Benefits and drawbacks are listed within each example as `+` and `-`.

**EXAMPLE 1** Run multiple WebSphere Message Broker instances in the global zone in one resource group.

Create a single failover resource group that will contain all the WebSphere Message Broker instances that will run in the global zones across `node1` and `node2`.

```
# clresourcegroup create -n node1,node2 RG1
```

- `+` Only the global zone per node is required.
- `-` Multiple WebSphere Message Broker instances do not have independent failover as they are all within the same failover resource group.
- `-` Under normal operation, only one node of the cluster at any time is actively processing the WebSphere Message Broker workload.

**EXAMPLE 2** Run multiple WebSphere Message Broker instances in the global zone in separate resource groups.

Create multiple failover resource groups that will each contain one WebSphere Message Broker instance that will run in the global zones across `node1` and `node2`.

```
# clresourcegroup create -n node1,node2 RG1
# clresourcegroup create -n node2,node1 RG2
```

- `+` Only the global zone per node is required.
- `+` Multiple WebSphere Message Broker instances have independent failover in separate failover resource groups.

**EXAMPLE 2** Run multiple WebSphere Message Broker instances in the global zone in separate resource groups. *(Continued)*

- + Under normal operation, each node of the cluster is actively processing a WebSphere Message Broker workload, thereby utilizing each node of the cluster.

**EXAMPLE 3** Run multiple WebSphere Message Broker instances in zones in one resource group.

Create a single failover resource group that will contain all the WebSphere Message Broker instances that will run in the same zones across node1 and node2.

```
# clresourcegroup create -n node1:z1,node2:z1 RG1
```

- + Only one zone per node is required.
- - Although all zones are booted, only one zone at any time is actively processing the WebSphere Message Broker workload.
- - Multiple WebSphere Message Broker instances do not have independent failover as they are all within the same failover resource group.
- - Multiple WebSphere Message Broker instances are not isolated within their own separate zones.

**EXAMPLE 4** Run multiple WebSphere Message Broker instances in zones in separate resource groups.

Create multiple zones, where each zone pair will contain just one WebSphere Message Broker instance that will run in the same zones across node1 and node2.

```
# clresourcegroup create -n node1:z1,node2:z1 RG1
```

```
# clresourcegroup create -n node2:z2,node1:z2 RG2
```

- + Multiple WebSphere Message Broker instances have independent failover in separate failover resource groups and separate zones.
- + All WebSphere Message Broker instances are isolated within their own separate zones.
- - Each resource group requires a unique zone per node.

## Configuration Requirements

The configuration requirements in this section apply only to Sun Cluster HA for WebSphere Message Broker.



**Caution** – If your data service configuration does not conform to these requirements, the data service configuration might not be supported.

---

## Determine which Solaris zone WebSphere Message Broker will use

Solaris zones provides a means of creating virtualized operating system environments within an instance of the Solaris 10 OS. Solaris zones allow one or more applications to run in isolation from other activity on your system. For complete information about installing and configuring a Solaris Container, see *System Administration Guide: Solaris Containers-Resource Management and Solaris Zones*.

You must determine which Solaris zone WebSphere Message Broker will run in. WebSphere Message Broker can run within a global zone or zone configuration. [Table 3](#) provides some reasons to help you decide which zone is appropriate.

**TABLE 3** Choosing the appropriate Solaris zone for WebSphere Message Broker

Zone type	Reasons for choosing the appropriate Solaris Zone for WebSphere Message Broker
Global Zone	<p>Only one instance of WebSphere Message Broker will be installed.</p> <p>You are upgrading your cluster where previously a single or multiple WebSphere Message Broker instances were deployed on the cluster nodes.</p> <p>Zones are not required.</p>
Non-global Zone	<p>Multiple WebSphere Message Broker instances need to be consolidated and isolated from each other.</p> <p>Different versions of WebSphere Message Broker will be installed.</p> <p>Failover testing of WebSphere Message Broker between zones on a single node cluster is required.</p>

## Installing and Configuring WebSphere Message Broker

This section contains the procedures you need to install and configure WebSphere Message Broker.

### ▼ How to Install and Configure WebSphere Message Broker

This section contains the procedures you need to install and configure WebSphere Message Broker.

#### 1 Determine how many WebSphere Message Broker instances will be used.

Refer to [“Restriction for multiple WebSphere Message Broker instances”](#) on page 12 for more information.

#### 2 Determine which Solaris zone to use.

Refer to [“Determine which Solaris zone WebSphere Message Broker will use”](#) on page 15 for more information.

**3 If a zone will be used, create the whole root zone.**

Refer to *System Administration Guide: Solaris Containers-Resource Management and Solaris Zones* for complete information about installing and configuring a zone.

---

**Note** – When creating a zone for use by the cluster, `autoboot=true` must be used.

---

**4 If a zone is being used, ensure the zone is booted.**

Repeat this step on all nodes of the cluster if a zone is being used.

Boot the zone if it is not running.

```
# zoneadm list -v
# zoneadm -z zonename boot
```

**5 Determine how WebSphere Message Broker should be deployed in the cluster.**

The WebSphere Message Broker files can be deployed onto a cluster file system or highly available file system in the cluster. The following discussion will help you determine the correct approach to take.

Within this section, a single instance or multiple instances of WebSphere Message Broker will be considered within a global zone or zone.

In each scenario, file system options for the WebSphere Message Broker files (`/var/mqsi`) will be listed together with a recommendation where appropriate.

**a. Single Instance of WebSphere Message Broker****i. Global zone deployment**

`/var/mqsi` Can be deployed on a cluster file system, however you are recommend to deploy on a highly available local file system.

**ii. Zone deployment**

`/var/mqsi` Must be deployed on a highly available local file system.

**b. Multiple Instances of WebSphere Message Broker****i. Global zone deployment**

`/var/mqsi` Must be deployed on a cluster file system.

**ii. Zone deployment**

`/var/mqsi` Must be deployed on a highly available local file system.

---

**Note** – Refer to [Appendix A](#) for Deployment Example: Installing a WebSphere Message Broker in zones for an example on how to set up the WebSphere Message Broker files.

---



## 6 Create a cluster file system or highly available local file system for the WebSphere Message Broker files.

Within this step you will create a file system for the WebSphere Message Broker files (`/var/mqsi`). Once you have determined how WebSphere Message Broker should be deployed in the cluster, you can choose one of the sub steps below.

- Create the WebSphere Message Broker files on a cluster file system by using [Step a](#).
- Create the WebSphere Message Broker files on a highly available local file systems by using [Step b](#).

### a. WebSphere Message Broker files on a cluster file system.

Within this deployment:

- The WebSphere Message Broker files (`/var/mqsi`) are deployed on a cluster file system.
- However, `/var/mqsi/local` or `/var/mqsi/common/local` requires a symbolic link to a local file system. This is required as WebSphere Message Broker generates specific locks that require the locks directory to be located on local storage within each node.

If WebSphere Business Integration Message Broker v5 is being deployed you must create a symbolic link for `/var/mqsi/locks` to a local file system, e.g. `/local/mqsi/locks` on each node in the cluster.

If WebSphere Message Broker v6 is being deployed you must create a symbolic link for `/var/mqsi/common/locks` to a local file system, e.g. `/local/mqsi/locks` on each node in the cluster.

### b. WebSphere Message Broker files on a highly available local file system.

Within this deployment:

- The WebSphere Message Broker files (`/var/mqsi`) are deployed on a highly available local file system.
- Highly available local file systems can include the Zettabyte File System (ZFS).
- A symbolic link for the locks directory is *not* required, regardless if you are deploying WebSphere Business Integration Message Broker v5 or WebSphere Message Broker v6.

## 7 Mount the highly available local file system

Perform this step on one node of the cluster.

### a. If a non ZFS highly available local file system is being used for the WebSphere Message Broker.

Ensure the node has ownership of the disk set or disk group.

For Solaris Volume Manager.

```
# metaset -s disk-set -t
```

For Veritas Volume Manager.

```
# vxdg -C import disk-group
# vxdg -g disk-group startall
```

**i. If the global zone is being used for WebSphere Message Broker.**

```
# mount websphere-message-broker-highly-available-local-file-system
```

**ii. If a zone is being used for WebSphere Message Broker.**

Create the mount point on all zones of the cluster that are being used for WebSphere Message Broker.

```
# zlogin zonename mkdir websphere-message-broker-highly-available-local-file-system
```

Mount the highly available local file system on one of the zones being used.

```
# mount -F lofs websphere-message-broker-highly-available-local-file-system \
> /zonepath/root/websphere-message-broker-highly-available-local-file-system
```

**b. If a ZFS highly available local file system is being used for WebSphere Message Broker.**

**i. If the global zone is being used for WebSphere Message Broker.**

```
# zpool import -R / HAZpool
```

**ii. If a zone is being used for WebSphere Message Broker.**

```
# zpool import -R /zonepath/root HAZpool
```

---

**Note** – If you are repeating this step to mount the ZFS highly available local file system on another node or zone *before* installing the WebSphere Message Broker software, you must first export the ZFS pool from the node that currently has the ZFS pool imported.

To export the ZFS pool, issue the following,

```
# zpool export -f HAZpool
```

---

**8 Install WebSphere Message Broker on all nodes or zones of the cluster.**

After you have created and mounted the appropriate file system for the WebSphere Message Broker files, you must install WebSphere Message Broker on *each* node of the cluster, either in the global zone or zone as required.

For compatibility reasons, the Sun Cluster HA for WebSphere Message Broker data service requires that `/opt/mqsi` exists on all nodes or zones in the cluster, even if WebSphere Message Broker v6 is being deployed. Therefore you *must* create the directory `/opt/mqsi`.

Follow IBM's *WebSphere Message Broker Installation Guide* to install WebSphere Message Broker.

---

**Note** – If the WebSphere Message Broker files will use a highly available local file system, you will need to mount the highly available local file system on each node or zone *before* installing the WebSphere Message Broker software.

Repeat [Step 7](#) as required.

---

**9 Ensure that WebSphere MQ and the appropriate database are running.**

WebSphere Message Broker requires that a queue manager and appropriate database are running when creating a Broker, Configuration Manager or UserNameServer. You must ensure that the queue manager and database are running on the node where you will create a Broker, Configuration Manager or UserNameServer.

**10 Create the WebSphere Message Broker, Configuration Manager or UserNameServer as required.**

Follow *IBM's WebSphere Message Broker Installation Guide* to create a WebSphere Message Broker.

## Verifying the Installation and Configuration of WebSphere Message Broker

This section contains the procedure you need to verify the installation and configuration.

### ▼ How to Verify the Installation and Configuration of WebSphere Message Broker

This procedure does not verify that your application is highly available because you have not yet installed your data service.

Perform this procedure on one node or zone of the cluster unless a specific step indicates otherwise.

**1 Ensure the zone is booted, if a zone is being used.**

Repeat this step on all nodes on the cluster if a zone is being used.

Boot the zone if it is not running.

```
# zoneadm list -v
# zoneadm -z zonename boot
```

**2 Login to the zone, if a zone is being used.**

```
# zlogin zonename
```

**3 Start the WebSphere Message Broker, Configuration Manager or UserNameServer.**

```
# su - message-broker-userid
$ mqsisstart message-broker
```

**4 List all WebSphere Message Brokers that are running.**

Perform this step as the *message-broker-userid*.

```
$ mqsilist
```

**5 Stop the WebSphere Message Broker, Configuration Manager or UserNameServer.**

Perform this step as the *message-broker-userid*.

```
$ mqsisstop -i message-broker
$ exit
```

**6 Logout from the zone, if a zone is being used.**

```
# exit
```

**7 Unmount the highly available local file system.**

Perform this step in the global zone only.

You should unmount the highly available file system you mounted in [Step 7](#) in “[How to Install and Configure WebSphere Message Broker](#)” on page 15

**a. If a non ZFS highly available local file system is being used for WebSphere Message Broker.**

**i. If the global zone is being used for WebSphere Message Broker.**

```
# umount websphere-message-broker-highly-available-local-file-system
```

**ii. If a zone is being used for WebSphere Message Broker.**

Unmount the highly available local file system from the zone.

```
# umount /zonepath/root/websphere-message-broker-highly-available-local-file-system
```

**b. If a ZFS highly available file system is being used for WebSphere Message Broker.**

```
# zpool export -f HAZpool
```

**8 Relocate the shared storage to other node.**

Perform this step on another node of the cluster.

**a. If a non ZFS highly available local file system is being used for the WebSphere Message Broker files.**

Ensure the node has ownership of the disk set or disk group.

For Solaris Volume Manager.

```
# metaset -s disk-set -t
```

For Veritas Volume Manager.

```
# vxdg -C import disk-group
# vxdg -g disk-group startall
```

**i. If the global zone is being used for WebSphere Message Broker.**

```
# mount websphere-message-broker-highly-available-local-file-system
```

**ii. If a zone is being used for WebSphere Message Broker.**

Create the mount point on all zones of the cluster that are being used for WebSphere Message Broker.

Mount the highly available local file system on one of the zones being used .

```
# zlogin zonename mkdir websphere-message-broker-highly-available-local-file-system
#
# mount -F lofs websphere-message-broker-highly-available-local-file-system \
> /zonepath/root/websphere-message-broker-highly-available-local-file-system
```

**b. If a ZFS highly available file system is being used for WebSphere Message Broker.**

**i. If the global zone is being used for WebSphere Message Broker.**

```
# zpool import -R / HAZpool
```

**ii. If a zone is being used for WebSphere Message Broker.**

```
# zpool import -R /zonepath/root HAZpool
```

**9 Login to the zone, if a zone is being used.**

Perform this step on the other node of the cluster.

```
# zlogin zonename
```

**10 Start the WebSphere Message Broker, Configuration Manager or UserNameServer.**

Perform this step on the other node or zone of the cluster.

```
# su - message-broker-userid
$ mqsisstart message-broker
```

**11 List all WebSphere Message Brokers that are running.**

Perform this step as the *message-broker-userid*.

```
$ mqsilist
```

**12 Stop the WebSphere Message Broker, Configuration Manager or UserNameServer.**

Perform this step as the *message-broker-userid*.

```
$ mqsisstop -i message-broker
$ exit
```

**13 Logout from the zone, if a zone is being used.**

```
# exit
```

**14 Unmount the highly available local file system.**

Perform this step in the global zone only.

You should unmount the highly available file system you mounted in [Step 7](#) in “How to Install and Configure WebSphere Message Broker” on page 15

**a. If a non ZFS highly available local file system is being used for WebSphere Message Broker.**

**i. If the global zone is being used for WebSphere Message Broker.**

```
# umount websphere-message-broker-highly-available-local-file-system
```

**ii. If a zone is being used for WebSphere Message Broker.**

Unmount the highly available local file system from the zone.

```
# umount /zonepath/root/websphere-message-broker-highly-available-local-file-system
```

**b. If a ZFS highly available file system is being used for WebSphere Message Broker.**

```
# zpool export -f HAZpool
```

## Installing the Sun Cluster HA for WebSphere Message Broker Packages

If you did not install the Sun Cluster HA for WebSphere Message Broker packages during your initial Sun Cluster installation, perform this procedure to install the packages. To install the packages, use the Sun Java™ Enterprise System Installation Wizard.

### ▼ How to Install the Sun Cluster HA for WebSphere Message Broker Packages

Perform this procedure on each cluster node where you are installing the Sun Cluster HA for WebSphere Message Broker packages.

You can run the Sun Java Enterprise System Installation Wizard with a command-line interface (CLI) or with a graphical user interface (GUI). The content and sequence of instructions in the CLI and the GUI are similar.

---

**Note** – Even if you plan to configure this data service to run in non-global zones, install the packages for this data service in the global zone. The packages are propagated to any existing non-global zones and to any non-global zones that are created after you install the packages.

---

**Before You Begin** Ensure that you have the Sun Java Availability Suite DVD-ROM.

If you intend to run the Sun Java Enterprise System Installation Wizard with a GUI, ensure that your DISPLAY environment variable is set.

**1 On the cluster node where you are installing the data service packages, become superuser.**

**2 Load the Sun Java Availability Suite DVD-ROM into the DVD-ROM drive.**

If the Volume Management daemon vold(1M) is running and configured to manage DVD-ROM devices, the daemon automatically mounts the DVD-ROM on the /cdrom directory.

**3 Change to the Sun Java Enterprise System Installation Wizard directory of the DVD-ROM.**

- **If you are installing the data service packages on the SPARC® platform, type the following command:**

```
# cd /cdrom/cdrom0/Solaris_sparc
```

- **If you are installing the data service packages on the x86 platform, type the following command:**

```
# cd /cdrom/cdrom0/Solaris_x86
```

**4 Start the Sun Java Enterprise System Installation Wizard.**

```
# ./installer
```

**5 When you are prompted, accept the license agreement.**

If any Sun Java Enterprise System components are installed, you are prompted to select whether to upgrade the components or install new software.

**6 From the list of Sun Cluster agents under Availability Services, select the data service for WebSphere Message Broker.**

**7 If you require support for languages other than English, select the option to install multilingual packages.**

English language support is always installed.

**8 When prompted whether to configure the data service now or later, choose Configure Later.**

Choose Configure Later to perform the configuration after the installation.

**9 Follow the instructions on the screen to install the data service packages on the node.**

The Sun Java Enterprise System Installation Wizard displays the status of the installation. When the installation is complete, the wizard displays an installation summary and the installation logs.

**10 (GUI only) If you do not want to register the product and receive product updates, deselect the Product Registration option.**

The Product Registration option is not available with the CLI. If you are running the Sun Java Enterprise System Installation Wizard with the CLI, omit this step

**11 Exit the Sun Java Enterprise System Installation Wizard.**

**12 Unload the Sun Java Availability Suite DVD-ROM from the DVD-ROM drive.**

a. To ensure that the DVD-ROM is not being used, change to a directory that does *not* reside on the DVD-ROM.

b. Eject the DVD-ROM.

```
# eject cdrom
```

**Next Steps** See “[Registering and Configuring Sun Cluster HA for WebSphere Message Broker](#)” on page 24 to register Sun Cluster HA for WebSphere Message Broker and to configure the cluster for the data service.

## Registering and Configuring Sun Cluster HA for WebSphere Message Broker

This section contains the procedures you need to configure Sun Cluster HA for WebSphere Message Broker.

Some procedures within this section require you to use certain Sun Cluster commands. Refer to the relevant Sun Cluster command man page for more information about these command and their parameters.

The Sun Cluster HA for WebSphere Message Broker data service

### ▼ How to Register and Configure Sun Cluster HA for WebSphere Message Broker

Perform this procedure on one node of the cluster only.



This procedure assumes that you installed the data service packages during your initial Sun Cluster installation.

If you did not install the Sun Cluster HA for WebSphere Message Broker packages as part of your initial Sun Cluster installation, go to [“How to Install the Sun Cluster HA for WebSphere Message Broker Packages” on page 22.](#)

---

**Note** – This procedure requires that WebSphere MQ and a broker database have been installed and that the Sun Cluster HA for WebSphere MQ data service and database data service have been registered and configured.

The registration and configuration of Sun Cluster HA for WebSphere Message Broker must use the same resource group that WebSphere MQ and the broker database use.

You must therefore have completed the installation of the Sun Cluster Data Service for WebSphere MQ data service and the database data service before continuing with this procedure.

---

- 1 On a cluster member, become superuser or assume a role that provides `solaris.cluster.modify` RBAC authorization.**
- 2 Create a resource for the WebSphere Message Broker Disk Storage.**

**a. If a ZFS highly available local file system is being used.**

```
# clresource create -g websphere-mq-resource-group \
> -t SUNW.HASStoragePlus \
> -p Zpools=websphere-message-broker-zspool \
> websphere-message-broker-hastorage-resource
```

Alternatively, you can simply add the `websphere-message-broker-zspool` to the existing `websphere-mq-hastorage-resource`.

```
# clresource set \
> -p Zpools=websphere-mq-zspools,websphere-message-broker-zspool
> websphere-mq-hastorage-resource
```

**b. If a cluster file system or a non ZFS highly available local file system is being used.**

```
# clresource create -g websphere-mq-resource-group \
> -t SUNW.HASStoragePlus \
> -p FilesystemMountPoints=websphere-message-broker-filesystem-mountpoint \
> websphere-message-broker-hastorage-resource
```

Alternatively, you can simply add the *websphere-message-broker-filesystem-mountpoint* to the existing *websphere-mq-hastorage-resource*.

```
# clresource set \  
> -p FilesystemMountPoints=mq-filesystem-mountpoints,message-broker-filesystem-mountpoint \  
> websphere-mq-hastorage-resource
```

### 3 Enable the Disk Storage resource.

```
# clresource enable websphere-message-broker-hastorage-resource
```

### 4 Create and register a resource for the Broker.

Edit `/opt/SUNWscmqi/sib/util/sib_config` and follow the comments within that file. After you have edited `sib_config`, you must register the resource.

If you require the broker probe to perform a simple message flow test, you must create a message flow and specify the *inbound* queue in the `SC3_IN` variable and the *outbound* queue in the `SC3_OUT` variable.

Refer to IBM's *WebSphere Message Broker Message Flows* to create a simple message flow.

Alternatively, the default values for `SC3_IN` and `SC3_OUT` are set to `NONE` which will cause the broker probe to not perform a simple message flow and just check that the `bipservice` program is running.

A value for the `RDBMS_RS` parameter is not required if WebSphere Message Broker v6 is being deployed. This implies that a remote database can be used for WebSphere Message Broker v6 and that the broker does not need to be restarted if the broker database is restarted.

```
# cd /opt/SUNWscmqi/sib/util  
# vi sib_config  
# ./sib_register
```

The following listing has been taken from the deployment example, [Step 2](#), which can be found in [Appendix A](#) and shows `/opt/SUNWscmqi/sib/util/sib_config` that has been edited to configure a broker resource.

```
Vigor5# cat > /var/tmp/brk_config <<-EOF  
RS=wmq1-brk  
RG=wmq1-rg  
QMGR=qmgr1  
LH=wmq1-lh  
HAS_RS=wmq1-ZFShas  
SC3_IN=NONE  
SC3_OUT=NONE  
MQSI_ID=mqsiuser  
BROKER=brk  
QMGR_RS=wmq1-qmgr  
RDBMS_RS=  
START_CMD=
```

```
STOP_CMD=
EOF
```

```
Vigor5# /opt/SUNWscmqi/sib/util/sib_register -f /var/tmp/brk_config
```

## 5 Enable the Broker resource.

---

**Note** – Before you enable the Broker resource, ensure that /opt/mqsi exists.

For compatibility reasons, the Sun Cluster HA for WebSphere Message Broker data service requires that /opt/mqsi exists on all nodes or zones in the cluster.

---

```
# clresource enable websphere-message-broker-resource
```

## 6 (Optional) Create and register a resource for the Configuration Manager.

Edit /opt/SUNWscmqi/sib/util/sib\_config and follow the comments within that file. After you have edited sib\_config, you must register the resource.

The configuration manager resource *must* specify NONE for the SC3\_IN and SC3\_OUT variables.

A value for the RDBMS\_RS parameter is not required if WebSphere Message Broker v6 Configuration Manager is being deployed.

```
# cd /opt/SUNWscmqi/sib/util
# vi sib_config
# ./sib_register
```

The following listing has been taken from the deployment example, [Step 4](#), which can be found in [Appendix A](#) and shows /opt/SUNWscmqi/sib/util/sib\_config that has been edited to configure a configuration manager resource.

```
Vigor5# cat > /var/tmp/cmng_config <<-EOF
RS=wmq1-cmg
RG=wmq1-rg
QMGR=qmgr1
LH=wmq1-lh
HAS_RS=wmq1-ZFShas
SC3_IN=NONE
SC3_OUT=NONE
MQSI_ID=mqsiuser
BROKER=cmg
QMGR_RS=wmq1-qmgr
RDBMS_RS=
START_CMD=
STOP_CMD=
EOF
```

```
Vigor5# /opt/SUNWscmqi/sib/util/sib_register -f /var/tmp/cmng_config
```

**7 (Optional) Enable the Configuration Manager resource.**

```
# clresource enable websphere-message-broker-configuration-manager-resource
```

**8 (Optional) Create and register a resource for the UserNameServer.**

Edit /opt/SUNWscmqi/siu/util/siu\_config and follow the comments within that file. After you have edited siu\_config, you must register the resource.

```
# cd /opt/SUNWscmqi/siu/util
# vi siu_config
# ./siu_register
```

The following listing has been taken from the deployment example, [Step 6](#), which can found in [Appendix A](#) and shows /opt/SUNWscmqi/siu/util/siu\_config that has been edited to configure a UserNameServer resource.

```
Vigor5# cat > /var/tmp/cmconfig <<-EOF
RS=wmq1-uns
RG=wmq1-rg
QMGR=qmgr1
LH=wmq1-lh
HAS_RS=wmq1-ZFShas
MQSI_ID=mqsiuser
QMGR_RS=wmq1-qmgr
START_CMD=
STOP_CMD=
EOF
```

```
Vigor5# /opt/SUNWscmqi/siu/util/siu_register -f /var/tmp/uns_config
```

**9 (Optional) Enable the UserNameServer resource.**

```
# clresource enable websphere-message-broker-usernameserver-resource
```

## Verifying the Sun Cluster HA for WebSphere Message Broker Installation and Configuration

This section contains the procedure you need to verify that you installed and configured your data service correctly.

## ▼ How to Verify the Sun Cluster HA for WebSphere Message Broker Installation and Configuration

- 1 On a cluster member, become superuser or assume a role that provides `solaris.cluster.modify` RBAC authorization.
- 2 Ensure all the WebSphere Message Broker resources are online.  

```
# cluster status
```

Enable any WebSphere Message Broker resources that are not online.

```
# clresource enable websphere-message-broker-resource
```
- 3 Switch the WebSphere Message Broker resource group to another cluster node or node:zone.  

```
# clresourcegroup switch -n node[:zone] websphere-mq-resource-group
```

## Upgrading Sun Cluster HA for WebSphere Message Broker

Upgrade the Sun Cluster HA for WebSphere Message Broker data service if the following conditions apply:

- You are upgrading from an earlier version of the Sun Cluster HA for WebSphere Message Broker data service, that was previously known as Sun Cluster HA for WebSphere MQ Integrator.
- You need to use the new features of this data service.

## ▼ How to Upgrade to the New Version of Sun Cluster HA for WebSphere Message Broker

Perform steps 1, 2, 3 and 6 if you have an existing Sun Cluster HA for WebSphere Message Broker deployment and wish to upgrade to the new version. Complete all steps if you need to use the new features of this data service.

---

**Note** – If you intend to run all steps, you should consider if your current WebSphere Message Broker resources have been modified to have specific timeout values that suit your deployment. If timeout values were previously adjusted you should reapply those timeout values to your new WebSphere Message Broker resources.

---

- 1 On a cluster member, become superuser or assume a role that provides `solaris.cluster.modify` RBAC authorization.

**2 Disable the WebSphere Message Broker resources.**

```
# clresource disable websphere-messabge-broker-resource
```

**3 Install the new version of Sun Cluster HA for WebSphere Message Broker to each cluster**

Refer to “[How to Install the Sun Cluster HA for WebSphere Message Broker Packages](#)” on page 22 for more information.

**4 Delete the WebSphere Message Broker resources, if you want to use new features that have been introduced in the new version of Sun Cluster HA for WebSphere Message Broker.**

```
# clresource delete websphere-message-broker-resource
```

**5 Reregister the WebSphere Message Broker resources, if you want to use new features that have been introduced in the new version of Sun Cluster HA for WebSphere Message Broker.**

Refer to “[How to Register and Configure Sun Cluster HA for WebSphere Message Broker](#)” on page 24 for more information.

**6 Enable the WebSphere Message Broker resources**

If you have only performed steps 1, 2 and 3 you will need to re-enable the WebSphere Message Broker resources.

```
# clresource enable websphere-message-broker-resource
```

## Understanding the Sun Cluster HA for WebSphere Message Broker Fault Monitor

This section describes the Sun Cluster HA for WebSphere Message Broker fault monitor probing algorithm or functionality, states the conditions, and recovery actions associated with unsuccessful probing.

For conceptual information on fault monitors, see the *Sun Cluster Concepts Guide*.

### Resource Properties

The Sun Cluster HA for WebSphere Message Broker fault monitor uses the same resource properties as resource type SUNW.gds. Refer to the SUNW.gds (5) man page for a complete list of resource properties used.

## Probing Algorithm and Functionality

The Sun Cluster HA for WebSphere Message Broker fault monitor is controlled by the extension properties that control the probing frequency. The default values of these properties determine the preset behavior of the fault monitor. The preset behavior should be suitable for most Sun Cluster installations. Therefore, you should tune the Sun Cluster HA for WebSphere Message Broker fault monitor *only* if you need to modify this preset behavior.

- Setting the interval between fault monitor probes (`Thorough_probe_interval`)
- Setting the timeout for fault monitor probes (`Probe_timeout`)
- Setting the number of times the fault monitor attempts to restart the resource (`Retry_count`)

The Sun Cluster HA for WebSphere Message Broker fault monitor checks the broker and other components within an infinite loop. During each cycle the fault monitor will check the relevant component and report either a failure or success.

If the fault monitor is successful it returns to its infinite loop and continues the next cycle of probing and sleeping.

If the fault monitor reports a failure a request is made to the cluster to restart the resource. If the fault monitor reports another failure another request is made to the cluster to restart the resource. This behavior will continue whenever the fault monitor reports a failure.

If successive restarts exceed the `Retry_count` within the `Thorough_probe_interval` a request to failover the resource group onto a different node or zone is made.

### Operations of the Broker probe

The broker probe can check the broker by using a simple message flow test, if `SC3_IN` and `SC3_OUT` are set to the *inbound* and *outbound* queues.

If set, the broker probe puts a message to the *inbound* queue referenced by the `SC3_IN` variable. After waiting two seconds, the broker probe checks that the message has arrived at the *outbound* queue referenced by the `SC3_OUT` variable.

If `SC3_IN` and `SC3_OUT` are set to `NONE` the simple message flow is not performed. Instead the broker probe checks that the `bipservice` process is still running.

`SC3_IN` and `SC3_OUT` are set when the broker resource was configured and registered within `/opt/SUNWscmqi/sib/util/sib_config`.

### Operations of the Configuration Manager probe

The broker probe checks the configuration manager to see if the `bipservice` process is still running.

The configuration manager resource must set `SC3_IN` and `SC3_OUT` to `NONE`. This ensures that the simple message flow test is not performed.

## Operations of the UserNameServer probe

The broker probe checks the UserNameServer to see if the bipservice process is still running.

# Debug Sun Cluster HA for WebSphere Message Broker

## ▼ How to turn on debug for Sun Cluster HA for WebSphere Message Broker

Sun Cluster HA for WebSphere Message Broker can be used by multiple WebSphere Message Broker instances. It is possible to turn debug on for all WebSphere Message Broker instances or a particular WebSphere Message Broker instance.

A config file exists under `/opt/SUNWscmqi/xxx/etc`, where `xxx` can be `sib` (Broker or Configuration Manager) or `siu` (UserNameServer).

These files allow you to turn on debug for all WebSphere Message Broker instances or for a specific WebSphere Message Broker instance on a particular node or zone within the cluster. If you require debug to be turned on for Sun Cluster HA for WebSphere Message Broker across the whole cluster, repeat this step on all nodes within the cluster.

### 1 Edit `/etc/syslog.conf` and change `daemon.notice` to `daemon.debug`.

```
# grep daemon /etc/syslog.conf
*.err;kern.debug;daemon.notice;mail.crit      /var/adm/messages
*.alert;kern.err;daemon.err                    operator
#
```

Change the `daemon.notice` to `daemon.debug` and restart `syslogd`. Note that the output below, from `grep daemon /etc/syslog.conf`, shows that `daemon.debug` has been set.

```
# grep daemon /etc/syslog.conf
*.err;kern.debug;daemon.debug;mail.crit      /var/adm/messages
*.alert;kern.err;daemon.err                    operator
```

Restart the `syslog` daemon.

#### a. If running Solaris 9

```
# pkill -1 syslogd
```

#### b. If running Solaris 10

```
# svcadm disable system-log
# svcadm enable system-log
```



**2 Edit /opt/SUNWscmqi/xxx/etc/config.**

Perform this step for each component that requires debug output, on each node of Sun Cluster as required.

Edit /opt/SUNWscmqi/xxx/etc/config and change DEBUG= to DEBUG=ALL or DEBUG=*resource*.

```
# cat /opt/SUNWscmqi/sib/etc/config
#
# Copyright 2006 Sun Microsystems, Inc. All rights reserved.
# Use is subject to license terms.
#
##ident    "@(#)config 1.2    06/03/21 SMI"
#
# Usage:
#     DEBUG=<RESOURCE_NAME> or ALL
#
DEBUG=ALL
```

---

**Note** – To turn off debug, reverse the steps above.

---



# Deployment Example: Installing WebSphere Message Broker in Zones

---

This appendix presents a complete example of how to install and configure a WebSphere Message Broker in zones. It presents a single node cluster configuration. If you need to install the application in any other configuration, refer to the general-purpose procedures presented elsewhere in this manual.

## Target Cluster Configuration

This example uses a single node cluster with the following node and zone names:

- Vigor5            The physical node, which owns the file system.
- Vigor5:z1        A whole root zone named z1.
- Vigor5:z2        A whole root zone named z2.

## Software Configuration

This deployment example uses the following software products and versions:

- Solaris 10 06/06 software for SPARC or x86 platforms
- Sun Cluster 3.2 core software
- Sun Cluster HA for WebSphere MQ data service
- Sun Cluster HA for WebSphere Message Broker data service
- WebSphere Message Broker v6 Solaris x86-64
- WebSphere MQ v6 Solaris x86-64
- DB2 v8 Solaris x86-64

This example assumes that you have already installed and established your cluster. It illustrates the installation and configuration of the data service application only.

## Assumptions

The instructions in this example were developed with the following assumptions:

- **Shell environment:** All commands and the environment setup in this example are for the Korn shell environment. If you use a different shell, replace any Korn shell-specific information or instructions with the appropriate information for your preferred shell environment.
- **User login:** Unless otherwise specified, perform all procedures as superuser or assume a role that provides `solaris.cluster.admin`, `solaris.cluster.modify`, and `solaris.cluster.read` RBAC authorization.

## Installing and Configuring WebSphere Message Broker

---

**Note** – This deployment example is designed for a single node cluster. It is provided simply as a concise guide to help you if you need to refer to an installation and configuration of WebSphere Message Broker.

This deployment example is *not* meant to be a precise guide to install and configure WebSphere Message Broker.

If you need to install WebSphere Message Broker in any other configuration, refer to the general purpose procedures elsewhere in this manual.

---

The instructions with this deployment example assumes that you are using the WebSphere Message Broker v6 Solaris x86–64 platform and will configure WebSphere Message Broker on a ZFS highly available local file system.

The cluster resource group has already be configured to failover between two zones on a single node cluster.

This deployment examples assumes that you have completed the Deployment Example: Installing WebSphere MQ in Zones from the Sun Cluster Data Service for WebSphere MQ Guide.

The tasks you must perform to install and configure WebSphere Message Broker in the zones are as follows:

- “Example: Prepare the Cluster for WebSphere Message Broker” on page 37
- “Example: Configure zones z1 and z2 for WebSphere Message Broker” on page 37
- “Example: Install WebSphere Message Broker in the zones” on page 38
- “Example: Verify WebSphere Message Broker” on page 41
- “Example: Configure Cluster Resources for WebSphere Message Broker” on page 45
- “Example: Enable the WebSphere Message Broker Software to Run in the Cluster” on page 45
- “Example: Verify the Sun Cluster HA for WebSphere Message Broker Resource Group” on page 47

## ▼ Example: Prepare the Cluster for WebSphere Message Broker

Perform all steps within this example in the global zone.

- 1 **Install and configure the cluster as instructed in *Sun Cluster Software Installation Guide for Solaris OS*.**

Install the following cluster software components.

- Sun Cluster core software
- Sun Cluster HA for WebSphere Message Broker data service

---

**Note** – This deployment example assumes that WebSphere MQ has been installed into zones z1 and z2 and that the Sun Cluster for WebSphere MQ data service has been installed and configured.

This deployment example further assumes that the Deployment Example: Installing WebSphere MQ in Zones, from the Sun Cluster Data Service for WebSphere MQ Guide, was used to create the resource group wmq1-rg and zones z1 and z2.

Within this deployment example a GDS resource is used to create and register a DB2 resource.

---

- 2 **Install and configure a Zettabyte file system.**

Create a ZFS pool.

---

**Note** – The following `zpool` definitions represent a very basic configuration for deployment on a single node cluster.

You should *not* consider this example for use within a productive deployment, instead it is a very basic configuration for testing or development purposes only.

---

```
Vigor5# zpool create -m /ZFSwmb1 HAZpool3 c1t5d0
```

## ▼ Example: Configure zones z1 and z2 for WebSphere Message Broker

- 1 **Import the ZFS pool into zone z1.**

Perform this step in the global zone only.

```
Vigor5# zpool export -f HAZpool3
Vigor5# zpool import -R /zones/z1/root HAZpool3
```

**2 Create some directories and a symbolic link for the WebSphere Message Broker and DB2 software.**

Perform this step in the global zone only.

```
Vigor5# zlogin z1 mkdir /ZFSwmb1/mqsiuser /ZFSwmb1/db2user /ZFSwmb1/mqsi
Vig0r5# zlogin z1 touch /ZFSwmb1/mqsiuser/.profile
Vig0r5# zlogin z1 touch /ZFSwmb1/db2user/.profile
Vigor5# zlogin z1 mkdir /opt/mqsi
Vigor5# zlogin z2 mkdir /opt/mqsi
Vigor5# zlogin z1 ln -s /ZFSwmb1/mqsi /var/mqsi
Vigor5# zlogin z2 ln -s /ZFSwmb1/mqsi /var/mqsi
```

**3 Create the WebSphere Message Broker and DB2 userid in the zones.**

Perform this step from the global zone and repeat for zone z2.

```
Vigor5# zlogin z1
# groupadd -g 2000 mqbrkrs
# useradd -u 2000 -G mqm,mqbrkrs -d /ZFSwmb1/mqsiuser -s /usr/bin/ksh mqsiuser
# groupadd -g 3000 dba
# useradd -u 3000 -G dba -d /ZFSwmb1/db2user -s /usr/bin/ksh db2user
# passwd mqsiuser
New Password: mqsiuser
Re-enter new Password: mqsiuser
# passwd db2user
New Password: db2user
Re-enter new Password: db2user
# exit
```

**4 Setup file permissions in the ZFS pool.**

Perform this step in zone z1 only.

```
Vigor5# zlogin z1
# cd /ZFSwmb1
# chown db2user:dba db2user
# chown mqm:mqbrkrs mqsi
# chown mqsiuser:mqbrkrs mqsiuser
# exit
```

**▼ Example: Install WebSphere Message Broker in the zones**


---

**Caution** – The steps within this procedure are *not* precise steps to install WebSphere Message Broker or DB2. Refer to the relevant IBM documentation for complete information.

---

**1 Mount the WebSphere Message Broker software in the zones.**

Perform this step in the global zone only.

In this example, the WebSphere Message Broker software and DB2 software has been copied to node Vigor5 in directories /export/software/ibm/wmbv6 and /export/software/ibm/db2v8.

```
Vigor5# zlogin z1 mkdir -p /var/tmp/software
Vigor5# zlogin z2 mkdir -p /var/tmp/software
Vigor5# mount -F lofs /export/software /zones/z1/root/var/tmp/software
Vigor5# mount -F lofs /export/software /zones/z2/root/var/tmp/software
```

**2 Install the DB2 software in zone z1.**

Perform this step from the global zone for zone z1.

```
Vigor5# zlogin z1
# cat > /var/tmp/db2_response <<-EOF
PROD           = ENTERPRISE_SERVER_EDITION
INSTALL_TYPE   = TYPICAL
LIC_AGREEMENT = ACCEPT
EOF
# cd /var/tmp/software/ibm/db2v8
# ./db2setup -r /var/tmp/db2_response
```

Comment out chk\_kernel\_conf in /opt/IBM/db2/V8.1/instance/db2iutil as indicated by ->.

```
    # Check that kernel parameters are updated
-> # chk_kernel_conf
    # Set the value of vars INSTHOME and INSTPGRP
    # and check their validity

# vi /opt/IBM/db2/V8.1/instance/db2iutil
# exit
```

**3 Install the WebSphere Message Broker software in zone z1.**

Perform this step from the global zone for zone z1 which can be performed at the same time you are installing the DB2 software.

```
Vigor5# zlogin z1
# cat > /var/tmp/install.opt <<-EOF
-W setupTypes.selectedSetupTypeId=typical
-P installLocation=/opt/IBM/mqsi/6.0
-P brokerFeature.active=true
-P transformationServicesFeature.active=true
-p unsFeature.active=true
-P configManagerFeature.active=true
EOF
# cd /var/tmp/software/ibm/wmbv6/messagebroker_runtime1
# ./setupsolarisx86 -options /var/tmp/install.opt -silent
# exit
```

**4 Relocate the ZFS pool to zone z2.**

Perform this step in the global zone.

```
Vigor5# zpool export -f HAZpool3
Vigor5# zpool import -R /zones/z2/root HAZpool3
```

**5 Install the DB2 software in zone z2.**

Perform this step from the global zone for zone z2.

```
Vigor5# zlogin z2
# cat > /var/tmp/db2_response <<-EOF
PROD           = ENTERPRISE_SERVER_EDITION
INSTALL_TYPE   = TYPICAL
LIC_AGREEMENT  = ACCEPT
EOF
# cd /var/tmp/software/ibm/db2v8
# ./db2setup -r /var/tmp/db2_response
```

Comment out `chk_kernel_conf` in `/opt/IBM/db2/V8.1/instance/db2iutil` as indicated by `->`.

```
    # Check that kernel parameters are updated
-> # chk_kernel_conf
    # Set the value of vars INSTHOME and INSTPGRP
    # and check their validity

# vi /opt/IBM/db2/V8.1/instance/db2iutil
# exit
```

**6 Install the WebSphere Message Broker software in zone z2.**

Perform this step from the global zone for zone z2 which can be performed at the same time you are installing the DB2 software.

```
Vigor5# zlogin z2
# cat > /var/tmp/install.opt <<-EOF
-W setupTypes.selectedSetupTypeId=typical
-P installLocation=/opt/IBM/mqsi/6.0
-P brokerFeature.active=true
-P transformationServicesFeature.active=true
-p unsFeature.active=true
-P configManagerFeature.active=true
EOF
# cd /var/tmp/software/ibm/wmbv6/messagebroker_runtime1
# ./setupsolarisx86 -options /var/tmp/install.opt -silent
# exit
```



**7 Relocate the ZFS pool back to zone z1.**

Perform this step in the global zone.

```
Vigor5# zpool export -f HAZpool3
Vigor5# zpool import -R /zones/z1/root HAZpool3
```

**▼ Example: Verify WebSphere Message Broker****1 Create the Broker database.**

Perform this step in the global zone for zone z1.

```
Vigor5# zlogin z1
# cd /opt/IBM/db2/V8.1/instance
# ./db2icrt -u db2user db2user
# su - db2user
$ db2start
$ db2 create database BROKERDB
$ db2 connect to BROKERDB
$ db2 bind ./sqllib/bnd/@db2cli.lst grant public CLIPKG 5
$ db2 update database configuration for BROKERDB using dbheap 900
$ chmod 644 /ZFSwmb1/db2user/sqllib/db2nodes.cfg
$ cat > /ZFSwmb1/db2user/sqllib/db2nodes.cfg <<-EOF
0 db2user 0
EOF
$ chmod 444 /ZFSwmb1/db2user/sqllib/db2nodes.cfg
$ exit
```

**2 Update /etc/hosts with db2user on both zones.**

Perform this step in zones z1 and z2.

```
# vi /etc/hosts
```

The following listing shows db2user that has been added to /etc/hosts on z1.

```
127.0.0.1      localhost    loghost     z1    db2user
```

**3 Create the Broker, Configuration Manager and UserNameServer.**

Perform this step in zone z1 only.

---

**Note** – The broker queue manager and broker database must be running *before* you perform this step.

Ensure that DB2 is started and resource group wmq1- rg is online on Vigor5:z1.

Deployment Example: Installing WebSphere MQ in Zones, from the Sun Cluster Data Service for WebSphere MQ Guide, was used to create the resource group wmq1- rg.

---

```

# cat > /ZFSwmb1/mqsiuser/.profile <<-EOF
. /ZFSwmb1/db2user/sqllib/db2profile
. /opt/IBM/mqsi/6.0/bin/mqsiprofile
EOF
# su - mqsiuser
$ mqsicreatebroker brk \
> -i mqsiuser -a mqsiuser -q qmgr1 -n BROKERDB -u db2user -p db2user
$ mqsicreateconfigmgr cmg \
> -i mqsiuser -a mqsiuser -q qmgr1
$ mqsicreateusernameserver \
> -i mqsiuser -a mqsiuser -q qmgr1
$ exit

```

#### 4 Start the Broker, Configuration Manager and UserNameServer.

Perform this step in zone z1.

```

# su - mqsiuser
$ mqsistart brk
$ mqsistart cmg
$ mqsistart UserNameServer

```

#### 5 Verify that the Broker, Configuration Manager and UserNameServer have been created and are running.

Perform this step in zone z1.

```

# su - mqsiuser
$ mqsilist
BIP8099I: ConfigMgr: cmg - qmgr1
BIP8099I: UserNameServer: UserNameServer - qmgr1
BIP8099I: Broker: brk - qmgr1

```

BIP8071I: Successful command completion.

```

$ exit
# ptree mqsiuser
2608 zsched
    15573 bipservice brk
        15574 bipbroker brk
            15590 biphttplistener brk
15594 bipservice cmg
    15595 bipconfigmgr cmg
15665 bipservice UserNameServer
    15666 bipuns UserNameServer

```

#### 6 Stop the Broker, Configuration Manager and UserNameServer.

Perform this step in zone z1.

```

# su - mqsiuser
$ mqsistop -i brk

```

```
$ mqsistop -i cmg
$ mqsistop -i UserNameServer
$ exit
```

## 7 Stop the Broker database.

Perform this step in zone z1.

```
# su - db2user
$ db2stop force
$ exit
# exit
```

## 8 Failover the WebSphere MQ resource group to the other zone.

Perform this step in the global zone.

```
Vigor5# clrg switch -n Vigor5:z2 wmq1-rg
```

## 9 Relocate the ZFS pool to the other zone.

Perform this step in the global zone.

```
Vigor5# zpool export -f HAZpool3
Vigor5# zpool import -R /zones/z2/root HAZpool3
```

## 10 Setup /etc/services and start the Broker database.

Perform this step in zone z2.

---

**Note** – The port list entries for db2user should be the same as those on zone z1.

---

```
Vigor5# z2
# cat >> /etc/services <<-EOF
DB2_db2user      60000/tcp
DB2_db2user_1    60001/tcp
DB2_db2user_2    60002/tcp
DB2_db2user_END  60003/tcp
EOF
# su - db2user
$ db2start
$ exit
```

## 11 Start the Broker, Configuration Manager and UserNameServer.

Perform this step in zone z2.

```
# su - mqsuser
$ mqsistart brk
$ mqsistart cmg
$ mqsistart UserNameServer
$ exit
```

**12 Verify that the Broker, Configuration Manager and UserNameServer are running.**

Perform this step in zone z2.

```
# su - mqsiuser
$ mqsilist
BIP8099I: ConfigMgr: cmg - qmgr1
BIP8099I: UserNameServer: UserNameServer - qmgr1
BIP8099I: Broker: brk - qmgr1

BIP8071I: Successful command completion.
$ exit
# ptree mqsiuser
2614 zsched
    6658 bipservice brk
        6659 bipbroker brk
            6681 biphttplistener brk
        6674 bipservice cmg
            6675 bipconfigmgr cmg
        6691 bipservice UserNameServer
            6692 bipuns UserNameServer
```

**13 Stop the Broker, Configuration Manager and UserNameServer.**

Perform this step in zone z2.

```
# su - mqsiuser
$ mqsistop -i brk
$ mqsistop -i cmg
$ mqsistop -i UserNameServer
$ exit
```

**14 Stop the Broker database.**

Perform this step in zone z2.

```
# su - db2user
$ db2stop force
$ exit
# exit
```

**15 Export the ZFS pool.**

Perform this step in the global zone.

```
Vigor5# zpool export -f HAZpool3
```

## ▼ Example: Configure Cluster Resources for WebSphere Message Broker

Perform all steps within this example in the global zone.

### 1 Create the HASStoragePlus resource in the wmq1-rg resource group.

```
Vigor5# clresource create -g wmq1-rg -t SUNW.HASStoragePlus \
> -p Zpools=HAZpool3 wmq1-ZFSbrokerhas
```

Alternatively, you can simply add HAZpool3 to the existing wmq1-ZFSHas resource.

Deployment Example: Installing WebSphere MQ in Zones, from the Sun Cluster Data Service for WebSphere MQ Guide, was used to create the wmq1-ZFSHas resource..

```
Vigor5# clresource set -p Zpools=HAZpool1,HAZpool2,HAZpool3 wmq1-ZFSHas
```

### 2 Enable the resource.

This step is only required if you created the wmq1-ZFSbrokerhas resource.

```
Vigor5# clresource enable wmq1-ZFSbrokerhas
```

## ▼ Example: Enable the WebSphere Message Broker Software to Run in the Cluster

Perform all steps within this example in the global zone.

### 1 Create and enable the DB2 cluster resource.

---

**Note** – At the time of writing this deployment example, an IBM DB2 agent for Sun Cluster 3.2 was not available. Instead to provide high availability for DB2 the following GDS resource was used.

---

```
Vigor5# z2
# cat > /ZFSwmb1/db2user/ha-db2probe <<-EOF
if su - db2user -c "db2gcf -s -i db2user -p 0" > /dev/null
then
    rc=0
else
    su - db2user -c "ipclean -a"
    rc=100
fi
return ${rc}
EOF
# chmod 755 /ZFSwmb1/db2user/ha-db2probe
# exit
```

```
Vigor5# clresource create -g wmq1-rg -t SUNW.gds \
-p Start_command='/usr/bin/su - db2user -c "db2start"' \
-p Stop_command='/usr/bin/su - db2user -c "db2stop force"' \
-p Probe_command='/usr/bin/ksh /ZFSwmb1/db2user/ha-db2probe' \
-p Network_aware=false wmq1-db2
Vigor5# clresource enable wmq1-db2
```

## 2 Create the Broker configuration file.

Either cat the following into `/var/tmp/brk_config` or edit `/opt/SUNWscmqi/sib/util/sib_config` and execute `/opt/SUNWscmqi/sib/util/sib_register`.

Within this step `HAS_RS=wmq1-ZFS` has is specified, if you created resource `wmq1-ZFSbrokerhas` you must specify `HAS_RS=wmq1-ZFSbrokerhas`.

```
Vigor5# cat > /var/tmp/brk_config <<-EOF
RS=wmq1-brk
RG=wmq1-rg
QMGR=qmgr1
LH=wmq1-lh
HAS_RS=wmq1-ZFS
SC3_IN=NONE
SC3_OUT=NONE
MQSI_ID=mqsiuser
BROKER=brk
QMGR_RS=wmq1-qmgr
RDBMS_RS=
START_CMD=
STOP_CMD=
EOF
```

## 3 Register and enable the Broker resource.

```
Vigor5# /opt/SUNWscmqi/sib/util/sib_register -f /var/tmp/brk_config
Vigor5# clresource enable wmq1-brk
```

## 4 Create the Configuration Manager configuration file.

Either cat the following into `/var/tmp/cmg_config` or edit `/opt/SUNWscmqi/sib/util/sib_config` and execute `/opt/SUNWscmqi/sib/util/sib_register`.

Within this step `HAS_RS=wmq1-ZFS` has is specified, if you created resource `wmq1-ZFSbrokerhas` you must specify `HAS_RS=wmq1-ZFSbrokerhas`.

```
Vigor5# cat > /var/tmp/cmg_config <<-EOF
RS=wmq1-cmg
RG=wmq1-rg
QMGR=qmgr1
LH=wmq1-lh
HAS_RS=wmq1-ZFS
SC3_IN=NONE
```

```

SC3_OUT=NONE
MQSI_ID=mqsiuser
BROKER=cmg
QMGR_RS=wmq1-qmgr
RDBMS_RS=
START_CMD=
STOP_CMD=
EOF

```

**5 Register and enable the Configuration Manager resource.**

```

Vigor5# /opt/SUNWscmqi/sib/util/sib_register -f /var/tmp/cmg_config
Vigor5# clresource enable wmq1-cmg

```

**6 Create the UserNameServer configuration file.**

Either cat the following into /var/tmp/uns\_config or edit /opt/SUNWscmqi/siu/util/siu\_config and execute /opt/SUNWscmqi/siu/util/siu\_register.

Within this step HAS\_RS=wmq1-ZFSHas is specified, if you created resource wmq1-ZFSbrokerhas you must specify HAS\_RS=wmq1-ZFSbrokerhas.

```

Vigor5# cat > /var/tmp/uns_config <<-EOF
RS=wmq1-uns
RG=wmq1-rg
QMGR=qmgr1
LH=wmq1-lh
HAS_RS=wmq1-ZFSHas
MQSI_ID=mqsiuser
QMGR_RS=wmq1-qmgr
START_CMD=
STOP_CMD=
EOF

```

**7 Register and enable the UserNameServer resource.**

```

Vigor5# /opt/SUNWscmqi/siu/util/siu_register -f /var/tmp/uns_config
Vigor5# clresource enable wmq1-uns

```

## ▼ Example: Verify the Sun Cluster HA for WebSphere Message Broker Resource Group

Perform this step in the global zone.

**► Switch the WebSphere MQ resource group between the two zones.**

```

Vigor5# for node in Vigor5:z2 Vigor5:z1
do
    clrg switch -n $node wmq1-rg

```

```
clrs status wmq1-brk
clrs status wmq1-cmg
clrs status wmq1-uns
clrg status wmq1-rg
done
```



# Index

---

## C

- clnode command, 8
- Command, cluster command, 29
- commands
  - clreslogicalhostname, 15-19
  - clresource, 15-19
  - clresourcegroup, 15-19
  - clresourcetype, 15-19
  - node information, 8
- Configuration, Verifying the Installation and
  - Configuration of WebSphere Message Broker, 19-22
- configuration requirements, 14-15
- configuration restrictions, 11-14

## D

- deployment examples, WebSphere MQ Broker, 35

## E

- error messages, cluster, 8
- examples, WebSphere MQ Broker, 35

## F

- Fault Monitoring
  - Probing Algorithm and Functionality, 31-32
  - Resource Properties, 30
  - Understanding the Sun Cluster HA for WebSphere Message Broker Fault Monitor, 30-32

## G

- global zone, 23

## H

- help, 8

## I

- Installation, Verifying the Sun Cluster HA for WebSphere Message Broker Installation and Configuration, 28-29
- installing
  - Sun Cluster HA for WebSphere Message Broker, 22-24
  - WebSphere Message Broker, 15-19

## L

- local zones, *See* non-global zones

## M

- messages file, 8

## N

- non-global zones, 23

## O

overview  
    installation, 10  
    product, 9-10

## P

packages, 22-24  
prtconf -v command, 8  
prtdiag -v command, 8  
psrinfo -v command, 8

## R

restrictions, zones, 23

## S

show- rev subcommand, 8  
showrev -p command, 8  
software packages, 22-24  
Solaris zone Type, 15  
Sun Cluster HA for WebSphere Message Broker  
    installing, 22-24  
    software packages  
        installing, 22-24

## T

technical support, 8

## V

/var/adm/messages file, 8

## Z

zones, 23