

---

# PeopleSoft® Enterprise Learning Management 8.81 to 9.0 Upgrade

---

**May 2006**

PeopleSoft Enterprise Enterprise Learning Management 8.81 to 9.0  
Upgrade  
SKU uels9\_050406  
Copyright © 2006, Oracle. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

### **U.S. GOVERNMENT RIGHTS**

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are “commercial computer software” or “commercial technical data” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee’s responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

### **Open Source Disclosure**

Oracle takes no responsibility for its use or distribution of any open source or shareware software or documentation and disclaims any and all liability or damages resulting from use of said software or documentation. The following open source software may be used in Oracle’s PeopleSoft products and the following disclaimers are provided.

#### *Apache Software Foundation*

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>). Copyright © 1999-2000. The Apache Software Foundation. All rights reserved.

THIS SOFTWARE IS PROVIDED “AS IS” AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#### *OpenSSL*

Copyright © 1998-2003 The OpenSSL Project. All rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>).

THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT “AS IS” AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#### *SSLeay*

Copyright © 1995-1998 Eric Young. All rights reserved.

This product includes cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)). This product includes software written by Tim Hudson ([tjh@cryptsoft.com](mailto:tjh@cryptsoft.com)). Copyright © 1995-1998 Eric Young. All rights reserved. THIS SOFTWARE IS PROVIDED BY ERIC YOUNG “AS IS” AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#### *Loki Library*

Copyright © 2001 by Andrei Alexandrescu. This code accompanies the book: Alexandrescu, Andrei. “Modern C++ Design: Generic Programming and Design Patterns Applied.” Copyright © 2001 Addison-Wesley. Permission to use, copy, modify, distribute and sell this software for any purpose is hereby granted without fee, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation.

#### *Helma Project*

Copyright © 1999-2004 Helma Project. All rights reserved. THIS SOFTWARE IS PROVIDED “AS IS” AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE HELMA PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Helma includes third party software released under different specific license terms. See the licenses directory in the Helma distribution for a list of these licenses.

*Sarissa*

Copyright © 2004 Manos Batsis.

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA.

# Contents

## Preface

|                                       |            |
|---------------------------------------|------------|
| <b>About This Documentation.....</b>  | <b>xix</b> |
| Understanding This Documentation..... | xix        |
| Prerequisites.....                    | xix        |
| Audience.....                         | xix        |
| Organization.....                     | xix        |
| Related Information.....              | xx         |

## Chapter 1

|  |          |
|--|----------|
| <b>Prepare Your Database.....</b>                  | <b>1</b> |
| Understanding Database Preparation.....            | 1        |
| Understanding Your Upgrade.....                    | 2        |
| Understanding PeopleSoft Upgrades.....             | 2        |
| Verifying the Software Installation.....           | 2        |
| Defining Upgrade Databases.....                    | 2        |
| Reviewing Upgrade Notes and Tips.....              | 3        |
| Copying Your Production Database .....             | 3        |
| Making a Copy of Production Database.....          | 3        |
| Increasing Database Space.....                     | 4        |
| Applying Upgrade Planning Files.....               | 4        |
| Understanding Applying Upgrade Planning Files..... | 5        |
| Applying the UPGOPT Project.....                   | 5        |
| Building the UPGOPT Project.....                   | 5        |
| Setting Up Upgrade Planning Security.....          | 6        |
| Loading Upgrade Planning Messages.....             | 6        |
| Editing Upgrade Planning DB2 Scripts.....          | 7        |
| Updating Statistics.....                           | 7        |
| Running Initial Audit Reports.....                 | 8        |
| Understanding Running Initial Audit Reports.....   | 8        |
| Run the Initial DDDAUDIT Report.....               | 8        |
| Run the Initial SYSAUDIT Report.....               | 9        |
| Create the INITALTAUD Project.....                 | 9        |
| Run the Initial Alter Audit.....                   | 10       |
| Review the Initial Audits.....                     | 10       |

|  |    |
|--|----|
| Processing Pending Approvals.....            | 11 |
| Creating Approval Process Definitions.....   | 12 |
| Reporting Row Count for Tables.....          | 13 |
| Preparing Your Database .....                | 13 |
| Understanding Database Preparation.....      | 13 |
| Verify Database Integrity.....               | 14 |
| Clean the PSOBJCHNG Table.....               | 14 |
| Drop PeopleTools Tables.....                 | 14 |
| Shrink Images.....                           | 15 |
| Purge Message Queues.....                    | 16 |
| Backing Up Demo Databases.....               | 16 |
| Backing Up Current Release Demo.....         | 16 |
| Backing Up New Release Demo.....             | 17 |
| Comparing Customizations.....                | 17 |
| Modifying Compare Report Options.....        | 17 |
| Running Compare UPGCUST.....                 | 19 |
| Running UPGCUST Filter Script.....           | 19 |
| Reviewing UPGCUST Compare Log.....           | 20 |
| Restoring Current Release Demo.....          | 20 |
| Identifying Customizations.....              | 20 |
| Preparing for the Application Upgrade.....   | 22 |
| Creating a Copy of RecField Definitions..... | 22 |
| Deleting Old Pagelet Wizard Data.....        | 22 |
| Editing the System Data Swap Script.....     | 23 |
| Editing the PeopleTools Swap Script.....     | 23 |
| Exporting Objectives Data.....               | 24 |
| Backing Up After Prepare Your Database.....  | 24 |

## Chapter 2

|   |           |
|---|-----------|
| <b>Apply PeopleTools Changes.....</b>     | <b>25</b> |
| Understanding PeopleTools Changes.....    | 25        |
| Verifying Upgrade User.....               | 26        |
| Performing Script Modifications.....      | 26        |
| Understanding Script Modifications.....   | 27        |
| Update Configuration Manager Profile..... | 27        |
| Run a DBTSFIX Report.....                 | 28        |
| Edit the DBTSFIX Output Scripts.....      | 29        |
| Edit the GRANT Script.....                | 30        |
| Edit the PSLANGUAGES Script.....          | 30        |

|   |    |
|---|----|
| Edit the TLSUPGNONCOMP Script.....                    | 30 |
| Edit the PTxxxTLS Scripts.....                        | 30 |
| Edit the DB2 Scripts.....                             | 31 |
| Edit Move to Production Import Scripts.....           | 32 |
| Edit Move to Production Password.....                 | 32 |
| Edit the DDLDB2 Script.....                           | 33 |
| Edit the DDLDBX Script.....                           | 33 |
| Edit the DDLORA Script.....                           | 33 |
| Edit the DDLIFX Script.....                           | 34 |
| Edit the MSGTLSUPG Script.....                        | 34 |
| Edit Multilingual Step Properties.....                | 34 |
| Updating PeopleTools System Tables .....              | 35 |
| Understanding Updating PeopleTools System Tables..... | 35 |
| Recreate Performance Views.....                       | 36 |
| Update PeopleTools System Tables.....                 | 36 |
| Grant Privileges to the CONNECT ID.....               | 36 |
| Update the Product License Code.....                  | 37 |
| Update PeopleTools Patch Information.....             | 38 |
| Create Temporary Performance Indexes.....             | 38 |
| Export PeopleTools System Tables.....                 | 38 |
| Import PeopleTools System Tables.....                 | 39 |
| Rerun Update Statistics for DB2 zOS.....              | 39 |
| Rerun RUNSTATS Report for DB2 UNIX NT.....            | 39 |
| Rerun Update Statistics for DB2 UNIX NT.....          | 40 |
| Rerun Update Statistics for Informix.....             | 40 |
| Rerun Update Statistics for Oracle .....              | 40 |
| Turning Off Change Control .....                      | 41 |
| Loading Model Definition Data.....                    | 41 |
| Understanding Model Definition Data Load Process..... | 41 |
| Load Model Definitions for DB2 zOS.....               | 41 |
| Load Model Definitions for DB2 UNIX NT.....           | 42 |
| Load Model Definitions for Oracle.....                | 42 |
| Load Model Definitions for Informix.....              | 42 |
| Load Model Definitions for Microsoft.....             | 42 |
| Load Model Definitions for Sybase.....                | 43 |
| Loading Message Data.....                             | 43 |
| Reviewing PeopleTools Objects.....                    | 43 |
| Exporting and Copying Projects .....                  | 45 |
| Understanding Exporting and Copying Projects.....     | 45 |
| Export and Copy PPLTLS84CUR Project.....              | 45 |

|  |    |
|--|----|
| Export and Copy PPLTLS84CURML Project.....                 | 46 |
| Export and Copy PPLTLSML Project.....                      | 47 |
| Export and Copy PPLTLS84CURDEL Project.....                | 48 |
| Export and Copy PATCH84X Project.....                      | 48 |
| Export and Copy PATCH84XML Project.....                    | 49 |
| Populating Tablespace Data.....                            | 49 |
| Create Application Tablespaces.....                        | 50 |
| Populate Tablespace Data.....                              | 50 |
| Update Tablespace Names.....                               | 51 |
| Building Updated PeopleTools Project.....                  | 52 |
| Generate Updated PeopleTools Script.....                   | 52 |
| Edit the Updated PeopleTools Script.....                   | 52 |
| Run the Updated PeopleTools Script.....                    | 53 |
| Migrating Records to New Tablespaces.....                  | 53 |
| Understanding Migration of Records to New Tablespaces..... | 53 |
| Export and Copy the PT84TBLSPC Project.....                | 53 |
| Build the Tablespace Alter Script.....                     | 54 |
| Edit the Tablespace Alter Script.....                      | 54 |
| Run the Tablespace Alter Script.....                       | 54 |
| Loading Base Data.....                                     | 55 |
| Loading Language Data.....                                 | 55 |
| Populate Languages.....                                    | 55 |
| Load Language Data.....                                    | 56 |
| Loading PeopleTools Data.....                              | 56 |
| Load NonComparable Objects.....                            | 56 |
| Load English Messages.....                                 | 56 |
| Load English String Data.....                              | 57 |
| Load English Currency Codes.....                           | 57 |
| Load Stored Statements Data.....                           | 57 |
| Loading PeopleTools Definition Group.....                  | 58 |
| Converting PeopleTools Objects .....                       | 58 |
| Update Ren Server Configuration.....                       | 58 |
| Populate MCF Data.....                                     | 59 |
| Convert Portal Objects.....                                | 59 |
| Convert Query Prompt Headings.....                         | 60 |
| Encrypt Connector Passwords.....                           | 60 |
| Load Conversion Data.....                                  | 60 |
| Report Conversion Details.....                             | 61 |
| Run Data Conversion.....                                   | 61 |
| Creating PeopleTools Views.....                            | 61 |



|   |    |
|---|----|
| Create Updated PeopleTools Views.....     | 61 |
| Setting Object Version Numbers.....       | 62 |
| Backing Up After PeopleTools Upgrade..... | 62 |

## Chapter 3

|   |           |
|---|-----------|
| <b>Run and Review Compare Reports.....</b>  | <b>63</b> |
| Understanding Compare Reports.....          | 63        |
| Preparing for Application Changes .....     | 63        |
| Exporting Project Definitions.....          | 63        |
| Importing Project Definitions.....          | 64        |
| Running New Release Compare Reports.....    | 64        |
| Understanding the New Release Compare.....  | 64        |
| Preserving Local Message Node.....          | 64        |
| Modifying New Release Compare Options.....  | 65        |
| Running New Release UPGCUST Compare.....    | 66        |
| Resetting Take Action Flags in UPGCUST..... | 67        |
| Reviewing New Release Compare Reports.....  | 67        |
| Reviewing New Release Changes.....          | 67        |
| Reviewing NonComparable Objects.....        | 68        |

## Chapter 4

|   |           |
|---|-----------|
| <b>Apply Application Changes.....</b>         | <b>69</b> |
| Understanding Application Changes.....        | 69        |
| Customizing the New Release.....              | 70        |
| Understanding New Release Customizations..... | 70        |
| Copying the UPGCUST Project.....              | 70        |
| Reviewing UPGCUST Copy Results.....           | 70        |
| Running New Release Upgrade Copy.....         | 71        |
| Exporting Selected PeopleTools Tables.....    | 71        |
| Importing Selected PeopleTools Tables.....    | 72        |
| Updating Target Values.....                   | 72        |
| Swapping PeopleTools Tables.....              | 72        |
| Exporting New Release Objects.....            | 73        |
| Importing New Release Objects.....            | 73        |
| Copying the UPGNONCOMP Project.....           | 73        |
| Reviewing UPGNONCOMP Copy Results.....        | 74        |
| Resetting Object Version Numbers.....         | 74        |
| Backing Up New Release Demo Again.....        | 74        |

|   |    |
|---|----|
| Updating Database Overrides.....                    | 74 |
| Understanding Database Overrides.....               | 75 |
| Set Index Parameters After Copy .....               | 75 |
| Set Tablespace Names After Copy.....                | 75 |
| Set Record Parameters After Copy.....               | 76 |
| Create New Tablespaces.....                         | 76 |
| Backing Up After the Upgrade Copy.....              | 78 |
| Modifying the Database Structure.....               | 79 |
| Understanding Modifying the Database Structure..... | 79 |
| Backing Up for DB2.....                             | 79 |
| Building the Upgrade Tables Script.....             | 80 |
| ReCreating Upgrade Tables.....                      | 80 |
| Creating the ALLTEMPTABS Project.....               | 80 |
| Building the Create Temp Tables Script.....         | 81 |
| Creating the ALLTABS Project.....                   | 81 |
| Building the Create and Alter Scripts.....          | 81 |
| Editing the Create and Alter Scripts.....           | 82 |
| Creating Temporary Tables.....                      | 82 |
| Creating Tables.....                                | 83 |
| Altering Tables.....                                | 83 |
| Creating Indexes.....                               | 83 |
| Reviewing the Create Indexes Log.....               | 84 |
| Setting Index Parameters.....                       | 84 |
| Setting Temp Table Tablespace Names.....            | 84 |
| Setting Tablespace Names.....                       | 85 |
| Setting Record Parameters.....                      | 85 |
| Generating a DB2 UNIX RUNSTATS Script .....         | 85 |
| Updating Statistics for DB2 UNIX.....               | 86 |
| Updating Statistics for DB2 zOS.....                | 86 |
| Updating Statistics for Informix.....               | 86 |
| Updating Statistics for Oracle.....                 | 87 |
| Creating Upgrade Views.....                         | 87 |
| Creating the Upgrade Views Project.....             | 87 |
| Exporting the Upgrade Views Project.....            | 88 |
| Importing the Upgrade Views Project.....            | 88 |
| Building the Upgrade Views.....                     | 88 |
| Running the Upgrade Views Script.....               | 88 |
| Loading Data for Data Conversion.....               | 89 |
| Swapping Languages on System Data.....              | 89 |
| Exporting Application Messages.....                 | 90 |

|  |     |
|--|-----|
| Importing Application Messages.....          | 90  |
| Exporting Record Groups.....                 | 90  |
| Importing Record Groups.....                 | 91  |
| Exporting the System Setup Data .....        | 92  |
| Importing the System Setup Data.....         | 92  |
| Exporting the PW Pagelet Data.....           | 92  |
| Importing the PW Pagelet Data.....           | 92  |
| Exporting the Pagelet Wizard Data.....       | 93  |
| Importing the Pagelet Wizard Data.....       | 93  |
| Exporting Data Conversion Driver Data.....   | 93  |
| Importing Data Conversion Driver Data.....   | 94  |
| Importing Approval Process Seed Data.....    | 94  |
| Restoring New Release Demo.....              | 94  |
| Applying Updates Before Data Conversion..... | 95  |
| Configuring Scheduler and Server.....        | 96  |
| Backing Up Before Data Conversion.....       | 96  |
| Running Data Conversion .....                | 96  |
| Reviewing Data Conversion Tips.....          | 97  |
| Running Data Conversion for Group 1.....     | 99  |
| Backing Up After Data Conversion.....        | 99  |
| Finalizing the Database Structure.....       | 100 |
| Understanding Final Database Structure.....  | 100 |
| Building the Alter with Deletes Scripts..... | 100 |
| Altering Tables with Deletes.....            | 101 |
| Creating Indexes Again.....                  | 101 |
| Creating Triggers.....                       | 101 |
| Running the AE SYNCIDGEN Process.....        | 101 |
| Creating All Views.....                      | 102 |
| Loading Data to Complete System Setup.....   | 102 |
| Exporting Strings.....                       | 103 |
| Importing Strings.....                       | 103 |
| Exporting EDI Statements.....                | 103 |
| Importing EDI Statements.....                | 103 |
| Exporting Mass Change Data.....              | 104 |
| Importing Mass Change Data.....              | 104 |
| Exporting XML Service Information.....       | 104 |
| Importing XML Service Information.....       | 105 |
| Exporting Related Language System Data.....  | 105 |
| Importing Related Language System Data.....  | 105 |
| Exporting Application System Data.....       | 106 |

|   |     |
|---|-----|
| Importing Application System Data.....    | 106 |
| Exporting Setup Data.....                 | 106 |
| Importing Setup Data.....                 | 107 |
| Importing Learning Filters.....           | 107 |
| Updating Language Data.....               | 107 |
| Understanding Updating Language Data..... | 107 |
| Run the TSRECPOP Script.....              | 107 |
| Completing PeopleTools Conversion.....    | 108 |
| Updating Object Version Numbers.....      | 108 |
| Running the Final Audit Reports.....      | 108 |
| Run the Final DDDAUDIT Report.....        | 109 |
| Run the Final SYSAUDIT Report.....        | 109 |
| Create the FNLALTAUD Project.....         | 109 |
| Run the Final Alter Audit.....            | 110 |
| Review the Final Audits.....              | 110 |
| Run a Final SETINDEX Report.....          | 111 |
| Run a Final SETTABLE Report.....          | 111 |

## Chapter 5

|  |            |
|--|------------|
| <b>Complete Database Changes.....</b>        | <b>113</b> |
| Understanding Database Changes.....          | 113        |
| Configuring the Upgrade Environment.....     | 113        |
| Configure Application Server.....            | 114        |
| Configure Portal.....                        | 114        |
| Reapplying Customizations.....               | 115        |
| Understanding the Reapplication.....         | 115        |
| Performing Customized Object Adjustment..... | 115        |
| Registering Portal Navigation Objects.....   | 116        |
| Setting Up Security.....                     | 116        |
| Understanding Security.....                  | 116        |
| Set Up Security.....                         | 116        |
| Synchronize CREF Permissions.....            | 117        |
| Grant Access to Personalize Homepage.....    | 118        |
| Completing Portal Data Conversion.....       | 119        |
| Reviewing Pagelet and Collection Log.....    | 119        |
| Enabling Pagelet Publishing.....             | 120        |
| Reviewing PeopleTools Functionality.....     | 121        |
| Preparing the Content Provider Registry..... | 121        |
| Updating the Portal Options Data.....        | 122        |

|   |     |
|---|-----|
| Running Database Full Sync Processes.....               | 123 |
| Setting Up Learning Environments.....                   | 124 |
| Understanding Multiple Learning Environment Set Up..... | 124 |
| Updating Learning Administrator Roles.....              | 124 |
| Setting Up Administrator Access.....                    | 125 |
| Stamping the Database.....                              | 125 |
| Reviewing Change Control.....                           | 126 |
| Backing Up Before Testing.....                          | 127 |
| Testing Your Copy of Production.....                    | 127 |

## Chapter 6

|  |            |
|--|------------|
| <b>Apply Changes to Production Database.....</b> | <b>129</b> |
| Understanding the Move to Production.....        | 129        |
| Testing the Move to Production.....              | 129        |
| Understanding the Move to Production Test.....   | 129        |
| Understand Move to Production.....               | 130        |
| Creating a New Change Assistant Job.....         | 131        |
| Testing Once More.....                           | 132        |
| Performing the Move to Production.....           | 132        |
| Completing the Upgrade Survey .....              | 132        |

## Chapter 7

|                               |            |
|-------------------------------|------------|
| <b>Appendices.....</b>        | <b>135</b> |
| Understanding Appendices..... | 135        |

## Appendix A

|   |            |
|---|------------|
| <b>Applying Fixes Required for Upgrade.....</b> | <b>137</b> |
| Preparing to Apply Fixes.....                   | 137        |
| Applying Fixes During Installation.....         | 138        |
| Applying Fixes After Copying Project.....       | 138        |
| Applying Fixes After Data Conversion.....       | 139        |
| Applying Fixes Between Upgrade Passes.....      | 139        |
| Applying Fixes in Move to Production.....       | 140        |

## Appendix B

|   |            |
|---|------------|
| <b>Changing the User Interface.....</b>   | <b>141</b> |
| Change the User Interface.....            | 141        |
| Change the User Interface for Mobile..... | 143        |

## Appendix C

|  |            |
|--|------------|
| <b>Using Data Conversion Utilities.....</b>  | <b>145</b> |
| Understanding Data Conversion Utilities..... | 145        |
| Using the Upgrade Driver Program.....        | 145        |
| Using the Upgrade Drivers Page.....          | 145        |
| Understanding Upgrade Drivers Page.....      | 145        |
| Accessing the Upgrade Drivers Page.....      | 146        |
| Adding New Upgrade Drivers Section Page..... | 146        |
| Inactivating Upgrade Drivers Section.....    | 147        |
| Reviewing the Data Conversion Report.....    | 148        |

## Appendix D

|  |            |
|--|------------|
| <b>Improving Performance.....</b>            | <b>149</b> |
| Understanding Performance Improvement.....   | 149        |
| Planning Your Upgrade for Performance.....   | 149        |
| Performing the Upgrade.....                  | 150        |
| Verifying the Database Structure Task.....   | 150        |
| Creating and Altering SQL Scripts.....       | 150        |
| Performing Data Conversion.....              | 150        |
| Improving Performance for Your Platform..... | 150        |
| Using Oracle.....                            | 151        |
| Using DB2.....                               | 151        |
| Consulting the Global Support Center.....    | 152        |

## Appendix E

|   |            |
|---|------------|
| <b>Preserving Queries and Tree Objects.....</b> | <b>153</b> |
| Preserving Queries and Trees.....               | 153        |
| Preparing the Database.....                     | 154        |
| Creating a New Project.....                     | 154        |
| Comparing the New Project.....                  | 155        |
| Copying the Project.....                        | 156        |
| Testing the Project.....                        | 156        |

|   |     |
|---|-----|
| ReExporting the PeopleTools Tables..... | 156 |
|---|-----|

## Appendix F

|  |            |
|--|------------|
| <b>Planning for Upgrade Testing.....</b>   | <b>159</b> |
| Understanding Testing Techniques.....      | 159        |
| Deciding When to Test.....                 | 159        |
| Evaluating Your Testing Requirements.....  | 160        |
| Defining Your Testing Strategy.....        | 160        |
| Understanding Your Testing Strategy.....   | 160        |
| Evaluating Unit Testing .....              | 160        |
| Evaluating System Testing.....             | 161        |
| Evaluating Integration Testing.....        | 161        |
| Evaluating Parallel Testing.....           | 161        |
| Evaluating Performance Testing.....        | 162        |
| Evaluating User Acceptance Testing.....    | 162        |
| Evaluating Regression Testing.....         | 162        |
| Determining the Testing Conditions.....    | 163        |
| Developing Your Test Plan.....             | 163        |
| Developing Test Scripts.....               | 164        |
| Reviewing Tips and Techniques.....         | 165        |
| Reducing the Time of Upgrade Process.....  | 165        |
| Performing Testing on Up to Date Data..... | 165        |
| Performing Test Move to Production.....    | 166        |
| Tracking Issues.....                       | 166        |
| Reviewing Testing Tools.....               | 166        |
| Discussing Change Control.....             | 166        |
| Discussing Back Up Procedures.....         | 166        |
| Evaluating Unexpected Results.....         | 167        |
| Evaluating Reasons for Failure.....        | 167        |

## Appendix G

|  |            |
|--|------------|
| <b>Using the Comparison Process.....</b>   | <b>169</b> |
| Understanding the Comparison Process.....  | 169        |
| Reviewing Source and Target Columns.....   | 170        |
| Reviewing the Action Column.....           | 171        |
| Reviewing the Upgrade Column.....          | 171        |
| Putting it All Together.....               | 172        |
| Understanding Upgrade Compare Reports..... | 172        |

|                               |     |
|-------------------------------|-----|
| Reviewing Report Columns..... | 173 |
| Using Reports.....            | 173 |

## Appendix H

|   |            |
|---|------------|
| <b>Upgrading the Content Provider Registry.....</b>             | <b>177</b> |
| Understanding the Content Provider Registry Upgrade.....        | 177        |
| Copying Your Enterprise Portal Database.....                    | 178        |
| Upgrading Enterprise Portal PeopleTools.....                    | 179        |
| Updating Registry Permission Lists.....                         | 179        |
| Understanding Registry Permission Lists Updates.....            | 179        |
| Updating Portal Registry.....                                   | 179        |
| Deleting the Database Cache.....                                | 180        |
| Creating the Portal Project.....                                | 180        |
| Understanding Portal Project Creation.....                      | 180        |
| Creating the Target Enterprise Portal Project.....              | 181        |
| Cleaning the Target Enterprise Portal Project.....              | 182        |
| Deleting the Target Enterprise Portal Database Cache.....       | 182        |
| Copying the Target Enterprise Portal Project Definition.....    | 182        |
| Creating the Copy of Production Portal Project.....             | 183        |
| Cleaning the Copy of Production Portal Project.....             | 185        |
| Deleting the Copy of Production Database Cache.....             | 185        |
| Comparing the Portal Project.....                               | 186        |
| Reviewing the Portal Project.....                               | 186        |
| Copying the Portal Project.....                                 | 186        |
| Understanding Portal Project Copying.....                       | 187        |
| Copying the Portal Project.....                                 | 187        |
| Deleting the Enterprise Portal Database Cache.....              | 187        |
| Copying Portal Project to Production.....                       | 188        |
| Understanding Portal Project to Production Copying.....         | 188        |
| Copying the Portal Project to File.....                         | 188        |
| Copying the Portal Project From File.....                       | 188        |
| Deleting the Enterprise Portal Database Cache Again.....        | 189        |
| Deleting Obsolete Folders.....                                  | 189        |
| Understanding Obsolete Folder Deletion.....                     | 189        |
| Deleting Obsolete Folders on Enterprise Portal 8.4.....         | 190        |
| Deleting Obsolete Folders on Enterprise Portal 8.8.....         | 190        |
| Updating Registry Folder Permissions.....                       | 190        |
| Understanding Registry Folder Permissions Updates.....          | 190        |
| Updating the Enterprise Portal Registry Folder Permissions..... | 191        |



|   |            |
|---|------------|
| Deleting the Enterprise Portal Cache..... | 191        |
| <b>Index .....</b>                        | <b>193</b> |



# About This Documentation

---

## Understanding This Documentation

This documentation is designed to direct you through the process of upgrading to your new PeopleSoft release.

This section describes information you should know before you begin working with PeopleSoft products and documentation, including PeopleSoft-specific documentation conventions.

---

## Prerequisites

You must complete the tasks in the document *Getting Started on Your PeopleSoft Upgrade* before beginning this upgrade. If you have not yet completed these tasks, do so now.

See PeopleSoft Customer Connection (Implement Optimize + Upgrade, Upgrade Guide, Upgrade Documentation and Software, Upgrade Documentation and Scripts).

---

## Audience

This documentation assumes you have a basic understanding of the PeopleSoft system. One of the most important components of a successful upgrade of your PeopleSoft installation is your onsite experience.

You should be familiar with your operating hardware environment and have the necessary skills to support that environment. You should also have a working knowledge of:

- SQL and SQL command syntax.
- PeopleSoft system navigation.
- PeopleSoft windows, menus, and pages (and how to modify them).
- The World Wide Web.
- Microsoft Windows or Windows NT graphical user interface.

PeopleSoft recommends that you complete training before performing this upgrade.

See PeopleSoft Customer Connection (Oracle University).

---

## Organization

This documentation is divided into chapters, each containing tasks that represent major milestones in the upgrade process:

- Prepare Your Database

- Apply PeopleTools Changes
- Run and Review Compare Reports
- Apply Application Changes
- Complete Database Changes
- Apply Changes to Production Database

This documentation may also contain appendices. When additional information is required to complete an upgrade task, you will be directed to the appropriate appendix.

---

## Related Information

PeopleSoft provides additional information that may help with your upgrade. The following information (as well as updates to our upgrade) is available on PeopleSoft Customer Connection:

- *PeopleSoft Release Notes.* Before you begin your upgrade, read the PeopleTools and PeopleSoft application release notes to determine what has changed in the system and to familiarize yourself with the new features in this release. The release notes also indicate whether you need to upgrade other portions of your system, such as your RDBMS software or batch files.
- *Upgrades Documentation.* The upgrade documentation on PeopleSoft Customer Connection contains information posted after shipment of this release that may not be included in these upgrade instructions. This information may include updates and fixes required at upgrade. Always check the upgrade documentation for the most current documentation and information.
- *Getting Started on Your PeopleSoft Upgrade.* Before beginning a PeopleSoft upgrade, you must complete the tasks in the document *Getting Started on Your PeopleSoft Upgrade*. This document guides you through planning your upgrade as well as installing the software necessary to upgrade to the next PeopleSoft release. If you did not complete the tasks in this documentation, do so now.

---

**Important!** Before upgrading, it is imperative that you check the upgrade documentation on PeopleSoft Customer Connection for updates to the upgrade instructions. We continually post updates as we refine the upgrade process.

---

See PeopleSoft Customer Connection (Implement Optimize + Upgrade, Upgrade Guide, Upgrade Documentation and Software, Upgrade Documentation and Scripts, Release, Enterprise).

# CHAPTER 1

## Prepare Your Database

This chapter discusses:

- Understanding Database Preparation
- Understanding Your Upgrade
- Copying Your Production Database
- Applying Upgrade Planning Files
- Editing Upgrade Planning DB2 Scripts
- Updating Statistics
- Running Initial Audit Reports
- Processing Pending Approvals
- Creating Approval Process Definitions
- Reporting Row Count for Tables
- Preparing Your Database
- Backing Up Demo Databases
- Comparing Customizations
- Identifying Customizations
- Preparing for the Application Upgrade
- Backing Up After Prepare Your Database

---

## Understanding Database Preparation

You must make a copy of your production database before you start preparations for the technical portion of the upgrade. Unless otherwise noted, run these tasks on your Copy of Production database (not the New Release Demo database). These tasks do not use the new PeopleSoft release. You should use your current codeline and current PeopleTools release to perform these tasks unless instructed otherwise.

---

**Important!** You must read the documentation *Getting Started on Your PeopleSoft Upgrade* before you continue with your upgrade. This getting started guide explains the upgrade process, terminology, and setup tasks that *must* be performed prior to starting your upgrade.

---

---

## Task 1-1: Understanding Your Upgrade

This section discusses:

- Understanding PeopleSoft Upgrades
- Verifying the Software Installation
- Defining Upgrade Databases
- Reviewing Upgrade Notes and Tips

### Understanding PeopleSoft Upgrades

This task reviews information you need to know before you begin your upgrade. It explains the different types of databases you will use and provides useful upgrade tips and information you may need to apply before beginning your upgrade.

#### Task 1-1-1: Verifying the Software Installation

Before continuing with the upgrade, you must complete all of the tasks in *Getting Started on Your PeopleSoft Upgrade*, “Install the Software Release.” Verify that the following tasks are complete:

- Installing the new release.
- Applying PeopleTools patches.
- Applying updates required for upgrade.
- Installing the Change Assistant.
- Creating and configuring an upgrade job.
- Setting Configuration Manager profile.
- Reviewing upgrade step properties.

#### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

#### Task 1-1-2: Defining Upgrade Databases

The following databases will be used during your upgrade:

- The New Release Demo database always refers to the database delivered with your new PeopleSoft release. It contains the new and changed database objects you want to add. The New Release Demo database is also referred to as the Demo database later in the upgrade.
- The Copy of Production database refers to the copy of your production database, into which you will add the new and changed objects for this release from the New Release Demo database.

---

**Note.** You will create more than one Copy of Production database. Your second and subsequent copies are referred to as the New Copy of Production.

---

- The Current Release Demo refers to the copy of the demo database for the release you are currently using.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 1-1-3: Reviewing Upgrade Notes and Tips

This section contains information that may apply to your upgrade product. Review the information in this section before beginning your upgrade.

- Performance Recommendations

Before beginning your upgrade, you should plan for performance issues.

See Appendix: “Improving Performance.”

- Microsoft SQL Server 2000 Column Statistics

Microsoft SQL Server 2000 introduced a feature to create user-defined statistics on columns within a table. This feature is not supported by PeopleTools. If you added user-defined statistics to any columns in your PeopleSoft application, it may cause errors to occur during the upgrade steps that alter tables. PeopleSoft recommends that you drop all user-defined statistics on columns of PeopleSoft tables before proceeding with your upgrade.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 1-2: Copying Your Production Database

This section discusses:

- Making a Copy of Production Database
- Increasing Database Space

### Task 1-2-1: Making a Copy of Production Database

Make a copy of your production database. You will upgrade this database, rather than performing the upgrade directly on your production database. Performing an upgrade on a copy of your production database enables you to test your upgrade in a controlled environment. Refer to the administration guide for your database platform for information on copying databases.

---

**Note.** Move to Production: This is a second Copy of Production sometimes referred to as the New Copy of Production. The first Copy of Production, or “old” Copy of Production, will now be the source database (it was the target database in the initial test pass). The second, or “new” Copy of Production, is now the target database.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-2-2: Increasing Database Space

To prepare for the upgrade, you may need to increase the space allocated to your Copy of Production database. Depending on your relational database management system (RDBMS), this may include allocating space to tablespaces or allocating database primary space and log files. Be aware that your new environment needs to accommodate both the existing data in your Copy of Production database as well as the new data, new data structures, and new database objects. Every site and configuration is different, so PeopleSoft cannot offer a guaranteed estimate of your database sizing needs.

As part of the initial upgrade pass, you may need to revisit your initial space allocation settings more than once as you progress through the upgrade. At the end of the initial pass, the final space allocation settings will closely reflect the space you will need to complete any subsequent Move to Production passes. Work with your DBA to ensure that your environment is set up appropriately for both the initial and Move to Production passes.

See PeopleSoft installation documentation for your product line and release.

---

**Note.** Oracle customers also need to alter the tablespace for PSIMAGE and increase it to 200 MB; autoextend on next 10 MB; maxsize unlimited.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 1-3: Applying Upgrade Planning Files

This section discusses:

- Understanding Applying Upgrade Planning Files
- Applying the UPGOPT Project
- Building the UPGOPT Project
- Setting Up Upgrade Planning Security
- Loading Upgrade Planning Messages



## Understanding Applying Upgrade Planning Files

In this task, you apply the upgrade planning files that you downloaded from the Upgrade database on Customer Connection to your current codeline. These files may include Structured Query Report (SQR) programs and scripts that you will execute in later tasks, and a project that you will apply to your Copy of Production database. This project may include records, fields, pages, menus, queries, and process definitions that allow functional users to define conversion information needed for later upgrade tasks.

### Task 1-3-1: Applying the UPGOPT Project

In this step, apply the UPGOPT project to your Copy of Production database using the Copy Project from File process.

To apply the UPGOPT project:

1. Using your current codeline, launch Application Designer and sign on to your Copy of Production database.
2. Select Tools, Copy Project, From File.
3. From the dialog box, select the import directory PS\_HOME\PROJECTS\ (current codeline).
4. Click UPGOPT in the Projects box, and then click Open.
5. Click Copy.

This copies the UPGOPT project onto your Copy of Production database.

#### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

### Task 1-3-2: Building the UPGOPT Project

In this step you create and alter tables, and create views.

To build the UPGOPT project:

1. Using your current codeline, launch Application Designer and sign on to your Copy of Production database.
2. Select File, Open...
3. In the Definition drop-down list box, select Project and click Open to display the list of projects.
4. Select UPGOPT and click Open again.
5. Select Build, Project...
6. Under Build Options, select Create Tables, Alter Tables, Create Views.
7. Click Settings...
8. On the Create tab, select Recreate View if it already exists and Skip Table if it already exists.
9. Select the Alter tab. Ensure that the following fields are set correctly:
  - a. The Adds, Changes, Renames, and Deletes check boxes should be selected under the Alter Any option section.
  - b. Drop Column Options should be set to Drop Column if data present.

- c. Change Column Length Options should be set to Truncate data if field too short.
10. On the Logging tab, select Fatal errors, warnings, and informational messages.
11. On the Scripts tab, select Output to separate files.
12. In the Script File Names box, give your scripts a unique name that reflects this task number and the object being created.
13. Click OK.
14. Under Build Execute Options, select Build script file.
15. Click Build.
16. Using the appropriate SQL query tool for your platform, run the scripts created in the step above. Run the scripts in the following order: Create Tables, Alter Tables, Create Views, Create Indexes.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-3-3: Setting Up Upgrade Planning Security

In this step, you will set up security on your Copy of Production database.

To set up security:

1. Select PeopleTools, Security, Permissions and Roles, Permission Lists.
2. Enter the permission list for the users who will be reviewing and setting up functional requirements for the upgrade, then click Search.
3. Select the Pages tab.
4. Add a row for the menu name LM\_ENRLMT, then click Edit Components.
5. Click the Select All button to authorize all components, then click OK.
6. Add a row for the menu name UPG\_APPRVLS\_INP, then click Edit Components.
7. Click the Select All button to authorize all components, then click OK.
8. Click the Save button.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-3-4: Loading Upgrade Planning Messages

In this step, run a DataMover script to import message text which will be used in later tasks.

The script name for your upgrade path is:

PULMUP88105.DMS

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 1-4: Editing Upgrade Planning DB2 Scripts

Perform this step only if your database platform is DB2 z/OS. DB2 z/OS scripts that create tables need a `set current sqlid` statement so that the tables are created with the correct owner ID. Open each script listed below, then uncomment and modify all the DB2-specific statements to reflect your environment.

For SQL scripts, if the script does not contain DB2-specific statements, add the following line to the top of the script and edit it for your environment inserting the appropriate owner ID in uppercase characters:

```
set current sqlid = 'OWNER_ID';
```

For Data Mover scripts (DMS), if the script does not contain DB2-specific statements, add the following line to the top of the script and edit it for your environment inserting the appropriate owner ID in uppercase characters:

```
set execute_sql set current sqlid = 'OWNER_ID';
```

The following is a list of scripts that you need to edit:

PUUPX07.DMS

PULMOB01.DMS

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

---

## Task 1-5: Updating Statistics

Run this task to improve performance of your compare and copy processes. Have your database administrator update statistics on your database before proceeding with your upgrade. Later in the upgrade, you will update your statistics again due to changes in the database structure.

See Appendix: “Improving Performance.”

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-6: Running Initial Audit Reports

This section discusses:

- Understanding Running Initial Audit Reports
- Run the Initial DDDAUDIT Report
- Run the Initial SYSAUDIT Report
- Create the INITALTAUD Project
- Run the Initial Alter Audit
- Review the Initial Audits

## Understanding Running Initial Audit Reports

In this task, you run and review your initial DDDAUDIT, SYSAUDIT, and Alter Audit reports. Running these reports ensures that your database is as clean as possible for the remainder of the upgrade.

### Task 1-6-1: Run the Initial DDDAUDIT Report

DDDAUDIT is an SQR script that compares your production SQL data tables with the PeopleTools record definitions to identify inconsistencies.

In this step, DDDAUDIT is run using SQR from your current (old) release of PeopleSoft against the Copy of Production to ensure that you are starting with a clean database.

You will review the output from the report in a later step.

See Review the Initial Audits.

See Enterprise PeopleTools PeopleBook: System and Server Administration for your current release.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-6-2: Run the Initial SYSAUDIT Report

SYSAUDIT is an SQR script used to identify “orphaned” PeopleSoft objects. For example, SYSAUDIT can identify a module of PeopleCode that exists but does not relate to any other objects in the system. SYSAUDIT also identifies other inconsistencies within your database.

In this step, SYSAUDIT is run using SQR from your current (old) release of PeopleSoft against the Copy of Production to ensure that you are starting with a clean database.

You will review the output from the report in a later step.

See Review the Initial Audits.

See Enterprise PeopleTools PeopleBook: System and Server Administration for your current release.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-6-3: Create the INITALTAUD Project

In this step, you create the INITALTAUD project and use it to run your initial Alter Audit. Creating this new project now ensures that all the records with type *Table* in your system are audited. This project also includes any custom records that you created in your system.

---

**Note.** If your old PeopleTools release is 8.44 or later, this step can be automatically run by Change Assistant. To automatically run this step, open the step properties for this step in Change Assistant and change the type from ManualStop to CreateProject. Then run your job.

---

To create the INITALTAUD project:

1. Launch PeopleTools and sign on to the Target database.
2. From Application Designer, select File, New...
3. Select Project, and then click OK.
4. Select Insert, Definitions into Project...
5. Select Records from the Object Type drop-down list box.
6. Select Table from the Type drop-down list box.
7. Click Insert, and then click Select All.
8. Click Insert, and then click Close.
9. Select File, Save All.
10. Enter the project name *INITALTAUD*.

---

**Warning!** You must name the project *INITALTAUD* or else the next step will fail.

---

11. Click OK.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-6-4: Run the Initial Alter Audit

To verify that the PeopleTools definitions are synchronized with the underlying SQL data tables in your database, run the PeopleTools alter record process on all records in your system. This process, called an Alter Audit, compares the data structures of your database tables with the PeopleTools definitions to identify inconsistencies. Alter Audit then creates SQL scripts with the data definition language (DDL) changes that are required to synchronize your database with the PeopleTools definitions.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-6-5: Review the Initial Audits

In this step, you review the audits you performed earlier in this task. Review the audits before proceeding with the upgrade.

Review the output from the SYSAUDIT and DDDAUDIT reports and correct any discrepancies. When application tables are deleted from the Application Designer, they are not automatically deleted from the system tables. PeopleSoft takes this precaution in case you have customized information that you want to preserve. When you review your DDDAUDIT listing, these tables are listed as a discrepancy between the PeopleSoft application and the database.

Now you must decide whether to drop these tables or retain them. In most cases, you will want to drop the tables, using your SQL tool to drop the tables from the system catalogs. If you have customized information or processes that access these tables, you may want to retain them in the system tables even though they will no longer be accessed or updated by PeopleSoft. Drop any unnecessary deleted tables now so that your future DDDAUDIT reports will be as clean as possible.

The Alter Audit produces the scripts INITIALAUD\_ALTTBL.SQL, INITIALAUD\_CRTIDX.SQL, and INITIALAUD\_CRTTRG.SQL. These scripts contain SQL that corrects any discrepancies between your PeopleTools Record definitions and the database system catalog table definitions. Review the Alter Audit output and correct any discrepancies.

---

**Note.** Triggers are always dropped and re-created during the alter process and will always show up in the generated Alter Audit script. You can ignore the generated script for triggers.

---



---

**Note.** For Microsoft SQL Server and DB2 UNIX/NT platforms, if your database has tables containing the MSSCONCATCOL or DBXCONCATCOL column, you will see SQL alter the tables and re-create their associated indexes, even though the underlying tables and indexes may not have changed.

---

---

**Note.** You will rerun the DDDAUDIT and SYSAUDIT SQR scripts later in the upgrade. If you wish to preserve the log files generated by Change Assistant from this run, you will need to manually rename the files after completing this task.

---

See Enterprise PeopleTools PeopleBook: System and Server Administration for your current release.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 1-7: Processing Pending Approvals

The new release of Oracle's PeopleSoft Enterprise Enterprise Learning Management (ELM) uses a new framework for approval processing. Before the database is upgraded, all supplemental learning, enrollments, and registrations that are currently in "Pending Approval" or "Payment Approval" status must be manually approved or declined. After the upgrade, any enrollments that are still in Pending Approval status will not be accessible by managers. However, learning administrators will have the ability to approve these enrollments from the Activity or Program Roster pages.

---

**Note.** The upgrade data conversion process will convert any enrollments and registrations remaining in Payment Approval status to Pending Approval.

---



---

**Note.** Supplemental learning which remains in Pending Approval status will be inaccessible once the upgrade is completed.

---

To process pending approvals:

1. To get a report on enrollments pending approval:
  - a. Select Enterprise Learning, Learning Reports, Activity Roster.
  - b. If you already have a run control ID from previously in the upgrade, use that ID in this step. Otherwise, do the following to add a new run control ID:
    - i. Select Add a New Value.
    - ii. Enter a new run control ID.
  - c. Select the enrollment status *Pending Approval* (PEAP). Leave other parameter values blank.
  - d. Run the report.
  - e. Save the report for reference later.
  - f. Go back to run the report, select the enrollment status *Payment Approval* (PPYA). Leave other parameter values blank.
  - g. Run the report.
  - h. Save the report for reference later.

2. To get reports on registrations pending approval (for each program):
  - a. Select Enterprise Learning, Learning Reports, Program Roster.
  - b. Reuse the run control ID from the previous report.
  - c. Select or enter a program code or program name. Leave other values blank.
  - d. Run the report.
  - e. Save the report for reference later.
  - f. Repeat steps c-e for each program in the system.
3. Review the generated reports and manually approve or decline all pending enrollments and registrations possible. Those that remain in pending approval status will not be accessible by managers after the upgrade. Again, learning administrators will have the ability to approve these from the Activity or Program Roster pages.

See PeopleSoft Enterprise Learning Management PeopleBook for your current release, “Enrolling and Registering in Learning Activities and Programs,” Approving Enrollment and Registration Requests.

4. To identify supplemental learning requests pending approval, use the SQL query tool of your choice and execute the following SQL:

```
SELECT LM_ADHC_LRN_ID, LM_PERSON_ID, LM_PER_TRN_NM, LM_PER_TRN_ST_DT, LM_PER_TRN_ED_DT, LM_REQUESTOR_ID, LM_APPR_ID FROM PS_LM_ADHC_LRN_TBL WHERE LM_ADHC_LRN_STTS = 'PEAP'
```

5. Using the output from the SQL statement, manually approve or decline all pending supplemental learning requests as necessary. Supplemental learning requests that remain in Pending Approval status will be inaccessible once the upgrade is completed. Therefore, it is important that all requests be approved or denied prior to upgrading the database.

See PeopleSoft Enterprise Learning Management PeopleBook for your current release, “Managing Supplemental Learning”.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-8: Creating Approval Process Definitions

This task creates process definitions for approval processing by setID. You have two options from which to choose: option one creates approval process definitions for *all* setIDs in the Learning Management application, while option two creates process definitions for a subset of setIDs. To improve performance, we recommend option two. While it does not matter which setIDs are used, we do recommend you create process definitions for the same number of setIDs as you have learning environments. For example, if you have five learning environments, you should create process definitions for five setIDs.

To create the approval process definitions:

1. Select Set Up ELM, Upgrade, Approval Process Definitions.



2. Select one of the two radio buttons.
3. If you selected the option for specific setIDs, enter the setIDs in the grid.
4. Save the page.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 1-9: Reporting Row Count for Tables

You may find it helpful to run a report that identifies any table without rows, that is, any table not used in your production database. This information can help you determine whether to accept a change from the New Release Demo database. The UPGCOUNT process reports the row counts of all PeopleSoft tables in your database. You can find the resulting report (UPGCOUNT.LIS) in your C:\TEMP directory.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 1-10: Preparing Your Database

This section discusses:

- Understanding Database Preparation
- Verify Database Integrity
- Clean the PSOBJCHNG Table
- Drop PeopleTools Tables
- Shrink Images
- Purge Message Queues

### Understanding Database Preparation

In this task, you perform a variety of steps in preparation for the PeopleTools upgrade. These steps prevent errors in tasks later in the upgrade.

## Task 1-10-1: Verify Database Integrity

The DBCC CHECKDB command is run to perform a database consistency check on your Copy of Production database. A database consistency check ensures that your database platform environment is clean and minimizes any potential upgrade errors due to possible database corruption.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms               | Languages |
|----------------------|----------------|----------|-------------------------|-----------|
| Target               | Both           | All      | MS SQL Server<br>Sybase | All       |

## Task 1-10-2: Clean the PSOBJCHNG Table

This step deletes all data stored in the PSOBJCHNG table, which contains all renamed records and fields. The data stored in the PSOBJCHNG table must be deleted before starting your upgrade. The build process looks in this table when running alter renames. Change Assistant will execute the following SQL:

```
DELETE FROM PSOBJCHNG
```

---

**Note.** Move to Production: If you rename records or fields later in your upgrade, you should expect to see rows in the PSOBJCHNG table at the end of the upgrade pass. During the Move to Production these rows will be copied from your old Copy of Production to your new Copy of Production. Thus, this step is not necessary during Move to Production.

---

See “Apply Application Changes,” Modifying the Database Structure.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 1-10-3: Drop PeopleTools Tables

In this step, you drop PeopleTools tables to ensure the successful completion of your upgrade. You will drop the following tables, if they exist in your database, using the SQL tool of your choice.

Drop the following tables:

- PS\_PSMCFQUEUESLANG

---

**Note.** The table, PS\_PSMCFQUEUESLANG, contains no data and can be safely dropped. Do *not* drop the table PSMCFQUEUESLANG.

---

- PSOPTSTATUS

The table, PSOPTSTATUS, will be converted into a view and can be safely dropped. Do not drop the view PSOPTSTATUS.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-10-4: Shrink Images

If you have customized images stored in your database, you may need to shrink these images before updating PeopleTools system tables later in the upgrade. Large image fields could cause that step to fail because it is not possible to bind long raw data that is longer than 32 KB.

To shrink images using a PeopleTools 8.44 release later than 8.44.14 or any PeopleTools release later than 8.45.07:

1. Launch Configuration Manager and select the Profile tab.
2. Select the profile for the upgrade database and click Edit.
3. Select the Common tab.
4. Select the radio button Convert DIB and BMP images to JPG.
5. Click OK.

---

**Note.** If you reshrink images, select Don't Convert, but Shrink Images to Image Size Limit. Specify the number of bytes for the image size limit.

---

6. Launch Application Designer.
7. Select Tools, Upgrade, Convert Images...
8. Select Convert Static Images in Image Catalog.
9. Click Start to convert or shrink images.
10. Select Tools, Upgrade, Convert Images...
11. Select Convert Dynamic Images for fields. Select the box for all of the fields listed.
12. Click Start to convert or shrink images.

If you are using a PeopleTools release earlier than 8.44.15 or a PeopleTools 8.45 release earlier than 8.45.08, you will need to manually save and temporarily remove any custom images greater than 32 KB. Using your SQL query tool, run the following SQL to identify images greater than 32 KB:

```
-- CREATE A TABLE TO HOLD THE CONVERTED IMAGE
CREATE TABLE PS_CONVIMG (CONTNAME VARCHAR2(30), IMAGE SIZE BLOB);
-- LOAD CONVERTED DATA INTO THE TABLE
INSERT INTO PS_CONVIMG SELECT CONTNAME, TO_LOB(CONTDATA) FROM PSCONTDEFN;
-- RETRIEVE IMAGES OVER 32K
SELECT CONTNAME, DBMS_LOB.GETLENGTH(IMAGE SIZE) IMAGE SIZE FROM PS_CONVIMG WHERE⇒
  DBMS_LOB.GETLENGTH(IMAGE SIZE) > 32768;
```

To manually save images greater than 32 KB:

1. In Application Designer, insert your images into a project. Select Insert, Definitions into Project.
2. Save the project.

3. Copy the images to file. Select Tools, Upgrade, Copy Project to File.
4. Delete the rows for the images in your project from the PSCONTDEFN table.
5. When you are finished with the upgrade, copy the project from file to restore your custom images. Select Tools, Upgrade, Copy Project from File.

See “Apply PeopleTools Changes,” Updating PeopleTools System Tables.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Oracle    | All       |

## Task 1-10-5: Purge Message Queues

Ensure that all your message transactions are complete before starting the upgrade. Message functionality and structure changed in the new release, which will prevent old messages from processing successfully.

This step runs the following Data Mover script (DMS), found in the %PS\_HOME\SCRIPTS directory of your old release codeline, on your Copy of Production database to purge your message queues:

```
APPMMSGPURGEALL.DMS
```

---

**Warning!** A script of the same name is found in the codeline of the release to which you are upgrading. Do not use this script; it will not run successfully.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-11: Backing Up Demo Databases

This section discusses:

- Backing Up Current Release Demo
- Backing Up New Release Demo

### Task 1-11-1: Backing Up Current Release Demo

Back up your Current Release Demo database now. This upgrade requires you to run scripts on this database. Before the upgrade starts, you need to take a backup of this environment to preserve your vanilla demo implementation.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Current Demo         | Initial        | All      | All       | All       |

## Task 1-11-2: Backing Up New Release Demo

Back up your New Release Demo database now. This upgrade requires you to run scripts on this database. Before the upgrade starts, you need to take a backup of this environment to preserve your vanilla demo implementation.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

---

## Task 1-12: Comparing Customizations

This section discusses:

- Modifying Compare Report Options
- Running Compare UPGCUST
- Running UPGCUST Filter Script
- Reviewing UPGCUST Compare Log
- Restoring Current Release Demo

---

**Note.** In this task, you identify customizations on the Copy of Production by running a database compare against the Current Release Demo database.

---

### Task 1-12-1: Modifying Compare Report Options


PeopleSoft Change Assistant templates are delivered with the default report filters turned on. This limits the size of the reports and keeps them manageable. Before you start the compare, review the compare options in your Change Assistant template step properties and modify them based on your specific requirements.

If you decide not to modify the compare options, the objects are still compared. However, the results are only available online in Application Designer, and are not written into the compare reports. The compare reports are tools to help you review changed objects. However, based on the report filters you select, you may need to review the action flags for other objects in the compare project in Application Designer.

For example, you can modify the compare options so the report contains customized objects that are present in your Copy of Production database but are absent from the Old Release Demo database. Alternatively, you can review these objects online, through Application Designer, after the database compare.

To modify the upgrade compare options:

1. Highlight the Run Compare UPGCUST step and right-click.
2. Select Step Properties  
The Step Definition dialog box appears.
3. Click Upgrade.  
The Compare and Report dialog box appears.
4. Click Options.
5. Select the Report Filter tab.  
The default options include your custom changes on the reports.
6. Change the default options as necessary and click OK.



Upgrade Options page, Report Filter tab

7. In the Compare and Report dialog box, click OK.
8. In the Step Definition dialog box, click OK.
9. Select File, Save Job.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 1-12-2: Running Compare UPGCUST

This step creates a project on your Copy of Production database called UPGCUST and executes a database compare of all comparable object types. This compare is run to identify all customizations on the Copy of Production database. The database compare occurs between your Copy of Production and the Current Release Demo database. The following comparable object types are omitted from the comparison:

- Message catalog entries.
- Portal registry user home pages.
- Portal registry user favorites.
- File reference type codes.
- Java portlet user preferences.

Message catalog entries are exported and imported with Data Mover in a later step. Portal registry user home pages, portal registry user favorites, file reference type codes, and Java portlet user preferences remain in the Copy of Production environment and are not copied from the New Release Demo database.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Current Demo         | Initial        | All      | All       | All       |

## Task 1-12-3: Running UPGCUST Filter Script

This step removes all objects from the UPGCUST project that are not marked *\*Changed* or *\*Unchanged* in your Copy of Production environment. It is used to isolate only custom objects in the UPGCUST project.

The script name for your upgrade is:

```
PUUPX99.DMS
```

See Appendix: “Using the Comparison Process.”

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 1-12-4: Reviewing UPGCUST Compare Log

In this step, review the log file and compare reports generated by the database compare in the previous step to ensure that it completed successfully. A detailed analysis of these compare reports is not necessary. Later in the upgrade, you will review a new set of compare reports when customizations are compared to the New Release Demo database.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 1-12-5: Restoring Current Release Demo

Restore your Current Release Demo database from the backup taken earlier in the upgrade. The backup was taken before rename scripts ran against the Current Release Demo. This is done to restore the environment to a vanilla demo implementation.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Current Demo         | Initial        | All      | All       | All       |

---

## Task 1-13: Identifying Customizations

In this task, identify your modifications to Mass Change, EDI, Message Catalog, SQR Strings, XML Service Information, Verity Based Indexes, Setup Manager data, and related language system data, so that you can reload them later in the upgrade process.

The upgrade tasks will replace all Mass Change processes, Verity Based Indexes, and Setup Manager data. You cannot print Mass Change code. Be sure you have extracted your modifications to reapply them later. You must extract your modifications, using cut and paste, to a file for manual reapplication later. EDI tables must be handled in the same way. Reload additional data and review customizations in PeopleSoft-delivered data.

Message sets 0-19,999 will be overlaid during the upgrade, so any customizations you have made in this range will be lost. In addition, all SQR strings will be replaced. To save your customizations, cut and paste your changes to a file and manually reapply them.

Be aware that the PeopleSoft-loaded data must not be overwritten.

If you have multiple languages loaded, you should save any custom data you have in related language tables for system data. For these tables, data will be exported from the New Release Demo database when you export related language system data, and imported to your Copy of Production when you import related language system data. The import may delete your custom data, depending on the import option.

The tables that need to be reviewed are listed in the following scripts. These scripts can be found in your new release PS\_HOME\SCRIPTS directory.



---

**Important!** The script(s) below are delivered with and run from your new PeopleSoft release. These scripts are *not* run in this task. You will run these scripts later in the upgrade process.

---

Review the tables that will be overwritten in these scripts:

| Tables                  | Script       |
|-------------------------|--------------|
| Message Catalog         | DLUPX01E.DMS |
| SQR Strings             | DLUPX04E.DMS |
| EDI                     | DLUPX05E.DMS |
| Mass Change             | DLUPX06E.DMS |
| XML Service Information | DLUPX13E.DMS |

If your database contains translations, review the list of related language system data tables that will be exported and imported in these scripts:

---

**Note.** Move to Production: Once you have reapplied these customizations at the end of your initial upgrade pass, you will not need to apply them again. The affected tables are moved from the old Copy of Production to the New Copy of Production by the scripts listed in the following table:

---

| Tables                  | Scripts                      |
|-------------------------|------------------------------|
| Mass Change             | MVAPPEXP.DMS<br>MVAPPIMP.DMS |
| EDI                     | MVPRDEXP.DMS<br>MVPRDIMP.DMS |
| Strings                 | MVAPPEXP.DMS<br>MVAPPIMP.DMS |
| Messages                | MVAPPEXP.DMS<br>MVAPPIMP.DMS |
| XML Service Information | MVPRDEXP.DMS<br>MVPRDIMP.DMS |

## See Also

“Apply Application Changes,” Loading Data for Data Conversion.

“Apply Application Changes,” Loading Data to Complete System Setup.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 1-14: Preparing for the Application Upgrade

This section discusses:

- Creating a Copy of RecField Definitions
- Deleting Old Pagelet Wizard Data
- Editing the System Data Swap Script
- Editing the PeopleTools Swap Script
- Exporting Objectives Data

**Note.** In this task, you perform a variety of steps in preparation for the application portion of the upgrade. These steps will prevent errors in tasks later in the upgrade.

### Task 1-14-1: Creating a Copy of RecField Definitions

This step creates a copy of the contents of PSRECFIELD, before the upgrade is begun. It is used by the data conversion code to determine the structure of tables that may have been impacted by fixes you applied. The script name is:

PUUPX07.DMS

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | Both     | All       | All       |

### Task 1-14-2: Deleting Old Pagelet Wizard Data

This step is only applicable if you have already upgraded your production application to PeopleTools 8.46 or greater.

In this step, you run a script to delete the Common Component Pagelet Wizard (PW) data to ensure that when the UPGPT846PP conversion program is run subsequently, the old existing Common Components Pagelet Wizard data is not re-entered into the PeopleTools Pagelet Wizard tables. If you do not run the script, then items that were removed from the PeopleTools version of Pagelet Wizard, but still exist in the Common Components version of Pagelet Wizard, will be copied back into the PeopleTools version when the UPGPT846PP conversion program is run.

The script also updates the Common Component portal option tables with the existing values in the PeopleTools portal options tables. If you do not run the script, then changes made to the current PeopleTools options tables may be overwritten with values from the Common Components portal options when the UPGPT846PP conversion program is run. The affected values include the default registry prefix, default owner ID, and the default style sheet.

Only run the script if *both* of the following conditions are met.

- Your current production application release database is *already* on PeopleTools 8.46 or greater.
- The table PS\_EOPPB\_LINKPATHS exists on the Target database.

If both of the above conditions are met, then run the following script:

```
PTPPB_EOPPB.DMS
```

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 1-14-3: Editing the System Data Swap Script

This step should only be done if your Copy of Production has a base language other than English. In the next step you will be swapping all system data tables that have related language on your New Release Demo database, so that it is translated correctly when you copy to your Copy of Production. You will first need to edit the script that will do the swapping to set your New Release Demo database language to the same language as your Copy of Production. To do this, edit the line that says, "SET BASE\_LANGUAGE <NEW LANGUAGE\_CD>," changing <NEW LANGUAGE\_CD> to the language code on your Copy of Production. The swap system data script for your path is:

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages                 |
|----------------------|----------------|----------|-----------|---------------------------|
| Target               | Initial        | All      | All       | Non-English Base Language |

## Task 1-14-4: Editing the PeopleTools Swap Script

This step should only be completed if your Copy of Production has a base language other than English. In a later step you will swap all PeopleTools Managed Object tables that have related languages on your New Release Demo database so that it is translated correctly when you copy to your Copy of Production. In this step you edit the swap script to set your New Release Demo database language to the same language as your Copy of Production.

To edit the swap script:

1. Find the line SET BASE\_LANGUAGE NEW LANGUAGE\_CD.
2. Change NEW LANGUAGE\_CD to the language code on your Copy of Production.

The swap script for your upgrade path is:

PT\_RELEASE\_SWAP.DMS

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages                 |
|----------------------|----------------|----------|-----------|---------------------------|
| Target               | Initial        | All      | All       | Non-English Base Language |

**Task 1-14-5: Exporting Objectives Data**

Run a Data Mover script to export data from Objectives tables and load that data into temporary tables for use later during application data conversion.

The script name for your upgrade path is:

PULMOB01.DMS

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

**Task 1-15: Backing Up After Prepare Your Database**

Back up your Copy of Production database now. This enables you to restart your upgrade from this point, should you experience any database integrity problems during the remaining tasks in the upgrade process.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## CHAPTER 2

# Apply PeopleTools Changes

This chapter discusses:

- Understanding PeopleTools Changes
- Verifying Upgrade User
- Performing Script Modifications
- Updating PeopleTools System Tables
- Turning Off Change Control
- Loading Model Definition Data
- Loading Message Data
- Reviewing PeopleTools Objects
- Exporting and Copying Projects
- Populating Tablespace Data
- Building Updated PeopleTools Project
- Migrating Records to New Tablespaces
- Loading Base Data
- Loading Language Data
- Loading PeopleTools Data
- Loading PeopleTools Definition Group
- Converting PeopleTools Objects
- Creating PeopleTools Views
- Setting Object Version Numbers
- Backing Up After PeopleTools Upgrade

---

## Understanding PeopleTools Changes

In order to implement a successful upgrade, you must apply the necessary PeopleTools changes. This involves updating PeopleTools system tables, copying and building PeopleTools projects, loading PeopleTools seed data, and converting PeopleTools objects. From this point forward, you run all steps using your newly installed version of PeopleTools.

---

**Note.** Unless otherwise indicated, all scripts can be found in your new release PeopleSoft codeline PS\_HOME\SCRIPTS directory. The actual script name is indicated in the description of each step in uppercase letters.

---

---

## Task 2-1: Verifying Upgrade User

In this task, you verify that the user performing the upgrade steps has proper permissions to complete the upgrade.

Ensure that your upgrade user has PeopleSoft administrator privileges. This allows access to the PeopleSoft portal in order to make necessary security changes for the upgrade and to run the Portal Application Engine upgrade program. You use this ID to update the security setting for your other users so they can sign on after the upgrade.

---

**Warning!** You must perform this step now using your old version of PeopleTools. If you skip this step, or if your user has insufficient PeopleSoft administrator privileges, you will not be able to complete your upgrade. You cannot complete this step later in the upgrade process. Perform the following steps to grant administrator privileges now.

---

To grant your upgrade user PeopleSoft administrator privileges:

1. From the browser, select PeopleTools, Security, User Profiles, User Profiles.
2. Select the user ID for your upgrade user.
3. Select the Roles tab.
4. Add the role *PeopleSoft Administrator* if it is not already granted to your upgrade user.
5. Save the User Profile.

See Enterprise PeopleTools PeopleBook: Security Administration for your new release.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 2-2: Performing Script Modifications

This section discusses:

- Understanding Script Modifications
- Update Configuration Manager Profile
- Run a DBTSFIX Report
- Edit the DBTSFIX Output Scripts
- Edit the GRANT Script

- Edit the PSLANGUAGES Script
- Edit the TLSUPGNONCOMP Script
- Edit the PTxxxTLS Scripts
- Edit the DB2 Scripts
- Edit Move to Production Import Scripts
- Edit Move to Production Password
- Edit the DDLDB2 Script
- Edit the DDLDBX Script
- Edit the DDLORA Script
- Edit the DDLIFX Script
- Edit the MSGTLSUPG Script
- Edit Multilingual Step Properties

## Understanding Script Modifications

In this task, you perform preparation steps and make manual modifications to scripts delivered with your new PeopleSoft release. You must make the following modifications before proceeding with the remainder of your upgrade.

---

**Note.** Move to Production: These steps will be repeated in the Move to Production (MTP) pass. The script you previously edited may be acceptable, or you may need to change it again if your New Copy of Production has a different security or data definition language (DDL) configuration.


---

### Task 2-2-1: Update Configuration Manager Profile

The Configuration Manager default profile needs to be updated to use values for your new release PS\_HOME. Change Assistant uses this information to run automated steps for the rest of the upgrade. These are settings on the workstation and you need to do this for each workstation you may use during the upgrade.

To update the profile:

1. Open Configuration Manager.
2. On the Profile tab, select the Default profile, click Edit, and select the Common tab.



Edit Profile - Default dialog box

**Note.** The Input Directory must be <PS\_HOME>\data\, substituting <PS\_HOME> with your directory. The Output Directory must be the same.

3. The Log Directory is set by Change Assistant and should be left as is.
4. Click on Process Scheduler tab and verify your SQR settings. Change Assistant will use these settings to launch SQR.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 2-2-2: Run a DBTSFIX Report

The DBTSFIX.SQR script aligns the tablespaces in the delivered release scripts with the Target database used during the upgrade. This process generates new release scripts, conforming to the RELxxxDBTSFIX.SQL naming convention that you run in a later task. Run this script to preserve your existing table-to-tablespace mapping in the Target database. The result of this task will be a RELxxxDBTSFIX.SQL script in which xxx represents a release number (for example, 800, 810, 811, 812, and so on) associated with your particular path.



---

**Note.** Before running this step, verify that the PS\_HOME values are set correctly in the Change Assistant environment for your upgrade job. Change Assistant uses the PS\_HOME information to determine which scripts need to be generated.

---



---

**Important!** Do not run the new release script at this point. You will be instructed to run this script later in the upgrade process.

---

## Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | Oracle<br>Informix<br>DB2 UNIX/NT<br>DB2 z/OS | All       |

## Task 2-2-3: Edit the DBTSFIX Output Scripts

Edit the generated RELxxxDBTSFIX scripts according to the comments within each script. Verify that the data definition language (DDL) is accurate for your environment for tablespaces, database names, owner IDs, and so forth. The scripts can be found in your Change Assistant output directory for this upgrade path.

---

**Warning!** Do not run output scripts at this time. At this point in the upgrade process, you must only review the DBTSFIX output scripts.

---



---

**Note.** For DB2 z/OS customers only: When upgrading from one PeopleSoft release to the next, it is possible to move tables from a tablespace using a 4-KB buffer pool to one using a 32-KB buffer pool. The tablespaces PSIMAGE and PSIMGR use 32-KB buffer pools in PeopleSoft-delivered applications. To maintain the tablespace schema used at your site, the DBTSFIX.SQR script will revise the upgrade scripts with the database and tablespace information from your database (the Target database). Tables assigned to tablespaces PSIMAGE or PSIMGR in the upgrade scripts are the exception to this approach. Note that PeopleSoft has reassigned some tables to PSIMAGE or PSIMGR because they now require a 32-KB buffer pool. You must manually edit the “Create Table” statements in the upgrade scripts to replace the tablespace name PSIMAGE or PSIMGR with an appropriate tablespace name in your implementation that utilizes a 32-KB buffer pool. The database name must also be replaced with the value corresponding to the tablespace you are using.

---

## Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | Oracle<br>Informix<br>DB2 UNIX/NT<br>DB2 z/OS | All       |

## Task 2-2-4: Edit the GRANT Script

Edit `PS_HOME\SCRIPTS\GRANT.SQL` and make the necessary modifications as documented in the script.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 2-2-5: Edit the PSLANGUAGES Script

Edit `PS_HOME\SCRIPTS\PSLANGUAGES.DMS` and make the necessary modifications as documented in the script.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 2-2-6: Edit the TLSUPGNONCOMP Script

Edit `PS_HOME\SCRIPTS\TLSUPGNONCOMP.DMS` and make the necessary modifications as documented in the script.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 2-2-7: Edit the PTxxxTLS Scripts

This step applies only if you are running on a DB2 z/OS platform.

To edit the PTxxxTLS scripts:

1. Edit all the scripts in the PS\_HOME\SCRIPTS directory on the file server that conform to this file naming convention:

```
PTxxxTLS.DMS
PTxxxTLSyyy.DMS
```

The xxx represents a PeopleTools release greater than your current PeopleTools release and yyy represents the three-letter language code.

2. Uncomment and modify the set owner ID command within each script, as in the following example:

```
set execute_sql set current sqlid = 'OwnerId In Upper Case';
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 2-2-8: Edit the DB2 Scripts

Perform this step only if your database platform is DB2 z/OS. DB2 z/OS scripts that create tables need the `set current sqlid` statement so that the tables are created with the correct owner ID. Open each script listed below, then uncomment and modify all of the DB2-specific statements to reflect your environment.

For SQL scripts, if the script does not contain DB2-specific statements, add the following line to the top of the script and edit it for your environment:

```
set current sqlid = 'OWNERID (in uppercase)';
```

For Data Mover scripts (DMSs), if the script does not contain DB2-specific statements, add the following line to the top of the script and edit it for your environment:

```
set execute_sql set current sqlid = 'OWNERID (in uppercase)';
```

Following is a list of the scripts you need to edit:

```
DB2TMPIDXCREATE.SQL
DLUPX02I.DMS
DLUPX13I.DMS
DLUPX14I.DMS
DLEPSYSI.DMS
DLEPLASYSI.DMS
DLUPX96I.DMS
PT_RELEASE_IMPORT.DMS
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 2-2-9: Edit Move to Production Import Scripts

Perform this step only if your database platform is DB2 z/OS.

During the Move to Production, there are several scripts that export data from the previous Copy of Production to the New Copy of Production. These scripts export the tables to a DAT file. When the tables are exported, all the table attributes, including the database specific information (table owner, database name, and tablespace name), are stored in the DAT file. When you run the import script, it tries to create the tables and indexes using the database-specific information from the DAT file. So even though you ran the import script against your Copy of Production, you would still create tables in the upgraded database (which is the source database for the Move to Production step). To create the tables in the Target database, open each script listed below, then uncomment and modify all of the DB2-specific statements to reflect your environment.

You will also need to add the following command into MVPRDIMP.DMS, near the end of the script, just after the REPLACE\_DATA PSSTATUS command, but before the REPLACE\_VIEW PSTEMPTBLCNTVW command, to change *ownerid* to the owner ID of your database.

```
Update PSSTATUS set OWNERID='OWNERID (in uppercase)';
```

Following is a list of the scripts you need to edit:

```
MVAPPIMP.DMS
MVPRDIMP.DMS
```

If you prefer, you can copy these overrides from the xxDMODBO.DMS script that was generated from DBSetup while installing your database. Make sure you remove the SET NO RECORD if you copy from the DBSetup generated file.

See Enterprise PeopleTools PeopleBook: Data Management for your new release.

See “Apply Changes to Production Database,” Performing the Move to Production.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | DB2 z/OS  | All       |

## Task 2-2-10: Edit Move to Production Password

If your access ID and access password are different in the Copy of Production database than in the New Copy of Production database, you need to reset the access password in the MVPRDIMP.DMS script.

To modify passwords in your New Copy of Production database, append the following to your MVPRDIMP.DMS script and replace *ownerID*, *accessID*, and *accesspswd* with your values in the New Copy of Production database:

```
UPDATE PSSTATUS set OWNERID = 'ownerID';
UPDATE PSACCESSPRFL SET ACCESSID = 'accessID',
```

```
ACCESSPSWD = 'accesspswd', ENCRYPTED = 0;
ENCRYPT_PASSWORD *;
```

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | All       | All       |

## Task 2-2-11: Edit the DDLDB2 Script

Edit PS\_HOME\SCRIPTS\DDLDB2.DMS. At the bottom of this script, you will see an insert into PSDDLDEFPARMS. This insert contains default information used when creating a table, an index, a unique index, or a tablespace. Verify with your database administrator that the last value for each row is appropriate for your environment by checking the values currently stored in your PSDDLDEFPARMS table. Otherwise, the values will be reset to the default values delivered by PeopleSoft in this script.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 2-2-12: Edit the DDLDBX Script

Edit PS\_HOME\SCRIPTS\DDLDBX.DMS. At the bottom of this script, you will see an insert into PSDDLDEFPARMS. This insert contains default information used when creating a table, an index, a unique index, or a tablespace. Verify with your database administrator that the last value for each row is appropriate for your environment by checking the values currently stored in your PSDDLDEFPARMS table. Otherwise, the values will be reset to the default values delivered by PeopleSoft in this script.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms   | Languages |
|----------------------|----------------|----------|-------------|-----------|
| Target               | Both           | All      | DB2 UNIX/NT | All       |

## Task 2-2-13: Edit the DDLORA Script

Edit PS\_HOME\SCRIPTS\DDLORA.DMS. At the bottom of this script, you will see an insert into PSDDLDEFPARMS. This insert contains default information used when creating a table, an index, a unique index, or a tablespace. Verify with your database administrator that the last value for each row is appropriate for your environment by checking the values currently stored in your PSDDLDEFPARMS table. Otherwise, the values will be reset to the default values delivered by PeopleSoft in this script.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Oracle    | All       |

## Task 2-2-14: Edit the DDLIFX Script

Edit `PS_HOME\SCRIPTS\DDLIFX.DMS`. At the bottom of this script, you will see an insert into `PSDDLDEFPARMS`. This insert contains default information used when creating a table, an index, a unique index, or a tablespace. Verify with your database administrator that the last value for each row is appropriate for your environment by checking the values currently stored in your `PSDDLDEFPARMS` table. Otherwise, the values will be reset to the default values delivered by PeopleSoft in this script.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Informix  | All       |

## Task 2-2-15: Edit the MSGTLSUPG Script

Edit `PS_HOME\SCRIPTS\MSGTLSUPG.DMS` and make the necessary modifications as documented in the script.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 2-2-16: Edit Multilingual Step Properties

In this step, you will edit the Change Assistant step properties for the multilingual PeopleTools project copy step (or steps). Copy only the translated objects for the languages you license. This prevents the translated objects for unlicensed languages from copying over. You will copy any multilingual projects later in the upgrade process.

Depending on which languages you license, you will need to complete the following instructions once or twice. If you license any of these languages, Arabic, Czech, Danish, Finnish, French, Hebrew, Hungarian, Norwegian, Polish, Russian, or Turkish, perform the following instructions for the step “Export and Copy PPLTLSML Project.” If you license any of these languages, Canadian French, Dutch, German, Greek, Italian, Japanese, Korean, Malay, Portuguese, Simplified Chinese, Spanish, Swedish, Traditional Chinese, or Thai, perform the following instructions for the step “Export and Copy PPLTLS84CURML Project.”

To edit multilingual step properties:

1. In Change Assistant, select the step.
2. Open the Step Properties dialog box.
3. Click the Upgrade button, and then click the Options button.

4. On the Copy Options tab, deselect any languages that you do not license.  
Common and English should remain deselected.
5. Click OK three times.
6. Save the template in Change Assistant.

See Export and Copy PPLTLS84CURML Project.

See Export and Copy PPLTLSML Project.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages       |
|----------------------|----------------|----------|-----------|-----------------|
| Target               | Initial        | All      | All       | All Non-English |

---

## Task 2-3: Updating PeopleTools System Tables

This section discusses:

- Understanding Updating PeopleTools System Tables
- Recreate Performance Views
- Update PeopleTools System Tables
- Grant Privileges to the CONNECT ID
- Update the Product License Code
- Update PeopleTools Patch Information
- Create Temporary Performance Indexes
- Export PeopleTools System Tables
- Import PeopleTools System Tables
- Rerun Update Statistics for DB2 zOS
- Rerun RUNSTATS Report for DB2 UNIX NT
- Rerun Update Statistics for DB2 UNIX NT
- Rerun Update Statistics for Informix
- Rerun Update Statistics for Oracle

### Understanding Updating PeopleTools System Tables

In this task, you update your PeopleTools system tables by running various scripts.

---

**Important!** From this point forward, run all steps using the new release of PeopleTools on your Copy of Production database, unless otherwise indicated.

---

## Task 2-3-1: Recreate Performance Views

This step runs the SYSVIEW8 script, which recreates the SYSKEYS and SYSINDEXES views. This will enhance performance during the upgrade process.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Oracle    | All       |

## Task 2-3-2: Update PeopleTools System Tables

Release scripts are SQL scripts that modify the underlying table structure of a database so that it is compatible with a more recent PeopleTools release. They are located in the PS\_HOME/SCRIPTS directory. Release scripts can be identified by their common naming standard, RELxxx.SQL, in which xxx designates a PeopleTools release number.

These release (REL) scripts alter and update your PeopleTools tables to the current release. Change Assistant determines which RELxxx scripts to run based on the PeopleTools release of your Source and Target databases.

If you created RELxxxDBTSFIX (in which xxx is a PeopleTools release) earlier in your upgrade, the procedure will look at your Output folder and will know to run RELxxxDBTSFIX. If you did not run DBTSFIX, Change Assistant will run RELxxx.

---

**Note.** Before running this step, verify that the PS\_HOME values are set correctly in the Change Assistant environment for your upgrade job. Your new release PS\_HOME/SCRIPTS directory should contain all scripts that will be run during this step. This step runs at least one script. Do not proceed to the next step until these scripts run successfully.

---

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your new release.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 2-3-3: Grant Privileges to the CONNECT ID

This step runs the GRANT.SQL script. This script grants select access to the connect ID for tables necessary for sign on.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |



## Task 2-3-4: Update the Product License Code

This section discusses:

- Understanding the Product License Code
- Updating the Product License Code

### Understanding the Product License Code

The new PeopleSoft release stores your application product license code on the database. This code is used to unlock the pages and Application Engine programs that you licensed. It also provides necessary product information about your database to be used for identifying software maintenance that may need to be applied.

You need to populate the databases that were upgraded to the new PeopleSoft release so that you have the correct access to Pages and Application Engine programs that you licensed.

When your new PeopleSoft databases were installed, the appropriate application license code was added to your database in the PSOPTIONS table. This was done in an update statement that was created when DBSETUP was run to create the Data Mover script for the new PeopleSoft release. The location of this script is:

```
PS_HOME\SCRIPTS\DBnameDBplatform.DMS
```

*DBname* is the name of the Demo database you installed and *DBplatform* represents the database platform using the following chart:

| Database Platform    | Code Used |
|----------------------|-----------|
| Microsoft SQL Server | MSS       |
| DB2 UDB z/OS         | DB2       |
| DB2 UDB UNIX/NT      | DBX       |
| Oracle               | ORA       |
| Informix             | INF       |
| Sybase               | SYB       |

### Updating the Product License Code

Follow the steps below to update your product license code.

To update the product license code:

1. From the Data Mover script that was created for your new PeopleSoft database installation, copy out the update to PSOPTIONS.

The statement should look similar to this:

```
update PSOPTIONS set LICENSE_CODE = 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx', LICENSE_⇒
GROUP = 'xx';
```

where 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx' equals your license code and 'xx' equals your license group.

2. Run the SQL command identified above using your SQL tool.

Your database is now updated with the appropriate license code. You can now access the pages and Application Engine programs that you licensed.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-3-5: Update PeopleTools Patch Information

In this step, you update your database with the version of the PeopleTools patch being applied.

---

**Note.** You only need to run this step if you are applying a PeopleTools patch as part of the upgrade process.

---

Log on to Data Mover in user mode and run the %PS\_HOME\SCRIPTS\PTPATCH.DMS script.

Review the PeopleTools patch instructions and perform any additional database upgrade instructions that may be listed prior to the copy of the patch project. The patch project will be copied later during the upgrade.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-3-6: Create Temporary Performance Indexes

Perform this step only if you are running on a DB2 z/OS platform. This step runs the DB2TMPIDXCREATE script to create multiple indexes for rename performance. You will drop these indexes later in the upgrade process.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | DB2 z/OS  | All       |

## Task 2-3-7: Export PeopleTools System Tables

The script for this step exports the content of the PeopleTools tables from the Copy of Production database during your Move to Production passes. During the initial pass, you run programs to convert some objects, like PeopleCode and Fields. You perform analysis to decide which objects, such as records and menus, to bring over to your production database and which customized objects to keep. At the end of the initial pass, you reapply customizations or make other changes, such as modifying your permission lists. You do not need to repeat those tasks in the Move to Production pass because this script exports all your changes to the PeopleTools objects.

The script name for your upgrade path is:

MVPRDEXP.DMS

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | MTP            | All      | All       | All       |

## Task 2-3-8: Import PeopleTools System Tables

The script for this step imports the content of the PeopleTools tables into your New Copy of Production database during your Move to Production passes.

These MVPRD\* scripts replace tasks and steps performed in the initial pass. These tasks and steps may include:

- Renaming Records and Fields
- Running New Release Compare Reports
- Running New Release Upgrade Copy

If your relational database management system (RDBMS) uses tablespaces, edit this script for the proper DDL information.

The script name for your upgrade path is:

```
MVPRDIMP.DMS
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | All       | All       |

## Task 2-3-9: Rerun Update Statistics for DB2 z/OS

Earlier in the upgrade process, you updated your statistics for DB2 z/OS. Due to changes in the database structure, you must update statistics again to improve the performance of your compare and copy. Contact your database administrator to have the statistics updated on your database before proceeding with your upgrade.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 2-3-10: Rerun RUNSTATS Report for DB2 UNIX NT

This script creates the RUNSTATS.DAT file for the script to update the statistics for DB2 UDB on UNIX, Linux, or Windows.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms   | Languages |
|----------------------|----------------|----------|-------------|-----------|
| Target               | Both           | All      | DB2 UNIX/NT | All       |

## Task 2-3-11: Rerun Update Statistics for DB2 UNIX NT

Earlier in the upgrade process, you updated your statistics for DB2 UDB on UNIX, Linux, or Windows. Due to changes in the database structure, you must update statistics again to improve the performance of your compare and copy. This step runs `RUNSTATS .SQL` to update statistics on your database.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms   | Languages |
|----------------------|----------------|----------|-------------|-----------|
| Target               | Both           | All      | DB2 UNIX/NT | All       |

## Task 2-3-12: Rerun Update Statistics for Informix

Earlier in the upgrade process, you updated your statistics for Informix. Due to changes in the database structure, you must update statistics again to improve the performance of your compare and copy. This step runs `UPDATESTATS` to update statistics on your database.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Informix  | All       |

## Task 2-3-13: Rerun Update Statistics for Oracle

Earlier in the upgrade process, you updated your statistics for Oracle. Due to changes in the database structure, you must update statistics again to improve the performance of your compare and copy. Contact your database administrator to have the statistics updated on your database before proceeding with your upgrade.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Oracle    | All       |

---

## Task 2-4: Turning Off Change Control

This task executes a SQL statement that turns off the Change Control feature to improve performance for the upgrade copy. One of the tasks for completing database changes will remind you to turn this feature on again, if you want to use it.

---

**Note.** Move to Production: The Change Control feature slows down copy functions. The large copy projects are only executed during the initial pass and the feature is only disabled for the initial pass.

---

See “Complete Database Changes,” Reviewing Change Control.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 2-5: Loading Model Definition Data

This section discusses:

- Understanding Model Definition Data Load Process
- Load Model Definitions for DB2 zOS
- Load Model Definitions for DB2 UNIX NT
- Load Model Definitions for Oracle
- Load Model Definitions for Informix
- Load Model Definitions for Microsoft
- Load Model Definitions for Sybase

### Understanding Model Definition Data Load Process

In this task, you load model definition scripts for your database platform and populate DDL model definitions. This step runs the DDL model definition script applicable to your database platform. If required by your database platform, you modified this script in the task “Performing Script Modifications,” to use your site-specific information.

See Performing Script Modifications.

### Task 2-5-1: Load Model Definitions for DB2 zOS

This step runs the DDLDB2.DMS script to populate DDL model definitions for the DB2 z/OS platform.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

**Task 2-5-2: Load Model Definitions for DB2 UNIX NT**

This step runs the DDLDBX.DMS script to populate DDL model definitions for DB2 UDB on UNIX, Linux, or Windows.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms   | Languages |
|----------------------|----------------|----------|-------------|-----------|
| Target               | Both           | All      | DB2 UNIX/NT | All       |

**Task 2-5-3: Load Model Definitions for Oracle**

This step runs the DDLORA.DMS script to populate DDL model definitions for the Oracle platform.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Oracle    | All       |

**Task 2-5-4: Load Model Definitions for Informix**

This step runs the DDLIFX.DMS script to populate DDL model definitions for the Informix platform.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Informix  | All       |

**Task 2-5-5: Load Model Definitions for Microsoft**

This step runs the DDLMSS.DMS script to populate DDL model definitions for the Microsoft SQL Server.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms     | Languages |
|----------------------|----------------|----------|---------------|-----------|
| Target               | Both           | All      | MS SQL Server | All       |

## Task 2-5-6: Load Model Definitions for Sybase

This step runs the DDLSYB.DMS script to populate DDL model definitions for the Sybase platform.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Sybase    | All       |

---

## Task 2-6: Loading Message Data

This step loads system messages in the message catalog.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 2-7: Reviewing PeopleTools Objects

Run this step to identify any PeopleTools objects that you have customized. This step only identifies the customized PeopleTools objects. You still must overwrite the customized objects with the new PeopleTools definitions when you copy the project.

During the upgrade process, you copy PeopleTools objects into your database. PeopleTools functionality, such as Security, is built using PeopleTools objects and it is possible that you could have modified the PeopleTools objects that make up a product like Security.

**Warning!** Do not change the delivered PeopleTools objects. The delivered objects are integral to the smooth operation of your system, and the modification of these objects could cause system instability.

When you perform the copy of the PeopleTools projects during the upgrade, you may overwrite modifications you have made. Excluding any PeopleTools-delivered objects from the upgrade may result in instability due to dependencies on specific objects.

To review PeopleTools objects:

1. Open the PPLTLS84CUR project on your Source database.
  - a. Launch Application Designer and sign on to the Demo (Source) database.
  - b. Select File, Open...
  - c. In the Definition field, select Project and click Open to display a list of projects.
  - d. Select the PPLTLS84CUR project and click Open.
2. If the PPLTLS84CUR project does not exist on your Demo (Source) database, then copy the project definition; otherwise continue to the next step.
  - a. Select Tools, Copy Project, From File...
  - b. In the resulting dialog box, change the import directory to *PS\_HOME*PROJECTS, select PPLTLS84CUR from the list of projects and click on the Open button.
  - c. The Copy dialog box appears. Click on the Deselect All button and then click the Copy button.  
When the progress dialog disappears, the project definition has been copied.
3. On your Source database, make a copy of the PPLTLS84CUR project and name it PPLTLS84CURCOMP. You will use this project for the compare process.
  - a. If the PPLTLS84CUR project is not open, open it now.
  - b. Select File, Save Project As...
  - c. Name the project PPLTLS84CURCOMP.
4. On your Source database, perform a project compare of the PPLTLS84CURCOMP project against your Target database.
  - a. If the PPLTLS84CURCOMP project is not open, open it now.
  - b. Select Tools, Compare and Report...
  - c. Sign on to the Target database.
  - d. Verify that all object types are selected.
  - e. Select Options...
  - f. On the Compare Options tab, select Compare Type of Project.
  - g. Select a value for Target Orientation.
  - h. For Comparison by Release, select the highest release in the list.
  - i. Under Compare Languages, select Common and English.
  - j. If you have non-English languages loaded, select the other language(s) loaded into your database.
  - k. Click the Report Filter tab and click Default.  
This will cause only customizations to appear on the compare reports.
  - l. Click OK.
  - m. Click Compare to start the compare process.

---

**Note.** To preserve the PPLTLS84CURCOMP compare reports, you must perform one of the following actions: 1) rename the reports, 2) move the reports to a different folder, or 3) reset the Compare Report Output Directory: Within Application Designer, select Tools, Options. On the General tab, change the path specified for the Report Output Directory.

---



5. Evaluate the compare reports to identify whether the delivered objects conflict with any of your customizations.

You will overwrite the customized objects with the new PeopleTools definitions when you copy the PeopleTools projects in a later task. You must not make any modifications that will affect PeopleTools objects when re-implementing your customizations after the upgrade.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-8: Exporting and Copying Projects

This section discusses:

- Understanding Exporting and Copying Projects
- Export and Copy PPLTLS84CUR Project
- Export and Copy PPLTLS84CURML Project
- Export and Copy PPLTLSML Project
- Export and Copy PPLTLS84CURDEL Project
- Export and Copy PATCH84X Project
- Export and Copy PATCH84XML Project

### Understanding Exporting and Copying Projects

In this task, you export and copy projects.

PeopleSoft recommends that you verify the results of all copied projects. After a project has been copied, each object is identified with a checkmark in the Done column. You can view these results from the Upgrade tab in Application Designer. It is also recommended that you copy the PeopleTools projects with the take action flags set as they originally were set when the database was delivered.

**Note.** If you are running Sybase, check the configuration parameter for “open objects.” If this parameter is set too low, you may encounter the following error: `ct_connect(): network packet layer: internal net library error` during the compare or copy process. If you encounter this error, you will need to increase your parameter accordingly.

See Enterprise PeopleTools PeopleBook: PeopleSoft Application Designer for your new release.

### Task 2-8-1: Export and Copy PPLTLS84CUR Project

This process copies specified objects to the database that are necessary for the proper operation of PeopleTools. The PPLTLS84CUR project contains all PeopleTools objects that have been created or updated since PeopleTools 8.40 was released.

Before the copy of records and fields, the upgrade process detects if the object definition exists or not. PeopleSoft delivers the PPLTLS84CUR project with an Action of CopyProp to prevent the possible overwrites of custom field labels and recfields. When the upgrade process detects that a given field or record does not exist, it changes that action so that the entire definition can be copied. You can ignore any errors you may receive at this time similar to the following examples:

```
Changed Action from CopyProp to Copy, definition does not exist on target.
Definition Name: OBJECTNAME not copied, entire definition already opied.
```

These warnings occur because the PeopleTools project contains fields along with their field label. This is necessary so the software does not overwrite any customized field labels on PeopleSoft field objects.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-8-2: Export and Copy PPLTLS84CURML Project

This process copies language-specific PeopleTools objects to the database that are necessary for the proper operation of PeopleTools.

Before the copy of records and fields, the upgrade process detects if the object definition exists or not. PeopleSoft delivers the PPLTLS84CURML project with an Action of CopyProp to prevent the possible overwrites of custom field labels. When the upgrade process detects that a given field does not exist, it changes that action so that the entire definition can be copied. You can ignore any errors you may receive at this time similar to the following example:

```
Changed Action from CopyProp to Copy, definition does not exist on target.
Definition Name: OBJECTNAME not copied, entire definition already copied.
```

This warning occurs because the PeopleTools project contains fields along with their field label. This is necessary so the software does not overwrite any customized field labels on PeopleSoft field objects.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages  |
|----------------------|----------------|----------|-----------|--|
| Target               | Initial        | All      | All       | Canadian French<br>Dutch<br>Greek<br>German<br>Italian<br>Japanese<br>Korean<br>Portuguese<br>Simplified Chinese<br>Spanish<br>Swedish<br>Traditional Chinese<br>Thai<br>Malay |

## Task 2-8-3: Export and Copy PPLTLSML Project

This process copies language-specific PeopleTools objects to the database that are necessary for the proper operation of PeopleTools.

Before copying records and fields, the upgrade process detects whether the object definition exists. PeopleSoft delivers the PPLTLSML project with an Action of `CopyProp` to prevent the possible overwrites of custom field labels and recfields. When the upgrade process detects that a given field or record does not exist, it changes that action so that the entire definition can be copied. You can ignore any errors you may receive at this time similar to the following examples:

```
Changed Action from CopyProp to Copy, definition does not exist on target.
Definition Name: OBJECTNAME not copied, entire definition already copied.
```

These warnings occur because the PeopleTools project contains fields along with their field labels. This is necessary so PeopleSoft does not overwrite any customized field labels on PeopleSoft field objects.

---

**Note.** Ignore this warning when copying Server Definitions:

```
'Definition Name: server definition not copied, check copy options'
```

---

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages  |
|----------------------|----------------|----------|-----------|--|
| Target               | Initial        | All      | All       | Arabic<br>Czech<br>Danish<br>Finnish<br>French<br>Hebrew<br>Hungarian<br>Norwegian<br>Polish<br>Russian<br>Turkish |

## Task 2-8-4: Export and Copy PPLTLS84CURDEL Project

This process deletes specified PeopleTools objects from your database.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-8-5: Export and Copy PATCH84X Project

This process copies specified objects to the database that are necessary for the proper operation of PeopleTools.

---

**Note.** Perform this process only if you are applying a PeopleTools patch that includes a database project. Check the patch documentation to verify whether a database project was delivered with the patch.

---

Use Application Designer to perform the following steps.

To export and copy the project:

1. Log on to your Target database as a valid user.
2. Select Tools, Copy Project, From File...
3. In the Import Directory field, enter *PS\_HOME\PROJECTS*.
4. Select the PATCH84X project from the list, where 84X corresponds to the PeopleTools release of the patch project. This should correspond with the PeopleTools release to which you are upgrading.
5. Click Copy.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-8-6: Export and Copy PATCH84XML Project

This process copies language-specific PeopleTools objects to your database that are necessary for the proper operation of PeopleTools.

---

**Note.** Perform this process only if you are applying a PeopleTools patch that includes a database project. Check the patch documentation to verify whether a multilingual database project was delivered with the patch.

---

Use Application Designer to perform the following steps.

To export and copy the project:

1. Log on to your Target database as a valid user.
2. Select Tools, Copy Project, From File...
3. In the Import Directory field, enter *PS\_HOME\PROJECTS*.
4. Select the PATCH84XML project from the list, where 84X represents the PeopleTools release of the patch project. This should correspond to the PeopleTools release to which you are upgrading.
5. Click Options, and then select the Copy Options tab and verify that only the non-English languages that are installed are selected.

---

**Note.** The languages English and Common should not be selected.

---

6. Click OK.
7. Click Copy.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages       |
|----------------------|----------------|----------|-----------|-----------------|
| Target               | Initial        | All      | All       | All Non-English |

---

## Task 2-9: Populating Tablespace Data

This section discusses:

- Create Application Tablespaces
- Populate Tablespace Data
- Update Tablespace Names

## Task 2-9-1: Create Application Tablespaces

During each Move to Production pass, you must create any new tablespaces. You can reuse the same script created during the initial pass when you created new tablespaces, or you can build a new one if you plan to use different tablespaces on your production system.

See “Apply Application Changes,” Updating Database Overrides.

See “Apply Application Changes,” Create New Tablespaces.

The script supplied by PeopleSoft to create tablespaces for your upgrade is:

LMDDL . SQL

---

**Important!** For DB2 UNIX/NT sites, the script name is LMDDL . SQL for ANSI, and LMDDL . SQL for Unicode.

---

Once you have determined which script to run during Move to Production, you can change this step to run automatically.

To run the Create Application Tablespaces step automatically:

1. In Change Assistant, open your upgrade job.
2. In the task Populating Tablespace Data, right-click on the step Create Application Tablespaces, and then select Step Properties.
3. In the Step Properties dialog box, change the value in the Type field from *Manual - Stop* to *SQL Script*.
4. In the Script/Procedure field, enter the name of the script you want to run and click OK.
5. Select File, Save.
6. Select the step Create Application Tablespaces.
7. Select Edit, Run.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | MTP            | All      | Oracle<br>Informix<br>DB2 UNIX/NT<br>DB2 z/OS | All       |

## Task 2-9-2: Populate Tablespace Data

This step populates all tablespace information in the PSRECTBLSPC table. This step runs the SETSPACE.SQR script, which ensures that the correct tablespace information is populated for tasks later in the upgrade process.

The values stored in the DDLSPACENAME field are updated with current values found in the system catalog for tables already defined in your database. If you modified tablespace names from the PeopleSoft-delivered names, this step makes those same changes in the PeopleSoft record definition.

If you receive any errors when you run this script, correct them by creating the needed tablespace or changing the tablespace definition on the record object. Then run the script again to validate that you have created all tablespaces.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | Oracle<br>Informix<br>DB2 UNIX/NT<br>DB2 z/OS | All       |

## Task 2-9-3: Update Tablespace Names

The SETSPACE SQR script identifies the tables with an invalid database name/tablespace combination. However, the PeopleTools Metadata tables in your Copy of Production (Target) database contain the database/tablespace values from the Demo (Source) database. This also occurs if your Demo and Copy of Production databases are in the same DB2 subsystem after the upgrade/copy is completed. SETSPACE.SQR corrects these values for those tables defined in DB2. For those tables that are defined in the PeopleTools metadata tables, but have not been defined in DB2, you need to review the SETSPACE SQR script for those tables that are reported as not defined in the database, but where the database/tablespace combination is valid. If the report shows an invalid database/tablespace combination, or shows your Demo (source) database and tablespace names instead of your Copy of Production (target) database and tablespace names, you can correct the database and tablespace names using one of the following options:

- Generate the alter/create scripts and globally edit the scripts, changing the database/tablespace values to those of your Copy of Production.
- Directly update the PSRECTBLSPC table with your Target database names before generating the alter/create scripts. This will ensure that the database name/tablespace names in the generated alter/create scripts will be correct. The syntax to update the PSRECTBLSPC table is as follows:

```
UPDATE PSRECTBLSPC SET DBNAME = dbname, DDLSPACENAME = tablespace name WHERE⇒
DDLSPACENAME = tablespace identified in SETSPACE OUTPUT AND DBNAME = database⇒
identified in SETSPACE OUTPUT;
```

If you are using the PeopleSoft-delivered tablespaces, you can omit the references to DDLSPACENAME in the SQL statement above.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 2-10: Building Updated PeopleTools Project

This section discusses:

- Generate Updated PeopleTools Script
- Edit the Updated PeopleTools Script
- Run the Updated PeopleTools Script

### Task 2-10-1: Generate Updated PeopleTools Script

This step generates the SQL script to create and alter records of the type table that are delivered in the PPLTLS84CUR project. The tables are altered to add new columns, rename existing columns, and change columns that have modified properties, such as length, and delete columns. The script will also create new indexes, re-create modified indexes, and create triggers. The script name is:

PPLTLS84CURTABLES.SQL

**Note.** For DB2 z/OS sites, if this step takes an exceptionally long time, performing a RUNSTATS on the system catalog tablespace SYSDBASE may improve performance.

#### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

### Task 2-10-2: Edit the Updated PeopleTools Script

In this step, you edit the PPLTLS84CURTABLES.SQL script that was generated in the previous step for tablespace names and sizing. If you are running on a relational database management system (RDBMS) platform that uses tablespaces, and you are *not* using the PeopleSoft tablespace names, have your database administrator review this script and modify the tablespace names appropriately. The script can be found in your Change Assistant output directory for this upgrade path.

#### Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | DB2 z/OS<br>DB2 UNIX/NT<br>Oracle<br>Informix | All       |



## Task 2-10-3: Run the Updated PeopleTools Script

This step runs the script you generated in this task to create all records of the type table. This creates new table structures, alters existing PeopleSoft table structures, creates new indexes, re-creates modified indexes, and creates triggers.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 2-11: Migrating Records to New Tablespaces

This section discusses:

- Understanding Migration of Records to New Tablespaces
- Export and Copy the PT84TBLSPC Project
- Build the Tablespace Alter Script
- Edit the Tablespace Alter Script
- Run the Tablespace Alter Script

## Understanding Migration of Records to New Tablespaces

In this task you migrate the tables delivered in the PT84TBLSPC project to the correct tablespaces.

### Task 2-11-1: Export and Copy the PT84TBLSPC Project

This process copies the records that moved to different tablespaces in the new release of PeopleTools. The upgrade copy options are set to “Copy From Source” for record DDL to pick up the new tablespace information.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Initial        | All      | DB2 z/OS<br>DB2 UNIX/NT<br>Oracle<br>Informix | All       |

## Task 2-11-2: Build the Tablespace Alter Script

This step generates the SQL script to alter records of the type table that are delivered in the PT84TBLSPC project. The tables are altered to move them to the correct tablespaces for the new release of PeopleTools. The script name is:

TABLESPACEALERTABLES.SQL

---

**Note.** For DB2 z/OS sites, if this step takes an exceptionally long time, performing a RUNSTATS on the system catalog tablespace SYSDBASE may improve performance.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | DB2 z/OS<br>DB2 UNIX/NT<br>Oracle<br>Informix | All       |

## Task 2-11-3: Edit the Tablespace Alter Script

In this step, you edit the TABLESPACEALERTABLES.SQL script for tablespace names and sizing. If you are running on an RDBMS platform that uses tablespaces, and you are *not* using the PeopleSoft tablespace names, you need to review and modify the scripts above. Have your database administrator review these scripts and modify the tablespace names appropriately. The script can be found in your Change Assistant output directory for this upgrade path.

---

**Note.** If you are a DB2 z/OS customer, you must edit the scripts for database name regardless of whether you are using the delivered PeopleSoft tablespace names.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | DB2 z/OS<br>DB2 UNIX/NT<br>Oracle<br>Informix | All       |

## Task 2-11-4: Run the Tablespace Alter Script

This step runs the TABLESPACEALERTABLES.SQL script to move the tables to the new tablespaces.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | DB2 z/OS<br>DB2 UNIX/NT<br>Oracle<br>Informix | All       |

---

**Task 2-12: Loading Base Data**

These Data Mover scripts (DMSs) initialize and modify the data in various PeopleTools tables required for the system to execute properly. This step runs scripts conforming to the PTxxxTLS.DMS and PTxxxTLYyy.DMS naming conventions that are greater than your current PeopleTools release, where xxx represents a PeopleTools release number and yyy represents a three-letter language code. For some upgrades, no data scripts are required. In this case, Change Assistant continues to the next step without producing a log file.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

**Task 2-13: Loading Language Data**

This section discusses:

- Populate Languages
- Load Language Data

**Task 2-13-1: Populate Languages**

This step runs the PSLANGUAGES.DMS script. This script populates the PSLANGUAGES table with Verity Locale data and other language-specific data.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-13-2: Load Language Data

If your database has languages installed in addition to English, you must populate the PSLANGUAGES table.

To load language data:

1. From the DMS that was created for your PeopleSoft 8.x database installation, find the UPDATE to PSLANGUAGES. The statement should look similar to the following:

```
UPDATE PSLANGUAGES SET INSTALLED=1 WHERE LANGUAGE_CD = 'xxx' ;
```

2. Run the SQL command identified above using your SQL tool.

Your database is now updated with the language data.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages       |
|----------------------|----------------|----------|-----------|-----------------|
| Target               | Initial        | All      | All       | All Non-English |

---

## Task 2-14: Loading PeopleTools Data

This section discusses:

- Load NonComparable Objects
- Load English Messages
- Load English String Data
- Load English Currency Codes
- Load Stored Statements Data

### Task 2-14-1: Load NonComparable Objects

This step runs the TLSUPGNONCOMP.DMS script. This script loads the TLSUPGNONCOMP project and all PeopleTools-owned object definitions that cannot be delivered using Copy Project to File.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

### Task 2-14-2: Load English Messages

This script loads English messages into your database.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | English   |

**Task 2-14-3: Load English String Data**

This step runs the PTSTRENG.DMS script, which loads English string data into the STRINGS\_TBL table.

---

**Note.** The non-English language data was loaded in the task “Loading Base Data.”

---

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

**Task 2-14-4: Load English Currency Codes**

This step runs the CURRENG script that loads the currency code data for English.

---

**Note.** The non-English language data was loaded in the task “Loading Base Data.”

---

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

**Task 2-14-5: Load Stored Statements Data**

Loading the stored statements ensures that the dynamic SQL statements will work correctly with the delivered COBOL programs.

This script loads the dynamic SQL used by the PeopleTools-delivered COBOL.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 2-15: Loading PeopleTools Definition Group

This task runs the PTDEFNSEC.DMS script that loads the PeopleTools definition security group. This ensures that the definition security group is updated with the PeopleTools objects introduced in this release.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 2-16: Converting PeopleTools Objects

This section discusses:

- Update Ren Server Configuration
- Populate MCF Data
- Convert Portal Objects
- Convert Query Prompt Headings
- Encrypt Connector Passwords
- Load Conversion Data
- Report Conversion Details
- Run Data Conversion

### Task 2-16-1: Update Ren Server Configuration

This step runs the Application Engine program UPGMCF843, which converts real-time event notification server configuration information to the new format. Ren servers run in the application server domain. They are used for the PeopleTools MultiChannel Framework (MCF) and Reporting Window output option. The program converts standard Ren server configurations to the new format, including MCF cluster information. All Ren server configuration information is now stored within the database. You must upgrade old Ren server configurations before attempting to boot with the new version of PeopleTools. If you did not have any Ren servers configured prior to starting the upgrade, then the UPGMCF843 program does not make any changes. If one of your configurations cannot be converted, error messages will be written in the Application Engine message log.

After running this step, you should also check the PSRENCONFIG.TXT file located in each application server domain that started an old Ren server. (The file will not exist in domains that did not start a Ren server.) Each old file should be replaced with the new template file located at PS\_HOME/APPSEV/REN/PSRENCONFIG.TXT. Old template files cannot be used with the new version of Ren server. If you customized your old configuration files, manually edit the new files and update them with your customizations.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 2-16-2: Populate MCF Data

This step runs the Application Engine program MCF\_UPGR\_SND, which populates the PS\_MCFEM\_MAIL\_DSCR table with data. In PeopleTools 8.44, the REPLY\_TO header functionality was added. The field PS\_MCFEM\_MAIL\_DSCR.MCF\_REPLY\_TO is populated with the values stored in PS\_MCFEM\_MAIL\_MAIN.MCF\_EMAIL\_SENDER.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 2-16-3: Convert Portal Objects

This step runs the Application Engine program UPG844PORTAL, which splits PSPRSMDEFN.PORTAL\_URLTEXT into segments and stores them in separate columns: PORTAL\_URI\_SEG1, PORTAL\_URI\_SEG2, PORTAL\_URI\_SEG3, and PORTAL\_URI\_SEG4. This is performed for PeopleSoft Component URLs to extract values for Menu, Component, and Market. Values for Record, Field, Event, and Function Names are extracted from Iscript URLs.

You may see some errors or messages in your log. Following is a list of some of the errors and what to do about them:

- Not authorized CRef: *Portal Object Name* (95,5032).

This means that you do not have proper privileges to run this conversion. You need to grant the user ID that you are using to upgrade Portal Administrator permissions.

- Security synchronization failed for Portal Object: *Portal Object Name* (96,61).

This is not a fatal error. It may be caused by a content reference that contains invalid URL text and indicates that there was an internal error writing to the security table. The invalid URL text may be pointing to a component or script that does not exist in the database. You need to fix the content reference and then rerun the UPG844PORTAL process.

- Cref *Portal Object Name* points to Menu: *Menu Name*, Component *Component Name* which doesn't exist. (96,80).

The content reference is pointing to an invalid Menu/Component combination. You need to fix the content reference so that it points at a valid Menu/Component combination and then rerun the UPG844PORTAL process.

- Duplicate key. Portal: *Portal Name*, Obj Name: *Portal Object Name*, Nodename: *Node*, URL: *URL* (133,4).

This Portal object has the same URL as another Portal object. Delete or modify this object to remove the conflict and then rerun the UPG844PORTAL process.

See Enterprise PeopleTools PeopleBook: Internet Technology for your new release.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-16-4: Convert Query Prompt Headings

This step runs the Application Engine program UPGQRYDUPHED, which searches for duplicate prompt headings in the table PSQRYBIND and appends numbers onto the text. For example, *Item ID* would become *Item ID 2*. When you run Crystal 9 through the process scheduler, it cannot handle queries with two or more prompts that have the same heading. These duplicates are also not legal in Query. You need to alter any old queries that have duplicate prompt headings so that they work with Crystal 9.

If you find a duplicate heading that exceeds the length of the field HEADING, you need to manually change the heading. In these cases, the following error is written to the log file:

```
The prompt heading HEADING for Query QUERY is duplicated. Please manually correct.⇒
(108, 1108)
```

See Enterprise PeopleTools PeopleBook: PeopleSoft Query for your new release.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 2-16-5: Encrypt Connector Passwords

This step runs the Application Engine program UGRDPASSWDS, which encrypts the password property field for the POP3Target, FTPTarget, GetMailTarget, and JMSTarget connectors.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 2-16-6: Load Conversion Data

This step imports PeopleTools data conversion Application Engine driver data into your database.



**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

**Task 2-16-7: Report Conversion Details**

This step runs the PTUCONV.SQR script. It details which sections will be called by the Upgrade Driver program and what they are doing. Each of the upgrade data conversion sections contains comments that describe the processing done by the section. The information contained in the report is used to evaluate the conversions run in the next step and any actions that are required as a result of the conversion.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

**Task 2-16-8: Run Data Conversion**

The Upgrade Driver Application Engine program, PTUPGCONVERT, runs additional PeopleTools upgrade data conversions. The program then reads the table PS\_PTUPGCONVERT, selecting all rows with the group number of 01 and ordering them by the sequence number on the row. A list of Application Engine library sections that must be run for data conversion is returned. The program then calls each section in the order of the sequence number. After running PTUPGCONVERT, review the output data generated in the previous step for more details.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

**Task 2-17: Creating PeopleTools Views**

This section discusses:

- Create Updated PeopleTools Views

**Task 2-17-1: Create Updated PeopleTools Views**

This step creates all views defined in the PPLTLS84CUR project. These are PeopleTools views that have changed and are required for tasks later in the upgrade.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 2-18: Setting Object Version Numbers

In this task, you run the VERSION Application Engine program. This ensures that all of your version numbers are correct and, if not, resets them to 1.

**Note.** You will rerun the VERSION application engine program later in the upgrade. If you wish to preserve the log files generated by Change Assistant from this run, you will need to manually rename the files after completing this task.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 2-19: Backing Up After PeopleTools Upgrade

Back up your Copy of Production database now. This enables you to restart your upgrade from this point, in case you experience any database integrity problems during the remaining tasks in the upgrade process.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## CHAPTER 3

# Run and Review Compare Reports

This chapter discusses:

- Understanding Compare Reports
- Preparing for Application Changes
- Running New Release Compare Reports
- Reviewing New Release Compare Reports

---

## Understanding Compare Reports

Now that your Copy of Production database is at the same PeopleTools release as your new release, you can compare the two databases to see the differences. In this chapter you run and review compare reports to make decisions regarding your upgrade. Be sure you have plenty of space to run these reports, as some can be rather large.

---

## Task 3-1: Preparing for Application Changes

This section discusses:

- Exporting Project Definitions
- Importing Project Definitions

---

**Note.** This task contains several unrelated steps that are required before you continue the upgrade.

---

### Task 3-1-1: Exporting Project Definitions

In this step you will export from your Demo database the definition of projects that will be used later in this upgrade. You will import these definitions in the next step. Your export script is:

```
DLUPX08E.DMS
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Both           | All      | All       | All       |

## Task 3-1-2: Importing Project Definitions

In this step you will import the project definitions into your Copy of Production database. These projects will be used later in this upgrade. Your import script is:

```
DLUPX08I.DMS
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 3-2: Running New Release Compare Reports

This section discusses:

- Understanding the New Release Compare
- Preserving Local Message Node
- Modifying New Release Compare Options
- Running New Release UPGCUST Compare
- Resetting Take Action Flags in UPGCUST

## Understanding the New Release Compare

In this task you will compare your customizations to the new release objects by running a project compare against the Demo database.

### Task 3-2-1: Preserving Local Message Node

In this step add your Local Message Node to the UPGCUST project before the project compare between the Copy of Production and Demo database.

To add Local Message Node:

1. Run the following SQL in your Copy of Production database to identify your Local Message Node:

```
SELECT MSGNODENAME FROM PMSGNODEDEFN WHERE LOCALDEFAULTFLG = 'Y'
```

2. Open Application Designer from your Copy of Production database.
3. Open project UPGCUST.

4. Select Insert, Definitions Into Project.
5. Select Definition Type of Message Node.
6. Enter the Message Node name that was returned from the SQL you ran above.
7. Click Insert.
8. Save project UPGCUST.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 3-2-2: Modifying New Release Compare Options


PeopleSoft Change Assistant templates are delivered with the default reports filter turned on. This limits the size of the reports and keeps them manageable. Before you start the compare, review the compare options in the Change Assistant template step properties and modify them based on your requirements.

If you decide not to modify the compare options, the objects are still compared. However, the results are only available online in Application Designer. They are not written to the compare reports. The compare reports are tools to help you review changed objects. However, based on the report filters you select, you may need to review the action flags for other objects in the compare project in Application Designer.

For example, you can modify the compare options so the report contains customized objects that are present in your Copy of Production database but absent from the Demo database. Alternatively, you can review these objects online, through Application Designer, after the compare.

To modify upgrade compare options:

1. Highlight the Run New Release UPGCUST Compare step and right-click.
2. Select Step Properties.  
The Step Properties dialog box appears.
3. Click Upgrade.  
The Compare and Report dialog box appears.
4. Click Options.
5. Select the Report Filter tab.  
The default options include your custom changes on the reports.
6. Change the default options as necessary and click OK.



Upgrade Options page, Report Filter tab

7. In the Compare and Report dialog box, click OK.
8. In the Step Definitions dialog box, click OK.
9. Select File, Save Job.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 3-2-3: Running New Release UPGCUST Compare

This step executes a project compare of all comparable objects in the UPGCUST project.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 3-2-4: Resetting Take Action Flags in UPGCUST

This step turns all Take Action flags *off* in the UPGCUST project after the compare. You will analyze the compare results and adjust the upgrade flags in the next step.

The script for your upgrade is:

```
DLUPX98.DMS
```

See Appendix: “Using the Comparison Process.”

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 3-3: Reviewing New Release Compare Reports

This section discusses:

- Reviewing New Release Changes
- Reviewing NonComparable Objects

### Task 3-3-1: Reviewing New Release Changes

In this step, review the UPGCUST and UPGNONCOMP projects to evaluate how changes in the new release affect your customizations.

The UPGCUST project was created earlier in the upgrade when you ran a database compare, comparing your Old Release Demo database to your Copy of Production database. The project exists in your Copy of Production database and contains all the objects you customized in the old release. This project may include object definitions that are on your Copy of Production database but are not on the Demo database. If these are custom objects that you intend to keep in your upgraded system, you will want to ensure they are set to copy in the UPGCUST project. The project compare produces compare reports that you can view by opening the project in Application Designer. You can use these reports to determine your copy action for each object in the project. Currently all Upgrade Flags are deselected, meaning no action will take place. Analyze the UPGCUST project and select the Upgrade Flags for the customizations you wish to retain.

In the UPGCUST project, if the Target column has the value *Absent* it can indicate one of two possible conditions. If PeopleSoft originally delivered the object definition, then it can be considered obsolete in the new release. This value can also indicate that you originally created the object definition for some custom functionality. To ensure the integrity and functionality of the system, delete obsolete PeopleSoft-delivered objects. If you have made a customization to an obsolete object, refer to the product's Release Notes to assess the functionality of the customization and determine where to reapply it in the new release.

See Appendix: "Using the Comparison Process."

---

**Warning!** Pay close attention to the compare results for URLs, permission lists, and message nodes. It is highly likely that you will want to keep any customizations that you have made to these objects. You will want to migrate your customized local message node. Please be sure to select the Upgrade Flags from within Application Designer to retain these customizations.

---



---

**Note.** Steps in the database and/or third-party software installation documentation can result in PeopleSoft-delivered objects being identified in the compare reports as *\*Changed* in the Source column. You should investigate all instances where objects are identified as *\*Changed* in the Source column to determine their origin and determine a plan of action based on the findings for each object.

---

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 3-3-2: Reviewing NonComparable Objects

The UPGNONCOMP project is delivered in your Demo database. It contains object definitions that cannot be compared using Application Designer. The UPGNONCOMP project for your upgrade may contain some or all objects of the following object types: trees, access groups, roles, dimensions, cube definitions, and cube instance definitions. These object definitions are required for your upgraded database to function correctly. You need to review this project to see whether you customized any of the objects. You then need to reapply those customizations later in the upgrade.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |



## CHAPTER 4

# Apply Application Changes

This chapter discusses:

- Understanding Application Changes
- Customizing the New Release
- Running New Release Upgrade Copy
- Updating Database Overrides
- Backing Up After the Upgrade Copy
- Modifying the Database Structure
- Creating Upgrade Views
- Loading Data for Data Conversion
- Restoring New Release Demo
- Applying Updates Before Data Conversion
- Configuring Scheduler and Server
- Backing Up Before Data Conversion
- Running Data Conversion
- Backing Up After Data Conversion
- Finalizing the Database Structure
- Loading Data to Complete System Setup
- Updating Language Data
- Completing PeopleTools Conversion
- Updating Object Version Numbers
- Running the Final Audit Reports

---

## Understanding Application Changes

Earlier in the upgrade, you made various application changes. Now it is time to apply these application changes to your Copy of Production database.

## Task 4-1: Customizing the New Release

This section discusses:

- Understanding New Release Customizations
- Copying the UPGCUST Project
- Reviewing UPGCUST Copy Results

### Understanding New Release Customizations

In this task, the UPGCUST project is copied from the Copy of Production database to the Demo database.

**Note.** If you are running Sybase, check the configuration parameter for open objects. If this parameter is set too low, you may encounter the following error: `ct_connect(): network packet layer: internal net library error during the compare or copy process`. If you encounter this error, you need to increase the value of this parameter accordingly.

### Task 4-1-1: Copying the UPGCUST Project

This step copies your customized PeopleTools and application objects from the Copy of Production database to your Demo database.

#### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

### Task 4-1-2: Reviewing UPGCUST Copy Results

Review the results of the project copies that were performed in this task. For each of the projects copied, review the copy logs for any errors. Also, verify in Application Designer that each of the projects copied shows that the Done flags are checked for those objects you expected to be copied.

There are many different kinds of errors you can find in the copy logs, depending on which objects you chose to copy or not copy. For example, if you chose not to copy a record definition, but neglected to clear the PeopleCode Upgrade checkbox for that record, you will receive errors when trying to copy the PeopleCode. Application Designer maintains PeopleTools integrity during the copy and will not copy PeopleCode for records that do not exist.

Review any errors you receive during the copy process and determine whether they are acceptable cases or unacceptable errors that need correction. In the example above, either the PeopleCode error is acceptable because you do not intend to copy the record definition, or the error is unacceptable and you should copy the record and then copy the PeopleCode for that record again.

You may get messages similar to “Warning: FIELDNAME is a key field and has been appended to the end of the RECORDNAME record.” This is an acceptable message and you can ignore them.

The following error occurs when copying a Portal Registry Structure that has a different PORTAL\_OBJNAME but the same PORTAL\_URLTEXT as an existing registry object.

Duplicate Key. Portal: *portalname*, Obj name: *objectname*, CP: *nodename*, URL (1st 50⇒  
char): *URL*

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-2: Running New Release Upgrade Copy

This section discusses:

- Exporting Selected PeopleTools Tables
- Importing Selected PeopleTools Tables
- Updating Target Values
- Swapping PeopleTools Tables
- Exporting New Release Objects
- Importing New Release Objects
- Copying the UPGNONCOMP Project
- Reviewing UPGNONCOMP Copy Results
- Resetting Object Version Numbers
- Backing Up New Release Demo Again

### Task 4-2-1: Exporting Selected PeopleTools Tables

Depending on your upgrade path you will need to export one or more PeopleTools tables to preserve values on your Copy of Production Database. This step exports PeopleTools tables in the Copy of Production before the upgrade copy has occurred.

The script for your upgrade path is:

```
DLUPX96E.DMS
```

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-2-2: Importing Selected PeopleTools Tables

Depending on your upgrade path you will need to import one or more PeopleTools tables to preserve values on your Copy of Production Database. This step imports PeopleTools tables into the Demo database before the upgrade copy occurs.

The script for your upgrade path is:

```
DLUPX96I.DMS
```

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-2-3: Updating Target Values

This step updates the Message Node table on the Demo database to keep the assignment of the Local Node defined in the Copy of Production. The update uses the copy of the Message Node table taken earlier in the upgrade.

The script for your upgrade path is:

```
DLUPX97.DMS
```

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-2-4: Swapping PeopleTools Tables

This step swaps the base language for tables that contain PeopleTools Managed Object data and related language data on your Demo database. This is in preparation for the next step, “Exporting New Release Objects.” This script should only be run if your Copy of Production has a base language other than English. The script name for your upgrade path is:

```
PT_RELEASE_SWAP.DMS
```

If you would like to automate this step, follow the procedure below.

To make this step automated:

1. Select the step Swap PeopleTools Tables in Change Assistant.
2. Open the Step Properties dialog box.
3. Change the Type from ManualStop to DataMoverUser.
4. Click OK twice.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages                 |
|----------------------|----------------|----------|-----------|---------------------------|
| Source               | Initial        | All      | All       | Non-English Base Language |

## Task 4-2-5: Exporting New Release Objects

This step exports the new release objects and your customizations that you copied to the Demo database in an earlier step, to a file.

The script name for your upgrade path is:

```
PT_RELEASE_EXPORT.DMS
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-2-6: Importing New Release Objects

This step imports the new release objects and your customizations into your Copy of Production database.

The script name for your upgrade path is:

```
PT_RELEASE_IMPORT.DMS
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-2-7: Copying the UPGNONCOMP Project

In this step, copy the non-compare project, UPGNONCOMP. This project consists of object types you cannot compare and object types not included in your compare project. In a previous step, you reviewed this PeopleSoft-delivered project and modified the Upgrade checkbox for any objects you did not want to copy.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-2-8: Reviewing UPGNONCOMP Copy Results

Review the results of the UPGNONCOMP project copy that was performed earlier in this task. Review the copy log for any errors and verify in Application Designer that the Done flags are checked for the objects in each of the projects.

There are many different kinds of errors you can find in the copy logs, depending on which objects you chose to copy or not copy. Review any errors you received during the copy process to determine whether they are acceptable cases or unacceptable errors that need corrective action.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-2-9: Resetting Object Version Numbers

In this step, you run the VERSION Application Engine program. This ensures that all of your version numbers are correct and, if not, resets them to 1.

---

**Note.** You will rerun the VERSION Application Engine program later in the upgrade. If you want to preserve the log files generated by Change Assistant from this run, you will need to manually rename the files after completing this step.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-2-10: Backing Up New Release Demo Again

Back up your New Release Demo database now. This enables you to restart your upgrade from this point, should you experience any database integrity problems during the remainder of the tasks in the upgrade process.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

---

## Task 4-3: Updating Database Overrides

This section discusses:

- Understanding Database Overrides

- Set Index Parameters After Copy
- Set Tablespace Names After Copy
- Set Record Parameters After Copy
- Create New Tablespaces

## Understanding Database Overrides

In this task, you update PeopleTools tables with DDL information from your physical database DDL. You may have overwritten information about where tables exist in your database during the copy project steps of this upgrade. The following steps synchronize your PeopleTools table definitions with your database again.

### Task 4-3-1: Set Index Parameters After Copy

This step updates index overrides stored in the PSIDXDDLARM table. The values stored in the PARMVALUE field are updated with current values found in the system catalog. The name of the process is:

SETINDEX.SQR

#### Properties

| Database Orientation | Initial or MTP | Products | Platforms          | Languages |
|----------------------|----------------|----------|--------------------|-----------|
| Target               | Initial        | All      | Oracle<br>DB2 z/OS | All       |

### Task 4-3-2: Set Tablespace Names After Copy

This step updates tablespace names stored in the PSRECTBLSPC table. In addition, the values stored in the DDLSPACENAME field are updated with current values found in the system catalog. If you modified tablespace names from the PeopleSoft-delivered names, this process makes those same changes in the PeopleSoft record definition. It also corrects any tablespace names that were reset with values from the Demo database during the copy project step. The process then lists any tablespaces defined in the PeopleTools tables that are not currently on your database. Use this report to create new tablespaces later in this task. The name of the process is:

SETSPACE.SQR

---

**Note.** This step updates both the database and tablespace names in the PSRECTBLSPC table for DB2 z/OS sites. The report produced by this process lists database/tablespace combinations that were not defined in the DB2 system catalog. The report may show your Demo database and tablespace names instead of your Copy of Production database and tablespace names. You will correct this situation when you create new tablespaces.

---

See Create New Tablespaces.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Initial        | All      | Oracle<br>Informix<br>DB2 UNIX/NT<br>DB2 z/OS | All       |

### Task 4-3-3: Set Record Parameters After Copy

This step updates table overrides stored in the PSRECDDLPRM table. The values stored in the PARMVALUE field are updated with the current values found in the system catalog. The name of the process is:

```
SETTABLE.SQR
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | Oracle    | All       |

### Task 4-3-4: Create New Tablespaces

This section discusses:

- Prerequisites
- Creating PeopleSoft Delivered Tablespaces
- Creating Custom Tablespaces

## Prerequisites

Before you perform this step, you must make sure your database administrator has created all new tablespaces that will be used in new tables.

---

**Note.** DB2 z/OS sites need to create databases as well as tablespaces at this time.

---

## Creating PeopleSoft Delivered Tablespaces

If you use PeopleSoft-delivered tablespace names, be aware that there may be new ones in this release. The report that you produced when you set tablespace names after copying provides a list of tablespaces that are missing from your database.

See Set Tablespace Names After Copy.

You need to create all of the tablespaces listed on the report as missing on the database. Once you create all of the tablespaces, you can rerun the SETSPACE.SQR; the report should show that no additional modifications are needed.



---

**Note.** For DBX sites, create all of the tablespaces on the report listed as missing on the database in addition to the corresponding index (IDX) tablespace.

---

PeopleSoft delivered a shell SQL script containing the DDL commands to create all of the PeopleSoft-delivered tablespaces. Edit the script to create just the new tablespaces and to set up the script for your environment.

---

**Note.** PeopleSoft reassigned some tables to larger tablespaces because they now require a 32-KB buffer pool. You must manually edit the Create Table statements in the upgrade scripts to replace the tablespace names with an appropriate tablespace name in your implementation that utilizes a 32-KB buffer pool.

---

The script name is:

LMDDL.SQL

---

**Important!** For DB2 UNIX/NT sites, the script name is LMDDL.SQL for ANSI, and LMDDL.U.SQL for Unicode.

---

DB2 z/OS sites must also consider how database names are assigned. After the upgrade/copy is completed, some of the PeopleTools metadata tables in your Copy of Production database will contain the database values from the Demo database. Review the SETSPACE SQR report for those tables that are reported as not defined in the database. If the report shows your Demo database names instead of your Copy of Production database names you can reset them with the following SQL:

```
UPDATE PSRECTBLSPC SET DBNAME = 'Copy of Production dbname'
WHERE DBNAME = 'Demo dbname'
```

## Creating Custom Tablespaces

If you will use custom tablespaces, create those tablespaces now. Choose one of the following two methods to get the information into PeopleTools:

- Update PeopleTools for each record you will put into a custom tablespace. You can do this directly through Application Designer, or you can update PSRECTBLSPC directly by using the appropriate SQL for your site, as follows:

DB2 z/OS sites:

```
UPDATE PSRECTBLSPC
SET DBNAME = 'new dbname', DDLSPACENAME = 'new tablespacename'
WHERE DBNAME = 'current dbname'
AND DDLSPACENAME = 'current tablespacename';
```

All other sites:

```
UPDATE PSRECTBLSPC
SET DDLSPACENAME = 'new tablespacename'
WHERE DDLSPACENAME = 'current tablespacename';
```

To update each table individually, add the following clause to the predicate of the above statement, making sure you use the record name in this clause:

```
AND RECNAME = record name
```

The SETSPACE report contains the table name. The record name will not have the “PS\_” prefix.

You can double-check that you created all tablespaces by rerunning the SETSPACE.SQR report. If you created all tablespaces for records defined in PeopleTools, the report will be empty.

- When you edit the Create and Alter scripts, you can change the SQL to create the tables in the correct tablespaces. Later in this task you will set tablespace names, which will update PeopleTools with the correct tablespaces or Database/tablespace in DB2 z/OS. The report should be empty at that time.

---

**Note.** For DB2 z/OS sites, the SETSPACE report may list some Database/tablespace combinations as “Table Undefined - DB/TS OK” when in fact the Database name is one that was defined for your Demo database. This occurs if your Demo and Copy of Production databases are in the same DB2 subsystem. The SETSPACE.SQR detected that the Database/tablespace combinations do exist in the subsystem and are therefore valid. Make sure that you update these Database/tablespace names to match those that exist in your Copy of Production, using the instructions above.

---



---

**Note.** During the Move to Production pass, you will create these tablespaces when you populate tablespace data. You can reuse this script, or you can create a new script for your production environment. To reuse the script you have created for this task, save it and copy it into the PS\_HOME\SCRIPTS directory that you use during the Move to Production pass.

---

See Enterprise PeopleTools Installation for DB2 UDB for z/OS for your new release, Correcting Invalid Database/Tablespace Combinations.

See Modifying the Database Structure: Editing the Create and Alter Scripts and Setting Tablespace Names.

See “Apply PeopleTools Changes,” Populating Tablespace Data.

See “Apply Changes to Production Database,” Performing the Move to Production.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Initial        | All      | Oracle<br>Informix<br>DB2 z/OS<br>DB2 UNIX/NT | All       |

---

## Task 4-4: Backing Up After the Upgrade Copy

Back up your database now. This enables you to restart your upgrade from this point, should you experience any database integrity problems during the remaining tasks in the upgrade process.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 4-5: Modifying the Database Structure

This section discusses:

- Understanding Modifying the Database Structure
- Backing Up for DB2
- Building the Upgrade Tables Script
- ReCreating Upgrade Tables
- Creating the ALLTEMPTABS Project
- Building the Create Temp Tables Script
- Creating the ALLTABS Project
- Building the Create and Alter Scripts
- Editing the Create and Alter Scripts
- Creating Temporary Tables
- Creating Tables
- Altering Tables
- Creating Indexes
- Reviewing the Create Indexes Log
- Setting Index Parameters
- Setting Temp Table Tablespace Names
- Setting Tablespace Names
- Setting Record Parameters
- Generating a DB2 UNIX RUNSTATS Script
- Updating Statistics for DB2 UNIX
- Updating Statistics for DB2 zOS
- Updating Statistics for Informix
- Updating Statistics for Oracle

### Understanding Modifying the Database Structure

In this task you run various scripts and processes that will modify your database structure, including creating new tables and altering existing ones.

#### Task 4-5-1: Backing Up for DB2

If you are using the DB2 z/OS platform, back up your database now. This enables you to restart your upgrade from this point if you should experience any database integrity problems during the remaining tasks in the upgrade process.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | DB2 z/OS  | All       |

## Task 4-5-2: Building the Upgrade Tables Script

This step generates the SQL script to drop and re-create all the tables in the project named UPGCONVERT. These tables will be used during data conversion by Application Engine programs. They can be safely dropped at this time because they do not contain application data required by your PeopleSoft system. The script name for your upgrade path is:

UPGCONVERT\_CRTTBL.SQL

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-3: ReCreating Upgrade Tables

This step runs the SQL script you generated to re-create all the tables in the project named UPGCONVERT. The script name for your upgrade path is:

UPGCONVERT\_CRTTBL.SQL

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-4: Creating the ALLTEMPTABS Project

This step creates a project named ALLTEMPTABS and inserts all records of the type *Temporary Table*.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-5: Building the Create Temp Tables Script

This step generates the SQL script to drop and re-create all the records of type Temporary Table in the database. Processes use the Temporary Tables dynamically in your system. They can be safely dropped at this time because they do not contain transaction data required by your PeopleSoft system. The script name for your upgrade path is:

ALLTEMPTABS\_CRTTBL.SQL

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-6: Creating the ALLTABS Project

This step creates a project named ALLTABS and inserts all records of the type *Table*.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-7: Building the Create and Alter Scripts

This step generates the SQL script to create all new records of the type *Table*. The script name is:

ALLTABS\_CRTTBL.SQL

This step generates the SQL script to alter all existing records of the type *Table*. This script is referred to as Alter Without Deletes. The tables are altered to add new columns, rename existing columns and change columns that have modified properties, such as length. Columns that will eventually be deleted will still exist on the tables after this script is executed. The script name is:

ALLTABS\_ALTTBL.SQL

This step generates the SQL script to create new indexes and to re-create modified indexes as needed for the tables in the first two scripts. The script name is:

ALLTABS\_CRTIDX.SQL

---

**Note.** This step also creates the script ALLTABS\_CRTTRG.SQL, which re-creates all database triggers. You do not need to run this script, because all database triggers will be created in the “Finalizing the Database Structure” task.

---



---

**Note.** For DB2 z/OS sites, if this step takes an exceptionally long time, performing a RUNSTATS on the system catalog tablespace SYSDBASE may improve performance.

---

See Finalizing the Database Structure.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-8: Editing the Create and Alter Scripts

In this step, you will edit the SQL create and alter scripts for tablespace names and sizing. The script names for your upgrade path are:

```
ALLTEMPTABS_CRTTBL.SQL
ALLTABS_CRTTBL.SQL
ALLTABS_ALTTBL.SQL
ALLTABS_CRTIDX.SQL
```

If you are not using the PeopleSoft tablespace names, you will need to review and modify the scripts above. When the new record was copied to the Copy of Production database, the PeopleSoft default tablespace name was copied as well. When you performed the step “Create Tablespaces” you were given the option to correct the tablespace names online or to wait and edit the scripts. After you have completed running these scripts you will run the programs that synchronize the PeopleTools definitions with the database catalog again. Therefore, any changes you make to the scripts now will be reflected in the PeopleTools definition. Have your database administrator review these scripts and modify the tablespace names appropriately.

Many of the new tables and indexes will be populated during the upgrade. If they are not sized appropriately for your database, the conversion programs will stop with errors. After the upgrade is complete, you may want your database administrator to review and make adjustments to the amount of free space left in some of the tables or tablespaces.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | DB2 z/OS<br>DB2 UNIX/NT<br>Oracle<br>Informix | All       |

## Task 4-5-9: Creating Temporary Tables

This step runs the SQL script you generated to create all the records of the type *Temporary Table*. The script name for your upgrade path is:

```
ALLTEMPTABS_CRTTBL.SQL
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-10: Creating Tables

This step runs the SQL script you generated to create all the records of the type *Table*. This step creates new table structures in your database. The script name for your upgrade path is:

ALLTABS\_CRTTBL.SQL

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-11: Altering Tables

This step runs the SQL script you generated to alter the existing records of type *Table*. This step alters existing PeopleSoft table structures to comply with your new PeopleSoft release. The script name for your upgrade path is:

ALLTABS\_ALTTBL.SQL

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-12: Creating Indexes

This step runs the SQL script you generated to create indexes on records of the type *Table*. This step creates or modifies indexes as required. The script name for your upgrade path is:

ALLTABS\_CRTIDX.SQL

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-13: Reviewing the Create Indexes Log

When Change Assistant runs the create indexes script to create indexes, it will not stop when it encounters errors. When you view the log file, you will see that some indexes cannot be created due to unique index constraints. The data causing those indexes to fail will be updated during the task, “Running Data Conversion.” The indexes will then create successfully during the task, “Finalizing the Database Structure.”

Review the errors in the log file. Unique constraint errors are acceptable. If you see any other types of index creation errors, such as space problems, you must correct them before you continue with the upgrade. If you do not correct the errors, it may degrade your performance during data conversion. The log file name for your upgrade path is:

```
ALLTABS_CRTIDX.LOG
```

See Running Data Conversion.

See Finalizing the Database Structure.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-5-14: Setting Index Parameters

This step updates index overrides stored in the PSIDXDDLPARM table. The values stored in the PARMVALUE field are updated with current values found in the system catalog. The name of the process is:

```
SETINDEX.SQR
```

### Properties

| Database Orientation | Initial or MTP | Products | Platforms          | Languages |
|----------------------|----------------|----------|--------------------|-----------|
| Target               | Both           | All      | Oracle<br>DB2 z/OS | All       |

## Task 4-5-15: Setting Temp Table Tablespace Names

This step populates the PeopleTools table PSRECTBLSPC with the table name, database name, and tablespace name information for the temporary table instances created on the database in a previous step. This information will be required by processes that perform in-stream RUNSTATS (%UpdateStats) on the temporary table instances.

```
SETTMPIN.SQR
```



## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 4-5-16: Setting Tablespace Names

This step populates all tablespace information in the PSRECTBLSPC table. The values stored in the DDLSPACENAM field are updated with current values found in the system catalog. If you modified tablespace names when you edited the SQL script that created your new tables from the PeopleSoft-delivered names, this will make those same changes in the PeopleSoft record definition. The name of the process is:

SETSPACE.SQR

## Properties

| Database Orientation | Initial or MTP | Products | Platforms                                     | Languages |
|----------------------|----------------|----------|---|-----------|
| Target               | Both           | All      | Oracle<br>Informix<br>DB2 UNIX/NT<br>DB2 z/OS | All       |

## Task 4-5-17: Setting Record Parameters

This step updates table overrides stored in the PSRECDDLPRM table. The values stored in the PARMVALUE field are updated with the current values found in the system catalog. The name of the process is:

SETTABLE.SQR

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Oracle    | All       |

## Task 4-5-18: Generating a DB2 UNIX RUNSTATS Script

This step executes the RUNSTATS.SQR that creates the RUNSTATS.SQL to update the statistics on DB2 UNIX/NT.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms   | Languages |
|----------------------|----------------|----------|-------------|-----------|
| Target               | Both           | All      | DB2 UNIX/NT | All       |

## Task 4-5-19: Updating Statistics for DB2 UNIX

Earlier in the upgrade process, you updated your statistics. Now that you have copied your new objects and created new indexes, update your statistics again. Run the RUNSTATS.SQL script created in the previous step to improve performance of your data conversions and generation of the Alter with Delete script.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms   | Languages |
|----------------------|----------------|----------|-------------|-----------|
| Target               | Both           | All      | DB2 UNIX/NT | All       |

## Task 4-5-20: Updating Statistics for DB2 zOS

Earlier in the upgrade process, you updated your statistics. Now that you have copied your new objects and created new indexes, update your statistics again to improve performance of your data conversions and generation of the Alter with Delete script. Contact your database administrator to have the statistics updated on your database before proceeding with your upgrade.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | DB2 z/OS  | All       |

## Task 4-5-21: Updating Statistics for Informix

Earlier in the upgrade process, you updated your statistics. Now that you have copied your new objects and created new indexes, update your statistics again to improve performance of your data conversions and generation of the Alter with Delete script.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Informix  | All       |

## Task 4-5-22: Updating Statistics for Oracle

Earlier in the upgrade process, you updated your statistics. Now that you have copied your new objects and created new indexes, update your statistics again to improve performance of your data conversions and generation of the Alter with Delete script. Contact your database administrator to have the statistics updated on your database before proceeding with your upgrade.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Oracle    | All       |

---

## Task 4-6: Creating Upgrade Views

This section discusses:

- Creating the Upgrade Views Project
- Exporting the Upgrade Views Project
- Importing the Upgrade Views Project
- Building the Upgrade Views
- Running the Upgrade Views Script

### Task 4-6-1: Creating the Upgrade Views Project

This step creates a project named UPGVIEWS and inserts records of type *View/Query View*.

To create the upgrade views project:

1. Sign onto your Copy of Production using your current PeopleTools 8.x.
2. Select PeopleTools, Application Designer.
3. Select New Project.
4. Select Insert, Definitions Into Project from the menu.
5. Select *Records* for the object type.
6. Select *View/Query View* for the selection criteria type.
7. Select the LM\_LRNR\_COMP\_VW record.
8. Click the Insert button.
9. Select the LM\_LRNR\_OBJV\_VW record.
10. Click the Insert button and then Close.
11. Select File, Save Project. Save the project as UPGVIEWS.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

**Task 4-6-2: Exporting the Upgrade Views Project**

This step preserves the UPGVIEWS project for the Move to Production pass by copying it from the Target database to the new release home directory.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

**Task 4-6-3: Importing the Upgrade Views Project**

This step imports the UPGVIEWS project during the Move to Production pass by copying it from the new release home directory to the Target database.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | All       | All       |

**Task 4-6-4: Building the Upgrade Views**

This step generates the script to create (or re-create) the upgrade views in the database.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

**Task 4-6-5: Running the Upgrade Views Script**

In this step, run the SQL script you generated to create the views needed for the upgrade.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-7: Loading Data for Data Conversion

This section discusses:

- Swapping Languages on System Data
- Exporting Application Messages
- Importing Application Messages
- Exporting Record Groups
- Importing Record Groups
- Exporting the System Setup Data
- Importing the System Setup Data
- Exporting the PW Pagelet Data
- Importing the PW Pagelet Data
- Exporting the Pagelet Wizard Data
- Importing the Pagelet Wizard Data
- Exporting Data Conversion Driver Data
- Importing Data Conversion Driver Data
- Importing Approval Process Seed Data

### Task 4-7-1: Swapping Languages on System Data

This script swaps the base language for tables that contain system data on your Demo database and have related language data, in preparation for the system data exports in the next step. This script should be run only if your Copy of Production has a base language other than English. The script name for your upgrade path is:

If you want to make this step automated, select the step Swap Languages on System Data in Change Assistant, open the Step Properties dialog box, change the Type from ManualStop to DataMoverUser, and click OK twice.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages                 |
|----------------------|----------------|----------|-----------|---------------------------|
| Source               | Initial        | All      | All       | Non-English Base Language |

## Task 4-7-2: Exporting Application Messages

This step exports Application Messages data from the Demo database. The script name for your upgrade path is:

DLUPX01E.DMS

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-7-3: Importing Application Messages

This step imports Application Message data into your Copy of Production database. Message Sets 0-999 are overlaid during the PeopleTools Upgrade. Application Message Sets 1000-19,999 are overlaid with this task. If you have added custom messages in this set range, you must add those messages again at the end of the upgrade. To prevent this from happening again in future maintenance or upgrades, add your custom messages in a set range of 20,000 or greater.

---

**Note.** If the script fails, verify that your Configuration Manager Profile output and input directories are set to the same location. If not, this could be the cause of the problem.

---

The script name for your upgrade path is:

DLUPX01I.DMS

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-7-4: Exporting Record Groups

This step exports Record Group data from the Demo database. The script name for your upgrade path is:

DLUPX02E.DMS

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-7-5: Importing Record Groups

This step imports Record Group data and populates Set Control data in your Copy of Production database. The following records are related to Record Groups and Set Control data:

- REC\_GROUP\_REC
- REC\_GROUP\_TBL
- SET\_CNTRL\_TBL
- SET\_CNTRL\_GROUP
- SET\_CNTRL\_REC
- SETID\_TBL

The import script deletes from, and then reloads, the Record Group tables, REC\_GROUP\_REC and REC\_GROUP\_TBL. These are the tables that are modified when you use PeopleTools, Utilities, Administration, Record Group. The script then rebuilds the related setID tables, PS\_SET\_CNTRL\_GROUP and PS\_SET\_CNTRL\_REC. The PS\_SET\_CNTRL\_TBL and PS\_SETID\_TBL tables contain the setIDs you use in your system; this script does not update PS\_SET\_CNTRL\_TBL. However, it does check for orphan Set ID references in PS\_SET\_CNTRL\_REC and adds the missing Set IDs to PS\_SETID\_TBL.

If you have moved a PeopleSoft-delivered record into a custom added record group, and deleted the record from the PeopleSoft-delivered record group, this script will put the record back into the PeopleSoft-delivered record group and remove it from the custom added record group.

If you have created a new record group, it will be deleted in this step if all of its records are assigned to PeopleSoft-delivered record groups in the new release. To continue using your custom record group, you will need to re-create it in the Reapply Customizations task.

This script creates an output file and uses it to create a temporary table. To run successfully, the Configuration Manager input and output Data Mover directories should be the same.

---

**Note.** If the script fails, verify that your Configuration Manager Profile output and input directories are set to the same location. If not, this could be the cause of the problem.

---

The script name for your upgrade path is:

DLUPX02I.DMS

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-7-6: Exporting the System Setup Data

This script exports the contents of the Message, Strings, Stored Statements, Record Group, data conversion driver, EDI, and Mass Change tables from the Copy of Production database during your Move to Production passes. During the initial pass, you ran other scripts to load this data and in some cases had to reapply customizations. This script exports the entire contents of these tables, including customizations, so that you will not need to reapply them after the Move to Production. The script name for your upgrade path is:

MVAPPEXP.DMS

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | MTP            | All      | All       | All       |

## Task 4-7-7: Importing the System Setup Data

This script imports the data exported in the previous step into your New Copy of Production database during your Move to Production passes. This script replaces many scripts that you ran in the initial pass. It will move all data in these tables so that any customizations you have added to these tables during your initial pass will be moved to your New Copy of Production database. Also, it will rebuild the Set Control tables using the Record Groups from the Copy of Production database and your current Set Control values on the New Copy of Production database. The script name for your upgrade path is:

MVAPPIMP.DMS

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | All       | All       |

## Task 4-7-8: Exporting the PW Pagelet Data

This script exports the application specific Pagelet Wizard pagelet definition, header, footer, and category tables from the Demo database in the initial pass. The script name is:

DLUPX14E.DMS

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-7-9: Importing the PW Pagelet Data

This script imports the application specific data for the Pagelet Wizard pagelet definition, header, footer, and category tables into your Copy of Production database during the initial pass. This data is needed for the data conversion. The script name is:



DLUPX14I.DMS

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

**Task 4-7-10: Exporting the Pagelet Wizard Data**

This script exports the contents of the Pagelet Wizard tables from the Copy of Production database during your Move to Production passes. During the initial pass, you ran programs and scripts to load this data and in some cases had to make changes. This script exports the entire contents of these tables, including changes, so that you will not need to reapply them after the Move to Production. This data is needed for the data conversion. The script name is:

MVUPX16E.DMS

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | MTP            | All      | All       | All       |

**Task 4-7-11: Importing the Pagelet Wizard Data**

This script imports the Pagelet Wizard tables from the Copy of Production database into the New Copy of Production during your Move to Production passes. This script replaces processes that you ran in the initial pass. It will move all data in the affected tables so that any changes you have made during your initial pass will be moved to your New Copy of Production database. This data is needed for the data conversion. The script name is:

MVUPX16I.DMS

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | All       | All       |

**Task 4-7-12: Exporting Data Conversion Driver Data**

This step exports data conversion Application Engine driver data from the Demo database. The script name for your upgrade path is:

DLUPX03E.DMS

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-7-13: Importing Data Conversion Driver Data

This step imports data conversion Application Engine driver data into your Copy of Production database.

The script name for your upgrade path is:

DLUPX03I.DMS

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-7-14: Importing Approval Process Seed Data

This script loads seed data for cloning approval process definitions. This seed data will later be deleted during data conversion.

The script name for your upgrade path is:

PULMAP01.DMS

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-8: Restoring New Release Demo

Restore your New Release Demo database from the backup you took in Chapter 1 earlier in the upgrade. The backup was taken before projects were copied and scripts were run against the Demo database. This is done to restore the environment to the original Demo database.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-9: Applying Updates Before Data Conversion

You should have downloaded and applied Required For Upgrade updates just after you installed your Demo database. Now is a great time to check PeopleSoft Customer Connection again for any new postings, and apply them now. Before data conversion, you should also verify that you have the most current UPGCONVERT.EXE.

This is just one place that you can apply updates. There are other places in the upgrade process where applying updates may be applicable as well. How you apply the update varies depending on where you are in the upgrade.

See Appendix: “Applying Fixes Required for Upgrade.”

---

**Important!** Apply all fixes listed under the product line/release, even if you have not licensed the product the fix is listed under. There are many interdependencies between products and database objects. If you do not apply the fix, you may be introducing another error in a different area of the conversion code.

---

To apply PeopleSoft project fixes before data conversion:

1. Download Required for Upgrade Change Package(s) using the “Download Change Package” functionality in Change Assistant.
2. Use Change Assistant to install/apply the update(s) into your Demo database for this upgrade pass. Review the documentation included with each update prior to applying the update.

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your current release.

3. The project is now loaded on your Demo database. You should run a project compare to make sure the objects in the fix will not overwrite any of your customizations. If you find customizations, you must decide how to deal with them before you copy the fix to your Copy of Production.
4. If you are performing a Move to Production upgrade pass, first migrate the Change Package(s) into the Source database for this upgrade pass. If needed, first set up Change Assistant with the environment information for your Source database. If you customized any of the objects delivered in the Change Package, you should repackage the fix to include your customizations. If you did not customize any objects delivered in the fix you may directly apply it to the Source database.

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your new release, Applying Updates.

5. Migrate the Change Package(s) into the Target database for this upgrade pass. If needed, first set up Change Assistant with the environment information for your Target database.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-10: Configuring Scheduler and Server

You can manually run data conversion jobs on the server. Refer to the appendix “Improving Performance” for instructions. If you choose to run data conversion manually, configure and start your process scheduler and application servers now.

Tips for configuring and starting the application server:

- Make sure the application server domain being configured points to the Target database for this pass of the upgrade.
- Set a different JSL port for each database instance.

See the Enterprise PeopleTools installation guide for your database platform for the new release.

See Appendix: “Improving Performance.”

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-11: Backing Up Before Data Conversion

Back up your database now. This enables you to restart your upgrade from this point, should you experience any database integrity problems during the remainder of the tasks in the upgrade process.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-12: Running Data Conversion

This section discusses:

- Reviewing Data Conversion Tips
- Running Data Conversion for Group 1

---

**Note.** In this task you will populate new tables and columns. Earlier, you altered tables and added all new and modified columns. You did not, however, remove obsolete columns. The following steps will move data from the obsolete columns to the new columns and tables. Later in this chapter, in the task “Finalizing the Database Structure,” you will generate and run SQL to delete those obsolete columns. The Upgrade Driver Application Engine program, UPG\_DATACONV, will run all upgrade data conversions.

---

## Task 4-12-1: Reviewing Data Conversion Tips

This section discusses:

- Upgrade Driver Program – UPG\_DATACONV
- Data Conversion Documentation
- Running Data Conversion Concurrently
- Writing Data Conversion for Your Non-PeopleSoft Records
- Data Conversion Errors Expected During the Initial Upgrade Pass
- Restarting Data Conversion

### Upgrade Driver Program – UPG\_DATACONV

UPG\_DATACONV is an Application Engine program designed to run all upgrade data conversions. Each time the program is run during an upgrade pass, Change Assistant passes a group number parameter to the program. The program then reads the table PS\_UPG\_DATACONV, selecting all rows with that group number and ordering them by the sequence number on the row. A list of Application Engine library sections that must be run for data conversion is returned. The program then calls each section in the order of the sequence number. You can review the sections that are called by the Upgrade Driver program by accessing the Define Upgrade Drivers page on the Demo database.

### Data Conversion Documentation

Each section called by the Upgrade Driver program contains comments describing the underlying conversion. By running the UDATACNV.SQR report you can find which sections are called by the Upgrade Driver program and what they are doing.

See Appendix: “Using Data Conversion Utilities.”

### Running Data Conversion Concurrently

Each data conversion step in this task corresponds to a group number as defined in the Define Upgrade Drivers page. Each group is independent of the others unless otherwise documented, allowing the groups to be run concurrently. PeopleSoft recommends that you run data conversion in the order it appears in your template during the initial upgrade pass to determine processing times. This is why the Change Assistant templates are delivered with the data conversion steps’ “Run Concurrently” property set to “No.” To reduce overall processing time during your Move to Production passes, you may decide to run some or all conversion steps concurrently. To run steps concurrently, reset the “Run Concurrently” property to “Yes” in your Change Assistant template.

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your new release.

## Writing Data Conversion for Your Non-PeopleSoft Records

The data conversion code delivered for this upgrade was written to handle only PeopleSoft-delivered records. You may have added your own records to the system. To convert data in the underlying tables, you may need to create your own Application Engine library. The Upgrade Driver program can call an Application Engine library section that you create. To have the Upgrade Driver program call your custom section during this task, you will need to add the section on the Define Upgrade Drivers page.

See Appendix: “Using Data Conversion Utilities.”

## Data Conversion Errors Expected During the Initial Upgrade Pass

During your initial upgrade pass you can expect to have data conversion programs fail. This is because your PeopleSoft installation is unique, which makes it difficult to write data conversions that will work for everyone all of the time. Your database may be larger than most, you may have customized PeopleSoft-defined records, or you may not have copied all object deletions onto your Copy of Production. These differences will cause data conversion to fail. You must fix each problem on your initial Copy of Production and restart the Application Engine program. Your fixes will be automatically copied to your New Copy of Production during the Move to Production passes and data conversion will run smoothly.

If you have customized records that are delivered from PeopleSoft, you may need to make changes to the Application Engine programs to handle these customizations. For example, here are two situations in which you may need to customize data conversion code:

- If you added fields to a PeopleSoft-delivered record, you may need to add your additional fields to the conversion code for those records.
- If a PeopleSoft-delivered record you customized will be deleted, you may need to add your own conversions to move the data to a new location.

Use the Find In feature of Application Designer to determine which Application Engine programs affect your customized records.

To use the Find In feature:

1. Create a project and add all Application Engine programs and related objects that have a name starting with 'UPG' and save the project.
2. Click Edit, Find In.
3. Enter each customized record name in the Find What field and your project name in the Project field.
4. Click Find.

The results will appear in the output window

Document any changes you make to data conversion programs. This way, if a new version of the program is delivered through PeopleSoft Customer Connection, you will know exactly what changes you have made. You can then reapply the changes to the new version of the program.

If your database is large, you may have data conversion programs that fail due to running out of space as you move data from one table to another. This problem can happen on all RDBMS platforms, but is more of a problem on those platforms using tablespaces. If your data conversion terminates abnormally with a space error, examine the Application Engine SQL statements that caused the problem. Determine where the data is coming from and how much will be moved. Have your DBA adjust the allocated space accordingly. The data conversion can then be restarted.

If you get a data conversion error because a field does not exist on a table, and the field is not one you have customized, check your field renames. If a field that appears on a record that is deleted in the new PeopleSoft release but was not deleted in your compare and copy, your table will be out of sync with what is expected by data conversion. If you had deleted the record, the rename would not happen on the physical table and the field would have the old name. This is what the data conversion program expects. If you did not delete the record, the field was renamed during the altering of tables and the data conversion program will terminate abnormally. Edit the Application Engine SQL to use the name, which is now on your table, and then restart the data conversion.

See Appendix: “Using the Comparison Process.”

## Restarting Data Conversion

Before restarting a data conversion step, rename the log file. Change Assistant uses the same log file name each time you start or restart an Application Engine program. This means that the restarted Application Engine program will replace the original log file if it is not renamed.

If your data conversion program fails, fix the problem on your Copy of Production and restart the program. When you set the data conversion step to Restart in your Change Assistant job, it will rerun the program using the `PROCESS_INSTANCE` and `RUN_CNTL_ID` from the initial run and the conversion will restart right after the last committed SQL command. Application Engine keeps track of data committed to the database in the table `PS_AERUNCONTROL`, keyed by `PROCESS_INSTANCE` and `RUN_CNTL_ID`.

See Finalizing the Database Structure.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-12-2: Running Data Conversion for Group 1

This step runs the `UPG_DATACONV` Application Engine program for Group 1. For additional documentation for Group 1, run the `UDATACNV` report.

Group 1 must execute successfully before any other groups (if applicable) can run. If there are other groups and you decide to run groups concurrently, Group 1 must complete before you launch any other groups.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-13: Backing Up After Data Conversion

Back up your database now. This enables you to restart your upgrade from this point, should you experience any database integrity problems during the remaining tasks in the upgrade process.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-14: Finalizing the Database Structure

This section discusses:

- Understanding Final Database Structure
- Building the Alter with Deletes Scripts
- Altering Tables with Deletes
- Creating Indexes Again
- Creating Triggers
- Running the AE SYNCIDGEN Process
- Creating All Views

### Understanding Final Database Structure

Now that Data Conversion is completed, this task will alter the tables to remove obsolete columns, and create final indexes and views.

#### Task 4-14-1: Building the Alter with Deletes Scripts

This step uses the previously created project ALLTABS and generates three SQL scripts: one that will alter tables to drop obsolete columns, one that will also create any remaining indexes that could not be created with the first alter, and one that will create triggers. The script names are:

```
ALLTABS_DEL_ALTTBL.SQL
ALLTABS_DEL_CRTIDX.SQL
ALLTABS_DEL_CRTRTG.SQL
```

---

**Important!** All indexes should create when the ALLTABS\_DEL\_CRTIDX.SQL script is run. When a unique index fails to create, it is probably due to a data conversion issue. If a unique index fails to create, you must resolve the issue and not simply remove the index. To prevent this issue, you can back up tables in the ALLTABS\_DEL\_ALTTBL.SQL script that will be dropping recfields that have data. This way, if you have an issue you may have the old fields and data you need to correct it.

---



---

**Note.** For DB2 z/OS sites, if this step takes an exceptionally long time, performing a RUNSTATS on the system catalog tablespace SYSDBASE may improve performance.

---



**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

**Task 4-14-2: Altering Tables with Deletes**

This step executes the script, ALLTABS\_DEL\_ALTTLBL.SQL, which was generated in the previous step.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

**Task 4-14-3: Creating Indexes Again**

This step executes the script ALLTABS\_DEL\_CRTIDX.SQL, which was generated in the previous step. All indexes should create at this time.

---

**Important!** Review the log to find any unique indexes that might have failed to create. All indexes should create at this time, so those errors are not acceptable and should be corrected. When a unique index fails to create, it is probably due to a data conversion issue.

---

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

**Task 4-14-4: Creating Triggers**

This step executes the script ALLTABS\_DEL\_CRTTRG.SQL, which was generated in a previous step.

**Properties**

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

**Task 4-14-5: Running the AE SYNCIDGEN Process**

This step executes the AE\_SYNCIDGEN Application Engine program. Mobile applications use Sync IDs in order to give each row a unique identifier. For any tables with the Sync ID column set to the default value of zero, the AE\_SYNCIDGEN program will populate the column with the next valid Sync ID value.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-14-6: Creating All Views

This step runs CREATEVW.dms to re-create all views in the Copy of Production database. The script will try to create every view in Application Designer. If there is an error on one view, it will keep going until it gets to the end of the list.

---

**Important!** Review the log to find any views that failed to create. All views should create at this time, so those errors are not acceptable and should be corrected.

---

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-15: Loading Data to Complete System Setup

This section discusses:

- Exporting Strings
- Importing Strings
- Exporting EDI Statements
- Importing EDI Statements
- Exporting Mass Change Data
- Importing Mass Change Data
- Exporting XML Service Information
- Importing XML Service Information
- Exporting Related Language System Data
- Importing Related Language System Data
- Exporting Application System Data
- Importing Application System Data
- Exporting Setup Data
- Importing Setup Data
- Importing Learning Filters

## Task 4-15-1: Exporting Strings

This script exports Strings data from the Demo database. The script name for your upgrade path is:

DLUPX04E.DMS

This data will be exported during Move to Production by the script MVAPPEXP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-15-2: Importing Strings

This script imports Strings data into the Copy of Production database. The script name for your upgrade path is:

DLUPX04I.DMS

This data will be imported during Move to Production by the script MVAPPIMP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-15-3: Exporting EDI Statements

This script exports EDI Statements from the Demo database. The script name for your upgrade path is:

DLUPX05E.DMS

This data will be exported during Move to Production by the script MVPRDEXP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-15-4: Importing EDI Statements

This script imports the EDI Statements into the Copy of Production database. The script name for your upgrade path is:

DLUPX05I.DMS

This data will be imported during Move to Production by the script MVPRDIMP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-15-5: Exporting Mass Change Data

This script exports Mass Change tables from the Demo database. The script name for your upgrade path is:

`DLUPX06E.DMS`

This data will be exported during Move to Production by the script MVAPPEXP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-15-6: Importing Mass Change Data

This script imports Mass Change tables into the Copy of Production database. The script name for your upgrade path is:

`DLUPX06I.DMS`

This data will be imported during Move to Production by the script MVAPPIMP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-15-7: Exporting XML Service Information

This script exports XML service data from the Demo database. The script name for your upgrade path is:

`DLUPX13E.DMS`

This data will be exported during Move to Production by the script MVPRDEXP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-15-8: Importing XML Service Information

This script imports XML service data into the Copy of Production database. The script name for your upgrade path is:

DLUPX13I.DMS

This data will be imported during Move to Production by the script MVPRDIMP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-15-9: Exporting Related Language System Data

This script exports system data from various application related language tables in your Demo database into a Data Mover \*.dat file. In a later step, this data will be loaded into your Copy of Production. The script name for your upgrade path is:

DLLMLASYSE.DMS

---

**Note.** During Move to Production passes you can reuse the data files that are created by this export script. Preserve this DAT file, and set the 'Type of Upgrade' property in the Change Assistant template to Initial Upgrade for this step.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages                            |
|----------------------|----------------|----------|-----------|--------------------------------------|
| Source               | Both           | All      | All       | Any installed in addition to English |

## Task 4-15-10: Importing Related Language System Data

This script will delete old related language system data from related language tables. The script then imports the data exported by the scripts above. The script name for your upgrade path is:

DLLMLASYSI.DMS

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages                            |
|----------------------|----------------|----------|-----------|--------------------------------------|
| Target               | Both           | All      | All       | Any installed in addition to English |

## Task 4-15-11: Exporting Application System Data

This script exports system data from various application tables from the Demo database into a Data Mover \*.DAT file. In a later step, this data will be loaded into the Copy of Production database. The script name for your upgrade path is:

DLLMSYSE.DMS

---

**Note.** During Move to Production passes, you can reuse the data files that are created by this export script. To do this, change the Type of Upgrade from Both to Initial Upgrade in the step properties and save the job.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Both           | All      | All       | All       |

## Task 4-15-12: Importing Application System Data

This script imports the application system data, exported in the above step, into the Copy of Production database. The script name for your upgrade path is:

DLLMSYSI.DMS

---

**Note.** Some of the data will be imported using the *ignore dups* option. These data loads will give the message “Error: duplicate SQL rows” and then give a “Successful completion” message. These error messages can be ignored because duplicate data is expected.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-15-13: Exporting Setup Data

This script exports setup data from the Demo database. The script name for your upgrade path is:

DLUPX16E.DMS

This data will be exported during Move to Production by the script MVAPPEXP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Source               | Initial        | All      | All       | All       |

## Task 4-15-14: Importing Setup Data

This script imports setup data into the Copy of Production database. The script name for your upgrade path is:

`DLUPX16I.DMS`

This data will be imported during Move to Production by the script MVAPPIMP.DMS.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 4-15-15: Importing Learning Filters

In this step, run a Data Mover script to import filters that can be used to search through learning activities and programs. A set of sample filters will be created for each learning environment in your system. You can modify, delete, or add to these filters in the future by selecting Set Up ELM, Learning Filters.

The script name for your upgrade path is:

`UVLMUP88105.DMS`

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-16: Updating Language Data

This section discusses:

- Understanding Updating Language Data
- Run the TSRECPOP Script

### Understanding Updating Language Data

In this task, you run scripts to modify data in PeopleTools related language tables.

---

**Note.** For DB2 z/OS customers, PeopleSoft recommends that you run RUNSTATS against the system catalog tables at this time.

---

### Task 4-16-1: Run the TSRECPOP Script

In this step, the TSRECPOP script initializes and modifies the data in PeopleTools related language architecture tables.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 4-17: Completing PeopleTools Conversion

The PeopleTools Upgrade Driver Application Engine program, PTUPGCONVERT, runs additional PeopleTools upgrade data conversions. The program then reads the table PS\_PTUPGCONVERT, selecting all rows with a group number of 02 and ordering them by the sequence number on the row. A list of Application Engine library sections that must be run for data conversion is returned. The program then calls each section in the order of the sequence number. Review the report generated by PTUCONV.SQR for details on the conversions run in this step.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-18: Updating Object Version Numbers

In this task, you run the VERSION Application Engine program. This ensures that all of your version numbers are correct and, if not, resets them to 1.

---

**Note.** Do not update statistics after you complete this task.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 4-19: Running the Final Audit Reports

This section discusses:

- Run the Final DDDAUDIT Report
- Run the Final SYSAUDIT Report



- Create the FNLALTAUD Project
- Run the Final Alter Audit
- Review the Final Audits
- Run a Final SETINDEX Report
- Run a Final SETTABLE Report

## Task 4-19-1: Run the Final DDDAUDIT Report

DDDAUDIT is an SQR that compares your production SQL data tables with the PeopleTools record definitions to uncover inconsistencies. You can expect some errors from this report. You will review the output from the report in another step.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-19-2: Run the Final SYSAUDIT Report

SYSAUDIT is an SQR that identifies *orphaned* PeopleSoft objects. For example, SYSAUDIT will identify a module of PeopleCode that exists but does not relate to any other objects in the system. SYSAUDIT also identifies other inconsistencies within your database.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-19-3: Create the FNLALTAUD Project

In this step, you create the FNLALTAUD project and use it to run your final Alter Audit. Creating this new project now ensures that all the records in your system are audited, including SQL tables and temp tables. This project also includes any custom records that you have created in your system.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-19-4: Run the Final Alter Audit

Run the PeopleTools alter record process on all tables in your system to check whether the PeopleTools definitions are synchronized with the underlying SQL data tables in your database. PeopleSoft calls this process an Alter Audit. Alter Audit compares the data structures of your database tables with the PeopleTools definitions to uncover inconsistencies. Alter Audit then creates an SQL script with the DDL changes needed to synchronize your database with the PeopleTools definitions.

The Alter Audit script is built using the FNLALTAUD project created in the previous step.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 4-19-5: Review the Final Audits

The Alter Audit process creates SQL scripts that correct any discrepancies between your PeopleTools record definitions and the database system catalog table definitions. Review the Alter Audit output and correct any discrepancies noted by running the generated scripts with your platform-specific SQL tool. The script names are:

```
FNLALTAUD_ALTTLBL.SQL
FNLALTAUD_CRTIDX.SQL
```

---

**Note.** The Alter Audit process also creates the script FNLALTAUD\_CRTTRG.SQL, which re-creates all database triggers. You do not need to run this script, since all database triggers were created in a previous task.

---

See Finalizing the Database Structure.

---

**Note.** For Informix sites, if your database has Application Functions, you use SQL to drop and re-create these functions and their associated indexes, even though the underlying tables and indexes have not changed.

---



---

**Note.** For Microsoft SQL Server and DB2 UNIX platforms, if your database has tables containing the MSSCONCATCOL or DBXCONCATCOL column, you will see SQL alter the tables and re-create their associated indexes, even though the underlying tables and indexes may not have changed.

---

Review the output from the SYSAUDIT and DDDAUDIT reports and correct any discrepancies.

Your DDDAUDIT listing shows some expected discrepancies. Tables and views deleted from the Application Designer are not automatically deleted from the system tables. PeopleSoft takes this precaution in case you have customized information that you want to preserve. Therefore, the report lists any tables and views that the new release does not have. Review these tables to verify that you do not wish to preserve any custom data, and then drop the tables and views.

Your SYSAUDIT report may have some errors due to references to obsolete PeopleSoft-owned objects. For instance, if PeopleSoft deletes a Permission List, and you have a Role that still refers to that Permission, then it will appear on the SYSAUDIT report.

See Enterprise PeopleTools PeopleBook: Data Management for your new release.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

### Task 4-19-6: Run a Final SETINDEX Report

The SETINDEX SQR updates index overrides stored in the PSIDXDDLPARM table. The SQR updates the values stored in the PARMVALUE field with current values found in the system catalog. Running SETINDEX cleans up fragmentation issues that may have occurred during data conversion.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms          | Languages |
|----------------------|----------------|----------|--------------------|-----------|
| Target               | Both           | All      | DB2 z/OS<br>Oracle | All       |

### Task 4-19-7: Run a Final SETTABLE Report

The SETTABLE SQR updates table overrides stored in the PSRECDDLPARM table. The SQR updates the values stored in the PARMVALUE field with the current values found in the system catalog. Running SETTABLE will clean up fragmentation issues that may have occurred during data conversion.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | Oracle    | All       |



## CHAPTER 5

# Complete Database Changes

This chapter discusses:

- Understanding Database Changes
- Configuring the Upgrade Environment
- Reapplying Customizations
- Setting Up Security
- Completing Portal Data Conversion
- Reviewing PeopleTools Functionality
- Preparing the Content Provider Registry
- Updating the Portal Options Data
- Running Database Full Sync Processes
- Setting Up Learning Environments
- Stamping the Database
- Reviewing Change Control
- Backing Up Before Testing
- Testing Your Copy of Production

---

## Understanding Database Changes

Many changes were made in the previous chapters of this documentation. In this chapter, you complete these changes so you can begin testing your Copy of Production. By testing your Copy of Production, you ensure that you can still operate day-to-day processes on your new PeopleSoft release.

---

## Task 5-1: Configuring the Upgrade Environment

This section discusses:

- Configure Application Server
- Configure Portal

## Task 5-1-1: Configure Application Server

Running Portal requires a fully functional application server domain. In this step, you configure your application server.

---

**Note.** If you configured your application server earlier in the upgrade, you can skip this step.

---

Tips for configuring and starting the application server:

- Make sure the Application Server domain you configure points to the Target database for this pass of the upgrade.
- Set a different JSL port for each database instance.

See the Enterprise PeopleTools installation guide for your database platform.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 5-1-2: Configure Portal

PeopleSoft applications are accessed through the Portal. You need to grant users access to complete the upgrade process. You must install and configure the Portal to complete the upgrade.

---

**Note.** If you configured your Portal earlier in the upgrade, you can skip this step.

---

You also must define a password in Node Definition for Single Signon to work properly. If you do not define a password, the signon page appears when trying to access a report directly, instead of the report itself. To avoid this issue, follow the procedure below to assign a password.

To assign a password:

1. Select PeopleTools, Integration Broker, Integration Setup, Node Definitions.
2. Click Search.
3. Select the database's default local node.  
The default local node shows a *Y* in the Default Local Node column.
4. On the Node Info page, select *Password* as the Authentication Option.
5. Enter a password in the Password field.
6. Enter the password again in the Confirm Password field.
7. Save the Node Definition.
8. Reboot the application server and web server.

See the Enterprise PeopleTools installation guide for your database platform.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 5-2: Reapplying Customizations

This section discusses:

- Understanding the Reapplication
- Performing Customized Object Adjustment
- Registering Portal Navigation Objects

### Understanding the Reapplication

In this task, you work with your customized objects to ensure that they are properly integrated into your upgraded database.

#### Task 5-2-1: Performing Customized Object Adjustment

When you reviewed your upgrade compare reports, you decided whether to take the Source or Target version of the objects. If you took the PeopleSoft version of an object instead of your own customized version, you may need to customize the new objects to get the blend of new standard features and your custom features. In complex cases, this may take several iterations. You need to make manual adjustments to the objects to apply these customizations.

Once you reapply all of your customizations, you should run the DDDAUDIT and SYSAUDIT reports to make sure that you did not introduce any problems into your system.

Reapply any Mass Change or EDI customizations.

See “Prepare Your Database,” Identifying Customizations.

Be aware that you must not overwrite PeopleSoft-loaded data. The customizations, extracted during an earlier step, must be manually applied now.

In another step, you applied the PeopleSoft-delivered record group assignments.

See “Apply Application Changes,” Importing Record Groups.

If you maintain any custom record group assignments, reapply them to your Copy of Production database now.

During Move to Production passes, you will not need to reapply these customizations. The changes you make now will be copied to any subsequent Copy of Production database using Data Mover scripts.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 5-2-2: Registering Portal Navigation Objects

You must register your customized objects, such as menus and components, in order to access them in Portal. You can use the Registration Wizard or the Menu Import process to grant access to the appropriate components. Make sure you register your components for all of your portals (for example, Customer, Supplier, Employee, and so forth). Also, make sure that you select the node name that matches the database. Do not use the Local node.

See Enterprise PeopleTools PeopleBook: PeopleSoft Application Designer for your new release, Using the Registration Wizard.

See Enterprise PeopleTools PeopleBook: Internet Technology for your new release, Administering Portals.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 5-3: Setting Up Security

This section discusses:

- Understanding Security
- Set Up Security
- Synchronize CREF Permissions
- Grant Access to Personalize Homepage

## Understanding Security

In this task you perform steps to set up security, grant access to the user ID, set up permissions lists, and grant access to navigation and homepages.

## Task 5-3-1: Set Up Security

This section discusses:

- Understanding Security Setup



## Understanding Security Setup

Select the PeopleTools, Security folder now to add the new PeopleTools and application menus, delete old menus, and set up appropriate operator security for your system.

Many menu additions and deletions have occurred. Examine the menu compare report and the PeopleSoft Demo database for details of the required security changes, then decide which of your roles and permission lists should have access to each of the new menus.

Many tasks in this chapter instruct you to select a specific menu within the new PeopleSoft release. To perform these tasks, set up appropriate security for each of the menus referenced in each of the tasks.

See PeopleSoft Enterprise Portal Solutions PeopleBook: Enterprise Portal Application Technology for your new release, information on PeopleSoft-delivered security.

---

**Note.** Move to Production: If you changed the user profiles in your production system after you froze your PeopleTools, you must manually apply the changes to your Copy of Production database before the end of the final Move to Production.

---

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 5-3-2: Synchronize CREF Permissions

This section discusses:

- Understanding Content Reference Permissions
- Running the Portal Security Synchronization Process

### Understanding Content Reference Permissions

As part of the PeopleTools 8.4x Portal architecture, Portal Registry Structures reference permission lists. At this point, however, the Portal Registry Structures copied from the Demo database do not reference any permission lists on the Copy of Production database. This synchronization program will match the existing permission lists to the appropriate Registry Structures and update it.

---

**Note.** The user ID that invokes this process must have the security role Portal Administrator. Otherwise, the process may terminate abnormally.

---



---

**Note.** Your Process Scheduler must be running in order to perform this task.

---

### Running the Portal Security Synchronization Process

Follow the steps below to run the Portal security synchronization process.

To run the security synchronization process:

1. From your browser, sign on to your Target database.
2. Select PeopleTools, Portal, Portal Security Sync.

3. Select Add a New Value.
4. Enter the run control ID *UPG\_PORTAL\_SYNC\_BOTH*.
5. Click Add.
6. Keep the default value for the default portal registry name in the Portal Name field (for example: *EMPLOYEE*, *CUSTOMER*, or *SUPPLIER*).
7. Click Save.
8. Click Run.
9. In the Process Scheduler page, check that you set your parameters correctly.
10. Click OK.
11. Click the Process Monitor link to monitor the program's process.
12. Repeat steps 6 through 11 for each Portal name used in the database for your specific applications. With each repeat, in step 6 change the Portal Name field to one of the following: *EMPLOYEE*, *CUSTOMER*, *SUPPLIER*, *MOBILE*, and so on.
13. Review any messages received during the running of this process with your Portal Administrator.

See Enterprise PeopleTools PeopleBook: Internet Technology for your new release.

---

**Note.** If the permission lists for your upgrade user do not allow you access to a component, you will encounter this error when running the security synchronization process for that page: `Security synchronization failed for Portal Object`. This error may indicate other problems with the component or folder, but you should check your security first.

---

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 5-3-3: Grant Access to Personalize Homepage

This section discusses:

- Understanding Access to Portal Homepage
- Updating Homepage Personalization Permission List
- Adding the Portal User Role

### Understanding Access to Portal Homepage

You must complete this step if you use any of the Portal Pack products or pagelets. In order to add, remove, or change the layout of the homepage, you must grant homepage personalization security access to all non-guest users.

### Updating Homepage Personalization Permission List

To update the homepage personalization permission list:

1. Using PeopleSoft Data Mover, sign on to the Target database.

2. Open the Data Mover script *PS\_HOME\SCRIPTS\ PORTAL\_HP\_PERS.DMS*.
3. Run this script against the Target database.
4. Close Data Mover.

### Adding the Portal User Role

To add the Portal User Role to the user IDs:

1. Using PeopleSoft Data Mover, sign on to the Target database.
2. Open the Data Mover script *PS\_HOME\SCRIPTS\ PORTAL\_ ADD\_ROLE.DMS*.
3. Run this script against the Target database.
4. Close Data Mover.

---

**Note.** You should grant the PAPP\_USER role to all new user IDs for access to the homepage personalization. After running this script, manually remove the role PAPP\_USER from any GUEST user ID, since a GUEST user should not be personalizing the common homepage.

---

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 5-4: Completing Portal Data Conversion

This section discusses:

- Reviewing Pagelet and Collection Log
- Enabling Pagelet Publishing

### Task 5-4-1: Reviewing Pagelet and Collection Log

This section discusses:

- Correct Logged Issues
- Run UPGPT846PP Again

This step explains how to correct logged issues for Navigation Collections, Portal Registry objects, and Pagelet Wizard objects.

---

**Note.** Perform this step only if there are logged issues that need to be resolved for Navigation Collections, Portal Registry Objects, or Pagelet Wizard objects reported from the UPGPT846PP process.

---

## Correct Logged Issues

Review the log from running the data conversion UPGPT846PP Application Engine program in the task titled, "Completing PeopleTools Conversion." Correct the issues from the log using the instructions in the MAIN section comments of the UPGPT846PP program. These instructions were reported in the Chapter 2 task "Converting PeopleTools Objects" in the "Report Conversion Details" step.

## Run UPGPT846PP Again

In this step, you run the UPGPT846PP process again.

---

**Note.** The Application Engine process UPGPT846PP can be run repeatedly, if necessary, as you resolve data issues.

---

To run UPGPT846PP again:

1. Run the Application Engine conversion process UPGPT846PP with the upgrade User ID. The program can be run from the command line with the following:

```
$PS_HOME\bin\client\winx86\psae -CD dbname -CT dbtype -CS dbservername -CO =>
oprid -CP oprpswd -R 1 -AI UPGPT846PP
```

2. Review the log file according to the instructions in the previous step.
3. If there are any remaining issues, correct them and rerun UPGPT846PP.
4. Repeat steps 2 and 3, if necessary, until there are no remaining issues for Navigation Collections, Portal Registry objects, or Pagelet Wizard objects.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 5-4-2: Enabling Pagelet Publishing

This step enables the creation of homepage pagelets for Navigation Collections and Pagelet Wizard. The script name for your upgrade path is:

```
PTPP_PORTAL_PACK.DMS
```

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 5-5: Reviewing PeopleTools Functionality

The PeopleBooks detail the current PeopleTools functionality. There are many new features delivered in the new release that you may wish to use. You should now review the PeopleSoft Enterprise PeopleBooks and PeopleTools Installation Guide in order to configure your environment properly. This may include, but is not limited to, configuring and starting a process scheduler, report server, and reviewing portal settings.

See the Enterprise PeopleTools installation guide for your database platform on your new release.

See PeopleSoft Customer Connection (Implement Optimize + Upgrade, Upgrade Guide, Upgrade Documentation and Software, Release Notes).

- If you applied a PeopleTools patch earlier in the upgrade, review the patch documentation and run any steps that you have not already performed during the upgrade. Check your Change Assistant output directory if you do not know whether a script was already run during the upgrade process.
- PeopleTools has updated the styles that define the look of the user interface. The classic (old) style sheet, as well as two new styles, are delivered with this release of PeopleTools. PeopleTools system databases and PeopleSoft 8.4 applications use the classic style, whereas all other applications use the new dark blue style. After the PeopleTools portion of the upgrade, PeopleSoft sets the classic style as the default, but you can update to one of the new user interface styles.

See Appendix: “Changing the User Interface.”

---

**Note.** The new user interface styles are supported by Internet Explorer release 5 and above and Netscape Navigator release 6 and above. If you are using any other browser or release, the system defaults to the classic style.

---

- PeopleTools uses Verity release 5.0 to implement free text search. Verity 5.0 is not compatible with the version of Verity that was used in previous PeopleTools releases. Check the necessary application patches that may be required in order to use the new version of Verity.

See PeopleSoft Customer Connection (Updates + Fixes, Required for Install or Upgrade).

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 5-6: Preparing the Content Provider Registry

You should perform this task if you use Enterprise Portal 8.4 or higher running on PeopleTools 8.4x with full or partial navigation load access method. This means you do not use a single link to access your content provider databases, but instead you load some or all of the portal registry structures from the content provider database into your Enterprise Portal database. PeopleSoft refers to Content Provider databases as the application database(s) that contain the transaction content. Your Copy of Production database is your Content Provider database for this task.

When you upgrade a content provider database, the registry structures are updated, old registry structures are removed, and new registry structures are added. These changes need to be copied to the Enterprise Portal database by updating the portal registry structures in your Enterprise Portal database to match what is in the Content Provider database. Follow the detailed instructions in the appendix referenced below.

See Appendix: “Upgrading the Content Provider Registry.”

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 5-7: Updating the Portal Options Data

In this step you update the PeopleTools Portal Options data.

---

**Note.** Only perform this step if your upgraded database is on PeopleTools 8.46 or greater.

---

This step sets the portal options prefix and Owner ID. These values are used when creating for Pagelet Wizard definitions and Navigation Collection objects.

To set the Portal Options Prefix and Owner ID:

1. From your browser, sign on to your New Copy of Production database.
2. Select PeopleTools, Portal, Portal Utilities, System Options.
3. Update the value for the Registry Object Prefix with a 1– to 4–character prefix that is unique to your organization.

---

**Note.** Do *not* use PAPP, PAPX, PAPQ, PAPI, PRTL, EO, or PT. Do *not* use any product line specific prefix (such as CR, HC, EP, or CI). Do *not* use a blank value.

---

4. Enter the Owner ID value with your organization’s specific owner ID.

---

**Note.** The Owner ID is a translate value on the PeopleTools field OBJECTOWNERID. Do *not* use any delivered product Owner ID. If you do not have an Owner ID, then either create one, or leave the Owner ID value as a blank space.

---

5. Click Save.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | All       | All       |

## Task 5-8: Running Database Full Sync Processes

This task is applicable only for customers who have PeopleSoft HRMS and multiple job data. If you have HRMS 8.9 or higher and maintain person of interest (POI) data, you will run all of the following processes in the order listed. If you have HRMS 8.8 or do not maintain HR POI data that you want to import into ELM, you do not need to run the Person of Interest Types, Persons of Interest Data, or Person Data processes.

---

**Important!** If you do not have multiple jobs assigned to any individual, you may skip this task entirely. However, if you have effective-sequenced job data in HRMS (that is, multiple PS\_JOB rows for an individual on a single day), then skipping this task may cause data to be out of sync between HRMS and ELM. Specifically, if you skip this task and later delete a learner's job row in HRMS, that learner will no longer be viewable in ELM. Should this situation occur, the data can be restored by running the WORKFORCE\_FULLSYNC process in HRMS.

---



---

**Note.** First go to your HRMS database and publish all of the appropriate data.

---

To run the database full sync processes:

1. Select Set Up ELM, Process FullSync Data.
2. If you already have a run control ID from previously in the upgrade, use that ID in this step. Otherwise, do the following to add a new run control ID:
  - a. Select Add a New Value.
  - b. Enter a new run control ID.
3. Run the following processes in the order listed.

Make sure you select the Validate Staging Tables and Upload Data to ELM options each time. Ensure that each of the following processes has completed before you start the next one:

- a. HR Company Data.

---

**Note.** This process may be skipped if you are not using the Training Plan or French Training Law features in the new release of ELM.

---

- b. Organization Data (leave the setID fields blank to process all setIDs).

---

**Note.** This process may be skipped if you are not using the Training Plan or French Training Law features in the new release of ELM.

---

- c. Person of Interest Types.

---

**Note.** This process may be skipped if you have HRMS 8.8 or do not maintain POI data that you want to import into ELM.

---

- d. Persons of Interest Data.

---

**Note.** This process may be skipped if you have HRMS 8.8 or do not maintain POI data that you want to import into ELM.

---

- e. Person Data (leave the Employee ID fields blank to process all employee IDs).

---

**Note.** This process may be skipped if you have HRMS 8.8 or do not maintain POI data that you want to import into ELM.

---

- f. Workforce Data (leave the Employee ID fields blank to process all employee IDs).

These processes can be rerun as needed.

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 5-9: Setting Up Learning Environments

This section discusses:

- Understanding Multiple Learning Environment Set Up
- Updating Learning Administrator Roles
- Setting Up Administrator Access

### Understanding Multiple Learning Environment Set Up

If you have applied ELM 8.81 Bundle 3 (update ID #153597) or later, or ELM 8.81 Maintenance Pack 1 (MP1), then you do not need to complete this task. If you have not yet applied Bundle 3 (or later) or the maintenance pack (MP1), then you need to complete this task. This task is necessary to grant learning administrators the ability to access and work in multiple learning environments. Once the administrator signs into the application, they can switch between learning environments using a new component, Set Learning Environment.

### Task 5-9-1: Updating Learning Administrator Roles

To add the learning administrator permission list to all custom learning administrator roles:

1. Select PeopleTools, Security, Permissions and Roles, Roles.
2. Search for all administrator type custom roles; you do not need to include learner, manager, and simple ELM user roles.

---

**Note.** ELM standard roles begin with LMLELM.

---

3. For each role that is an administrator role, add the permission list: LMLELM0500.
4. Save your changes.



## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

## Task 5-9-2: Setting Up Administrator Access

To set up initial learning environment access for all administrators:

1. Run the following script:

```
uvlmup88101.DMS
```

2. After running the script, verify correct setup as follows:
  - a. Select Set Up ELM, Learning Environments.
  - b. Perform a blank search.
  - c. For each learning environment, verify the list of assigned administrators.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 5-10: Stamping the Database

In this step, you set the database to the release level of the Demo database. The values you enter here appear whenever you view the Help, About PeopleTools dialog.

To stamp the database:

1. Launch Application Designer on your Copy of Production database using the new PeopleSoft release.
2. Select Tools, Upgrade, Stamp Database...
3. Fill in all three of the PeopleSoft Release fields with the appropriate value for your product line and release number:

```
Enterprise Learning Solutions 9.00
```

4. In the Service Pack field, enter the service pack number to which you are upgrading. For example, if you are upgrading to SP2, enter the number 2. If you are upgrading to a release that is not at a service pack level, enter 0.
5. Click Stamp.
6. Close Application Designer.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |


## Task 5-11: Reviewing Change Control

Earlier in the upgrade process, in the beginning of the chapter “Apply PeopleTools Changes,” the Change Control feature was disabled. In this step, you re-enable Change Control, if your site uses this functionality.

To turn on Change Control:

1. Sign on to the Target database using Application Designer.
2. Select Tools, Change Control, Administrator.

The following dialog box appears:



Change Control Administrator dialog box

3. Set Use change control locking and Use change control history according to your site specifications.

**Note.** Move to Production: The Change Control feature slows down copy functions. The large copy projects are only executed during the initial pass, and the feature is only disabled during the initial pass. If you enable the feature at this point, it will remain enabled during future test Move to Production passes.

See “Apply PeopleTools Changes,” Turning Off Change Control.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Initial        | All      | All       | All       |

---

## Task 5-12: Backing Up Before Testing

Back up your Copy of Production database now. This enables you to restart your upgrade from this point, should you experience any database integrity problems during the remaining tasks in the upgrade process.

See Appendix: “Planning for Upgrade Testing.”

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 5-13: Testing Your Copy of Production

In this task, you test your Copy of Production. Testing your Copy of Production will ensure that you can still operate your day-to-day processes on your new release. After you have reviewed your DDDAUDIT and SYSAUDIT, verify that the system is working properly by reviewing the system online. After you are comfortable that the system is working properly, you can perform the Test Move to Production upgrade pass.

See Appendix: “Planning for Upgrade Testing.”

### Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |



## CHAPTER 6

# Apply Changes to Production Database

This chapter discusses:

- Understanding the Move to Production
- Testing the Move to Production
- Testing Once More
- Performing the Move to Production
- Completing the Upgrade Survey

---

## Understanding the Move to Production

Once you complete all of the necessary tasks to launch your system into production, you are ready to begin your Test Move to Production passes or to move your system into production.

---

## Task 6-1: Testing the Move to Production

This section discusses:

- Understanding the Move to Production Test
- Understand Move to Production
- Creating a New Change Assistant Job

## Understanding the Move to Production Test

Everything you have done to this point is the initial pass of the upgrade process. Now you are ready to start the Test Move to Production pass. The initial pass is very time consuming and requires a lot of analysis at different steps of the process and to troubleshoot issues. The Test Move to Production pass is a different series of steps, which includes a subset of the previous tasks, and takes advantage of the tasks performed during the first upgrade pass.

You should perform as many test moves to production as necessary to work out any issues and to be comfortable with the process. During each Test Move to Production you will be able to refine the process so that you can save time and avoid manual processes. These test passes will also let you know how long the process takes so you can plan your production downtime for your move to production weekend.

## Task 6-1-1: Understand Move to Production

The following text is a high level view of what you will be doing in the Move to Production test pass. The remaining steps in this task will prepare your test environment. For example, you may need to move some scripts generated in the initial pass to a new Change Assistant staging directory. Next you will create a new Change Assistant job, setting the Type of Upgrade to Move to Production. That will give you a job with steps filtered with only those steps that apply to the Move to Production (MTP) test pass. From that point forward, you will simply follow the steps as they exist in your new job.

One of those first steps will be to take a Copy of Production. This second Copy of Production is sometimes referred to as the “New Copy of Production.” The first Copy of Production, or “old” Copy of Production, will now be the source database (it was the target database in the initial test pass). The New Copy of Production is now the target database.

The steps executed in the MTP pass vary in several ways. Many of the tasks/steps in the initial test pass will be replaced in the MTP pass with Data Mover export and import scripts. In the initial pass, some steps required you to make functional decisions and take time to manually setup data. That data can be copied from the first database to the next, saving you setup time and eliminating the chance for manual error or typos.

Also, the MTP pass does not repeat the database compare/copy steps. You made the decisions once; there is no need to repeat these steps. Instead, a Data Mover script, MVPRDEXP, will export all the tables that contain the PeopleTools objects like records and PeopleCode from the first database. Another Data Mover script, MVPRDIMP, will import those tables into the second database. Anything you have done to PeopleTools objects while executing or testing the first pass—copied objects from DMO, reapplied customizations, applied updates from the PeopleSoft Customer Connection website—will be moved to the second Copy of Production with these scripts.

Another important difference with the MTP pass is the handling of SQL scripts that create and alter tables. In the initial pass, you generated the SQL scripts, sometimes edited the SQL script, and then executed the SQL scripts. In the MTP pass, you may be able to skip the generation steps and use the SQL you previously generated. This is another way to save time in your critical go-live window and is the ultimate goal, but it is an incremental process to get to that point.

In the first MTP pass, everyone must regenerate the SQL. There are small differences between the initial and MTP passes that require the SQL to be regenerated in at least one MTP pass. The Change Assistant Templates are delivered with the steps set this way.

In subsequent MTP passes, you may choose to “turn off” the generation steps if possible. If you have not changed any records at the end of one MTP pass, then you can reuse the SQL in your next pass. If you have done anything to change records, you should generate SQL again. This can include things like applying PeopleTools upgrades (for example, 8.41 to 8.42), or applying updates from the PeopleSoft Customer Connection website that involve record changes, or making additional customizations to records.

If you choose to skip some of these steps, do one of the following: mark the step complete in your job, or change the step properties in the template, so the step will never show up in your MTP filtered job again. To change the step properties, double-click on the step to open the Step Properties dialog, and change the Type of Upgrade to Initial Upgrade. In addition, copy the SQL scripts from the previous pass output directory to the new pass output directory. Change Assistant will look for the SQL scripts in the output directory set on the job’s Database Configuration, so make sure it will find them when it tries to run them.

The steps that are eligible for this treatment will contain Move To Production documentation notes indicating such.

---

**Note.** If you have made any changes to your trees, tree structures, or PS/Query objects since the upgrade began, you may want information on how to preserve those changes.

---

See Appendix: “Preserving Queries and Tree Objects.”

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

## Task 6-1-2: Creating a New Change Assistant Job

You need to create a new Change Assistant Job for each test Move to Production pass.

To create a new Change Assistant job:

1. PeopleSoft recommends that you use new output and stage directories for each new test pass. Create those directories now.
2. From Change Assistant, select Tools, Options and specify the new output and staging directories on the Change Assistant Options page.
3. Select File, Open Environment and select the environment.
4. Review the configuration on the General Settings window.

The Database Type, Language and SQL Query Executable will be the same as your previous job. Make changes to the PS\_HOME settings, if necessary, and select Next.

5. Specify the Source Database setup information and click Next.

This is the Copy of Production database from your previous pass.

6. Specify the Target Database setup information and click Next.

This is the new Copy of Production database.

7. Review the environment configuration on the Confirm Selections window and click Next to save the changes to the environment.
8. Select File, New Job.
9. Select the template on the Use Template window and click OK.
10. On the Type of Upgrade window, select Move to Production.
11. Click OK.

A new upgrade job using the naming convention of *Template\_Environment\_Move to Production* is created.

12. Highlight the job name and select Edit, Set Documentation Directory, then select the directory where the documentation is located and click OK.

If you have been using documentation printed from the filtered view on the jobs, print the documentation again. The steps for Move to Production are different than in the initial pass.

13. Select View, Documentation.
14. Select View, Expand All to display all the steps in the job that apply to your upgrade.

The job will contain steps that were not in the initial upgrade pass and will exclude some steps that were in the initial upgrade pass based on the step properties.

Now you are ready to run the job.

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 6-2: Testing Once More

As in any implementation project, you must consider planning, resources, development, and training. Testing also needs to be an integral part of your implementation project. Testing your database once more, after you have completed the upgrade, ensures that you can still operate your day-to-day processes on your new PeopleSoft release.

The level of testing in this task will focus primarily on the strategies to employ before moving into production.

See Appendix: “Planning for Upgrade Testing.”

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | Both           | All      | All       | All       |

---

## Task 6-3: Performing the Move to Production

When you are ready, you can move the system into production. Take your system out of production and perform all of the steps involved in testing the Move to Production against your production database.

See Testing the Move to Production

## Properties

| Database Orientation | Initial or MTP | Products | Platforms | Languages |
|----------------------|----------------|----------|-----------|-----------|
| Target               | MTP            | All      | All       | All       |

---

## Task 6-4: Completing the Upgrade Survey

We are interested in feedback on your upgrade experience and any thoughts and/or suggestions you have on how we can improve the process in the future. Note that this survey should only be accessed once you have completed your upgrade and are in production on the new release.



**See Also**

<http://www.peoplesoft.com/go/upgradesurvey>

**Properties**

| <b>Database Orientation</b> | <b>Initial or MTP</b> | <b>Products</b> | <b>Platforms</b> | <b>Languages</b> |
|-----------------------------|-----------------------|-----------------|------------------|------------------|
| Target                      | MTP                   | All             | All              | All              |



## CHAPTER 7

# Appendices

---

### Understanding Appendices

The appendices portion of this documentation contains information you may need for your upgrade. The appendices have been referenced throughout the upgrade documentation for further understanding of the upgrade you are performing. PeopleSoft recommends that you read each appendix as it is referenced in the documentation.



## APPENDIX A

# Applying Fixes Required for Upgrade

This appendix discusses:

- Preparing to Apply Fixes
- Applying Fixes During Installation
- Applying Fixes After Copying Project
- Applying Fixes After Data Conversion
- Applying Fixes Between Upgrade Passes
- Applying Fixes in Move to Production

---

### Task A-1: Preparing to Apply Fixes

This appendix gives general instructions for applying a Required for Upgrade fix for your upgrade. If the directions given in a particular fix are different from those given here, then follow the instructions in the fix.

It is important that you run your upgrade using the latest versions of all upgrade software. In Customer Connection, check the Upgrade page and the Updates and Fixes page to ensure that you have all of the latest code.

Ideally, you should follow the steps below to apply the various files and fixes.

To apply files and fixes:

1. Install the new release from the CD.
2. Apply any additional scripts and projects from the Customer Connection Upgrade page to your new release codeline (and to the New Release Demo database, if applicable).
3. Apply any other Required for Upgrade fixes from Customer Connection's Updates and Fixes to your new release codeline (and to the New Release Demo database, if applicable).
4. Run your initial pass of the upgrade.
5. Before you begin each subsequent upgrade pass, check the Upgrade page for new versions of any files you previously applied. Then check Updates and Fixes for any new Required for Upgrade fixes.

Your initial upgrade pass will differ from your subsequent test Move to Production passes. Some of the upgrade tasks and steps are common to both the initial upgrade pass and the Move to Production pass. For this reason, you may find Required for Upgrade fixes that do not apply to the upgrade pass that you are currently performing. The details provided with each fix will help you determine whether to apply the fix and when to apply it. The fix will also tell you what to do if you have already passed the step for which the fix is needed.

How you apply a fix depends on where you are in the upgrade process. This appendix explains how to apply a typical fix, and is organized by the various points within the upgrade where you will apply fixes.

---

## Task A-2: Applying Fixes During Installation

In the chapter, “Install the Software” of *Getting Started on Your PeopleSoft Upgrade*, you should first download and apply all files and objects from the Upgrade page on Customer Connection. Then you must download all Required for Upgrade fixes from Updates and Fixes on Customer Connection. You can use the instructions in this section to apply any additional fixes that are posted, until you reach the task, “Running New Release Compare Reports.”

If a fix contains a project that needs to be copied from a file, apply it to your New Release Demo database during installation. If the project contains changes for Records or Fields, those objects will be updated during the normal compare and copy steps in the upgrade. You will not have to build objects in the project separately or consider whether it will have impact on customizations. You will do that with the rest of the objects during the upgrade. Apply as many of the fixes as you can at this time.

To apply script fixes during installation:

1. Download Required for Upgrade Change Package(s) using the “Download Change Package” functionality in Change Assistant.
2. Use Change Assistant to install/apply the update(s) into your New Release Demo database. Review the documentation included with each update prior to applying each update. There may be manual steps that need to be performed in order to successfully apply the update.

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your current release, “Applying Updates.”

---

## Task A-3: Applying Fixes After Copying Project

It is best not to apply fixes during the Compare and Copy tasks in the “Run and Review Compare Reports” and “Apply Application Changes” chapters of the initial upgrade pass. It can also be cumbersome to apply record and field changes during the Creating and Altering of tables in the “Complete Database Changes” chapter. It is, therefore, best to wait until just before the “Running Data Conversions” task in the “Apply Application Changes” chapter to apply additional fixes. Most of the fixed objects will be data conversion code, delivered in projects.

To apply PeopleSoft project fixes before data conversion:

1. Download Required for Upgrade Change Package(s) using the “Download Change Package” functionality in Change Assistant.
2. Use Change Assistant to install/apply the update(s) into your New Release Demo database for this upgrade pass. Review the documentation included with each update prior to applying each update.

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your current release, “Applying Updates.”

3. The project is now loaded on your New Release Demo database. You should run a project compare to make sure the objects in the fix will not overwrite any of your customizations. If you find customizations, you must decide how to deal with them before you copy the fix to your Copy of Production.

4. If you are performing a Move to Production upgrade pass, first migrate the Change Package(s) into the Source database for this upgrade pass. If needed, first set up Change Assistant with the environment information for your Source Database. If you customized any of the objects delivered in the Change Package, you should repackage the fix to include your customizations. If you did not customize any objects delivered in the fix you may directly apply them to your source database.

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your current release, “Applying Updates.”

5. Migrate the Change Package(s) into the Target database for this upgrade pass. If needed, first set up Change Assistant with the environment information for your Target Database.

---

## Task A-4: Applying Fixes After Data Conversion

At this point, you have already converted all of your data for the upgrade pass, and you cannot apply Application Engine program fixes and use them in this upgrade pass. You should refer to the fix instructions to determine what to do in each case. Often, the instructions say that you need to restore your database from a pre-conversion backup and rerun data conversion to get the benefits of the fix. Since this is the only way you can get the fix onto your current Copy of Production, you may decide to allow the error and not apply the fix until you do a test Move to Production. Then after you have completed that test pass, you can test the affected function. However, you should not do this if your next pass is your final Move to Production, and you are going into production with the resulting database. You should always test your upgraded database between test passes if changes have been made to procedures, scripts, or programs. You do not want any surprises during the final Move to Production.

---

## Task A-5: Applying Fixes Between Upgrade Passes

You can apply fixes just before you start a test Move to Production pass in the same way you would in the step above, Apply Fixes After Copying Project. In those instructions, you apply the fix to your New Release Demo database and compare it to the Copy of Production. Make sure that you do the database comparison in order to verify that the fix does not wipe out any customizations you made to Application Engine programs during your initial upgrade pass. If you have made customizations, merge your customizations into the new Application Engine code on the New Release Demo database. Then apply the fix to your Copy of Production, which you will use as the Source database in the test Move to Production. The fix will then get moved to your New Copy of Production when you run the MVPRDEXP.DMS and MVPRDIMP.DMS scripts in the “Apply PeopleTools Changes” chapter.

---

## Task A-6: Applying Fixes in Move to Production

Once you have started a test Move to Production, do not apply any fixes until just before data conversion. Apply any fixes using the step above, Applying Fixes After Copying Project. In those instructions you apply the fix to your New Release Demo database and compare it to your Copy of Production. Instead of using the original Copy of Production as the Target, you must now use your New Copy of Production, the one defined as the Target in your Move to Production Change Assistant job. Be sure to do the database comparison to verify that the fix does not wipe out any customizations you made to Application Engine programs during your initial upgrade pass. If you have made customizations, merge your customizations into the new Application Engine code on the New Release Demo database, then copy the project to your New Copy of Production.



## APPENDIX B

# Changing the User Interface


This appendix discusses:

- Change the User Interface
- Change the User Interface for Mobile

## Task B-1: Change the User Interface

Three user interface options were delivered with your current release of PeopleSoft 8.x. The classic style, the style seen in previous releases of your PeopleSoft application, is set as your default style. The following are examples of the three delivered styles: classic, light blue, and dark blue.

The classic style, shown below, is set as your default style delivered with your PeopleSoft release.



The classic style user interface option

The following example represents the light blue style.

The screenshot shows the PeopleSoft web interface with a light blue theme. The top navigation bar includes links for Home, Worklist, Add to Favorites, and Sign out. A left-hand menu is expanded to show the 'Permissions & Roles' section, with 'Permission Lists' selected. The main content area displays the 'Component Interfaces' tab for 'Permission List: PTPT1200' and 'Description: PeopleTools'. A table lists several component interfaces with 'Edit' links and '+'/'-' buttons. At the bottom, there are buttons for Save, Return to Search, Next in List, Previous in List, Add, and Update/Display. The breadcrumb trail at the very bottom reads: General | Pages | PeopleTools | Process | Sign-on Times | Component Interfaces | Message Monitor | Web Libraries |

The light blue style user interface option

This example represents the dark blue style.

This screenshot shows the same PeopleSoft web interface but with a dark blue theme. The layout and content are identical to the first screenshot, including the navigation bar, left menu, main content area with the 'Component Interfaces' table, and the bottom buttons and breadcrumb trail.

The dark blue style user interface option

See Enterprise PeopleTools PeopleBook: PeopleSoft Application Designer for your new release.

To change your styles, you must delete the substyle sheets associated with the classic style and replace them with either the light or dark blue substyle sheet.

---

**Note.** The new user interface looks are supported by Internet Explorer release 5 and above and Netscape Navigator release 6 and above. If using a browser and release other than these, the system defaults to the classic style.

---


To enable one of the new user interface looks:

1. In Application Designer, open the stylesheet PSSTYLEDEF.
2. Click on the PSALTERNATE Sub Style Sheet, and press Delete.
3. Select Insert, Insert Sub Style Sheet.
4. Select PSALTERNATE\_LIGHTBLUE or PSALTERNATE\_DARKBLUE.
5. Repeat steps 1 through 4 for the PTSTYLEDEF and PSACE Sub Style Sheets, making sure to use the same extension (\_LIGHTBLUE or \_DARKBLUE) as you did for PSALTERNATE.
6. Select Save.
7. Open the stylesheet PSQUERYSTYLEDEF.
8. Click on the PTQUERYSTYLESUB Sub Style Sheet, and press Delete.
9. Select Insert, Insert Sub Style Sheet.
10. Select PTQUERYSTYLESUB\_LIGHTBLUE or PTQUERYSTYLESUB\_DARKBLUE. Use the same extension as you did in Step 4.
11. Select Save.

---

## Task B-2: Change the User Interface for Mobile

You use Related Content Projects to synchronize extraneous PeopleTools objects to a mobile device. In particular, you can use a Related Content Project to synchronize a new or customized stylesheet to the mobile device. Related Content Projects are associated with a Component Interface. PeopleSoft recommends that you associate a given Related Content Project with a synchronizable Component Interface that is common to your mobile application.



The Synchronization tab

To change the user interface look for mobile applications:

1. Follow the procedure above to add the new or customized stylesheet to a PeopleTools Project.
2. In Application Designer, open a synchronizable Component Interface that is common to your mobile application.
3. Open the Properties dialog box from the pop-up menu.
4. Select Synchronization.
5. Click Select for the Related Content Project.
6. Find and highlight the desired project and click Select.
7. Select Save.

The stylesheet will be synchronized to the mobile device during the next Bootstrap or Update Applications synchronization.

See Enterprise PeopleTools PeopleBook: PeopleSoft Component Interfaces for your new release.

See Enterprise PeopleTools PeopleBook: PeopleSoft Mobile Agent for your new release.

## APPENDIX C

# Using Data Conversion Utilities

This appendix discusses:

- Understanding Data Conversion Utilities
- Using the Upgrade Driver Program
- Using the Upgrade Drivers Page
- Reviewing the Data Conversion Report

---

## Understanding Data Conversion Utilities

This appendix contains information regarding the Application Engine program UPG\_DATACONV and the PS\_UPG\_DATACONV table.

---

## Task C-1: Using the Upgrade Driver Program

In order to run all data conversions in the correct sequence, PeopleSoft has provided the Application Engine program UPG\_DATACONV and the PS\_UPG\_DATACONV table. This program runs the Application Engine sections defined in the table PS\_UPG\_DATACONV. The PS\_UPG\_DATACONV table contains a list of all of the Application Engine sections that you need to run and in what sequence they should be run.

---

## Task C-2: Using the Upgrade Drivers Page

This section discusses:

- Understanding Upgrade Drivers Page
- Accessing the Upgrade Drivers Page
- Adding New Upgrade Drivers Section Page
- Inactivating Upgrade Drivers Section

## Understanding Upgrade Drivers Page

Before you run data conversion, you may need to change what the Upgrade Driver program runs. You can add, remove, or deactivate Application Engine sections through the Upgrade Drivers page.

You do not have an active portal on your Copy of Production during data conversion, so you need to view and update the Data Conversion Definitions on your Demo database and then copy the updated data to your Copy of Production database.

## Task C-2-1: Accessing the Upgrade Drivers Page

To access the Upgrade Drivers page:

1. From your browser, sign on to the Demo database.
2. Select Set Up ELM, Upgrade Definition.
3. Enter your upgrade path:

LM88

4. Click Search.

You are now on the Upgrade Drivers page. The following are descriptions for each section of the Upgrade Drivers page.

| Upgrade Drivers                                     |              |         |         |          |             |                           |          |   |   |
|---|--------------|---------|---------|----------|-------------|---------------------------|----------|---|---|
| Customize   Find   View All   First 1-25 of 86 Last |              |         |         |          |             |                           |          |   |   |
| Upgrade Path  | Program Name | Group # | Section | Sequence | Active Flag | Description               | Comments |   |   |
| CR80  | UPG_CDM      | 1       | CDMA010 | 10       | Active      | General Preparation       | Comments | + | - |
| CR80  | UPG_CDM      | 1       | CDMX140 | 20       | Active      | Upgrade Basic Data Tables | Comments | + | - |
| CR80  | UPG_CP       | 2       | CPA00   | 100      | Active      | Upgrade Constraint        | Comments | + | - |
| CR80  | UPG_CP       | 2       | CPA01   | 105      | Active      | Upgrade User Cd Detl      | Comments | + | - |

Upgrade Drivers page

- Upgrade Path. This field contains the upgrade path on which the section will be run.
- Program Name. This is the Application Engine program that contains the section.
- Group #. This is the group number. All sections with the same group number will be run during the same run of the UPG\_DATACONV Application Engine program.
- Section. This is the section that will be called from the UPG\_DATACONV Application Engine program.
- Sequence. This is the order in which the sections will be called during the run of UPG\_DATACONV for the group number.
- Active Flag. This field determines whether the section will be run. If the value of this field is *Active*, the section will be run. If the value is *Inactive*, it will not be run. If you need to remove a section, change the value in this field to *Inactive*.
- Description.
- Comments.

## Task C-2-2: Adding New Upgrade Drivers Section Page

Follow the instructions below to add a new section to the Upgrade Drivers page.

**Note.** To add a new section, the Application Engine program and section must exist on the Demo database.

To add a new section to the Upgrade Drivers page:

1. From your browser, sign on to the Demo database.

2. Select Set Up ELM, Upgrade Definition.
3. Select Add a New Value.
4. Click Add.
5. Enter values for Upgrade Path and Program Name.
6. Enter a value for Group #.

---

**Note.** Each group number corresponds to a data conversion step in the Change Assistant template. If you select a group number that already exists in the PS\_UPG\_DATACONV table, your section will be executed when Change Assistant runs the data conversion step that corresponds to the group number you selected. Alternatively, if you assign a group number to your new section that does not already exist in PS\_UPG\_DATACONV, you must add a new step to your Change Assistant template. The new template step will have the same properties as the other data conversion steps, except for the group number specified in the step properties Parameters box.

---

7. Enter values for Section and Sequence.  
The Description and Comments fields are optional.
8. Click Save.
9. When you have completed all changes, sign on to your Demo database using Data Mover and run the following script to export the updated data conversion data:

```
DLUPX03E.DMS
```

10. Sign on to your Copy of Production database using Data Mover and run the following script to load the updated data conversion data:

```
DLUPX03I.DMS
```

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your new release, Appendix: "Using a Change Assistant Template."

## Task C-2-3: Inactivating Upgrade Drivers Section

Follow the instructions below to deactivate a section on the Upgrade Drivers page. Once deactivated, the section will not run as part of data conversion.

To inactivate a section on the Upgrade Drivers page:

1. From your browser, sign on to the Demo database.
2. Select Set Up ELM, Upgrade Definition.
3. Enter your upgrade path:  
  
LM88
4. Click Search.
5. Find the row with the Program Name and Section you want to remove and change the value of the Active Flag field to *Inactive*.
6. Click Save.
7. When you have completed all changes, sign on to your Demo database using Data Mover and run the following script to export the updated data conversion data:

DLUPX03E.DMS

8. Sign on to your Copy of Production database using Data Mover and run the following script to load the updated data conversion data:

DLUPX03I.DMS

---

## Task C-3: Reviewing the Data Conversion Report

Each of the upgrade data conversion sections contains comments that describe the processing performed by the section. PeopleSoft has delivered an SQR to list all of these comments by the group and sequence numbers that determine how they run. The name of this report is UDATAACNV.

To run UDATAACNV:

1. Using SQRW, run SQR UDATAACNV on your Copy of Production database.
2. When prompted for Upgrade Path, enter:

LM88

3. When prompted for Group Number, enter the two-digit group number to report on, or enter 0 to see the comments for all groups.



## APPENDIX D

# Improving Performance

This appendix discusses:

- Understanding Performance Improvement
- Planning Your Upgrade for Performance
- Performing the Upgrade
- Improving Performance for Your Platform
- Consulting the Global Support Center

---

## Understanding Performance Improvement

Performance is always a challenge when you are upgrading. Much of the data currently in your database will be affected. No other batch processing works quite like it. Upgrade performance is sensitive to your unique environment and data. These performance recommendations are designed to help you improve performance during your upgrade.

---

## Task D-1: Planning Your Upgrade for Performance

Review the following guidelines to help plan for better upgrade performance:

- Provide as much hardware, memory, and disk space as you can.
- Run long processes on a dedicated server, not the client. Configure that server similarly to your production environment.
- Size the Copy of Production database (Target) like your production database — allow for growth.
- Use a dedicated workstation, configured like the production environment.
- Provide an application server and process scheduler for the Target database on the new PeopleSoft release.
- Look for fragmented tables. Resize or reorganize the initial and next extends accordingly.
- Know which tables are your largest. This information will be valuable during the upgrade.

---

## Task D-2: Performing the Upgrade

This section discusses:

- Verifying the Database Structure Task
- Creating and Altering SQL Scripts
- Performing Data Conversion

### Task D-2-1: Verifying the Database Structure Task

When performing the “Modifying the Database Structure” task, perform all recommended update statistics, so the optimizer can make a good decision.

### Task D-2-2: Creating and Altering SQL Scripts

The following list provides tips to use when performing the “Modifying the Database Structure” task.

- Perform all recommended update statistics, so the optimizer can make a good decision.
- Look for large tables that are being altered. Create separate scripts for each of these tables and run the script concurrently with your other alter scripts. You can run these concurrently even if you are using the Alter by Rename build option because each table creation uses an independent temporary table name in the new PeopleSoft release (*PSYrecname*).
- Run your create table script concurrently with the alter tables without deletes script.
- Some indexes will not create during alter without deletes because of a unique key violation. You can expect this because index structures have changed. The data in these indexes will be corrected during data conversion. You can create the index as a non-unique key for data conversion. Create this non-unique index, without the field that caused the error, so that data conversion does not have to update the index as well as the data pages as it corrects the data in this field.

### Task D-2-3: Performing Data Conversion

PeopleSoft delivers the Change Assistant templates to run the steps on the client by default. The server can run Application Engine programs. You may want to run these programs on the server to increase performance. Change Assistant uses the PSEMHUB and PSEMAgent to execute jobs to the server. You will need to configure and start your Environment Management Hub and Agent, enter the Environment Management information into the Change Assistant options, set your Change Assistant mode, check the Perform Server Processing check box, and modify the run location of the steps you wish to run on the server. Consider running data conversion application engine programs concurrently as they were designed with no dependencies between programs. Any exceptions to this are noted in the documentation. If you would like to take advantage of concurrent processing, modify the step properties and set the Run Concurrently option to Yes.

See Enterprise PeopleTools PeopleBook: PeopleSoft Software Updates for your new release.

---

## Task D-3: Improving Performance for Your Platform

This section discusses:

- Using Oracle
- Using DB2

## Task D-3-1: Using Oracle

You should use the cost-based optimizer during the upgrade. The application engine scripts use MetaSQL to run the update statistics command at various times during data conversion. If you are running the rule-based optimizer, you will not take advantage of these statements.

When running the alter scripts, remember the Oracle hint `/*APPEND*/`. This command will improve the performance of your alter script if you are doing an “Alter by Rename.” This hint performs like an Oracle Direct Load Insert and does not capture redo or recovery information. The syntax is as follows:

```
INSERT /*+ APPEND */ INTO TABLENAME (FIELD1, FIELD2, ...
```

Make sure your database administrator has turned autoextend on. Autoextend allows tablespaces to grow larger than their set maximum size and will be useful during the upgrade process since tablespaces grow several times larger than they would in production.

Alter the tablespace for PSIMAGE and increase it to 200 MB; autoextend on the next 10 MB; set the maxsize to *unlimited*.

## Task D-3-2: Using DB2

Perform all recommended update statistics on the system catalog as well as the application tablespaces.

Interspersed throughout the Application Engine data conversion programs are steps that make a dynamic call for RUNSTATS to be performed against selected tables. An example of how this is used follows:

- Step01 - Start with an empty Temp\_Table\_TAO.
- Step02 - INSERT 60,000 rows into the Temp\_Table\_TAO.
- Step03 - Application Engine Step calls %UpdateStats(Temp\_Table\_TAO).
- Step04 - You can now perform SQL against Temp\_Table\_TAO using new statistics.

This will allow you to use indexes when processing against Temp\_Table\_TAO. If DB2 z/OS is not configured correctly, Application Engine programs skip these steps and the performance of the SQL steps that follow will suffer.

In order to take advantage of the %UpdateStats feature, at least one of these conditions must be met:

- You implemented the DSNUTILS stored procedure.
- You followed the enhanced installation path.

See Enterprise PeopleTools Installation for DB2 UDB for z/OS for your new release.

---

**Note.** If you disable the %UpdateStats feature of Application Engine, it will adversely affect the performance of your data conversion programs, because statistics will not update when the tables are loaded with large volumes of data.

---

---

## Task D-4: Consulting the Global Support Center

If you do have a problem with your upgrade, contact the Global Support Center (GSC). PeopleSoft will be able to give you a solution to the problem faster if you supply the following information:

- Include details about the table row counts and indexes available on the tables involved in the processing:
  - Include indexes in your physical database, not those defined in Application Designer.
  - Mention any additional indexes that you custom-added; they could be getting in the way.
- Include RDBMS (Oracle, SQL Server, or DB2, and so on) and RDBMS release (for example, Oracle 7.3 or 8.16).
- If you are running on Oracle, specify whether you are running in cost-based or rule-based mode.
- Include the PeopleSoft upgrade path for both PeopleTools and the application.
- Provide trace files: PeopleTools trace and RDBMS-specific trace files, SQL explains, and so on.

## APPENDIX E

# Preserving Queries and Tree Objects

This appendix discusses:

- Preserving Queries and Trees
- Preparing the Database
- Creating a New Project
- Comparing the New Project
- Copying the Project
- Testing the Project
- ReExporting the PeopleTools Tables

---

## Task E-1: Preserving Queries and Trees

This appendix contains information for preserving queries, trees, and tree structures. At the beginning of your upgrade, you should have informed your end-users and development team that your PeopleSoft system was frozen, meaning that no changes should have been made to any PeopleTools tables or objects including queries, trees, and tree structures. The freeze on PeopleTools changes is important because you will lose any changes to these objects made during an upgrade to PeopleTools tables. Occasionally, however, end-users may have to make critical changes to trees, tree structures, and PS/Query objects. If this has happened in your system, you can perform a process to preserve those additions and changes to trees, tree structures, and queries. You will have to work with your end-users and developers to obtain a list of queries, trees, and tree structures that you need to preserve.

You will run through the test Move to Production steps several times for practice and testing purposes. Please note that you have the option to perform the preserving queries and trees procedure during each of your test Move to Production runs, but you must perform it during the last run of the test Move to Production. If you do not perform this procedure during your last run in order to preserve the trees, tree structures, and queries that have been changed since the beginning of your upgrade, they will be lost.

---

**Note.** The process outlined in this appendix to preserve trees and queries should be performed prior to data conversion so that any additional conversion would be taken care of by the appropriate data conversion programs.

---

This appendix includes instructions to prepare your database and create a project on which to preserve your queries, trees, and tree structure changes.

---

## Task E-2: Preparing the Database

In this step, you create a new copy of your current production database, perform steps on the new copy, and run scripts against the new copy to update the release level.

To prepare the database:

1. At the beginning of the test Move to Production, you should make a new copy of your current production database. To preserve queries and trees, you need to make not only that Copy of Production but also an additional copy of your current production database. For clarity, PeopleSoft refers to this additional copy of your production database as the Tree/Query Copy of Production database. So now you should have a Copy of Production database and a Tree/Query Copy of Production database.
2. Perform the test Move to Production on your Copy of Production database.
3. To obtain the queries and trees that you want to preserve, the Tree/Query Copy of Production database needs to be at the same release level as the Copy of Production database on which you just completed the test Move to Production. To update your Tree/Query Copy of Production to the same release, you run release scripts against this database. PeopleSoft refers to this as “reling up” the database. Use the Custom Compare template to “rel up” your database. Select the Product Line *PEOPLETOOLS* when configuring your Change Assistant job.

---

## Task E-3: Creating a New Project

Now that your Tree/Query Copy of Production is at the same release as your Copy of Production database, you create a project in the Tree/Query Copy of Production that contains all of the queries and trees that you wish to preserve.

To create a new project:

1. Using PeopleTools 8.4x, sign on to the Tree/Query Copy of Production using a valid PeopleSoft User ID and launch Application Designer.
2. Select File, New...
3. Select *Project* for Object Type.
4. Select File, Save Project and enter a project name; for example, *PRESERVED*.
5. Select the Upgrade tab in Application Designer.

---

**Note.** Queries and trees do not appear in projects under the Development tab in Application Designer. To see the queries and trees that you will insert into the *PRESERVED* project in the next step, you must make sure that you are using the Upgrade view of Application Designer.

---

6. Select Insert, Definitions into Project...
7. Select Queries from the Definition Type drop-down list box and click Insert.
8. Using your list of identified queries that need to be preserved, highlight each one of those queries from the Application Designer list.

You can highlight more than one by holding down the Control (CTRL) key while you click the name of the query.

9. After you have highlighted all of the queries that you want to preserve, click Insert, then click Close.  
Under the PRESERVED project name in the Upgrade view of Application Designer, you will see Queries as an object type in the project.
10. Double-click on queries under the PRESERVED project to see a listing of all of the queries to preserve in the right-hand window of Application Designer.
11. Select File, Save Project.
12. Repeat steps 6 through 11 for trees and tree structures.  
Now your PRESERVED project should contain all of the queries, trees, and tree structures that you want to preserve.

---

## Task E-4: Comparing the New Project

In this step, you compare the queries, trees, and tree structures that are in your PRESERVED project against your Copy of Production database. Because the tree objects in your PRESERVED project are not comparable objects in Application Designer, you must manually compare the tree objects that you want to preserve. During the query and tree structure compare process, the Application Upgrade utility sets the project flags. These flags determine whether the following actions will occur:

- Changes will be performed on the Copy of Production (Target) database when you perform the export and copy.
- Changes will be tagged as *Copy* or *Delete* operations.
- The project flags will be set to automatically take these actions or not.

These settings are determined based on whether or not the objects in the project currently exist on the Copy of Production (Target) database.

To compare the new project:

1. Using PeopleTools 8.4x, sign on to the Tree/Query Copy of Production using a valid PeopleSoft User ID and launch Application Designer.
2. Select File, Open...
3. For Definition, select Project and click Open to display the list of projects.
4. Select the PRESERVED project and click Open.
5. Select Tools, Compare and Report.
6. Sign on to your Copy of Production.
7. From the Object Type box, select *Queries and Tree Structures*.
8. Click Options...
9. Select *PeopleSoft Vanilla* for the Target Orientation.
10. Select *Project* for the Compare Type.
11. Verify that the Compare Report output directory is set to the correct location.
12. Select the Report Filter tab and set the report filter check boxes appropriately for your compare.
13. Click OK.

14. Select Compare.
15. Review the compare reports for queries and tree structures. In addition, perform a manual compare of the trees that you want to preserve. Based on the results of this review, set the Action and Upgrade check box appropriately in the PRESERVED project.

---

## Task E-5: Copying the Project

In the following steps, you copy the PRESERVED project to the target database. This is the Copy of Production database on which you ran the test Move to Production.

To copy the project:

1. Using PeopleTools 8.4x, sign on to the Tree/Query Copy of Production using a valid PeopleSoft User ID and launch Application Designer.
2. Select File, Open...
3. For Definition, select *Project* and click Open to display the list of projects.
4. Select the PRESERVED project and click Open.
5. Select Tools, Upgrade, Copy.
6. Sign on to your Copy of Production database.
7. Make sure that the Reset Done Flags and Copy Project check boxes are selected.
8. Click the Select All button.
9. Click the Copy button.
10. Using the Upgrade view of the PRESERVED project in Application Designer, review the Done flags in the project to make sure that all of the objects that you wanted to preserve were copied to the Target database.

---

## Task E-6: Testing the Project

Now that the queries, trees, and tree structures that you wanted to preserve are in the Copy of Production database, you must test and re-test and make any necessary changes if the test results are not what you expected.

---

## Task E-7: ReExporting the PeopleTools Tables

Once you are satisfied with the test results, you must re-export the PeopleTools tables in order to actually preserve the queries, trees, and tree structures. During your test Move to Production, you ran MVPRDEXP.DMS in order to export the PeopleTools tables. You will use the output files created from running this job as input files during your Move to Production. Because these files were created before copying the queries, trees, and tree structures that you wanted to preserve, the files do not contain the preserved objects, so you must run the MVPRDEXP.DMS script again. Running the MVPRDEXP.DMS script again ensures that you have the most current PeopleTools tables.

To re-export the PeopleTools tables:



1. As a PeopleSoft user, launch Data Mover against your Copy of Production database and run the following script:

`\PS_HOME\SCRIPTS\MVPRDEXP.DMS`

2. Use the output files created during your final Move to Production.



## APPENDIX F

# Planning for Upgrade Testing

This appendix discusses:

- Understanding Testing Techniques
- Deciding When to Test
- Evaluating Your Testing Requirements
- Defining Your Testing Strategy
- Determining the Testing Conditions
- Developing Your Test Plan
- Developing Test Scripts
- Reviewing Tips and Techniques

---

## Understanding Testing Techniques

As with any project, testing is a critical part of your upgrade project. With proper testing, you can ensure that you upgrade successfully and you are ready for your Move to Production.

Upgrades vary in complexity and scale from release to release and customer to customer, so the testing periods and the activities required to perform testing vary from upgrade to upgrade. Because PeopleSoft cannot anticipate how every organization uses the system to fit their own business practices, including customizations and data setup, PeopleSoft does not deliver upgrade test scripts. However, there are some general testing guidelines that you can follow to assist with your upgrade testing. In this section, you will find information that will help you plan your testing efforts.

---

## Task F-1: Deciding When to Test

An effective testing strategy involves an understanding of the stages of a PeopleSoft upgrade and where, within these stages, testing should be performed. You can take more than one approach and use more than one method to test your upgrade.

---

## Task F-2: Evaluating Your Testing Requirements

To evaluate your testing requirements, you need the following information:

- The number of products and modules you currently have in your production database.
- The number of customizations you have in your production database.
- The functional design and business requirements addressed by each customization.
- Your online, batch, and reporting business processes that you want to include in testing.

---

## Task F-3: Defining Your Testing Strategy

This section discusses:

- Understanding Your Testing Strategy
- Evaluating Unit Testing
- Evaluating System Testing
- Evaluating Integration Testing
- Evaluating Parallel Testing
- Evaluating Performance Testing
- Evaluating User Acceptance Testing
- Evaluating Regression Testing

### Understanding Your Testing Strategy

Once you evaluate your testing requirements, you can determine what types of testing you need. You should define the tests to be performed for the project and the goals of each test—including roles and responsibilities, test-case management, control points, and success criteria. In addition, you should define and document the scope of each type of testing. Use the definitions below to determine the levels of testing required in your organization.

To ensure upgrade success, be sure to train upgrade members before the upgrade. It is critical to have educated testers to ensure adequate test coverage of new functionality.

### Task F-3-1: Evaluating Unit Testing

In this stage of testing, you have completed your upgrade tasks and your database is now at the new release level. However, you should unit test before you use the new system. Unit testing validates data, business rules, and business process requirements. In addition, it ensures that business processes work as designed and your database is ready for full functionality testing. The processes for performing unit testing are described below:

- Test individual online transactions and batch processes on the upgraded database.
- Validate data converted during the upgrade.
- Verify that you can access existing data and enter new data successfully.

- Test customizations reapplied to the upgraded database.
- Each customization is tested individually along with all related processes.
- Business processes are not tested.
- Test scripts are not required.
- Test – Document – Resolve issues – Retest.

## Task F-3-2: Evaluating System Testing

System testing ensures that all business functions and processes execute appropriately from the customer's view. Business processes are tested from beginning to end during system testing; this is sometimes referred to as end-to-end testing. The processes for performing system testing are described below:

- Create system test environment via a test Move to Production.
- Test inbound and outbound interfaces and related business processes.
- Test online business processes using relevant security (i.e., user IDs, roles, and permission lists).
- Test batch business processes.
- Test reporting processes (SQR, PS/Query, nVision, and Crystal).
- Test customizations to business processes.
- Perform using test scripts.
- Compare expected results to actual results.
- Test – Document – Resolve issues – Retest – Document – Sign off.

## Task F-3-3: Evaluating Integration Testing

After system testing, you perform integration testing. In this stage, you test business processes and groups of related business processes within the application to determine that they function as designed. In addition, you ensure that any design flaws are resolved before user testing. The following list of activities describes integration testing:

- Create integration test environment via a test Move to Production.
- Test specific business processes.
- Test integration between modules and business processes.
- Perform using test scripts.
- Compare expected results to actual results.
- Test – Document – Resolve issues – Retest – Document – Sign off.

## Task F-3-4: Evaluating Parallel Testing

Parallel testing validates that the current production system and the upgraded database generate the expected results for specific business events. Parallel testing is optional, but frequently used to ensure that the new release will generate the same results given the same testing scenarios. The processes for performing parallel testing are described below:

- Create a parallel test environment via a test Move to Production. The Copy of Production should be taken before the major business processes/events are executed so that the same processes can be run during the parallel test.
- Retain any output from production processes for later comparison.
- Run the same business processes/events in the upgraded database.
- Compare results generated in the production system with the results generated using the upgraded database.
- Perform using test scripts.
- Test – Document – Resolve issues – Retest – Document – Sign off.

## **Task F-3-5: Evaluating Performance Testing**

You conduct performance testing to determine if the system can accomplish stated objectives within a specified time period. Performance of the current production system is often used as a baseline. The processes for performing performance testing are described below:

- Define performance objectives for each business process included in the scope of the test.
- Perform business process.
- Monitor performance.
- Compare actual performance and acceptance criteria.
- Perform using test scripts.
- Test – Document – Resolve issues – Retest – Document – Sign off.

## **Task F-3-6: Evaluating User Acceptance Testing**

User acceptance testing determines if day-to-day users can complete daily work activities within the system with an acceptable level of effort. For example, run through business processes such as hiring, terminating, and paying an employee in Human Resources or creating, editing, and posting journals in Financials. The processes for performing user acceptance testing are described below:

- Functional resources should execute test scenarios (with their appropriate production security access to ensure they have access to all the components, pages, and processes used in their daily functions).
- Perform using test scripts.
- User testing should not be performed with developer or Super User access.
- Test – Document – Resolve issues – Retest – Test – Document – Sign off.

## **Task F-3-7: Evaluating Regression Testing**

You perform regression, or re-testing, if problems were found and resolved or changes were made during any of the previous tests. This stage of testing validates the test Move to Production and Move to Production parts of the upgrade. When all the tests have received sign-off, you will use the initial Copy of Production to upgrade the production database/environment. You then perform a test move into the production environment and customers confirm that the test move executed successfully. At this point you conduct regression testing. The following tips will assist you with regression testing:

- Ensure that no new defects have been introduced during the move.
- Execute a predefined set of scripts to confirm the test move.

- Performed by Functional Resources before *Go Live*.
- Rerun scripts from previous testing.

---

## Task F-4: Determining the Testing Conditions

After you identify the types of testing to include in your upgrade, determine conditions for each stage of testing. Be sure to test the actual test Move to Production to resolve any technical issues in the upgrade process itself in addition to performing functional application testing. Perform the following actions for each testing type:

- Determine criteria for successful completion.
- Determine which tests you can run concurrently and which you must run serially.
- Set up test plans and test scripts you will need.
- Define the testing environment.
- Define issue resolution procedures.
- Define change control and migration procedures.
- Define which third-party tools you must install and configure.
- Identify database maintenance procedures, for example, backup and refresh.
- Evaluate the need for a testing tool to aid in the testing process.

---

## Task F-5: Developing Your Test Plan

If you have test plans from your implementation or previous upgrades, consider modifying them for this upgrade project, ensuring that you incorporate features and functions delivered with the new release. Use existing test plans and scripts wherever possible. Identify modifications during the fit/gap analysis and complete script generation during the initial upgrade. Based on the objectives and scope defined in your test strategy, identify the following items for each type of testing:

- Test procedures
- Assumptions
- Timing
- Deliverables
- Acceptance criteria
- Roles and responsibilities
- Resource requirements
- Training requirements
- Test environment
- Data requirements
- Issue and change control tracking procedures

- Testing Tools

---

## Task F-6: Developing Test Scripts

The process of developing test scripts can assist with detecting problems in the requirements or design of an application. It requires thinking through the entire operation of the application. For this reason, you may find it useful to start preparing test scripts early in the upgrade cycle and, if possible, base them on existing test scripts from your implementation project or previous upgrade.

If you have test scripts from your original implementation, recycle them and modify them to accommodate new functionality. That way, you can be sure to cover your critical end-to-end business processes. You will also want to focus additional testing time on your customizations to verify that they have upgraded successfully.

If you do not have test scripts from your implementation, you can create them by documenting what you currently do within the system.

Create a test script for each business process to define the Action or Event, Input, and the expected result to determine if a feature of an application is working correctly. Functional people who are aware of current processes should write your test scripts. However, when writing test scripts, assume the person testing does not know how to use the system. Use the following procedure for developing test scripts:

- Test scripts should contain specifics, such as test identifier, test name, objective, test conditions and setup, input data requirements, steps, and expected results.
- Write as a step-by-step guide, stating what data should be entered, when, and where.
- Organize by module, business process, and process cycles.
- Create with full production security in mind.
- Create early in the upgrade process.

Make sure that your tests are consistent with the following tips:

- Action
  - Include the script name, description, and purpose.
  - Include the navigation steps in PeopleSoft.
  - Include navigation steps outside of PeopleSoft.
- Input
  - Include security requirements: what User ID, Role, and Permission List should be used to perform the test.
  - Specify key data elements: entering new or accessing existing data.
- Results
  - Include the exact results.
  - Print screens to support the results and print the report output.



---

## Task F-7: Reviewing Tips and Techniques

This section discusses:

- Reducing the Time of Upgrade Process
- Performing Testing on Up to Date Data
- Performing Test Move to Production
- Tracking Issues
- Reviewing Testing Tools
- Discussing Change Control
- Discussing Back Up Procedures
- Evaluating Unexpected Results
- Evaluating Reasons for Failure

### Task F-7-1: Reducing the Time of Upgrade Process

All testing can be performed at the end, including running the tests on the current system to obtain results for comparison. One way to reduce the overall timeframe of an upgrade is to execute the tests on the current system while the upgrade is in progress. This way you will have the results ready when the upgraded database is to be tested. This can be achieved by taking two copies of the production database at the start of the upgrade. Only one copy is upgraded, while the other remains at current release. The testing time is now reduced to only performing the tests on one database.

After each test Move to Production, you may want to turn over the upgraded database to the testing team while the technical team begins a new iteration of the test Move to Production. Conducting the two efforts in parallel may decrease the overall time required to upgrade. Any issues that are found by the testing team can be incorporated into the newly upgraded database as soon as it is available.

One approach that may be used for the Move to Production is to run the production database and upgraded database in parallel to ensure that key business processes operate as expected. Although this may require dual maintenance of data during the parallel testing period, it may minimize the impact of the actual Move to Production. If you are interested in using this method, once you have performed a test Move to Production to your satisfaction, schedule the production cutover weekend. Then, perform the next test Move to Production during that weekend. Bring the existing production system back up and run the upgraded database concurrently. If, after comparing the outcome of your critical business processes, you are satisfied with the results, simply set the upgraded database to your production system. If you are not satisfied with the results, make the necessary adjustments and perform another test Move to Production.

### Task F-7-2: Performing Testing on Up to Date Data

The previous technique will mean that testing is performed on *old* data. The copies of production may have been taken some weeks or months in the past. It will confirm that the data you started with has upgraded successfully. However, it may be required to perform the tests on the most recent data set as follows:

- Take a copy of production and upgrade
- Perform all phases of testing on the upgrade version up to unit testing
- Determine that the database is ready for full functionality testing

## Task F-7-3: Performing Test Move to Production

Performing a test Move to Production is a good technique for assuring database readiness as follows:

- Take two up to date copies of the production database.
- Perform the test Move to Production steps to upgrade one of the databases.
- Execute test scripts on the remaining database.
- Perform tests on the upgraded database and compare results.

## Task F-7-4: Tracking Issues

You should implement a method for tracking the tests and issues discovered during testing. Tracking issues and resolutions on a central document serves as a communication tool and minimizes duplication effort. The following tips should be considered while tracking issues:

- Categorize issues:  
Critical, Major, Minor, Cosmetic
- Use a central document repository or tracking tool

## Task F-7-5: Reviewing Testing Tools

SQA Robot :

- Records key strokes (like a macro recorder) into Visual Basic scripts.
- Useful for regression testing.
- SQA Manager—can be used to simulate multiple users.

Test Director by Mercury/Interactive:

- Tool that manages test scripts—tracks execution and defects.
- Useful for regression testing.

## Task F-7-6: Discussing Change Control

Make sure that you have a procedure for implementing changes during the testing stage. You may have several databases, if server space permits. All changes should be made in a master database. If an issue is found during testing, the resolution should be applied to the master database and promoted via pre-defined migration procedures. Remember that a master database will also be required to perform the Move to Production.

## Task F-7-7: Discussing Back Up Procedures

The following tips should be considered when backing up your data:

- Back up at baseline before testing (use a backup technique that will allow you to restore individual tables).
- Back up at key points for point in time testing.
- Implement refresh procedures to avoid duplicate data.

## **Task F-7-8: Evaluating Unexpected Results**

In the event you receive unexpected results and you cannot determine their cause, attempt to replicate any issues you encounter in your Copy of Production database on a delivered Demo database. If the issue does occur on Demo, it should be reported to the Global Support Center. Check PeopleSoft Customer Connection to see if a fix has been posted to resolve the issue.

See PeopleSoft Customer Connection (Updates + Fixes).

## **Task F-7-9: Evaluating Reasons for Failure**

The list below identifies reasons why your test plan might have failed:

- Testing strategy was poorly defined
- Test plans were poorly defined
- Test scripts were poorly defined
- Lack of resources and resource commitment
- Lack of understanding of the upgrade process



## APPENDIX G

# Using the Comparison Process

This appendix discusses:

- Understanding the Comparison Process
- Understanding Upgrade Compare Reports

---

## Task G-1: Understanding the Comparison Process

This section discusses:

- Reviewing Source and Target Columns
- Reviewing the Action Column
- Reviewing the Upgrade Column
- Putting it All Together

During the upgrade you run a compare process and then review the resulting reports. The compare process first compares every property of an object definition on the New Release Demo database to the properties of object definitions on the Copy of Production database. PeopleSoft tracks object changes using the contents of the PSRELEASE table, and the value of two fields, LASTUPDDTTM and LASTUPDOPRID, used in the PeopleTools tables.

- The PSRELEASE table maintains the Comparison Release Level. This table contains rows of data for every release level at which the database has ever existed. The first column in this table, RELEASEDTTM, contains a date/time stamp identifying when each release level was “stamped.” The second column, RELEASELABEL, identifies the release level. The format of a release label is *M XX.XX.XX.YYY*, where *M* is the market code, *XX* is an integer from 0 to 99, and *YYY* is an integer from 0 to 999. A release label has two parts: the PeopleSoft release number (*M XX.XX.XX*) and the customer release number (*YYY*). Each time you customize your production database, you can stamp it with a new customer release level to help you track your changes over time. You should not change any portion of the PeopleSoft release number unless specifically instructed to do so.
- The LASTUPDDTTM field in our *PSobjectDEFN* tables—such as PSRECDEFN, PSPNLDEFN, and so on—stores a date/time stamp of when each object was last modified.
- The LASTUPDOPRID field stores the operator ID of the user who made the modification. If PeopleSoft made the modification, the proprietary ID *PPLSOFT* is used.

---

**Note.** Maintain Security prevents you from creating an operator named PPLSOFT.

---

If an object definition is defined differently in the New Release Demo database than in the Copy of Production, the compare process will check to see whether either object definition has changed since the comparison release. If the object’s LASTUPDDTTM value is greater than the RELEASEDTTM

value for the comparison release level (stored in PSRELEASE), the object has changed. If the object's LASTUPDDTTM value is equal to or less than RELEASEDTTM, the object has not changed (since the comparison release). Whether the compared object has changed or not, if it has *ever* been changed prior to the comparison release by someone other than PeopleSoft (LASTUPDOPRID  $\neq$  'PPLSOFT'), the object is identified as a customization.

After you run a compare report, you see the following information when you open an object type in the upgrade project from the Upgrade Tab of Application Designer. This is called the Application Designer Upgrade Definition window.

## Task G-1-1: Reviewing Source and Target Columns

The status of each object is reported as it appears on the New Release Demo database (Source) and the Copy of Production database (Target). The following table explains the various status types:

| Status Type | Definition   |
|-------------|--|
| Unknown     | The object has not been compared. This is the default status for all objects inserted manually into a project and the permanent status of all non-comparison objects.  |
| Absent      | The object was found in the other database, but not in this one. When upgrading to a new PeopleSoft release, all of our new objects should have Absent status in the target database and all of your new objects should have Absent status in the source database.       |
| Changed     | The object has been compared, its LASTUPDOPRID value is <i>PPLSOFT</i> , and its LASTUPDTIME value is greater than the date/time stamp of the comparison release database. In other words, PeopleSoft modified the object since the comparison release.                  |
| Unchanged   | The object has been compared, its LASTUPDOPRID value is <i>PPLSOFT</i> , and its LASTUPDTIME value is less than or equal to the date/time stamp of the comparison release database. In other words, PeopleSoft last modified the object prior to the comparison release. |
| *Changed    | The object has been compared, its LASTUPDOPRID value is not <i>PPLSOFT</i> , and its LASTUPDTIME value is greater than the date/time stamp of the comparison release database. In this case, the customer has modified the object since the comparison release.          |

| Status Type | Definition   |
|-------------|--|
| *Unchanged  | The object has been compared, its LASTUPDOPRID value is not <i>PPLSOFT</i> , and its LASTUPDTIME value is less than or equal to the date/time stamp of the comparison release database. In this case, the customer last modified the object prior to the comparison release.   |
| Same        | The object has been compared and is defined as the same in both databases. When an object in one database has this status, so will its counterpart in the other database. This status would never be seen when performing a database comparison because in that case, the project is only populated with objects defined differently. However, it can occur when performing a project comparison because in a project comparison, the project contents are static; the project is not repopulated based on the comparison results. |

## Task G-1-2: Reviewing the Action Column

The default actions for each object that you compared are reported in the Action column. The compare sets the action column based on what you need to do to make the Copy of Production database consistent with the source. You should not change these actions. You can decide whether or not to accept each action by setting the Upgrade value. Action types include:

| Action Type                         | Definition                                     |
|-------------------------------------|--|
| Copy                                | Object will be added to the Demo Database      |
| Copy Prop (Records and Fields only) | Object will be added to the Demo database      |
| Delete                              | Object will be deleted from the Demo database. |
| None                                | No action will be taken on this object.        |

PeopleSoft assigns one of these action types to every object in a comparison project and in the compare reports. However, these actions are not necessarily carried out during the copy process. The value of the Upgrade column for each object makes that determination.

## Task G-1-3: Reviewing the Upgrade Column

The Upgrade values for each object – Yes or NO – determine whether the object action will be carried out during the copy process. The upgrade orientation you assign during the compare process determines these settings. You can orient the Upgrade to keep PeopleSoft changes or to retain your changes in the Copy of Production. Whichever orientation you choose, you will still have the option to set each Upgrade value individually before launching the copy process.

You may find that after the compare process, your project contains objects that show up as Unchanged on the Demo database and Changed on the Copy of Production and the Upgrade column is not checked. What this status combination means is that the PeopleSoft object on your Copy of Production was changed more recently than on the Demo database. In these instances, PeopleSoft recommends that you accept the Demo database version of the object.

## Task G-1-4: Putting it All Together

The following chart summarizes every possible Status, Action, and Upgrade value that could be set by the compare process to a single object:

| Source Status | Target Status          | Action | PeopleSoft Vanilla | Keep Customizations |
|---------------|------------------------|--------|--------------------|---------------------|
| (Any)         | Absent                 | COPY   | YES                | YES                 |
| Absent        | Changed or Unchanged   | DELETE | YES                | YES                 |
|               | Changed* or Unchanged* | DELETE | NO                 | NO                  |
| Changed       | Changed or Unchanged   | COPY   | YES                | YES                 |
|               | Changed* or Unchanged* | COPY   | YES                | NO                  |
| Unchanged     | Changed                | COPY   | NO                 | NO                  |
|               | Unchanged              | COPY   | YES                | YES                 |
|               | Changed* or Unchanged* | COPY   | YES                | NO                  |
| Changed*      | Changed or Unchanged   | COPY   | NO                 | YES                 |
|               | Changed* or Unchanged* | COPY   | YES                | YES                 |
| Unchanged*    | Changed or Unchanged   | COPY   | NO                 | YES                 |
|               | Changed*               | COPY   | NO                 | NO                  |
|               | Unchanged*             | COPY   | YES                | YES                 |

---

## Task G-2: Understanding Upgrade Compare Reports

This section discusses:

- Reviewing Report Columns
- Using Reports

When you run the compare process, it creates reports to help you understand what objects differ between the Source and Target databases, and how they differ. If you have documentation of your database modifications, you should retrieve it before reviewing these reports. This will help you understand how the Target objects



have changed and enable you to better compare the Target version of the object with the Source version. If you are upgrading to a new PeopleSoft release, you should also review the Release Notes for your product. These notes will identify and explain object changes in the Source database.

Upgrade reports can be a little intimidating at first glance, until you understand what data you are looking for and how best to use it. This section includes the following topics:

- Report columns
- Using reports

## Task G-2-1: Reviewing Report Columns

For the most part, the columns in upgrade reports correspond with the columns you see in Application Designer's upgrade definition window. Moving from left to right, you see the Name of the object, then other key columns that vary by object type, then the Source and Target status, the Action value and Upgrade flag (*Yes* or *No*).

After these columns are three more that are not included in Application Designer. The first is Attribute. This tells you the type of difference that was found between the two objects. For example, record field Attribute values include *Use/Edit*, which identifies key or audit differences, and Default Field Name (*Def. Fldnm*), which identifies differences in a default value. Lastly, there is a Source column and a Target column. These wide columns display the actual differences between the object definitions. For example, on a *Use/Edit* attribute recfield difference, the Source column might contain *Xlat Table Edit* while the Target column is empty. This means the Source record field has a translate table edit while the Target record field does not.

If you are unsure of the meaning of any value in the last three report columns, open the PeopleTool that edits the particular object. The values in these columns correspond directly to dialog options in the tool.

## Task G-2-2: Using Reports

PeopleSoft delivers several cross-reference reports that you can run to provide information about the inter-relationships between various objects. PeopleSoft delivers these reports in the form of SQRs (found in PS\_HOME\SQR), Crystal Reports (found in PS\_HOME\CRW\ENG), and Queries.

The cross-reference reports include:

| Object Type(s)                           | Report Name | Report Description  |
|--|-------------|---|
| Applications and Fields                  | XRFAPFL     | Lists all application windows, such as General Tables, in alphabetical order, as well as the fields within each window. For each field, the report details the Field Name, Field Type, Length, and Format, as well as all the record and page definitions that contain the field (within the window). |
| Fields Referenced by PeopleCode Programs | XRFFLPC     | Lists all PeopleCode programs in alphabetical order by associated record definition/field. The report includes type of field and lists all fields referenced in the PeopleCode program.   |

| Object Type(s)                           | Report Name | Report Description  |
|--|-------------|---|
| Fields and Panels                        | XRFFLPN     | Lists all fields in alphabetical order. The report includes the names of all record and page definitions in which each field is used, as well as the Long Name of each field.   |
| Records and Fields                       | XRFFLRC     | Lists all fields in alphabetical order. The report details the Long Name, Field Type, Field Length, and Formatting specified for the field, and includes the names of all record definitions that contain the field.                        |
| Field Listing                            | XRFIELDS    | Lists all fields in alphabetical order. The report includes Field Type, Length, Format, Long Name and Short Name.   |
| Menu Listing                             | XRFMENU     | Lists application windows in alphabetical order. The report details all menus within each window, and all page definitions within each menu. It also includes the associated search record definition name and detail page definition name. |
| Panel Listing                            | XRFPANEL    | Lists all page definitions in alphabetical order.   |
| PeopleCode Programs and Field References | XRFPCL      | Lists record definitions that contain fields with PeopleCode program attributes. The report includes the Field Name, as well as the associated record definitions and fields referenced in the PeopleCode program.                          |
| Panels with PeopleCode                   | XRFPNPC     | Lists all pages that contain fields with PeopleCode attributes. For each page, the report includes the name of the record definition(s) that contain the field as well as the Field Name and Type.  |
| Fields and Records                       | XRFRCL      | Lists all fields in alphabetical order by associated record definition name. The report details the Long Name, Field Type, Field Length, and Formatting specified for the field.  |

| Object Type(s)     | Report Name | Report Description  |
|--------------------|-------------|---|
| Records and Panels | XRFRCPN     | Lists all record definitions in alphabetical order. The report includes the menu and page definitions associated with each record definition. |
| Window Listing     | XRFWIN      | Lists all application windows in alphabetical order.  |

In addition to using our standard cross-reference reports, you can also generate ad hoc reports to extract the exact combination of information you need. Or, you can create permanent custom reports for information you extract on a regular basis.

PeopleSoft recommends that you mark your upgrade reports using a color-coding system to help you quickly identify what you need to do to certain objects.

If you have several people reviewing sections of the reports, a good documentation policy is to have everyone on your review cycle initial and date the action defaults and overrides they select.

You may also find it easier to change some objects manually after the upgrade, rather than copying the new versions from the source.



## APPENDIX H

# Upgrading the Content Provider Registry

This appendix discusses:

- Understanding the Content Provider Registry Upgrade
- Copying Your Enterprise Portal Database
- Upgrading Enterprise Portal PeopleTools
- Updating Registry Permission Lists
- Creating the Portal Project
- Comparing the Portal Project
- Reviewing the Portal Project
- Copying the Portal Project
- Copying Portal Project to Production
- Deleting Obsolete Folders
- Updating Registry Folder Permissions

---

## Understanding the Content Provider Registry Upgrade

You should perform this task if you use the Enterprise Portal 8.4 or higher running on PeopleTools 8.4x with the full navigation load access method. This means you do not use a single link to access your content provider database, but instead load some or all of the portal registry structures from the content provider database into your Enterprise Portal database. PeopleSoft refers to its application databases that contain the transaction content as Content Provider databases. Your Copy of Production database is your Content Provider database for this task.

When you upgrade a content provider database, the registry structures are updated, removed and added. These changes need to be copied to the Enterprise Portal database. This task will update the portal registry structures in your Enterprise Portal database to match what is in the Content Provider database. This is accomplished by the following:

- Upgrade the PeopleTools on a copy of the Enterprise Portal database. This allows a project compare to run between the Enterprise Portal and the Content Provider database.
- Create a portal project in the Enterprise Portal database containing all of the existing Content Provider registry structures. Copy the portal project (definition only) to the Content Provider database.
- Create a portal project in the Content Provider database containing all of the current Content Provider registry structures, then merge the project definition copied from the Enterprise Portal database into this

project. You will have a complete list of all registry structures for the Content Provider, including what is current and what should be deleted.

- Compare the complete list of registry structures in the Content Provider database to what exists in the Enterprise Portal, via project compare. This marks the missing registry structures as delete and the updated or added registry structures as copy in the portal project definition.
- Copy the portal project from the Content Provider database to the Enterprise Portal database. This deleted, updates, and adds registry structures to the Enterprise Portal database which syncs it up with what is current in the Content Provider database.

If you use Enterprise Portal 8 SP2, PeopleSoft recommends you upgrade your Enterprise Portal to the latest available release. If you do upgrade your Enterprise Portal database, you must be on PeopleTools 8.46 or higher.

---

**Note.** If you use Enterprise Portal 8.4 you *do not* need to upgrade to Enterprise Portal 8.8. You can still upgrade to PeopleTools 8.46.

---

*Enterprise Portal 8.1x – Managing Information Architecture* contains additional information on this topic.

See PeopleSoft Customer Connection (Support, Documentation, Documentation Updates, Enterprise, Portal Products, Enterprise Portal).

In this appendix, you load your new Portal Registry definitions from your Copy of Production database to a copy of your Enterprise Portal database.

---

**Note.** You must complete the tasks in the appendix for each of your separately installed Enterprise Portal databases that correspond to one of the four Portal Registry definitions: EMPLOYEE, CUSTOMER, SUPPLIER, and PARTNER. If your installed Enterprise Portal uses all the registries, then complete this task for each of the portal registries using the same copy of the single Enterprise Portal database.

---

In the first task of this appendix, you create a copy of your Enterprise Portal database. You use this copy for all subsequent steps for the initial and test Move to Production upgrade passes. For the final Move to Production, do not make a copy, instead perform the steps on the production Enterprise Portal database.

This document uses the term “target Enterprise Portal database” to refer to the Enterprise Portal database used in the upgrade steps. Use the table below to determine the correct copy of your Enterprise Portal database for each pass.

| Upgrade Pass             | Target Enterprise Portal Database      |
|--------------------------|--|
| Initial pass             | Copy of the Enterprise Portal database |
| Test Move to Production  | Copy of the Enterprise Portal database |
| Final Move to Production | Enterprise Portal production database  |

---

## Task H-1: Copying Your Enterprise Portal Database

You initially upgrade the Content Provider registry on a copy of your Enterprise Portal database, then test the results of the upgrade. During your test Move to Production, you perform this task against another Copy of the Enterprise Portal.

Create a copy of your current Enterprise Portal production database now. Use this database as your target Enterprise Portal database.

---

**Note.** During your final Move to Production, you copy the registry definitions directly to your Enterprise Portal production database. Therefore, you do not need to execute this step during your final Move to Production.

---

---

## Task H-2: Upgrading Enterprise Portal PeopleTools

During the initial upgrade pass, your Enterprise Portal database must run on the same PeopleTools release level as your Copy of Production database so that you can do the compare step. Since you do not need to run the compare step during your Move to Production passes, you can skip this task during Move to Production passes.

If the release level of PeopleTools on your target Enterprise Portal database is not the same as your Copy Production database release level, upgrade your PeopleTools now.

See PeopleSoft Customer Connection (Implement Optimize + Upgrade, Upgrade Guide, Upgrade Documentation and Software, Upgrade Documentation and Scripts, Release, Enterprise, PeopleTools).

---

## Task H-3: Updating Registry Permission Lists

This section discusses:

- Understanding Registry Permission Lists Updates
- Updating Portal Registry
- Deleting the Database Cache

### Understanding Registry Permission Lists Updates

This task applies only to the initial upgrade pass.

Earlier in this upgrade you copied portal registry data from the Demo database to your Copy of Production database. You must update this registry data to include your permission list changes. After updating the portal registry permission lists, delete the database cache.

This process takes between a few minutes and a few hours, depending on the volume of the portal data.

---

**Note.** The user ID that invokes this process must have the security role Portal Administrator, or the process may terminate with an abend.

---

---

**Note.** You must have a process scheduler started for your Copy of Production database.

---

### Task H-3-1: Updating Portal Registry

Follow the steps below to update your portal registry permission lists.

To update the portal registry permission lists:

1. On your Copy of Production database, select PeopleTools, Portal, Portal Security Sync.

2. Select the Add a New Value tab.
3. Add a run control as follows:
  - a. Enter a value for the Run Control ID. The Run Control ID is *SECURITY\_SYNC\_XXXX*, where *XXXX* represents the portal registry name (EMPLOYEE, CUSTOMER, SUPPLIER, or PARTNER).
  - b. Click Add.
4. Enter a value for the Portal Name. This value must match the portal registry name you used to replace the *XXXX* in the run control ID.
5. Click Save.
6. Click Run.
7. Set up the process scheduler information and click OK.
8. Click the Process Monitor link to view the progress of the process.

## Task H-3-2: Deleting the Database Cache

Follow the steps below to delete the database cache.

To delete the database cache:

1. Delete the Copy of Production database application server cache.
2. Stop and restart the Copy of Production database web server service.

---

## Task H-4: Creating the Portal Project

This section discusses:

- Understanding Portal Project Creation
- Creating the Target Enterprise Portal Project
- Cleaning the Target Enterprise Portal Project
- Deleting the Target Enterprise Portal Database Cache
- Copying the Target Enterprise Portal Project Definition
- Creating the Copy of Production Portal Project
- Cleaning the Copy of Production Portal Project
- Deleting the Copy of Production Database Cache

## Understanding Portal Project Creation

This task applies only to the initial upgrade pass. In this task, you create and modify a project on your target Enterprise Portal database. Then you copy the project definition to the Copy of Production database, where you further modify the project.




## Task H-4-1: Creating the Target Enterprise Portal Project

Follow the steps below to create the target Enterprise Portal project.

To create the target Enterprise Portal project:

1. Launch Application Designer and sign on to your target Enterprise Portal database.
2. Select Insert, Definitions into Project...
3. Select the following values:
  - a. For Definition Type, select *Portal Registry Structures*.
  - b. Leave the Portal Name field blank.
  - c. For Owner ID, select *All Owners*.
  - d. Do not select any values for Related Definitions.



Insert into Project dialog box

4. Click Insert.
5. Click Select All, and then click Insert again.
6. Click Close.
7. From Application Designer, select File, Save Project As....
8. Enter the project name *PORTAL\_PA84X\_REGISTRY*.
9. Close Application Designer.

## Task H-4-2: Cleaning the Target Enterprise Portal Project

In this step, you clean the target Enterprise Portal Project so that it contains only the existing Content Provider registry structure content references.

To clean the target Enterprise Portal project:

1. In your Enterprise Portal database, select PeopleTools, Portal, Portal Utilities, Clean Portal Project.

---

**Warning!** Do not follow the instructions on the Clean Portal Project page. Instead, follow the instructions below.

---

2. Add the run control ID `CLEAN_PORTAL_XXXXXXXX` where `XXXXXXXX` represents the portal definition name: `EMPLOYEE`, `CUSTOMER`, `SUPPLIER` or `PARTNER` for example.
3. In the Project Name field, enter the project name `PORTAL_PA84X_REGISTRY`.
4. Enter a value in the Portal Name field; `EMPLOYEE` for example.
5. Enter a value in the Content Provider Name field; `CRM` for example.

---

**Note.** Before running the Clean Portal Project you must enter the Node URI text for the Message Node you selected.

---

6. Select Full Navigation.
7. Click Save.
8. Click Run.
9. Set up the Process Scheduler information and click OK.
10. Select the Process Monitor link to view the progress of the process.

## Task H-4-3: Deleting the Target Enterprise Portal Database Cache

In this step, you delete the target Enterprise Portal database cache.

To delete the target Enterprise Portal database cache:

1. On your target Enterprise Portal database, launch Configuration Manager.
2. On the Startup tab, click Purge Cache Directories...
3. Select the target Enterprise Portal database name.
4. Click Delete.
5. Click OK.
6. Click Close.
7. Click OK to close Configuration Manager.

## Task H-4-4: Copying the Target Enterprise Portal Project Definition

In this step, you copy the target Enterprise Portal project definition to your Copy of Production database.

To copy the target Enterprise Portal project definition:

1. Using PeopleSoft Data Mover, sign on to your target Enterprise Portal database.
2. Run the following Data Mover script:

```
PS_HOME\SCRIPTS\UVUPX10E.dms
```

3. Close Data Mover.
4. Using PeopleSoft Data Mover, sign on to the Copy of Production database.
5. Run the following Data Mover script:

```
PS_HOME\SCRIPTS\UVUPX10I.dms
```


6. Close Data Mover.

## Task H-4-5: Creating the Copy of Production Portal Project

Create a project containing all Portal Registry data on your Copy of Production database.

To create the Copy of Production Portal project:


1. Launch Application Designer and sign on to your Copy of Production database.
2. Select Insert, Definitions into Project....
3. For Definition Type, select *Permission Lists*.



Insert into Project dialog box: Definition Type Permission Lists

4. Click Insert.
5. Click Select All, and then click Insert again.
6. Select the following values:

- a. For Definition Type, select *Portal Registry Definitions*.
- b. For Name, enter the Enterprise Portal database's default portal name (EMPLOYEE, CUSTOMER, SUPPLIER or PARTNER).
- c. For Owner ID, select *All Owners*.
- d. For Related Definitions, select *Portal Registry Structures*.



Insert into Project dialog box with Portal Registry Structures selected

7. Click Insert.
8. Click Select All, then click Insert again.
9. Click Close.
10. From Application Designer, select File, Save Project As....
11. Enter the appropriate new project name from the table below. This project is referred to as the Portal Project.

| Portal Name | Project Name           |
|-------------|------------------------|
| EMPLOYEE    | PORTAL_APP84X_EMPLOYEE |
| CUSTOMER    | PORTAL_APP84X_CUSTOMER |
| PARTNER     | PORTAL_APP84X_PARTNER  |
| SUPPLIER    | PORTAL_APP84X_SUPPLIER |

12. Click OK.
13. From Application Designer, select File, Merge Projects...

14. Enter the Project Name *PORTAL\_PA84X\_REGISTRY*.

This merges the objects from the *PORTAL\_PA84XREGISTRY* project into your newly created Portal Project.

15. Select File, Save Project to save the updated Portal Project.
16. Close Application Designer.

## Task H-4-6: Cleaning the Copy of Production Portal Project

In this step, you clean the Copy of Production Portal project so that it contains only the Content Provider registry data.

---

**Important!** Before using the Copy of Production Portal project, you must run the Clean Portal Project on the Copy of Production database. Follow the directions on the Clean Portal Project Page.

---

To clean the Copy of Production Portal project:

1. In your Copy of Production database, select PeopleTools, Portal, Portal Utilities, Clean Portal Project.
2. Add the run control ID, *CLEAN\_PORTAL\_XXXXXXXX*, where *XXXXXXXX* represents the portal definition name; *EMPLOYEE*, *CUSTOMER*, *SUPPLIER*, or *PARTNER*, for example.
3. In the Project Name field, enter the Portal Project name you created in the Creating the Copy of Production Portal Project step (*PORTAL\_APP84X\_[your portal name here]*).
4. Enter a value in the Portal Name field; *EMPLOYEE*, for example.
5. Enter a value in the Content Provider Name field; *CRM*, for example.

---

**Important!** Before running the Clean Portal Project, you must enter the Node URI text for the Message Node you selected.

---

6. Select Full Navigation.
7. Click Save.
8. Click Run.
9. Set up the Process Scheduler information and click OK.
10. Select the Process Monitor link to view the progress of the process.

## Task H-4-7: Deleting the Copy of Production Database Cache

In this step, you delete the Copy of Production database cache.

To delete the Copy of Production database cache:

1. On your Copy of Production database, start Configuration Manager.
2. On the Startup tab, click Purge Cache Directories...
3. Select the Copy of Production database name.
4. Click Delete.
5. Click OK.
6. Click Close.

7. Click OK to close Configuration Manager.

---

## Task H-5: Comparing the Portal Project

This task only applies to the initial upgrade pass.

In this step, you compare the Portal project you created in the previous step and then review the compare results. This will allow you to adjust the portal project as necessary before copying it into the Enterprise Portal database.

To compare the Portal Project:

1. Launch Application Designer and sign on to your Copy of Production database.
2. Select Tools, Compare and Report....
3. Enter the Portal Project name you specified in the step “Creating the Copy of Production Portal Project” (PORTAL\_APP84X\_[your portal name here])..
4. Enter the database name of your target Enterprise Portal database, and the user ID and password.
5. Click the Options button.
6. For the Compare Type, select *Project*, and click OK.
7. Select all object types and click OK.
8. Close Application Designer.

---

## Task H-6: Reviewing the Portal Project

This task applies only to the initial upgrade pass.

Review the Portal project (PORTAL\_APP84X\_[your portal name here]) on the Copy of Production database, looking for customizations that you have applied to your database. Object definitions that you changed have *\*Changed* or *\*Unchanged* in the Target column of the compare report. The \* indicates that the change was not made by PeopleSoft. Review each of these objects carefully. If PeopleSoft delivered the object, the Source column of the report will read *Changed*. Note the changes you made to the object. After you complete the upgrade, when you test the system, you can decide whether you still need the customization. You can reapply the customization at that time.

See Appendix: “Using the Comparison Process.”

---

## Task H-7: Copying the Portal Project

This section discusses:

- Understanding Portal Project Copying
- Copying the Portal Project

- Deleting the Enterprise Portal Database Cache

## Understanding Portal Project Copying

This task only applies to the initial upgrade pass.

In this step, you copy the project from your Copy of Production database to your target Enterprise Portal database.

### Task H-7-1: Copying the Portal Project

Follow the steps below to copy the Portal Project to the Enterprise Portal database.

---

**Important!** Before exporting the Portal Project from the Content Provider database, you must successfully clean the Copy of Production Portal Project. If you proceed with this step without cleaning the project, you will overwrite critical Enterprise Portal data.

---

See Creating the Portal Project, Cleaning the Copy of Production Portal Project.

To copy the Portal Project:

1. Launch Application Designer and sign on to your Copy of Production database.
2. Select File, Open...
3. For the Definition, select *Project* and click Open.
4. Highlight the newly created Portal Project name (PORTAL\_APP84X\_[your portal name]) and click Open again.
5. Select Tools, Copy Project, To Database...
6. Enter the name of your target Enterprise Portal database, and the user ID and password.
7. Click Select All.
8. Click Copy.  
This may take a few minutes.
9. Close Application Designer.

---

**Note.** You do not need to create or alter any records or views.

---

### Task H-7-2: Deleting the Enterprise Portal Database Cache

In this step, you delete the Enterprise Portal database cache.

To delete the Enterprise Portal database cache:

1. Delete the target Enterprise Portal database application server cache.
2. Stop and restart the target Enterprise Portal database web server service.

---

## Task H-8: Copying Portal Project to Production

This section discusses:

- Understanding Portal Project to Production Copying
- Copying the Portal Project to File
- Copying the Portal Project From File
- Deleting the Enterprise Portal Database Cache Again

### Understanding Portal Project to Production Copying

You must perform this step during both your test and final Move to Production upgrade passes.

#### Task H-8-1: Copying the Portal Project to File

Follow the steps below to copy the Portal Project to file.

---

**Note.** If your Copy of Production and target Enterprise Portal databases run on the same PeopleTools release and database platform, you can copy the project directly to the target Enterprise Portal database from within the Copy of Production Application Designer and skip the rest of this step.

---

To copy the Portal Project to file:

1. Launch Application Designer and sign on to your Copy Production database.
2. Select File, Open....
3. For the Definition, select *Project*. Click Open.
4. Highlight the newly created Portal Project name (PORTAL\_APP84X\_[your portal name]) and click Open again.
5. Select Tools, Copy Project, To File....
6. Click the Browse button for the Export Directory. Select a temporary directory. Click OK.
7. Click Select All.
8. Click Copy.

This may take a few minutes.

9. Close Application Designer.

#### Task H-8-2: Copying the Portal Project From File

In this step, you copy the Portal project from file.

To copy the Portal project from file:

1. Launch Application Designer and sign on to your target Enterprise Portal database.
2. Select Tools, Copy Project, From File....
3. Browse to the Copy of Production database server's temporary directory.



If you cannot access the Copy of Production database server's temporary directory, then copy the portal project folder and files from the temporary directory to the target Enterprise Portal database server's *PS\_HOME\PROJECTS* directory, and browse to that directory.

4. Select the Portal project name you just copied to file in the previous step.
5. Click Open.
6. Click Select All.
7. Set the project language options as follows:
  - a. Click Options...
  - b. In the Copy Options tab, select *English*, and *COMMON*.
  - c. If your Enterprise Portal database is a multi-language database, then also select the languages you have installed on your Enterprise Portal database.
  - d. Click OK.
8. Click Copy.
9. Select the Upgrade tab and view the Output window.

All objects should have copied successfully.
10. Close Application Designer.

---

**Note.** After the copy, you do not need to create or alter any records or views on the target Enterprise Portal database.

---

## Task H-8-3: Deleting the Enterprise Portal Database Cache Again

In this step, you delete the Enterprise Portal database cache.

To delete the Enterprise Portal database cache:

1. Delete the target Enterprise Portal database's application server cache.
2. Stop and restart the target Enterprise Portal database web server service.

---

## Task H-9: Deleting Obsolete Folders

This section discusses:

- Understanding Obsolete Folder Deletion
- Deleting Obsolete Folders on Enterprise Portal 8.4
- Deleting Obsolete Folders on Enterprise Portal 8.8

### Understanding Obsolete Folder Deletion

This task applies to all upgrade passes: Initial, Test Move to Production, and Final Move to Production.

In this step, you delete folders on your target Enterprise Portal database that the Portal Registry Structures no longer reference. The process you run depends on your version of Enterprise Portal.

## Task H-9-1: Deleting Obsolete Folders on Enterprise Portal 8.4

Follow this procedure to delete obsolete folders on Enterprise Portal 8.4.

To delete obsolete folders on Enterprise Portal 8.4:

1. Using PeopleSoft Data Mover, sign on to your target Enterprise Portal database.
2. Run the following Data Mover script, located in the Enterprise Portal PS\_HOME\SCRIPTS directory:

```
PORTAL_REG_FOLDER_DEL.DMS
```

3. Close Data Mover.

## Task H-9-2: Deleting Obsolete Folders on Enterprise Portal 8.8

Follow this procedure to delete obsolete folders on Enterprise Portal 8.8 or higher.

To delete obsolete folders on Enterprise Portal 8.8 or higher:

1. On your target Enterprise Portal database, navigate accordingly:
  - a. For Enterprise Portal 8.8: Portal Administration, Navigation, Run Folder Cleanup.
  - b. For Enterprise Portal 8.9 or higher: Portal Administration, Navigation, Delete Empty Folders.
2. Add a run control as follows:
  - a. Enter a value for Run Control ID. The run control ID is *FOLDER\_CLEAN\_XXXX*, where *XXXX* represents the portal registry name (EMPLOYEE, CUSTOMER, PARTNER, or SUPPLIER).
  - b. Click Add.
3. Enter a value for Portal Name. This value must match the portal registry name you used to replace *XXXX* in the run control ID (EMPLOYEE, CUSTOMER, PARTNER, or SUPPLIER).
4. Click Save.
5. Click Run.
6. Set up the process scheduler information and click OK.
7. Click the Process Monitor link to view the progress of the process.

---

## Task H-10: Updating Registry Folder Permissions

This section discusses:

- Understanding Registry Folder Permissions Updates
- Updating the Enterprise Portal Registry Folder Permissions
- Deleting the Enterprise Portal Cache

### Understanding Registry Folder Permissions Updates

This task applies to all upgrade passes: Initial, Test Move to Production, and Final Move to Production.

Portal data from different Content Provider databases may share a common portal folder. After copying the registry projects, you must update the folder permissions to reflect the changes. After you update the folder permissions, you must delete the target Enterprise Portal database cache files to propagate the changes.

## Task H-10-1: Updating the Enterprise Portal Registry Folder Permissions

Follow this procedure to update your Enterprise Portal registry folder permissions.

---

**Note.** This process will take between a few minutes to a few hours, depending on the volume of portal data. The user ID that invokes this process must have the security role Portal Administrator, or the process may terminate with an abend.

---

To update the Enterprise Portal folder permissions:

1. On your target Enterprise Portal database, select PeopleTools, Portal, Portal Security Sync.
2. Add a run control as follows:
  - a. Enter a value for Run Control ID. The run control ID is *SECURITY\_SYNC\_XXXX*, where *XXXX* represents the portal registry name (EMPLOYEE, CUSTOMER, PARTNER, or SUPPLIER).
  - b. Click Add.
3. Enter a value for Portal Name. This value must match the portal registry name you used to replace *XXXX* in the run control ID (EMPLOYEE, CUSTOMER, PARTNER, or SUPPLIER).
4. Click Save.
5. Click Run.
6. Set up the process scheduler information and click OK.
7. Click the Process Monitor link to view the progress of the process.

## Task H-10-2: Deleting the Enterprise Portal Cache

In this step delete the Enterprise Portal cache.

To delete the Enterprise Portal cache:

1. Delete the target Enterprise Portal database application server cache.
2. Stop and restart the target Enterprise Portal database web server service.



# Index

## A

- AE SYNCIDGEN, running 101
- ALLTABS project, creating 81
- ALLTEMPTABS project, creating 80
- Alter Audit
  - final, reviewing 110
  - final, running 110
  - initial, running 10
- alter tables script, running 83
- alter with deletes script
  - building 100
  - running 101
- application changes
  - preparing 63
- Application Engine driver program,
  - using 145
- application messages
  - exporting 90
  - importing 90
- application servers
  - configuring 96, 114
  - granting administrator permissions 26
  - updating Ren servers 58
- application system data
  - exporting 106
  - importing 106
- application tablespaces, creating 50
- application upgrade, preparing 22
- applying
  - fixes after copying project 138
  - fixes after data conversion 139
  - fixes between upgrade passes 139
  - fixes during installation 138
  - fixes during Move to Production 140
  - updates before data conversion 95
  - UPGOPT project 5
  - upgrade planning files 4
- approval process definitions, creating 12
- approval process seed data, importing 94
- approvals, pending
  - processing 11
- audits
  - Alter Audit 10
  - DDDAUDIT 8, 109
  - final 108

- initial 8, 10
- SYSAUDIT 9, 109

## B

- backing up
  - after data conversion 99
  - after PeopleTools upgrade 62
  - after preparing your database 24
  - after upgrade copy 78
  - before conversion 96
  - before testing 127
  - Current Release Demo database 16
  - demo databases 16
  - new release demo again 74
  - New Release Demo database 17
- base data, loading 55
- building
  - alter with deletes script 100
  - tablespace alter script 54
  - UPGOPT project 5
  - upgrade views 88

## C

- Change Assistant
  - creating new job 131
  - editing multilingual step properties 34
- change control
  - reviewing 126
  - turning off 41
- compare options, modifying 65
- compare reports
  - columns 173
  - modifying options 17
  - reviewing 67
  - understanding 172
  - using 173
- comparing
  - customizations 17
  - new release 64
  - running UPGCUST 19
- comparison process
  - default actions for objects 171
  - settings for objects 172
  - status of objects 170
  - Upgrade column 171

- completing
  - data conversion 119
- completing system setup
  - exporting data 103–104
  - exporting EDI statements 103
  - exporting mass change data 104
  - importing data 103, 105
  - importing EDI statements 103
  - importing mass change data 104
  - loading data 102
- Configuration Manager profile,
  - updating 27
- configuring
  - application servers 96, 114
  - Portal 114
  - Process Scheduler 96
  - upgrade environment 113
- connect ID, granting privileges to 36
- connector passwords, encrypting 60
- contacting global support 152
- Content Provider registry
  - upgrading 121
- content reference permissions,
  - synchronizing 117
- conversion
  - loading data 60
  - reporting details 61
  - running data conversion 61
- converting
  - PeopleTools objects 58
  - Portal objects 59
  - query prompt headings 60
- Copy of Production
  - creating 3
  - testing 127
- Copy of Production database
  - backing up 62
- Copy of Production database cache,
  - deleting 180
- copying
  - Enterprise Portal database 178
  - PATCH84X project 48
  - PATCH84XML project 49
  - PPLTLS84CUR project 45
  - PPLTLS84CURDEL project 48
  - PPLTLS84CURML project 46
  - PPLTLSML project 47
  - production database 3
  - projects 45
  - PT84TBLSPC project 53
  - RecField definitions 22
  - UPGCUST 70
  - UPGNONCOMP 73
- create and alter scripts
  - building 81
  - editing 82
- create indexes script, running 101
- create tables script
  - running 83
- create temp tables script
  - building 81
  - running 82
- create triggers script, running 101
- create upgrade tables script
  - building 80
- CREATEVW, running 102
- creating
  - all views 102
  - ALLTABS project 81
  - ALLTEMPTABS project 80
  - application tablespaces 50
  - approval process definitions 12
  - custom tablespaces 77
  - FNLALTAUD project 109
  - indexes 83
  - INITALTAUD project 9
  - new Change Assistant job 131
  - new tablespaces 76
  - PeopleSoft-delivered tablespaces 76
  - PPLTOOLS views 61
  - RUNSTATS.DAT 39
  - target Enterprise Portal project 181
  - temporary performance indexes 38
  - updated PeopleTools views 61
  - upgrade views 87
  - upgrade views project 87
- currency codes, loading 57
- Current Release Demo database
  - backing up 16
  - restoring 20
- customizations
  - comparing 17
  - identifying 20
  - reapplying 115
- customized objects
  - adjusting 115
- customizing
  - new release 70

**D**

- data
  - base data, loading 55
  - conversion data, loading 60
  - data conversion, running 61
  - English currency codes, loading 57
  - English messages, loading 56
  - English string data, loading 57
  - exporting objectives data 24
  - importing approval process seed data 94
  - language data, loading 56
  - MCF data, populating 59
  - PeopleTools data, loading 56
  - stored statements data, loading 57
- data conversion
  - applying updates before 95
  - backing up after 99
  - loading data 89
  - loading data for PeopleTools 60
  - reporting details 61
  - running for application changes 96
  - running for group 1 99
  - running for PeopleTools changes 61
  - understanding 97
  - using utilities 145
- data conversion driver data
  - exporting 93
  - importing 94
- data conversion report 148
- data conversion, completing 119
- data model definitions, loading
  - DB2 UNIX/NT 42
  - DB2 z/OS 41
  - Informix 42
  - Oracle 42
  - SQL Server 42
  - Sybase 43
  - understanding 41
- database
  - increasing space 4
- database cache
  - deleting from Copy of Production 180
- database full sync processes, running 123
- database servers, backing up 62
- database structure
  - finalizing 100
  - modifying 79
- databases
  - backing up 62
  - Copy of Production 62
  - New Copy of Production 32
  - preparing for the upgrade 13
  - production 13
  - stamping 125
  - updating overrides 74
  - verifying integrity 14
- DB2
  - editing upgrade planning scripts 7
- DB2 UNIX RUNSTATS script, generating 85
- DB2 UNIX/NT
  - loading data model definitions 42
  - rerunning RUNSTATS 39
  - updating statistics 40
- DB2 z/OS
  - backing up database 79
  - editing create table scripts 31
  - editing MTP import scripts 32
  - loading data model definitions 41
  - updating statistics 39
- DB2TMPIDXCREATE script 38
- DBTSFIX output scripts
  - editing 29
  - running 36
- DBTSFIX script, running 28
- DDDAUDIT script
  - final, running 109
  - initial, running 8
- DDLDB2 script
  - editing 33
  - running 41
- DDLDBX script
  - editing 33
  - running 42
- DDLIFX script
  - editing 34
  - running 42
- DDLMS script, running 42
- DDLORA script
  - editing 33
  - running 42
- DDLSYB script, running 43
- deleting
  - Copy of Production database cache 180
  - Pagelet Wizard Common Components data 22
- developing
  - test plan 163

test scripts 164  
 dropping PeopleTools tables 14

## E

EDI tables, identifying 20  
 editing  
   DB2 z/OS create table scripts 31  
   DB2 z/OS MTP import scripts 32  
   DBTSFIX output scripts 29  
   DDLDB2 script 33  
   DDLDBX script 33  
   DDLIFX script 34  
   DDLORA script 33  
   GRANT script 30  
   Move to Production import scripts 32  
   MSGTLSUPG script 34  
   multilingual step properties 34  
   MVPRDIMP script 32  
   PeopleTools swap script 23  
   PPLTLS84CURTABLES script 52  
   PSLANGUAGES script 30  
   PTxxxTLS scripts 30  
   system data swap script 23  
   tablespace alter script 54  
   TLSUPGNONCOMP script 30  
   upgrade planning DB2 scripts 7  
 encrypting connector passwords 60  
 Enterprise Portal  
   copying database 178  
   upgrading PeopleTools 179  
 Enterprise Portal project, target  
   creating 181  
 environments, *See* learning environments  
 exporting  
   application messages 90  
   application system data 106  
   data conversion driver data 93  
   new release objects 73  
   objectives data 24  
   Pagelet Wizard application data 92  
   Pagelet Wizard data 93  
   PATCH84X project 48  
   PATCH84XML project 49  
   PeopleTools system tables 38  
   PPLTLS84CUR project 45  
   PPLTLS84CURDEL project 48  
   PPLTLS84CURML project 46  
   PPLTLSML project 47  
   project definitions 63  
   projects 45

PT84TBLSPC project 53  
 record groups 90  
 related language system data 105  
 selected PeopleTools tables 71  
 setup data 106  
 system setup data 92  
 upgrade views project 88

## F

file servers  
   editing PTxxxTLS scripts 30  
 final audit reports, running 108  
 fixes  
   applying after copying project 138  
   applying after data conversion 139  
   applying between upgrade passes 139  
   applying during installation 138  
   applying during Move to  
     Production 140  
 FNLALTAUD project, creating 109

## G

generating  
   DB2 UNIX RUNSTATS script 85  
   PPLTLS84CURTABLES script 52  
 getting started 1  
 global support, contacting 152  
 GRANT script  
   editing 30  
   running 36  
 granting  
   home page personalization access 118  
   privileges to connect ID 36

## H

home page personalization access,  
   granting 118

## I

identifying  
   customizations 20  
   EDI tables 20  
   mass change 20  
 images, shrinking 15  
 importing  
   application messages 90  
   application system data 106  
   approval process seed data 94  
   data conversion driver data 94



- DB2 z/OS-specific information 32
- learning filters 107
- new release objects 73
- Pagelet Wizard application data 92
- Pagelet Wizard data 93
- PeopleTools system tables 39
- project definitions 64
- record groups 91
- related language system data 105
- selected PeopleTools tables 72
- setup data 107
- system setup data 92
- upgrade views project 88
- improving performance 149
- increasing space, log file and database 4
- index parameters
  - setting 84
- indexes
  - creating 83
  - parameters, setting after copy 75
  - reviewing the create indexes log 84
  - temporary performance, creating 38
- Informix
  - loading data model definitions 42
  - updating statistics 40
- INITALTAUD project, creating 9
- initial audits
  - reviewing 10
  - running 8
- installation, applying fixes during 138
- integration testing 161

## L

- language data, updating 107
- language system data
  - exporting related 105
  - importing related 105
- languages
  - loading data 56
  - populating 55
  - swapping on system data 89
- learning administrators
  - setting up access 125
  - updating roles 124
- learning environments
  - importing learning filters 107
  - setting up 124
  - setting up learning administrator access 125

- updating learning administrator roles 124
- license code, updating 37
- loading
  - base data 55
  - conversion data 60
  - data for data conversion 89
  - data model definitions 41
  - data to complete system setup 102
  - English currency codes 57
  - English messages 56
  - English string data 57
  - language data 56
  - message data 43
  - noncomparable objects 56
  - PeopleTools data 56
  - PeopleTools definition security group 58
  - stored statements data 57
  - system messages 43
  - upgrade planning messages 6
- local message node, preserving 64
- log
  - reviewing for pagelet and collection issues 119
- log file, increasing space 4

## M

- mass change, identifying 20
- message data
  - loading 43
  - loading English messages 56
  - upgrade planning, loading 6
- message queues, purging 16
- migrating records 53
- model definitions, *See* data model definitions
- modifying
  - compare options 65
  - compare report options 17
  - database structure 79
- Move to Production
  - editing import scripts 32
  - editing password 32
  - performing 132
  - testing 129
  - understanding 130
- MSGTLSUPG script, editing 34
- MultiChannel Framework (MCF) data 59
- multilingual step properties, editing 34

MVPRDIMP script, editing 32

## N

New Copy of Production database

importing data 32

new release

exporting objects 73

importing objects 73

new release database

backing up again 74

new release demo

restoring 94

New Release Demo database

backing up 17

non-comparable objects, reviewing 68

notes and tips, for your upgrade 3

## O

object version numbers

setting 62

updating 108

object version numbers, resetting 74

objectives data

exporting 24

Oracle

loading data model definitions 42

updating statistics 40

## P

pagelet and collection log 119

pagelet publishing, enabling 120

Pagelet Wizard

exporting application data 92

exporting data 93

importing application data 92

importing data 93

Pagelet Wizard Common Components data,

deleting 22

parallel testing 161

password, Move to Production 32

passwords, encrypting connector

passwords 60

patch information, updating 38

PATCH84X project 48

PATCH84XML project 49

PeopleSoft upgrade survey 132

PeopleTools

data, loading 56

definition security group, loading 58

editing swap script 23

exporting system tables 38

functionality 121

importing system tables 39

objects, converting 58

objects, reviewing 43

re-exporting tables 156

script 52

tables, dropping 14

updating patch information 38

updating system tables 35

upgrade, backing up after 62

upgrading Enterprise Portal 179

PeopleTools conversion

completing 108

PeopleTools tables

exporting 71

importing 72

swapping languages 72

performance

improving 149

improving for your platform 150

tips and techniques 149

views, recreating 36

performance testing 162

performance tips

for creating and altering SQL 150

for data conversion 150

for DB2 151

for modify database structures 150

for Oracle 151

permission lists

updating Portal registry 179

permissions lists

understanding registry updates 179

Portal

configuring 114

converting objects 59

running security synchronization 117

Portal navigation objects, registering 116

portal options data, updating 122

Portal registry

updating permission lists 179

PPLTLS84CUR project 45, 52

PPLTLS84CURDEL project 48

PPLTLS84CURML project 46

PPLTLS84CURTABLES script

editing 52

generating 52

running 53

- PPLTLSML project 47
- preparing
  - application upgrade 22
  - for the upgrade 13
- preserving queries and trees 153
- preserving, local message node 64
- Process Scheduler
  - configuring 96
- processes, running database full sync 123
- processing
  - pending approvals 11
- product license code, updating 37
- production database
  - identifying empty tables 13
- production database, copying 3
- project definitions
  - exporting 63
  - importing 64
- projects
  - exporting and copying 45
  - INITALTAUD 9
  - PATCH84X 48
  - PATCH84XML 49
  - PPLTLS84CUR 45, 52
  - PPLTLS84CURDEL 48
  - PPLTLS84CURML 46
  - PPLTLSML 47
  - PT84TBLSPC 53
- PSLANGUAGES script
  - editing 30
  - running 55
- PSOBJCHNG table, cleaning 14
- PT84TBLSPC project 53
- PTUPGCONVERT 108
- PTUPGCONVERT program 61
- PTxxxTLS scripts
  - editing 30
  - running 55

## Q

- queries and trees, preserving 153
- query prompt headings, converting 60

## R

- reapplying customizations 115
- RecField definitions, copying 22
- record groups
  - exporting 90
  - importing 91

- record parameters
  - setting 85
- records
  - migrating 53
  - setting parameters after copy 76
- registering Portal navigation objects 116
- registry permission lists, understanding updates 179
- registry, upgrading Content Provider 121
- regression testing 162
- Ren servers, updating configuration 58
- reporting conversion details 61
- resetting
  - action flags in UPGCUST 67
  - object version numbers 74
- restoring
  - Current Release Demo database 20
  - new release demo 94
- reviewing
  - Alter Audit, final 110
  - audits 10
  - change control 126
  - create indexes log 84
  - new release changes 67
  - new release compare reports 67
  - non-comparable objects 68
  - PeopleTools functionality 121
  - PeopleTools objects 43
  - UPGCUST compare log 20
  - UPGCUST copy results 70
  - UPGNONCOMP copy results 74
- running
  - Alter Audit 10, 110
  - alter tables script 83
  - alter with deletes script 101
  - audits 8, 108
  - create indexes script 83
  - create tables script 83
  - create temp tables script 82
  - create triggers script 101
  - data conversion, for application changes 96
  - data conversion, for PeopleTools changes 61
  - database full sync processes 123
  - DB2TMPIDXCREATE script 38
  - DBTSFIX output scripts 36
  - DBTSFIX script 28
  - DDDAUDIT script 8, 109
  - DDLDB2 script 41

- DDLDBX script 42
- DDLIFX script 42
- DDL MSS script 42
- DDLORA script 42
- DDLSYB script 43
- GRANT script 36
- new release UPGCUST 66
- new release upgrade copy 71
- Portal security synchronization 117
- PPLTLS84CURTABLES script 53
- PSLANGUAGES script 55
- PTUPGCONVERT program 61
- PTxxxTLS scripts 55
- row count report 13
- SETINDEX script 75, 111
- SETSPACE script 75
- SETTABLE script 76, 111
- SYSAUDIT script 9, 109
- SYSVIEW8 script 36
- tablespace alter script 54
- TLSUPGNONCOMP script 56
- TSRECPOP script 107
- update statistics 39–40
- UPGCOUNT script 13
- UPGCUST 19
- UPGCUST filter script 19
- upgrade views project 88
- RUNSTATS.DAT, creating 39

## S

### scripts

- DB2 z/OS create table scripts 31
- DB2 z/OS MTP import scripts 32
- DB2TMPIDXCREATE 38
- DBTSFIX 28
- DBTSFIX output scripts 29, 36
- DDDAUDIT 8
- DDLDB2, editing 33
- DDLDB2, running 41
- DDLDBX, editing 33
- DDLDBX, running 42
- DDLIFX, editing 34
- DDLIFX, running 42
- DDL MSS, running 42
- DDLORA, editing 33
- DDLORA, running 42
- DDLSYB, running 43
- DHC8X01DMS 90–91
- editing DB2 upgrade planning 7
- GRANT 36

- GRANT, editing 30
- MSGTLSUPG 34
- MVPRDIMP 32
- PeopleTools 52
- PeopleTools swap script 23
- PPLTLS84CURTABLES 52
- PSLANGUAGES 55
- PSLANGUAGES, editing 30
- PTxxxTLS scripts 55
- PTxxxTLS scripts, editing 30
- running ALLTABS\_ALTTL 83
- running ALLTABS\_CRTTL 83
- SETINDEX 75
- SETSPACE 75
- SETTABLE 76
- SYSAUDIT 9
- system data swap script 23
- SYSVIEW8 36
- TLSUPGNONCOMP 56
- TLSUPGNONCOMP, editing 30
- UPGCOUNT 13
- security
  - granting home page personalization
    - access 118
  - loading PeopleTools definition security
    - group 58
  - running Portal security
    - synchronization 117
  - setting up 116
  - setting up, upgrade planning 6
  - synchronizing content reference
    - permissions 117
  - understanding setup 117
- servers
  - application servers 26, 58, 96, 114
  - database servers 62
  - file servers 30
  - Ren servers 58
- SETINDEX script 75, 111
- SETSPACE script 75
- SETTABLE script 76, 111
- setting 62
  - index parameters 75
  - object version numbers 62
  - record parameters after copy 76
  - tablespace names 75
- setting up
  - learning administrator access 125
  - learning environments 124
  - security 116

- security for upgrade planning 6
- setup data, exporting 106
- setup data, importing 107
- shrinking images 15
- software installation
  - verifying 2
- SQL Server
  - loading data model definitions 42
- stamping the database 125
- starting
  - application servers 114
- statistics
  - DB2 UNIX/NT, updating 40
  - DB2 z/OS, updating 39
  - Informix, updating 40
  - Oracle, updating 40
  - updating 7
- stored statements data, loading 57
- string data, loading 57
- support, contacting 152
- Sybase
  - loading data model definitions 43
- synchronizing content reference
  - permissions 117
- SYSAUDIT script
  - running final 109
  - running initial 9
- system
  - messages, loading 43
  - tables, exporting 38
  - tables, importing 39
- system data swap script, editing 23
- system setup data
  - exporting 92
  - importing 92
- system testing 161
- SYSVIEW8 script, running 36

## T

- tables
  - moving to new tablespaces 54
  - PeopleTools system tables, updating 35
  - PeopleTools, dropping 14
  - PSOBJCHNG 14
  - running row count report 13
  - system tables, exporting 38
  - system tables, importing 39
- tablespaces
  - alter script 54
  - creating custom 77

- creating new 76
- creating PeopleSoft-delivered 76
- migrating records to 53
- populating data 49
- setting names 75, 85
- setting names for temporary tables 84
- updating names 51
- target values, updating 72
- temporary tables, setting tablespace
  - names 84
- test plan, developing 163
- test scripts, developing 164
- testing
  - after the upgrade 132
  - backing up before 127
  - Copy of Production 127
  - determining conditions 163
  - evaluating requirements 160
  - integration 161
  - Move to Production 129
  - parallel environments 161
  - performance 162
  - planning 159
  - regression 162
  - system 161
  - tips and techniques 165
  - unit 160
  - user acceptance 162
- testing strategy
  - defining 160
  - determining conditions 163
  - when to test 159
- TLSUPGNONCOMP script
  - editing 30
  - running 56
- Tree/Query Copy of Production
  - comparing project 155
  - copying project 156
  - creating project in 154
  - preparing database 154
- TSRECPPOP script, running 107
- turning off change control 41

## U

- unit testing 160
- updates
  - applying before data conversion 95
- updating
  - Configuration Manager profile 27
  - database overrides 74

- language data 107
- learning administrator roles 124
- object version numbers 108
- PeopleTools patch information 38
- PeopleTools system tables 35
- portal options data 122
- product license code 37
- Ren server configuration 58
- statistics for DB2 UNIX during
  - application changes 86
- statistics for DB2 UNIX/NT 40
- statistics for DB2 z/OS 39
- statistics for DB2 z/OS during application
  - changes 86
- statistics for Informix 40
- statistics for Informix during application
  - changes 86
- statistics for Oracle 40
- statistics for Oracle during application
  - changes 87
- statistics, initial 7
- tablespace names 51
- target values 72
- updating statistics
  - DB2 UNIX/NT 40
  - DB2 z/OS 39
  - Informix 40
  - Oracle 40
- UPGCOUNT script, running 13
- UPGCUST
  - copying 70
  - resetting action flags 67
  - reviewing compare log 20
  - reviewing copy results 70
  - running 19
  - running filter script 19
  - running new release 66
- UPGNONCOMP
  - copying 73
  - reviewing copy results 74
- UPGOPT project
  - applying 5
  - building 5
- upgrade
  - compare reports, understanding 172
  - configuring environment 113
  - creating upgrade views 87
  - database preparation 1
  - databases, defined 2
  - getting started 1

- loading planning messages 6
- notes and tips 3
- PeopleTools, backing up after 62
- planning for performance 149
- planning for testing 159
- preparing for 13
- setting up upgrade planning security 6
- user, verifying 26
- upgrade copy, running 71
- Upgrade Drivers page
  - accessing 145
  - adding new section 146
  - inactivating section 147
- upgrade planning files, applying 4
- upgrade tables script
  - recreating 80
- upgrade views
  - building 88
  - creating the project 87
  - exporting the project 88
  - importing the project 88
  - running the script 88
- upgrading
  - Content Provider registry 121
  - Enterprise Portal PeopleTools 179
- user acceptance testing 162
- user interface
  - changing for desktop computers 141
  - changing for mobile devices 143
- using
  - Application Engine Driver
    - program 145

## V

- verifying
  - database integrity 14
  - software installation 2
  - upgrade user 26
- version numbers
  - setting 62
  - updating 108
- views
  - creating all 102
  - creating PPLTOOLS 61