

## **Oracle® Identity Manager**

Connector Guide for Database Application Tables

Release 9.0.2

**B32154-01**

September 2006

Copyright © 2006, Oracle. All rights reserved.

Primary Authors: Debapriya Datta, Shiladitya Guha

Contributing Authors: Don Gosselin, Lyju Vadassery

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

---

---

# Contents

<b>Preface</b> .....	v
Audience .....	v
Documentation Accessibility .....	v
Related Documents .....	vi
Documentation Updates .....	vii
Conventions .....	vii
 <b>What's New in the Oracle Identity Manager Connector for Database Application Tables?</b> .....	ix
Software Updates .....	ix
Documentation-Specific Updates.....	x
 <b>1 About the Connector</b>	
Supported Functionality .....	1-1
Multilanguage Support.....	1-3
Reconciliation Module .....	1-3
Reconciliation of New and Updated User Profiles .....	1-3
Reconciliation of Deleted Users .....	1-6
Files and Directories That Comprise the Connector .....	1-7
Determining the Release Number of the Connector.....	1-8
 <b>2 Deploying the Connector</b>	
Step 1: Verifying Deployment Requirements.....	2-1
Step 2: Configuring the Target System.....	2-2
Sample Configuration.....	2-7
Create User Configuration.....	2-8
Update User Properties Configuration.....	2-9
Update User Password Configuration.....	2-10
Delete User Configuration.....	2-10
Step 3: Copying the Connector Files and External Code .....	2-11
Step 4: Configuring the Oracle Identity Manager Server.....	2-12
Changing to the Required Input Locale.....	2-12
Clearing Content Related to Connector Resource Bundles from the Server Cache .....	2-12
Step 5: Importing the Connector XML File .....	2-13
Defining IT Resources .....	2-13

<b>Step 6: Configuring Reconciliation.....</b>	<b>2-14</b>
Specifying Values for the Scheduled Task Attributes .....	2-15
<b>Step 7: Compiling Adapters .....</b>	<b>2-16</b>
<b>Configuring the Connector for Multiple Sets of Database Application Tables .....</b>	<b>2-17</b>
<b>Security Considerations .....</b>	<b>2-17</b>
Secure JDBC Connectivity .....	2-17
Password Encryption and Decryption.....	2-20

### **3 Testing and Troubleshooting**

Running Test Cases .....	3-1
Troubleshooting.....	3-2

### **4 Known Issues**

### **Index**

---

---

# Preface

*Oracle Identity Manager Connector Guide for Database Application Table* provides information about integrating Oracle Identity Manager with database application tables.

---

---

**Note:** Some parts of the product and documentation still refer to the original Thor company name and Xellerate product name and will be rebranded in future releases.

---

---

## Audience

This guide is intended for users who want to integrate Oracle Identity Manager with database application tables.

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

### Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

### Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

### **TTY Access to Oracle Support Services**

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

## **Related Documents**

For more information, refer to the following documents in the Oracle Identity Manager documentation set:

- *Oracle Identity Manager Release Notes*
- *Oracle Identity Manager Installation and Upgrade Guide for JBoss*
- *Oracle Identity Manager Installation and Upgrade Guide for WebLogic*
- *Oracle Identity Manager Installation and Upgrade Guide for WebSphere*
- *Oracle Identity Manager Administrative and User Console Guide*
- *Oracle Identity Manager Administrative and User Console Customization Guide*
- *Oracle Identity Manager Design Console Guide*
- *Oracle Identity Manager Tools Reference Guide*
- *Oracle Identity Manager Audit Report Developer Guide*
- *Oracle Identity Manager Best Practices Guide*
- *Oracle Identity Manager Connector Guide for BMC Remedy User Management*
- *Oracle Identity Manager Connector Guide for CA-ACF2 Advanced*
- *Oracle Identity Manager Connector Guide for CA-Top Secret Advanced*
- *Oracle Identity Manager Connector Guide for Database Application Tables*
- *Oracle Identity Manager Connector Guide for Database User Management*
- *Oracle Identity Manager Connector Guide for IBM RACF*
- *Oracle Identity Manager Connector Guide for IBM RACF Advanced*
- *Oracle Identity Manager Connector Guide for IBM Lotus Notes and Domino*
- *Oracle Identity Manager Connector Guide for Microsoft Active Directory*
- *Oracle Identity Manager Password Synchronization Module for Microsoft Active Directory Installation and Configuration Guide*
- *Oracle Identity Manager Connector Guide for Microsoft Exchange 2000 and 2003*
- *Oracle Identity Manager Connector Guide for Microsoft Exchange 5.5*
- *Oracle Identity Manager Connector Guide for Microsoft Windows 2000*
- *Oracle Identity Manager Connector Guide for Microsoft Windows NT 4.0*
- *Oracle Identity Manager Connector Guide for Novell eDirectory*
- *Oracle Identity Manager Connector Guide for Novell GroupWise*
- *Oracle Identity Manager Connector Guide for Oracle e-Business Employee Reconciliation*
- *Oracle Identity Manager Connector Guide for Oracle e-Business User Management*
- *Oracle Identity Manager Connector Guide for Oracle Internet Directory*
- *Oracle Identity Manager Connector Guide for PeopleSoft Employee Reconciliation*

- *Oracle Identity Manager Connector Guide for PeopleSoft User Management*
- *Oracle Identity Manager Connector Guide for Siebel Enterprise Applications*
- *Oracle Identity Manager Connector Guide for RSA Authentication Manager*
- *Oracle Identity Manager Connector Guide for RSA ClearTrust*
- *Oracle Identity Manager Connector Guide for SAP CUA*
- *Oracle Identity Manager Connector Guide for SAP Employee Reconciliation*
- *Oracle Identity Manager Connector Guide for SAP Enterprise Portal*
- *Oracle Identity Manager Connector Guide for SAP User Management*
- *Oracle Identity Manager Connector Guide for Sun Java System Directory*
- *Oracle Identity Manager Connector Guide for UNIX SSH*
- *Oracle Identity Manager Connector Guide for UNIX Telnet*

## Documentation Updates

Oracle is committed to delivering the best and most recent information available. For information about updates to the Oracle Identity Manager 9.0.2 connector documentation set, visit Oracle Technology Network at

<http://www.oracle.com/technology/documentation/index.html>

## Conventions

The following text conventions are used in this document:

Convention	Meaning
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.





---

---

# What's New in the Oracle Identity Manager Connector for Database Application Tables?

This chapter provides an overview of the updates made to the connector and documentation for Database Application Tables in release 9.0.2 of the Oracle Identity Manager connector pack.

The updates discussed in this chapter are divided into the following categories:

- [Software Updates](#)

These include updates made to the connector software.

- [Documentation-Specific Updates](#)

These include major changes made to the connector documentation. These changes are not related to software updates.

**See Also:** *Oracle Identity Manager Release Notes*

## Software Updates

This section discusses the following software updates implemented in this release of the connector.

### **Incorporation of Multilanguage Support**

In addition to English, this release of the connector supports the French and Japanese languages. The following are documentation updates pertaining to the incorporation of this feature:

- The installation media directory includes resource bundle files for the languages supported by the connector. These resource bundle files are described in the ["Files and Directories That Comprise the Connector"](#) section on page 1-7.
- The ["Step 3: Copying the Connector Files and External Code"](#) section on page 2-11 specifies the destination directory into which you must copy the resource bundle files during the deployment procedure.
- The ["Step 4: Configuring the Oracle Identity Manager Server"](#) section on page 2-12 describes the procedure to change to the required input locale and to clear content related to connector resource bundles from the server cache.
- [Chapter 4, "Known Issues"](#) discusses a new issue related to the use of non-English locales.

### **Determining the Release Number of the Connector**

Instructions to determine the release number of the connector are given in the ["Determining the Release Number of the Connector"](#) section on page 1-8.

### **Change in the External Code File Requirement**

If the target system is Oracle Database, then you use the `ojdbc14.jar` file instead of the `classes12.zip` file. This change has been made in the ["Step 3: Copying the Connector Files and External Code"](#) section on page 2-11.

### **New Adapters**

The following adapters have been added to the list in the ["Step 7: Compiling Adapters"](#) section on page 2-16:

- DBRES Update Role
- DBRES Update Group

### **Introduction of a Troubleshooting Utility**

[Chapter 3, "Testing and Troubleshooting"](#) has been added to provide instructions on using the troubleshooting utility to test connector functionality.

### **Reduced Number of Connector XML Files**

The `dbtablesResAdp.xml` file has replaced the remaining connector XML files that were provided in the `xml\Xellerate Config` directory. This change has been reflected in the ["Files and Directories That Comprise the Connector"](#) section on page 1-7.

### **Changes to the Known Issues List**

The following point has been added in the Known Issues list in [Chapter 4](#):

"The directory path that you specify as the value of the `Configuration XML Path` IT resource parameter must not contain spaces."

The following point has been removed from the Known Issues list:

"Reconciliation of users deleted from the target system works as expected only if there is a single IT resource defined for the resource object."

## **Documentation-Specific Updates**

The following documentation-specific updates have been made in this release of the guide:

- In the ["Reconciliation of New and Updated User Profiles"](#) section on page 1-3, information has been added about changes to be made in the configuration XML file if any user fields are updated.
- In the ["Files and Directories That Comprise the Connector"](#) section on page 1-7, descriptions have been added for all the XML files in the `xml\DB Schema XML` directory.
- Oracle Identity Manager uses a target system user account to connect to and exchange data with the target system. The ["Step 1: Verifying Deployment Requirements"](#) section on page 2-1 provides information about the minimum rights that must be assigned to this user account.

- In the "[Step 2: Configuring the Target System](#)" section on page 2-2, possible values of the following attributes have been modified:
  - `col_type (column)`
  - `xel_data_source (column)`
  - `col_type (record_lookup_key)`
  - `xel_data_source (record_lookup_key)`
- Information in the "[Sample Configuration](#)" section on page 2-7 has been reworded.
- Instructions to copy the connector JAR files and adapter files to all the nodes of a clustered environment have been added in the following sections:
  - [Step 3: Copying the Connector Files and External Code](#) on page 2-11
  - [Step 4: Configuring the Oracle Identity Manager Server](#) on page 2-12
  - [Step 7: Compiling Adapters](#) on page 2-16
- Instructions to use Oracle Identity Manager for linking multiple installations of the target system are given in the "[Configuring the Connector for Multiple Sets of Database Application Tables](#)" section on page 2-17.
- Information about including certain parameters in the `sqlnet.ora` file has been added in the "[Secure JDBC Connectivity Configuration for Oracle Database](#)" section on page 2-18.
- Instructions to make changes in the configuration XML file for disabling secure JDBC connectivity have been added in the "[Disabling Secure JDBC Connectivity](#)" section on page 2-19.
- The "[Troubleshooting](#)" section has been moved to [Chapter 3](#).
- This connector cannot be used in a scenario in which user attributes are stored in more than two database tables. This limitation of the connector has been added in the Known Issues list in [Chapter 4](#).



---

## About the Connector

Oracle Identity Manager automates access rights management, security, and provisioning of IT resources. Oracle Identity Manager connectors are used to integrate Oracle Identity Manager with third-party applications. This guide discusses the deployment procedure for the connector that is used to integrate Oracle Identity Manager with database application tables.

---

**Note:** Oracle Identity Manager connectors were referred to as *resource adapters* prior to the acquisition of Thor Technologies by Oracle.

---

This chapter contains the following sections:

- [Supported Functionality](#)
- [Multilanguage Support](#)
- [Reconciliation Module](#)
- [Files and Directories That Comprise the Connector](#)
- [Determining the Release Number of the Connector](#)

### Supported Functionality

The following table lists the functions that are available with this connector.

Function	Type	Description
Create User	Provisioning	Creates a user
Delete User	Provisioning	Deletes a user
Enable User	Provisioning	Enables or disables a user
or Disable User		
Reset User's Password	Provisioning	Resets a user's password
Update User's First Name	Provisioning	Updates a user's first name
Update User's Last Name	Provisioning	Updates a user's last name
Update User's Group	Provisioning	Updates a user's group

Function	Type	Description
Update User's Title	Provisioning	Updates a user's title
Update User's Department	Provisioning	Updates a user's department
Update User's Communication Language	Provisioning	Updates a user's communication language preference
Update User's Logon Language	Provisioning	Updates a user's logon language preference
Update User's Email Address	Provisioning	Updates a user's e-mail address
Update User's Telephone Number	Provisioning	Updates a user's telephone number
Update User's Time Zone	Provisioning	Updates a user's time zone
Update User's Date Format	Provisioning	Updates a user's date format
Update User's Role	Provisioning	Updates a user's role
Create User (Account Discovery)	Reconciliation	Reconciles new user accounts
Delete User	Reconciliation	Reconciles user accounts that are deleted from the target system
Enable User or Disable User	Reconciliation	Reconciles user accounts that are enabled or disabled
Reset User's Password	Reconciliation	Reconciles user accounts with modified password
Update User's First name	Reconciliation	Reconciles user accounts with modified first name
Update User's Last Name	Reconciliation	Reconciles user accounts with modified last name
Update User's Group	Reconciliation	Reconciles user accounts with modified group
Update User's Title	Reconciliation	Reconciles user accounts with modified title
Update User's Department	Reconciliation	Reconciles user accounts with modified department
Update User's Communication Language	Reconciliation	Reconciles user accounts with modified communication language preference
Update User's Logon Language	Reconciliation	Reconciles user accounts with modified logon language preference
Update User's Email Address	Reconciliation	Reconciles user accounts with modified e-mail address
Update User's Telephone Number	Reconciliation	Reconciles user accounts with modified telephone number
Update User's Time Zone	Reconciliation	Reconciles user accounts with modified time zone
Update User's Date Format	Reconciliation	Reconciles user accounts with modified date format

Function	Type	Description
Update User's Decimal Notation	Reconciliation	Reconciles user accounts with modified decimal notation
Update User's Role	Reconciliation	Reconciles user accounts with modified role

## Multilanguage Support

In addition to English, this release of the connector supports the following languages:

- French
- Japanese

## Reconciliation Module

The reconciliation module handles the reconciliation of new, updated, and deleted user profiles in the target database application. A reconciliation event is created for each user profile to be reconciled.

The default data fields of each reconciliation event record are taken from the configuration XML file. For reconciliation of new or updated user profiles, the data fields are declared in the `reconcileCreateUpdate` section of the XML file. For reconciliation of deleted user profiles, the default data elements are declared in the `reconcileDelete` section. The reconciliation configuration XML code for reconciliation provides the flexibility for enabling or disabling the reconciliation of created, updated, and deleted users.

The following sections describe the configuration XML file content for the following reconciliation types:

- [Reconciliation of New and Updated User Profiles](#)
- [Reconciliation of Deleted Users](#)

### Reconciliation of New and Updated User Profiles

The following is sample code from the configuration XML file, `OraApp2.xml`, for reconciliation of new and updated user profiles:

**See Also:** The `OraApp2.xml` file listed in the ["Files and Directories That Comprise the Connector"](#) section on page 1-7

```
<operation name = "reconcileCreateUpdate" enabled="true">
  <task table_name="XELUSER1.MDL2_USER_PROF" xeltask_type="select">
    <column table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_ID"
      data_type="VARCHAR2" data_typ_size="20" col_info="primary"
      required="true"
      col_type="xellerate" xel_data_source="xel_usr_id" />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET" col_name="USR_ID"
      data_type="VARCHAR2" data_typ_size="20" col_info="foreign"
      required="true" col_type="xellerate" xel_data_source="xel_usr_id" />
    <look_up_group logic_operator="NA">
      <record_lookup_key table_name="XELUSER1.MDL2_USER_PROF"
        logic_operator="NA" comparison_operator="&gt;="
        col_name="USR_LAST_UPDATE" data_type="DATE" data_typ_size="50"
        col_type="join" xel_data_source="XEL_LAST_RECON_TIME" />
      <record_lookup_key table_name="XELUSER1.MDL2_USER_ADDN_DET"
        logic_operator="AND" comparison_operator="&gt;="
```

```

        col_name="USR_LAST_UPDATE" data_type="DATE" data_typ_size="50"
        col_type="join" xel_data_source="XEL_LAST_RECON_TIME" />
    </look_up_group>
    <look_up_group logic_operator="AND">
        <record_lookup_key logic_operator="NA" comparison_operator="="
        table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_ID"
        data_type="VARCHAR2" data_typ_size="20" col_info="primary"
        required="true" col_type="join" xel_data_source="xel_usr_id" />
        <record_lookup_key logic_operator="AND" comparison_operator="="
        table_name="XELUSER1.MDL2_USER_ADDN_DET" col_name="USR_ID"
        data_type="VARCHAR2" data_typ_size="20" col_info="foreign"
        required="true" col_type="join" xel_data_source="xel_usr_id" />
    </look_up_group>
</task>
<task table_name="XELUSER1.MDL2_USER_PROF" xeltask_type="select">
    <column table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_ID"
    data_type="VARCHAR2" data_typ_size="20" col_info="primary"
    required="true" col_type="xellerate" xel_data_source="xel_usr_id" />
    <column table_name="XELUSER1.MDL2_USER_PROF"
    col_name="USR_FIRST_NAME" data_type="VARCHAR2" data_typ_size="60"
    required="true" col_type="xellerate" xel_data_source="xel_usr_first_
    name" />
    <column table_name="XELUSER1.MDL2_USER_PROF"
    col_name="USR_FIRST_NAME" data_type="VARCHAR2" data_typ_size="60"
    required="true" col_type="xellerate" xel_data_source="xel_usr_first_
    name" />
    <column table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_LAST_NAME"
    data_type="VARCHAR2" data_typ_size="60" required="true" col_
    type="xellerate" xel_data_source="xel_usr_last_name" />
    <column table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_PASSWORD"
    data_type="VARCHAR2" data_typ_size="40" required="true" col_
    type="xellerate" xel_data_source="xel_usr_password" encrypt="false"
    reconcile="true" encryption_impl=
    "com.thortech.xl.integration.dbadapter.security.EncryptionSupportImpl
    " />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET"
    col_name="USR_GROUP" data_type="VARCHAR2" data_typ_size="50"
    required="true" col_type="xellerate" xel_data_source="xel_usr_group"
    />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET" col_name="USR_ROLE"
    data_type="VARCHAR2" data_typ_size="50" required="false" col_
    type="xellerate" xel_data_source="xel_usr_role" />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET" col_name="USR_TITLE"
    data_type="VARCHAR2" data_typ_size="50" required="false" col_
    type="xellerate" xel_data_source="xel_usr_title" />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET" col_name="USR_DEPT"
    data_type="VARCHAR2" data_typ_size="50" required="false" col_
    type="xellerate" xel_data_source="xel_usr_dept" />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET" col_name="USR_EMAIL"
    data_type="VARCHAR2" data_typ_size="60" required="false" col_
    type="xellerate" xel_data_source="xel_usr_email" />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET"
    col_name="USR_COMM_LANG" data_type="VARCHAR2" data_typ_size="50"
    required="false" col_type="xellerate" xel_data_source="xel_usr_comm_
    lang" />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET"
    col_name="USR_LOGON_LANG" data_type="VARCHAR2" data_typ_size="50"
    required="false" col_type="xellerate" xel_data_source="xel_usr_logon_
    lang" />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET"

```



```

col_name="USR_TEL_NO" data_type="VARCHAR2" data_typ_size="15"
required="false" col_type="xellerate" xel_data_source="xel_usr_tel_
no" />
<column table_name="XELUSER1.MDL2_USER_ADDN_DET"
col_name="USR_TIME_ZONE" data_type="VARCHAR2" data_typ_size="50"
required="false" col_type="xellerate" xel_data_source="xel_usr_time_zone"
/>
<column table_name="XELUSER1.MDL2_USER_ADDN_DET"
col_name="USR_DATE_FMT" data_type="VARCHAR2" data_typ_size="50"
required="false" col_type="xellerate" xel_data_source="xel_usr_date_
fmt" />
<column table_name="XELUSER1.MDL2_USER_ADDN_DET"
col_name="USR_DEC_NTN" data_type="VARCHAR2" data_typ_size="50"
required="false" col_type="xellerate" xel_data_source="xel_usr_dec_
ntn" />
<look_up_group logic_operator="NA">
  <record_lookup_key table_name="XELUSER1.MDL2_USER_PROF"
  logic_operator="NA" comparison_operator="&gt;="
  col_name="USR_LAST_UPDATE" data_type="DATE" data_typ_size="50"
  col_type="join" xel_data_source="XEL_LAST_RECON_TIME"/>
  <record_lookup_key table_name="XELUSER1.MDL2_USER_ADDN_DET"
  logic_operator="AND" comparison_operator="&gt;="
  col_name="USR_LAST_UPDATE" data_type="DATE" data_typ_size="50"
  col_type="join" xel_data_source="XEL_LAST_RECON_TIME"/>
</look_up_group>
<look_up_group logic_operator="AND">
  <record_lookup_key logic_operator="NA" comparison_operator="="
  table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_ID"
  data_type="VARCHAR2" data_typ_size="20" col_info="primary"
  required="true" col_type="xellerate" xel_data_source="xel_usr_id"
  />
</look_up_group>
<look_up_group logic_operator="AND">
  <record_lookup_key logic_operator="NA" comparison_operator="="
  table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_ID"
  data_type="VARCHAR2" data_typ_size="20" col_info="primary"
  required="true" col_type="join" xel_data_source="xel_usr_id" />
  <record_lookup_key logic_operator="AND" comparison_operator="="
  table_name="XELUSER1.MDL2_USER_ADDN_DET" col_name="USR_ID"
  data_type="VARCHAR2" data_typ_size="20" col_info="foreign"
  required="true" col_type="join" xel_data_source="xel_usr_id" />
</look_up_group>
</task>
</operation>

```

In the preceding sample configuration XML, the names of the data elements are the values given for the `xel_data_source` tag. You can change these names. The same name is also used as the label for elements in each reconciliation event record.

The create or update reconciliation operation involves running two tasks. The first task identifies the users who have been created or modified after the last reconciliation. This returns a list of key field values for the new and modified users.

For example, if the key field to identify a user is the user ID, then this task returns a list of user IDs corresponding to the user profiles that have been created or modified after the last reconciliation run.

The second task collects all required information about all new and modified users for creating the reconciliation event. The division of tasks is designed for optimal use of memory.

The lookup groups in the task help to create lookup conditions for retrieving relevant data. The preceding sample configuration XML code implements the following lookup conditions:

- Join the two tables in which user profile information is stored, and retrieve nonrepeated data for these users.
- Perform incremental reconciliation by retrieving only those records that are modified after the last reconciliation.

The second task has one more lookup for the user ID, so that user information can be retrieved for each user ID by using the first task.

The time at which the previous reconciliation run was completed is stored in the `Reconciliation Timestamp` IT resource parameter. This value is updated with the new system timestamp after the end of the current reconciliation run. This value is compared against the last updated time in the target database tables, as given in the configuration XML file. In this file, the time at which the last reconciliation run was completed is represented as `XEL_LAST_RECON_TIME`. It is a connector configuration constant.

If you update any user field, then you must set the value of `XEL_LAST_RECON_TIME` to the current system date (`sysdate`) in both tables.

For example, suppose you update the first name of the user as follows:

```
UPDATE MDL2_USER_PROF SET usr_first_name = 'John' WHERE usr_id='jdoe'
```

Then, you must also make the following changes:

```
UPDATE MDL2_USER_PROF SET usr_last_update =sysdate WHERE usr_id='jdoe'
UPDATE MDL2_USER_ADDN_DET SET usr_last_update =sysdate WHERE usr_id=' jdoe'
```

---

**Note:** Incremental reconciliation is possible only if the target application is capable of updating the last update time in its database while modifying or creating records. If the target application does not have this feature, then you must not create the lookup group for comparing the last reconciliation time.

---

## Reconciliation of Deleted Users

The following is sample code from the configuration XML file, `OraApp2.xml`, for reconciliation of users deleted from the target system:

```
<operation name = "reconcileDelete" enabled="true">
  <task table_name="XELUSER1.MDL2_USER_PROF" xeltask_type="select">
    <column table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_ID"
      data_type="VARCHAR2" data_typ_size="20" col_info="primary"
      required="true" col_type="xellerate" xel_data_source="xel_usr_id"
    />
    <column table_name="XELUSER1.MDL2_USER_ADDN_DET"
      col_name="USR_ID" data_type="VARCHAR2" data_typ_size="20"
      col_info="foreign" required="true" col_type="xellerate"
      xel_data_source="xel_usr_id" />
    <look_up_group logic_operator="NA">
      <record_lookup_key logic_operator="NA" comparison_operator="="
        table_name="XELUSER1.MDL2_USER_PROF" col_name="USR_ID"
        data_type="VARCHAR2" data_typ_size="20" col_info="primary"
        required="true" col_type="join" xel_data_source="xel_usr_id"/>
      <record_lookup_key logic_operator="AND" comparison_
```

```

        operator="=" table_name="XELUSER1.MDL2_USER_ADDN_DET"
        col_name="USR_ID" data_type="VARCHAR2" data_typ_size="20"
        col_info="foreign" required="true" col_type="join
        xel_data_source="xel_usr_id" />
    </look_up_group>
</task>
</operation>

```

Only user IDs are required for creating deletion reconciliation events. Therefore, the preceding configuration XML code shows only the user ID as the data element to be retrieved according to the conditions given in the lookup group.

## Files and Directories That Comprise the Connector

The files and directories that comprise this connector are compressed in the following ZIP file on the installation media:

Database Servers\Database Application Table\Database Application Table Rev 2.2.0.zip

These files and directories are listed in the following table.

File in the Installation Media Directory	Description
xml\Xellerate Config\dbtablesResAdp.xml	<p>This XML file contains definitions for the following connector components:</p> <ul style="list-style-type: none"> <li>■ IT resource type</li> <li>■ Process form</li> <li>■ Process task and task adapter</li> <li>■ Resource object</li> </ul>
Files in the xml\DB Schema XML directory	These files contain information about the configuration of the target database schema mapping.
xml\DB Schema XML\OraApp1.xml	<p>For an Oracle Database installation, you must use this configuration XML file if all the user attributes are stored in a single table.</p> <p>If you use this file, then you cannot update the attributes of users you disable during provisioning.</p>
xml\DB Schema XML\OraPerf1.xml	<p>For an Oracle Database installation, you must use this configuration XML file if all the user attributes are stored in a single table.</p> <p>If you use this file, then you can update the attributes of users, regardless of whether or not the user accounts are disabled.</p>
xml\DB Schema XML\OraApp2.xml	<p>For an Oracle Database installation, you must use this configuration XML file if all the user attributes are stored in two tables, a parent table and a child table.</p> <p><b>Note:</b> In this guide, the OraApp2.xml file has been used to illustrate some of the procedures described in this guide.</p>
xml\DB Schema XML\SybApp1.xml	For a Sybase installation, you must use this configuration XML file if all the user attributes are stored in a single table.

File in the Installation Media Directory	Description
xml\DB Schema XML\SybApp2.xml	For a Sybase installation, you must use this configuration XML file if all the user attributes are stored in two tables, a parent table and a child table.
xml\DB Schema XML\xdb_app_map.xsd	This XML file contains information about the validation rules of the configuration XML files that are placed in the same directory.
jar\dbadapter.jar	This JAR file contains the class files that are used to implement provisioning and reconciliation.
Files in the resources directory	Each of these files contains locale-specific information that is used by the connector.
docs\B32154_01.pdf	This guide, which provides instructions to deploy the connector.

The ["Step 3: Copying the Connector Files and External Code"](#) section on page 2-11 provides instructions to copy these files into the required directories.

## Determining the Release Number of the Connector

To determine the release number of the connector:

1. Extract the contents of the `dbadapter.jar` file. This file is in the `jar` directory inside the installation media directory.
2. Open the `manifest.mf` file in a text editor, which is one of the files bundled inside the `dbadapter.jar` file.

In the `manifest.mf` file, the release number of the connector is displayed as the value of the `Version` property.

---

## Deploying the Connector

Deploying the connector involves the following steps:

- [Step 1: Verifying Deployment Requirements](#)
- [Step 2: Configuring the Target System](#)
- [Step 3: Copying the Connector Files and External Code](#)
- [Step 4: Configuring the Oracle Identity Manager Server](#)
- [Step 5: Importing the Connector XML File](#)
- [Step 6: Configuring Reconciliation](#)
- [Step 7: Compiling Adapters](#)

If you want to configure the connector for multiple installations of Database Application Tables, then perform the following procedure:

- [Configuring the Connector for Multiple Sets of Database Application Tables](#)

This chapter also discusses the following postdeployment topic:

- [Security Considerations](#)

### Step 1: Verifying Deployment Requirements

The following table lists the deployment requirements for the connector.

Item	Requirement
Oracle Identity Manager	Oracle Identity Manager release 8.5.3 or later
Target systems	The target system can be any one of the following: <ul style="list-style-type: none"><li>■ Oracle9i Database</li><li>■ Sybase 12.5.2</li></ul>
External code	<ul style="list-style-type: none"><li>■ <code>xerces.jar</code> (the XML parser)</li><li>■ <code>ojdbc14.jar</code> (required if the target system is Oracle Database)</li><li>■ <code>jconn2.jar</code> (required if the target system is Sybase)</li></ul>

Item	Requirement
Target system user account	<p>If target database tables are to be created, then the user account must have the CONNECT privilege.</p> <p>If existing target database tables are to be used, then the user account must have the following privileges on the tables:</p> <ul style="list-style-type: none"> <li>■ CONNECT</li> <li>■ INSERT</li> <li>■ DELETE</li> <li>■ UPDATE</li> <li>■ SELECT</li> </ul> <p>You provide the credentials of this user account while performing the procedure in the <a href="#">"Defining IT Resources"</a> section on page 2-13.</p>

In addition to the requirements mentioned in the preceding table, you must ensure that the following requirements are addressed:

- JDBC connectivity is available to the target database.
- The target database application schema is analyzed and the corresponding XML file is available according to the IT resource definition.
- The JDBC driver and Xerces classes are available in the CLASSPATH environment variable on the Oracle Identity Manager server.
- For secure connectivity to the target database, the required configuration has been performed on the database server.

## Step 2: Configuring the Target System

You must analyze and modify the configuration XML file that you want to use so that it matches the structure of the target application tables.

**See Also:** The ["Files and Directories That Comprise the Connector"](#) section on page 1-7 for information about the various configuration XML files.

The configuration XML file is validated against the schema definition in the `xdb_app_map.xsd` file to ensure that changes that you make in the configuration XML file conform to the schema definition. Therefore, it is recommended that you review the schema definition in the `xdb_app_map.xsd` file before modifying the configuration XML file.

---

**Note:** In the configuration XML file, you must specify `xdb_app_map.xsd` as the value of the `xsi:noNamespaceSchemaLocation` parameter. For example:

```
<xdb_app_map xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="xdb_app_map.xsd" name="OracleApp1">
```

---

The configuration XML file can be divided into the following sections:

- [target\\_application](#)

- [target\\_database](#)
- [mapping\\_data](#)
- [database\\_adapter](#)

### target\_application

This section is used to identify the target application. The purpose of this section is to provide information that simplifies maintenance of the configuration file.

Section	Description	Attributes
Database	Name of the database	name
target_app_name	Name of the application	None
target_app_ver	Version of the application	None
target_app_provider	Vendor or provider of the application	None

### target\_database

This section contains information that is used to configure the database connection properties.

**See Also:** ["Security Considerations"](#) on page 2-17

### mapping\_data

This section is used to keep track of the configuration files modification history.

### database\_adapter

This section is divided into operations. Each operation is further divided into one or more tasks. The number of tasks in an operation depends on the number of tables involved in the operation. Tasks are divided into columns depending on the target application table.

The following table explains the organization of the database\_adapter section.

Description of the Section	Description of the Attributes	Possible Values of the Attributes
operation Each operation is linked with an Oracle Identity Manager connector.	name Type of Oracle Identity Manager operation	create, update, delete, reconcileCreateUpdate, or reconcileDelete
task Each operation is divided into one or more tasks. The number of tasks in an operation depends on the number of tables involved in the operation.	table_name Name of the table on which the task is going to operate	Any valid table name
	xeltask_type Type of task in the database	insert, update, delete, or select
column It is a representation of a single column in the target application table.	col_name Name of the column	Any valid column name

Description of the Section	Description of the Attributes	Possible Values of the Attributes
	data_type Data type	VARCHAR, VARCHAR2, CHAR, LONGVARCHAR, REAL, DOUBLE, NUMERIC, DECIMAL, FLOAT, DATE, TIME, TIMESTAMP, NULL, BOOLEAN, OTHER, or INTEGER
	data_typ_size Data type size	20
	col_info Table indexing and relation to other tables	primary or secondary
	required Specifies whether or not the value of this column can be NULL	true or false
	col_type Data source for the column to be used while creating a user	<ul style="list-style-type: none"> <li>■ substitute: To use, for example, SYSDATE.</li> <li>■ xellerate: Provided by Oracle Identity Manager</li> <li>■ default: Some default value</li> </ul>



Description of the Section	Description of the Attributes	Possible Values of the Attributes
	<p>xel_data_source</p> <p>If col_type is substitute, then xel_data_source holds the substitution string (can be used for functions like sysdate and sequence.nextVal).</p> <p>If col_type is default, then xel_data_source holds the default value.</p> <p>If col_type is xellerate, then xel_data_source holds the mapped Oracle Identity Manager attribute name.</p>	<ul style="list-style-type: none"> <li>Sample string value if col_type is substitute:           <pre>column col_name="USR_LAST_UPD ATE" data_type="DATE" data_typ_size="60" required="false" col_type="substitute"</pre> </li> <li>Sample string value if col_type is default:           <pre>col_name="USR_STATUS" data_type="VARCHAR2" data_typ_size="5" required="true" col_type="default" xel_data_source="true"</pre> </li> <li>Sample string value if col_type is xellerate:           <pre>col_name="USR_ID" data_type="VARCHAR2" data_typ_size="20" col_info="primary" required="true" col_type="xellerate" xel_data_source="xel_u sr_id"</pre> </li> </ul>
	<p>encrypt</p> <p>Specifies whether or not this data must be encrypted</p>	true or false
	<p>reconcile</p> <p>Specifies whether or not this field can be reconciled</p>	true or false
	<p>encryption_impl</p> <p>Encryption method implementation class that provides this operation</p>	Any fully qualified class name
look_up_group	logic_operator	AND or OR
Grouping of lookup fields	Used to connect two lookup groups with an operator	
record_lookup_key	logic_operator	AND or OR
This tag is used to collect the information required to identify a particular record in a table. Note that multiple lookup keys can be used to identify a record in a table.	Used to connect two record lookup keys (columns) with an operator in a group	

Description of the Section	Description of the Attributes	Possible Values of the Attributes
	comparison_operator Operator used to compare the data with the given data for the column	< > = >= <= !=
	table_name Name of the table	Any table name
	col_name Name of the column	Any column name
	data_type Data type	VARCHAR, VARCHAR2, CHAR, LONGVARCHAR, REAL, DOUBLE, NUMERIC, DECIMAL, FLOAT, DATE, TIME, TIMESTAMP, NULL, BOOLEAN, OTHER, or INTEGER
	data_typ_size Data type size	20
	col_info Table indexing and relation to other tables	primary or secondary
	required Specifies whether or not the value of this column can be NULL	true or false
	col_type Data source for the column to be used while creating a user  In addition to substitute, xellerate, and default, the following tag is also applicable for record_lookup_key: join  This tag contains the name of the column that is common to multiple tables.	Xellerate or Default

Description of the Section	Description of the Attributes	Possible Values of the Attributes
	xel_data_source	<pre> &lt;record_lookup_key   logic_operator="NA"   comparison_operator="="   table_name="tcs1234.MDL2_USER_PROF"   col_name="USR_ID"   data_type="VARCHAR2"   data_typ_size="20"   col_info="primary"   required="true"   col_type="join"   xel_data_source="xel_usr_id" /&gt; &lt;record_lookup_key   logic_operator="AND"   comparison_operator="="   table_name="tcs1234.MDL2_USER_ADDN_DET"   col_name="USR_ID"   data_type="VARCHAR2"   data_typ_size="20"   col_info="foreign"   required="true"   col_type="join"   xel_data_source="xel_usr_id" /&gt; </pre>

## Sample Configuration

The sample configuration discussed in this section is based on code from the OraApp2.xml configuration XML file. However, instructions described in this section apply to any configuration XML file that you decide to use.

The following tables correspond to the records defined in the OraApp2.xml configuration XML file.

### MDL2\_USER\_PROF

Field Name	Type and Length	Comments	Required/Optional
USR_ID	VARCHAR(20)	Primary Key	Required
USR_FIRST_NAME	VARCHAR(60)	None	Required
USR_LAST_NAME	VARCHAR(60)	None	Required
USR_PASSWORD	VARCHAR(40)	None	Required
USR_STATUS	VARCHAR(5)	Default value is true	Required
USR_LAST_UPDATE	DATE	SYSDATE	Required

### MDL2\_USER\_ADDN\_DET

Field Name	Type and Length	Comments	Required/Optional
USR_ID	VARCHAR(20)	Foreign Key	Required

Field Name	Type and Length	Comments	Required/Optional
USR_GROUP	VARCHAR (50)	None	Optional
USR_ROLE	VARCHAR (50)	None	Optional
USR_TITLE	VARCHAR (50)	None	Optional
USR_DEPT	VARCHAR (50)	None	Optional
USR_EMAIL	VARCHAR (60)	None	Optional
USR_COMM_LANG	VARCHAR (50)	None	Optional
USR_LOGON_LANG	VARCHAR (50)	None	Optional
USR_TEL_NO	VARCHAR (15)	None	Optional
USR_TIME_ZONE	VARCHAR (50)	None	Optional
USR_DATE_FMT	VARCHAR (50)	None	Optional
USR_DEC_NTN	VARCHAR (50)	None	Optional
USR_LAST_UPDATE	DATE	SYSDATE	Required

---

**Note:** In these code samples, XELUSER1 is a dummy login ID for the database user.

---

The configuration information is divided into the following sections:

- [Create User Configuration](#)
- [Update User Properties Configuration](#)
- [Update User Password Configuration](#)
- [Delete User Configuration](#)

### Create User Configuration

To create a user, the configuration XML must contain the table name, column names, and properties of each column. This is illustrated in the following sample XML code.

```
<operation name="create">
  <task table_name="XELUSER1.MDL2_USER_PROF" xeltask_type="insert">
    <column col_name="USR_ID" data_type="VARCHAR2" data_typ_size="20"
      col_info="primary" required="true" col_type="xellerate"
      xel_data_source="xel_usr_id" />
    <column col_name="USR_FIRST_NAME" data_type="VARCHAR2"
      data_typ_size="60" required="true" col_type="xellerate"
      xel_data_source="xel_usr_first_name" />
    <column col_name="USR_LAST_NAME" data_type="VARCHAR2"
      data_typ_size="60" required="true" col_type="xellerate"
      xel_data_source="xel_usr_last_name" />
    <column col_name="USR_PASSWORD" data_type="VARCHAR2"
      data_typ_size="40" required="true" col_type="xellerate"
      xel_data_source="xel_usr_password" encrypt="false" reconcile="false"
      encryption_impl=
        "com.thortech.xl.integration.dbadapter.security.EncryptionSu
        pportImpl" />
    <column col_name="USR_LAST_UPDATE" data_type="DATE"
      data_typ_size="60" required="true" col_type="substitute"
      xel_data_source="sysdate" />
  </task>
</operation>
```

```

</task>
<task table_name="XELUSER1.MDL2_USER_ADDN_DET" xeltask_type="insert">
  <column col_name="USR_ID" data_type="VARCHAR2" data_typ_size="20"
    col_info="primary" required="true" col_type="xellerate"
    xel_data_source="xel_usr_id" />
  <column col_name="USR_GROUP" data_type="VARCHAR2"
    data_typ_size="50" required="true" col_type="xellerate"
    xel_data_source="xel_usr_group" />
  <column col_name="USR_ROLE" data_type="VARCHAR2"
    data_typ_size="50" required="false" col_type="xellerate"
    xel_data_source="xel_usr_role" />
  <column col_name="USR_TITLE" data_type="VARCHAR2"
    data_typ_size="50" required="false" col_type="xellerate"
    xel_data_source="xel_usr_title" />
  <column col_name="USR_DEPT" data_type="VARCHAR2"
    data_typ_size="50" required="false" col_type="xellerate"
    xel_data_source="xel_usr_dept" />
  <column col_name="USR_EMAIL" data_type="VARCHAR2"
    data_typ_size="60" required="false" col_type="xellerate"
    xel_data_source="xel_usr_email" />
  <column col_name="USR_COMM_LANG" data_type="VARCHAR2"
    data_typ_size="50" required="false" col_type="xellerate"
    xel_data_source="xel_usr_comm_lang" />
  <column col_name="USR_LOGON_LANG" data_type="VARCHAR2"
    data_typ_size="50" required="false" col_type="xellerate"
    xel_data_source="xel_usr_logon_lang" />
  <column col_name="USR_TEL_NO" data_type="VARCHAR2"
    data_typ_size="15" required="false" col_type="xellerate"
    xel_data_source="xel_usr_tel_no" />
  <column col_name="USR_TIME_ZONE" data_type="VARCHAR2"
    data_typ_size="50" required="false" col_type="xellerate"
    xel_data_source="xel_usr_time_zone" />
  <column col_name="USR_DATE_FMT" data_type="VARCHAR2"
    data_typ_size="50" required="false" col_type="xellerate"
    xel_data_source="xel_usr_date_fmt" />
  <column col_name="USR_DEC_NTN" data_type="VARCHAR2"
    data_typ_size="50" required="false" col_type="xellerate"
    xel_data_source="xel_usr_dec_ntn" />
  <column col_name="USR_LAST_UPDATE" data_type="DATE"
    data_typ_size="60" required="true" col_type="substitute"
    xel_data_source="sysdate" />
</task>
</operation>

```

## Update User Properties Configuration

The update operation requires lookup information for identifying the user and properties of the columns that are to be updated. This is illustrated in the following sample XML code.

```

<operation name="update" xel_data_source="xel_usr_dept">
  <task table_name="XELUSER1.MDL2_USER_ADDN_DET" xeltask_type="update">
    <column col_name="USR_DEPT" data_type="VARCHAR2"
      data_typ_size="50" required="true" col_type="xellerate"
      xel_data_source="xel_usr_dept" />
    <column col_name="USR_LAST_UPDATE" data_type="DATE"
      data_typ_size="60" required="true" col_type="substitute"
      xel_data_source="sysdate" />
    <look_up_group logic_operator="NA">
      <record_lookup_key
        table_name="XELUSER1.MDL2_USER_ADDN_DET"

```

```
        logic_operator="NA" comparison_operator="=" col_name="USR_ID"
        data_type="VARCHAR2" data_typ_size="20" required="true"
        col_type="xellerate" xel_data_source="xel_usr_id"/>
    </look_up_group>
</task>
</operation>
```

## Update User Password Configuration

The update password operation works the same way as the update user operation. In addition, it performs data encryption if the `encrypt` attribute is set to `true`.

This is illustrated in the following sample XML code.

```
<operation name="update" xel_data_source="xel_usr_password">
  <task table_name="XELUSER1.MDL1_USER_PROF" xeltask_type="update">
    <column col_name="USR_PASSWORD" data_type="VARCHAR2"
      data_typ_size="40" required="true" col_type="xellerate"
      xel_data_source="xel_usr_password" encrypt="true" reconcile="false"
      encryption_impl=
        "com.thortech.xl.integration.dbadapter.security.EncryptionSu
        pportImpl" />
    <column col_name="USR_LAST_UPDATE" data_type="DATE"
      data_typ_size="60" required="true" col_type="substitute"
      xel_data_source="sysdate" />
    <look_up_group logic_operator="NA">
      <record_lookup_key table_name="XELUSER1.MDL1_USER_PROF"
        logic_operator="NA" comparison_operator="=" col_name="USR_ID"
        data_type="VARCHAR2" data_typ_size="20" required="true"
        col_type="xellerate" xel_data_source="xel_usr_id"/>
    </look_up_group>
  </task>
</operation>
```

## Delete User Configuration

The delete operation requires only lookup information to find the user to be deleted. Column information is used to find the user in the table. This is illustrated in the following sample XML code.

The `lookup_up_group` tags are used to group lookup conditions provided in `record_lookup_key`.

---

**Note:** Two tasks are run to delete user records from both tables. The task related to the secondary table must be run before the primary table task. If the order is not correct, then a referential integrity exception is thrown.

---

```
<operation name="delete">
  <task table_name="XELUSER1.MDL2_USER_ADDN_DET" xeltask_type="delete">
    <look_up_group logic_operator="NA">
      <record_lookup_key logic_operator="NA" comparison_operator="="
        col_name="USR_ID" data_type="VARCHAR2" data_typ_size="20"
        required="true" col_type="xellerate" xel_data_source="xel_usr_
        id"/>
    </look_up_group>
  </task>
  <task table_name="XELUSER1.MDL2_USER_PROF" xeltask_type="delete">
    <look_up_group logic_operator="NA">
```

```

        <record_lookup_key logic_operator="NA" comparison_operator="="
        col_name="USR_ID" data_type="VARCHAR2" data_typ_size="20"
        required="true" col_type="xellerate" xel_data_source="xel_usr_
        id" />
    </look_up_group>
</task>
</operation>

```

## Step 3: Copying the Connector Files and External Code

The connector files to be copied and the directories to which you must copy them are given in the following table.

**Note:** The directory paths given in the first column of this table correspond to the location of the connector files in the following ZIP file on the installation media:

Database Servers\Database Application Table\Database Application Table Rev 2.2.0.zip

Refer to the ["Files and Directories That Comprise the Connector"](#) section on page 1-7 for more information about these files.

Files in the Installation Media Directory	Destination Directory
xml\Xellerate Config\dbtablesResAdp.xml	OIM_home\xellerate\XMLIntegrations\xml\Xellerate Config
Files in the xml\DB Schema XML directory	OIM_home\xellerate\XMLIntegrations\xml\DB Schema
jar\dbadapter.jar	OIM_home\xellerate\JavaTasks OIM_home\xellerate\ScheduleTask
Files in the resources directory	OIM_home\xellerate\connectorResources
docs\B32154_01.pdf	OIM_home\xellerate\docs\DBTables

After you copy the connector files listed in the preceding table, copy the following files to the *OIM\_home\xellerate\ext* directory:

- If the target database is Oracle Database, then the *ojdbc14.jar* file is used. This file is already present in the *OIM\_home\xellerate\ext* directory.

If the target database is Sysbase, then copy the *sybase\_installation\jConnect-5\_2\classes\jconn2.jar* file.

- *xerces.jar*

This file is in the *OIM\_home\xellerate\ext* directory.

**Note:** While installing Oracle Identity Manager in a clustered environment, you copy the contents of the installation directory to each node of the cluster. Similarly, you must copy the *connectorResources* directory and the JAR files to the corresponding directories on each node of the cluster.

## Step 4: Configuring the Oracle Identity Manager Server

Configuring the Oracle Identity Manager server involves the following procedures:

---

---

**Note:** In a clustered environment, you must perform this step on each node of the cluster.

---

---

- [Changing to the Required Input Locale](#)
- [Clearing Content Related to Connector Resource Bundles from the Server Cache](#)

### Changing to the Required Input Locale

Changing to the required input locale involves installing the required fonts and setting the required input locale.

To set the required input locale:

---

---

**Note:** Depending on the operating system used, you may need to perform this procedure differently.

---

---

1. Open Control Panel.
2. Double-click **Regional Options**.
3. On the Input Locales tab of the Regional Options dialog box, add the input locale that you want to use and then switch to the input locale.

### Clearing Content Related to Connector Resource Bundles from the Server Cache

Whenever you add a new resource bundle file in the `OIM_home\xellerate\connectorResources` directory or make a change in an existing resource bundle file, you must clear content related to connector resource bundles from the server cache.

To clear content related to connector resource bundles from the server cache:

1. In a command window, change to the `OIM_home\xellerate\bin` directory.
2. Enter one of the following commands:

---

---

**Note:** You must perform Step 1 before you perform this step. If you run the command as follows, then an exception is thrown:

---

---

`OIM_home\xellerate\bin\batch_file_name`

---

---

- On Microsoft Windows:  
`PurgeCache.bat ConnectorResourceBundle`
- On UNIX:  
`PurgeCache.sh ConnectorResourceBundle`

In this command, `ConnectorResourceBundle` is one of the content categories that you can remove from the server cache. Refer to the following file for information about the other content categories:



`OIM_home\xellerate\config\xlConfig.xml`

---

**Note:** You can ignore the exception that is thrown when you perform Step 2.

---

## Step 5: Importing the Connector XML File

To import the connector XML file into Oracle Identity Manager:

1. Open the Oracle Identity Manager Administrative and User Console.
2. Click the **Deployment Management** link on the left navigation bar.
3. Click the **Import** link under Deployment Management. A dialog box for locating files is displayed.
4. Locate and open the `dbtablesResAdp.xml` file, which is in the `OIM_home\xellerate\XMLIntegrations\xml\Xellerate Config` directory. Details of this XML file are shown on the File Preview page.
5. Click **Add File**. The Substitutions page is displayed.
6. Click **Next**. The Confirmation page is displayed.
7. Click **Next**. The Provide IT Resource Instance Data page for the IT resource is displayed.
8. Specify values for the parameters of the IT resource. Refer to the table given in the ["Defining IT Resources"](#) section on page 2-13 for information about the values to be specified.
9. Click **Next**. The Provide IT Resource Instance Data page for a new instance of the Database IT resource type is displayed.
10. Click **Skip** to specify that you do not want to define another IT resource. The Confirmation page is displayed.

**See Also:** If you want to define another IT resource, then refer to *Oracle Identity Manager Tools Reference Guide* for instructions.

11. Click **View Selections**.

The contents of the XML file are displayed on the Import page. You may see a cross-shaped icon along with some nodes. Remove these nodes by right-clicking each node and then selecting **Remove**.

12. Click **Import**. The connector file is imported into Oracle Identity Manager.

After you import the connector XML file, proceed to the ["Step 6: Configuring Reconciliation"](#) section on page 2-14.

## Defining IT Resources

You must specify values for the IT resource parameters listed in the following table.

Parameter	Description
Database User ID	Database user ID on the target database Sample value: xeluser

Parameter	Description
Database Password	Database user password on the target database Sample value: xeluser
Database URL	JDBC URL for the target database  Format and sample values for Oracle Database:  jdbc:oracle:thin:@host:port:sid jdbc:oracle:thin@145.125.23.26:1521:cust_db  jdbc:oracle:oci:userid/password@host:port:sid jdbc:oracle:oci:scott/tiger@145.125.23.26:1521:cust_db  Format and sample values for Sybase:  jdbc:sybase:Tds:host:port/database jdbc:sybase:Tds:123.432.154.12:2639/sales
Database Driver	JDBC driver class  Value for Oracle Database:  oracle.jdbc.driver.OracleDriver  Value for Sybase:  com.sybase.jdbc3.jdbc.SybDriver
Application Name	Target application name Sample value: myapplication
Configuration XML Path	Directory path and name of the configuration XML file Sample value:  OIM_home\xellerate\XLIIntegrations\xml\DB_Schema\OraApp2.xml  <b>Note:</b> You must ensure that the path that you specify does not contain spaces.  <b>See Also:</b> The <a href="#">"Files and Directories That Comprise the Connector"</a> section on page 1-7 for information about the various configuration XML files that are available in the connector installation media directory. Based on the description of each configuration XML file, select an XML file that meets your requirements.
Reconciliation Timestamp	Variable to store last create/update reconciliation time. This value is updated by the reconciliation adapter. You need not manually provide any data.

After you specify values for these IT resource parameters, proceed to Step 9 of the procedure to import connector XML files.

## Step 6: Configuring Reconciliation

Configuring reconciliation involves creating the reconciliation scheduled tasks:

1. Open the Oracle Identity Manager Design Console.
2. Expand the **Xellerate Administration** folder.
3. Select **Task Scheduler**.
4. Click **Find**. The details of the predefined scheduled task are displayed.

5. Enter a number in the **Max Retries** field. This number represents the number of times Oracle Identity Manager must attempt to complete the task before assigning the ERROR status to the task.
6. Ensure that the **Disabled** and **Stop Execution** check boxes are not selected.
7. In the Start region, double-click the **Start Time** field. From the date-time editor that is displayed, select the date and time at which you want the task to run.
8. In the Interval region, set the following schedule parameters:
  - To set the task to run on a recurring basis, select the **Daily**, **Weekly**, **Recurring Intervals**, **Monthly**, or **Yearly** option.  
If you select the **Recurring Intervals** option, then you must also specify the time interval at which you want the task to run on a recurring basis.
  - To set the task to run only once, select the **Once** option.
9. Provide values for the attributes of the scheduled task. Refer to the ["Specifying Values for the Scheduled Task Attributes"](#) section on page 2-15 for information about the values to be specified.  
  
**See Also:** *Oracle Identity Manager Design Console Guide* for information about adding and removing task attributes
10. Click **Save**. The scheduled task is created. The INACTIVE status is displayed in the **Status** field, because the task is not currently running. The task is run at the date and time that you set in Step 7.

After you define the scheduled task, proceed to the ["Step 7: Compiling Adapters"](#) section on page 2-16.

## Specifying Values for the Scheduled Task Attributes

You must specify values for the following attributes of the reconciliation scheduled task.

---

**Note:** Attribute values are predefined in the connector XML file that you import. Specify values only for those attributes that you want to change.

---

Attribute	Description
resource	Name of the IT resource for which the reconciliation process is to be run Sample value: Oracle Application2
application	Name of the target database application that should be reconciled Sample value: Oracle Application2
objectName	Resource object name of the connector Sample value: Database Application Resource

After you specify values for these scheduled task attributes, proceed to Step 10 of the procedure to create scheduled tasks.

## Step 7: Compiling Adapters

The following adapters are imported into Oracle Identity Manager when you import the XML connector file:

- DBRES Create User
- DBRES Update First Name
- DBRES Update Last Name
- DBRES Update Password
- DBRES Update Status
- DBRES Update Title
- DBRES Update Department
- DBRES Update Email
- DBRES Update Communication Language
- DBRES Update Logon Language
- DBRES Update Time Zone
- DBRES Update Date Format
- DBRES Update Telephone Number
- DBRES Update Decimal Notation
- DBRES Delete User
- DBRES Update Role
- DBRES Update Group

You must compile these adapters before you can use them to provision accounts on the target system.

To compile adapters by using the Adapter Manager form:

1. Open the Adapter Manager form.
2. To compile all the adapters that you import into the current database, select **Compile All**.

To compile multiple (but not all) adapters, select the adapters you want to compile. Then, select **Compile Selected**.

---

---

**Note:** Click **Compile Previously Failed** to recompile only those adapters that were not compiled successfully. Such adapters do not have an OK compilation status.

---

---

3. Click **Start**. Oracle Identity Manager compiles the selected adapters.
4. If Oracle Identity Manager is installed in a clustered environment, then copy the compiled adapters from the *OIM\_home\xellerate\Adapter* directory to the same directory on each of the other nodes of the cluster. If required, overwrite the adapter files on the other nodes. Then, restart each node.

To view detailed information about an adapter:

1. Highlight the adapter in the Adapter Manager form.

2. Double-click the row header of the adapter, or right-click the adapter.
3. Select **Launch Adapter** from the shortcut menu that is displayed. Details of the adapter are displayed.

---

**Note:** To compile one adapter at a time, use the Adapter Factory form. Refer to *Oracle Identity Manager Tools Reference Guide* for information about using the Adapter Factory and Adapter Manager forms.

---

## Configuring the Connector for Multiple Sets of Database Application Tables

---

**Note:** Perform this procedure only if you want to configure the connector for multiple database application tables. Refer to *Oracle Identity Manager Design Console Guide* for detailed instructions on performing each step of this procedure.

---

To configure the connector for multiple sets of database application tables:

1. Create and configure one IT resource for each set of database application tables.  
The IT Resources form is in the Resource Management folder. The *Oracle Application2* IT resource is created when you import the connector XML file. You can use this IT resource as the template for creating the remaining IT resources, of the same resource type.
2. Configure reconciliation for each set of database application tables. Refer to the ["Step 6: Configuring Reconciliation"](#) section on page 2-14 for instructions. Note that only the value of the `resource` attribute needs to be changed for each reconciliation scheduled task.

When you use the Administrative and User Console to perform provisioning, you can specify the IT resource corresponding to the set of database application tables to which you want to provision the user.

## Security Considerations

This section outlines security considerations that you must address when working with this connector. The following topics are discussed in this section:

- [Secure JDBC Connectivity](#)
- [Password Encryption and Decryption](#)

### Secure JDBC Connectivity

You can establish secure JDBC connectivity with the target database by providing information about security properties in the configuration XML file and enabling the database server. The security configuration differs with respect to the target database.

---

**Note:** The following sections discuss code from the OraApp2.xml configuration XML file. You must make similar changes in the configuration XML file that you specify in the IT resource definition as the value of the Configuration XML Path parameter.

Refer to:

- The ["Defining IT Resources"](#) section on page 2-13 for information about the Configuration XML Path parameter.
  - The ["Files and Directories That Comprise the Connector"](#) section on page 1-7 for information about the various configuration XML files that are available in the connector installation media directory.
- 

Depending on the database that you use, refer to one of the following section for information about securing JDBC connectivity:

- [Secure JDBC Connectivity Configuration for Oracle Database](#)
- [Secure JDBC Connectivity Configuration for Sybase](#)

If you do not want to use secure JDBC connectivity, then refer to the following section:

- [Disabling Secure JDBC Connectivity](#)

### Secure JDBC Connectivity Configuration for Oracle Database

The following is the security configuration for Oracle Database:

```
<target_database>
  <database name="Oracle">
    <properties>
      <encryption_nego_level impl_class_name="oracle.net.encryption_
        client" value="REQUESTED"/>
      <encryption_algorithm impl_class_name="oracle.net.encryption_
        client" value="DES40"/>
      <crypto_seed impl_class_name="oracle.net.crypto_seed"
        value="xelsysadmin_seed"/>
      <crypto_checksum_level
        impl_class_name="oracle.net.crypto_checksum_client"
        value="REQUIRED"/>
      <crypto_checksum_client
        impl_class_name="oracle.net.crypto_checksum_types_client"
        value="MD5"/>
    </properties>
  </database>
</target_database>
```

This configuration contains the security properties to be provided to the JDBC driver for establishing a secure connection to Oracle Database. Note that if these parameters are not provided, then a nonsecure JDBC connection is established to the target database.

The following are the permitted values for each configuration parameter mentioned in the configuration XML code listed earlier.

Configuration Parameter	Permitted Value
encryption_nego_level	REJECTED, ACCEPTED, REQUESTED, or REQUIRED

Configuration Parameter	Permitted Value
encryption_algorithm	RC4_256, RC4_128, RC4_56, RC4_40, AES256, AES192, AES128, 3DES168, 3DES112, DES, or DES40
crypto_seed	xelsysadmin_seed
crypto_checksum_level	REJECTED, ACCEPTED, REQUESTED, or REQUIRED
crypto_checksum_client	MD5 or SHA1

In addition to the changes in the configuration XML file, you must add the following parameters in the `sqlnet.ora` file:

```
SQLNET.CRYPTO_CHECKSUM_TYPES_SERVER= (MD5)
SQLNET.AUTHENTICATION_SERVICES= (NTS)
SQLNET.ENCRYPTION_TYPES_SERVER= (DES40)
SQLNET.CRYPTO_SEED = xelsysadmin_seed
```

Depending on the Oracle Database release that you are using, this file is in a directory whose path is similar to the following:

```
oracle_home\ora92\network\admin
```

### Secure JDBC Connectivity Configuration for Sybase

The following is the security configuration for Sybase:

```
<target_database>
<database name="Sybase">
  <properties>
    <cipher_suites impl_class_name="CIPHER_SUITES_1"
      value="SSL_DH_anon_EXPORT_WITH_RC4_40_MD5" />
  </properties>
</database>
</target_database>
```

You can assign any one of the following values to cipher suite:

- SSL\_DH\_anon\_EXPORT\_WITH\_RC4\_40\_MD5
- SSL\_DH\_DSS\_EXPORT\_WITH\_DES40\_CBC\_SHA
- SSL\_RSA\_EXPORT\_WITH\_RC2\_CBC\_40\_MD5
- SSL\_DH\_RSA\_EXPORT\_WITH\_DES40\_CBC\_SHA

### Disabling Secure JDBC Connectivity

If you do not want to implement secure JDBC connectivity, then in the configuration XML file, put the child tags of the `<database>` tag in a comment.

This is shown in the following example:

```
<target_database>
<database name="Oracle">
  <!--<properties>
    <encryption_nego_level impl_class_name="oracle.net.encryption_client" value
      ="REQUESTED"/>
    <encryption_algorithm impl_class_name="oracle.net.encryption_client"
      value="DES40"/>
    <crypto_seed impl_class_name="oracle.net.crypto_seed" value="xelsysadmin_seed"/>
    <crypto_checksum_level impl_class_name="oracle.net.crypto_checksum_client"
```

```
value="REQUIRED" />
<crypto_checksum_clientimpl_class_name="oracle.net.crypto_checksum_types_client"va
lue="MD5" />
  </properties>-->
</database>
</target_database>
```

## Password Encryption and Decryption

You can implement third-party encryption and decryption algorithms when you use this connector. The connector exposes the `EncryptionSupportIntf` interface, which you must implement and make available in the `CLASSPATH` environment variable.

While configuring the encryption for a column, the fully qualified class name must be provided. Before updating the data in the database, the connector encrypts the data. If reconciliation of the encrypted password is possible, then the decryption method is used to retrieve the actual password and to reconcile the password in Oracle Identity Manager.



---

## Testing and Troubleshooting

After you deploy the connector, you must test it to ensure that it functions as expected. This chapter discusses the following topics related to connector testing:

- [Running Test Cases](#)
- [Troubleshooting](#)

### Running Test Cases

You can use the troubleshooting utility to identify the cause of problems associated with connecting to the target system and performing basic operations on the target system.

To use the troubleshooting utility:

1. Open a command window, and change to the `OIM_home\xellerate\JavaTasks` directory in which the `dbadapter.jar` file is stored.
2. Run the following command:  

```
java -jar dbadapter.jar
```
3. Select the test that you want to run.
4. Depending on the test that you select, you are prompted to enter the required information as shown in the following table.

Test	Required Information
Create a user	User ID
	First name
	Last name
	...
	(All other information that is required to create a user account)
Update a user attribute	User ID
	Attribute name
	Attribute value
Delete a user	User ID

If you select the test to update a user, then you can specify any one of the following as the user attribute name:

- xel\_usr\_first\_name
- xel\_usr\_last\_name
- xel\_usr\_password
- xel\_usr\_group
- xel\_usr\_group
- xel\_usr\_role
- xel\_usr\_title
- xel\_usr\_dept
- xel\_usr\_email
- xel\_usr\_comm\_lang
- xel\_usr\_logon\_lang
- xel\_usr\_tel\_no
- xel\_usr\_time\_zone
- xel\_usr\_date\_fmt
- xel\_usr\_dec\_ntn

5. Check if the required action has been successfully carried out.

## Troubleshooting

The following table provides solutions to some commonly encountered issues associated with this connector.

Problem Description	Returned Error Code	Solution
Oracle Identity Manager cannot establish a connection with the target database.	DATABASE CONNECTION FAILED	<ul style="list-style-type: none"> <li>■ Ensure that the drivers of the database are specified in the CLASSPATH environment variable of the Oracle Identity Manager server.</li> <li>■ Ensure that Oracle Identity Manager is running.</li> <li>■ Ensure that all the adapters have been compiled.</li> <li>■ Use the IT Resources form to examine the Oracle Identity Manager record. Ensure that the IP address, administrator ID, and administrator password are correct.</li> </ul>
	DATABASE DRIVER NOT LOADED	Ensure that the database driver is available in the CLASSPATH environment variable of the Oracle Identity Manager server.

Problem Description	Returned Error Code	Solution
A provisioning operation fails with an error code other than those described in the following rows.	CONFIGURATION ERROR	<ul style="list-style-type: none"> <li>■ Ensure that the configuration XML file given in the IT resource definition exists at the specified file system path.</li> <li>■ Ensure that the XML schema file exists at the location specified in the configuration XML file.</li> <li>■ Ensure that the XML file adheres to the XML schema specified inside the file itself.</li> </ul>
	DATA SIZE MISMATCH	Ensure that the data size of the user profile attributes in the XML file adheres to the process form limitations.
	MANDATORY FIELD MISSING	<ul style="list-style-type: none"> <li>■ Ensure that values are provided for all user attributes specified as <code>required</code> in the configuration XML file. This error is thrown even if a blank string is provided.</li> <li>■ Ensure that the process form includes the fields marked as <code>required</code> in the configuration XML file.</li> </ul>
	DATABASE OPERATION FAILED	<ul style="list-style-type: none"> <li>■ Ensure that the maximum size of user profile attributes given in the configuration XML file matches the size defined in the actual database schema.</li> <li>■ Ensure that all the mandatory fields of the database table are marked as <code>required</code> in the configuration XML file.</li> </ul>
Create User provisioning operation fails	USER ALREADY EXISTS	Check if the target database table already has a record with the same user ID (or a combination of whichever primary key fields exist for the table).
Create User or Reset Password provisioning operation fails	ENCRYPTION INTERFACE MISSING	<ul style="list-style-type: none"> <li>■ Check if password encryption is set to <code>true</code> in the configuration XML file.</li> <li>■ Ensure that the encryption interface implementation class is available in the <code>CLASSPATH</code> environment variable of the Oracle Identity Manager server.</li> </ul>
	ENCRYPT/DECRYPT ERROR	<p>This error occurs if an exception is thrown from the encryption implementation class.</p> <ul style="list-style-type: none"> <li>■ Check if the encryption implementation class is working correctly.</li> <li>■ Check the logs for a description of the error and stack trace.</li> </ul>
Update Any User Profile Attribute, Delete a User, or Revoke a Provisioned Resource Object from a User provisioning operation fails	USER DOES NOT EXIST	Check if the record for the user exists in the target database tables.



---

## Known Issues

The following are known issues associated with this release of the connector:

- The directory path that you specify as the value of the `Configuration XML Path` IT resource parameter must not contain spaces.
- Some Asian languages use multibyte character sets. If the character limit for the fields in the target system is specified in bytes, then the number of Asian-language characters that you can enter in a particular field may be less than the number of English-language characters that you can enter in the same field. The following example illustrates this limitation:

Suppose you can enter 50 characters of English in the User Last Name field of the target system. If you were using the Japanese locale and if the character limit for the target system fields were specified in bytes, then you would not be able to enter more than 25 characters in the same field.

- This connector cannot be used in a scenario in which user attributes are stored in more than two database tables.



---

---

# Index

## A

---

Adapter Factory form, 2-17  
Adapter Manager form, 2-16  
adapters, compiling, 2-16  
additional files, 2-1, 2-11  
Administrative and User Console, 2-13

## C

---

changing input locale, 2-12  
clearing server cache, 2-12  
compiling adapters, 2-16  
configuration sample  
    create user, 2-8  
    delete user, 2-10  
    update user password, 2-10  
    update user properties, 2-9  
configuration XML file sections  
    database\_adapter, 2-3  
    mapping\_data, 2-3  
    target\_application, 2-3  
    target\_database, 2-3  
configuring  
    connector for multiple sets of database application  
        tables, 2-17  
    Oracle Identity Manager server, 2-12  
    reconciliation, 2-14  
    target system, 2-2  
connector files and directories  
    copying, 2-11  
    description, 1-7  
    destination directories, 2-11  
    installation media file, 1-7, 2-11  
connector testing, 3-1  
connector version number, determining, 1-8  
connector XML files  
    *See* XML files  
considerations for security, 2-17  
creating scheduled tasks, 2-14

## D

---

decrypting passwords, 2-20  
defining  
    IT resources, 2-13

    scheduled tasks, 2-14  
deployment requirements, 2-1  
Design Console, 2-14  
determining version number of connector, 1-8

## E

---

encrypting passwords, 2-20  
errors, 3-2  
external code files, 2-1, 2-11

## F

---

files  
    additional, 2-1, 2-11  
    external code, 2-1, 2-11  
    *See also* XML files  
files and directories of the connector  
    *See* connector files and directories  
functionality supported, 1-1  
functions available, 1-1

## G

---

globalization features, 1-3

## I

---

importing connector XML files, 2-13  
input locale, changing, 2-12  
issues, 4-1  
IT resources  
    defining, 2-13  
    parameters, 2-13  
    types, Database, 2-13

## J

---

JDBC, 2-17  
JDBC connectivity, disabling, 2-19  
JDBC connectivity, enabling, 2-17

## L

---

limitations, 4-1

## M

---

multilanguage support, 1-3

## O

---

Oracle Identity Manager Administrative and User Console, 2-13

Oracle Identity Manager Design Console, 2-14

Oracle Identity Manager server, configuring, 2-12

## P

---

parameters of IT resources, 2-13

passwords

    decrypting, 2-20

    encrypting, 2-20

problems, 3-2

process tasks, 1-1

provisioning functions, 1-1

## R

---

reconciliation

    configuring, 2-14

    deleted users, 1-6

    functions, 1-1

    module, 1-3

    new users, 1-3

    scheduled task, 2-15

    scheduled task attributes, 2-15

    updated users, 1-3

requirements for deploying, 2-1

## S

---

sample configuration

    create user, 2-8

    delete user, 2-10

    update user password, 2-10

    update user properties, 2-9

scheduled tasks

    attributes, 2-15

    defining, 2-14

secure JDBC, 2-17

secure JDBC connectivity, 2-17

security

    configuration for Oracle Database, 2-18

    configuration for Sybase, 2-19

    considerations, 2-17

server cache, clearing, 2-12

supported

    functionality, 1-1

    languages, 1-3

    releases of Oracle Identity Manager, 2-1

    target systems, 2-1

## T

---

target system configuration, 2-2

target system, multiple installations, 2-17

target systems supported, 2-1

test cases, 3-1

testing the connector, 3-1

troubleshooting, 3-2

troubleshooting utility, 3-1

## V

---

version number of connector, determining, 1-8

## X

---

XML files

    description, 1-7

    destination directory, 2-11

    importing, 2-13