

**Oracle® Identity Manager**

Connector Guide for Microsoft Exchange 2000 and 2003

Release 9.0.3

**B32356-01**

February 2007

Copyright © 1991, 2007, Oracle. All rights reserved.

Primary Authors: Debapriya Datta, Shiladitya Guha

Contributing Authors: Don Gosselin, Lyju Vadassery

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

---

---

# Contents

<b>Preface</b> .....	v
Audience .....	v
Documentation Accessibility .....	v
Related Documents .....	vi
Documentation Updates .....	vi
Conventions .....	vi
<b>What's New in the Oracle Identity Manager Connector for Microsoft Exchange 2000 and 2003?</b> .....	vii
Software Updates .....	vii
Documentation-Specific Updates.....	viii
<b>1 About the Connector</b>	
Supported Functionality .....	1-1
Multilanguage Support.....	1-2
Reconciliation Module .....	1-3
Provisioning Module .....	1-4
Files and Directories That Comprise the Connector .....	1-5
Determining the Release Number of the Connector.....	1-5
<b>2 Deploying the Connector</b>	
Step 1: Verifying Deployment Requirements.....	2-1
Step 2: Configuring the Target System.....	2-2
Step 3: Copying the Connector Files.....	2-2
Step 4: Configuring the Oracle Identity Manager Server.....	2-2
Changing to the Required Input Locale.....	2-3
Clearing Content Related to Connector Resource Bundles from the Server Cache .....	2-3
Enabling Logging .....	2-4
Step 5: Importing the Connector XML Files.....	2-5
Defining IT Resources .....	2-6
Step 6: Configuring Reconciliation.....	2-7
Creating Scheduled Tasks for Reconciliation.....	2-7
Specifying Values for the Scheduled Task Attributes .....	2-8
Enabling Reconciliation in Oracle Identity Manager Release 9.0.1 .....	2-8
Step 7: Compiling Adapters .....	2-8

Configuring the Connector for Multiple Installations of the Target System ..... 2-9

### **3 Known Issues**

#### **A Attribute Mappings Between Oracle Identity Manager and Microsoft Exchange 2000 and 2003**

#### **Index**

---

---

# Preface

*Oracle Identity Manager Connector Guide for Microsoft Exchange 2000 and 2003* provides information about integrating Oracle Identity Manager with Microsoft Exchange 2000 and 2003.

---

---

**Note:** Some parts of the product and documentation still refer to the original Thor company name and Xellerate product name and will be rebranded in future releases.

---

---

## Audience

This guide is intended for users who want to deploy the Oracle Identity Manager connector for Microsoft Exchange 2000 and 2003.

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

### Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

### Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

## TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

## Related Documents

For more information, refer to the following documents in the Oracle Identity Manager documentation library:

- *Oracle Identity Manager Release Notes*
- *Oracle Identity Manager Installation Guide for JBoss*
- *Oracle Identity Manager Installation Guide for Oracle Containers for J2EE*
- *Oracle Identity Manager Installation Guide for WebLogic*
- *Oracle Identity Manager Installation Guide for WebSphere*
- *Oracle Identity Manager Administrative and User Console Guide*
- *Oracle Identity Manager Administrative and User Console Customization Guide*
- *Oracle Identity Manager Design Console Guide*
- *Oracle Identity Manager Tools Reference Guide*
- *Oracle Identity Manager Audit Report Developer Guide*
- *Oracle Identity Manager Best Practices Guide*
- *Oracle Identity Manager Globalization Guide*
- *Oracle Identity Manager Glossary of Terms*

The following document is available in the Oracle Identity Manager Connector Pack documentation library:

- *Oracle Identity Manager Connector Framework Guide*

## Documentation Updates

Oracle is committed to delivering the best and most recent information available. For information about updates to the Oracle Identity Manager 9.0.3 connector documentation set, visit Oracle Technology Network at

<http://www.oracle.com/technology/documentation/index.html>

## Conventions

The following text conventions are used in this document:

<b>Convention</b>	<b>Meaning</b>
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

---

---

# What's New in the Oracle Identity Manager Connector for Microsoft Exchange 2000 and 2003?

This chapter provides an overview of the updates made to the connector and documentation for Microsoft Exchange 2000 and 2003 in release 9.0.3 of the Oracle Identity Manager connector pack.

**See Also:** The 9.0.2 release of this guide for information about updates that were new for the 9.0.2 release

The updates discussed in this chapter are divided into the following categories:

- [Software Updates](#)

These include updates made to the connector software.

- [Documentation-Specific Updates](#)

These include major changes made to the connector documentation. These changes are not related to software updates.

**See Also:** *Oracle Identity Manager Release Notes*

## Software Updates

This section discusses updates made to this release of the connector software.

### Enhancement in the Multilanguage Support

In addition to the three languages supported by the earlier release, this release of the connector supports seven new languages. All the supported languages are listed in the "[Multilanguage Support](#)" section on page 1-2.

### Support for OC4J

Earlier releases of the connector supported the following application servers:

- JBoss Application Server
- BEA WebLogic
- IBM WebSphere

This release of the connector also supports Oracle Containers for J2EE (OC4J).

## Documentation-Specific Updates

The following documentation-specific updates have been made in this release of the guide:

- This connector requires the installation and use of the Microsoft Active Directory connector. In addition, the Microsoft Active Directory connector must be configured to run with SSL enabled. Information explaining this requirement has been added in the "[Step 1: Verifying Deployment Requirements](#)" section on page 2-1.

This limitation has also been mentioned in the Known Issues list in [Chapter 3](#).

- In the "[Enabling Logging](#)" section on page 2-4, instructions for each of the application servers that are supported by this release of the connector have been added.
- In the "[Step 7: Compiling Adapters](#)" section on page 2-8, the instruction about restarting the node has been removed from Step 4 of the procedure to compile adapters.
- [Appendix A](#) provides information about attribute mappings between Oracle Identity Manager and Microsoft Exchange 2000 and 2003.

---

---

## About the Connector

Oracle Identity Manager automates access rights management, security, and provisioning of IT resources. Oracle Identity Manager connectors are used to integrate Oracle Identity Manager with third-party applications. The connector for Microsoft Exchange 2000 and 2003 is used to integrate Oracle Identity Manager with Microsoft Exchange 2000 and 2003.

---

---

**Note:** Oracle Identity Manager connectors were referred to as *resource adapters* prior to the acquisition of Thor Technologies by Oracle.

---

---

This chapter contains the following sections:

- [Supported Functionality](#)
- [Multilanguage Support](#)
- [Reconciliation Module](#)
- [Provisioning Module](#)
- [Files and Directories That Comprise the Connector](#)
- [Determining the Release Number of the Connector](#)

### Supported Functionality

The following table lists the functions that are available with this connector.

Process Task	Type	Description
Create Mailbox	Provisioning	Creates a mailbox in Microsoft Exchange 2000 and 2003
Delete Mailbox	Provisioning	Deletes a provisioned mailbox from Microsoft Exchange 2000 and 2003
Deleted Item Manager Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Deleted Item Manager attribute
Disable Mailbox	Provisioning	Disables a provisioned mailbox in Microsoft Exchange 2000 and 2003
Display Name Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Display Name attribute

<b>Process Task</b>	<b>Type</b>	<b>Description</b>
Email Alias Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Email Alias attribute
Enable Mailbox	Provisioning	Enables a disabled mailbox in Microsoft Exchange 2000 and 2003
Garbage Collection Period Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Garbage Collection Period attribute
Hide From Address Lists Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Hide From Address Lists attribute
Mailbox Size Receipt Quota Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Mailbox Size Receipt Quota attribute
Mailbox Size Transmit Quota Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Mailbox Size Transmit Quota attribute
Mailbox Warning Size Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Mailbox Warning Size attribute
Max Incoming Message Size Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Max Incoming Message Size attribute
Max Outgoing Message Size Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Max Outgoing Message Size attribute
Max Recipients Per Message Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Max Recipients Per Message attribute
Disable Mailbox Time Stamp Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Disable Mailbox Time Stamp attribute
Set Exchange Related Properties	Provisioning	Updates certain important configurations of a mailbox in Microsoft Exchange 2000 and 2003
Use Storage Defaults Updated	Provisioning	Updates the configuration of a mailbox in Microsoft Exchange 2000 and 2003 according to a change in the Use Storage Defaults attribute
Get ObjectGUID from Process	Provisioning	Retrieves the ObjectGUID (unique identifier in Microsoft Active Directory) for an existing provisioned Microsoft Active Directory user, for whom a Microsoft Exchange 2000 and 2003 mailbox needs to be provisioned
Create Mailbox	Reconciliation	Reconciles a mailbox from Microsoft Exchange 2000 and 2003 into Oracle Identity Manager

## Multilanguage Support

This release of the connector supports the following languages:

- English
- Brazilian Portuguese
- French
- German
- Italian
- Japanese
- Korean
- Simplified Chinese
- Spanish
- Traditional Chinese

**See Also:** *Oracle Identity Manager Globalization Guide* for information about supported special characters

## Reconciliation Module

The reconciliation module extracts the following elements from the target system to construct reconciliation event records:

- Display Name
- Employee Type
- Mobile Number
- Pager Number
- ObjectGUID
- SAMAccountName
- Mail
- Mail Nick Name
- Garbage Collection Period
- Deleted Item Flags
- Delivery Cont Length
- Submission Cont Length
- DB Over Hard Quota Limit
- DB Over Quota Limit
- DB Storage Quota
- Exchange Recipient Limit
- DB User Defaults
- Exchange Hide From Address Lists
- Employee ID
- Street Address
- Telephone Number
- Other Telephone Number

- Extension Attribute1
- Extension Attribute2
- Extension Attribute3
- Extension Attribute4
- Extension Attribute6
- Extension Attribute8
- Extension Attribute12
- Extension Attribute15
- Exchange Server
- AD Server
- Distinguished Name

## Provisioning Module

The following fields of Microsoft Exchange 2000 and 2003 are provisioned:

- Email Alias
- Display Name
- Garbage Collection Period
- Deleted Item Manager
- Max Incoming Message Size
- Max Outgoing Message Size
- Mailbox Size Receipt Quota
- Mailbox Size Transmit Quota
- Mailbox Warning Size
- Max Recipients Per Message
- Use Storage Defaults
- Hide From Address Lists
- Rout Email
- Employee Type
- Registered Represent
- Desk Location
- PL Proceed
- Company Address
- Mailbox Type
- Mobile Number
- Pager Number
- Routing Email Addr
- Major Business Number

- Other Business Number
- ObjectGUID

## Files and Directories That Comprise the Connector

The files and directories that comprise this connector are compressed in the following directory on the installation media:

Collaboration and Messaging Applications\Microsoft Exchange

These files and directories are listed in the following table.

File in the Installation Media Directory	Description
lib\xliExchange.jar	This JAR file contains the class files required for provisioning and reconciliation.
Files in the <code>resources</code> directory	Each of these resource bundle files contains language-specific information that is used by the connector.  <b>Note:</b> A <b>resource bundle</b> is a file containing localized versions of the text strings that are displayed on the user interface of Oracle Identity Manager. These text strings include GUI element labels and messages displayed on the Administrative and User Console.
xml\xliExchangeObject_DM.xml	This XML file contains definitions for the following components of the connector: <ul style="list-style-type: none"> <li>■ IT resource type</li> <li>■ Custom process form</li> <li>■ Process task and adapters (along with their mappings)</li> <li>■ Resource object</li> <li>■ Provisioning process</li> <li>■ Pre-populate rules</li> </ul>
xml\xliExchangeSchedulerTask_DM.xml	This XML file contains the parameters for setting up the reconciliation scheduled task.

The "[Step 3: Copying the Connector Files](#)" section on page 2-2 provides instructions to copy these files into the required directories.

## Determining the Release Number of the Connector

To determine the release number of the connector that you have deployed:

1. Extract the contents of the `xliExchange.jar` file. For a connector that has been deployed, this file is in the following directory:

`OIM_home\xellerate\JavaTasks`

2. Open the `manifest.mf` file in a text editor. The `manifest.mf` file is one of the files bundled inside the `xliExchange.jar` file.

In the `manifest.mf` file, the release number of the connector is displayed as the value of the `Version` property.

**See Also:** *Oracle Identity Manager Design Console Guide*

---



---

## Deploying the Connector

Deploying the connector involves the following steps:

- [Step 1: Verifying Deployment Requirements](#)
- [Step 2: Configuring the Target System](#)
- [Step 3: Copying the Connector Files](#)
- [Step 4: Configuring the Oracle Identity Manager Server](#)
- [Step 5: Importing the Connector XML Files](#)
- [Step 6: Configuring Reconciliation](#)
- [Step 7: Compiling Adapters](#)

If you want to configure the connector for multiple installations of Microsoft Exchange 2000 and 2003, then perform the following procedure:

- [Configuring the Connector for Multiple Installations of the Target System](#)

### Step 1: Verifying Deployment Requirements

The following table lists the deployment requirements for the connector.

Item	Requirement
Oracle Identity Manager	Oracle Identity Manager release 8.5.3 or later
Target systems	Microsoft Exchange 2000 and 2003
Target system host platforms	The target system host platform can be any one of the following: <ul style="list-style-type: none"> <li>■ Microsoft Windows Server 2000</li> <li>■ Microsoft Windows Server 2003</li> </ul>
Other systems	Microsoft Active Directory
Target system user account	Because this connector requires the Microsoft Active Directory connector for its functioning, the target system user account requirements are the same as the requirements for the Microsoft Active Directory connector.

---

---

**Note:** You must deploy the Microsoft Active Directory connector before you can deploy and use the Microsoft Exchange connector. In addition, you must ensure that the Microsoft Active Directory connector is configured for use with SSL enabled.

Refer to *Oracle Identity Manager Connector Guide for Microsoft Active Directory* for instructions to deploy the Microsoft Active Directory connector.

---

---

## Step 2: Configuring the Target System

For using this connector, you do not need to perform any configuration steps on the target system.

## Step 3: Copying the Connector Files

The connector files to be copied and the directories to which you must copy them are given in the following table.

---

---

**Note:** The directory paths given in the first column of this table correspond to the location of the connector files in the following directory on the installation media:

Collaboration and Messaging Applications\Microsoft Exchange

Refer to the "[Files and Directories That Comprise the Connector](#)" section on page 1-5 for more information about these files.

---

---

File in the Installation Media Directory	Destination Directory
lib\xliExchange.jar	OIM_home\xellerate\JavaTasks OIM_home\xellerate\ScheduleTask
Files in the resources directory	OIM_home\xellerate\connectorResources
Files in the xml directory	OIM_home\xellerate\XLIntegrations\Exchange\xml

---

---

**Note:** While installing Oracle Identity Manager in a clustered environment, you copy the contents of the installation directory to each node of the cluster. Similarly, you must copy the connectorResources directory and the JAR files to the corresponding directories on each node of the cluster.

---

---

## Step 4: Configuring the Oracle Identity Manager Server

Configuring the Oracle Identity Manager server involves the following procedures:

---

---

**Note:** In a clustered environment, you must perform this step on each node of the cluster.

---

---

- [Changing to the Required Input Locale](#)
- [Clearing Content Related to Connector Resource Bundles from the Server Cache](#)
- [Enabling Logging](#)

## Changing to the Required Input Locale

Changing to the required input locale (language and country setting) involves installing the required fonts and setting the required input locale.

To set the required input locale:

---



---

**Note:** Depending on the operating system used, you may need to perform this procedure differently.

---



---

1. Open Control Panel.
2. Double-click **Regional Options**.
3. On the Input Locales tab of the Regional Options dialog box, add the input locale that you want to use and then switch to the input locale.

## Clearing Content Related to Connector Resource Bundles from the Server Cache

Whenever you add a new resource bundle in the `OIM_home\xellerate\connectorResources` directory or make a change in an existing resource bundle, you must clear content related to connector resource bundles from the server cache.

To clear content related to connector resource bundles from the server cache:

1. In a command window, change to the `OIM_home\xellerate\bin` directory.
2. Enter one of the following commands:

---



---

**Note:** You must perform Step 1 before you perform this step. If you run the command as follows, then an exception is thrown:

```
OIM_home\xellerate\bin\batch_file_name
```

---



---

- On Microsoft Windows:

```
PurgeCache.bat ConnectorResourceBundle
```

- On UNIX:

```
PurgeCache.sh ConnectorResourceBundle
```

In this command, `ConnectorResourceBundle` is one of the content categories that you can remove from the server cache. Refer to the following file for information about the other content categories:

```
OIM_home\xellerate\config\xlConfig.xml
```

---



---

**Note:** You can ignore the exception that is thrown when you perform Step 2.

---



---

## Enabling Logging

When you enable logging, Oracle Identity Manager automatically stores in a log file information about events that occur during the course of provisioning and reconciliation operations. To specify the type of event for which you want logging to take place, you can set the log level to one of the following:

- ALL  
This level enables logging for all events.
- DEBUG  
This level enables logging of information about fine-grained events that are useful for debugging.
- INFO  
This level enables logging of informational messages that highlight the progress of the application at coarse-grained level.
- WARN  
This level enables logging of information about potentially harmful situations.
- ERROR  
This level enables logging of information about error events that may still allow the application to continue running.
- FATAL  
This level enables logging of information about very severe error events that could cause the application to stop functioning.
- OFF  
This level disables logging for all events.

The file in which you set the log level and the log file path depend on the application server that you use:

- **For JBoss Application Server**

To enable logging:

1. In the *JBoss\_home\server\default\conf\log4j.xml* file, locate the following lines:

```
<category name="XELLERATE">  
  <priority value="log_level"/>  
</category>
```

2. In the second XML code line, replace *log\_level* with the log level that you want to set. For example:

```
<category name="XELLERATE">  
  <priority value="INFO"/>  
</category>
```

After you enable logging, log information is written to the following file:

```
JBoss_home\server\default\log\server.log
```

- **For IBM WebSphere:**

To enable logging:

1. Add the following line in the *OIM\_home\xellerate\config\log.properties* file:  

```
log4j.logger.XELLERATE=log_level
```
2. In this line, replace *log\_level* with the log level that you want to set.

For example:

```
log4j.logger.XELLERATE=INFO
```

After you enable logging, log information is written to the following file:

```
WebSphere_home\AppServer\logs\server_name\startServer.log
```

- **For BEA WebLogic**

To enable logging:

1. Add the following line in the *OIM\_home\xellerate\config\log.properties* file:  

```
log4j.logger.XELLERATE=log_level
```
2. In this line, replace *log\_level* with the log level that you want to set.

For example:

```
log4j.logger.XELLERATE=INFO
```

After you enable logging, log information is written to the following file:

```
WebLogic_home\user_projects\domains\domain_name\server_name\server_name.log
```

- **For OC4J**

To enable logging:

1. Add the following line in the *OIM\_home\xellerate\config\log.properties* file:  

```
log4j.logger.XELLERATE=log_level
```
2. In this line, replace *log\_level* with the log level that you want to set.

For example:

```
log4j.logger.XELLERATE=INFO
```

After you enable logging, log information is written to the following file:

```
OC4J_home\opmn\logs\default_group-home-default_group-1.log
```

## Step 5: Importing the Connector XML Files

To import the connector XML files into Oracle Identity Manager:

1. Open the Oracle Identity Manager Administrative and User Console.
2. Click the **Deployment Management** link on the left navigation bar.
3. Click the **Import** link under Deployment Management. A dialog box for locating files is displayed.

4. Locate and open the `xliExchangeObject_DM.xml` file, which is in the `OIM_home\xellerate\XLIntegrations\Exchange\xml` directory. Details of this XML file are shown on the [File Preview](#) page.
5. Click **Add File**. The Substitutions page is displayed.
6. Click **Next**. The Confirmation page is displayed.
7. Click **Next**. The Provide IT Resource Instance Data page for the Exchange Server - Dev IT resource is displayed.
8. Specify values for the parameters of the Exchange Server - Dev IT resource. Refer to the table in the ["Defining IT Resources"](#) section on page 2-6 for information about the values to be specified.
9. Click **Next**. The Provide IT Resource Instance Data page for a new instance of the Exchange Server - Dev IT resource type is displayed.
10. Click **Skip** to specify that you do not want to define another IT resource. The Confirmation page is displayed.

**See Also:** If you want to define another IT resource, then refer to *Oracle Identity Manager Tools Reference Guide* for instructions.

11. Click **View Selections**.

The contents of the XML file are displayed on the Import page. You may see a cross-shaped icon along with some nodes. Remove these nodes by right-clicking each node and then selecting **Remove**.

12. Click **Import**. The connector XML file is imported into Oracle Identity Manager.
13. Perform the same procedure to import the `xliExchangeSchedulerTask_DM.xml` file, which is in the `OIM_home\xellerate\XLIntegrations\Exchange\xml` directory.

After you import the connector XML files, proceed to the ["Step 6: Configuring Reconciliation"](#) section on page 2-7.

## Defining IT Resources

You must specify values for the Exchange Server - Dev IT resource parameters listed in the following table.

Parameter	Parameter Description
Server Name	Host name of the Microsoft Windows computer on which Microsoft Exchange 2000 and 2003 is installed Sample value: W2K_HOST <b>Note:</b> The value must be specified in uppercase.
Store Name	Mailbox store name Sample value: Mailbox Store (W2K_HOST) Here, W2K_HOST is the host name of the Microsoft Exchange 2000 and 2003 Server.

Parameter	Parameter Description
Last Modified Time Stamp	<p>Time at which the last reconciliation run was completed</p> <p>This is in the timestamp format YYYYMMDDHHMMSSZ . At the end of each reconciliation run, the value is updated with the target system timestamp at that instance.</p> <p>Sample value: 19721001000000Z</p> <p>The initial value must be 0 .</p>

After you specify values for these IT resource parameters, proceed to Step 9 of the procedure to import connector XML files.

## Step 6: Configuring Reconciliation

Configuring reconciliation involves performing the following tasks:

- [Creating Scheduled Tasks for Reconciliation](#)
- [Enabling Reconciliation in Oracle Identity Manager Release 9.0.1](#)

### Creating Scheduled Tasks for Reconciliation

To create the reconciliation scheduled tasks:

1. Open the Oracle Identity Manager Design Console.
2. Expand the **Xellerate Administration** folder.
3. Select **Task Scheduler**.
4. Click **Find**. The details of the predefined scheduled task are displayed.
5. For the first scheduled task, enter a number in the **Max Retries** field. This number represents the number of times Oracle Identity Manager must attempt to complete the task before assigning the `ERROR` status to the task.
6. Ensure that the **Disabled** and **Stop Execution** check boxes are not selected.
7. In the Start region, double-click the **Start Time** field. From the date-time editor that is displayed, select the date and time at which you want the task to run.
8. In the Interval region, set the following schedule parameters:
  - To set the task to run on a recurring basis, select the **Daily**, **Weekly**, **Recurring Intervals**, **Monthly**, or **Yearly** option.
 

If you select the **Recurring Intervals** option, then you must also specify the time interval at which you want the task to run on a recurring basis.
  - To set the task to run only once, select the **Once** option.
9. Provide values for the attributes of the scheduled task. Refer to the "[Specifying Values for the Scheduled Task Attributes](#)" section on page 2-8 for information about the values to be specified.
 

**See Also:** *Oracle Identity Manager Design Console Guide* for information about adding and removing task attributes
10. Click **Save**. The scheduled task is created. The `INACTIVE` status is displayed in the **Status** field, because the task is not currently running. The task is run at the date and time that you set in Step 7.

After you create the scheduled task, proceed to the ["Enabling Reconciliation in Oracle Identity Manager Release 9.0.1"](#) section on page 2-8.

### Specifying Values for the Scheduled Task Attributes

You must specify values for the following attributes of the reconciliation scheduled task.

---

**Note:** Attribute values are predefined in the connector XML file that you import. Specify values only for those attributes that you want to change.

---

Attribute	Description	Default/Sample Value
ADServer	Name of the Microsoft Active Directory IT resource	Active Directory Server - Dev
Server	Name of the Microsoft Exchange 2000 and 2003 IT resource	Exchange Server - Dev

After you specify values for these scheduled task attributes, proceed to Step 10 of the procedure to create scheduled tasks.

## Enabling Reconciliation in Oracle Identity Manager Release 9.0.1

If you are using Oracle Identity Manager release 9.0.1, then you must perform the following procedure to enable reconciliation:

**See Also:** *Oracle Identity Manager Design Console Guide*

1. Open the Process Definition form. This form is in the Process Management folder.
2. Click the **Reconciliation Field Mappings** tab.
3. For each field that is of the IT resource type:
  - a. Double-click the field to open the Edit Reconciliation Field Mapping window for that field.
  - b. Deselect **Key Field for Reconciliation Matching**.

## Step 7: Compiling Adapters

The following adapters are imported into Oracle Identity Manager when you import the connector XML file:

- check user process ordered
- Exchange Delete Mailbox
- AD Set User Property
- Set Time Stamp
- Get Value Form User Process
- Chk Value Set
- Exchange Create Mailbox

- Exchange Set User Properties
- DB Prepopulate UserLogin

You must compile these adapters before you can use them to provision accounts on the target system.

To compile adapters by using the Adapter Manager form:

1. Open the Adapter Manager form.
2. To compile all the adapters that you import into the current database, select **Compile All**.

To compile multiple (but not all) adapters, select the adapters you want to compile. Then, select **Compile Selected**.

---



---

**Note:** Click **Compile Previously Failed** to recompile only those adapters that were not compiled successfully. Such adapters do not have an OK compilation status.

---



---

3. Click **Start**. Oracle Identity Manager compiles the selected adapters.
4. If Oracle Identity Manager is installed in a clustered environment, then copy the compiled adapters from the *OIM\_home\xellerate\Adapter* directory to the same directory on each of the other nodes of the cluster. If required, overwrite the adapter files on the other nodes.

To view detailed information about an adapter:

1. Highlight the adapter in the Adapter Manager form.
2. Double-click the row header of the adapter, or right-click the adapter.
3. Select **Launch Adapter** from the shortcut menu that is displayed. Details of the adapter are displayed.

---



---

**Note:** To compile one adapter at a time, use the Adapter Factory form. Refer to *Oracle Identity Manager Tools Reference Guide* for information about using the Adapter Factory and Adapter Manager forms.

---



---

## Configuring the Connector for Multiple Installations of the Target System

---



---

**Note:** Perform this procedure only if you want to configure the connector for multiple installations of Microsoft Exchange 2000 and 2003. Refer to *Oracle Identity Manager Design Console Guide* for detailed instructions on performing each step of this procedure.

---



---

To configure the connector for multiple installations of the target system:

1. Create and configure one IT resource for each target system installation.

The IT Resources form is in the Resource Management folder. An IT resource is created when you import the connector XML file. You can use this IT resource as the template for creating the remaining IT resources, of the same resource type.

2. Configure reconciliation for each target system installation. Refer to the "[Step 6: Configuring Reconciliation](#)" section on page 2-7 for instructions. Note that you need to modify only the attributes that are used to specify the IT resource and to specify whether or not the target system installation is to be set up as a trusted source.

You can designate either a single or multiple installations of Microsoft Exchange 2000 and 2003 as the trusted source.

3. If required, modify the fields to be reconciled for the Xellerate User resource object.

When you use the Administrative and User Console to perform provisioning, you can specify the IT resource corresponding to the Microsoft Exchange 2000 and 2003 installation to which you want to provision the user.

---

---

## Known Issues

The following are known issues associated with this release of the connector:

- The `Server Name` parameter of the IT resource accepts only the host name of the Microsoft Exchange 2000 and 2003 server. Provisioning and reconciliation would not work if the IP address of the computer is provided as the input.
- Some Asian languages use multibyte character sets. If the character limit for the fields in the target system is specified in bytes, then the number of Asian-language characters that you can enter in a particular field may be less than the number of English-language characters that you can enter in the same field. The following example illustrates this limitation:

Suppose you can enter 50 characters of English in the User Last Name field of the target system. If you were using the Japanese language and if the character limit for the target system fields were specified in bytes, then you would not be able to enter more than 25 characters in the same field.

- This connector requires the deployment of a Microsoft Active Directory connector that is configured to run with SSL enabled.



# A

## Attribute Mappings Between Oracle Identity Manager and Microsoft Exchange 2000 and 2003

The following table discusses attribute mappings between Oracle Identity Manager and Microsoft Exchange 2000 and 2003.

Oracle Identity Manager Attribute	Microsoft Exchange 2000 and 2003 Attribute	Description
Company Address	physicalDeliveryOfficeName	Office address
Deleted Item Manager	deletedItemFlags	Number of items in the Deleted Items folder
Desk Location	extensionAttribute6, desktopProfile	Location of the desktop profile for a user or group of users
Display Name	displayName	Name of a user as displayed in the address book This is usually a combination of the user's first name, middle initial, and last name.
Email Alias	mailNickname	Mailbox alias, which is generally the same as SAMAccountName
Employee Type	extensionAttribute1, employeeType	Job category for an employee
Garbage Collection Period	garbageCollPeriod	Time interval, in hours, between garbage collection runs
Hide From Address Lists	msExchHideFromAddressLists	Specifies if the user appears in address lists
Mailbox Size Receipt Quota	mDBOverHardQuotaLimit	Maximum mailbox size, in KB, over which sending and receiving email is disabled
Mailbox Size Transmit Quota	mDBOverQuotaLimit	Mailbox quota overdraft limit, in KB
Mailbox Type	extensionAttribute15, otherMailbox	Specifies the type of mailbox other than the standard X.400 and RFC822 configuration
Mailbox Warning Size	mDBStorageQuota	Message database quota, in KB
Major Business Number	telephonenumber	Primary office phone number
Max Incoming Message Size	delivContLength	Maximum incoming message size, in KB
Max Outgoing Message Size	submissionContLength	Maximum outgoing message size, in KB

<b>Oracle Identity Manager Attribute</b>	<b>Microsoft Exchange 2000 and 2003 Attribute</b>	<b>Description</b>
Max Recipients Per Message	msExchRecipLimit	Maximum number of recipients of a single e-mail
Mobile Number	mobile	Primary mobile phone number of the user
Object GUID	objectGUID	GUID based on the current time stamp assigned to an object
Other Business Number	otherTelephone	Alternative office phone number
Pager Number	pager	Primary pager number
PL Proceed	extensionAttribute8	A custom attribute in Microsoft Exchange
Registered Represent	extensionAttribute3	A custom attribute in Microsoft Exchange
Rout Email	extensionAttribute2	Flag that specifies whether or not e-mail is to be routed
Routing Email Addr	extensionAttribute4	E-mail routing address
Use Storage Defaults	mDBUseDefaults	Specifies whether or not the mailbox store must use the default quota, instead of the per-mailbox quota

---

---

# Index

## A

---

Adapter Factory form, 2-9  
Adapter Manager form, 2-9  
adapters, compiling, 2-8  
attributes mappings, A-1

## C

---

changing input locale, 2-2, 2-3  
clearing server cache, 2-3  
compiling adapters, 2-8  
configuring  
    connector for multiple installations of the target system, 2-9  
    Oracle Identity Manager server, 2-2  
    reconciliation, 2-7  
configuring target system, 2-2  
connector files and directories  
    copying, 2-2  
    description, 1-5  
    destination directories, 2-2  
    installation directory, 1-5, 2-2  
connector version number, determining, 1-5  
connector XML files  
    *See* XML files  
creating scheduled tasks, 2-7

## D

---

defining  
    IT resources, 2-6  
    scheduled tasks, 2-7  
deployment requirements, 2-1  
Design Console, 2-7  
determining version number of connector, 1-5

## E

---

enabling logging, 2-4

## F

---

files and directories of the connector  
    *See* connector files and directories  
functionality supported, 1-1  
functions available, 1-1

## G

---

globalization features, 1-2

## I

---

importing connector XML files, 2-5  
input locale, changing, 2-2, 2-3  
issues, 3-1  
IT resources  
    defining, 2-6  
    Exchange Server - Dev, 2-6  
    parameters, 2-6

## L

---

limitations, 3-1  
logging enabling, 2-4

## M

---

mapping between attributes of target system and Oracle Identity Manager, A-1  
Microsoft Active Directory, 2-1  
multilanguage support, 1-2

## O

---

Oracle Identity Manager Administrative and User Console, 2-5  
Oracle Identity Manager Design Console, 2-7  
Oracle Identity Manager Release 9.0.1, 2-8  
Oracle Identity Manager server, configuring, 2-2

## P

---

parameters of IT resources, 2-6  
process tasks, 1-1  
provisioning  
    fields, 1-4  
    functions, 1-1  
    module, 1-4

## R

---

reconciliation  
    configuring, 2-7

- enabling in Oracle Identity Manager Release
  - 9.0.1, 2-8
- functions, 1-1
- module, 1-3
- scheduled task, 2-8
- scheduled tasks, 2-7
- requirements for deploying, 2-1

## **S**

---

- scheduled task
  - attributes, 2-8
  - reconciliation, 2-8
- scheduled tasks, 2-7
  - defining, 2-7
- server cache, clearing, 2-3
- supported
  - functionality, 1-1
  - languages, 1-2
  - releases of Oracle Identity Manager, 2-1
  - target system host platforms, 2-1
  - target systems, 2-1

## **T**

---

- target system, multiple installations, 2-9
- target systems
  - configuration, 2-2
  - host platforms supported, 2-1
- target systems supported, 2-1

## **U**

---

- user attribute mappings, A-1

## **V**

---

- version number of connector, determining, 1-5

## **X**

---

- XML files
  - copying, 2-2
  - description, 1-5
  - importing, 2-5
  - reconciliation scheduled task, 2-6