

Oracle® Identity Manager

Connector Guide for JD Edwards EnterpriseOne

Release 9.0.3

B32448-01

February 2007

Copyright © 1991, 2007, Oracle. All rights reserved.

Primary Author: Lyju Vadassery

Contributing Authors: Deepa Aswani, Debapriya Datta

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Contents

Preface	v
Audience	v
Documentation Accessibility	v
Related Documents	vi
Documentation Updates	vi
Conventions	vi
1 About the Connector	
Supported Functionality	1-1
Language Support	1-2
Reconciliation Module	1-2
Lookup Fields Reconciliation	1-2
User Reconciliation	1-3
Reconciled JD Edwards EnterpriseOne Object Fields	1-3
Reconciled Xellerate User Fields	1-3
Provisioning Module	1-3
Files and Directories That Comprise the Connector	1-4
Determining the Release Number of the Connector	1-5
2 Deploying the Connector	
Step 1: Verifying Deployment Requirements	2-1
Step 2: Copying the Connector Files and External Code	2-1
Changes to Be Made in the Property Files	2-3
jdbj.ini	2-3
jdeinterop.ini	2-5
jdelog.properties	2-6
Step 4: Configuring the Oracle Identity Manager Server	2-7
Changing to the Required Input Locale	2-7
Clearing Content Related to Connector Resource Bundles from the Server Cache	2-7
Enabling Logging	2-8
Step 5: Importing the Connector XML Files	2-9
Defining IT Resources	2-10
Step 6: Configuring Reconciliation	2-11
Configuring Trusted Source Reconciliation	2-11
Creating the Reconciliation Scheduled Tasks	2-11

Specifying Values for the Scheduled Task Attributes	2-12
Lookup Fields Reconciliation Scheduled Task.....	2-12
User Reconciliation Scheduled Task	2-13
Step 7: Compiling Adapters	2-14
Configuring the Connector for Multiple Installations of the Target System	2-15

3 Testing the Connector

4 Known Issues

A Attribute Mappings Between Oracle Identity Manager and JD Edwards

Index

Preface

Oracle Identity Manager Connector Guide for JD Edwards EnterpriseOne provides information about integrating Oracle Identity Manager with JD Edwards EnterpriseOne.

Note: This is a transitional release following Oracle's acquisition of Thor Technologies. Some parts of the product and documentation still refer to the original Thor company name and Xellerate product name and will be rebranded in future releases.

Audience

This guide is intended for users who want to deploy the Oracle Identity Manager connector for JD Edwards EnterpriseOne.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

Related Documents

For more information, refer to the following documents in the Oracle Identity Manager documentation library:

- *Oracle Identity Manager Release Notes*
- *Oracle Identity Manager Installation and Upgrade Guide for JBoss*
- *Oracle Identity Manager Installation and Upgrade Guide for WebLogic*
- *Oracle Identity Manager Installation and Upgrade Guide for WebSphere*
- *Oracle Identity Manager Administrative and User Console Guide*
- *Oracle Identity Manager Administrative and User Console Customization Guide*
- *Oracle Identity Manager Design Console Guide*
- *Oracle Identity Manager Tools Reference Guide*
- *Oracle Identity Manager Audit Report Developer Guide*
- *Oracle Identity Manager Best Practices Guide*
- *Oracle Identity Manager Globalization Guide*
- *Oracle Identity Manager Glossary of Terms*

The following document is available in the Oracle Identity Manager Connector Pack documentation library:

- *Oracle Identity Manager Connector Framework Guide*

Documentation Updates

Oracle is committed to delivering the best and most recent information available. For information about updates to the Oracle Identity Manager 9.0.3 connector documentation set, visit Oracle Technology Network at

<http://www.oracle.com/technology/documentation/index.html>

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

About the Connector

Oracle Identity Manager automates access rights management, security, and Provisioning of IT resources. Oracle Identity Manager connectors are used to integrate Oracle Identity Manager with third-party applications. The JD Edwards EnterpriseOne Connector is used to integrate Oracle Identity Manager with JD Edwards EnterpriseOne.

Note: Oracle Identity Manager Connectors were referred to as *resource adapters* prior to the acquisition of Thor Technologies by Oracle.

This chapter contains the following sections:

- [Supported Functionality](#)
- [Language Support](#)
- [Reconciliation Module](#)
- [Provisioning Module](#)
- [Files and Directories That Comprise the Connector](#)
- [Determining the Release Number of the Connector](#)

Supported Functionality

The following table lists the functions that are available with this connector.

Function	Type	Description
Create User	Provisioning	Creates a user in the JD Edwards system
Update User	Provisioning	Updates a user in the JD Edwards system
Reset Password	Provisioning	Updates the user password in the JD Edwards system
Enable User	Provisioning	Enables a user in the JD Edwards system
Disable User	Provisioning	Disables a user in the JD Edwards system
Delete User	Provisioning	Deletes a user from the JD Edwards system
Add User Role	Provisioning	Adds a role to a user in the JD Edwards system
Remove User Role	Provisioning	Removes the Role from a user in the JD Edwards system

Function	Type	Description
List Roles of User	Provisioning	Lists the roles of a user in the JD Edwards system
List All Roles	Provisioning	Lists all the roles present in the JD Edwards system
Reconciliation Insert Received	Reconciliation	Inserts information in Oracle Identity Manager about a user that is created in the JD Edwards system
Reconciliation Update Received	Reconciliation	Updates Oracle Identity Manager with information about a user that is updated in the JD Edwards system
Reconciliation Delete Received	Reconciliation	Deletes information in Oracle Identity Manager about a user that is deleted from the JD Edwards system

Language Support

This release of the connector supports only the English language.

Reconciliation Module

This section discusses the elements that the reconciliation module extracts from the target system to construct reconciliation event records. The following are features of these records:

- The default data elements of each reconciliation event record are Organization, Xellerate type, and Role.
- The default labels for the data elements in each reconciliation event record are:
 - Event Linked (for successful reconciliation)
 - No Match Found (for failed reconciliation)

The reconciliation module reconciles the fields listed in the following sections:

- [Lookup Fields Reconciliation](#)
- [User Reconciliation](#)

Lookup Fields Reconciliation

For user reconciliation to work, the following lookup definitions must be available and the lookup values must be reconciled:

- Lookup.JDE.DateSeparationCharacter
- Lookup.JDE.Language
- Lookup.JDE.Roles
- Lookup.JDE.LocalizationCountryCode
- Lookup.JDE.DateFormat
- Lookup.JDE.FastPathCreate
- Lookup.JDE.UniversalTime
- Lookup.JDE.TimeFormat

- Lookup.JDE.DecimalFormatCharector

User Reconciliation

User reconciliation can be divided into the following:

- [Reconciled JD Edwards EnterpriseOne Object Fields](#)
- [Reconciled Xellerate User Fields](#)

Reconciled JD Edwards EnterpriseOne Object Fields

The following fields are reconciled:

- User ID
- Password
- Language
- Date Format
- Date Separation Character
- Localization Country Code
- Universal Time
- Time Format
- IT Resource Type
- Decimal Format Character
- Fast Path Create
- Disable User
- Roles

Reconciled Xellerate User Fields

If trusted source reconciliation is implemented, then the following additional fields are reconciled:

- User ID
- Password
- First Name
- Last Name
- Organization
- Xellerate Type
- Role

Provisioning Module

The following fields must be specified for a provisioning task to work for JD Edwards resource objects:

- User ID
- Password

Note: If you create a user in Oracle Identity Manager and do not assign a role to the user, then the user would not be able to log in to the JD Edwards system.

Files and Directories That Comprise the Connector

The files and directories that comprise this connector are located in the following directory on the installation media:

Enterprise Applications\JDEwards\JDE

These files and directories are listed in the following table.

File in the Installation Media Directory	Description
xml\JDEResourceObject.xml	This XML file contains definitions for the following components of the connector: <ul style="list-style-type: none"> IT resource definition JD Edwards User form Lookup definitions Adapters Resource object Process definition Reconciliation scheduled tasks
xml\JDEXLResourceObject.xml	This XML file contains the configuration for the Xellerate User. You must import this file only if you plan to use the connector in trusted source reconciliation mode.
lib\JDEConnector.jar	This is the connector code JAR file. This file contains all the classes and definitions required for provisioning and reconciliation.
Files in the resources directory	This directory contains files for locale-specific information that is used by the connector. Note: In this release, the JD Edwards connector supports only the English language.
test\TroubleShootUtility.class	This utility is used to test connector functionality.
test\global.properties	This file is used to specify the parameters and settings required to connect to the target system by using the Troubleshoot utility.
test\log.properties	This file is used to specify the log level and the directory in which the log file is to be created when you run the Troubleshoot utility.

Note: The files in the test directory are used only to run tests on the connector.

The "[Step 2: Copying the Connector Files and External Code](#)" section on page 2-1 provides instructions to copy these files into the required directories.

Determining the Release Number of the Connector

To determine the release number of the connector that you have deployed:

1. Extract the contents of the `JDEConnector.jar` file. For a connector that has been deployed, this file is in the following directory:

`OIM_home\xellerate\JavaTasks`

2. Open the `manifest.mf` file in a text editor. The `manifest.mf` file is one of the files bundled inside the `JDEConnector.jar` file.

In the `manifest.mf` file, the release number of the connector is displayed as the value of the `Version` property.

See Also: *Oracle Identity Manager Design Console Guide*

Deploying the Connector

Deploying the connector involves the following steps:

- [Step 1: Verifying Deployment Requirements](#)
- [Step 2: Copying the Connector Files and External Code](#)
- [Step 4: Configuring the Oracle Identity Manager Server](#)
- [Step 5: Importing the Connector XML Files](#)
- [Step 6: Configuring Reconciliation](#)
- [Step 7: Compiling Adapters](#)

This chapter also discusses the following topic:

- [Configuring the Connector for Multiple Installations of the Target System](#)

Step 1: Verifying Deployment Requirements

The following table lists the deployment requirements for the connector.

Item	Requirement
Oracle Identity Manager	Oracle Identity Manager release 8.5.3 or later
Target system	JD Edwards EnterpriseOne 8.12

Step 2: Copying the Connector Files and External Code

The connector files to be copied and the directories to which you must copy them are given in the following table.

File in the Installation Media Directory	Destination Directory
Files in the <code>xml</code> directory	<i>OIM_home</i> \Xellerate\JDE9.0.3\xml
Files in the <code>resources</code> directory	<i>OIM_home</i> \xellerate\connectorResources
Files in the <code>lib</code> directory	<i>OIM_home</i> \Xellerate\JDE9.0.3\lib <i>OIM_home</i> \Xellerate\JavaTasks
Files in the <code>test</code> directory	<i>OIM_home</i> \Xellerate\JDE9.0.3\test

Note: The directory paths given in the first column of this table correspond to the location of the connector files at the following location on the installation media:

Enterprise Applications\JDEdwards\JDE

Refer to the ["Files and Directories That Comprise the Connector"](#) section on page 1-4 for more information about these files.

The target system files to be copied and the directories to which you must copy them are given in the following table.

File on the Target System Server	Destination Directory
The following JAR files from the <i>JDE_installation_dir</i> \E812\DDP\system\classes directory on the JD Edwards EnterpriseOne server:	<i>OIM_home</i> \Xellerate\JavaTasks
<ul style="list-style-type: none"> ■ ApplicationAPIs_JAR.jar ■ Base_JAR.jar ■ BizLogicContainer_JAR.jar ■ BizLogicContainerClient_JAR.jar ■ BusinessLogicServices_JAR.jar ■ castor.jar ■ Connector.jar ■ Generator_JAR.jar ■ JdbjBase_JAR.jar ■ JdbjInterfaces_JAR.jar ■ JdeNet_JAR.jar ■ log4j.jar ■ Metadata.jar ■ MetadataInterface.jar ■ PMApi_JAR.jar ■ Spec_JAR.jar ■ System_JAR.jar ■ xalan.jar ■ xerces.jar ■ xml-apis.jar 	

File on the Target System Server	Destination Directory
<p>Extract the following template files from the <i>JDE_installation_dir\E812\DDP\system\classes\ConnectorSamples.zip</i> file:</p> <ul style="list-style-type: none"> ▪ <i>jdbj.ini.templ</i> ▪ <i>jdeinterop.ini.templ</i> ▪ <i>jdelog.properties</i> <p>Rename <i>jdbj.ini.templ</i> to <i>jdbj.ini</i>, and rename <i>jdeinterop.ini.templ</i> to <i>jdeinterop.ini</i>.</p> <p>Then, copy all three files to the specified destination directory.</p>	<i>OIM_home\Xellerate\JDE9.0.3\Properties</i>
<p>If the EnterpriseOne server is running on Oracle Database, then copy the <i>tnsnames.ora</i> file to the specified destination directory.</p>	<i>OIM_home\Xellerate\JDE9.0.3\Properties</i>

Note: While installing Oracle Identity Manager in a clustered environment, you copy the contents of the installation directory to each node of the cluster. Similarly, you must copy the JAR files listed in this table to the corresponding directories on each node of the cluster.

Changes to Be Made in the Property Files

You must modify the following property files to suit your deployment requirements:

- [jdbj.ini](#)
- [jdeinterop.ini](#)
- [jdelog.properties](#)

Note: The lists of configuration properties included in the following subsections are not comprehensive and include only those properties that are essential for the functioning of the connector. The files allow further customization of the connector functionality with other optional properties. Explicit descriptions and instructions to use the other configuration properties are included in the configuration files.

jdbj.ini

You need to modify the *jdbj.ini* file based on your requirements. This file contains configuration information for JDBj, which provides general database access capabilities for JD Edwards EnterpriseOne.

Note: All property values in this file are case-sensitive.

In the [JDBj-BOOTSTRAP SESSION] section of this file, specify values for the parameters described in the following table:

Property	Sample Value	Description
user	user=JDE	User ID to connect to the target system This is an optional parameter.
password	password=jDPass	Password of the user This is an optional parameter.
environment	environment=PY812	Environment in which the user connects to the JD Edwards EnterpriseOne server The is a required parameter and <i>must</i> be specified in the <code>jdbj.ini</code> file. JD Edwards EnterpriseOne provides the following environments in which a user can access the system: <ul style="list-style-type: none"> ■ Development Environment (DV812) ■ Production Environment (PD812) ■ Prototype Environment (PY812) ■ Pristine Environment (PS812) To access the system in a particular environment, the user needs privileges for that environment.
role	role=*ALL	Role of the connecting user This is an optional parameter.

In the `[JDBj-BOOTSTRAP DATA SOURCE]` section of this file, specify values for the properties specified in the following table.

Property	Description
name	Name of the data source This property is not important for bootstrap connections. However, it shows up in error messages and logs. Sample value: <code>name=System - 812</code>
databaseType	Type of database used by the target system This value depends on the database used by the system. It can be any of the following: <ul style="list-style-type: none"> ■ I = AS/400 ■ O = Oracle ■ S = SQL Server ■ W = UDB ■ M = MSDE Sample value: <code>databaseType=0</code>
server	Name of the EnterpriseOne host server. Applicable for IBM AS/400 and SQL Server. Sample value: <code>server=ibm1</code>
serverPort	EnterpriseOne host server port number. Applicable only for Microsoft SQL Server

Property	Description
database	Database instance name Applicable only for Oracle Database and IBM DB2 UDB Sample value: database=ora10g
physicalDatabase	The physical database (used as library qualifier for IBM AS/400). This is applicable for Microsoft SQL Server and IBM AS/400
owner	Owner of the data source This is applicable for Oracle Database, Microsoft SQL Server, and IBM DB2 UDB. Sample value: owner=SY812
lob	Boolean value that indicates support for LOBs. This is applicable for Oracle Database and IBM AS/400. Sample value: lob=Y
unicode	Boolean value that indicates support for Unicode conversion is supported. This is applicable for Microsoft SQL Server. Sample value: unicode=N

Note: A client of the EnterpriseOne server, also known as the Fat Client, has settings that correspond with the settings in the [JDBj-BOOTSTRAP DATA SOURCE] section in the `jdbj.ini` file. The values in this file must match those specified on the Fat Client. On the Fat Client, these settings are in the [DB SYSTEM SETTINGS] section of the `jde.ini` file.

In the [JDBj-JDBC DRIVERS] section of this file, specify the JDBC driver to connect to EnterpriseOne server. To do this, uncomment the line that specifies the driver for the database you are using. For example, if you are using Oracle Database, uncomment the line that specifies the driver for Oracle Database.

```
ORACLE=oracle.jdbc.driver.OracleDriver
```

In the [JDBj-ORACLE] section of this file, specify the location of the `tnsnames.ora` that you copy from the EnterpriseOne server. The following setting is required only when you use Oracle Database:

```
tns=OIM_home\Xellerate\JDE9.0.3\Properties\tnsnames.ora
```

jdeinterop.ini

The `jdeinterop.ini` file is a configuration file that is used by the JD Edwards connector to enable interoperability between the Oracle Identity Manager and JD Edwards system.

Modify the `jdeinterop.ini` file and specify values for the properties described in the following table:

Section in the File	Property/Sample Value	Description
[OCM]	OCMEnabled=false	Boolean value that specifies whether the connector uses Object Configuration Mapping (OCM) to find the EnterpriseOne server
[JDENET]	serviceNameConnect=6014	Port number to connect to EnterpriseOne server from Oracle Identity Manager
[SERVER]	glossaryTextServer=ibm1:6014	Name and port number to connect to glossary Text server
	codePage=1252	Code page number for a particular language
[SECURITY]	SecurityServer=ibm1	Name of the security server Note: The security server is the same as the EnterpriseOne server.
[INTEROP]	enterpriseServer=ibm1	Name of the EnterpriseOne server
	port=6014	Port number to connect to EnterpriseOne server

jdelog.properties

You can customize this file to enable logging at different levels. To enable logging, you need to specify the properties described in the following table:

Property	Description	Sample Value
FILE	Location of the log file	FILE=\\jderoot.log
LEVEL	Logging level You can specify any of the following values: <ul style="list-style-type: none"> ■ SEVERE ■ WARN ■ APPS ■ DEBUG These values are in decreasing order of priority.	LEVEL=WARN
FORMAT	Logging format This property can be set to: <ul style="list-style-type: none"> ■ APPS ■ TOOLS ■ TOOLS_THREAD In a production environment, this must be set to APPS.	FORMAT=APPS
MAXFILESIZE	Maximum size of the log file in MB	MAXFILESIZE=10MB
MAXBACKUPINDEX	Maximum number of log file backups to be maintained	MAXBACKUPINDEX=20
COMPONENTS	Components for which events are logged in the log file You can specify other components as well. A list of all the components is specified in the template for this file.	COMPONENT=RUNTIME JAS JDBJ

Property	Description	Sample Value
APPEND	Boolean value that specifies that log entries must be appended at the end of the file The value can be TRUE or FALSE.	APPEND=TRUE

Step 4: Configuring the Oracle Identity Manager Server

Configuring the Oracle Identity Manager server involves the following procedures:

- [Changing to the Required Input Locale](#)
- [Clearing Content Related to Connector Resource Bundles from the Server Cache](#)
- [Enabling Logging](#)

Changing to the Required Input Locale

Changing to the required input locale involves installing the required fonts and setting the required input locale. To set the required input locale:

Note: Depending on the operating system used, you may need to perform this procedure differently.

1. Open Control Panel.
2. Double click **Regional Options**.
3. On the Input Locales tab of the Regional Options dialog box, add and switch to the input locale that you want to use.

Clearing Content Related to Connector Resource Bundles from the Server Cache

Whenever you add a new resource bundle file in the `OIM_home\xellerate\connectorResources` directory or make a change in an existing resource bundle file, you must clear content related to connector resource bundles from the server cache.

To clear content related to connector resource bundles from the server cache:

1. In a command window, change to the `OIM_home\xellerate\bin` directory.
2. Enter one of the following commands:

Note: You must perform Step 1 before you perform this step.

If you run the command as follows, then an exception is thrown:

```
OIM_home\xellerate\bin\batch_file_name
```

- On Microsoft Windows
`PurgeCache.bat ConnectorResourceBundle`
- On UNIX
`PurgeCache.sh ConnectorResourceBundle`

In this command, `ConnectorResourceBundle` is one of the content categories that you can remove from the server cache. Refer to the following file for Information about the other content categories:

```
OIM_home\xellerate\config\xlConfig.xml
```

Enabling Logging

When you enable logging, Oracle Identity Manager automatically stores in a log file information about events that occur during the course of provisioning and reconciliation operations. To specify the type of event for which you want logging to take place, you can set the log level to one of the following:

- ALL
This level enables logging for all events.
- DEBUG
This level enables logging of information about fine-grained events that are useful for debugging.
- INFO
This level enables logging of informational messages that highlight the progress of the application at coarse-grained level.
- WARN
This level enables logging of information about potentially harmful situations.
- ERROR
This level enables logging of information about error events that may still allow the application to continue running.
- FATAL
This level enables logging of information about very severe error events that could cause the application to stop functioning.
- OFF
This level disables logging for all events.

The file in which you set the log level and the log file path depend on the application server that you use:

- **For JBoss Application Server**

To enable logging:

1. In the `JBoss_home\server\default\conf\log4j.xml` file, locate the following lines:

```
<category name="XELLERATE">  
  <priority value="log_level"/>  
</category>
```

2. In the second XML code line, replace `log_level` with the log level that you want to set. For example:

```
<category name="XELLERATE">  
  <priority value="INFO"/>  
</category>
```

After you enable logging, log information is written to the following file:

```
JBoss_home\server\default\log\server.log
```

- **For IBM WebSphere:**

To enable logging:

1. Add the following line in the *OIM_home*\xellerate\config\log.properties file:
`log4j.logger.XELLERATE=log_level`
2. In this line, replace *log_level* with the log level that you want to set.

For example:

```
log4j.logger.XELLERATE=INFO
```

After you enable logging, log information is written to the following file:

```
WebSphere_home\AppServer\logs\server_name\startServer.log
```

- **For BEA WebLogic**

To enable logging:

1. Add the following line in the *OIM_home*\xellerate\config\log.properties file:
`log4j.logger.XELLERATE=log_level`
2. In this line, replace *log_level* with the log level that you want to set.

For example:

```
log4j.logger.XELLERATE=INFO
```

After you enable logging, log information is written to the following file:

```
WebLogic_home\user_projects\domains\domain_name\server_name\server_name.log
```

- **For OC4J**

To enable logging:

1. Add the following line in the *oim_home*\xellerate\config\log.properties file:
`log4j.logger.XELLERATE=log_level`
2. In this line, replace *log_level* with the log level that you want to set.

For example:

```
log4j.logger.XELLERATE=INFO
```

After you enable logging, log information is written to the following file:

```
OC4J_home\opmn\logs\default_group~home~default_group~1.log
```

Step 5: Importing the Connector XML Files

To import the connector XML file into Oracle Identity Manager:

1. Open the Oracle Identity Manager Administrative and User Console.

2. Click the **Deployment Management** link on the left navigation bar.
3. Click the **Import** link under Deployment Management. A dialog box for locating files is displayed.
4. Locate and open the `JDEResourceObject.xml` file, which is in the `OIM_home\Xellerate\JDE9.0.3\xml` directory. Details of this XML file are shown on the File Preview page.
5. Click **Add File**. The Substitutions page is displayed.
6. Click **Next**. The Confirmation page is displayed.
7. Click **Next**. The Provide IT Resource Instance Data page for the `JDE IT Resource IT` resource is displayed.
8. Specify values for the parameters of the `JDE IT Resource IT` resource. Refer to the table in the "[Defining IT Resources](#)" section on page 2-10 for information about the values to be specified.
9. Click **Next**. The Provide IT Resource Instance Data page for a new instance of the `JDE IT Resource` type is displayed.
10. Click **Skip** to specify that you do not want to define another IT resource. The Confirmation page is displayed.
11. Click **View Selections**. The contents of the XML file are displayed on the Import page. You may see a Cross-shaped icon along with some nodes. Remove these nodes by right-clicking each node and then selecting **Remove**.
12. Click **Import**. The connector XML file is imported into Oracle Identity Manager.
13. If you plan to use the connector in trusted source reconciliation mode, then perform the same procedure to import the `JDEConnectorXLResourceObject.xml` file. This file is in the `OIM_home\Xellerate\JDE9.0.3\xml` directory.

Defining IT Resources

You must specify values for the `JDE IT Resource IT` resource parameters listed in the following table:

Parameter	Description
User	User ID of the user connecting to EnterpriseOne server
Password	Password of the user connecting to EnterpriseOne Server
Environment	Environment of the connecting user Sample value: DV812
Role	Role of the user connecting to EnterpriseOne Server Sample value: *ALL
ProxyUser	User ID of the system user in EnterpriseOne server
ProxyUserPassword	Password of the system user in EnterpriseOne server
TimeStamp	Timestamp for the first reconciliation run, the timestamp value is not set. For subsequent rounds of reconciliation, the time at which the previous round of reconciliation was completed is stored in this parameter. The following is sample timestamp value: Jun 01, 2006 at 10:00:00 GMT+05:30

Step 6: Configuring Reconciliation

Configuring reconciliation involves the following steps:

- [Configuring Trusted Source Reconciliation](#)
- [Creating the Reconciliation Scheduled Tasks](#)

Configuring Trusted Source Reconciliation

Note: Perform this step of the procedure only if you want to configure trusted source reconciliation. Only one connector can be configured for trusted source reconciliation. If you import the `JDEConnectorXLResourceObject.xml` file while you have another trusted source configured, then both connector reconciliations would stop working.

Refer to *Oracle Identity Manager Connector Framework Guide* for conceptual information about reconciliation configurations.

To configure trusted source reconciliation, you must first import the XML file for trusted source reconciliation as follows:

1. Open the Oracle Identity Manager Administrative and User Console.
2. Click the **Deployment Management** link on the left navigation bar.
3. Click the **Import** link under Deployment Management. A dialog box for locating files is displayed.
4. Locate and open the `JDEConnectorXLResourceObject.xml` file, which is in the `OIM_home\Xellerate\JDE9.0.3\xml` directory. Details of this XML file are shown on the File Preview page.
5. Click **Add File**. The Substitutions page is displayed.
6. Click **Next**. The Confirmation page is displayed.
7. Click **Import**.
8. In the message that is displayed, click **Import** to confirm that you want to import the XML file and then click **OK**.

Then, set the value of the `isTrustedSource` reconciliation scheduled task attribute to `True` while performing the procedure described in the following section.

Creating the Reconciliation Scheduled Tasks

1. Open the Oracle Identity Manager Design Console.
2. Expand the `Xellerate Administration` folder.
3. Select **Task Scheduler**.
4. Click **Find**. The details of the predefined scheduled tasks are displayed on two different tabs.
5. For the first scheduled task, enter a number in the **Max Retries** field. This number represents the number of times Oracle Identity Manager must attempt to complete the task before assigning the `ERROR` status to the task.
6. Ensure that the **Disabled** and **Stop Execution** check boxes are not selected.

7. In the Start region, double-click the **Start Time** field. From the date-time editor that is displayed, select the date and time at which you want the task to run.
8. In the Interval region, set the following schedule parameters:
 - To set the task to run on a recurring basis, select the **Daily, Weekly, Recurring Intervals, Monthly, or Yearly** option. If you select the **Recurring Intervals** option, then you must also specify the time interval at which you want the task to run on a recurring basis.
 - To set the task to run only once, select the **Once** option.
9. Provide values for the attributes of the scheduled task. Refer to the "[Specifying Values for the Scheduled Task Attributes](#)" section on page 2-12 for information about the values to be specified.
10. Click **Save**. The scheduled task is created. The `INACTIVE` status is displayed in the **Status** field, because the task is not currently running. The task is run at the date and time that you set in Step 7.
11. Repeat Steps 5 through 10 to create the second scheduled task.

Specifying Values for the Scheduled Task Attributes

This section provides information about the values to be specified for the following scheduled tasks:

- [Lookup Fields Reconciliation Scheduled Task](#)
- [User Reconciliation Scheduled Task](#)

Lookup Fields Reconciliation Scheduled Task You must specify values for the following attributes of the lookup fields reconciliation scheduled task.

Note: Attribute values are predefined in the connector XML file that you import. Specify values only for those attributes that you want to change.

Attribute	Description	Sample Value
Language	Code of the language to be used in the lookup reconciliation	en
Country	Code of the country to be used in the lookup reconciliation	us
IT Resource	Name of the IT resource for setting up a connection to JD Edwards	JDE IT Resource
isRoleLookup	Specifies whether or not to perform a lookup for the Role value during reconciliation The value can be <code>true</code> or <code>false</code> .	<code>true</code>
isDateSeparationCharacterLookup	Specifies whether or not to perform a lookup for the Date Separation Character value during reconciliation The value can be <code>true</code> or <code>false</code> .	<code>true</code>
isLanguageLookup	Specifies whether or not to perform a lookup for the Language value during reconciliation The value can be <code>true</code> or <code>false</code> .	<code>true</code>

Attribute	Description	Sample Value
isLocalizationCountryCodeLookup	Specifies whether or not to perform a lookup for the Localization Country Code value during reconciliation The value can be <code>true</code> or <code>false</code> .	<code>true</code>
isDateFormatLookup	Specifies whether or not to perform a lookup for the Date Format value during reconciliation The value can be <code>true</code> or <code>false</code> .	<code>true</code>
isUniversalTimeLookup	Specifies whether or not to perform a lookup for the Universal Time value during reconciliation The value can be <code>true</code> or <code>false</code> .	<code>true</code>
isDecimalFormatCharacterLookup	Specifies whether or not to perform a lookup for the Decimal Format Character value during reconciliation The value can be <code>true</code> or <code>false</code> .	<code>true</code>
isTimeFormatLookup	Specifies whether or not to perform a lookup for the Time Format value during reconciliation The value can be <code>true</code> or <code>false</code> .	<code>true</code>

After you specify values for the task attributes, proceed to Step 10 of the procedure to create scheduled tasks.

User Reconciliation Scheduled Task You must specify values for the following attributes of the user reconciliation scheduled task.

Note: Attribute values are predefined in the connector XML file that you import. Specify values only for those attributes that you want to change.

Attribute	Description	Sample Value
Organization	Default organization assigned to a new user	Xellerate Users
Xellerate Type	Default type assigned to a new user	End-User Administrator
Role	Default role assigned to a new user	Consultant
ITResource	Name of the IT Resource for setting up a connection with JD Edwards	JDE IT Resource
ResourceObject	Name of the resource object that is used for	JDE Resource Object
isTrustedSource	Specifies whether or not trusted source reconciliation is to be performed If it is set to <code>true</code> , then the target system is treated as a trusted source. If it is set to <code>false</code> , then the target system is treated as a nontrusted target. By default, the value is <code>false</code> .	<code>false</code>
Password	Default dummy password	dummy

Attribute	Description	Sample Value
XLDeleteUsersAllowed	Specifies whether or not users are to be deleted in Oracle Identity Manager during user reconciliation	false

After you specify values for the task attributes, proceed to Step 10 of the procedure to create scheduled tasks.

Step 7: Compiling Adapters

The following adapters are imported into Oracle Identity Manager when you import the `JDEResourceObject.xml` file:

- Enable and Disable User
- JDE Delete User
- Modify Password
- PrePopulate JDE Form
- JDE Remove Role
- JDE Modify User
- JDE Create User
- JDE Add Role

You must compile these adapters before you can use them to provision accounts on the target system.

To compile adapters by using the Adapter Manager form:

1. Open the Adapter Manager form.
2. To compile all the adapters that you import into the current database, select **Compile All**. To compile multiple (but not all) adapters, select the adapters you want to compile. Then, select **Compile Selected**.

Note: Click **Compile Previously Failed** to recompile only those adapters that were not compiled successfully. Such adapters do not have an OK compilation status.

3. Click **Start**. Oracle Identity Manager compiles the selected adapters.
4. If Oracle Identity Manager is installed in a clustered environment, then copy the compiled adapters from the `OIM_home\xellerate\Adapter` directory to the same directory on each of the other nodes of the cluster. If required, overwrite the adapter files on the other nodes.

To view detailed information about an adapter:

1. Highlight the adapter in the Adapter Manager form.
2. Double-click the row header of the adapter, or right-click the adapter.
3. Select **Launch Adapter** from the shortcut menu that is displayed. Details of the adapter are displayed.

Note: To compile one adapter at a time, use the Adapter Factory form. Refer to *Oracle Identity Manager Tools Reference Guide* for information about using the Adapter Factory and Adapter Manager forms.

Configuring the Connector for Multiple Installations of the Target System

Note: Perform this procedure only if you want to configure the connector for multiple installations of JD Edwards. Refer to *Oracle Identity Manager Design Console Guide* for detailed instructions on performing each step of this procedure.

To configure the connector for multiple installations of the target system:

1. Create and configure one resource object for each target system installation. The Resource Objects form is in the Resource Management folder. The `JDE_Resource_Object` resource object is created when you import the connector XML file. You can use this resource object as the template for creating the remaining resource objects.
2. Create and configure one IT resource for each resource object. The IT Resources form is in the Resource Management folder. The `JDE_IT_Resource` IT resource is created when you import the connector XML file. You can use this IT resource as the template for creating the remaining IT resources, of the same resource type.
3. Create and configure one process definition for each resource object.
The Process Definition form is in the Process Management folder. The `JDE_Process` process definition is created when you import the connector XML file. You can use this process definition as the template for creating the remaining process definitions. While creating each process definition, the following steps that you must perform are specific to this procedure:
 - a. From the **Object Name** lookup field, select the resource object that you create in Step 1.
 - b. While mapping the adapter variables for the IT Resource data type, ensure that you select the IT resource that you create in Step 2 from the **Qualifier** list. Design one process form for each process definition.
4. The Form Designer form is in the Development Tools folder. The following process forms are created when you import the connector XML file:
 - `UD_JDE` (parent form)
 - `UD_JDEROL` (child form for multivalued attributes)

You can use these process forms as templates for creating the remaining process forms. While creating the process forms, from the Object Name lookup field, select the resource object that you create in Step 1.
5. Configure reconciliation for each target system installation. Refer to the "[Step 6: Configuring Reconciliation](#)" section on page 2-11 for instructions. Note that only the values of the following attributes are to be changed for each reconciliation scheduled task:
 - `ITResource`

- ResourceObject
- isTrustedSource

Set the `isTrustedSource` attribute to `True` for the JD Edwards installation that you want to designate as a trusted source. You can designate either a single or multiple installations of JD Edwards as the trusted source. For the remaining JD Edwards installations, set this attribute to `False`.

6. If required, modify the fields to be reconciled for the Xellerate User resource object. When you use the Administrative and User Console to perform provisioning, you can specify the IT resource corresponding to the JD Edwards installation to which you want to provision the user.

Testing the Connector

After you deploy the connector, you must test it to ensure that it functions as expected. This chapter discusses procedure to test connector.

You can use the testing utility to identify the cause of problems associated with connecting to the target system and performing basic operations on the target system

To use the utility:

1. Specify the required values in the `global.properties` file. This file is in the `OIM_home\Xellerate\JDE 9.0.3\test` directory. The following table describes the sections of this file in which you must provide information for running the tests.

Section	Description
Server Information	Connection parameters required to connect to the target system
Create User Parameter	Field information required to create or delete a user profile
Modify User Parameter	Field information required to modify a user profile
Password Reset	Field information required to reset a password for a user profile
Modify Enable / Disable User Parameters	Field information required to enable or disable a user profile
Add Role to User Parameters	Field information required add a role to a user profile
Remove Role from User Parameters	Field information required remove a role from a user profile
Reconcile Users	The From Date timestamp The To Date is set to the current date and time by default.

2. Add all the JAR files mentioned in the "[Step 2: Copying the Connector Files and External Code](#)" section on page 2-1 to the CLASSPATH environment variable.

Add all the files in the `OIM_home\Xellerate\JDE9.0.3\Properties` directory to the CLASSPATH environment variable.

3. In the `log.properties` file in the same directory:
 - a. In the following parameter, set the path of the directory in which you want to create the log files:

```
log4j.appender.logfile.File=log_file_path
```

Here, *log_file_path* is the path of the directory in which you want to create the log file.

b. Specify any one of the following log levels:

- DEBUG
- INFO
- WARN
- ERROR
- FATAL

For example, if the log level for DEBUG is to be enabled, then you must add the following entry file:

```
log4j.logger.ADAPTERS.ACTIVEDIRECTORY=DEBUG
```

4. Create an ASCII-format copy of the `global.properties` file as follows:

a. In a command window, change to the following directory:

```
OIM_home\Xellerate\JDE9.0.3\test
```

b. Enter the following command:

```
native2ascii global.properties troubleshoot.properties
```

The `troubleshoot.properties` file is created when you run the `native2ascii` command. The contents of this file are an ASCII-format copy of the contents of the `global.properties` file.

5. Perform the following tests:

■ Enter the following command to create a user:

```
java -DTproperties=OIM_home/test/troubleshoot.properties  
-Dlog4j.configuration=file:/OIM_home/test/log.properties  
TroubleShootUtility C
```

■ Enter the following command to delete a user:

```
java -DTproperties=OIM_home/test/troubleshoot.properties  
-Dlog4j.configuration=file:/OIM_home/test/log.properties  
TroubleShootUtility D
```

■ Enter the following command to modify a user:

```
java -DTproperties=OIM_home/test/troubleshoot.properties  
-Dlog4j.configuration=file:/OIM_home/test/log.properties  
TroubleShootUtility M
```

■ Enter the following command to reset the password of a user:

```
java -DTproperties=OIM_home/test/troubleshoot.properties  
-Dlog4j.configuration=file:/OIM_home/test/log.properties  
TroubleShootUtility P
```

■ Enter the following command to enable and disable a user:

```
java -DTproperties=OIM_home/test/troubleshoot.properties  
-Dlog4j.configuration=file:/OIM_home/test/log.properties  
TroubleShootUtility ED
```

-
- Enter the following command to add a role to user:

```
java -DTproperties=OIM_home/test/troubleShoot.properties  
-Dlog4j.configuration=file:/OIM_home/test/log.properties  
TroubleShootUtility AUR
```

- Enter the following command to remove a role from user:

```
java -DTproperties=OIM_home/test/troubleShoot.properties  
-Dlog4j.configuration=file:/OIM_home/test/log.properties  
TroubleShootUtility RUR
```

- Enter the following command to test reconcile users:

```
java -DTproperties=OIM_home/test/troubleShoot.properties  
-Dlog4j.configuration=file:/OIM_home/test/log.properties  
TroubleShootUtility R
```

Known Issues

The following are known issues associated with this release of the connector:

- The target system does not accept a user ID that is longer than 10 characters. During provisioning, if you specify a user ID that is longer than 10 characters, then the first 10 characters are the used to create the user ID on the target system.

This limitation also applies to the password that you specify for the new user.

- While reconciling users from the target system, the User ID value is used to populate the First Name and Last Name fields of the Xellerate User account in Oracle Identity Manager.
- This connector does not support secure connection between Oracle Identity Manager and the target system because the interoperability solution used in building the connector does not support this type of connection.

The only way to secure communication between Oracle Identity Manager and the target system is to place both on a secure network.

- Linking in Oracle Identity Manager is asynchronous. If a user is created in the target JD Edwards system, and the same user is then disabled in the JD Edwards system, then that user might not be disabled in Oracle Identity Manager in the first reconciliation run. The user will be disabled in Oracle Identity Manager in the second reconciliation run.

Attribute Mappings Between Oracle Identity Manager and JD Edwards

The following table discusses attribute mappings between Oracle Identity Manager and JD Edwards.

Oracle Identity Manager Attribute	JD Edwards Attribute	Description
sUserId	USER	Login ID
sLanguagePreference	LNGP	Language preference
sDateFormat	FRMT	Date format character
sDateSeparator	DSEP	Date separation character
sDecimalFormat	DECF	Decimal format character
sCountry	CTR	Country
sUniversalTime	UTCTIME	Universal time
sTimeFormat	UTCTIME	Time format
sFastPath	FSTP	Fast path
EnabledUser	EUSER	Enable or disable user This is a Boolean value that toggles the enabling and disabling of the user.
RoleName	FRROLE	Name of the role
EffectiveDate	EFFDATE	Effective date of the role
ExpirationDate	EXPIRDATE	Expiration date of the role
IncludeAll	FUROLE1	Include a role or privilege in the *ALL role

Index

A

Adapter Factory form, 2-15
Adapter Manager form, 2-14
adapters, compiling, 2-14
additional files, 2-2
Administrative and User Console, 2-9, 2-11
attributes
 lookup fields reconciliation scheduled task, 2-12
 user reconciliation scheduled task, 2-13
attributes mappings, A-1

C

changing input locale, 2-7
clearing server cache, 2-7
compiling adapters, 2-14
configuring
 connector for multiple installations of the target system, 2-15
 Oracle Identity Manager server, 2-7
 reconciliation, 2-11
connector files and directories
 copying, 2-1
 description, 1-4
 destination directories, 2-1
 installation media file, 1-4, 2-2
connector release number, determining, 1-5
connector testing, 3-1
connector XML files
 See XML files
creating scheduled tasks, 2-11

D

defining
 IT resources, 2-10
 scheduled tasks, 2-11
deployment requirements, 2-1
Design Console, 2-11
determining release number of connector, 1-5

E

enabling logging, 2-8
external code files, 2-2

F

files
 additional, 2-2
 external code, 2-2
files and directories of the connector
 See connector files and directories
functionality supported, 1-1
functions available, 1-1

G

globalization features, 1-2

I

importing connector XML files, 2-9
input locale changing, 2-7
input locale, changing, 2-7
issues, 4-1
IT resources
 defining, 2-10
 JDE IT Resource, 2-10, 2-12
 parameters, 2-10

L

limitations, 4-1
logging enabling, 2-8
lookup fields reconciliation, 1-2
lookup fields reconciliation scheduled task, 2-12

M

mapping between attributes of target system and
 Oracle Identity Manager, A-1
multilanguage support, 1-2

O

Oracle Identity Manager Administrative and User Console, 2-9, 2-11
Oracle Identity Manager Design Console, 2-11
Oracle Identity Manager server, configuring, 2-7

P

- parameters of IT resources, 2-10
- process tasks, 1-1
- provisioning
 - fields, 1-3
 - functions, 1-1
 - module, 1-3

R

- reconciliation
 - configuring, 2-11
 - functions, 1-1
 - lookup fields, 1-2
 - module, 1-2
 - trusted source, 2-11
 - trusted source mode, 1-4
 - user, 1-3
- release number of connector, determining, 1-5
- requirements for deploying, 2-1

S

- scheduled tasks
 - attributes, 2-12
 - defining, 2-11
 - lookup fields reconciliation, 2-12
 - user reconciliation, 2-13
- server cache, clearing, 2-7
- supported
 - functionality, 1-1
 - languages, 1-2
 - releases of Oracle Identity Manager, 2-1
 - target systems, 2-1

T

- target system, multiple installations, 2-15
- target systems
 - supported, 2-1
- testing the connector, 3-1
- trusted source reconciliation, 1-4, 2-11

U

- user attribute mappings, A-1
- user reconciliation, 1-3
- user reconciliation scheduled task, 2-13

X

- XML files
 - copying, 2-1
 - description, 1-4
 - for trusted source reconciliation, 1-4
 - importing, 2-9