

Oracle® VM

Manager User's Guide

Release 2.1

E10901-04

June 2009

Oracle VM Manager User's Guide, Release 2.1

E10901-04

Copyright © 2008, 2009, Oracle and/or its affiliates. All rights reserved.

Primary Author: Faxin Hou

Contributing Author: Alison Holloway, Huili Wang, Prakash Jashnani

Contributor: Adam Hawley, Julien Sero, Honglin Su, Carol Tian, Charles Wang, Xiaodong Yang, Yanbing Zheng

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	ix
Audience	ix
Documentation Accessibility	ix
Related Documents	x
Conventions	x
 What's New in Oracle VM Manager	xi
New Features in Release 2.1.5	xi
New Features in Release 2.1.2	xi
New Features in Release 2.1.1	xii
 1 Overview of Oracle VM Manager	
1.1 What Is Virtualization?	1-1
1.2 Why Virtualize?	1-1
1.3 Introduction to Oracle VM	1-2
1.4 Configuration of Oracle VM Manager	1-3
1.5 Roles in Oracle VM Manager	1-5
1.6 Main Features of Oracle VM Manager	1-6
 2 Getting Started with Oracle VM Manager	
2.1 Registering an Account with Oracle VM Manager	2-1
2.2 Logging In to Oracle VM Manager	2-2
2.3 Using the Wizard to Create a Server Pool	2-3
 3 Managing Server Pools	
3.1 Designing a Server Pool	3-1
3.2 Creating a Server Pool	3-3
3.3 Editing a Server Pool	3-6
3.3.1 Editing Server Pool	3-7
3.3.2 Editing Server Pool Servers	3-8
3.3.3 Editing Server Pool Users	3-8
3.4 Searching Server Pools	3-8
3.5 Restoring a Server Pool	3-8
3.6 Enabling High Availability (HA)	3-9

3.7	Deleting a Server Pool	3-11
-----	------------------------------	------

4 Managing Servers

4.1	Adding a Server	4-1
4.2	Viewing and Editing a Server	4-2
4.3	Restarting a Server	4-4
4.4	Shutting Down a Server	4-4
4.5	Deleting a Server	4-4

5 Managing Resources

5.1	Importing Virtual Machine Templates	5-2
5.1.1	Importing a Virtual Machine Template.....	5-3
5.1.1.1	Selecting from the Server Pool.....	5-3
5.1.1.2	Downloading from External Source	5-4
5.1.1.3	Converting a Linux or Windows Host to a Virtual Machine Template (P2V)	5-5
5.1.2	Statuses of Virtual Machine Templates	5-6
5.1.3	Reimporting a Virtual Machine Template	5-6
5.1.4	Approving the Imported Virtual Machine Template	5-6
5.1.5	Editing a Virtual Machine Template.....	5-7
5.1.6	Deleting a Virtual Machine Template.....	5-7
5.2	Importing Virtual Machine Images	5-7
5.2.1	Importing a Virtual Machine Image	5-7
5.2.1.1	Selecting from the Server Pool.....	5-8
5.2.1.2	Downloading from External Source	5-9
5.2.1.3	Converting a Linux or Windows Host to a Virtual Machine (P2V)	5-10
5.2.2	Statuses of Virtual Machine Images.....	5-12
5.2.3	Reimporting a Virtual Machine Image	5-12
5.2.4	Approving the Imported Virtual Machine Image.....	5-12
5.2.5	Editing a Virtual Machine Image	5-12
5.2.6	Deleting a Virtual Machine Image	5-12
5.3	Importing ISO Files.....	5-13
5.3.1	Importing an ISO File.....	5-13
5.3.1.1	Selecting from the Server Pool.....	5-13
5.3.1.2	Downloading from External Source	5-14
5.3.2	Statuses of ISO Files.....	5-14
5.3.3	Reimporting an ISO File	5-15
5.3.4	Approving the Imported ISO File	5-15
5.3.5	Changing Status of an ISO File	5-15
5.3.6	Deleting an ISO File.....	5-15
5.4	Managing Shared Virtual Disks.....	5-16
5.4.1	Creating a Shared Virtual Disk.....	5-16
5.4.2	Searching a Shared Virtual Disk.....	5-16
5.4.3	Deleting a Shared Virtual Disk	5-17

6 Managing Virtual Machines

6.1	Overview of Virtual Machines	6-1
-----	------------------------------------	-----

6.1.1	Virtual Machine Types.....	6-2
6.1.2	Virtual Machine Statuses.....	6-2
6.1.2.1	Creating.....	6-2
6.1.2.2	Initializing and Running	6-3
6.1.2.3	Pausing, Paused and Unpausing	6-3
6.1.2.4	Suspending, Suspended and Resuming.....	6-3
6.1.2.5	Shutting Down and Powered Off.....	6-3
6.1.2.6	Saving	6-3
6.1.2.7	Cloning.....	6-3
6.1.2.8	Migrating	6-3
6.1.2.9	Error.....	6-3
6.1.3	Life Cycle Management of a Virtual Machine.....	6-4
6.1.4	Viewing Virtual Machine Error Logs.....	6-6
6.2	Supported Guest Operating Systems.....	6-7
6.3	Creating a Virtual Machine	6-7
6.3.1	Creating a New Virtual Machine Based on Virtual Machine Template	6-8
6.3.2	Creating a New Virtual Machine from Installation Media.....	6-10
6.3.3	Creating a Network Bootable (PXE boot) Virtual Machine.....	6-13
6.4	Starting and Shutting Down a Virtual Machine.....	6-15
6.4.1	Starting a Virtual Machine	6-15
6.4.2	Shutting Down a Virtual Machine	6-15
6.4.3	Pausing and Unpausing a Virtual Machine.....	6-16
6.4.4	Suspending and Resuming a Virtual Machine.....	6-16
6.5	Connecting to a Virtual Machine's Console.....	6-17
6.5.1	Installing the Console Plug-In	6-17
6.5.2	Logging In to a Virtual Machine	6-17
6.6	Viewing Details of a Virtual Machine.....	6-19
6.7	Editing Virtual Machine Configuration.....	6-19
6.7.1	General	6-20
6.7.2	Network	6-22
6.7.3	Storage.....	6-23
6.7.4	Preferred Server	6-26
6.7.5	Profiles.....	6-27
6.8	Reproducing Virtual Machines.....	6-29
6.8.1	Deploying a Virtual Machine.....	6-29
6.8.2	Cloning Virtual Machines.....	6-30
6.8.3	Saving a Virtual Machine as a Template	6-31
6.9	Migrating a Virtual Machine	6-32
6.10	Deleting a Virtual Machine.....	6-32
6.10.1	Deleting a Virtual Machine in "Powered Off" or "Error" Status	6-32
6.10.2	Deleting a Virtual Machine Stuck in a Certain Status	6-32

7 Managing Users and Groups

7.1	The Default Account.....	7-1
7.2	Managing Users	7-1
7.2.1	Creating a User.....	7-1
7.2.2	Viewing Details	7-2

7.2.3	Editing a User.....	7-3
7.2.4	Changing a Role.....	7-3
7.2.5	Deleting a User.....	7-4
7.3	Managing Groups.....	7-4
7.3.1	Default Groups.....	7-4
7.3.2	Creating a Group	7-4
7.3.3	Adding a User to a Group	7-4
7.3.4	Editing a Group.....	7-5
7.3.5	Deleting a Group.....	7-5

A Preparing Virtual Machines For Importing

B Backing Up and Restoring Oracle VM Manager

B.1	Backing Up Oracle VM Manager.....	B-1
B.2	Restoring Oracle VM Manager	B-2

C Web Services API

C.1	Web Services API.....	C-1
C.2	Creating a Web Service Client.....	C-3
C.2.1	Creating a Proxy Class in Java	C-3
C.2.1.1	Using Oracle JDeveloper	C-3
C.2.1.2	Using wsimport	C-5
C.2.2	Creating a Proxy Class in Python.....	C-6
C.3	Authentication and Security.....	C-7
C.4	Web Service Locations.....	C-8
C.5	Web Services	C-9
C.5.1	LifecycleService.....	C-9
C.5.2	ResourceService	C-10
C.5.3	PluginService	C-11
C.5.4	ServerPoolService	C-12
C.5.5	VirtualMachineService.....	C-13
C.5.6	AdminService.....	C-14

D Troubleshooting

D.1	Log Files	D-1
D.2	Cannot Log In to Oracle VM Manager	D-2
D.3	Cannot Create a Virtual Machine from Installation Media	D-2
D.4	No Sufficient Space in Repository for Creating a Virtual Machine.....	D-3
D.5	The Virtual Machine Stuck in Certain Status.....	D-4
D.6	The Status of the Virtual Machine Is "Error".....	D-4
D.6.1	Error: HVM guest support is unavailable: is VT/AMD-V supported by your CPU and enabled in your BIOS?	D-5
D.6.2	Failed:<Exception: cannot find host server for vm('/OVS/running_pool/vm_name')>.	D-5
D.6.3	Failed:<Exception: Could not find '/OVS/running_pool/vm_name' in any storage repository.>	D-6

D.6.4	Failed:<Exception: /opt/ovs-agent-2.2/utls/rcp.py /OVS/running_pool/vm_name/ root@example.com:/OVS/running_pool/vm_name password=>encounter 'permission denied'! > D-6	
D.6.5	Failed:<Exception: return=>failed:<Exception: xm create '/OVS/running_pool/vm_ name/vm.cfg'=>Error: Domain 'vm_name' already exists with ID '6' >> D-6	
D.6.6	Failed:<Exception: vm('/OVS/running_pool/vm_name') status ('RUNNING') not in ('DOWN', 'ERROR')> D-6	
D.6.7	Failed:<Exception: no server selected to run vm('/OVS/running_pool/vm_name') memory=512> D-7	
D.6.8	Failed:<Exception: return=>failed:<Exception: xm create '/OVS/running_pool/vm_ name/vm.cfg'=>Error: Device 0 (vif) could not be connected. Could not find bridge device null >> D-7	
D.6.9	Failed:<Exception: no pxe bootable vif found.>	D-7
D.6.10	Failed:<Exception: failed:<Exception: virt-install --paravirt --name=vm_name --ram=256 --vcpus=1 --file /OVS/running_pool/vm_name/System.img --file-size=1 --vnc --vnclisten=0.0.0.0 --vncpasswd=/tmp/tmp01TOh4 --noautoconsole --location=nfs:host:/mnt=>mount: can't get address for host umount: /var/lib/xen/xennfs.mkvX0Q: not mounted ERROR: Unable to mount NFS location! >> D-7	
D.6.11	winxp_build failed:<Exception: return=>failed:<NameError: global name 'xen_ handle_vif_qos' is not defined>> D-8	
D.7	Cannot Access Virtual Machine Console	D-8
D.8	Cannot Perform Live Migration	D-8
D.9	Cannot Change CD in the Virtual Machine	D-8
D.10	Cannot Import External Resources	D-8
D.11	Remote Host Identification Error in Server Pool.....	D-9

E Third Party Licenses

E.1	Apache XML-RPC.....	E-1
E.1.1	Apache XML-RPC Software License.....	E-1
E.2	Third-Party Products Included with Sun Microsystems Products.....	E-4
E.2.1	CS CodeViewer v1.0	E-4
E.2.2	DES and 3xDES	E-5
E.2.3	Crimson v1.1.1.....	E-5
E.2.4	NSIS 1.0j	E-6
E.2.5	Some Portions licensed from IBM	E-7
E.2.6	Portions Copyright Eastman Kodak Company 1992.....	E-7
E.2.7	Lucida	E-7
E.2.8	Portions licensed from Taligent, Inc.	E-7
E.2.9	Additionally for JRE/JDK 1.5 / 5.0.....	E-7

Glossary

Index

Preface

This preface includes the following topics:

- [Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Conventions](#)

Audience

This document is intended for users of Oracle VM Manager.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Deaf/Hard of Hearing Access to Oracle Support Services

To reach Oracle Support Services, use a telecommunications relay service (TRS) to call Oracle Support at 1.800.223.1711. An Oracle Support Services engineer will handle technical issues and provide customer support according to the Oracle service request process. Information about TRS is available at

<http://www.fcc.gov/cgb/consumerfacts/trs.html>, and a list of phone numbers is available at <http://www.fcc.gov/cgb/dro/trsphonebk.html>.

Related Documents

For more information, see the following documents in the Oracle VM Release 2.1 documentation set:

- *Oracle VM Server Quick Start Guide*
- *Oracle VM Manager Installation Guide*
- *Oracle VM Manager Release Notes*
- *Oracle VM Server User's Guide*
- *Oracle VM Server Installation Guide*
- *Oracle VM Server Release Notes*
- *Oracle VM Managing Oracle Enterprise Linux with Oracle Enterprise Manager 10g Grid Control Guide for Linux*
- *Oracle VM Manager Web Services API Reference*

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

What's New in Oracle VM Manager

This preface introduces the new features and enhancements of Oracle VM Manager in the 2.1.x releases since the initial release version of 2.1. This information is useful to users who have used a previous release of Oracle VM Manager.

New Features in Release 2.1.5

The new features and enhancements in Oracle VM Manager Release 2.1.5 include:

Web Services API

A Web services Application Programming Interface (API) to enable integration of third party products with Oracle VM Manager. See [Appendix C, "Web Services API"](#).

Server Pool Management UI Enhancements

The server pool management pages in the user interface have been improved. See [Chapter 3, "Managing Server Pools"](#).

New Features in Release 2.1.2

The new features and enhancements in Oracle VM Manager Release 2.1.2 include:

Server Pool Wizard

If it is the first time you log in to Oracle VM Manager after installation, you are prompted to follow the Wizard to create a server pool containing only one physical server which will act as the Server Pool Master, the Virtual Machine Server, and the Utility Server. See [Section 2.3, "Using the Wizard to Create a Server Pool"](#).

High Availability (HA) for Server Pools and Virtual Machine Servers

In Release 2.1.2, various levels of high availability is implemented.

You can enable high availability for server pools and virtual machines when creating them. See [Section 3.6, "Enabling High Availability \(HA\)"](#) and [Section 6.3, "Creating a Virtual Machine"](#).

You can also enable high availability when importing virtual machine templates and images. See [Section 5.1, "Importing Virtual Machine Templates"](#) and [Section 5.2, "Importing Virtual Machine Images"](#).

You can choose to migrate the running virtual machines when restarting, shutting down, or deleting an Oracle VM Server. See [Section 4.3, "Restarting a Server"](#), [Section 4.4, "Shutting Down a Server"](#), and [Section 4.5, "Deleting a Server"](#).

Virtual Machine Conversions, V2V and P2V

Oracle VM allows you to convert a VMware virtual machine to an Oracle VM virtual machine (known as V2V), or to convert a Linux host to an Oracle VM virtual machine or template (known as P2V).

To convert a VMware virtual machine to an Oracle VM virtual machine (V2V), see [Section 5.2.1, "Importing a Virtual Machine Image"](#).

To convert a Linux host to an Oracle VM virtual machine or template (P2V), see [Section 5.1.1.3, "Converting a Linux or Windows Host to a Virtual Machine Template \(P2V\)"](#) and [Section 5.2.1.3, "Converting a Linux or Windows Host to a Virtual Machine \(P2V\)"](#).

Keyboard Layout Selection

Oracle VM Manager provides a keyboard selection when you create a virtual machine from installation media, or when you change configurations of a virtual machine. See [Section 6.3.2, "Creating a New Virtual Machine from Installation Media"](#) and [Section 6.7.5, "Profiles"](#).

Rate Limit of Virtual Network Interface (VIF)

You can set up the rate limit of a virtual network interface (VIF) to customize the network traffic threshold. See [Section 6.7.2, "Network"](#).

Priority Class of Virtual Disk

The enhanced virtual disk feature enables you to set up the priority class of a virtual disk. See [Section 6.7.3, "Storage"](#).

New Features in Release 2.1.1

The new features and enhancements in Oracle VM Manager Release 2.1.1 include:

Network Bootable (PXE boot) Virtual Machines

Oracle VM Manager provides a new way of creating virtual machines in Release 2.1.1. Besides creating virtual machines from templates and installation media, you can create network bootable (PXE boot) virtual machines. See [Section 6.3.3, "Creating a Network Bootable \(PXE boot\) Virtual Machine"](#).

Hot Plugging Memory, Virtual Network Interface (VIF), and Virtual Disk

Some changes in the configuration of a virtual machine take effect immediately without restarting the virtual machine. See [Section 6.7, "Editing Virtual Machine Configuration"](#).

Virtual Network Interface (VIF) Type

You can select the virtual network interface (VIF) type for a virtual machine. See [Section 6.7.2, "Network"](#).

Preferred Server

When creating a virtual machine, you can select a preferred server for a virtual machine. See Step 2 in [Section 6.3.1, "Creating a New Virtual Machine Based on Virtual Machine Template"](#).

Boot Source

After creating a virtual machine, you can choose to start the virtual machine from hard disk (HDD), CD-ROM, or through Preboot Execution Environment (PXE). See [Section 6.7.3, "Storage"](#).

Refresh Automatically

On the Virtual Machines page, you can choose to either refresh Web pages manually, or refresh every 30 seconds automatically. See [Section 6.4.1, "Starting a Virtual Machine"](#).

Deleting Related Directories

You can choose to either delete or retain the related directories when deleting a server pool. See [Section 3.7, "Deleting a Server Pool"](#).

Overview of Oracle VM Manager

This chapter gives an overview of Oracle VM Manager. It includes the following topics:

- [What Is Virtualization?](#)
- [Why Virtualize?](#)
- [Introduction to Oracle VM](#)
- [Configuration of Oracle VM Manager](#)
- [Roles in Oracle VM Manager](#)
- [Main Features of Oracle VM Manager](#)

1.1 What Is Virtualization?

Virtualization is the ability to run multiple *virtual* machines on a single piece of hardware. The hardware runs software that enables you to install multiple operating systems capable of running simultaneously and independently, in their own secure environment, with minimal impact on performance. Each virtual machine has its own virtual CPU, network interfaces, storage, and operating system.

1.2 Why Virtualize?

With increased server provisioning in the datacenter, several factors play a role in stifling growth. Increased power and cooling costs, physical space constraints, man power, and interconnection complexity all contribute significantly to the costs and feasibility of continued expansion.

Commodity hardware manufacturers have begun to address some of these concerns by shifting their design goals. Rather than focusing solely on raw gigahertz performance, manufacturers have enhanced the feature sets of CPUs and chip sets to include lower wattage CPUs, multiple cores per CPU die, advanced power management, and a range of virtualization features. By employing appropriate software to enable these features, several advantages are realized:

- **Server Consolidation:** By combining workloads from a number of physical hosts into a single host, a reduction in servers can be achieved as well as a corresponding decrease in interconnect hardware. Traditionally, these workloads would need to be specially crafted, partially isolated and well behaved, but with new virtualization techniques none of these requirements are necessary.
- **Reduction of Complexity:** Infrastructure costs are massively reduced by removing the need for physical hardware, and networking. Instead of having a large number

of physical computers, all networked together, consuming power and administration costs, fewer computers can be used to achieve the same goal. Administration and physical setup is less time consuming and costly.


- **Isolation:** Virtual machines run in sand-boxed environments. They cannot access each other, so if one virtual machine performs poorly, or crashes, it does not affect any other virtual machine.
- **Platform Uniformity:** In a virtualized environment, a broad, heterogeneous array of hardware components is distilled into a uniform set of virtual devices presented to each guest operating system. This reduces the impact across the IT organization: from support, to documentation, to tools engineering.
- **Legacy Support:** With traditional bare-metal operating system installations, when the hardware vendor replaces a component of a system, the operating system vendor is required to make a corresponding change to enable the new hardware to function properly (for example, an ethernet card). As an operating system ages, the operating system vendor may no longer provide hardware enabling updates. In a virtualized operating system, the hardware remains constant for as long as the virtual environment is in place, regardless of any changes occurring in the real hardware, including full replacement.

1.3 Introduction to Oracle VM

Oracle VM is a platform that provides a fully equipped environment to better leverage the benefits of virtualization technology. Oracle VM enables you to deploy operating systems and application software within a supported virtualization environment. The components of Oracle VM are:

- **Oracle VM Manager:** Provides the user interface, which is a standard ADF (Application Development Framework) web application, to manage Oracle VM Servers, virtual machines, and resources. Use Oracle VM Manager to:
 - Create virtual machines from installation media or from a virtual machine template
 - Delete virtual machines
 - Power off virtual machines
 - Import virtual machines
 - Deploy and clone virtual machines
 - Perform live migration of virtual machines
 - Import and manage ISOs
 - Create and manage virtual machine templates
 - Create and manage shared virtual disks
- **Oracle VM Server:** A self-contained virtualization environment designed to provide a lightweight, secure, server-based platform to run virtual machines. Oracle VM Server is based upon an updated version of the underlying Xen hypervisor technology, and includes Oracle VM Agent.
- **Oracle VM Agent:** Installed with Oracle VM Server. It communicates with Oracle VM Manager to manage virtual machines.


Figure 1–1, "Oracle VM Architecture" shows the components of Oracle VM.

Figure 1–1 Oracle VM Architecture

This book discusses Oracle VM Manager. See the *Oracle VM Server Installation Guide* and the *Oracle VM Server User's Guide* for information on installing and using Oracle VM Server.

1.4 Configuration of Oracle VM Manager

This section describes the configuration structure of Oracle VM Manager.

Figure 1–2 Deployment View of Oracle VM Manager

As shown in [Figure 1–2](#), when you deploy Oracle VM Manager, the following components are involved:

- The Oracle VM Manager Host

The host machine on which Oracle VM Manager is installed is known as an Oracle VM Manager host. It provides the interface where most of the virtual machine management tasks are performed. Its main function is to forward operational commands from users to other, possibly remote, servers and display their results.

- Servers

An Oracle VM Server, once added to a server pool, is assigned with one, two, or even all three functions, namely, Server Pool Master function, Utility Server function, and Virtual Machine Server function.

Oracle VM Agent provides the interface to each server function. Therefore, if An Oracle VM Server is assigned as a Server Pool Master only, then the Server Pool Master agent component is activated. Otherwise, if it is assigned as both a Server Pool Master, and a Utility Server, their respective agent components are activated, and so on.

An Oracle VM Server can perform one, two, or all of the three functions described below:

- Server Pool Master function

The Server Pool Master is the core of the server pool operations. It acts as the contact point of the server pool to the outside world, and also as the dispatcher to other servers within the server pool.

The load balancing is implemented by the Server Pool Master. For example, when you start a virtual machine, the Server Pool Master will choose a Virtual

Machine Server with the maximum resources available to run the virtual machine.

There is only one Server Pool Master in a server pool.

- Utility Server function

The Utility Server is responsible for I/O intensive operations such as, copying, or moving files. Its function focuses on the creation and removal operations of virtual machines, servers, and server pools.

There can be one or more Utility Servers in a server pool. When there are several Utility Servers, the Server Pool Master chooses the Utility Server with the maximum CPU resources available to conduct the task.

- Virtual Machine Server function

The primary function of the virtual machine server is to run virtual machines, thus acting as a hypervisor. Oracle VM Agent is set up on the Virtual Machine Server to establish communication between the Server Pool Master, other Utility Servers, and Virtual Machine Servers.

There can be one or more Virtual Machine Servers in a server pool. When there are several Virtual Machine Servers, the Server Pool Master chooses the Virtual Machine Server with the maximum resources available (for example, memory) to start and run the virtual machine.

- Server Pools

A server pool is an autonomous region that contains one or more Oracle VM Servers. A server pool presents a unified view of the storage in which the virtual machines reside. Each server pool must have its own shared storage.

The server functions described above can be deployed in a server pool in a variety of ways as shown in [Figure 1–2](#). For example, in Server Pool 1, each one of the three functions is implemented on an individual Oracle VM Server. In Server Pool 2, all of the three functions are performed by a single Oracle VM Server.

In medium to large scale environments with more than just a few virtual machines in a Server Pool, it is recommended that the Server Pool Master and Utility Server functions reside together or individually on a separate and dedicated physical server that does not host any guest virtual machines, as illustrated in Server Pool 3. This is to prevent any significant Server Pool Master or Utility Server usage from impacting the performance of the workloads hosted in the guest virtual machines.

- Storage

A storage resource is mounted to store virtual machines, external resources, and other data files that are shared among Oracle VM Servers in the server pool. In order to perform Live Migration of virtual machines between separate physical machines in the server pool, each machine involved must have shared access to storage.

1.5 Roles in Oracle VM Manager

As a user of Oracle VM Manager, you can have one of three roles: *User*, *Manager*, or *Administrator*.

- User

A *User* creates and manages virtual machines, and also imports resources.

- **Manager**
A `Manager` manages the server pools, resources, and servers. A manager also has all the privileges of the `User` role.
- **Administrator**
An `Administrator` performs administration tasks such as managing user accounts, importing resources, and approving imported resources. An `Administrator` also has all privileges of the `User` role and the `Manager` role.

[Table 1–1](#) briefly lists the available functions for each user role.

Table 1–1 Available Functions for Each Role

Roles	Available Functions
User	<ul style="list-style-type: none">■ Importing resources. See Chapter 5, "Managing Resources".■ Managing virtual machines, including all the operations described in Chapter 6, "Managing Virtual Machines".
Manager	<ul style="list-style-type: none">■ Managing server pools, including all the operations described in Chapter 3, "Managing Server Pools".■ Managing servers, including all the operations described in Chapter 4, "Managing Servers".■ Managing resources, including all the operations described in Chapter 5, "Managing Resources".■ Managing virtual machines, including all the operations described in Chapter 6, "Managing Virtual Machines".
Administrator	<ul style="list-style-type: none">■ Managing server pools, including all the operations described in Chapter 3, "Managing Server Pools".■ Managing servers, including all the operations described in Chapter 4, "Managing Servers".■ Managing resources, including all the operations described in Chapter 5, "Managing Resources".■ Managing virtual machines, including all the operations described in Chapter 6, "Managing Virtual Machines".■ Managing users and groups, including all the operations described in Chapter 7, "Managing Users and Groups".

1.6 Main Features of Oracle VM Manager

Oracle VM Manager provides the following main features:

- Virtual machine life cycle management. This includes creating virtual machines from either installation media or from templates, starting, logging in, shutting down, and deleting virtual machines.
- Importing virtual machines
- Cloning virtual machines
- Deploying virtual machines
- Migrating virtual machines
- Creating and configuring server pools
- Managing servers
- Managing resources, including ISO files, virtual machine templates, virtual machine images, and shared virtual disks

- Managing Oracle VM Manager users, and groups

Getting Started with Oracle VM Manager

This Chapter describes how to start using Oracle VM Manager. It includes the following sections:

- [Registering an Account with Oracle VM Manager](#)
- [Logging In to Oracle VM Manager](#)
- [Using the Wizard to Create a Server Pool](#)

After you install Oracle VM Manager, go to one of the following Web sites to log into Oracle VM Manager:

- For local access: `http[s]://127.0.0.1:port/OVS`
- For remote access: `http[s]://hostname:port/OVS`

Where, *hostname* refers to the host name or IP address of the Oracle VM Manager host. For example, to connect to Oracle VM Manager using the standard port of 8888 on a host named `example.com`, use:

`http://example.com:8888/OVS`

To connect to Oracle VM Manager using the Secure Sockets Layer (SSL) port of 4443 on a host named `example.com`, use:

`https://example.com:4443/OVS`

2.1 Registering an Account with Oracle VM Manager

You can obtain an account using one of the following ways:

- If you have configured the default administration account *admin* when you installed Oracle VM Manager, you can use this account to log in to Oracle VM Manager directly. By default, this account is granted the *administrator* role.
- Contact the administrator of Oracle VM Manager to create an account with any role you need, including *administrator*, *manager*, and *user*.
- If you only want to use the basic functions as a common user, such as creating and using virtual machines, or importing resources, you can register a new account by yourself. After registering the account, you need to ask the administrator to assign some server pools and groups to your account. By default, the account you register is granted the *user* role.

For more information about the roles, see [Section 1.5, "Roles in Oracle VM Manager"](#).

To register a new account with Oracle VM Manager:

1. On the Oracle VM Manager Login page, click **Register**.

2. The User Information screen is displayed. Enter your personal account information.

- Username

Enter a descriptive user name you use for login.

- Password

Enter the password for the account.

- Retype Password

- First Name

- Last Name

- Email

Click **Next**.

3. Confirm your account details.

An account is created, and a confirmation message is displayed on the Oracle VM Manager Login screen.

Before using any features, you need to ask the administrator to assign some server pools and groups to your account. For more information on editing users, see [Section 7.2.3, "Editing a User"](#).

Now you can use the new account to log in to Oracle VM Manager.

2.2 Logging In to Oracle VM Manager

To open the Login page of Oracle VM Manager, enter either of the following addresses in a Web browser:

- For local access: `http[s]://127.0.0.1:port/OVS`
- For remote access: `http[s]://hostname:port/OVS`

Where, *hostname* refers to the host name or IP address of the Oracle VM Manager host. For example, to connect to Oracle VM Manager using the standard port of 8888 on a host named example.com, use:

`http://example.com:8888/OVS`

To connect to Oracle VM Manager using the Secure Sockets Layer (SSL) port of 4443 on a host named example.com, use:

`https://example.com:4443/OVS`

On the Oracle VM Manager Login page, enter your user name and password to log in. Now you can create virtual machines, import resources, and so on.

After logging in, the available tabs vary, depending on the role of your account, as shown in [Table 2–1, "Available Tabs for Each Role"](#). If you want to change the role of your account, contact the administrator. Only administrators can change the roles of accounts.

Table 2–1 Available Tabs for Each Role


Role	Available Tabs
User	<ul style="list-style-type: none">■ Virtual Machines■ Resources

Table 2–1 (Cont.) Available Tabs for Each Role

Role	Available Tabs
Manager	<ul style="list-style-type: none"> Virtual Machines Resources Servers Server Pools
Administrator	<ul style="list-style-type: none"> Virtual Machines Resources Servers Server Pools Administration

To change your account information, such as e-mail address and password, click **Profile** on the upper-right part of any page.

If you forget your password, click **Forgot Password** on the Login page and submit your account name. A new password will be sent to your registered e-mail address.


Figure 2–1 Profile Link

2.3 Using the Wizard to Create a Server Pool

After installation, you can log in to Oracle VM Manager, and follow the Wizard to create a server pool containing a physical server which will act as the Server Pool Master, the Virtual Machine Server, and the Utility Server.

To create a server pool by following the Wizard:

1. On the Welcome page, click **Next**.

Figure 2–2 Welcome Page

2. On the Server Information page, enter the server pool information:

- Enter the name of the server pool in the **Server Pool Name** field.
- Select whether to enable HA with the **High Availability Mode** check box. To use HA, you must enable HA in the server pool, and on each virtual machine. For information about HA, see [Section 3.6, "Enabling High Availability \(HA\)"](#). For more information on how to set up HA prerequisites, see the *Oracle VM Server User's Guide*.

Enter the following information about the Oracle VM Server in the **Server Details** box:

- **Server Host/IP**
Enter the host name, or IP address of the Oracle VM Server, for example:
192.168.2.20
or
hostname.example.com
- **Server Name**
Enter a name for the Oracle VM Server. This must be unique.
- **Server Agent Password**
Enter the password to access Oracle VM Agent installed on the Oracle VM Server.
- **Server Username**
Enter the username to log in to the Oracle VM Server.
- **Server Password**
Enter the password to log in to the Oracle VM Server.
- **Location**
The location of the Oracle VM Server. For example, `Server Room 1`.
- **Description**

A description of the Oracle VM Server.

To test the connection to the Oracle VM Server click **Test Connection**. If the information is incorrect, or the Oracle VM Server is not available, you cannot add it to the server pool.

Figure 2–3 Adding Servers to a Server Pool

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources Servers **Server Pools** Administration

Server Pools > Create Server Pool Logged in as admin

Create Server Pool

Reset TestConnection Create Cancel

Provide details of the server pool you want to create.

* Server Pool Name

High Availability Mode ☐ Enable

Server Details

Provide details of the (master/utility/virtual) servers you want to register.

* Server Host/IP Location

Server Name Description

* Server Agent Password

* Server Username:

* Server Password:

Reset TestConnection Create Cancel

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007-2009. Oracle. All rights reserved. Oracle VM Manager 2.1.5

Click **Create** to create the server pool.

Now you have created a server pool, you can continue to add more Virtual Machine Servers and Utility Servers, or add more users to the server pool. For more information on creating server pools and adding servers, see [Section 3.2, "Creating a Server Pool"](#) and [Section 4.1, "Adding a Server"](#).

Once the server pool is created, you can start importing resources, or creating virtual machines. See [Chapter 5, "Managing Resources"](#) and [Chapter 6, "Managing Virtual Machines"](#).

Managing Server Pools

A server pool is logically an autonomous region that contains one or more physical servers. It presents a unified view of the storage in which the virtual machines reside.

Before creating a server pool, ensure you have:

- Oracle VM Servers that you will deploy as the Server Pool Master, the Utility Server, or the Virtual Machine Server.
- A repository that is used for live migration of virtual machines and for local storage on the Oracle VM Servers. For information on managing repositories, see the *Oracle VM Server User's Guide*.
- IP addresses or host names of these servers.
- Passwords to access Oracle VM Agent installed on these servers.

This chapter describes how to manage server pools. It includes the following sections:

- [Designing a Server Pool](#)
- [Creating a Server Pool](#)
- [Editing a Server Pool](#)
- [Searching Server Pools](#)
- [Restoring a Server Pool](#)
- [Enabling High Availability \(HA\)](#)
- [Deleting a Server Pool](#)

Note: Functions described in this chapter are only available to users who are granted the Manager or Administrator role.

3.1 Designing a Server Pool

This section guides you through the ways of designing a server pool to meet your requirements.

Before creating a server pool, you need to consider how many physical servers will be contained in the server pool, and what functions each physical server will perform. The more virtual machines you will run in the server pool, the more resources these virtual machines will consume, therefore the more physical servers are needed to provide sufficient resources for the server pool.

A server pool is scalable. If you find a server pool does not have sufficient resources, such as CPU and memory, to run the virtual machines and the applications inside, you can expand the server pool by adding more Virtual Machine Servers.


There are three typical server pool configurations: separate configuration, all-in-one configuration, and two-in-one configuration.

- **Separate Configuration**

In separate configuration, one single Oracle VM Server functions as a Server Pool Master, one or more Oracle VM Servers function as Utility Servers, and one or more Oracle VM Servers function as Virtual Machine Servers.

This configuration is recommended when there is a large number of virtual machines running on the server, or when applications on the virtual machines consume most of the hardware resources. It ensures that the performance of the hosted virtual machines is not impacted by any significant management activity handled by the Server Pool Master or Utility Servers.


Figure 3–1 The Separate Configuration



- **All-in-One Configuration**

In the all-in-one configuration, a single Oracle VM Server acts as the Server Pool Master, the Utility Server, and the Virtual Machine Server at the same time.


This configuration is recommended when there are only a few virtual machines running. In this case, the hardware resources of the Oracle VM Server are sufficient to support the virtual machines and the management activity handled by the Server Pool Master and Utility Server.

Figure 3–2 The All-in-One Configuration

- **Two-in-One Configuration**

In the two-in-one configuration, the Server Pool Master function, and the Utility Server function are grouped together on the same Oracle VM Server, while the Virtual Machine Server function is implemented separately on different Oracle VM Servers.

Compared with the two structures described earlier, this configuration serves well for a scenario where the server pool resource consumption is moderate. Since virtual machines use more hardware resources than other servers, you can typically deploy both the Server Pool Master and Utility Server on the same Oracle VM Server.

Figure 3–3 The Two-in-One Configuration

3.2 Creating a Server Pool

To create a server pool, perform the following:

1. On the Server Pools page, click **Create Pool**. The Create Server Pool page is displayed.

Figure 3–4 Adding Servers to a Server Pool

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources Servers **Server Pools** Administration

Server Pools > Create Server Pool Logged in as admin

Information
The server (192.168.2.20) can be connected.

Server Pool Information User Information Confirmation

Create Server Pool

Provide details of the server pool you want to create.

* Server Pool Name

High Availability Mode ☐ Enable

Server Details

Provide details of the (master/utility/virtual) servers you want to register.

* Server Host/IP Location

Server Name Description

* Server Agent Password

Server Type ☒ Server Pool Master ☒ Utility Server ☒ Virtual Machine Server

* Utility Server Username

* Utility Server Password

Select	Server Host/IP	Server Name	Server Type	Status	Location
	No rows yet.				

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007-2009. Oracle. All rights reserved. Oracle VM Manager 2.1.5

2. Enter the Oracle VM Server information and add the Oracle VM Server to the server pool. You can add multiple Oracle VM Servers to a server pool.

A server pool consists of at least one Server Pool Master, one Utility Server, and one Virtual Machine Server. See [Section 3.1, "Designing a Server Pool"](#).

Note: If you have registered a physical server to Oracle VM Manager, you cannot register it again, as this may result in duplicate host names or IP addresses.

Enter the name of the server pool in the **Server Pool Name** field.

A server pool name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (_) character. The maximum length of a server pool name is 200 characters.

Select whether to enable HA with the **High Availability Mode** check box. To use HA, you must enable HA in the server pool, and on each virtual machine. For information about HA, see [Section 3.6, "Enabling High Availability \(HA\)"](#). For more information on how to set up HA prerequisites, see the *Oracle VM Server User's Guide*.

Enter the following information on the Oracle VM Server in the **Server Details** box:

- **Server Host/IP**

Enter the host name, or IP address of the Oracle VM Server, for example:

192.168.2.20

or

hostname.example.com

- **Server Name**

Enter a name for the Oracle VM Server. This must be unique.

An Oracle VM Server name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (_) character. The maximum name length is 200 characters.

- **Server Agent Password**

Enter the password to access Oracle VM Agent installed on the Oracle VM Server.

- **Server Type**

Select the checkbox for each role the Oracle VM Server should perform in the server pool:

- Server Pool Master
- Utility Server
- Virtual Machine Server

If you select **Utility Server**, you must enter the Oracle VM Server login credentials in the **Utility Server Username** and **Utility Server Password** fields. The user must have read/write privileges for the /OVS folder.

- **Location**

The location of the Oracle VM Server. For example, `Server Room 1.`

- **Description**

A description of the Oracle VM Server.

To test the connection to the Oracle VM Server click **Test Connection**. If the information is incorrect, or the Oracle VM Server is not available, you cannot add it to the server pool.

When you have entered the information about the Oracle VM Server, click **Add**. The Oracle VM Server is added to the server pool and listed in the table at the bottom of the screen. You can select it, and then edit it or delete it with the **Edit** and **Delete** buttons.

To add more Oracle VM Servers to the server pool, enter the parameters for each Oracle VM Server, and click **Add**.

After adding the Oracle VM Server, click **Next** to proceed to the next page.

3. On the User Information page, select the users from the **Non-Administration User Information** table for which you want to grant access to the server pool. Users with the Administrator role are automatically granted access to the server pool.

Figure 3–5 Adding Users to a Server Pool

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources Servers **Server Pools** Administration

Logged in as admin

User Information Server Pool Information User Information Confirmation

User Information

Cancel Previous Next

Administration User Information

TIP Admin User will be server pool default user.

Username	Email	First Name	Last Name	Status	Role
admin	example@example.com			Unlocked	Administrator

Non-Administration User Information

Select and Delete | Add

Select All | Select None

Select	Username	Email	First Name	Last Name	Status	Role
<input checked="" type="checkbox"/>	name	name@example.com	First	Last	Unlocked	User

Cancel Previous Next

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007-2009, Oracle. All rights reserved. Oracle VM Manager 2.1.5

To add new users, see [Section 7.2.1, "Creating a User"](#). To change a user role, see [Section 7.2.4, "Changing a Role"](#).

After adding users, click **Next** to proceed to the next page.

4. On the Confirmation page, confirm the information you have entered for the server pool. Click **Confirm** to create the server pool.

The Server Pools page is displayed and the new server pool is listed in the **Server Pools** table.

3.3 Editing a Server Pool

You can change the server pool name, check HA infrastructure and enable or disable HA. You can also edit the servers in a server pool, and add or remove users.

Figure 3–6 Editing Server Pool Page Links

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources Servers **Server Pools** Administration

Logged in as admin

Server Pools

Refresh Create Pool

Search

Server Pool Name:

Status: All

TIP Search criteria are case insensitive. Use '%' as a wildcard, for example prod%

Server Pools

Select and Restore Edit Delete

Select	Server Pool Name	Status	HA Status	Servers	Users
<input type="radio"/>	10.1.1.1	Active	Disabled	Total: 1	Total: 1

Refresh Create Pool

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007, 2008, Oracle. All rights reserved. Oracle VM Manager 2.1.2

3.3.1 Editing Server Pool

To edit a server pool:

1. Select the server pool in the **Server Pools** table and click **Edit**. The Edit Server Pool page is displayed.

Figure 3–7 Editing a Server Pool

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources Servers **Server Pools** Administration

Server Pools > Edit Server Pool

Logged in as admin

Edit Server Pool

Cancel Apply OK

* Server Pool Name

High Availability Infrastructure

Enable High Availability ☐

Cancel Apply OK

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007-2009, Oracle. All rights reserved. Oracle VM Manager 2.1.5

2. Change the server pool name in the **Server Pool Name** field.

An Oracle VM Server name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (_) character. The maximum name length is 200 characters.

3. To check the HA infrastructure click **Check** in the **High Availability Infrastructure** field.
4. Enable or disable HA with the **Enable High Availability** check box.
5. Click **OK** or **Apply** to save your changes.

3.3.2 Editing Server Pool Servers

To edit the servers in a server pool, click the **Servers** link in the **Server Pools** table. For more information, refer to [Chapter 4, "Managing Servers"](#).

3.3.3 Editing Server Pool Users

To add or remove users from the server pool:

1. Click the **Users** link in the **Server Pools** table. The **Edit User Information for the Server Pool** screen is displayed.
2. Select the users from the **Non-Administration User Information** table for which you want to grant access to the server pool. Users with the Administrator role are automatically granted access to the server pool. Click **Apply**.

To add new users, see [Section 7.2.1, "Creating a User"](#). To change a user role, see [Section 7.2.4, "Changing a Role"](#).

3.4 Searching Server Pools

To search server pools, perform the following:

1. Enter the server pool name in the **Server Pool Name** field. Use % as a wildcard. All available server pools are displayed if you leave the **Server Pool Name** field empty.
2. Select the server pool status in the **Status** drop down. The server pool status reflects the status of the Server Pool Master.
 - **Active**
The server pool is available.
 - **Inactive**
The server pool is not available.
3. Click **Search**. The search results are displayed in the **Server Pools** table.

3.5 Restoring a Server Pool

If the server pool data on the server pool master is damaged, you can restore this data by synchronizing it with the data from the Oracle VM Manager database.

Note: When you restore a server pool, all the data stored in the server pool master will be deleted, and will be synchronized with the latest information from the Oracle VM Manager database.

To restore a server pool, select it, and click **Restore**.


3.6 Enabling High Availability (HA)

You can set up HA in Oracle VM to guarantee the availability of virtual machines if the Virtual Machine Server they are running on fails or restarts. When a Virtual Machine Server is restarted or shut down, the virtual machines running on it are either restarted on, or migrated to, another Virtual Machine Server.

You manage HA with Oracle VM Manager. To implement HA, you must create a cluster of Virtual Machine Servers in a server pool and have them managed by Oracle VM Manager. HA cannot be implemented with Oracle VM Server alone.

To use HA, you must first enable HA on the server pool, then on all virtual machines, as shown in [Figure 3–8, "Enabling HA"](#). If you enable HA in the server pool and then for virtual machines, when a Virtual Machine Server is shut down or fails, the virtual machines are migrated or restarted on another available Virtual Machine Server. HA must be enabled for **both** the server pool **and** for virtual machines. If HA is not enabled for both, HA is disabled.

Figure 3–8 Enabling HA



If HA is enabled, when you restart, shut down, or delete the Virtual Machine Server in Oracle VM Manager, you are prompted to migrate the running virtual machines to another available Virtual Machine Server. If you do not migrate the running virtual machines, Oracle VM Agent attempts to find an available Virtual Machine Server on which to restart the virtual machines. The Virtual Machine Server is selected using the preferred server setting for the server pool when you create a virtual machine in Oracle VM Manager:

- **Auto** selects an available Virtual Machine Server.
- **Manual** selects an available preferred Virtual Machine Server.

If you do not select a preferred server when creating a virtual machine in Oracle VM Manager, **Auto** is set as the default.

If there is no preferred Virtual Machine Server or Virtual Machine Server available, the virtual machines shut down (Power Off) and are restarted when a Virtual Machine Server becomes available.

If the Server Pool Master fails, HA also fails for the Virtual Machine Servers running in that server pool.

The possible HA scenarios are:

- If you shut down or restart a Virtual Machine Server in Oracle VM Manager, you are prompted which virtual machines to migrate to another available Virtual Machine Server. Any virtual machines which are not migrated, are restarted on an available Virtual Machine Server.
- If you shut down or restart a Virtual Machine Server at the Oracle VM Server command-line, Oracle VM Agent restarts the virtual machines on an available Virtual Machine Server.
- If a Virtual Machine Server fails, all running virtual machines are restarted automatically on another available Virtual Machine Server.
- If a Virtual Machine Server fails and no other Virtual Machine Servers are available, all running virtual machines are restarted when a Virtual Machine Server becomes available.

In all the above scenarios, if any virtual machines running on the Virtual Machine Server are not HA-enabled, they are shut down (Powered Off).

Figure 3–9 shows a Virtual Machine Server failing and the virtual machines restarting on other Virtual Machine Servers in the server pool.

Figure 3–9 HA in Effect for a Virtual Machine Server Failure





Figure 3–10 shows a Virtual Machine Server restarting or shutting down and the virtual machines migrating to other Virtual Machine Servers in the server pool.

Figure 3–10 HA in Effect for a Virtual Machine Server Restart or Shut Down

3.7 Deleting a Server Pool

To delete a server pool, perform the following:

1. On the **Server Pools** page, select the server pool you want to delete, and click **Delete**.
2. On the **Delete Confirmation** page, select **Remove all the working directories from the server pool** if you want to delete all the related directories. If you do not select this option, only the server pool data is removed from the database, while the relevant directories and files of the server pool remain on the server. Select **Force Remove** to force the removal of the servers if one or more servers are unavailable.

Caution: After you delete all the directories, all the servers and virtual machines on the server pool are then deleted as well. Ensure that the server pool is no longer in use before deleting it.

Managing Servers

There is at least one physical server in a server pool. You can change the parameters or functions of a server, restart it, shut it down, or delete it.

A server pool is expandable. When more virtual machines are running on the server pool and consuming more resources, you can add more Virtual Machine Servers to expand the resources for the server pool, such as the number of CPUs and the size of memory. When there are several Virtual Machine Servers, Server Pool Master chooses the Virtual Machine Server with the maximum resources available (including memory and CPU) to start and run the virtual machine.

You can also add more Utility Servers to enhance the processing ability of the server pool. When there are several Utility Servers, Server Pool Master chooses the Utility Server with the maximum CPU resources available to conduct the task.

However, you can not add more Server Pool Masters, as a server pool can have only one Server Pool Master.

Before you add servers to an existing server pool, you must:

- Identify the IP address, or host name of the computer that functions as the Utility Server or Virtual Machine Server.
- Identify the password to access Oracle VM Agent that has been installed on the computer.

This chapter describes how to manage servers. It includes the following sections:

- [Adding a Server](#)
- [Viewing and Editing a Server](#)
- [Restarting a Server](#)
- [Shutting Down a Server](#)
- [Deleting a Server](#)

4.1 Adding a Server

To add a Utility Server, or a Virtual Machine Server to an existing server pool, perform the following:

1. On the Servers page, click **Add Server**. The Add Server page is displayed.

Figure 4–1 Add Server Page

ORACLE VM Manager Home Profile Logout Help

Virtual Machines Resources **Servers** Server Pools Administration

Servers > Add Server Logged in as admin

Add Server [Cancel] [OK]

Server Details

Provide details of the (utility/virtual) servers you want to register.

* Server Host/IP: 192.168.2.21
 Server Name: Server_02
 * Server Agent Password: [Masked]
 * Server Type: ☒ Utility Server ☒ Virtual Machine Server
 Server Pool Name: MyServerPool [Search Icon]
 * Utility Server Username: root
 * Utility Server Password: [Masked]

Location: Server Room 1
 Description: [Text Area]
 [Test Connection] [Add]

Select	Server Host/IP	Server Name	Server Type	Status	Location
	No rows yet.				

[Cancel] [OK]

Virtual Machines Resources Servers Server Pools Administration
 Copyright © 2007-2009, Oracle. All rights reserved. Oracle VM Manager 2.1.5

- Enter the Oracle VM Server parameters. For information about these parameters, refer to [Section 3.2, "Creating a Server Pool"](#). In addition to the parameters in [Section 3.2, "Creating a Server Pool"](#), you must select a server pool for the Oracle VM Server. Select the search icon in the **Server Pool Name** field to search for a server pool.

After adding the server, click **OK**.

Note: If you have already registered a physical Oracle VM Server in Oracle VM Manager, you cannot register it again, as this may result in host name or IP address duplication.

4.2 Viewing and Editing a Server

To edit an existing Oracle VM Server, select the server, and click **Edit**.

Figure 4–2 Editing a Server

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources **Servers** Server Pools Administration

Servers > Edit Server Logged in as admin

Edit Server

Test Connection Apply Cancel OK

Edit Server

Server Pool MyServerPool

Server Host/IP 192.168.2.20

Server Name 192.168.2.20

* Server Agent Password •••••

* Server Type

☒ Server Pool Master

☒ Utility Server

☒ Virtual Machine Server

* Utility Server Username root

* Utility Server Password •••••

Location Server Room 1

Description

Test Connection Apply Cancel OK

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007-2009. Oracle. All rights reserved. Oracle VM Manager 2.1.5

You can also click the Oracle VM Server link to view general information about the Oracle VM Server. For information about the parameters, see [Section 3.2, "Creating a Server Pool"](#).

Figure 4–3 Viewing and Editing a Server

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources **Servers** Server Pools Administration

Servers > View Server Logged in as admin

View and Edit Server

General Information

Model Name: Intel(R) Core(TM)2 Duo CPU E8400 @ 3.00GHz

Model: 23

CPU Family: 6

Number of Cores: 2

Memory Size(MB): 2,005

Server Host/IP: 192.168.2.20

Server Name: 192.168.2.20

Server Pool Name: MyServerPool

Server Type: Server Pool Master, Utility Server, Virtual Machine Server

Server Username: root

Server Password: •••••

Status: Active

Server Location: Server Room 1

Description:

Edit

General Information

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007-2009. Oracle. All rights reserved. Oracle VM Manager 2.1.5

4.3 Restarting a Server

You can remotely restart the physical server with Oracle VM Server installed.

To restart a server:

1. On the Servers page, select the server, and click **Reboot**.
2. If there are virtual machines running on the server, you are prompted to migrate them to another server. Select the virtual machine you want to migrate, and then click **Migrate**. For information on migrating virtual machines, see [Section 6.9, "Migrating a Virtual Machine"](#).

If you restart the server without migrating the running virtual machines, the running virtual machines will be shut down, or be restarted, depending on whether high availability is enabled. If you have enabled high availability for both the server pool and virtual machines, the virtual machines will restart on other available servers; otherwise, they will be shut down. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).

Click **Refresh** periodically until the server status changes from Rebooting to Active.

During the restarting process, the server may be temporarily unavailable, and all virtual machines involved are shut down.

4.4 Shutting Down a Server

You can remotely shut down the physical server that performs as the Oracle VM Server.

To shut down a server:

1. On the Servers page, select the server, and then click **Power Off**.
2. If there are running machines on the server, you are prompted to migrate them to another server. Select the virtual machine you want to migrate, and then click **Migrate**. For information on migrating virtual machines, see [Section 6.9, "Migrating a Virtual Machine"](#).

If you shut down the server without migrating the running virtual machines, the running virtual machines will be shut down, or be restarted, depending on whether high availability is enabled. If you have enabled high availability for both the server pool and virtual machines, the virtual machines will restart on other available servers; otherwise, they will be shut down. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).

Click **Refresh** periodically until the server status changes from Shutting Down to Unreachable.

After you shut down the server, virtual machines based on this server cannot be used.

4.5 Deleting a Server

To delete an Oracle VM Server, select it, and then click **Delete**.

If there are running machines on the server, you are prompted to migrate them to another server. Select the virtual machine you want to migrate, and then click **Migrate**. For information on migrating virtual machines, see [Section 6.9, "Migrating a Virtual Machine"](#).

You cannot delete a server without migrating any running virtual machines, or shutting them down.

Caution: When you delete an Oracle VM Server, all virtual machines on the server are no longer available. Ensure that the server is no longer in use before you delete it.

Managing Resources

Resources include virtual machine templates, virtual machine images, ISO files, virtual disks, and converted virtual machines.

- Virtual machine templates
Virtual machine templates imported to Oracle VM Manager are used to create virtual machines.
- Virtual machine images
Virtual machine images imported to Oracle VM Manager are used directly, without the process of creating.
- ISO files
ISO files imported to Oracle VM Manager are used to create virtual machines from installation media.
- Shared virtual disks
Shared virtual disks extend the storage capability of your virtual machine.

This chapter describes how to manage resources. It includes the following sections:

- [Importing Virtual Machine Templates](#)
- [Importing Virtual Machine Images](#)
- [Importing ISO Files](#)
- [Managing Shared Virtual Disks](#)

Note: Only an Administrator or Manager can approve, edit, and delete the imported virtual machine templates, virtual machines, and ISO files.

Figure 5–1 Resources Page

The screenshot shows the Oracle VM Manager interface. At the top, there's a navigation bar with tabs: Virtual Machines, Resources (selected), Servers, Server Pools, and Administration. Below this, there's a sub-navigation bar with links: Virtual Machine Templates, Virtual Machine Images (selected), ISO Files, and Shared Virtual Disks. The user is logged in as 'admin'. The main section is titled 'Virtual Machine Images'. It includes a search area with fields for 'Virtual Machine Image Name', 'Server Pool Name', and a 'Status' dropdown set to 'All'. There's a 'Search' button and a tip: 'TIP Search criteria are case insensitive. Use '%' as a wildcard, for example prod%'. Below the search area is a table of virtual machine images. The table has columns: Select, Virtual Machine Image Name, Size(MB), Server Pool Name, Status, and Creation Time. One image is listed: 'vmware_el4u4' with size 20481, server pool 10.1.1.1, status 'Pending', and creation time 'Jul 17, 2008 3:51:42 AM'. Above the table are buttons: 'Select and', 'Approve', 'Edit', 'Delete', and 'Reimport'. Below the table are 'Refresh in: 30 seconds', 'Refresh', and 'Import' buttons. At the bottom, there's a footer with navigation tabs and copyright information: 'Copyright © 2007. 2008. Oracle. All rights reserved. Oracle VM Manager 2.1.2'.

5.1 Importing Virtual Machine Templates

Virtual machine templates are shared among users to create new virtual machines. New virtual machines will inherit the same contents and configurations from the template.

Typically, a virtual machine template contains basic configurations, such as the number of virtual CPUs, the size of memory, virtual disks, virtual network interfaces (VIFs), and so on. It may also contain some applications installed beforehand.

You can obtain a virtual machine template by:

- Saving an existing virtual machine as template. For more information, refer to [Section 6.8.3, "Saving a Virtual Machine as a Template"](#). You can then use the virtual machine template directly without importing it.
- Downloading Oracle VM templates at:

<http://www.oracle.com/technology/products/vm/templates.html>

The password for the *root* user of all Oracle VM templates is *ovsroot*. The password for the *oracle* account in the OVM_EL4U5_X86_HVM_ORACLE_11G template is *oracle*. For more information on how to use these templates, see

http://download.oracle.com/otn_software/virtualization/README.templates

Before using the downloaded templates, you must import them into Oracle VM Manager.

This section includes the following topics:

- [Importing a Virtual Machine Template](#)
- [Statuses of Virtual Machine Templates](#)

- [Reimporting a Virtual Machine Template](#)
- [Approving the Imported Virtual Machine Template](#)
- [Editing a Virtual Machine Template](#)
- [Deleting a Virtual Machine Template](#)

5.1.1 Importing a Virtual Machine Template

Note: Before you import a virtual machine template, rename the configuration file of the virtual machine to `vm.cfg`.

Depending on where your virtual machine templates are located, on the Virtual Machine Server, on other computers, or on the Internet, you can import virtual machine templates from the server pool or download them from external source. You can also convert a Linux or Windows host to a virtual machine template (P2V).

- [Selecting from the Server Pool](#)
- [Downloading from External Source](#)
- [Converting a Linux or Windows Host to a Virtual Machine Template \(P2V\)](#)

5.1.1.1 Selecting from the Server Pool

If you already have some virtual machine templates on your Server Pool, you can discover and register them in Oracle VM Manager directly.

Before importing, make sure the component files of the virtual machine template are stored in the folder `/OVS/seed_pool/template_name` on the Virtual Machine Server, and make sure the configuration file is named `vm.cfg`.

When importing, Oracle VM Agent can update the directory information in the `vm.cfg` file automatically. If you need to modify the `vm.cfg` file, refer to [Appendix A, "Preparing Virtual Machines For Importing"](#).

To select an existing virtual machine template from the server pool, and register it in Oracle VM Manager, perform the following:

1. On the Resources page, click **Virtual Machine Templates**, and then click **Import**.
2. Select **Select from Server Pool (Discover and register)**. Click **Next**.
3. On the General Information page, enter or select the following general information:
 - **Server Pool Name**
Select the server pool on which the imported virtual machine template will be located.
 - **Virtual Machine Template Name**
Select the virtual machine template to be imported.
 - **Operating System**
Select the guest operating system of the virtual machine template.
 - **Virtual Machine System Username**
Enter the user name used to log in to the virtual machine template.

- Virtual Machine System Password
Enter the password used to log in to the virtual machine template.
- Description
Enter a description of the virtual machine template.

Click **Next**.

4. Confirm the information you have entered.
5. After importing, the status of the virtual machine template is **Pending**. You need to approve it to make it available for creating virtual machines. See [Section 5.1.4, "Approving the Imported Virtual Machine Template"](#).

5.1.1.2 Downloading from External Source

To download a virtual machine template from outside of the server pool, such as OTN:

http://www.oracle.com/technology/software/products/virtualization/vm_templates.html

Or your own HTTP/FTP server, perform the following:

1. On the Resources page, click **Virtual Machine Templates**, and then click **Import**.
2. Select **Download from External Source (HTTP and FTP)**. Click **Next**.
3. On the General Information page, enter or select the following general information:
 - Server Pool Name
Select the server pool on which the imported virtual machine template will be located.
 - Virtual Machine Template Name
Enter a name for the imported virtual machine template. This must be unique. The name will be used as the name of the directory under /OVS/seed_pool, where the files associated with this virtual machine template are stored.

A template name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (_) and hyphen (-) characters. The maximum name length is 48 characters.
 - Operating System
Select the guest operating system of the virtual machine template.
 - Virtual Machine System Username
Enter the user name used to log in to the virtual machine template.
 - Virtual Machine System Password
Enter the password used to log in to the virtual machine template.
 - Description
Enter a description of the virtual machine template.

Click **Next**.

4. On the Import Information page, enter the URL where the virtual machine template is located. For example, enter either of the following:

`http://host/vm`

```
ftp://username:password@host/vm
```

When using a proxy, select **Use Proxy**, and enter the proxy address.

Click **Next**.

5. Confirm the information.
6. After importing, the status of the virtual machine template is `Pending`. You need to approve it to make it available for creating virtual machines. See [Section 5.1.4, "Approving the Imported Virtual Machine Template"](#).

5.1.1.3 Converting a Linux or Windows Host to a Virtual Machine Template (P2V)

You can convert a Linux or Windows host to an Oracle VM virtual machine template (Physical to Virtual, P2V). The conversion process is similar to downloading a template from external source.

Before conversion, you need to restart the Linux or Windows computer with the Oracle VM Server CD, and use P2V utility to start the conversion. For more information on how to use the P2V utility, see the *Oracle VM Server User's Guide*.

During the conversion, you are prompted to enter the number of virtual CPUs and memory size, and this information is configured in the `vm.cfg` file. The disk size in the virtual machine is determined by the size of the disks you have chosen to be included in the virtual machine. Make sure the Virtual Machine Server has sufficient resources for the conversion (disk space).

The converted virtual machine template is a hardware virtualized machine (HVM).

To convert a Linux or Windows host to a virtual machine template:

1. On the Resources page, click **Virtual Machine Templates**, and then click **Import**.
2. Select **Linux/Windows P2V Import**. Click **Next**.
3. On the General Information page, enter the following general information:
 - **Server Pool Name**
Select the server pool on which the converted virtual machine template will be located.
 - **Virtual Machine Template Name**
Enter a name for the converted virtual machine template. This must be unique. The name will be used as the name of the directory under `/OVS/seed_pool`, where the files associated with this virtual machine template are stored.

A template name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (`_`) and hyphen (`-`) characters. The maximum name length is 48 characters.
 - **Operating System**
Select the guest operating system of the virtual machine template.
 - **Virtual Machine System Username**
Enter the user name used to log in to the virtual machine template.
 - **Virtual Machine System Password**
Enter the password used to log in to the virtual machine template.
 - **Description**

Enter a description of the virtual machine template.

Click **Next**.

4. On the Import Information page, enter the host name or IP address of the Linux or Windows host. For example, enter:

hostname.example.com

When using a proxy, select **Use Proxy**, and enter the proxy address.

Click **Next**.

5. Confirm the information.
6. After importing, the status of the virtual machine template is `Pending`. You need to approve it to make it available. See [Section 5.1.4, "Approving the Imported Virtual Machine Template"](#).

5.1.2 Statuses of Virtual Machine Templates

The imported virtual machine template can be one of the following statuses.

- **Importing:** This status indicates that the virtual machine template is in the process of being imported.
- **Pending:** This status indicates that the virtual machine template has been imported successfully, and is waiting for the approval of the `Manager`.
- **Import Error:** This status indicates that there were some errors during importing. Reimport the template, or delete it.
- **Active:** This status indicates that the virtual machine template has been approved, and is available for creating virtual machines.
- **Inactive:** This status indicates that the virtual machine template is imported, but not available.
- **Creating:** This status indicates that the virtual machine template is in the process of being created from a virtual machine. See [Section 6.8.3, "Saving a Virtual Machine as a Template"](#).
- **Create Error:** This status indicates that there were some errors during the creating process. Delete it and try again to save a virtual machine as the template.

5.1.3 Reimporting a Virtual Machine Template

If an error occurs during downloading from an external source, check if the URL or proxy URL is correct, and then reimport the virtual machine template.

To reimport a virtual machine template:

1. On the Virtual Machine Templates page, select the virtual machine template you want to reimport, and click **Reimport**.
2. Enter the URL. When using a proxy, select **Use Proxy**.
3. Click **Reimport**.

5.1.4 Approving the Imported Virtual Machine Template

After importing, the status of virtual machine templates is `Pending`. After the `Manager` or `Administrator` approves them, the status changes to `Active` and the virtual machine now becomes an available template.

To approve an imported virtual machine template, you must have the `Manager` or `Administrator` role. On the Virtual Machine Templates page, select the template you want to approve, and then click **Approve**.

5.1.5 Editing a Virtual Machine Template

To edit a virtual machine template, perform the following:

1. On the Virtual Machine Templates page, select the template you want to update, and click **Edit**.
2. Update the template parameters. Click **Apply**.

For more information about the template parameters, refer to [Section 5.1.1, "Importing a Virtual Machine Template"](#).

5.1.6 Deleting a Virtual Machine Template

To delete a virtual machine template, perform the following:

1. On the Virtual Machine Templates page, select the template you want to delete, and click **Delete**.
2. When prompted, confirm the delete operation.

5.2 Importing Virtual Machine Images

You can import virtual machines from outside of Oracle VM Manager, and use them directly.

Oracle VM Manager allows you to import both Oracle VM virtual machines and VMware virtual machines. When you import VMware virtual machines, Oracle VM Manager converts them to Oracle VM virtual machines automatically (Virtual to Virtual, V2V).

This section includes the following topics:

- [Importing a Virtual Machine Image](#)
- [Statuses of Virtual Machine Images](#)
- [Reimporting a Virtual Machine Image](#)
- [Approving the Imported Virtual Machine Image](#)
- [Editing a Virtual Machine Image](#)
- [Deleting a Virtual Machine Image](#)

5.2.1 Importing a Virtual Machine Image

Note: Before you import an Oracle VM virtual machine, make sure the configuration file is named `vm.cfg`.

Depending on where your virtual machines are located, on the Virtual Machine Server, on other computers, or on the Internet, you can import a virtual machine image from different resources. You can also convert a Linux or Windows host to a virtual machine (Physical to Virtual, P2V).

- [Selecting from the Server Pool](#)

- [Downloading from External Source](#)
- [Converting a Linux or Windows Host to a Virtual Machine \(P2V\)](#)

When importing a VMware virtual machine, make sure you have enough free disk space in the /OVS/tmp directory to convert the VMware virtual machine to an Oracle VM virtual machine. Oracle VM requires at least twice the disk space of the VMware virtual machine.

5.2.1.1 Selecting from the Server Pool

If you already have some virtual machine images on your Server Pool, you can discover and register them in Oracle VM Manager directly, without going through the downloading or copying process.

Before importing, make sure the component files of the virtual machine are stored in the folder `/OVS/running_pool/virtual_machine_name` on the Virtual Machine Server, and make sure the configuration file is named `vm.cfg`.

When importing, Oracle VM Agent updates the directory information in `vm.cfg` automatically. If you need to modify the `vm.cfg` file, refer to [Appendix A, "Preparing Virtual Machines For Importing"](#).

To discover and select an existing virtual machine image from the Server Pool, and register it in Oracle VM Manager, perform the following:

1. On the Resources page, click **Virtual Machine Images**, and then click **Import**.
2. Select **Select from Server Pool (Discover and register)**. Click **Next**.
3. On the General Information page, enter the following general information:
 - **Server Pool Name**
Select the server pool on which the imported virtual machine will be located.
 - **Sharing**
Select whether you want to share this virtual machine.

`private`: This indicates that the virtual machine can only be used by the user who imports it.

`Shared (group_name)`: This indicates that the virtual machine can be used by members of this specific group.
 - **Virtual Machine Image Name**
Select the virtual machine to be imported.

Oracle VM Agent identifies the hypervisor type of the virtual machine directory, which can be Oracle VM or VMware. If both Oracle VM and VMware virtual machines are stored in the same directory, Oracle VM Agent only identifies the Oracle VM virtual machine, and ignores other types of virtual machines. If only the VMware virtual machine is detected, V2V (virtual machine to virtual machine) conversion is started.
 - **Enable High Availability**
You can enable high availability for the imported virtual machine. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).
 - **Operating System**
Select the guest operating system of the imported virtual machine.

- Virtual Machine System Username
Enter the user name used to log in to the virtual machine.
 - Virtual Machine System Password
Enter the password used to log in to the virtual machine.
 - Console Password
Set the password for the VNC login to access the virtual machine.
 - Confirm Console Password
Click **Next**.
4. Confirm the information.
 5. After importing, the status of the virtual machine is `Pending`. You need to approve it to make it available. See [Section 5.2.4, "Approving the Imported Virtual Machine Image"](#).

If the status turns out to be `Import Error`, click the error log link to check the detailed information.

5.2.1.2 Downloading from External Source

To download a virtual machine image from outside of the Server Pool, such as OTN:

http://www.oracle.com/technology/software/products/virtualization/vm_templates.html

Or your own HTTP/FTP server, perform the following:

1. On the Resources page, click **Virtual Machine Images**, and then click **Import**.
2. Select **Download from External Source (HTTP and FTP)**. Click **Next**.
3. On the General Information page, enter the following general information:
 - Server Pool Name
Select the server pool on which the imported virtual machine will be located.
 - Sharing
Select whether you want to share this virtual machine, or keep it private.

`Private`: This indicates that the virtual machine can only be used by the user who imports it.

`Shared (group_name)`: This indicates that the virtual machine can be used by members of a specific group.
 - Virtual Machine Image Name
Enter a new name for the imported virtual machine. This must be unique. The name will be used as the name of the directory under `/OVS/running_pool`, where the files associated with this virtual machine are stored.

A virtual machine image name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (`_`) and hyphen (`-`) characters. The maximum name length is 48 characters.
 - Enable High Availability

You can enable high availability for the imported virtual machine. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).

- **Operating System**

Select the guest operating system of the imported virtual machine.

- **Virtual Machine System Username**

Enter the user name used to log in to the virtual machine.

- **Virtual Machine System Password**

Enter the password used to log in to the virtual machine.

- **Console Password**

Set the password for the VNC login to access the virtual machine.

- **Confirm Console Password**

Click **Next**.

4. On the Import Information page, enter the URL of the folder where the virtual machine you want to import is located. For example, enter either of the following:

```
http://example.com/vm
ftp://username:password@example.com/vm
```

If you are importing a VMware virtual machine, enter the URL of the .vmx file. For example, enter:

```
ftp://username:password@example.com/vm/vm.vmx
```

Oracle VM Manager first copies the necessary files of the virtual machine, then converts the virtual machine to an Oracle VM virtual machine, and finally generates the vm.cfg file. After conversion, the VMware virtual machine will be deleted.

When using a proxy, select **Use Proxy**, and enter the proxy address.

Click **Next**.

5. Confirm the information.
6. After importing, the status of the virtual machine is Pending. You need to approve it to make it available. See [Section 5.2.4, "Approving the Imported Virtual Machine Image"](#).

If the status turns out to be `Import Error`, click the error log link to check the detailed information.

5.2.1.3 Converting a Linux or Windows Host to a Virtual Machine (P2V)

You can convert a Linux or Windows host to an Oracle VM virtual machine template (Physical to Virtual, P2V). The conversion process is similar to downloading a template from external source.

Before conversion, you need to restart the Linux or Windows computer with the Oracle VM Server CD, and use P2V utility to start the conversion. For more information on how to use the P2V utility, see the *Oracle VM Server User's Guide*.

During the conversion, you are prompted to enter the number of virtual CPUs and memory size, and this information is configured in the vm.cfg file. The disk size in the virtual machine is determined by the size of the disks you have chosen to be included

in the virtual machine. Make sure the Virtual Machine Server has sufficient resources for the conversion (disk space).

The converted virtual machine is a hardware virtualized machine (HVM).

To convert a Linux or Windows host to a virtual machine:

1. On the Resources page, click **Virtual Machine Images**, and then click **Import**.

2. Select **Linux/Windows P2V Import**. Click **Next**.

3. On the General Information page, enter the following general information:

- **Server Pool Name**

Select the server pool on which the imported virtual machine will be located.

- **Sharing**

Select whether you want to share this virtual machine, or keep it private.

Private: This indicates that the virtual machine can only be used by the user who imports it.

Shared (group_name): This indicates that the virtual machine can be used by members of a specific group.

- **Virtual Machine Image Name**

Enter a name for the imported virtual machine. This must be unique. The name will be used as the name of the directory under `/OVS/running_pool`, where the files associated with this virtual machine are stored.

- **Enable High Availability**

You can enable high availability for the imported virtual machine. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).

- **Operating System**

Select the guest operating system of the imported virtual machine.

- **Virtual Machine System Username**

Enter the user name used to log in to the virtual machine.

- **Virtual Machine System Password**

Enter the password used to log in to the virtual machine.

- **Console Password**

Set the password for the VNC login to access the virtual machine.

- **Confirm Console Password.**

Click **Next**.

4. On the Import Information page, enter the host name or IP address of the computer. For example, enter:

`hostname.example.com`

When using a proxy, select **Use Proxy**, and enter the proxy address.

Click **Next**.

5. Confirm the information.

6. After importing, the status of the virtual machine is `Pending`. You need to approve it to make it available. See [Section 5.2.4, "Approving the Imported Virtual Machine Image"](#).

If the status turns out to be `Import Error`, click the error log link to check the detailed information.

5.2.2 Statuses of Virtual Machine Images

The imported virtual machine can be one of the following statuses:

- **Importing:** This status indicates that the virtual machine is in the process of being imported.
- **Pending:** This status indicates that the virtual machine has been imported successfully, and is waiting for the approval of the `Manager`.
- **Import Error:** This status indicates that there were some errors during the importing process. Click the link to check the error log. You may need to reimport the virtual machine, or delete it.

5.2.3 Reimporting a Virtual Machine Image

If an error occurs during downloading from an external source, check if the URL or proxy URL is correct, and then reimport the virtual machine.

To reimport a virtual machine:

1. On the Virtual Machine Images page, select the virtual machine you want to reimport, and click **Reimport**.
2. Enter the URL. When using a proxy, select **Use Proxy**.
3. Click **Reimport**.

5.2.4 Approving the Imported Virtual Machine Image

The process of approving and managing virtual machine images is similar to that of virtual machine templates. For more information, refer to [Section 5.1.4, "Approving the Imported Virtual Machine Template"](#).

After approving, click the **Virtual Machines** tab, and you can find the virtual machine is displayed in the Virtual Machines list.

You can change the preferred server and other configurations of the imported virtual machine. See [Section 6.7, "Editing Virtual Machine Configuration"](#).

5.2.5 Editing a Virtual Machine Image

To edit a virtual machine image, perform the following:

1. On the Virtual Machine Images page, select the virtual machine you want to update, and click **Edit**.
2. Update the virtual machine parameters. Click **Apply**.

For more information about the virtual machine parameters, refer to [Section 5.2.1, "Importing a Virtual Machine Image"](#).

5.2.6 Deleting a Virtual Machine Image

To delete a virtual machine image, perform the following:

1. On the Virtual Machine Images page, select the virtual machine you want to delete, and click **Delete**.
2. If prompted, confirm the delete operation.

5.3 Importing ISO Files

You can import ISO files to provide installation media for creating virtual machines. This section includes the following topics:

- [Importing an ISO File](#)
- [Statuses of ISO Files](#)
- [Reimporting an ISO File](#)
- [Approving the Imported ISO File](#)
- [Changing Status of an ISO File](#)
- [Deleting an ISO File](#)

5.3.1 Importing an ISO File

Common rules about ISO files management:

- Any user can import an ISO file.
- The Administrator or server pool manager approves the imported ISO files.
- All ISO files of one image should belong to the same ISO group.
- All users in the same server pool can share ISO files on the server pool.

Depending on where your ISO files are located, on the Virtual Machine Server, on other computers, or on the Internet, you can import ISO files from different resources as follows:

- [Selecting from the Server Pool](#)
- [Downloading from External Source](#)

5.3.1.1 Selecting from the Server Pool

If you already have some ISO files on your Server Pool, you can discover and register them in Oracle VM Manager directly.

Before importing, make sure the ISO files are in the folder `/OVS/iso_pool/iso_group_name` on the Virtual Machine Server. You can also download ISO files from other computers, or from the Internet, and then copy them to this folder.

To select an existing ISO file on the Server Pool, and register it in Oracle VM Manager, perform the following:

1. On the Resources page, click **ISO Files**, and then click **Import**.
2. Select **Select from Server Pool (Discover and register)**. Click **Next**.
3. On the General Information page, select the following ISO file information:
 - **Server Pool Name**
Select the server pool on which the ISO file is stored.
 - **ISO Group**
Select the ISO group. One ISO group may contain multiple ISO files.

- **ISO Label**

Select the ISO file you want to import.

Click **Next**.

4. Confirm the information.
5. After importing, the status of the ISO file is **Pending**. You need to approve it to make it available to use. See [Section 5.3.4, "Approving the Imported ISO File"](#).

5.3.1.2 Downloading from External Source

To download an ISO file from outside of the Server Pool, such as your own HTTP or FTP server, or from the Internet, perform the following:

1. On the Resources page, click **ISO Files**, and then click **Import**.
2. Select **Download from External Source (HTTP and FTP)**. Click **Next**.
3. On the General Information page, enter the following ISO file information:
 - **Server Pool Name**
Select the server pool on which the ISO file is to be used and stored.
 - **ISO Group**
Enter the name of the ISO group. One ISO group may contain multiple ISO files. The name will be used as the name of the directory under `/OVS/iso_` pool, where the ISO files of this group are stored.
 - **ISO Label**
Enter the ISO label used to identify the imported ISO file. For example, enter `CD1`.

An ISO label must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (`_`) and hyphen (`-`) characters. The maximum label length is 100 characters.
 - **URL**
Enter the path where the ISO file is located. You can import the ISO file through an FTP service or through an HTTP web service. For example, enter an address similar to the following:

`http://example.com/el5_img/disc1.iso`

`ftp://username:password@example.com/el5_img/disc1.iso`

When using a proxy, select **User Proxy** and enter the proxy address. For example, enter a proxy address similar to the following:

`http://example.com:8888`

Click **Next**.
4. Confirm the information.
5. After importing, the status of the ISO file is **Pending**. You need to approve it to make it available for creating virtual machines. See [Section 5.3.4, "Approving the Imported ISO File"](#).

5.3.2 Statuses of ISO Files

The imported ISO file can be one of the following statuses:

- **Importing:** This status indicates that the ISO file is in the process of being imported.
- **Pending:** This status indicates that the ISO file has been imported successfully, and is waiting for the approval of the Manager.
- **Import Error:** This status indicates that there were some errors during the importing process. Reimport the ISO file, or delete it.
- **Active:** This status indicates that the ISO file has been approved, and is available for creating virtual machines.
- **Inactive:** This status indicates that the ISO file is imported successfully, but not available.

5.3.3 Reimporting an ISO File

If an error occurs during external import, check if the URL or proxy URL is correct, and then reimport the ISO file.

To reimport an ISO file:

1. On the ISO Files page, select the ISO file you want to reimport, and click **Reimport**.
2. Enter the URL. When using a proxy, select **Use Proxy**.
3. Click **Reimport**.

5.3.4 Approving the Imported ISO File

The process of approving, and managing ISO files is similar to that of virtual machine templates. For more information, refer to [Section 5.1.4, "Approving the Imported Virtual Machine Template"](#).

5.3.5 Changing Status of an ISO File

To change the status of the ISO files, perform the following:

1. Select the ISO file and click **Edit**.
2. Select the status. It can be **Active** or **Inactive**. Click **Apply**.

Only active ISO files are available to users.

Note: Only an administrator or server pool manager of the server pool can approve, and manage the imported ISO files and virtual machines.

5.3.6 Deleting an ISO File

If you do not need an ISO file, or there are errors during the ISO file importing process, you can delete it.

To delete an ISO file, from the ISO page, select the ISO file you want to delete, and click **Delete**.

5.4 Managing Shared Virtual Disks

You can create shared virtual disks, and use them to expand your virtual machines storage capacity. The available virtual disks can also be used by other users in the group.

Oracle VM now only supports using files as virtual disks, namely, the prefix of the disk in the configuration file can only be `file`. Physical devices can be used, but cannot be changed through Oracle VM Manager. The following is an example:

```
disk = [ 'file:/tmp/para_seed/system.img,hda,w', ]
```

For more information on how to assign shared hard disks to a virtual machine, refer to [Section 6.7.3, "Storage"](#).

This section includes the following topics:

- [Creating a Shared Virtual Disk](#)
- [Searching a Shared Virtual Disk](#)
- [Deleting a Shared Virtual Disk](#)

5.4.1 Creating a Shared Virtual Disk

To create a shared virtual disk, perform the following:

1. On the Resources page, click **Shared Virtual Disk**, and then click **Create Shared Virtual Disk**.
2. On the Add Shared Virtual Disks page, enter or select the following parameters:
 - **Virtual Disk Name**
Enter the disk name.

A disk name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (_) and hyphen (-) characters. The maximum name length is 200 characters.
 - **Virtual Disk Size (MB)**
Allocate at least 1024 MB for the virtual disk.
 - **Server Pool Name**
Select the server pool on which the shared virtual disk can be used, and shared.
 - **Group Name**
Select the group that can use this shared virtual disk. You can select one of the following groups:
 - **My Workspace**: The virtual disk will be a private one, and only you can use it.
 - `group_name`: Select a specific group with whom you want to share this virtual disk. If the virtual disk is available after creation, any member of this group can use it.
3. Confirm the information you have entered.

5.4.2 Searching a Shared Virtual Disk

You can search shared virtual disks for a particular server pool and group.

To search a shared virtual disk, perform the following:

1. The search criteria include: virtual disk name, server pool name, group name, status. Use % as a wildcard.
2. Click **Search** to view the shared virtual disks.

5.4.3 Deleting a Shared Virtual Disk

Note: Make sure no application is using the virtual disk before you delete it.

To delete a shared virtual disk, perform the following:

1. Select the shared virtual disk, and click **Delete**.
2. Confirm the delete operation.

After you delete the virtual disk, all the files on it will be deleted as well.

Managing Virtual Machines

A virtual machine contains a guest operating system and some preinstalled applications. It runs on a Virtual Machine Server.

Before you create a new virtual machine, ensure that the following resources are available:

- A server pool
- A Virtual Machine Server to run the virtual machine
- Imported ISO files for creating virtual machines from installation media, or imported virtual machine templates for creating virtual machines based on templates

This chapter describes how to create and use virtual machines. It includes the following sections:

- [Overview of Virtual Machines](#)
- [Supported Guest Operating Systems](#)
- [Creating a Virtual Machine](#)
- [Starting and Shutting Down a Virtual Machine](#)
- [Connecting to a Virtual Machine's Console](#)
- [Viewing Details of a Virtual Machine](#)
- [Editing Virtual Machine Configuration](#)
- [Reproducing Virtual Machines](#)
- [Migrating a Virtual Machine](#)
- [Deleting a Virtual Machine](#)

Note: As a user with the `User` role, you can only manage your virtual machines, and cannot manage virtual machines created by other users. Only the `Manager` or the `Administrator` can manage all the virtual machines in the server pool.

6.1 Overview of Virtual Machines

Virtual machines in Oracle VM Manager have various types and statuses during the life cycle.

This section introduces:

- [Virtual Machine Types](#)
- [Virtual Machine Statuses](#)
- [Life Cycle Management of a Virtual Machine](#)
- [Viewing Virtual Machine Error Logs](#)

6.1.1 Virtual Machine Types

This section describes the following types of virtual machines in Oracle VM Manager:

- **Private Virtual Machine**
By default, a virtual machine belongs to the user who created it. Only the user who created the virtual machine can view and manage the virtual machine. The **My Workspace** group contains all the private virtual machines which the user has created.
- **Shared Virtual Machine**
You can share virtual machines with members of specific groups. For example, when you deploy a virtual machine, you can grant access rights to members of another group. Such a virtual machine is then known as a shared virtual machine.
- **Public Virtual Machine**
Virtual machines that are shared among all users are known as public virtual machines. Everyone can view and deploy public virtual machines.

Note: Users with the **User** role and **Manager** role may be restricted from accessing some specific virtual machines.

6.1.2 Virtual Machine Statuses

The status of a virtual machine reflects the operation process which the virtual machine is undergoing.

The status of a virtual machine can be one of the following:

- [Creating](#)
- [Initializing and Running](#)
- [Pausing, Paused and Unpausing](#)
- [Suspending, Suspended and Resuming](#)
- [Shutting Down and Powered Off](#)
- [Saving](#)
- [Cloning](#)
- [Migrating](#)
- [Error](#)

6.1.2.1 Creating

When the creation of a virtual machine is triggered, its status is set to **Creating**. This status indicates that the virtual machine is being created, and cannot be used.

6.1.2.2 Initializing and Running

When you start a virtual machine, the status changes from `Powered Off` to `Initializing`. Periodically refresh the virtual machine until the status changes from `Initializing` to `Running`. Now, you can log on to the running virtual machine, or perform live migration.

6.1.2.3 Pausing, Paused and Unpausing

After you pause a running virtual machine to stop it temporarily, its status changes from `Running` to `Pausing`. Periodically refresh the virtual machine until the status changes from `Pausing` to `Paused`.

When you unpause the virtual machine, the status changes from `Paused` to `Unpausing`. Periodically refresh the virtual machine until the status changes from `Unpausing` to `Running`.

6.1.2.4 Suspending, Suspended and Resuming

After you suspend a running virtual machine, its status changes from `Running` to `Suspending`. Periodically refresh the virtual machine until the status changes from `Suspending` to `Suspended`.

When you resume the suspended virtual machine, the status changes from `Suspended` to `Resuming`. Periodically refresh the virtual machine until the status changes from `Resuming` to `Running`.

6.1.2.5 Shutting Down and Powered Off

After you shut down a virtual machine, its status changes from `Running` to `Shutting Down`. Periodically refresh the virtual machine until the status changes from `Shutting Down` to `Powered Off`.

A virtual machine with the `Powered Off` status is available for deploying, cloning, or starting.

6.1.2.6 Saving

When you save a virtual machine as a template, the status of the original virtual machine is set to `Saving`. Periodically refresh the virtual machine until the status changes from `Saving` to `Powered Off`.

6.1.2.7 Cloning

During the cloning process, the status of the original virtual machine, based on which you clone the virtual machines, is set to the `Cloning` status. Periodically refresh the virtual machine until the status changes from `Cloning` to `Powered Off`.

6.1.2.8 Migrating


When you perform live migration, the status of the virtual machines changes from `Running` to `Migrating`. Periodically refresh the virtual machine until the status changes from `Migrating` to `Running`.

6.1.2.9 Error

The `Error` status indicates that there are some errors with the virtual machine, and it cannot be used. To solve the problem, perform the following:

1. On the Virtual Machines page, click the **Show** link of the virtual machine and check the error log information for more details. See [Appendix D.6, "The Status of the Virtual Machine Is "Error"."](#)
2. Shut down the virtual machine, and then retry your operation.
3. If the error persists, delete the virtual machine and create a new one.

Figure 6–1 Virtual Machine Status Mechanism



6.1.3 Life Cycle Management of a Virtual Machine

Typically, the life cycle of a virtual machine consists of the following process:

1. Create a virtual machine. See [Section 6.3, "Creating a Virtual Machine"](#).

2. Start the virtual machine. See [Section 6.4.1, "Starting a Virtual Machine"](#).
3. The virtual machine is now running, and you can access it using the Console. See [Section 6.5, "Connecting to a Virtual Machine's Console"](#).
4. To reduce system resource consumption, shut down the virtual machine when it is not in use. See [Section 6.4.2, "Shutting Down a Virtual Machine"](#).
5. When you no longer require the virtual machine, delete it. See [Section 6.10, "Deleting a Virtual Machine"](#).

The life cycle of a virtual machine created from template is slightly different from the one created from installation media, as shown in [Figure 6-2](#) and [Figure 6-3](#).

Figure 6-2 Life Cycle of a Virtual Machine Created from Template





Figure 6-3 Life Cycle of a Virtual Machine Created from Installation Media



During the life cycle of the virtual machine, the following actions can be taken:

- To view virtual machine error logs, see [Section 6.1.4, "Viewing Virtual Machine Error Logs"](#).
- To stop the virtual machine temporarily, see [Section 6.4.3, "Pausing and Unpausing a Virtual Machine"](#).
- To move data stored in the memory to the hard disk, and suspend the virtual machine, see [Section 6.4.4, "Suspending and Resuming a Virtual Machine"](#).
- To modify configurations of the virtual machine, see [Section 6.7, "Editing Virtual Machine Configuration"](#).
- To deploy the virtual machine to another server pool, and share it with other group members, see [Section 6.8.1, "Deploying a Virtual Machine"](#).

- To create multiple copies of the virtual machine, and share them with other users, see [Section 6.8.2, "Cloning Virtual Machines"](#).
- To save the virtual machine as a template, based on which other users can create their virtual machines, see [Section 6.8.3, "Saving a Virtual Machine as a Template"](#).
- To move the virtual machine to another server pool with applications on the virtual machine running, see [Section 6.9, "Migrating a Virtual Machine"](#).
- To delete the virtual machine when it is stuck in a certain status, see [Section 6.10.2, "Deleting a Virtual Machine Stuck in a Certain Status"](#).

6.1.4 Viewing Virtual Machine Error Logs

The errors that occur when you create or run a virtual machine are logged in Oracle VM Manager. The error log provides you with essential details for troubleshooting.

To view the error log information, go to the Virtual Machines page, click the **Show** link, and then click the **Log** link. The number displayed here reflects the number of log items.

The error log information includes: operation, operation details, start time, and status. [Appendix D.6, "The Status of the Virtual Machine Is "Error"'"](#) describes the error logs and how to solve the problems.

Figure 6–4 Error Log

ORACLE VM Manager

Home Profile Logout Help

Virtual Machines Resources Servers Server Pools Administration

Logged in as admin

Virtual Machines

Refresh in: 30 seconds Refresh Create Virtual Machine

Search

Virtual Machine Name: Server Pool Name:

Group Name:

Search

TIP Search criteria are case insensitive. Use '%' as a wildcard, for example prod%

Virtual Machines

Select and

Power On Console Power Off Configure More Actions: --Select-- Go

Select	Details	Virtual Machine Name	Size (MB)	Status	Owner	Group Name	Server Name	Server Pool Name
<input checked="" type="radio"/>	<input type="checkbox"/> Hide	OVM_EL5U2_X86_64_HVM_4GB	7,169	Powered Off	admin	My Workspace	N/A	server_pool01

Memory Size(MB): 1,024 VNC Port: 0
 Operating System: Oracle Enterprise Linux 5 64-bit Created Time: Jul 15, 2008 3:42:22 AM
 Virtualization Method: Fully Virtualized Power-On Time: Jul 15, 2008 3:42:50 AM
 Number of Cores: 1 Log: 0

Refresh in: 30 seconds Refresh Create Virtual Machine

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007, 2008 Oracle. All rights reserved. Oracle VM Manager 2.1.2

6.2 Supported Guest Operating Systems

An operating system installed inside a virtual machine is known as a guest operating system. Oracle VM supports a variety of guest operating systems. For information on supported guest operating system, see *Oracle VM Server User's Guide*.


6.3 Creating a Virtual Machine

Depending on what resources you have, you can obtain a virtual machine by using one of the following methods:

- If you have imported some virtual machine templates, you can create a new virtual machine by using a virtual machine template. See [Section 6.3.1, "Creating a New Virtual Machine Based on Virtual Machine Template"](#).
- If you have imported some ISO files, you can create a new virtual machine from the installation media, and then install the guest operating system by using the ISO files. See [Section 6.3.2, "Creating a New Virtual Machine from Installation Media"](#).
- If you want to start the virtual machine using Preboot Execution Environment (PXE) over a network, you can create a network bootable (PXE boot) virtual machine. See [Section 6.3.3, "Creating a Network Bootable \(PXE boot\) Virtual Machine"](#).
- You can also import a prebuilt virtual machine image directly. See [Section 5.2.1, "Importing a Virtual Machine Image"](#).

Before creating a new virtual machine, you must have a server pool that contains a Virtual Machine Server. See [Section 3.2, "Creating a Server Pool"](#) for information on creating server pools, and [Section 4.1, "Adding a Server"](#) for information on adding more Virtual Machine Servers.

[Figure 6–5](#) shows the basic steps required to create a new virtual machine.

Figure 6–5 Basic Steps to Create a New Virtual Machine

6.3.1 Creating a New Virtual Machine Based on Virtual Machine Template

Typically, a virtual machine template can contain:

- An operating system
- The basic configuration, such as the number of virtual CPUs, the amount of memory, the size of disk, and so on
- Preinstalled applications

For information on how to obtain virtual machine templates, see [Section 5.1, "Importing Virtual Machine Templates"](#).

You can create a virtual machine by cloning a template. The virtual machine will then inherit all the content and configuration from the template.

To create a virtual machine based on a template, perform the following:

1. Select **Create virtual machine based on virtual machine template**. Click **Next**.
2. Select the server pool where the virtual machine is to be located, and select the preferred server.

A preferred server is a Virtual Machine Server that provides resources such as memory, CPUs, virtual network interfaces (VIFs), and disk for the virtual machine. If you select only one Virtual Machine Server as the preferred server, the virtual

machine then always starts from and runs on this server. If you select multiple preferred servers, each time the virtual machine starts, it will choose to run on the one with the maximum resources available (including memory and CPU).

When creating a virtual machine, there are two ways to select a Virtual Machine Server for the virtual machine:

- **Auto:** In the Auto mode, when the virtual machine starts, Oracle VM automatically assigns a Virtual Machine Server with the maximum resources available to run the virtual machine. The virtual machine then runs on this Virtual Machine Server temporarily, until it is shut down.
- **Manual:** In the Manual mode, you select one or more Virtual Machine Servers as the preferred servers. The virtual machine then starts from and runs on the preferred server with the maximum resources available.

Note: If none of the preferred servers can provide sufficient resources, the virtual machine may fail to start.

Click **Next** to proceed to the next page.

3. Select the template, which the virtual machine is based on. Click **Next**.
4. Enter the virtual machine name, and set the console password. The name will be used as the name of the directory under `/OVS/running_pool`, where the files associated with this virtual machine are stored.

If you want to enable high availability (HA) for this virtual machine, select **Enable High Availability**. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).

5. Optionally, click **Add Row** to add more virtual network interfaces. By default, virtual network interfaces are named `VIF0`, `VIF1`, `VIF2`, and so on. You can rename them *after* creating the virtual machine. See [Section 6.7.2, "Network"](#).

Oracle VM automatically assigns a random MAC address to the virtual network interface.

Select a bridge for the virtual network interface. By default, the number of bridges is the same as that of physical adaptors, and the bridges are named after physical adaptors. For example, if the Virtual Machine Server has several physical adaptors, `eth0`, `eth1`, `eth2`, and so on, the bridges are then named `xenbr0`, `xenbr1`, `xenbr2`, and so on.

When creating a virtual machine, you can set a maximum of *three* virtual network interfaces. After the virtual machine is created, you can set a maximum of *eight* virtual network interfaces. See [Section 6.7.2, "Network"](#).

Click **Next** to proceed to the next page.

6. Confirm the virtual machine information.
7. The process of creating a virtual machine takes time. Click **Refresh** periodically until the status of the virtual machine changes from `Creating` to `Powered Off`. You can choose to refresh manually, or to refresh every 30 seconds.

If the status turns out to be `Error`, refer to [Section 6.1.2.9, "Error"](#) for how to solve this problem.

Now you can start and log in to the virtual machine. By default, the virtual machine is private. Only you can access it.

In the virtual machine list, click **Show** to view the detailed information of the virtual machine.

Some parameters of the virtual machine, such as the virtual network interface and the boot source, are set by default. You cannot change them during the process of creating the virtual machine. If you want to change them *after* creating the virtual machine, see [Section 6.7, "Editing Virtual Machine Configuration"](#).

6.3.2 Creating a New Virtual Machine from Installation Media

If you have ISO files available, you can create a virtual machine from installation media, and configure the parameters manually. To create a virtual machine from installation media:

1. Select **Create from installation media**. Click **Next**.
2. Select the server pool where the virtual machine is to be located, and select a Virtual Machine Server on which the virtual machine will run.

Select **Auto** to assign a Virtual Machine Server automatically to the virtual machine, or select **Manual** to specify one or more preferred servers manually. For more information on the preferred server, see Step 2 in [Section 6.3.1, "Creating a New Virtual Machine Based on Virtual Machine Template"](#).

Click **Next** to proceed to the next page.

3. Select the virtualized method: **Fully Virtualized**, or **Paravirtualized**.

- **Fully Virtualized**

Select an ISO file from the list. For more information on supported guest operating systems, see *Oracle VM Server User's Guide*.

If you require more than one ISO file to create the virtual machine, select the first ISO file here. After creating the virtual machine, you need to log in to the virtual machine to install the guest operating system. See [Section 6.5.2, "Logging In to a Virtual Machine"](#).

See Also: For more information on importing ISO files, refer to [Section 5.3.1, "Importing an ISO File"](#).

Note: Do not use an ISO image that has Oracle VM Server installed on it. Otherwise, after creating the virtual machine, you will not be able to start it.

In the fully virtualized method, also known as the hardware virtualized machine (HVM), the unmodified guest operating system runs on the virtual machine. It traps and emulates every I/O and hardware instruction.

To apply the fully virtualized mode, you must have either an Intel processor with Virtualization Technology (VT) extension, or an AMD processor with Secure Virtual Machine (SVM) extension (also called AMD-V) available on the host. A complete list of compatible processors is available at:

http://wiki.xensource.com/xenwiki/HVM_Compatible_Processors

Note: Make sure the CPU and operating system support HVM, and you have enabled it in the BIOS. For more information, see [Appendix D.3, "Cannot Create a Virtual Machine from Installation Media"](#).

If the CPU does not support HVM, use the paravirtualized method to create the virtual machine.

- Paravirtualized

Before you create the virtual machine using the paravirtualized method, mount the ISO file on an NFS share, or HTTP or FTP server:

```
# mkdir mount-point
# mount -o loop,ro cd1.iso mount-point
```

Where, *mount-point* refers to the directory to which you want to mount the files. If you have multiple ISO files, you can mount each ISO file and copy the contents into a single directory, and then mount that directory.

In the **Resource Location** field, enter the full path of the *mount point*. HTTP, FTP, and NFS are supported. For example, enter a path similar to the following:

```
http://example.com/EL5-x86
```

In the paravirtualized method, the guest operating system is recompiled before being installed on a virtual machine. Also, the virtual machine does not need to trap privileged instructions. Trapping is a method used to handle unexpected conditions, or conditions that are not allowed, which is time-consuming and can impact operating system performance. Without trapping privileged instructions, the paravirtualized operating system runs at near native speed.

4. Enter the following information for the virtual machine:

- Virtual Machine Name

Enter the name of the virtual machine. This must be unique. The name will be used as the name of the directory under `/OVS/running_pool` on the Virtual Machine Server, where the files associated with this virtual machine are stored.

A virtual machine name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (`_`) character. The maximum name length is 200 characters.

- Number of Virtual CPUs

Select an appropriate number of virtual CPUs for the virtual machine according to the operating system and application consumptions. You can allocate a maximum of 32 virtual CPUs. The larger number you select, the more CPU resources the virtual machine can get.

If the sum of virtual CPUs on all the running virtual machines exceeds that of physical CPUs, each virtual CPU will get that fraction of CPU time. For example, if the sum of virtual CPUs on all the running virtual machines is 8, and you have 4 physical CPUs on the Virtual Machine Server, then each virtual CPU will get $4/8$, namely 50%, of CPU time, given that all the virtual CPUs are fully utilized at the same time.

- Keyboard Layout

Select an appropriate keyboard you need to use to interact with the virtual machine.

- Memory Size (MB)

Allocate an appropriate amount of memory for the virtual machine. Allocate at least 256 MB of memory. When allocating memory, consider the following:

- Memory consumption of applications that will run on the virtual machine
- Memory consumption of applications that are running and will run on the Virtual Machine Server
- Memory resources to be allocated to other virtual machines

- Virtual Disk Size (MB)

Allocate at least 1024 MB of virtual disk. When allocating disk, consider the following:

- Disk consumption of applications that will run on the virtual machine
- Disk consumption of applications that are running and will run on the Virtual Machine Server
- Disk resources to be allocated to other virtual machines

- Console Password

Set the console password for connecting to the virtual machine by using VNC.

- Confirm Console Password

Re-enter the console password.

If you want to enable high availability (HA) for this virtual machine, select **Enable High Availability**. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).

Click **Next** to proceed to the next page.

5. Optionally, click **Add Row** to add more virtual network interfaces (VIFs). By default, virtual network interfaces are named *VIF0*, *VIF1*, *VIF2*, and so on. You can rename them *after* creating the virtual machine. See [Section 6.7.2, "Network"](#).

Oracle VM automatically assigns a random MAC address to the virtual network interface.

Select a bridge for the virtual network interface. By default, the number of bridges is the same as that of physical adaptors, and the bridges are named after physical adaptors. For example, if the Virtual Machine Server has several physical adaptors, *eth0*, *eth1*, *eth2*, and so on, the bridges are then named *xenbr0*, *xenbr1*, *xenbr2*, and so on.

When creating a virtual machine, you can set a maximum of *three* virtual network interfaces. After the virtual machine is created, you can set a maximum of *eight* virtual network interfaces. See [Section 6.7.2, "Network"](#).

Click **Next** to proceed to the next page.

6. Confirm the virtual machine information you have entered.
7. The process of creating a virtual machine takes time. Click the **Refresh** button periodically until the status of the virtual machine changes from *Creating* to *Running*. You can choose to refresh manually, or to refresh every 30 seconds.

If the status turns out to be `Error`, refer to [Section 6.1.2.9, "Error"](#) for how to solve this problem.

Now you can log in to the virtual machine and install the guest operating system. See [Section 6.5, "Connecting to a Virtual Machine's Console"](#). By default, the virtual machine is private. Only you can access it.

In the virtual machine list, click **Show** to view the detailed information of the virtual machine.

Some parameters of the virtual machine, such as the virtual network interface and the boot mode, are set by default. You cannot change them during the process of creating the virtual machine. If you want to change them *after* creating the virtual machine, see [Section 6.7, "Editing Virtual Machine Configuration"](#).

6.3.3 Creating a Network Bootable (PXE boot) Virtual Machine

If you have neither virtual machine templates nor ISO files for the moment, you can create a network bootable (PXE boot) virtual machine that has the minimum configuration information, then start the virtual machine through Preboot Execution Environment (PXE) over a network later to install the guest operating system.

To create a network bootable (PXE boot) virtual machine, perform the following:

1. Select **Create a network bootable virtual machine (pxeboot)**. Click **Next**.
2. Select the server pool where the virtual machine is to be located, and select a Virtual Machine Server on which the virtual machine will run.

Select `Auto` to assign a Virtual Machine Server automatically for the virtual machine, or select `Manual` to specify one or more preferred servers manually. For more information on the preferred server, see Step 2 in [Section 6.3.1, "Creating a New Virtual Machine Based on Virtual Machine Template"](#).

Click **Next** to proceed to the next page.

3. Enter the following information for the virtual machine:

- **Virtual Machine Name**

Enter the name of the virtual machine. This must be unique. The name will be used as the name of the directory under `/OVS/running_pool`, where the files associated with this virtual machine are stored.

A virtual machine name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (`_`) character. The maximum name length is 200 characters.

- **Virtualization Method**

Select `Fully Virtualized`, or `Paravirtualized`. See Step 3 in [Section 6.3.2, "Creating a New Virtual Machine from Installation Media"](#) for information on the difference between fully virtualized and paravirtualized.

- **Operating System**

Select the guest operating system of the virtual machine.

- **Number of Virtual CPUs**

Select an appropriate number of virtual CPUs for the virtual machine according to the operating system and application consumptions. You can allocate a maximum of 32 virtual CPUs. The larger number you select, the more CPU resources the virtual machine can get.

If the sum of virtual CPUs on all the running virtual machines exceeds that of physical CPUs, each virtual CPU will get that fraction of CPU time. For example, if the sum of virtual CPUs on all the running virtual machines is 8, and you have 4 physical CPUs on the Virtual Machine Server, then each virtual CPU will get 4/8, namely 50%, of CPU time, given that all the virtual CPUs are fully utilized at the same time.

- **Memory Size (MB)**

Allocate an appropriate amount of memory for the virtual machine. Allocate at least 256 MB of memory. When allocating memory, consider the following:

- Memory consumption of applications that will run on the virtual machine
- Memory consumption of applications that are running and will run on the Virtual Machine Server
- Memory resources to be allocated to other virtual machines

- **Virtual Disk Size (MB)**

Allocate at least 1024 MB of virtual disk. When allocating disk, consider the following:

- Disk consumption of applications that will run on the virtual machine
- Disk consumption of applications that are running and will run on the Virtual Machine Server
- Disk resources to be allocated to other virtual machines

- **Console Password**

Set the console password for connecting to the virtual machine by using VNC.

- **Confirm Console Password**

Re-enter the console password.

If you want to enable high availability (HA) for this virtual machine, select **Enable High Availability**. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).

Click **Next** to proceed to the next page.

4. Optionally, click **Add Row** to add more virtual network interfaces (VIFs). By default, virtual network interfaces are named *VIF0*, *VIF1*, *VIF2*, and so on. You can rename them *after* creating the virtual machine. See [Section 6.7.2, "Network"](#).

Oracle VM automatically assigns a random MAC address to the virtual network interface.

Select a bridge for the virtual network interface. By default, the number of bridges is the same as that of physical adaptors, and the bridges are named after physical adaptors. For example, if the Virtual Machine Server has several physical adaptors, *eth0*, *eth1*, *eth2*, and so on, the bridges are then named *xenbr0*, *xenbr1*, *xenbr2*, and so on.

When creating a virtual machine, you can set a maximum of *three* virtual network interfaces. After the virtual machine is created, you can set a maximum of *eight* virtual network interfaces. See [Section 6.7.2, "Network"](#).

Click **Next** to proceed to the next page.

5. Confirm the virtual machine information you have entered.

6. The process of creating a virtual machine takes time. Click the **Refresh** button periodically until the status of the virtual machine changes from `Creating` to `Powered Off`. You can choose to refresh manually, or to refresh every 30 seconds.

If the status turns out to be `Error`, refer to [Section 6.1.2.9, "Error"](#) for how to solve this problem.

Before starting the virtual machine, you need to configure the DHCP and TFTP server first, and then start the virtual machine remotely over the network to install the guest operating system.

By default, the network bootable (PXE boot) virtual machine starts through PXE.

In the virtual machine list, click **Show** to view the detailed information of the virtual machine.

Some parameters of the virtual machine, such as the virtual network interface and the boot source, are set by default. You cannot change them during the process of creating the virtual machine. If you want to change them *after* creating the virtual machine, see [Section 6.7, "Editing Virtual Machine Configuration"](#).

6.4 Starting and Shutting Down a Virtual Machine

After a virtual machine is created, you can start it or shut it down. When a virtual machine is running, you can pause it or suspend it to stop it temporarily.

- [Starting a Virtual Machine](#)
- [Shutting Down a Virtual Machine](#)
- [Pausing and Unpausing a Virtual Machine](#)
- [Suspending and Resuming a Virtual Machine](#)

6.4.1 Starting a Virtual Machine

Starting a virtual machine is analogous to starting a computer by pressing the **Power On** button.

Note: Ensure that the virtual machine status is `Powered Off` before you start it.

To start a virtual machine:

1. Click the **Virtual Machines** tab.
2. On the Virtual Machines page, select the virtual machine you want to start.
3. Click the **Power On** button.

Periodically, click the **Refresh** button until the virtual machine status changes from `Initializing` to `Running`. You can choose to refresh manually, or to refresh every 30 seconds.

6.4.2 Shutting Down a Virtual Machine

When you do not use the virtual machine and log out, shut it down to release system resources.

Note: Shut down the virtual machine only when the virtual machine status is *Running*.

To shut down a virtual machine, perform the following:

1. Click the **Virtual Machines** tab.
2. On the Virtual Machines page, select the virtual machine you want to shut down. The virtual machine status should be *Running*.
3. Click **Power Off**.

Note that if you have enabled high availability for this virtual machine, you need to shut it down by clicking the **Power Off** button; otherwise, if you shut down the virtual machine through the guest operating system, high availability will take effect, and the virtual machine will restart instead of shutting down.

6.4.3 Pausing and Unpausing a Virtual Machine

Pausing a virtual machine allows you to save the virtual machine at a certain processing point, and resume it again quickly.

When you pause a virtual machine, the state of the virtual machine is saved, and the running operations will not be restarted as long as they have no persistent communication with other computers. All the settings in the virtual machine, and all the devices, such as CPUs, VIFs, amount of memory, and so on, remain the same. But the processes of the virtual machine are no longer scheduled by Oracle VM Server to be run on any CPU. Therefore if the virtual machine is running a server such as a Web server, it will appear to the clients that the virtual machine is shut down.

Note: Pause the virtual machine only when the virtual machine status is *Running*.

To pause a running virtual machine:

1. Click the **Virtual Machines** tab.
2. On the Virtual Machines page, select the virtual machine you want to pause.
3. Select **Pause**, and click **Go**.

To unpause the virtual machine, select **Unpause** and click **Go**. Unpausing a virtual machine is much faster than starting a virtual machine.

After unpausing, the applications resume from where they were paused, and the virtual machine content remains unchanged.

6.4.4 Suspending and Resuming a Virtual Machine

Use the Suspend function to save the status information of a running virtual machine to the disk. You can suspend a virtual machine when you need to back up the current status information, and restore it quickly.

After you suspend the virtual machine, all the status information is saved to the disk, and virtual machine is no longer running, thus the memory allocated to the virtual machine will be released for other virtual machines to use. When the virtual machine is suspended, the network connections will no longer be available.

Note: Suspend the virtual machine only when the virtual machine status is **Running**.

To suspend a running virtual machine:

1. Click the **Virtual Machines** tab.
2. On the Virtual Machines page, select the virtual machine you want to suspend.
3. Select **Suspend**, and click **Go**.

To resume the virtual machine, select **Resume** and click **Go**.

6.5 Connecting to a Virtual Machine's Console

If it is the first time you attempt to access a virtual machine, you need to install a plug-in to enable the **Console** button in Oracle VM Manager. After installing the plug-in, you can log in to the virtual machine.

- [Installing the Console Plug-In](#)
- [Logging In to a Virtual Machine](#)

6.5.1 Installing the Console Plug-In

The plug-ins you need to install vary, depending on which browser and operating system you are using to access Oracle VM Manager.

If you are using a Mozilla Firefox browser on Linux, download the Console Plug-in at: <http://oss.oracle.com/oraclevm/manager/RPMS>, and install it on the computer where your browser is running.

To install the Console Plug-in, perform the following:

1. Install the Console Plug-in using the command:

```
# rpm -ivh ovm-console-version.rpm
```

Where, *version* refers to the ovm-console version. It can be *1.0.0-2.x86_64* or *1.0.0-2.i386*.

2. If you have no standard installation of Mozilla Firefox, copy files:

```
# cp /opt/ovm-console/etc/mozpluggerrc /etc/
# cp /opt/ovm-console/bin/* /usr/bin
# cp /opt/ovm-console/lib/mozilla/plugins/ovm-console-mozplugger.so
/opt/firefox/plugins
```

Where, */opt/firefox/plugins* refers to the Firefox plug-in folder.

3. Restart Mozilla Firefox.

If you are using Internet Explorer (IE) on Windows, you need to download and install the TightVNC-Java applet on the Oracle VM Manager host. For information on installing the TightVNC-Java applet, see *Oracle VM Manager Installation Guide*.


6.5.2 Logging In to a Virtual Machine

The virtual machine is now running, and the Console Plug-in has been installed, and you can log in to it by using the Console.

To log in to the virtual machine, perform the following:

1. On the Virtual Machines page, select the running virtual machine, and then click **Console**.
2. A VNC Authentication is displayed. Enter the console password, and click **OK**.

Figure 6–6 VNC Authentication



3. Enter the user name and password of the guest operating system to log in to the virtual machine.


After the VNC authentication, you may need to continue with some further tasks before you can use the virtual machine, depending on the method by which you created the virtual machine.

- If you created this virtual machine based on a template, you can directly use the guest operating system and applications installed in advance, without any further configurations.
- If you created this virtual machine using the fully virtualized method, the installation of the guest operating system is triggered after your first login. Follow the installation wizard to install the guest operating system.

If you need more ISO files to complete the installation, select the next ISO file and then click **Change CD** to continue the installation, as shown in [Figure 6–7, "Changing CD"](#). Repeat this step until all the ISO files are installed.

For information on the supported guest operating systems, see *Oracle VM Server User's Guide*.

For more information on creating virtual machines using the fully virtualized method, refer to [Section 6.3.2, "Creating a New Virtual Machine from Installation Media"](#).

Figure 6–7 Changing CD

6.6 Viewing Details of a Virtual Machine

To view more details of the virtual machine:

1. Click the **Virtual Machines** tab.
2. In the **Details** column, click the **Show** link. You can see information such as, memory size, operating system, virtualization method, number of virtual CPUs, VNC port, creation time, power-on time, and a link to the log file.

If the virtual machine is running or shutting down, you can click the link of the VNC port number to open the VNC Authentication window and log in.

You can also click the link of the log number to view error log information. For more information about the error log, see [Appendix D.6, "The Status of the Virtual Machine Is "Error"."](#)

To view or change more configurations of the virtual machine, see [Section 6.7, "Editing Virtual Machine Configuration"](#).

6.7 Editing Virtual Machine Configuration

When creating a virtual machine, you can configure some of the parameters, such as the number of virtual CPUs, the size of memory, and so on; while the other parameters, such as boot source and the type of virtual network interfaces (VIFs), are assigned default settings by Oracle VM Manager, and you cannot configure them when creating the virtual machine. If needed, you can configure such parameters *after* the virtual machine is created.

To modify configurations of the virtual machine:

1. Click the **Virtual Machines** tab.
2. In the Virtual Machines table, you can

- Select the virtual machine you want to configure, and then click the **Configure** button.
- Or click the name of the virtual machine directly.

On the Edit page, you can modify the following information:

- [General](#)
- [Network](#)
- [Storage](#)
- [Preferred Server](#)
- [Profiles](#)

Some parameters, including the increased memory size, and the modified network information and virtual disk, can take effect immediately without restarting the virtual machine; for the other modified parameters to take effect, you need to restart the virtual machine.

6.7.1 General

On the General page, you can modify the general parameters of the virtual machine, including:

- **Virtual Machine Name**
Enter a new name for the virtual machine.
A virtual machine name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (_) character. The maximum name length is 200 characters.
- **Maximum Memory Size (MB)**
Enter the maximum size of memory that the virtual machine can consume. The default maximum size of memory is the same as the size you allocated when creating the virtual machine.
Change the maximum memory size only when the status of the virtual machine is **Powered Off**.
- **Memory Size (MB)**
Increase or decrease the memory size of the virtual machine. Allocate at least 256 MB memory.
Increased memory takes effect immediately without restarting the virtual machine. If you decrease the size of memory, you need to restart the virtual machine for the change to take effect.
- **Number of Virtual CPUs**
Change the number of virtual CPUs. Restart the virtual machine for the changes to take effect.
- **Enable High Availability**
You can enable high availability (HA) to guarantee the availability of virtual machines in case of the physical server failure or restart.
To make high availability take effect, you must enable high availability for both the server pool and the virtual machine. For more information about high availability, see [Section 3.6, "Enabling High Availability \(HA\)"](#).

To enable high availability for this virtual machine, select **Enable High Availability**.

- Description

A description of the virtual machine.

Click **Save** to save the configurations you have modified.

There is some other information you can view on this page, as shown in [Table 6–1](#).

Table 6–1 General Information

Item	Description
Created By	The user who now owns this virtual machine
Status	The current status of the virtual machine. For more information on the status, see Section 6.1.2, "Virtual Machine Statuses" .
Group Name	The group to which the virtual machine belongs.
Server Pool Name	The server pool in which the virtual machine is located
PVDriver Initialized	Whether PVDriver is initialized on the hardware virtualized machine (HVM) or not. Paravirtualized virtual machines (PV) do not have this parameter. The status can be one of the following: <ul style="list-style-type: none"> ■ True: PVDriver is installed on this hardware virtualized machine (HVM). ■ False: PVDriver is not installed on this hardware virtualized machine (HVM); or it is installed but not initialized. ■ Unknown: The virtual machine is shut down; Oracle VM Manager cannot detect the status of PVDriver; or you need to upgrade Oracle VM Agent to support this feature.
Creation Time	The time when the virtual machine was created
Running Time	How long the virtual machine has been running
Size (MB)	The total size of the virtual machine

Figure 6–8 General Information

The screenshot shows the Oracle VM Manager interface. At the top, there's a navigation bar with 'Virtual Machines', 'Resources', 'Servers', 'Server Pools', and 'Administration'. Below this, a breadcrumb trail shows 'Virtual Machines > Virtual Machine Configure'. The main content area has tabs for 'General', 'Network', 'Storage', 'Preferred Server', and 'Profiles'. The 'General' tab is active, displaying 'General Information' and 'Detailed Information' sections. The 'General Information' section lists: Created By: admin, Status: Powered Off, Group Name: My Workspace, Server Pool Name: MyServerPool, Creation Time: Jun 13, 2009, Running Time: N/A, and Size (MB): 13313. The 'Detailed Information' section lists: * Virtual Machine Name: MyVirtualMachine, * Maximum Memory Size (MB): 2048, * Memory Size (MB): 2048, Number of Virtual CPUs: 2 (with a dropdown arrow), Enable High Availability: (unchecked checkbox), and Description: (empty text area). A 'Save' button is located at the top right of the configuration area. At the bottom, there's a footer with 'Copyright © 2007-2009. Oracle. All rights reserved. Oracle VM Manager 2.1.5'.

6.7.2 Network

On the Network page, you can add, edit, or delete virtual network interfaces. You can set a maximum of eight virtual network interfaces.

Select Virtual Machine Type

If the virtual machine is a fully virtualized (hardware virtualized) machine, you can configure the virtual network interface (VIF) type to be either:

- **Fully Virtualized**
- **Paravirtualized**

The paravirtualized driver, also known as the netfront driver, can be used with either a paravirtualized machine, or a fully virtualized machine. The fully virtualized driver, also known as the ioemu driver, can only be used with a fully virtualized machine. Both drivers contain the BIOS and device emulation code to support fully virtualized machines.

For fully virtualized machines, the type can be either **Fully Virtualized** (ioemu) or **Paravirtualized** (netfront), and the default is **Fully Virtualized** (ioemu). For paravirtualized machines, the default is **Paravirtualized** (netfront), and this cannot be changed.

After you configure the virtual network interface type for one virtual network interface, all the virtual network interfaces in the virtual machine will be set to the same type.

Add a Virtual Network Interface (VIF)


To add a VIF:

1. Click **Add**.
2. Enter a name, and then select a bridge.
3. In Oracle VM, all the virtual network interfaces (VIFs) share the physical network interface card (NIC) to communicate with the outside. If you have several VIFs, and you want to control how much bandwidth is granted to each VIF, you can configure the rate limit.

Select **Enable Rate Limit**, and enter the rate value. The network traffic through the virtual network interface will not exceed the limit. The change will take effect without restart.

You can also edit or delete an existing VIF on this page.

Figure 6–9 Network Information



6.7.3 Storage

There are two ways to expand the storage capacity of a virtual machine: by creating non-sharable virtual disks, or by adding shared virtual disks.

Oracle VM Manager only supports file-based disks. Physical disks are not supported.

Note: For a hardware virtualized machine (HVM), you can attach up to four IDE disks (including CD-ROM and shared virtual disks), and seven SCSI disks.

A paravirtualized machine (PV) has no such limitation. But you need to restart it for the disk changes to take effect.

Use Non-sharable Virtual Disks

To create a non-sharable virtual disk:

1. Click the **Create New Virtual Disk** button.
2. Enter the disk name and size. Allocate at least 1024 MB to the virtual disk.

For a hardware virtualized machine (HVM), if you select **Auto**, Oracle VM Agent first selects **IDE** as the type of the hard driver. If the IDE disks have reached the

maximum of four, Oracle VM Agent then selects **SCSI**. If the SCSI disks have reached the maximum of seven, you cannot add any more disks. To verify how many interfaces are available, see the message on the upper right of the page, as shown in [Figure 6–10](#).

For a paravirtualized machine (PV), there is no limitation.

Figure 6–10 Available Disk Interfaces

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources Servers Server Pools Administration

Virtual Machines > Virtual Machine Configure Logged in as admin

Virtual Machines : OVM_EL5U2_X86_64_HVM_4GB

General Network Storage Preferred Server Profiles

Available Slot Interface: 7 Available IDE Interface: 0 Available SCSI Interface: 7

Virtual Disks Boot Source/CDROM

Virtual Disks

Select and Delete Edit Create New Virtual Disk Add Shared Virtual Disk Refresh

Select	Virtual Disk Name	Size (MB)	Frontend Device	Hard Disk Driver	QoS	Priority Class	Shared	Status	
								Disk Attachment	Disk Status
<input checked="" type="radio"/>	snake	1,024	hdb	IDE	Y	3	Non-Sharable		Active
<input type="radio"/>	houfaxin	1,024	hdd	Auto	Y	4	Non-Sharable	Attached	Active
<input type="radio"/>	system	6,145		Unknown		N/A	Non-Sharable		

General Network Storage Preferred Server Profiles

Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007, 2008, Oracle. All rights reserved. Oracle VM Manager 2.1.2

If you want to prioritize the virtual disk, you can enable disk priority with the **QoS Enabled** check box, and select an appropriate priority class. The priority class ranges from 0 to 7. The priority class 0 has the highest priority, and 7 the lowest.

Rather than being confined to a particular virtual machine, the priority of a virtual disk is global on the entire Oracle VM Server. Virtual disks of the same priority class take the same priority on the Oracle VM Server, even if they belong to different virtual machines.

There are three IO scheduling classes: Idle, Best Effort, and Real Time. Oracle VM adopts the Real Time scheduling class. The Real Time scheduling class is given the first access to the disk, regardless of what else is going on in the system. The eight priority levels are defined denoting how big a time slice a given process will receive on each scheduling window.

3. Click **Next**, and confirm the information you have entered.

The new virtual disk can only be used by this virtual machine. You cannot share it.

To delete the non-sharable virtual disk, select it, and then click the **Delete** button. After you delete the virtual disk, all the files on it will be deleted as well.

To delete shared virtual disks, see [Section 5.4.3, "Deleting a Shared Virtual Disk"](#).

Use Shared Virtual Disks

Shared virtual disks can only be shared among virtual machines within the same server pool. For information on how to create shared virtual disks, see [Section 5.4.1, "Creating a Shared Virtual Disk"](#).

To assign a shared disk to the virtual machine:

1. Click the **Add Shared Virtual Disk** button.
2. From the **Available Shared Virtual Disks** column, double-click the disk name to move it to the **Selected Shared Virtual Disks** column.
3. Click **Apply** or **OK**.

The selected virtual disk is displayed in the virtual disk table.

To release a virtual disk assigned to the virtual machine, move the virtual disk from the **Selected Shared Virtual Disks** column to the **Available Shared Virtual Disks** column, and click **Apply** or **OK**. The virtual disk is removed from the virtual disk table. Now you can assign it to another virtual machine.

Virtual Disks Table

[Table 6–2](#) displays the information you can view on the Virtual Disks Table.

Table 6–2 Column Headers in the Virtual Disks Table

Column Header	Description
Virtual Disk Name	The name of the virtual disk.
Size	The size of the virtual disk.
Frontend Device	The name of the disk displayed in the virtual machine.
Hard Disk Driver	The type of the hard disk. For a hardware virtualized machine (HVM), it can be IDE , SCSI , or Auto . For a paravirtualized machine (PV), it can be IDE , SCSI , XVD , or Auto .
QoS	Whether the QoS is enabled or not.
Priority Class	If QoS is enabled, the value of the priority class is displayed here.
Shared	Whether the virtual disk is shared or not.
Status - Disk Attachment	Whether the disk is attached to the virtual machine or not. It can be either of the following statuses: <ul style="list-style-type: none"> ■ Attached: The disk is attached to the virtual machine. It works well. ■ Detached: The disk is not attached to the virtual machine, due to the lack of disk interfaces. For example, you create an IDE disk, but now the number of IDE disks exceeds four, no more IDE interface available for this disk. Therefore the disk is detached. <p>It is also possible that Oracle VM Agent cannot connect to the disk. In this case, you need to edit the storage and save your changes. Oracle VM Agent will then reconnect to the disk.</p>

Table 6–2 (Cont.) Column Headers in the Virtual Disks Table

Column Header	Description
Status - Disk Status	<p>The status of the disk can be one of the following:</p> <ul style="list-style-type: none"> ■ Creating: The disk is being created. It may take a few minutes. ■ Active: The disk is now available. ■ Deleting: The disk is being deleted. ■ Error: Some errors occur to the disk. You need to delete it and create a new one.

Boot Source/CDROM

- Boot Device

You can choose to start the virtual machine from any of the following:

- HDD: Start the virtual machine from the hard disk.
- CDROM: Start the virtual machine from the CD-ROM. This option is only available to hardware virtualized machines (HVM).
- PXE: Start the virtual machine through Preboot Execution Environment (PXE).

- CD-ROM


Select the ISO file from which to start installing the guest operating system of the virtual machine. This option is only available to hardware virtualized machines (HVM).

6.7.4 Preferred Server

You can choose the Manual mode to run the virtual machine on a specified server, or choose the Auto mode to allow Oracle VM to assign a Virtual Machine Server automatically to run the virtual machine. For more information about the preferred server, see Step 2 in [Section 6.3.1, "Creating a New Virtual Machine Based on Virtual Machine Template"](#).

Note: If none of the preferred servers can provide sufficient resources, the virtual machine may fail to start.

When the virtual machine is Powered Off or Suspended, you can switch between the Auto mode and the Manual mode.

Figure 6–11 Preferred Server Information

6.7.5 Profiles

On the Profiles page, you can set up or modify the user name and password for login, boot source, operating system, and keyboard.

Login/Password

- Virtual Machine System Username
Enter the user name used to log in to the guest operating system.
- Virtual Machine System Password
Enter the password used to log in to the guest operating system.
- Console Password
Reset the password for the VNC Authentication.

Click **Send me the password** if you want these passwords to be sent to your registered e-mail.

Figure 6–12 Profile Information - Login/Password

ORACLE[®] VM Manager

Home Profile Logout Help

Virtual Machines Resources Servers Server Pools Administration

Virtual Machines > Virtual Machine Configure Logged in as admin

Virtual Machines : mont_i_e4u7

General Network Storage Preferred Server Profiles

Login/Password Operating System

Login/Password

Virtual Machine System Username:

Virtual Machine System Password:

Console Password:

[Send me the password.](#)

Apply

General Network Storage Preferred Server Profiles


Virtual Machines Resources Servers Server Pools Administration

Copyright © 2007, 2008, Oracle. All rights reserved. Oracle VM Manager 2.1.2

Operating System and Keyboard

You can select an operating system, according to which Oracle VM optimizes the virtual machine profile, such as the configuration information in the `vm.cfg` file, and the timer mode for hardware virtualized machines (HVM). There are other behaviors controlled by selecting the operating system type, for example, Windows guests get to use USB tablet emulation instead of mouse emulation. By selecting the appropriate operating system, you can run the virtual machine with a better performance.

You can change the keyboard for the virtual machine on this page. Select an appropriate keyboard you need to use to interact with the virtual machine.

Figure 6–13 Profile Information - Operating System

6.8 Reproducing Virtual Machines

Oracle VM Manager enables you to reproduce one or multiple virtual machines easily based on an existing virtual machine.

Use one of the following to reproduce virtual machines:

- [Deploying a Virtual Machine](#)
- [Cloning Virtual Machines](#)
- [Saving a Virtual Machine as a Template](#)

6.8.1 Deploying a Virtual Machine

By deploying a virtual machine, you can clone a new virtual machine to a specific server pool, and share it with other users, or keep it private. After deploying a virtual machine, the original virtual machine remains in the original server pool. You can only deploy virtual machines to the server pools and groups to which you belong.

Note: Make sure the status of virtual machine is `Powered Off` before you deploy the virtual machine.

To deploy a virtual machine:

1. Click the **Virtual Machines** tab.
2. Select the virtual machine you want to deploy. In the More Actions list, select **Deploy**, and click **Go**. You can only deploy one virtual machine at a time.
3. Enter the name of the new virtual machine.
4. Select the group with whom you want to share the virtual machine.
 - Public Group

Deploy the virtual machine to the public group, so that all Oracle VM Manager users can use this new virtual machine.

- **My Workspace**

Deploy the virtual machine to a server pool that only you are allowed to use and make it private.

- **group_name**

Share the new virtual machine with members of a specific group.

5. If you have selected **My Workspace** or a specific group, continue to select a server pool to which you want to deploy this virtual machine.
6. On the Confirm Information page, confirm the virtual machine information and click **Confirm**.
7. The virtual machine is deployed. This process may take some time. After you deploy the virtual machine, click the **Refresh** button periodically until the status of the new virtual machine changes from `Creating` to `Powered Off`. You can choose to refresh manually, or to refresh every 30 seconds.

If the status is set to `Error`, see [Section 6.1.2.9, "Error"](#) to assist solving the error.

Note: If you deploy a virtual machine to the Public Group, the deployed virtual machine image is compressed and copied to the `/OVS/publish_pool` of the Oracle VM Server. The deployed virtual machine cannot be Powered On. To make this virtual machine available to all users, download or copy the virtual machine image, uncompress it and import it as a virtual machine image or template. Alternatively, you can select the deployed virtual machine and deploy it again to My Workspace, or another group.

Now you have finished deploying the virtual machine. To start the new virtual machine, see [Section 6.4.1, "Starting a Virtual Machine"](#).

You can change the preferred server and other configurations of the new virtual machine. See [Section 6.7, "Editing Virtual Machine Configuration"](#).

6.8.2 Cloning Virtual Machines

Cloning a virtual machine is a process to create one or more copies of an existing virtual machine. By cloning a virtual machine, you can save multiple copies to another server pool and share them with other users.

Note: Make sure the status of the virtual machine is `Powered Off` before you clone the virtual machine.

To clone a virtual machine:

1. Click the **Virtual Machines** tab.
2. On the Virtual Machines page, select the virtual machine you want to clone. In the More Actions list, select **Clone**, and click **Go**.
3. Enter the required information.
 - **Virtual Machine Name Prefix**

Enter the prefix used to name the virtual machine copies. For example, if you enter `vm`, the virtual machine copies will be named `vm0`, `vm1`, `vm2`, and so on.

- **Number of Copies**

Enter the number of copies you want to clone. For example, if you enter `5`, five copies of the virtual machine will be created.

You can clone a maximum of 10 copies.

- **Server Pool Name**

Select the server pool where the cloned virtual machine copies will be located.

- **Group Name**

Select the group who can use the cloned virtual machines copies.

4. This process may take some time. When the status of the original virtual machine changes from `Cloning` to `Powered Off`, click **Refresh** to check the latest virtual machine status. You can choose to refresh manually, or to refresh every 30 seconds. When the status of the cloned virtual machine changes from `Creating` to `Powered Off`, the cloning process is complete.

If the status turns out to be `Error`, see [Section 6.1.2.9, "Error"](#) for how to solve the problem.

Now you have created multiple copies of the virtual machine. You can change the preferred server and other configurations of the cloned virtual machines. See [Section 6.7, "Editing Virtual Machine Configuration"](#).

6.8.3 Saving a Virtual Machine as a Template

You can save a virtual machine as a template, to enable other users to create their new virtual machines based on this template. For more information on this, refer to [Section 6.3.1, "Creating a New Virtual Machine Based on Virtual Machine Template"](#).

Note: Make sure the status of the virtual machine is `Powered Off` before you save the virtual machine as a template.

To save a virtual machine as a template, perform the following:

1. Click the **Virtual Machines** tab.
2. Select the virtual machine you want to deploy as a template. In the More Actions list, select **Save As Template**, and click **Go**. You can only save one virtual machine at a time.
3. Enter the template name, and click **Confirm**.
4. The status of the original virtual machine changes from `Powered Off` to `Saving`.

This process may take some time. When the status returns to `Powered Off`, click the **Resources** tab, and then click the **Virtual Machine Templates** tab. Refresh the virtual machine periodically until the status changes from `Creating` to `Active`. You can see the new virtual machine template.

Now you can use the new template to create virtual machines.

6.9 Migrating a Virtual Machine

Live migration is a process to migrate a running virtual machine from one Virtual Machine Server to another, while applications on the existing virtual machine continue to run. Live migration ensures high availability of virtual machines. This feature is important, and useful, when the existing Virtual Machine Server may be out of commission, or on a planned shutdown for maintenance purposes.

Cross-server-pool live migration is not allowed. You can only migrate virtual machines from one Virtual Machine Server to another within the same server pool. You must use identical computers to perform live migrations, that is, the computer make and model number of both the source computer and the destination computer must be identical.

You must create a shared virtual disk before migrating the virtual machine.

To migrate a virtual machine:

1. Click the **Virtual Machines** tab.
2. On the Virtual Machines page, select the running virtual machine. In the More Actions list, select **Live Migration**, and click **Go**.
3. Select the Virtual Machine Server to which you want to migrate the virtual machine. Click **Next**.
4. Check the virtual machine information, and click **Confirm**.

The virtual machine is migrated.

6.10 Deleting a Virtual Machine

When you delete a virtual machine, all the files and data associated with this virtual machine will be removed from Oracle VM Manager. Before deleting a virtual machine, make sure you do not need it any longer.

Note: Delete the virtual machine only when the virtual machine status is `Powered Off` or `Error`.

The process of deleting a normal virtual machine is different from that of deleting a virtual machine stuck in a certain status.

- [Deleting a Virtual Machine in "Powered Off" or "Error" Status](#)
- [Deleting a Virtual Machine Stuck in a Certain Status](#)

6.10.1 Deleting a Virtual Machine in "Powered Off" or "Error" Status

To delete a virtual machine in the `Powered Off` or `Error` status:

1. On the Virtual Machines page, select the virtual machine you want to delete.
2. In the More Actions list, select **Delete**, and click **Go**.
3. Confirm the delete action.

6.10.2 Deleting a Virtual Machine Stuck in a Certain Status

When a virtual machine gets stuck in any status such as `Shutting Down` or `Creating`, you need to shut down the virtual machine, and then delete it.

To delete a virtual machine stuck in a certain status:

1. Click the **Virtual Machines** tab.
2. On the Virtual Machines page, select the virtual machine, and then click **Power Off**.
3. After the status changes to `Powered Off`, delete the virtual machine.

Managing Users and Groups

This chapter describes how to manage users and groups as an administrator. It includes the following sections:

- [The Default Account](#)
- [Managing Users](#)
- [Managing Groups](#)

Note:

- Functions described in this chapter are only available to administrators.
 - A small mistake made by an administrator may cause serious damage to the entire Oracle VM Manager environment. Please minimize the number of administrators when creating the accounts.
-

7.1 The Default Account

Oracle VM Manager provides a default account. The default user name is `admin` (lowercase). The password is set when you install Oracle VM Manager.

7.2 Managing Users

You can create new users, delete obsolete users, change the users' role, and reset the user password. This section includes the following topics:

- [Creating a User](#)
- [Viewing Details](#)
- [Editing a User](#)
- [Changing a Role](#)
- [Deleting a User](#)

7.2.1 Creating a User

To create a user, perform the following:

1. On the Administration page, click the **User** tab and then click the **Create** button.
2. Enter the following user information:

- Username

Enter an account name for the user.

You cannot use `manager`, or `user` as the user name.

An account name must consist of alphanumeric characters, and must not contain spaces or special characters, except the underscore (`_`) and hyphen (`-`) characters. The maximum name length is 100 characters.

- Password

Set the password used by the user to log in to Oracle VM Manager.

- Retype Password

- First Name

- Last Name

- Email

Enter the user's e-mail address. If the user forgets the password, a new password will be sent to this e-mail.

- Status

Select the account status. It can be **Locked** or **Unlocked**.

The account is available only when the status is **Unlocked**.

To lock this account, select **Locked**.

- Role

Grant the user one of the three roles: `User`, `Manager`, or `Administrator`.

For more information about the roles, refer to [Section 1.5, "Roles in Oracle VM Manager"](#).

3. Select server pools for the user.
4. Select groups for the user. One user can join multiple groups.
5. Click **Confirm**.

7.2.2 Viewing Details

To view a user's detailed information, perform the following:

1. On the Administration page, click the **User** tab.
2. Click the **Show** link, and you can view the server pools that the user is allowed to use, and the groups to which the user belongs.

Figure 7–1 Viewing Details of User

The screenshot shows the Oracle VM Manager interface. The top navigation bar includes 'Virtual Machines', 'Resources', 'Servers', 'Server Pools', and 'Administration'. The 'Administration' tab is selected, and the 'User' sub-tab is active. The page title is 'User Information'. There is a 'Create' button in the top right. Below the title, there is a search section with fields for 'Username', 'Email', and a 'Status' dropdown menu. A 'Search' button is below these fields. A tip states: 'TIP Search criteria are case insensitive. Use '%' as a wildcard, for example prod%'. Below the search section, there is a table with columns: 'Select', 'Details', 'Username', 'Email', 'First Name', 'Last Name', 'Status', and 'Role'. The table contains one row for user 'admin007' with email 'admin007@example.com', status 'Unlocked', and role 'Administrator'. The 'Show' button in the 'Select' column is circled in red. There is also a 'Create' button at the bottom right of the table.

Select	Details	Username	Email	First Name	Last Name	Status	Role
Show		admin007	admin007@example.com			Unlocked	Administrator

7.2.3 Editing a User

Edit the user information when you want to:

- Change the user information, such as e-mail address.
- Change the account status to either lock or unlock the account.
- Change the role.
- Add the user to some groups, or server pools.
- Remove the user from some groups, or server pools.

To edit a user, perform the following:

1. On the Administration page, search and select the user you want to edit, and click the **Edit** button.
2. On the Edit page you can update the user information, change the user's role, add the user to groups or server pools, or remove the user from groups or server pools.

The account status can be **Locked** or **Unlocked**. By default, the status is **Unlocked**. If you lock an account, the user cannot use it any more.

3. Click **Apply**.

7.2.4 Changing a Role

When a user's role has changed, for example, a common user is assigned as an administrator, you need to change the user's role in Oracle VM Manager.

For more information about roles, refer to [Section 1.5, "Roles in Oracle VM Manager"](#).

To change the user role, perform the following:

1. On the Administration page, select the target user, and click the **Edit** button.
2. Select the role accordingly, and then click the **Apply** button.

7.2.5 Deleting a User

To delete a user, perform the following:

1. On the Administration page, search and then select the users you want to delete. Click the **Delete** button.
2. Confirm the users you want to delete.

7.3 Managing Groups

There are many users in the Oracle VM Manager system, and it is time-consuming to assign privileges individually to each user. The **group** function enables you to add some specific users to a group. After you assign some privileges to the group, all members of this group will have the group privileges. This will facilitate the job for administrators.

This section includes the following topics:

- [Default Groups](#)
- [Creating a Group](#)
- [Adding a User to a Group](#)
- [Editing a Group](#)
- [Deleting a Group](#)

7.3.1 Default Groups

There are two default groups: **Public Group** and **My Workspace**.

- The **Public Group** contains all public virtual machines. All users can deploy and view virtual machines in the **Public Group**.
- The **My Workspace** group only contains private virtual machines. Only the virtual machine owner can manage virtual machines in **My Workspace**.

7.3.2 Creating a Group

When there are a large number of users, you can combine specific users into a group, or groups. For example, you can combine users who belong to the same server pool into one group.

To create a group, perform the following:

1. On the Administration page, click the **Group** tab.
2. Click the **Create** button, enter the group name and description.
3. Select users for the group. Double-click the user name in the **Available Users** column to add it to the **Selected Users** column.
4. Click **Confirm**.

7.3.3 Adding a User to a Group

To add a user to a new group, perform the following:

1. On the Administration page, click the **User** tab.
2. Search and select the user you want to add to the group, and click **Edit**.

3. In the Group area, double-click the group in the **Available Groups** column to move it to the **Selected Groups** column.
4. Check the **Group** section. Make sure the group you have selected shows up in the **Selected Groups** column.
5. Click **Apply**.

7.3.4 Editing a Group

To edit a group, select the group you want to update, and click the **Edit** button to update the group information. You can also add users to the group, or remove users from the group.

7.3.5 Deleting a Group

To delete a group, perform the following:

1. On the Administration page, select the group you want to delete, and click the **Delete** button.
2. Confirm the group you want to delete.

After you delete a group, all users in this group will still remain in the system. If you want to delete users along with the group, see [Section 7.2.5, "Deleting a User"](#).

Preparing Virtual Machines For Importing

If you have prebuilt Oracle VM virtual machines, you can import them into Oracle VM Manager to use as virtual machines, or templates.

Before you import a virtual machine, you must have an Oracle VM Server and store the virtual machine files in the correct directory of the Oracle VM Server, according to your needs. Oracle VM Agent updates the directory information in the `vm.cfg` file automatically when importing virtual machines.

For information about Oracle VM Servers, refer to [Section 1.4, "Configuration of Oracle VM Manager"](#), and [Section 3.2, "Creating a Server Pool"](#).

If you want to import a prebuilt virtual machine as a template, copy the virtual machine files to the Oracle VM Server directory:

```
/OVS/seed_pool/vm_name/
```

If you want to import a prebuilt virtual machine as a private virtual machine (it is not shared with others), copy the virtual machine files to the Oracle VM Server directory:

```
/OVS/running_pool/vm_name/
```

To move the virtual machine to the correct location for importing:

1. Log in to the Oracle VM Server.
2. Download, or copy the virtual machine to the correct directory for your needs. For example, to download the virtual machine `XEN_EL4U5_X86_HVM` from `http://example.com/seeds/` as a template:

- If the virtual machine is compressed, run the `wget` command to download it:

```
# cd /OVS/seed_pool
# wget http://example.com/seeds/XEN_EL4U5_X86_HVM.tgz
```

Uncompress the virtual machine:

```
# cd /OVS/seed_pool
# tar -xzf XEN_EL4U5_X86_HVM.tgz
```

- If the virtual machine is not compressed, run the `wget -r` command to download it:

```
# cd /OVS/seed_pool
# wget -r http://example.com/seeds/XEN_EL4U5_X86_HVM/
```

A directory named `XEN_EL4U5_X86_HVM` is created under the `/OVS/seed_pool/` directory, and the virtual machine files are extracted and ready to be imported as a template in Oracle VM Manager.

Backing Up and Restoring Oracle VM Manager

Back up Oracle VM Manager before you:

- Uninstall Oracle VM Manager.
- Move the Oracle VM Server from one computer to another.
- Make any major change in Oracle VM Manager.

This Appendix includes the following topics:

- [Backing Up Oracle VM Manager](#)
- [Restoring Oracle VM Manager](#)

B.1 Backing Up Oracle VM Manager

Before backup, make sure the status of all Oracle VM Servers is Running.

To back up Oracle VM Manager, perform the following:

1. Log in to the Oracle VM Server as the *root* user.
2. Back up the Oracle VM Manager resources stored in the following directories:
 - `/OVS/running_pool` for virtual machine images
 - `/OVS/seed_pool` for virtual machine templates
 - `/OVS/iso_pool` for ISO files

Skip this step if you have enabled the storage backup mechanism.

3. Back up the existing Oracle VM Manager data by using the following commands:

```
# cd /opt/ovs-manager-2.1/bin
# sh backup.sh
```

Enter 1 to back up the data.

Please enter the choice: [1|2]

1. Back up Oracle VM Manager,
2. Restore Oracle VM Manager

Enter the database information, and the path for the dump and log files.

Back up data now ...

Please enter the password for database account 'OVS':

Please specify the path for dump file?

Please specify the path for log file?

Oracle VM Manager is backed up.

B.2 Restoring Oracle VM Manager

To restore Oracle VM Manager:

1. Log in to the Oracle VM Server as the *root* user.
2. Save or copy the Oracle VM Manager resources into the following directories respectively:
 - /OVS/running_pool for virtual machine images
 - /OVS/seed_pool for virtual machine templates
 - /OVS/iso_pool for ISO files
3. Restore the backup data of the Oracle VM Manager by using the following commands:

```
# cd /opt/ovs-manager-2.1/bin
# sh backup.sh
```

Enter 2 to restore the data.

```
Please enter the choice: [1|2]
1. Back up Oracle VM Manager,
2. Restore Oracle VM Manager
```

Enter the database information, and the path for the dump and log files.

```
Please enter the password for database account 'SYS':
Please enter the password for database account 'OVS':
Please specify the path for dump file?
Please specify the path for log file?
```

For example, enter:

```
Please enter the password for database account 'SYS':
Please enter the password for database account 'OVS':
Please specify the path for dump file?/dump
Please specify the path for log file?/log
```

Oracle VM Manager is restored.

Web Services API


Oracle VM Manager provides a Web services Application Programming Interface (API) to enable integration of third party products with Oracle VM Manager. You can use the API to perform any of the operations in Oracle VM Manager, for example, to create a server pool, add servers, and create virtual machines. You can use any language that supports Web services to access the API, for example Java or Python.

This Appendix describes the Oracle VM Manager Web services API and contains:

- [Web Services API](#)
- [Creating a Web Service Client](#)
- [Authentication and Security](#)
- [Web Service Locations](#)
- [Web Services](#)

C.1 Web Services API


Oracle VM Manager acts as an administration platform for Oracle VM Servers connected on a network to direct actions to the virtual machines, virtual servers and the server pool. Oracle VM Manager provides the management environment for Oracle VM. A Web services API is available for Oracle VM Manager. The Oracle VM Manager Web services API architecture is shown in [Figure C-1, "Oracle VM Manager Web Services API Architecture"](#).

Figure C–1 Oracle VM Manager Web Services API Architecture

The Oracle VM Manager API provides a complete set of interfaces to Oracle VM Manager. The Oracle VM Manager API is accessed through the Oracle VM Manager Web services API using the SOAP protocol.

The Oracle VM Manager Web service API provides all the operations necessary, including life-cycle operations, to monitor and manage virtual infrastructure components, like server pools, virtual servers, virtual machines, networks, storage, and so on.

The Oracle VM Manager Web services API is implemented as shown in [Figure C–2, "Oracle VM Manager Web Services API Implementation"](#).

Figure C–2 Oracle VM Manager Web Services API Implementation

The Oracle VM Manager API is used by the Oracle VM Manager UI layer, and by the virtualization management component of Oracle Enterprise Manager. The Web services API can be used by Oracle applications as well as third party applications.

C.2 Creating a Web Service Client

You can use any programming language that supports Web services to create a Web services client. Most example code in this Chapter is written in Java and created using Oracle JDeveloper, although you can use the language and development tool of your choice.

To use Web services in Java, you can create SOAP messages directly, or generate proxy classes for each Web service. In Oracle JDeveloper, use the Web service WSDL URL to automatically generate proxy classes.

C.2.1 Creating a Proxy Class in Java

The examples given here use Oracle JDeveloper and the Java wsimport utility to create proxy classes in Java.

C.2.1.1 Using Oracle JDeveloper

To create a proxy class for an Oracle VM Manager Web service in Java using Oracle JDeveloper, use the Web service WSDL URL feature.

Example C–1 Retrieving a Server Pool by Name Using Oracle JDeveloper

An Oracle JDeveloper proxy class for retrieving a server pool using its name might look similar to:

```
public ServerPool getServerPoolByName(String poolName) throws Exception{
    String username = "myuser";
    String password = "mypassword";

    //ServerPoolServiceSoapHttpClient is generated by Jdeveloper.
    server.ServerPoolServiceSoapHttpClient myPort =
        new server.ServerPoolServiceSoapHttpClient();
    myPort.setMaintainSession(true);
    myPort.setUsername(username);
    myPort.setPassword(password);
    ServerPool thePool = myPort.getServerPoolByName(poolName);
    return thePool;
}
```

Example C–2 Importing a Guest Virtual Machine or Template Using Oracle JDeveloper

An Oracle JDeveloper proxy class for importing a guest virtual machine, or template, might look similar to:

```
/**
 * @param args
 */
public static void main(String[] args) {
    try {
        oracle.ovs.api.ResourceServiceSoapHttpClient myPort = new
        oracle.ovs.api.ResourceServiceSoapHttpClient();
        System.out.println("calling " + myPort.getEndpoint());

        /* External Template Importing */
        VirtualMachineTemplate vmt = new VirtualMachineTemplate();
```

```
        /* set template name */
        vmt.setImgName("MyTemplate");
        /* set download url */
        vmt.setDownloadURL("http://example.com/OEL5");
        /* set proxy url(optional) */
        vmt.setProxyURL("http://proxy.example.com:80");
        /* set vm username */
        vmt.setVmUsername("myuser");
        /* set vm password */
        vmt.setVmPassword("mypassword");
        /* set operating system type */
        vmt.setOsType("Enterprise Linux 5");
        /* set description */
        vmt.setDescription("My description.");
        /* start importing */
        myPort.registerExternalTemplate("example.com", vmt);

        /* Internal Image Importing */
        VirtualMachineImage vmi = new VirtualMachineImage();
        /* set vm name */
        DiscoveredVirtualMachineImage[] unregisteredImages =
myPort.getAllDiscoverableImages("example.com");
        /* find unregistered vm */
        if (unregisteredImages.length > 0) {
            vmi.setImgName(unregisteredImages[0].getImgName());
        }
        else {
            return;
        }

        /* set vm username */
        vmi.setVmUsername("myuser");
        /* set vm passwd */
        vmi.setVmPassword("mypassword");
        /* set vnc password */
        vmi.setVncPassword("mypassword");
        /* set operating system type */
        vmi.setOsType("Enterprise Linux 4 64-bit");
        /* set description */
        vmi.setDescription("My description.");
        /* start importing */
        myPort.registerInternalImage("example.com", vmi);

    } catch (Exception ex) {
        ex.printStackTrace();
    }
}
```

Example C-3 Creating a Guest Virtual Machine From a Template Using Oracle JDeveloper

An Oracle JDeveloper proxy class for creating a guest virtual machine from a template might look similar to:

```
public static void main(String[] args) {
    try {
        LifecycleServiceSoapHttpClient myPort =
            new LifecycleServiceSoapHttpClient();
        System.out.println("calling " + myPort.getEndpoint());
        // Add your own code here
    }
}
```



```

        myPort.setUsername("myuser");
        myPort.setPassword("mypassword");

        TemplateVmConfig templateVMConfig= new TemplateVmConfig();
        templateVMConfig.setServerPoolName("example.com");
        //your serverpoolName
        templateVMConfig.setTemplateName("myTemplate");//your templateName

        NICConfig nic = new NICConfig();
        nic.setName("VIF0");
        nic.setIpAddress("ioemu");

        nic.setBridge("xenbr0");
        nic.setMacAddress("00:16:xx:xx:xx:xx");
        NetworkConfType confType = new NetworkConfType();
        confType.setType("Dynamic");
        nic.setNetworkConfType(confType);

        //nic.set
        NICConfig[] vifs = new NICConfig[]{nic};
        templateVMConfig.setVif(vifs);

        templateVMConfig.setVmName("MyGuestVirtualMachine");

        templateVMConfig.setConsolePassword("mypassword");
        templateVMConfig.setHaEnable(false);

        myPort.createVmBasedOnTemplate(templateVMConfig);
    } catch (Exception ex) {
        ex.printStackTrace();
    }
}

public LifecycleService _port;
public VirtualMachine createVmBasedOnTemplate(TemplateVmConfig templateVMConfig)
throws java.rmi.RemoteException{
    ServiceFactory factory = ServiceFactory.newInstance();
    _port = ((LifecycleService_Service)factory.loadService(LifecycleService_
Service.class))
        .getLifecycleServiceSoapHttpPort();
    return _port.createVmBasedOnTemplate(templateVMConfig);
}

```

C.2.1.2 Using wsimport

To create a proxy class for an Oracle VM Manager Web service in Java using the wsimport utility:

```

$ JAVA_HOME/bin/wsimport -d <dir-for-compiled classes> -keep -s
<dir-for-generated-source> -p com.oracle.ovm.manager.ws.vms -wsdllocation
http://ovm_host:port/OVSWS/nameService.wsdl <path-to-wsdl-file-in-local-host>

```

For example, to create a proxy class for the ServerPool Web service, you might enter:

```

$ JAVA_HOME/bin/wsimport -d <dir-for-compiled classes> -keep -s
<dir-for-generated-source> -p com.oracle.ovm.manager.ws.vms -wsdllocation
http://example.com:8888/OVSWS/ServerPoolService.wsdl
<path-to-wsdl-file-in-local-host>

```

Example C-4 Retrieving a Server Pool by Name Using wsimport

A wsimport proxy class for retrieving a server pool using its name might look similar to:

```
public ServerPool getServerPoolByName(String poolName) throws Exception{
    String url = "http://example.com:8888/";
    String contextPath = "OVSWs";
    String user = "myuser";
    String password = "mypassword";
    ServerPoolService_Service sps_service =
        new ServerPoolService_Service(new URL(url + contextPath +
            "/ServerPoolService.wsdl"),
            new QName("http://oracle.ovs.api/", "ServerPoolService"));
    sps = sps_service.getServerPoolServiceSoapHttpPort();

    BindingProvider bp = (BindingProvider) sps;
    Map<String, Object> rc = bp.getRequestContext();
    rc.put(BindingProvider.ENDPOINT_ADDRESS_PROPERTY, url + contextPath +
        "/ServerPoolServiceSoapHttpPort");
    rc.put(BindingProvider.SESSION_MAINTAIN_PROPERTY, new Boolean(true));
    rc.put(BindingProvider.USERNAME_PROPERTY, user);
    rc.put(BindingProvider.PASSWORD_PROPERTY, password);

    GetServerPoolByNameElement req = new GetServerPoolByNameElement();
    req.setPoolName(poolName);
    GetServerPoolByNameResponseElement res = sps.getServerPoolByName(req);
    ServerPool thePool = res.getResult();
    return thePool;
}
```

C.2.2 Creating a Proxy Class in Python

To create a proxy (stub) class for an Oracle VM Manager Web service using Python:

```
$ wsdl2py -b http[s]://ovm_host:port/OVSWs/nameService.wsdl
```

For example, to create a proxy class for the ServerPool Web service, you might enter:

```
$ wsdl2py -b https://ovm.example.com:4443/OVSWs/ServerPoolService.wsdl
```

Example C-5 Retrieving a Server Pool by Name using Python

A Python proxy class for retrieving a server pool using its name might look similar to:

```
import ServerPoolService_client as c

class ServerPoolManagementPort:

    def __init__(self, urlbase, auth):
        self.wspath = "/ServerPoolServiceSoapHttpPort"
        self.loc = c.ServerPoolServiceLocator()
        self.srv = self.loc.getServerPoolServiceSoapHttpPort(url = urlbase +
            self.wspath, auth = auth)
    def getServerPoolByName(self, poolName):
        """
        Return instance of a specific server pool managed by the system, by its
        name.
        @param poolName:
        @type poolName: str
        @return: ServerPool
        """
```

```

request = c.ServerPoolService_getServerPoolByName()
request._poolName = poolName
response = self.srv.getServerPoolByName(request)
return response._result

```

To call this code, including authentication with the Web service, you might use:

```

from ServerPoolManagementPort import *
from ZSI.auth import AUTH
auth=(AUTH.httpbasic, 'myuser', 'mypassword')
spm = ServerPoolManagementPort(urlbase = 'https://ovm.example.com:4443/OVSWs/',
                                auth = auth)
serverpool = spm.getServerPoolByName('myserverpool')

```

C.3 Authentication and Security

The Oracle VM Manager Web services use HTTP basic authentication to authenticate users and control access. HTTP basic authentication requires that the server requests a username and password from the Web services client, and verifies that the username and password are valid by comparing them against a valid Oracle VM Manager user.

SSL is enabled by default for Web services, and secures the data during transmission at transport level. For each Web service call, the server authenticates the log in credentials for valid Oracle VM Manager users in the basic header.

If you need to set up SSL for Web services after the original Oracle VM Manager installation, you can use the script:

```
# /opt/ovs-manager-2.1/bin/secure_ws.sh
```

This script generates the keystore for Oracle VM Manager Web services and configures OC4J.

To perform the authentication with Oracle VM Manager, you must pass the Oracle VM Manager login credentials to the Oracle VM Manager Web service from a Web services client.

Example C-6 Authentication in Java

To perform HTTP basic authentication from a Java Web services client:

1. Change the URL to the Web service from http to https. For example, https://ovm.example.com:4443. This is the URL used to obtain the SOAP HTTP port in step 3.
2. Add the following two system properties to the client-side Java to perform the SSL handshake:

```

-Djavax.net.ssl.trustStore=/path/ovmm_client_trust.jks    <=== this contains
the manager's cert
-Djavax.net.ssl.trustStorePassword=truststorepasswd

```

3. Obtain the SOAP HTTP port, with code similar to the following:

```

ServerPoolService_Service sps_service =
    new ServerPoolService_Service(new URL(url + contextPath +
        "/ServerPoolService.wsdl"),
    new QName("http://oracle.ovs.api/", "ServerPoolService"));
//Note, the URL here is the URL mentioned in Step 1. It is the HTTPS URL.
ServerPoolService sps = sps_service.getServerPoolServiceSoapHttpPort();

BindingProvider bp = (BindingProvider) sps;

```

```
Map<String, Object> rc = bp.getRequestContext();
rc.put(BindingProvider.ENDPOINT_ADDRESS_PROPERTY, url + contextPath +
      "/ServerPoolServiceSoapHttpPort");
rc.put(BindingProvider.SESSION_MAINTAIN_PROPERTY, new Boolean(true));
rc.put(BindingProvider.USERNAME_PROPERTY, myuser);
rc.put(BindingProvider.PASSWORD_PROPERTY, mypassword);
```

4. You must also generate a keystore and proxy on the Web services client. For example, you could use:

```
# java -Djavax.net.ssl.trustStore=/Users/myuser/ssl/client.keystore
-Djavax.net.ssl.keyStore=/Users/myuser/ssl/client.keystore
-Djavax.net.ssl.trustStorePassword=mypassword
-Djavax.net.ssl.keyStorePassword=mypassword
-jar $ORACLE_HOME/webservices/lib/wsa.jar
-genProxy
-wsdl https://ovm.example.com:4443/OVSWWS/AdminServiceSoapHttpPort?WSDL
```

5. To set the login credentials on the Web services client, you could use:

```
System.setProperty("javax.net.ssl.trustStore",
"/Users/myuser/ssl/client.keystore");
System.setProperty("javax.net.ssl.keyStore",
"/Users/myuser/ssl/client.keystore");
System.setProperty("javax.net.ssl.trustStorePassword", "mypassword");
System.setProperty("javax.net.ssl.keyStorePassword", "mypassword");
...
```

Example C-7 Authentication in Python

An Python proxy class to authenticate and retrieve a server pool might look similar to:

```
import ServerPoolService_client as c
from ZSI.auth import AUTH
loc = c.ServerPoolServiceLocator()
auth = (AUTH.httpbasic, 'myuser', 'mypassword')
srv = loc.getServerPoolServiceSoapHttpPort(auth=auth)
req = c.ServerPoolService_getServerPoolByName()
req._poolName = 'myserverpool'
resp = srv.getServerPoolByName(req)
serverPool = resp._result
```

C.4 Web Service Locations

Each Oracle VM Manager Web service URL has the syntax:

```
http[s]://ovm_manager_host:port/OVSWWS/WS_name.wsdl
```

SSL is enabled by default for Web services, and secures the data during transmission at transport level. Although you can access the Web services without using SSL, Oracle recommends you use SSL for increased security.

A test page is available for each Web service that enables you to test a Web service and values for the Web service parameters. The Web service test page URL has the syntax:

```
http[s]://ovm_manager_host:port/OVSWWS/WS_nameSoapHttpPort
```

When you open a Web service test page in a browser, you must authenticate with the Web service by entering an Oracle VM Manager administrator username and password. When you have authenticated, a form is displayed that enables you to input parameters and invoke different methods in the Web service. This form also contains a

link named **Service Description** that displays the WSDL for the Web service. The following is the syntax for the WSDL URL:

```
http[s]://ovm_manager_host:port/OVSWS/WS_nameSoapHttpPort?WSDL
```

or

```
http[s]://ovm_manager_host:port/OVSWS/WS_name.wsdl
```

The Web service test page also contains a link to the documentation for the Web service. The syntax for the Web service documentation is:

```
http[s]://ovm_manager_host:port/OVSWS/WS_nameSoapHttpPort?WS_nameSoapHttpPortstub.html
```

For example, if your Oracle VM Manager host is ovm.example.com, and its port is 4443 and SSL is enabled, then the following URL is the location for the LifecycleService:

```
https://ovm.example.com:4443/OVSWS/LifecycleService.wsdl
```

And the location of the test page for LifecycleService is:

```
https://ovm.example.com:4443/OVSWS/LifecycleServiceSoapHttpPort
```

The corresponding LifecycleService documentation URL is:

```
https://ovm.example.com:4443/OVSWS/LifecycleServiceSoapHttpPort?LifecycleServiceSoapHttpPortstub.html
```

C.5 Web Services

The Oracle VM Manager Web services available are:

- **LifecycleService**: Manages the lifecycle of virtual machines.
- **ResourceService**: Manages resources.
- **PluginService**: Manages the plug in.
- **ServerPoolService**: Manages servers and server pools.
- **VirtualMachineService**: Manages virtual machines.
- **AdminService**: Manages users and groups.

C.5.1 LifecycleService

The LifecycleService Web service manages the lifecycle of virtual machines. You can use this Web service to create a virtual machine, enable HA, perform live migration, attach CDs and disks, and so on.

The LifecycleService Web service is located at:

```
http[s]://ovm_manager_host:port/OVSWS/LifecycleService.wsdl
```

The methods available in this Web service are:

- addDisk
- addNIC
- attachCDtoVM
- attachSharedVirtualDisk
- changeNetworkType
- clone

- createVmBasedOnISO
- createVmBasedOnPXE
- createVmBasedOnTemplate
- deploy
- detachCD
- detachSharedVirtualDisk
- disableHA
- enableHA
- getConsolePassword
- getKeyboardLayoutArray
- getVMGroupByVMId
- liveMigrate
- liveMigrateAll
- removeDisk
- removeNIC
- resetStatus
- setBootPriority
- setConsolePassword
- setCPUCores
- setDynamicMemory
- setGuestCredential
- setMaximumMemory
- setNetworkInsideGuest
- setOperatingSystem
- setPreferredServers
- setVMConfigParam
- setVMDescription
- setVMKeyboardLayout

More detailed information on the functions available in this web service is available in the *Oracle VM Manager Web Services API Reference*.

C.5.2 ResourceService

The ResourceService Web service manages resources. You can use this Web service to import and manage ISO files, templates, virtual machines, and shared virtual disks.

The ResourceService Web service is located at:

`http[s]://ovm_manager_host:port/OVSWS/ResourceService.wsdl`

The methods available in this Web service are:

- ValidateVMConfig

- approveISOResource
- approveImage
- approveTemplate
- deleteISO
- deleteImage
- deleteSharedVirtualDisk
- deleteTemplate
- getAllDiscoverableISO
- getAllDiscoverableImages
- getAllDiscoverableTemplates
- getAllISOResources
- getAllImageResources
- getAllSharedVirtualDisks
- getAllTemplateResources
- getISOResource
- getISOResourceByGroupName
- getISOResourceByGroupNameAndISOName
- getISOResourceByISOName
- getImageResource
- getImageResourceByName
- getSharedDiskResource
- getSharedDiskResourceByName
- getTemplateResource
- getTemplateResourceByName
- registerExternalISO
- registerExternalImage
- registerExternalTemplate
- registerISO
- registerInternalISO
- registerInternalImage
- registerInternalTemplate
- registerSharedVirtualDisk

More detailed information on the functions available in this web service is available in the *Oracle VM Manager Web Services API Reference*.

C.5.3 PluginService

The PluginService Web service manages the plug in. You can use this Web service to set or get plug in scope properties.

The PluginService Web service is located at:

`http[s]://ovm_manager_host:port/OVSWS/PluginService.wsdl`

The methods available in this Web service are:

- `disposePlugin`
- `getDaemonManager`
- `preparePlugin`

More detailed information on the functions available in this web service is available in the *Oracle VM Manager Web Services API Reference*.

C.5.4 ServerPoolService

The ServerPoolService Web service manages servers and server pools. You can use this Web service to create and manage servers and server pools.

The ServerPoolService Web service is located at:

`http[s]://ovm_manager_host:port/OVSWS/ServerPoolService.wsdl`

The methods available in this Web service are:

- `addMembers`
- `checkHAAbility4ServerPoolById`
- `checkServerConnection`
- `checkVirtualServerCompatibility`
- `createServerPool`
- `deleteServerPool`
- `getAgentVersion`
- `getAllMembers`
- `getAllServerPools`
- `getClusterRootByServerPoolId`
- `getMasterAgentStatus`
- `getMasterServer`
- `getMinSupportedOVSAgentVersion`
- `getNetworkBridges`
- `getNetworkBridgesByServerIP`
- `getServer`
- `getServerByName`
- `getServerPool`
- `getServerPoolById`
- `getServerPoolByName`
- `getServerPoolMetricsByServerPoolId`
- `getServerPools`
- `getStorageRespositoriesByServerPoolId`

- `getVirtualServerById`
- `getVirtualServerByName`
- `getVirtualServerByServerPool`
- `getVirtualServerMetrics`
- `getVirtualServers`
- `rebootServer`
- `refreshServerPool`
- `removeMember`
- `restoreVirtualServerPoolByManagerData`
- `shutdownServer`
- `updateServerPool`
- `updateUserList4ServerPool`
- `updateUtilityServerPassword`
- `updateVirtualServer`
- `updateVirtualServerAgentPassword`
- `updateVirtualServerById`
- `validateAddMembers`
- `validateCreateServerPool`
- `validateDeleteServerPool`
- `validateRebootServer`
- `validateRemoveMember`
- `validateShutdownServer`
- `validateUpdateUtilityServerPassword`
- `validateUpdateVSAgentPassword`

More detailed information on the functions available in this web service is available in the *Oracle VM Manager Web Services API Reference*.

C.5.5 VirtualMachineService

The VirtualMachineService Web service manages virtual machines. You can use this Web service to create and manage virtual machines.

The VirtualMachineService Web service is located at:

`http[s]://ovm_manager_host:port/OVSWS/VirtualMachineService.wsdl`

The methods available in this Web service are:

- `createPropertiesFileOnVirtualMachine`
- `deleteVMByVMId`
- `getAllAlertAssociatedWithImg`
- `getAllOperatingSystemArray`
- `getAllVMs`

- getAssociatedPool
- getAssociatedServer
- getLastAlertAssociatedWithDisk
- getLastAlertAssociatedWithImg
- getRealPath
- getVM
- getVMByName
- getVncPassword
- pauseVMByVMId
- powerOffVMByVMId
- powerOnVMByVMId
- queryCdromArray
- queryLocalDiskInfo
- queryLocalDisks
- queryNetworkInterfaceCardArray
- queryPreferredServer
- querySharedDiskInfo
- querySharedVirtualDiskArray
- queryVMMetricArrayVyVMIds
- queryVMMetricByVMId
- queryVMStatusArrayByVMIds
- queryVMStatusByVMId
- rebootVMByVMId
- resumeVMByVMId
- saveAsTemplate
- setVMName
- suspendVMByVMId
- unpauseVMByVMId
- unregisterVMByVMId
- update
- uploadVirtualMachine

More detailed information on the functions available in this web service is available in the *Oracle VM Manager Web Services API Reference*.

C.5.6 AdminService

The AdminService Web service manages users and groups. You can use this Web service to create and manage users and groups.

The AdminService Web service is located at:

`http[s]://ovm_manager_host:port/OVSWS/AdminService.wsdl`

The methods available in this Web service are:

- `createGroup`
- `createUser`
- `createUserGroup`
- `createUserSite`
- `findAllOVMGroup`
- `findAllOVMRole`
- `finalAllOVMUser`
- `findAllOVMUserGroup`
- `findAllOVMUserRole`
- `findAllOVMUserSite`
- `findUserById`
- `isAdminUser`
- `login`
- `logout`
- `searchUsers`

More detailed information on the functions available in this web service is available in the *Oracle VM Manager Web Services API Reference*.

Troubleshooting

This appendix describes some problems you may encounter when using Oracle VM Manager, and explains how to resolve them. It includes the following topics:

- [Log Files](#)
- [Cannot Log In to Oracle VM Manager](#)
- [Cannot Create a Virtual Machine from Installation Media](#)
- [No Sufficient Space in Repository for Creating a Virtual Machine](#)
- [The Virtual Machine Stuck in Certain Status](#)
- [The Status of the Virtual Machine Is "Error"](#)
- [Cannot Access Virtual Machine Console](#)
- [Cannot Perform Live Migration](#)
- [Cannot Change CD in the Virtual Machine](#)
- [Cannot Import External Resources](#)
- [Remote Host Identification Error in Server Pool](#)

Find additional information on the following Oracle support-oriented Web sites:

- Oracle MetaLink, available at <http://metalink.oracle.com>
- Oracle Virtualization Forum, available at <http://forums.oracle.com/forums/forum.jspa?forumID=482>

D.1 Log Files

Oracle VM Manager log files are stored in the directory:

`/var/log/ovm-manager/`

[Table D-1, "Log Files"](#) lists the log files it contains.

Table D-1 Log Files

Log File	Description
ovm-manager.log	The Oracle VM Manager installation log.
db.log	The Oracle Database log. When you install Oracle VM Manager on an existing database, the log information is stored here.

Table D–1 (Cont.) Log Files

Log File	Description
oc4j.log	The Oracle Containers for J2EE (OC4J) installation log. When oc4j.log exceeds 10 MB, a new log file oc4j.log.1. is generated to store the logs in oc4j.log. Subsequently, the oc4j.log is cleared to record new log information.
upgrade_oldversion_ newversion.log.log	The Oracle VM Manager upgrading log.

D.2 Cannot Log In to Oracle VM Manager

It may take a very long time to log in, or it is stuck in the Login page. This may be caused by lack of memory for OC4J.

To solve this problem:

1. Log in to the computer where Oracle VM Manager is installed, and run the following command to check the log information:

```
# cat /var/log/ovm-manager/oc4j.log | grep "heap"
```

If OC4J runs out of memory, the following information is displayed:

```
Internal Exception: java.lang.OutOfMemoryError: Java heap space
```

2. Run the following command to restart OC4J:

```
# service oc4j stop
# service oc4j start
```

If OC4J runs out of memory, you need to increase the OC4J memory size. Follow these steps to do it:

1. View the OC4J configuration information:

```
# vi /opt/oc4j/bin/oc4j
```

2. Locate the following line, and increase the memory size to an appropriate value, such as 512:

```
OC4J_JVM_ARGS="-XX:PermSize=256m -XX:MaxPermSize=512m"
```

3. Restart OC4J:

```
# service oc4j stop
# service oc4j start
```

D.3 Cannot Create a Virtual Machine from Installation Media

The following message is displayed: "Error: There is no server supporting hardware virtualization in the selected server pool. "

To solve this problem, ensure that the Virtual Machine Server supports hardware virtualized machine (HVM).

Follow these steps to check:

1. Run the following command to check if HVM is supported by the CPU:

```
# cat /proc/cpuinfo | grep -E 'vmx|smx'
```

If any information that contains `vmx` or `smx` is displayed, it means that the CPU supports HVM. Here is an example of the returned message:

```
flags : fpu tsc msr pae mce cx8 apic mtrr mca cmov pat pse36 clflush dts acpi
mmx fxsr sse sse2 ss ht tm pbe nx lm constant_tsc pni monitor ds_cpl vmx est
tm2 cx16 xtpr lahf_lm
```

2. Ensure that you have enabled HVM in the BIOS.
3. Run the following command to check if the operating system supports HVM:

```
# xm info |grep hvm
```

The following is an example of the returned message:

```
xen_caps : xen-3.0-x86_64 xen-3.0-x86_32p hvm-3.0-x86_32 hvm-3.0-x
```

If the CPU does not support HVM, use the paravirtualized method to create the virtual machine. See [Section 6.3.2, "Creating a New Virtual Machine from Installation Media"](#).

D.4 No Sufficient Space in Repository for Creating a Virtual Machine

A message similar to the following is displayed: "Error: The largest virtual disk that can be allocated is: 4815 MB."

To solve this problem, decrease the disk size, or add a new repository.

Adding a New Repository

Before adding a new repository, ensure that all the Oracle VM Servers in the same server pool share the same repository, and mount it to the `/OVS` folder on each server.

To add a new repository:

1. Run the following command on Virtual Machine Server:

```
# /usr/lib/ovs/ovs-makerepo source shared description
```

The `source` parameter is the block device or NFS path to the file system to be added. The `shared` parameter sets whether the file system is to be shared between computers. Enter a 1 to have the file system shared, or a 0 to make it non-shared. The `description` parameter is the text displayed in Oracle VM Manager.

For example, run the following command:

```
# /usr/lib/ovs/ovs-makerepo /dev/sdc1 1 A new repository
```

You will get one repository in `/etc/ovs/repositories`:

```
# cat /etc/ovs/repositories
# This configuration file was generated by ovs-makerepo
# DO NOT EDIT
C860A37B7E4D437A93CA4116A79BD9C8 /dev/sdc1
```

The `makerepo` script identifies the file system or shared virtual disk as a repository, and updates the repository configuration to enable it.

2. Use the `df` command to review the usage and mount point:

```
# df
```

The following is an example of the returned information:

Filesystem	1K-blocks	Used	Available	Use%	Mounted on
/dev/sda1	9920592	848376	8560148	10%	/
tmpfs	262232	0	262232	0%	/dev/shm
/dev/sdb1	234380284	161920232	72460052	70%	/OVS
/dev/sdc1	292977372	5167844	287809528	2%	
/OVS/C860A37B7E4D437A93CA4116A79BD9C8					

The `/OVS/seed_pool`, `/OVS/running_pool`, and `/OVS/iso_pool` directories will be created automatically under the newly added repository.

3. Repeat the preceding steps on all Virtual Machine Servers to make sure the added repository has mounted correctly on each server.

When you create a virtual machine, Oracle VM Manager will choose a Virtual Machine Server with the maximum available disk size from `/OVS` or `/OVS/uuid` to run it.

D.5 The Virtual Machine Stuck in Certain Status

For Oracle VM Manager Release 2.1.1 and Release 2.1.2 Users

To solve this problem, reset the status to **Powered Off**, and then delete the virtual machine directly. See [Section 6.10.2, "Deleting a Virtual Machine Stuck in a Certain Status"](#) for more information.

For Oracle VM Manager Release 2.1 Users

To solve this problem, change the status manually as follows:

1. Make sure that the virtual machine in the target server has been shut down. Use **xm list** or **virsh list** to check the virtual machine name and ID.
2. If the virtual machine is running, use **xm shutdown *vm_id*** or **virsh shutdown *vm_id*** to shut it down, where *vm_id* refers to the virtual machine name or ID.
3. Use **xm list** or **virsh list** to check if the virtual machine has been shut down. If it is still running, use **xm destroy *vm_id***, or **virsh destroy *vm_id*** to shut it down.
4. Log in as **oracle** (or **root** first, then **su - oracle**) to the computer where Oracle VM Manager is installed, and run the following commands to change the virtual machine status to **Powered off** in Oracle XE database:

```
export ORACLE_HOME='/usr/lib/oracle/xe/app/oracle/product/10.2.0/server'
export ORACLE_SID=XE
$ORACLE_HOME/bin/sqlplus / as sysdba
SQL> update ovs.ows_vm_img t set t.status='Powered Off' where t.img_name like
'vm_name';
SQL> commit;
SQL> quit
```

vm_name refers to the virtual machine name.

5. Retry your operation, or delete the virtual machine directly.

D.6 The Status of the Virtual Machine Is "Error"

To view more details, click the **Virtual Machines** tab, and then click the **Show** link of the virtual machine. Click the number after the Log item to display the error log. The error log information includes: operation, operation details, start time and status.

The following are some error log items and solutions:

- Error: HVM guest support is unavailable: is VT/AMD-V supported by your CPU and enabled in your BIOS?
- Failed:<Exception: cannot find host server for vm('/OVS/running_pool/vm_name')>
- Failed:<Exception: Could not find '/OVS/running_pool/vm_name' in any storage repository.>
- Failed:<Exception: /opt/ovs-agent-2.2/utls/rcp.py /OVS/running_pool/vm_name/ root@example.com:/OVS/running_pool/vm_name password=>encounter 'permission denied'! >
- Failed:<Exception: return=>failed:<Exception: xm create '/OVS/running_pool/vm_name/vm.cfg'=>Error: Domain 'vm_name' already exists with ID '6' >>
- Failed:<Exception: vm('/OVS/running_pool/vm_name') status ('RUNNING') not in ('DOWN', 'ERROR')>
- Failed:<Exception: no server selected to run vm('/OVS/running_pool/vm_name') memory=512>
- Failed:<Exception: return=>failed:<Exception: xm create '/OVS/running_pool/vm_name/vm.cfg'=>Error: Device 0 (vif) could not be connected. Could not find bridge device null >>
- Failed:<Exception: no pxe bootable vif found.>
- Failed:<Exception: failed:<Exception: virt-install --paravirt --name=vm_name --ram=256 --vcpus=1 --file /OVS/running_pool/vm_name/System.img --file-size=1 --vnc --vnclisten=0.0.0.0 --vncpasswd=/tmp/tmp01TOh4 --noautoconsole --location=nfs:host:/mnt=>mount: can't get address for host umount: /var/lib/xen/xennfs.mkvX0Q: not mounted ERROR: Unable to mount NFS location! >>
- winxp_build failed:<Exception: return=>failed:<NameError: global name 'xen_handle_vif_qos' is not defined>>

D.6.1 Error: HVM guest support is unavailable: is VT/AMD-V supported by your CPU and enabled in your BIOS?

Possible Cause

The Virtual Machine Server does not support HVM.

Solution

Verify that the Virtual Machine Server supports HVM, and has HVM enabled in BIOS. See [Appendix D.3, "Cannot Create a Virtual Machine from Installation Media"](#).

If the Virtual Machine Server does not support HVM, you can create the virtual machine from installation media.

D.6.2 Failed:<Exception: cannot find host server for vm('/OVS/running_pool/vm_name')>

Possible Cause

- No Virtual Machine Server available to run the virtual machine.
- Insufficient memory on the Virtual Machine Server.

Solution

1. Ensure that at least one Virtual Machine Server is available to run the virtual machine.
2. Ensure that the Virtual Machine Server has sufficient memory.

To release server memory, you can:

- Shut down other running virtual machines.
- Decrease the virtual machine memory, and restart the virtual machine. See [Section 6.7, "Editing Virtual Machine Configuration"](#).

D.6.3 Failed:<Exception: Could not find '/OVS/running_pool/vm_name' in any storage repository.>

Possible Cause

The virtual machine has been removed from the Virtual Machine Server.

Solution

Remove the virtual machine in Oracle VM Manager, and create a new one.

D.6.4 Failed:<Exception: /opt/ovs-agent-2.2/utls/rcp.py /OVS/running_pool/vm_name/root@example.com:/OVS/running_pool/vm_name password=>encounter 'permission denied'! >

Possible Cause

You have entered an incorrect user name or password when creating the Utility Server.

Solution

Enter correct user name and password for the Utility Server. See [Section 3.2, "Creating a Server Pool"](#).

D.6.5 Failed:<Exception: return=>failed:<Exception: xm create '/OVS/running_pool/vm_name/vm.cfg'=>Error: Domain 'vm_name' already exists with ID '6' >>

Possible Cause

The virtual machine has been started already.

Solution

Use the command `xm list` to check the virtual machine status. Refresh the virtual machine periodically.

D.6.6 Failed:<Exception: vm('/OVS/running_pool/vm_name') status ('RUNNING') not in ('DOWN', 'ERROR')>

Possible Cause

The status in Oracle VM Manager has not been synchronized with the status data in the database.

Solution

Shut down the virtual machine, and then start it.

D.6.7 Failed:<Exception: no server selected to run vm('/OVS/running_pool/vm_name') memory=512>

Possible Cause

There is insufficient memory on this Virtual Machine Server.

Solution

Decrease the virtual machine memory, and then restart the virtual machine. Or shut down other running virtual machines to release more memory.

D.6.8 Failed:<Exception: return=>failed:<Exception: xm create '/OVS/running_pool/vm_name/vm.cfg'=>Error: Device 0 (vif) could not be connected. Could not find bridge device null >>

Possible Cause

No bridge for this virtual machine.

Solution

Select a bridge for it. See [Section 6.7.2, "Network"](#).

D.6.9 Failed:<Exception: no pxe bootable vif found.>

Possible Cause

Invalid VIF type for the virtual machine.

Solution

When starting a hardware virtualized machine through PXE, the VIF type must be **Fully Virtualized** (ioemu). Select a valid VIF type for the virtual machine. See [Section 6.7.2, "Network"](#).

D.6.10 Failed:<Exception: failed:<Exception: virt-install --paravirt --name=vm_name --ram=256 --vcpus=1 --file /OVS/running_pool/vm_name/System.img --file-size=1 --vnc --vnclisten=0.0.0.0 --vncpasswd=/tmp/tmp01TOh4 --noautoconsole --location=nfs:host:/mnt=>mount: can't get address for host umount: /var/lib/xen/xennfs.mkvX0Q: not mounted ERROR: Unable to mount NFS location! >>

Possible Cause

The resource location you entered is incorrect.

Solution

Delete the virtual machine, and create a new one. Make sure you enter a correct resource location when creating a paravirtualized machine.

D.6.11 winxp_build failed:<Exception: return=>failed:<NameError: global name 'xen_handle_vif_qos' is not defined>>

Possible Cause

The current Oracle VM Manager fails to detect the API `xen_handle_vif_qos`.

Solution

Upgrade both Oracle VM Manager and Oracle VM Server to 2.1.2 to support this feature.

D.7 Cannot Access Virtual Machine Console

If your operating system is Linux, and you are using Mozilla Firefox to access the virtual machine, download and install the Console Plug-in. See [Section 6.5.1, "Installing the Console Plug-In"](#).

If Oracle VM Manager is upgraded from the Release 2.1, rather than a fresh installation, you may encounter the following error when accessing the virtual machine console:

```
java.lang.ClassNotFoundException: VncViewer.class
```

This is caused by the delay in cache refresh. To solve this problem, shut down all the Web pages, and open a new one to access the virtual machine console.

D.8 Cannot Perform Live Migration

The following message is displayed:

Error: Server is not ready for live migration.

To solve this problem, you must use identical computers to perform live migrations, that is, the computer make and model number must be identical.

D.9 Cannot Change CD in the Virtual Machine

To change the CD in a virtual machine:

1. Unmount the first CD:

```
# umount mount-point
```
2. Select the second ISO file, and click **Change CD**.
3. Mount the second CD:

```
# mount /dev/cdrom mount-point
```

D.10 Cannot Import External Resources

Cannot Import Due to Invalid URL

The following information is displayed: "The URL is invalid", or "The proxy URL is invalid".

To solve this problem, log in to the Virtual Machine Server, and run the following command to test the network connection:

```
# wget url
```

Here, *url* refers to the link for downloading the resource.

If the resource is from the Internet, you may need a proxy before running the **wget** command. Contact your network administrator to get the proxy, and then run the following commands to configure the proxy:

```
# export http_proxy=http://host:port/
# export ftp_proxy=http://host:port/
```

Here, *host* refers to the host name or IP address of the proxy server, and *port* refers to the port number of the proxy.

Cannot Import Due to NFS Disk

The following information is displayed:

Cannot obtain memory size from vm.cfg.

This error may occur when there are two or more Utility Servers in a server pool, and the disk is shared by the Network File System (NFS) mode.

To solve this problem, click the **Next** button periodically.

D.11 Remote Host Identification Error in Server Pool

If you reinstall the Oracle VM Server software, or change the *root* user's password of an Oracle VM Server in a server pool, communication from the server pool to that server may fail.

If you reinstall the Oracle VM Server software (not upgraded), the RSA key is likely to change, even if you use the same IP address and host name. You may see an error similar to:

```
REMOTE HOST IDENTIFICATION HAS CHANGED
```

or

```
Host key verification failed
```

Workaround: Remove the Oracle VM Server from the server pool, and add the Oracle VM Server again.

Third Party Licenses

This Appendix includes the Third Party License for all the third-party products included with Oracle VM Manager.

E.1 Apache XML-RPC

Under the terms of the Apache xml-rpc license, Oracle is required to provide the following notices. However, the Oracle program license that accompanied this product determines your right to use the Oracle program, including the Apache software, and the terms contained in the following notices do not change those rights. Notwithstanding anything to the contrary in the Oracle program license, the Apache software is provided by Oracle "AS IS" and without warranty or support of any kind from Oracle or Apache.

E.1.1 Apache XML-RPC Software License

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical

transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.
3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.
4. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable

(except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

5. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:
 - (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
 - (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
 - (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
 - (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

6. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed

with Licensor regarding such Contributions.

7. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.
8. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.
9. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.
10. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

E.2 Third-Party Products Included with Sun Microsystems Products

Sun Microsystems has indicated that the following materials may be included in the Java Development Kit and/or JRE materials that are included in the Oracle product. Sun Microsystems currently provides the following notices as part of the Sun distribution:

E.2.1 CS CodeViewer v1.0

Use of any of this software is governed by the terms of the license below:

Copyright 1999 by CoolServlets.com.

Any errors or suggested improvements to this class can be reported as instructed on CoolServlets.com. We hope you enjoy this program... your comments will encourage further development! This software is distributed under the terms of the BSD License. Redistribution and use in source and binary forms, with or without

modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither name of CoolServlets.com nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

"THIS SOFTWARE IS PROVIDED BY COOLSERVLETS.COM AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE."

E.2.2 DES and 3xDES

Use of any of this software is governed by the terms of the license below:

"Copyright 2000 by Jef Poskanzer <jef@acme.com>. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE."

E.2.3 Crimson v1.1.1

Use of any of this software is governed by the terms of the license below:

The Apache Software License, Version 1.1

Copyright (c) 1999-2000 The Apache Software Foundation. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,

this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. The end-user documentation included with the redistribution, if any, must include the following acknowledgment: "This product includes software developed by the Apache Software Foundation

<http://www.apache.org/>

Alternately, this acknowledgment may appear in the software itself, if and wherever such third-party acknowledgments normally appear.

4. The names "Crimson" and "Apache Software Foundation" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact apache@apache.org.

5. Products derived from this software may not be called "Apache", nor may "Apache" appear in their name, without prior written permission of the Apache Software Foundation.

THIS SOFTWARE IS PROVIDED "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

=====

This software consists of voluntary contributions made by many individuals on behalf of the Apache Software Foundation and was originally based on software copyright (c) 1999, International Business Machines, Inc.,

<http://www.ibm.com>

For more information on the Apache Software Foundation, please see

<http://www.apache.org/>.

E.2.4 NSIS 1.0j

Use of any of this software is governed by the terms of the license below:

Copyright (C) 1999-2000 Nullsoft, Inc.

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software. Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.

3. This notice may not be removed or altered from any source distribution. Justin Frankel justin@nullsoft.com"

E.2.5 Some Portions licensed from IBM

Some Portions licensed from IBM are available at:
<http://oss.software.ibm.com/icu4j/>

E.2.6 Portions Copyright Eastman Kodak Company 1992

E.2.7 Lucida

Lucida is a registered trademark or trademark of Bigelow & Holmes in the U.S. and other countries.

E.2.8 Portions licensed from Taligent, Inc.

E.2.9 Additionally for JRE/JDK 1.5 / 5.0

The following software may be included in this product:

A. IAIK PKCS Wrapper

Use of any of this software is governed by the terms of the license below:

Copyright (c) 2002 Graz University of Technology. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The end-user documentation included with the redistribution, if any, must include the following acknowledgment:
"This product includes software developed by IAIK of Graz University of Technology."
Alternately, this acknowledgment may appear in the software itself, if and wherever such third-party acknowledgments normally appear.
4. The names "Graz University of Technology" and "IAIK of Graz University of Technology" must not be used to endorse or promote products derived from this software without prior written permission.
5. Products derived from this software may not be called "IAIK PKCS Wrapper", nor may "IAIK" appear in their name, without prior written permission of Graz University of Technology.

THIS SOFTWARE IS PROVIDED "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE LICENSOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS

SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Document Object Model (DOM) v. Level 3

The following software may be included in this product:

W3C SOFTWARE NOTICE AND LICENSE

<http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231>

This work (and included software, documentation such as READMEs, or other related items) is being provided by the copyright holders under the following license. By obtaining, using and/or copying this work, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions.

Permission to copy, modify, and distribute this software and its documentation, with or without modification, for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the software and documentation or portions thereof, including modifications:

1. The full text of this NOTICE in a location viewable to users of the redistributed or derivative work.
2. Any pre-existing intellectual property disclaimers, notices, or terms and conditions. If none exist, the W3C Software Short Notice should be included (hypertext is preferred, text is permitted) within the body of any redistributed or derivative code.
3. Notice of any changes or modifications to the files, including the date changes were made. (We recommend you provide URIs to the location from which the code is derived.)

THIS SOFTWARE AND DOCUMENTATION IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE OR DOCUMENTATION WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE SOFTWARE OR DOCUMENTATION.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to the software without specific, written prior permission. Title to copyright in this software and any associated documentation will at all times remain with copyright holders.

This formulation of W3C's notice and license became active on December 31 2002. This version removes the copyright ownership notice such that this license can be used with materials other than those owned by the W3C, reflects that ERCIM is now a host of the W3C, includes references to this specific dated version of the license, and removes the ambiguous grant of "use". Otherwise, this version is the same as the previous version and is written so as to preserve the Free Software Foundation's assessment of GPL compatibility and OSI's certification under the Open Source Definition. Please see our Copyright FAQ for common questions about using materials from our site, including specific terms and conditions for packages like libwww, Amaya, and Jigsaw. Other questions about this notice can be directed to site-policy@w3.org.

THIS SOFTWARE AND DOCUMENTATION IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE OR DOCUMENTATION WILL NOT INFRINGE ANY THIRD PARTY PATENTS,

COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS. COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE SOFTWARE OR DOCUMENTATION.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to the software without specific, written prior permission. Title to copyright in this software and any associated documentation will at all times remain with copyright holders.

This formulation of W3C's notice and license became active on August 14 1998 so as to improve compatibility with GPL. This version ensures that W3C software licensing terms are no more restrictive than GPL and consequently W3C software may be distributed in GPL packages. See the older formulation for the policy prior to this date. Please see our Copyright FAQ for common questions about using materials from our site, including specific terms and conditions for packages like libwww, Amaya, and Jigsaw. Other questions about this notice can be directed to site-policy@w3.org.

W3C XML Schema Test Collection v. 1.16.2

Use of any of this software is governed by the terms of the license below:

W3C DOCUMENT NOTICE AND LICENSE

Copyright 1994-2002 World Wide Web Consortium, (Massachusetts Institute of Technology, Institut National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved.

<http://www.w3.org/Consortium/Legal/>

Public documents on the W3C site are provided by the copyright holders under the following license. The software or Document Type Definitions (DTDs) associated with W3C specifications are governed by the Software Notice. By using and/or copying this document, or the W3C document from which this statement is linked, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions:

Permission to use, copy, and distribute the contents of this document, or the W3C document from which this statement is linked, in any medium for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the document, or portions thereof, that you use:

1. A link or URL to the original W3C document.
2. The pre-existing copyright notice of the original author, or if it doesn't exist, a notice of the form: "Copyright © 1994-2002 World Wide Web Consortium, (Massachusetts Institute of Technology, Institut National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved. <http://www.w3.org/Consortium/Legal/>" (Hypertext is preferred, but a textual representation is permitted.)
3. If it exists, the STATUS of the W3C document.

When space permits, inclusion of the full text of this NOTICE should be provided. We request that authorship attribution be provided in any software, documents, or other items or products that you create pursuant to the implementation of the contents of this document, or any portion thereof.

No right to create modifications or derivatives of W3C documents is granted pursuant to this license. However, if additional requirements (documented in the Copyright FAQ) are satisfied, the right to create modifications or derivatives is sometimes granted by the W3C to individuals complying with those requirements.

THIS DOCUMENT IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DOCUMENT ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE DOCUMENT OR THE PERFORMANCE OR IMPLEMENTATION OF THE CONTENTS THEREOF.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to this document or its contents without specific, written prior permission. Title to copyright in this document will at all times remain with copyright holders.

This formulation of W3C's notice and license became active on April 05 1999 so as to account for the treatment of DTDs, schema's and bindings. See the older formulation for the policy prior to this date. Please see our Copyright FAQ for common questions about using materials from our site, including specific terms and conditions for packages like libwww, Amaya, and Jigsaw. Other questions about this notice can be directed to site-policy@w3.org. webmaster (last updated by reagle on 1999/04/99.)

Mesa 3-D graphics library v. 5

Use of any of this software is governed by the terms of the license below:

core Mesa code include/GL/gl.h Brian Paul Mesa

GLX driver include/GL/glx.h Brian Paul Mesa

Ext registry include/GL/glexth SGI SGI Free B

include/GL/glxext.h

Mesa license:

The Mesa distribution consists of several components. Different copyrights and licenses apply to different components. For example, GLUT is copyrighted by Mark Kilgard, some demo programs are copyrighted by SGI, some of the Mesa device drivers are copyrighted by their authors. See below for a list of Mesa's components and the copyright/license for each.

The core Mesa library is licensed according to the terms of the XFree86 copyright (an MIT-style license). This allows integration with the XFree86/DRI project. Unless otherwise stated, the Mesa source code and documentation is licensed as follows:

Copyright (C) 1999-2003 Brian Paul All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL BRIAN PAUL BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Byte Code Engineering Library (BCEL) v. 5

Use of any of this software is governed by the terms of the license below:

Apache Software License

=====

The Apache Software License, Version 1.1

Copyright (c) 2001 The Apache Software Foundation. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The end-user documentation included with the redistribution, if any, must include the following acknowledgment:

"This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>)."

Alternately, this acknowledgment may appear in the software itself, if and wherever such third-party acknowledgments normally appear.

4. The names "Apache" and "Apache Software Foundation" and "Apache BCEL" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact apache@apache.org.

5. Products derived from this software may not be called "Apache", "Apache BCEL", nor may "Apache" appear in their name, without prior written permission of the Apache Software Foundation.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

=====

This software consists of voluntary contributions made by many individuals on

behalf of the Apache Software Foundation.

Regexp, Regular Expression Package v. 1.2

Use of any of this software is governed by the terms of the license below:

Use of any of this software is governed by the terms of Apache Software License, Version 1.1.

This software consists of voluntary contributions made by many individuals on behalf of the Apache Software Foundation. For more information on the Apache Software Foundation, please see <http://www.apache.org>.

CUP Parser Generator for Java v. 0.10k; Use of any of this software is governed by the terms of the license below:

CUP Parser Generator Copyright Notice, License, and Disclaimer

Copyright 1996-1999 by Scott Hudson, Frank Flannery, C. Scott Ananian

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both the copyright notice and this permission notice and warranty disclaimer appear in supporting documentation, and that the names of the authors or their employers not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

The authors and their employers disclaim all warranties with regard to this software, including all implied warranties of merchantability and fitness. In no event shall the authors or their employers be liable for any special, indirect or consequential damages or any damages whatsoever resulting from loss of use, data or profits, whether in an action of contract, negligence or other tortious action, arising out of or in connection with the use or performance of this software.

JLex: A Lexical Analyzer Generator for Java v. 1.2.5

Use of any of this software is governed by the terms of the license below:

JLEX COPYRIGHT NOTICE, LICENSE AND DISCLAIMER.

Copyright 1996-2003 by Elliot Joel Berk and C. Scott Ananian

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both the copyright notice and this permission notice and warranty disclaimer appear in supporting documentation, and that the name of the authors or their employers not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

The authors and their employers disclaim all warranties with regard to this software, including all implied warranties of merchantability and fitness. In no event shall the authors or their employers be liable for any special, indirect or consequential damages or any damages whatsoever resulting from loss of use, data or profits, whether in an action of contract, negligence or other tortious action, arising out of or in connection with the use or performance of this software.

Java is a trademark of Sun Microsystems, Inc. References to the Java programming language in relation to JLex are not meant to imply that Sun endorses this product.

SAX v. 2.0.1

Use of any of this software is governed by the terms of the license below:

Copyright Status

SAX is free!

In fact, it's not possible to own a license to SAX, since it's been placed in the public domain.

No Warranty

Because SAX is released to the public domain, there is no warranty for the design or for the software implementation, to the extent permitted by applicable law. Except when otherwise stated in writing the copyright holders and/or other parties provide SAX "as is" without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The entire risk as to the quality and performance of SAX is with you.

Should SAX prove defective, you assume the cost of all necessary servicing, repair or correction.

In no event unless required by applicable law or agreed to in writing will any copyright holder, or any other party who may modify and/or redistribute SAX, be liable to you for damages, including any general, special, incidental or consequential damages arising out of the use or inability to use SAX (including but not limited to loss of data or data being rendered inaccurate or losses sustained by you or third parties or a failure of the SAX to operate with any other programs), even if such holder or other party has been advised of the possibility of such damages.

Copyright Disclaimers

This page includes statements to that effect by David Megginson, who would have been able to claim copyright for the original work.

SAX 1.0

Version 1.0 of the Simple API for XML (SAX), created collectively by the membership of the XML-DEV mailing list, is hereby released into the public domain.

No one owns SAX: you may use it freely in both commercial and non-commercial applications, bundle it with your software distribution, include it on a CD-ROM, list the source code in a book, mirror the documentation at your own web site, or use it in any other way you see fit.

David Megginson, sax@megginson.com

1998-05-11

SAX 2.0

I hereby abandon any property rights to SAX 2.0 (the Simple API for XML), and release all of the SAX 2.0 source code, compiled code, and documentation contained in this distribution into the Public Domain. SAX comes with NO WARRANTY or guarantee of fitness for any purpose.

David Megginson, david@megginson.com

2000-05-05

Cryptix

Use of any of this software is governed by the terms of the license below:

Cryptix General License

Copyright 1995-2003 The Cryptix Foundation Limited. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE CRYPTIX FOUNDATION LIMITED AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE CRYPTIX FOUNDATION LIMITED OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Glossary

Domain

A configurable set of resources, including memory, virtual CPUs, network devices and disk devices, in which virtual machines run. A domain is granted virtual resources and can be started, stopped and rebooted independently.

See also [dom0](#) and [domU](#).

dom0

An abbreviation for *domain zero*. The management domain with privileged access to the hardware and device drivers. Dom0 is the first domain started by the Oracle VM Server at boot time. Dom0 has more privileges than domU. It can access the hardware directly and can manage the device drivers for other domains. It can also start new domains.

domU

An unprivileged domain with no direct access to the hardware or device drivers. Each domU is started by Oracle VM Server in dom0. The xm command-line tool is used to interact with each domU.

Guest

A guest operating system that runs within a domain in Oracle VM Server. A guest may be paravirtualized or hardware virtualized. Multiple guests can run on the same Oracle VM Server.

Hardware virtualized machine

A virtual machine with an unmodified guest operating system. It is not recompiled for the virtual environment. There may be substantial performance penalties running as a hardware virtualized guest. Enables Microsoft Windows™ operating system to be run, as well as legacy operating systems. Hardware virtualization is only available on Intel VT or AMD SVM CPUs.

Host computer

The physical computer on which Oracle VM Server is installed.

Hypervisor

The hypervisor, monitor, or Virtual Machine Manager (VMM). It is the only fully privileged entity in the system. It controls only the most basic resources of the system, including CPU and memory usage, privilege checks, and hardware interrupts.

Management domain

See [dom0](#).

Oracle VM Agent

An application installed with Oracle VM Server. It communicates with Oracle VM Manager for management of virtual machines. Oracle VM Manager manages the virtual machines running on Oracle VM Server by communicating with Oracle VM Agent. It contains three components: Server Pool Master, Utility Server, and Virtual Machine Server.

Oracle VM Server

A self-contained virtualization environment designed to provide a lightweight, secure, server-based platform for running virtual machines. Oracle VM Server is based upon an updated version of the Xen hypervisor technology. Includes Oracle VM Agent to enable communication with Oracle VM Manager.

Oracle VM Manager

Provides the user interface, which is a standard ADF (Application Development Framework) web application, to manage Oracle VM Server pools. Manages virtual machine lifecycle, including creating virtual machines from templates or from installation media, deleting, powering off, uploading, deployment and live migration of virtual machines. Manages resources including ISO files, templates and shared virtual disks. Also provides an API via a web service to Oracle VM Server.

Paravirtualized machine

A virtual machine with a kernel that is recompiled to be made aware of the virtual environment. Runs at near native speed, with memory, disk and network access optimized for maximum performance.

Preferred Server

A Virtual Machine Server that provides resources such as memory, CPU, network interface cards (NICs), and disk to the virtual machine. If you select only one Virtual Machine Server as the preferred server, the virtual machine always starts from and runs on this server. If you select multiple preferred servers, each time the virtual machine starts, it runs on the machine with the maximum available resources.

QEMU

Also referred to as qemu-dm, which is the process name. The virtualization process which allows full virtualization of a PC system within another PC system.

Server Pool

Logically an autonomous region that contains one or more physical Oracle VM Servers. Presents a unified view of the storage where the virtual machines reside, and groups the users of these virtual machines into a single community called a *group*, in which each user is a server pool member.

Server Pool Master

A component of Oracle VM Agent. An application that acts as the contact point to Oracle VM Manager, and to other Oracle VM Agents. Provides virtual machine host load-balancing, and local persistency for Oracle VM Server.

There is only one Server Pool Master in a server pool. A physical server can perform as the Server Pool Master, Utility Server and Virtual Machine Server simultaneously.

Utility Server

A component of Oracle VM Agent. An application that handles I/O intensive operations for virtual machines, server pools and servers, for example, copying, moving and renaming files.

There can be more than one Utility Server in a server pool. A physical server can perform as the Server Pool Master, Utility Server and Virtual Machine Server simultaneously.

vif

A virtual network interface for bridging network interfaces between domUs and dom0. When a domU is started it is assigned a number. This number is used to bridge the network interface from `ethn` to `vifn.0`.

Virtual disk

A file or set of files, usually on the host file system although it may also be a remote file system, that appears as a physical disk drive to the guest operating system.

Virtual Machine (VM)

A guest operating system and the associated application software that runs within Oracle VM Server. May be paravirtualized or hardware virtualized machines. Multiple virtual machines can run on the same Oracle VM Server.

Virtual Machine Manager (VMM)

See [Hypervisor](#).

Virtual Machine Server

A component of Oracle VM Agent. An application which runs Oracle VM Server virtual machines. It can start and stop virtual machines, and collect performance data for the host and guest operating systems. Enables communication between the Server Pool Master, Utility Server and Virtual Machine Servers.

There can be more than one Virtual Machine Server in a server pool. A physical server can perform as the Server Pool Master, Utility Server and Virtual Machine Server simultaneously.

Virtual Machine Template

A template of a virtual machine. Contains basic configuration information such as the number of CPUs, memory size, hard disk size, and network interface card (NIC). Create virtual machines based on a virtual machine template using Oracle VM Manager.

VMM

See [Virtual Machine Manager \(VMM\)](#).

Xen™

The Xen hypervisor is a small, lightweight, software virtual machine monitor, for x86-compatible computers. The Xen hypervisor securely executes multiple virtual machines on one physical system. Each virtual machine has its own guest operating system with almost native performance. The Xen hypervisor was originally created by researchers at Cambridge University, and derived from work done on the Linux kernel.

Index

A

adding utility or virtual machine servers, 4-1
AdminService, C-14
approving ISO files, 5-15
approving resources, 5-1
architecture of Oracle VM Manager, 1-3

C

changing password, 2-3
configurations of virtual machines, 6-19
conversion
 P2V image, 5-10
 P2V template, 5-5
 V2V, 5-7
creating groups, 7-4
creating server pools, 3-3
creating users, 7-1
creating virtual machines, 6-7

D

default account, 7-1
default group, 7-4
details of virtual machine, 6-19
dom0, Glossary-1
Domain, Glossary-1
domU, Glossary-1

E

editing groups, 7-5
editing server pools, 3-6
editing servers, 4-2
editing users, 7-3
error log and troubleshooting, D-4

G

groups
 adding users, 7-4
 creating, 7-4
 deleting, 7-5
 editing users, 7-5
groups advantages, 7-4
Guest, Glossary-1

Guest operating system, Glossary-1

H

Hardware virtualized machine, Glossary-1
high availability
 for virtual machines created based on
 template, 6-9
 for virtual machines created by PXE boot, 6-14
 for virtual machines created from installation
 media, 6-12
 overview, 3-9
Host computer, Glossary-1
Hypervisor, Glossary-1

I

importing ISO files, 5-13
importing virtual machine templates, 5-3
importing virtual machines, 5-7
ISO files
 approving, 5-15
 importing, 5-13
 reimporting, 5-15
 status, 5-14
ISO files status, 5-15

L

LifecycleService, C-9
log information and troubleshooting, D-4
logging in to Oracle VM Manager, 2-2

M

Management domain, Glossary-1

O

Oracle VM, 1-2
 Overview, 1-2
Oracle VM Agent, 1-2, Glossary-2
Oracle VM Manager, 1-2, Glossary-2
 architecture, 1-3
 main features, 1-6
 user roles, 1-5

P

P2V conversion
 image, 5-10
 template, 5-5
Paravirtualized machine, Glossary-2
PluginService, C-11
Preferred Server, Glossary-2
preferred server, 6-8, 6-26
profile information, 2-3

Q

QEMU, Glossary-2
QoS, 6-24
Quality of Service, 6-24

R

registering users, 2-1
reimporting ISO files, 5-15
reimporting virtual machine templates, 5-6
reimporting virtual machines, 5-12
ResourceService, C-10
restarting servers, 4-4
roles changing, 7-2
roles of users in Oracle VM Manager, 1-5

S

Server Pool, Glossary-2
server pool configurations, 3-2
Server Pool Master, Glossary-2
server pool master, 1-4
server pools
 creating, 3-3
 server type, 3-5
 testing connection, 3-5
 deleting, 3-11
 how to design, 3-1
 restoring, 3-8
 searching, 3-8
ServerPoolService, C-12
servers
 adding, 4-1
 deleting, 4-4
 editing, 4-2
 restarting, 4-4
 shutting down, 4-4
servers concept, 1-4
shared virtual disks
 creating, 5-16
 deleting, 5-17
 searching, 5-16
status of virtual machines, 6-2
storage, 1-5

T

troubleshooting, D-1

U

users
 changing roles, 7-3
 creating, 7-1
 deleting, 7-4
 editing, 7-3
 viewing details, 7-2
users status, 7-3
Utility Server, Glossary-3
utility server, 1-5

V

vif, Glossary-3
Virtual disk, Glossary-3
Virtual Machine, Glossary-3
virtual machine creating
 based on virtual machine template, 6-8
 basic steps, 6-8
 from installation media, 6-10
 PXE boot, 6-13
virtual machine log, 6-6
Virtual Machine Manager, Glossary-3
Virtual Machine Server, Glossary-3
virtual machine server, 1-5
virtual machine status mechanism, 6-4
Virtual machine template, Glossary-3
virtual machine templates
 approving, 5-6
 deleting, 5-7
 editing, 5-7
 importing, 5-3
 reimporting, 5-6
 status, 5-6
virtual machine types, 6-2
virtual machines
 approving, 5-12
 cloning, 6-30
 console, 6-17
 deleting, 6-32
 deleting in certain status, 6-32
 deploying, 6-29
 importing, 5-7
 pausing and unpausing, 6-16
 reimporting, 5-12
 saving as virtual machine template, 6-31
 shutting down, 6-15
 starting, 6-15
 suspending and resuming, 6-16
 viewing details, 6-6
virtual machines configuring, 6-19
virtual machines editing
 general information, 6-20
 network, 6-22
 preferred server, 6-26
 profile, 6-27

storage, 6-23
Virtual Network Interface, Glossary-3
VirtualMachineService, C-13
VM, Glossary-3
VM Server, Glossary-3
VMM, Glossary-3
VNC port, 6-19

W

Wizard to create a server pool, 2-3

X

Xen, Glossary-3
Xen hypervisor, Glossary-3

