

# **SECTION 2: Database Schema And Definitions**

Table	
Name	Definition
ASACCOUNTINGDETAIL	Contains the debits and credits stored as a result of the activities and suspense.
ASACCOUNTINGDETAILDISBURSEMENT	Contains accounting detail of disbursement records
ASACCOUNTINGDETAILFIELD	Stores field names and values relating to Accounting Details
ASACTIVITY	Stores instance date of policy activities
ASACTIVITYFIELD	Stores field names and values relating to Activities
ASACTIVITYMATH	Stores values of math variables that have a LOG attribute set to "Yes" in the transaction XML.
ASACTIVITYSPAWN	Stores Activity spawn information.
ASACTIVITYSUSPENSE	Stores activity suspense records
ASACTIVITYVALUATOIN	Stores Activity Valuation Records
ASACTIVITYVALUATIONCHILD	Stores Activity Valuation Child records
ASADDRESS	Location information: physical address, email, phone
ASADDRESSFIELD	Stores field names and values relating to Addresses
ASADDRESSOPTIONTEXT	Stores optiontext values
ASADDRESSROLE	Associates a client with an address. Clients may have several addresses of varying types and several clients may share the same address.
ASALLOCATION	Stores the Fund Allocation attached to a Policy, a Plan or an Activity
ASAPPROVAL	Stores States in which product can be sold
ASAUUXILIARY	Container for miscellaneous data
ASBATCH	Stores batch numbers
ASBATCHACTIVITY	Stores batch activities
ASBATCHACTIVITYALLOCATION	Stores batch activity allocations
ASBATCHACTIVITYFIELD	Stores the batch activity fields
ASBATCHFIELD	Stores batch field data
ASBATCHSCREEN	Contains the XML rules
ASBATCHSCREENOPTIONTEXT	Stores Batch Screen option text values
ASBENEFITSPLIT	Stores the benefit units that are necessary to pay the annuity benefit
ASBENEFITSPLITCHANGE	Stores Changes in Benefitsplit
ASBUSINESSRULES	Contains the XML rules
ASBUSINESSRULEHISTORY	Stores history of xml rules
ASCHARTOFACCOUNTS	General Ledger chart of accounts
ASCHARTOFACCOUNTSCRITERIA	Criteria for Chart of Accounts
ASCHARTOFACCOUNTSENTITY	Transaction or suspense entry for account
ASCHARTOFACCOUNTSENTRY	Debit/Credit entry for an account ( must be tied to transaction or suspense )
ASCHARTOFACCOUNTSENTRYCRITERIA	Criteria Values for the Entries
ASCHARTOFACCOUNTSMONEYTYPE	List of money types that will filter funds that calculate the accounting amount(s)
ASCHARTOFACCOUNTSRESULT	Writes values to the accounting record(s) being created
ASCLIENT	Holds people and corporations/companies that can fill various roles related to policies.
ASCLIENTACTIVITY	Stores client activities
ASCLIENTACTIVITYGROUP	Stores group activities
ASCLIENTACTIVITYGROUPFIELD	Stores group activity fields
ASCLIENTACTIVITYGROUPOPTIONTXT	Stores text values of client activities
ASCLIENTFIELD	Stores Field names and values related to Clients
ASCLIENTGROUP	Stores client group activities
ASCLIENTGROUPFIELD	Stores client group activity fields
ASCLIENTLANGUAGE	Stores language for each client
ASCODE	Stores a list of all AdminServer codes and their related descriptions

ASCOMMENTS	Stores comments that can be linked to a record in any table where the primary key is a GUID
ASCOMMENTSFIELD	Stores Comment field values
ASCOMMENTSOPTIONTEXT	Stores Comment optiontext values
ASCOMPANY	Contains names of all companies defined to the system
ASCURRENCY	Defines different types of currency
ASCYCLE	Populated by the nightly cycle
ASCYCLESTATUS	Results of cycles
ASDATADICTIONARY	Defines variable names used within the system
ASDATADICTIONARYCATEGORY	Links data dictionary category to data dictionary name
ASDATADICTIONARYCATEGORYNAME	Defines data dictionary categories
ASDATADICTIONARYDEPENDENCY	Links data dictionary item to rule or transaction, etc.
ASDETAILSUSPENSE	Holds user defined data associated with AsSuspense
ASDISBURSEMENT	Holds data containing disbursement to clients
ASDISBURSEMENTAPPROVAL	Stores approved disbursements
ASDISBURSEMENTFIELD	Stores disbursement fields
ASDOCUMENT	Holds names of documents linked to activities
ASENGINEMATH	Record of mathematical calculations performed in an activity
ASENGINESEGMENT	Stores debugging information
ASERRORCATALOG	Table of error messages
ASEXCHANGE	Currency exchange rates
ASFILE	Stores XSLT and XML
ASFILETRACKING	Stores file tracking
ASFILETRACKINGEVENT	Stores file tracking events
ASFILTER	Activity filters which define which activities are viewed on the Activities screen.
ASFUND	Contains the names of the fixed and variable funds
ASFUNDCLASS	Stores the Fund Series information
ASFUNDCLASSALLOCATION	Defines the allocation methods of groups of funds
ASFUNDFAMILY	Groups funds and fund classes together
ASFUNDFIELD	Stores Field names and values related to Funds
ASFUNDGROUP	Defines relationships between funds
ASFUNDSTATE	Defines fund information for states
ASFUNDSTATUS	Stores the status of all Funds in the system
ASFUNDWEIGHT	Relative weights of funds
ASHELPSCREEN	The table controls the help function in the system
ASHIERARCHY	Used to track the hierarchy of insurance agent roles, for commissions and such
ASHISTORY	Stores Change history of events, actions.
ASHISTORYDETAIL	Stores to and from data of history changes
ASILLUSTRATION	Represents an insurance policy or annuity
ASIMPORTLOG	Logging/reports of imports
ASINQUIRYSCREEN	Stores information for each Inquiry Screen that is created
ASLINKREQUIREMENT	Stores a requirements list available for the Delivery Requirements screen
ASLIQUIDITYUNITS	Stores liquidity unit values
ASLISTBILL	Groups policies together to process a common transaction
ASLISTBILLALLOCATION	Placeholder for allocations before they are moved to the AsAllocation table as part of the newly released ListBill activity.
ASLISTBILLFIELD	Stores Field names and values related to ListBill
ASLOOKUPREQUIREMENT	Contains criteria for generating a requirement
ASMAPCRITERIA	Stores Map criteria
ASMAPGROUP	Stores Map group data

ASMAPNAME	User defined lookup table
ASMAPVALUE	Stores map values
ASMATHDEBUG	Stores Debug information
ASMATHDEBUGEVENT	Stores Debug event information
ASMIGRATION	Stores Migration information
ASMIGRATIONFIELD	Stores migration field data
ASNETASSETVALUE	Holds the daily value of each fund
ASOPTIONTEXT	Stores the displayed text for the selected value of activity field combos
ASPLAN	Names and starting dates of plans
ASPLANFIELD	Stores Field names and values related to Plans
ASPLANGROUP	Stores parent and child plans
ASPOLICY	Stores key data related to Policies
ASPOLICYFIELD	Stores Field names and values related to Policies
ASPOSTALID	Associates a postal code with a city and state
ASPREMIUM	Stores information for the premiums entered under policies
ASPRESETCOMMENTS	Stores presetcomment information
ASRATE	Rate lookup table
ASRATECRITERIA	Contains the data that describe what criteria correspond to the rate table
ASRATEDESCRIPTOR	Contains the data used to describe how a table of rates is setup in an Excel spreadsheet
ASRATEGROUP	Index table that summarizes the contents of AsRate
ASRATEUPDATE	Stores Rate update values
ASREQUIREMENT	Stores dates for policy requirements
ASROLE	Defines the roles that clients can play relative to a policy
ASROLEFIELD	Stores Field names and values related to Roles
ASROLEOPTIONTEXT	Stores Role Option text values
ASROLESEQUENCE	For identical roles, this stores the number of the role on a policy
ASROLLBACK	Used for price rollbacks (corrections)
ASROLLBACKNUV	Used for price rollbacks
ASROLLBACKPOLICY	Policies affected by price rollbacks
ASROUTINGNUMBER	Contains bank routing numbers and is used to verify that a CSR enters a proper routing number on the screen. After entering the number, the system will do a verification of the number and/or bank name to make sure the data that was entered is correct.
ASSCHEDULEDVALUATION	Used for transaction daily valuation to hold information about policies by fund
ASSCHEDULEDVALUATIONCHILD	Stores scheduled valuation child information
ASSCHEDULEDVALUATIONDEPOSIT	Stores ScheduledValuation Deposit data
ASSCHEDULEDVALUATIONFIELD	Stores ScheduledValuation fields
ASSCHEDULEDVALUATIONFUND	Stores Scheduled Valuation funds
ASSCHEDULEDVALUATIONPOLICYVALUES	More detailed policy information linked with AsScheduledValuation, driven by the Business Rule PolicyValues
ASSECURITY	Stores the system user names and related login information
ASSECURITYROLE	Defines the levels of security in the system. Page/Field security in the AdminServer system is controlled via business rules. These business rules are maintained in this table.
ASSECURITYROLEHISTORY	Stores history of Security Roles
ASSEGMENT	Contains information about the pieces of insurance attached to a policy
ASSEGMENTFIELD	Stores Field names and values related to Segments
ASSEGMENTNAME	The definition of a segment
ASSEQUENCE	Multiple uses for any function that needs to track by date or integer: Cycle/Disbursement
ASSTATEAPPROVAL	Stores States in which product can be sold
ASSTATEAPPROVALTYPE	Stores States in which product can be sold and allows specified fields to be excluded on the segment screen by state approval
ASSUSPENSE	Holding area for money transactions

ASSUSPENSEFIELD	Stores Field names and values related to Suspense Records
ASSUSPENSEOPTIONTEXT	Stores suspense optiontext values
ASSYSTEMDATE	Stores systemdate records
ASSYSTEMDATEFIELD	Stores systemdate field records
ASTAXLOT	Track at the fund level tax lots
ASTRANSACTION	Contains transaction details and XML that drives the transaction
ASTRANSACTIONQUOTE	Stores an XML blob structured like our DataCarrier for quoted activities
ASTRANSFERDETAIL	Provides detailed information about where money is transferred and tracks its detail.
ASTRANSLATION	Stores English words and their translations in any language
ASUPLOAD	Used when uploading/attaching something to a Business Rule or activity
ASUPLOADCONNECTIVITY	Used when uploading/attaching to an activity
ASUPLOADRATE	Like AsRate but the rate was uploaded using our Business Rules screen
ASVALUATION	Holds values of amounts associated with fund allocations
ASVALUATIONCHILD	Stores valuation child information
ASVALUATIONXML	Carries all information regarding the value of a policy linked to an activity
ASVALUESREQUEST	Table that gets populated when daily valuation is run
ASWEBREQUEST	Stores all incoming XML for web service calls to AdminServer from external systems
ASWEIGHTEDNAV	Insert Net asset value into the system
ASWITHHOLDING	Stores information regarding withholding on a Policy / Plan /Activity
ASWITHHOLDINGFIELD	Stores Field names and values from the WithholdingScreen Business Rule

ASACCOUNTINGDETAIL			
Name	Datatype	Null Option	Comment
ACCOUNTINGDETAILGUID	CHARACTER(36)	NOT NULL	Unique ID
ActivityGUID	CHARACTER(36)	NULL	
SuspenseGUID	CHARACTER(36)	NULL	
FundGUID	CHARACTER(36)	NULL	
CHARTOFACCOUNTSGUID	CHARACTER(36)	NOT NULL	Foreign key into AsChartOfAccounts: identifies the G/L account
ACCOUNTNUMBER	VARCHAR(50)	NOT NULL	User defined via business rule (COAMask defines the format of the number)
DebitCreditCode	VARCHAR(2)	NOT NULL	
GainLossFlag	VARCHAR(1)	NOT NULL	
DoReversalAccountingFlag	VARCHAR(1)	NULL	
ReversalAccountingStatusCode	VARCHAR(3)	NULL	
EntryDescription	VARCHAR(255)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeCOAType (01-Debit, 02-Credit)
AMOUNT	DECIMAL(19,4)	NOT NULL	Dollar amount from activity or suspense
STATUSCODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = 'AsCodeStatus'
EFFECTIVEDATE	TIMESTAMP	NULL	System date of the activity
ACTIVEDATE	TIMESTAMP	NULL	
ENTRYGMT	TIMESTAMP	NULL	

ASACCOUNTINGDETAILDISBURSEMENT			
Name	Datatype	Null Option	Comment
ACCOUNTINGDETAILGUID	CHARACTER(36)	NOT NULL	
DISBURSEMENTGUID	VARCHAR(100)	NOT NULL	

ASACCOUNTINGDETAILFIELD			
Name	Datatype	Null Option	Comment
ACCOUNTINGDETAILGUID	CHARACTER(36)	NOT NULL	Primary Key
FIELDNAME	VARCHAR(50)	NOT NULL	Name of each Accounting Detail Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASACTIVITY			
Name	Datatype	Null Option	Comment
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Primary key
TRANSACTIONGUID	CHARACTER(36)	NOT NULL	Foreign key into AsTransaction
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeCOAType (01-Debit, 02-Credit)
STATUSCODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeStatus
EFFECTIVEDATE	TIMESTAMP	NOT NULL	System date of the activity
ACTIVEFROMDATE	TIMESTAMP	NULL	Date the activity ran
ACTIVETODATE	TIMESTAMP	NULL	Used by shadowed activities to mark when they became shadowed
CLIENTNUMBER	VARCHAR(50)	NOT NULL	Link to AsSecurity
POLICYGUID	CHARACTER(36)	NULL	Link to AsPolicy
RELATEDGUID	CHARACTER(36)	NULL	When an activity is reversed, this column is populated with the ActivityGUID that was reversed.
XMLDATA	CLOB(1048576)	NULL	User defined data for the activity
PROCESSINGORDER	DECIMAL(7,2)	NOT NULL	Relative order of operation for the activity
ERRORSTATUSCODE	VARCHAR(2)	NULL	01-No error, 02-Error
SUSPENSESTATUSCODE	VARCHAR(2)	NULL	Link to AsCodeSuspenseStatus
ACTIVITYGMT	TIMESTAMP	NULL	Date/time the activity was last saved
ENTRYGMT	TIMESTAMP	NULL	Date/time the activity was entered
CREATIONGMT	TIMESTAMP	NOT NULL	
SCHEDULEGUID	CHARACTER(36)	NULL	

ASACTIVITYFIELD			
Name	Datatype	Null Option	Comment
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Primary Key
FIELDNAME	VARCHAR(50)	NOT NULL	Name of each Activity Field

ASACTIVITYFIELD			
Name	Datatype	Null Option	Comment
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From asCode.CodeValue where CodeName = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASACTIVITYMATH			
Name	Datatype	Null Option	Comment
ACTIVITYGUID	CHARACTER(36)	NOT NULL	GUID of activity the math variable was calculated in
MATHNAME	VARCHAR(100)	NOT NULL	Name of variable (as defined by value of VARIABLENAME attribute in the transaction XML)
MATHVALUE	VARCHAR(7900)	NULL	Calculated value

ASACTIVITYSPAWN			
Name	Datatype	Null Option	Comment
ACTIVITYGUID	VARCHAR(36)	NOT NULL	GUID of activity that was spawned
SPAWNEDBYGUID	VARCHAR(36)	NOT NULL	GUID of the activity that did the spawning.

ASACTIVITYSUSPENSE			
Name	Datatype	Null Option	Comment
ACTIVITYGUID	CHARACTER(36)	NOT NULL	GUID of activity the suspense is attached
SUSPENSEGUID	CHARACTER(36)	NOT NULL	GUID of the suspense activity
SUSPENSESEQUENCE	INTEGER	NOT NULL	Sequence number
SPECIFIEDAMOUNT	DECIMAL(18,10)	Null	Amount specified

ASACTIVITYVALUATION			
Name	Datatype	Null Option	Comment
ACTIVITYVALUATIONGUID	CHARACTER(36)	NOT NULL	Primary Key
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Links to AsActivity
FUNDGUID	CHARACTER(36)	NOT NULL	Links to AsFund
VALUATIONTYPECODE	VARCHAR(2)	NOT NULL	Valuation Type Code
VALUATIONAMOUNT	DECIMAL(22,10)	NULL	Amount
VALUATIONUNITS	DECIMAL(22,10)	NULL	Unit
UNITVALUE	DECIMAL(22,10)	NULL	Unit Value

ASACTIVITYVALUATIONCHILD			
Name	Datatype	Null Option	Comment
ACTIVITYVALUATIONCHILDGUID	CHARACTER(36)	NOT NULL	Primary Key
ACTIVITYVALUATIONGUID	CHARACTER(36)	NOT NULL	Links to AsActivityValuation
CHILDGUID	CHARACTER(36)	NOT NULL	Links to AsFund
VALUATIONTYPECODE	VARCHAR(2)	NOT NULL	Valuation Type Code
VALUATIONAMOUNT	DECIMAL(22,10)	NULL	Amount
VALUATIONUNITS	DECIMAL(22,10)	NULL	Unit
UNITVALUE	DECIMAL(22,10)	NULL	Unit Value

ASADDRESS			
Name	Datatype	Null Option	Comment
ADDRESSGUID	CHARACTER(36)	NOT NULL	Primary Key
ADDRESSLINE1	VARCHAR(50)	NULL	Postal address 1
ADDRESSLINE2	VARCHAR(50)	NULL	Postal address 2
ADDRESSLINE3	VARCHAR(50)	NULL	Postal address 3
ADDRESSLINE4	VARCHAR(50)	NULL	Postal address 4
CITY	VARCHAR(50)	NULL	City
STATECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = 'AsCodeState'
COUNTRYCODE	VARCHAR(3)	NULL	From AsCode.CodeValue where CodeName = 'AsCodeCountry'
POSTALID	VARCHAR(30)	NULL	Foreign key into AsPostalID
EMAIL	VARCHAR(100)	NULL	E-Mail address
PHONENUMBER	VARCHAR(20)	NULL	Phone number
FAXNUMBER	VARCHAR(20)	NULL	Fax number
XMLDATA	CLOB(1048576)	NULL	User defined data

ASADDRESS			
Name	Datatype	Null Option	Comment
EFFECTIVEDATE	TIMESTAMP	NULL	Date after which this address is valid
EXPIRATIONDATE	TIMESTAMP	NULL	Date after which this address is invalid

ASADDRESSFIELD			
Name	Datatype	Null Option	Comment
ADDRESSGUID	CHARACTER(36)	NOT NULL	Primary Key
FIELDNAME	VARCHAR(50)	NOT NULL	Attributes relating to a specific address
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASADDRESSOPTIONTEXT			
Name	Datatype	Null Option	Comment
ADDRESSGUID	CHARACTER(36)	NOT NULL	Foreign key into AsAddress
FIELDNAME	VARCHAR(50)	NOT NULL	Field name from AsAddressField
OPTIONTEXT	VARCHAR(255)	NULL	Text Value of field from AsAddressField

ASADDRESSROLE			
Name	Datatype	Null Option	Comment
ADDRESSROLEGUID	CHARACTER(36)	NOT NULL	Primary key
ADDRESSROLECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where Codename = AsCodeAddressRole (01-EFT, 02-Home, 03-Employer, 04-Other)
CLIENTGUID	CHARACTER(36)	NULL	Identifies a client
ADDRESSGUID	CHARACTER(36)	NULL	Identifies a specific address
DEFAULTFLAG	VARCHAR(1)	NULL	If '1', this is the default address to use for the client.
EMAILCORRESPONDENCEFLAG	VARCHAR(2)	NULL	Refers to email addresses attached to an address

ASALLOCATION			
Name	Datatype	Null Option	Comment
ALLOCATIONGUID	CHARACTER(36)	NOT NULL	Primary key
GROUPGUID	CHARACTER(36)	NULL	Identifies the group to which this allocation belongs
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeAllocationType 01:Plan Default 02:Future Allocations 03:Activity Allocation 04:Plan Default - Issue 05:Segment Default 06:Issue-Retail 07:Issue-Insurance 08:Issue-Consults 09:Rebalancing Program 10:AIF 11:Systematic Withdrawal 12:Future Program 13:DCA From Fund 14:DCA Funds 15:Future 17:Future 25:Model - Capital Preservation 26:Model - Current Income 27:Income And Growth Model 28:Model - Long Term Growth 29:Model - Aggressive Growth 38:Future 51:Original Benefit 61:Directed Deductions 99:Deleted Allocation (used by Reversal)
RELATEDGUID	CHARACTER(36)	NULL	Either PolicyGUID, ActivityGUID or PlanGUID
FUNDGUID	CHARACTER(36)	NOT NULL	Link to AsFund
ALLOCATIONMETHODCODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = 'AsCodeAllocationMethod' 01:Percent



ASALLOCATION			
Name	Datatype	Null Option	Comment
			02:Amount 03:Units 04:Preferred Pro Rata
ALLOCATIONPERCENT	DECIMAL(18,10)	NULL	Percent entered
ALLOCATIONAMOUNT	DECIMAL(18,2)	NULL	Amount entered
ALLOCATIONUNITS	DECIMAL(18,10)	NULL	Units entered
PERCENTINALLOCATION	DECIMAL(18,10)	NOT NULL	Prorata calculated percentage
EFFECTIVEDATE	TIMESTAMP	NULL	As of date

ASAPPROVAL			
Name	Datatype	Null Option	Comment
RELATEDGUID	CHARACTER(36)	NOT NULL	PlanGUID or SegmentGUID
STATECODEVALUE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCode. Defines the approval state
TYPECODE	CHARACTER(2)	NOT NULL	Segment or Plan Approval From AsCode.CodeValue where CodeName = AsCodeApprovalStateType 01:RelatedGUID is the PlanGUID 02:RelatedGUID is the SegmentGUID 03:XML data approved on plan level
EFFECTIVEDATE	TIMESTAMP	NOT NULL	As of date
EXPIRATIONDATE	TIMESTAMP	NULL	
XMLDATA	CLOB(1048576)	NULL	Part of Segment or Plan that is getting the approval

ASAUUXILIARY			
Name	Datatype	Null Option	Comment
RELATEDGUID	CHARACTER(36)	NOT NULL	PolicyGUID
XMLDATA	CLOB(1048576)	NULL	User defined data passed into database

ASBATCH			
Name	Datatype	Null Option	Comment
BATCHGUID	CHARACTER(36)	NOT NULL	Batch GUID
BATCHNUMBER	VARCHAR(50)	NOT NULL	Number assigned to the batch
STATUSCODE	VARCHAR(2)	NOT NULL	Status Code of the batch

ASBATCHACTIVITY			
Name	Datatype	Null Option	Comment
BATCHACTIVITYGUID	CHARACTER(36)	NOT NULL	Batch Activity GUID
BATCHGUID	VARCHAR(36)	NOT NULL	Batch GUID
TRANSACTIONGUID	VARCHAR(36)	NOT NULL	GUID of the transaction run
POLICYGUID	VARCHAR(36)	NOT NULL	Policy GUID of the Policy that is part of the batch
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Effective Date of the transaction
SUSPENSENUMBER	VARCHAR(50)	NULL	Suspense number generated by the activity if applicable

ASBATCHACTIVITYALLOCATION			
Name	Datatype	Null Option	Comment
ALLOCATIONGUID	CHARACTER(36)	NOT NULL	Uniquely identifies Batch Activity Allocation record
GROUPGUID	CHARACTER(36)	NOT NULL	Batch Group GUID
TYPECODE	VARCHAR(2)	NOT NULL	Allocation type code
BATCHACTIVITYGUID	CHARACTER(36)	NOT NULL	Batch Activity GUID
FUNDGUID	CHARACTER(36)	NOT NULL	Fund GUID
ALLOCATIONMETHODCODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeAllocationMethod
ALLOCATIONPERCENT	DECIMAL(18,10)	NULL	Percent Allocated to a fund
ALLOCATIONAMOUNT	DECIMAL(18,2)	NULL	Amount Allocated to a fund
ALLOCATIONUNITS	DECIMAL(18,10)	NULL	Units Allocated to a fund
PERCENTINALLOCATION	DECIMAL(18,10)	NOT NULL	Percent of Allocation , total of all equals 1
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Effective Date of Allocation

ASBATCHACTIVITYFIELD			
Name	Datatype	Null Option	Comment
BATCHACTIVITYGUID	CHARACTER(36)	NOT NULL	Batch Activity GUID
FIELDNAME	VARCHAR(50)	NOT NULL	Field Name of the Batch Activity
FIELDTYPECODE	VARCHAR(2)	NOT NULL	From asCode.CodeValue where CodeName = AsCodeField

ASBATCHACTIVITYFIELD			
Name	Datatype	Null Option	Comment
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(255)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	DECIMAL(20,10)	NULL	Contains value if FieldTypeCode = 04

ASBATCHFIELD			
Name	Datatype	Null Option	Comment
BATCHGUID	CHARACTER(36)	NOT NULL	Batch GUID
FIELDNAME	VARCHAR(50)	NOT NULL	Batch Field Name
FIELDTYPECODE	VARCHAR(2)	NOT NULL	From asCode.CodeValue where CodeName = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(255)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	DECIMAL(20,10)	NULL	Contains value if FieldTypeCode = 04

ASBATCHSCREEN			
Name	Datatype	Null Option	Comment
BATCHSCREENGUID	CHARACTER(36)	NOT NULL	Uniquely identifies BatchScreen record
COMPANYGUID	CHARACTER(36)	NOT NULL	Company GUID
TYPECODE	VARCHAR(2)	NOT NULL	Type Code
SCREENNAME	VARCHAR(50)	NOT NULL	Name of the Batch Screen
RELATEDGUID	CHARACTER(36)	NULL	Related GUID
XMLDATA	CLOB(1048576)	NOT NULL	XML Data of Batch Screen Rule

ASBATCHOPTIONTEXT			
Name	Datatype	Null Option	Comment
BATCHGUID	CHARACTER(36)	NOT NULL	
FIELDNAME	CARCHAR(50)	NOT NULL	
OPTIONTEXT	VARCHAR(255)	NOT NULL	

ASBENEFITSPLIT			
Name	Datatype	Null Option	Comment
BENEFITSPLITGUID	CHARACTER(36)	NOT NULL	Uniquely identifies BenefitSplit
GROUPGUID	CHARACTER(36)	NULL	Identifies groupings of allocation records and how they are updated
TYPECODE	VARCHAR(2)	NOT NULL	The Status of the Split. 05 = Current, 99 = Past 51 future
RELATEDGUID	CHARACTER(36)	NOT NULL	SegmentGUID
FUNDGUID	CHARACTER(36)	NOT NULL	The fund that is related to the benefit split
BENEFITPERCENT	DECIMAL(18,10)	NULL	Percent of fund being paid, not currently used
BENEFITAMOUNT	DECIMAL(5,0)	NULL	Amount of Payment if a fixed account
BENEFITUNITS	DECIMAL(18,10)	NULL	Number of Units if Variable
ACTIVITYGUID	CHARACTER(36)	NULL	
SHADOWACTIVITYGUID	CHARACTER(36)	NULL	

ASBENEFITSPLITCHANGE			
Name	Datatype	Null Option	Comment
BENEFITSPLITCHANGEGUID	CHARACTER(36)	NOT NULL	Uniquely identifies BenefitSplitChange
BENEFITSPLITGROUPGUID	CHARACTER(36)	NOT NULL	BenefitSplitGroupGUID
FUNDGUID	CHARACTER(36)	NOT NULL	FundGUID
MONEYTYPECODE	VARCHAR(2)	NOT NULL	Money Type Code
BENEFITPERCENT	DECIMAL(9,18)	NULL	
BENEFITAMOUNT	DECIMAL(9,18)	NULL	
BENEFITUNITS	DECIMAL(9,18)	NULL	

ASBUSINESSRULES			
Name	Datatype	Null Option	Comment
BUSINESSRULEGUID	CHARACTER(36)	NOT NULL	Primary Key
COMPANYGUID	CHARACTER(36)	NULL	Links the business rule to a specific company, if desired
PLANGUID	CHARACTER(36)	NULL	Links the business rule to a specific plan, if desired
FUNDGUID	CHARACTER(36)	NULL	Links the business rule to a specific fund, if desired
TRANSACTIONGUID	CHARACTER(36)	NULL	Links the business rule to a specific transaction, if desired
STATECODE	VARCHAR(2)	NULL	From asCode.CodeValue where CodeName = AsCodeState;Links the business rule to a specific state, if desired
CLIENTGUID	CHARACTER(36)	NULL	Links the business rule to a specific client, if desired

ASBUSINESSRULES			
Name	Datatype	Null Option	Comment
POLICYGUID	CHARACTER(36)	NULL	Links the business rule to a specific policy, if desired
SEGMENTGUID	CHARACTER(36)	NULL	Links the business rule to a specific segment, if desired
ACTIVITYGUID	CHARACTER(36)	NULL	Links the business rule to a specific activity, if desired
RULENAME	VARCHAR(50)	NULL	Name of the business rule
TYPECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = AsCodeBusinessRuleType (01-Natural, 02-Table File, 03-Natural File)
LONGNAME	VARCHAR(100)	NULL	Descriptive rule name
KEYWORDS	VARCHAR(255)	NULL	Words or phrases used to help search for rules
COMMENTS	VARCHAR(255)	NULL	Description of the rule
ERRORNUMBER	VARCHAR(10)	NULL	From AsErrorCatalog, the number returned when the rule fails
XMLDATA	CLOB(1048576)	NULL	The body of the rule
XMLSCHEMA	CLOB(1048576)	NULL	Schema for the rule format
CLIENTNUMBER	VARCHAR(50)	NOT NULL	Identifies the client to which the rule applies
VBOTYPECODE	VARCHAR(2)	NULL	

ASCHARTOFACCOUNTS			
Name	Datatype	Null Option	Comment
CHARTOFACCOUNTSGUID	CHARACTER(36)	NOT NULL	Primary key
COMPANYGUID	CHARACTER(36)	NULL	Foreign key into AsCompany
ACCOUNTNUMBER	VARCHAR(50)	NULL	
ACCOUNTDESCRIPTION	CHARACTER(100)	NULL	

ASCHARTOFACCOUNTSCRITERIA			
Name	Datatype	Null Option	Comment
CHARTOFACCOUNTSENTRYGUID	CHARACTER(36)	NOT NULL	Primary key
CRITERIANAME	VARCHAR(50)	NOT NULL	Name of the Criteria
CRITERIAVALUE	VARCHAR(200)	NOT NULL	Value of the Criteria

ASCHARTOFACCOUNTSENTITY			
Name	Datatype	Null Option	Comment
CHARTOFACCOUNTSENTITYGUID	CHARACTER(36)	NOT NULL	Primary key
CHARTOFACCOUNTSGUID	CHARACTER(36)	NOT NULL	Chart of Account Record GUID
CHARTOFACCOUNTWENTITYCODE	VARCHAR(2)	NOT NULL	From asCode.CodeValue where CodeName = AsCOAType
TRANSACTIONNAME	VARCHAR(50)	NOT NULL	Transaction Name

ASCHARTOFACCOUNTSENTRY			
Name	Datatype	Null Option	Comment
CHARTOFACCOUNTSENTRYGUID	CHARACTER(36)	NOT NULL	Primary key
CHARTOFACCOUNTSENTITYGUID	CHARACTER(36)	NOT NULL	Chart of Account entity GUID
DEBITCREDITCODE	VARCHAR(2)	NOT NULL	From asCode.CodeValue where CodeName = AsCOAType
ENTRYDESCRIPTION	VARCHAR(100)	NULL	Entry description
ACCOUNTINGTYPECODE	VARCHAR(2)	NOT NULL	From asCode.CodeValue where CodeName = AsAccountingType
ACCOUNTINGAMOUNTFIELD	VARCHAR(100)	NULL	Accounting Amount
GAINLOSSFLAG	VARCHAR(1)	NOT NULL	0 or 1; 0 False, 1 True
FLIPNEGATIVEFLAG	VARCHAR(1)	NOT NULL	0 or 1; 0 False, 1 True
EFFECTIVEFROMDATE	DATE	NOT NULL	Start Effective Date of COA Entry
EFFECTIVETODATE	DATE	NULL	End date of COA entry
FORWARDACCOUNTSTATUSCODE	VARCHAR(3)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeStatus
REVERSALACCOUNTINGSTATUSCODE	VARCHAR(3)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeStatus
DOREVERSALACCOUNTINGFLAG	VARCHAR(1)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeStatus
ORIGINALDISBURSEMENTSTATUSCODE	VARCHAR(3)	NULL	From AsCode.CodeValue where CodeName = AsCodeStatus
FUNDTYPECODE	VARCHAR(3)	NOT NULL	From asCode.CodeValue where CodeName = AsCodeFundType
ACCOUNTNUMBERFORMAT	VARCHAR(225)	NULL	Format of Account Number

ASCHARTOFACCOUNTSENTRYCRITERIA			
Name	Datatype	Null Option	Comment
CHARTOFACCOUNTSENTRYGUID	CHARACTER(36)	NOT NULL	Chart of Account entry GUID
CRITERIANAME	VARCHAR(50)	NOT NULL	NAME
CRITERIAVALUE	VARCHAR(200)	NULL	VALUE

ASCHARTOFACCOUNTSMONEYTYPE			
Name	Datatype	Null Option	Comment
CHARTOFACCOUNTSENTRYGUID	CHARACTER(36)	NOT NULL	Chart of Account entry GUID
MONEYTYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeMoneyType

ASCHARTOFACCOUNTSRESULT			
Name	Datatype	Null Option	Comment
CHARTOFACCOUNTSENTRYGUID	CHARACTER(36)	NOT NULL	Chart of Account entry GUID
RESULTNAME	VARCHAR(50)	NOT NULL	User defined Value

ASCLIENT			
Name	Datatype	Null Option	Comment
CLIENTGUID	CHARACTER(36)	NOT NULL	Primary key
TYPECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = AsCodeClientType (01-Corporation, 02-Individual)
COMPANYNAME	VARCHAR(50)	NULL	Company name (if corporation)
LASTNAME	VARCHAR(50)	NULL	Last name
FIRSTNAME	VARCHAR(50)	NULL	First name
MIDDLEINITIAL	VARCHAR(50)	NULL	Middle initial
SEX	VARCHAR(1)	NULL	M-Male, F-Female
DATEOFBIRTH	TIMESTAMP	NULL	Date/time of birth of an individual or creation of the corporation
DATEOFDEATH	TIMESTAMP	NULL	Date/time of client's death or end of the corporation
TAXID	VARCHAR(20)	NULL	Federal tax id or social security number
EMAIL	VARCHAR(100)	NULL	Client's email address
XMLDATA	CLOB(1048576)	NULL	User defined data
UPDATEDGMT	TIMESTAMP	NULL	Date/time the record was updated

ASCLIENTACTIVITY			
Name	Datatype	Null Option	Comment
CLIENTGUID	CHARACTER(36)	NOT NULL	Client GUID
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Activity GUID

ASCLIENTACTIVITYGROUP			
Name	Datatype	Null Option	Comment
CLIENTACTIVITYGROUPGUID	CHARACTER(36)	NOT NULL	Primary key
CLIENTGUID	CHARACTER(36)	NOT NULL	Client GUID
POLICYGUID	CHARACTER(36)	NULL	Policy GUID that activity was spawned to
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Activity GUID

ASCLIENTACTIVITYGROUPFIELD			
Name	Datatype	Null Option	Comment
CLIENTACTIVITYGROUPGUID	CHARACTER(36)	NOT NULL	Client Activity Group GUID
FIELDNAME	VARCHAR(50)	NOT NULL	Field names within the Client Activity
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(255)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	DECIMAL(20,10)	NULL	Contains value if FieldTypeCode = 04

ASCLIENTACTIVITYGROUPOPTIONTXT			
Name	Datatype	Null Option	Comment
CLIENTACTIVITYGROUPGUID	CHARACTER(36)	NOT NULL	Client Activity Group GUID
FIELDNAME	VARCHAR(50)	NOT NULL	Field names with ClientActivityGroup

ASCLIENTACTIVITYGROUPOPTIONTXT			
Name	Datatype	Null Option	Comment
OPTIONTEXT	VARCHAR(255)	NOT NULL	Value

ASCLIENTFIELD			
Name	Datatype	Null Option	Comment
CLIENTGUID	CHARACTER(36)	NOT NULL	Primary Key
FIELDNAME	VARCHAR(50)	NOT NULL	Name of each Client Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASCLIENTGROUP			
Name	Datatype	Null Option	Comment
GROUPGUID	CHARACTER(36)	NOT NULL	Primary Key
CLIENTGUID	CHARACTER(36)	NULL	Foreign key into AsClient
POLICYGUID	CHARACTER(36)	NULL	PolicyGUID of each Policy in Group, one row for each.

ASCLIENTGROUPFIELD			
Name	Datatype	Null Option	Comment
CLIENTGUID	CHARACTER(36)	NOT NULL	Primary Key
FIELDNAME	VARCHAR(50)	NOT NULL	Name of each Activy Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(225)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	FLOATVALUE (DECIMAL(20,10))	NULL	Contains value if FieldTypeCode = 04

ASCLIENTLANGUAGE			
Name	Datatype	Null Option	Comment
CLIENTGUID	CHARACTER(36)	NOT NULL	From AsClient
TYPECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = AsCodeLanguageType

ASCODE			
Name	Datatype	Null Option	Comment
CODENAME	VARCHAR(24)	NOT NULL	Name of Code
CODEVALUE	VARCHAR(10)	NULL	Value of Code
SHORTDESCRIPTION	VARCHAR(50)	NULL	Short Description
LONGDESCRIPTION	VARCHAR(100)	NULL	Long Description

ASCOMMENTS			
Name	Datatype	Null Option	Comment
COMMENTGUID	CHARACTER(36)	NOT NULL	
RELATEDGUID	CHARACTER(36)	NULL	Relates the comment to a specific record in another table where that table conatins a PK named xxxGUID
COMMENTDATETIME	TIMESTAMP	NOT NULL	Date/Time the comment was entered
MODIFIEDDATETIME	TIMESTAMP	NULL	Time the comment was modified
CLIENTNUMBER	VARCHAR(50)	NOT NULL	Identifies the client entering the comment
MODIFIEDBY	VARCHAR(50)	NULL	Modified by
HIDDEN	VARCHAR(1)	NOT NULL	If the comment is hidden or not
COMMENTS	CLOB(1048576)	NOT NULL	Freeform text

ASCOMMENTSFIELD			
Name	Datatype	Null Option	Comment
COMMENTGUID	CHARACTER(36)	NOT NULL	
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(225)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	FLOATVALUE	NULL	Contains value if FieldTypeCode = 04

ASCOMMENTSFIELD			
Name	Datatype	Null Option	Comment
	(DECIMAL(20,10))		

ASCOMMENTSOPTIONTEXT			
Name	Datatype	Null Option	Comment
COMMENTSGUID	CHARACTER(36)	NOT NULL	
FIELDNAME	VARCHAR(50)	NOT NULL	Field Name
OPTIONTEXT	VARCHAR(255)	NULL	Option Text value

ASCOMPANY			
Name	Datatype	Null Option	Comment
COMPANYGUID	CHARACTER(36)	NOT NULL	Primary key
COMPANYNAME	VARCHAR(50)	NULL	Name of the company
EFFECTIVEDATE	TIMESTAMP	NULL	Date after which the company is valid
CLIENTGUID	CHARACTER(36)	NULL	Link to AsClient

ASCURRENCY			
Name	Datatype	Null Option	Comment
CURRENCYGUID	CHARACTER(36)	NOT NULL	Primary key
COUNTRY	VARCHAR(50)	NOT NULL	Country that issues the currency
LONGNAME	VARCHAR(50)	NOT NULL	Name of currency
SHORTNAME	VARCHAR(3)	NOT NULL	Abbreviation of currency
SIGN	VARCHAR(10)	NULL	Currency symbol, ie- \$, £, ¥
SUBUNITS	INTEGER	NULL	Number of units that make up one standard unit of currency (ex) 100 ---cents per US Dollar
SUBUNITNAME	VARCHAR(50)	NULL	Name of sub-currency (ex) cents in US
STATUSCODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = 'AsCodeStatus'

ASCYCLE			
Name	Datatype	Null Option	Comment
CYCLEGUID	CHARACTER(36)	NOT NULL	Primary key
CYCLEDATE	TIMESTAMP	NOT NULL	Current system date
MACHINENAME	VARCHAR(50)	NULL	Windows NT name of the machine running the activity
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeCycleType 01:Company Level activities (<= 1000) 02:Plan Level activities (<= 1000) 03:Policy Level activities 04:Plan Level activities (> 1000) 05:Company Level activities (> 1000) 06:Plan level activity that ran and its detailed status
PLANGUID	CHARACTER(36)	NULL	Link to AsPlan
POLICYGUID	CHARACTER(36)	NULL	Link to AsPolicy
ACTIVITYGUID	CHARACTER(36)	NULL	Link to AsActivity
CYCLESTATUSCODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeCycleStatus 01:Success 02:Pending 03:Business Error 04:System Error 05:Executing
XMLDATA	CLOB(1048576)	NULL	Holds stack dumps from errored activities
CYCLEGMT	TIMESTAMP	NOT NULL	Date/Time Cycle was executed
CLIENTGUID	CHARACTER(36)	NULL	ClientGUID
THREAD	INTEGER	NULL	

ASCYCLESTATUS			
Name	Datatype	Null Option	Comment
CYCLEGUID	CHARACTER(36)	NOT NULL	Link to AsCycle
POLICYGUID	CHARACTER(36)	NOT NULL	Link to AsPolicy
STARTTIME	TIMESTAMP	NULL	Start time of the cycle
ENDTIME	TIMESTAMP	NULL	End time of the cycle
TRANSACTIONCOUNT	INTEGER	NOT NULL	Number of transactions processed

ASDATADictionary			
Name	Datatype	Null Option	Comment
DATADictionaryGUID	CHARACTER(36)	NOT NULL	Primary Key
TERM	VARCHAR(50)	NOT NULL	Name of the variable
TYPECODE	VARCHAR(50)	NOT NULL	Term Type Code
DESCRIPTION	VARCHAR(4000)	NOT NULL	Description of the Term
XMLDATA	CLOB(1048576)	NULL	

ASDATADictionaryCATEGORY			
Name	Datatype	Null Option	Comment
DATADictionaryCATEGORYGUID	CHARACTER(36)	NOT NULL	Primary Key
DATADictionaryCATEGORYNAMEGUID	CHARACTER(36)	NOT NULL	Data Dictionary Category Name GUID
DATADictionaryGUID	CHARACTER(36)	NOT NULL	Data Dictionary GUID

ASDATADictionaryCATEGORYNAME			
Name	Datatype	Null Option	Comment
DATADictionaryCATEGORYNAMEGUID	CHARACTER(36)	NOT NULL	Primary Key
CATEGORYNAME	VARCHAR(50)	NOT NULL	Category Name
CATEGORYDESCRIPTION	VARCHAR(4000)	NOT NULL	Category Description



ASDATADictionaryDEPENDENCY			
Name	Datatype	Null Option	Comment
DATADictionaryDEPENDENCYGUID	CHARACTER(36)	NOT NULL	Primary Key
DATADictionaryGUID	CHARACTER(36)	NOT NULL	Data Dictionary GUID
BUSINESSRULEGUID	CHARACTER(36)	NULL	Business Rule GUID
TRANSACTIONGUID	CHARACTER(36)	NULL	Transaction GUID
SEGMENTNAMEGUID	CHARACTER(36)	NULL	SegmentName GUID
STOREDPROCEDURENAME	VARCHAR(50)	NULL	Stored Procedure Name
EXTERNALTYPECODE	VARCHAR(2)	NULL	External TypeCode
EXTERNALREFERENCENAME	VARCHAR(50)	NULL	External Reference Name

ASDETAILSUSPENSE			
Name	Datatype	Null Option	Comment
FIELDNAME	VARCHAR(50)	NOT NULL	Link to AsSuspense
SUSPENSEGUID	CHARACTER(36)	NOT NULL	Name of each Suspense field
FIELDVALUE	VARCHAR(100)	NOT NULL	Value of the Suspense field

ASDISBURSEMENT			
Name	Datatype	Null Option	Comment
DISBURSEMENTGUID	CHARACTER(36)	NOT NULL	Primary key
POLICYGUID	CHARACTER(36)	NULL	Link to AsPolicy
ROLEGUID	CHARACTER(36)	NULL	Link to AsRole (payee)
ACTIVITYGUID	CHARACTER(36)	NULL	Link to AsActivity
DISBURSEMENTNUMBER	VARCHAR(20)	NOT NULL	Identifies this disbursement
DISBURSEMENTDATE	TIMESTAMP	NULL	Date of the disbursement activity
DISBURSEMENTTYPECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = AsCodeDisbursementType 1:Check 2:EFT 3:MLAAccount 4:No Funds Received 5:Manual 6:Wire 7:Refund-Suspense 8:Refund -Internal 9:Suspended 10:AlterWithholding 11:Manual-Check 12:Manual-EFT 13:Manual-Wire 14:Due and Unpaid
DISBURSEMENTSTATUSCODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeStatus 01:Active 02:Pending 03:Inactive 04:Cancelled 05:Grace 06:Suspended 07:Surrendered 08:Pending 09:Pending 10:Death 11:Death - Annuitized 12:Shadow 13:NUV Pending 14:Gain/Loss Pending 15:Open 16:Closed 17:Lapsed 18:Transfer Pending 19:Issued 20:Disability Waiver 21:FreeLooked 22:Not Taken 23:Error(Cancel) 24:Default Segment



ASDISBURSEMENT			
Name	Datatype	Null Option	Comment
			27:Recovered 28:Recover Pending 30:Death Claim Pending 31:Death Claim Pending - Annuitized 32:Reviewed 33:Claim Pending 34:Pending Shadow 35:Partially Funded 36:Right To Return Period 37:RestrictedFinancial 38:Ready To Annuitize 39:Annuitized 40:Death - Notified 41:Death Notified - Annuitized 43:Unconfirmed 44:Recovered Suspense 45:RestrictedCOO 47:Due And Unpaid 48:Permanent 49:Active - FreeLook Period 52:History 56:Restricted
DISBURSEMENTAMOUNT	DECIMAL(19,4)	NOT NULL	Amount of the disbursement
TAXABLEAMOUNT	DECIMAL(19,4)	NULL	Amount taxable (for withholding)
XMLDATA	CLOB(1048576)	NULL	User defined data

ASDISBURSEMENTAPPROVAL			
Name	Datatype	Null Option	Comment
DISBURSEMENTAPPROVAL GUID	CHARACTER(36)	NOT NULL	Primary Key
DISBURSEMENTGUID	CHARACTER(36)	NOT NULL	Disbursement GUID
STATUSCODE	VARCHAR(2)	NOT NULL	From AsCode where CodeName='AsCodeStatus'
DISBURSEMENTDISAPPRO VALCODE3	VARCHAR(2)	NULL	From AsCode where CodeName='AsCodeStatus'
APPROVALDATE	TIMESTAMP	NULL	Date Approved
CLIENTNUMBER	VARCHAR(50)	NOT NULL	Client Number
XMLDATA	CLOB(1048576)	NULL	XML Data

ASDISBURSEMENTFIELD			
Name	Datatype	Null Option	Comment
DISBURSEMENTAPPROVAL GUID	CHARACTER(36)	NOT NULL	Disbursement Approval GUID
FIELDNAME	VARCHAR(50)	NOT NULL	Name of each Disbursement Approval Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(255)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	DECIMAL(20,10)	NULL	Contains value if FieldTypeCode = 04

ASDOCUMENT			
Name	Datatype	Null Option	Comment
DOCUMENTGUID	CHARACTER(36)	NOT NULL	Primary Key
POLICYGUID	CHARACTER(36)	NULL	Foreign key into AsPolicy
POLICYNUMBER	VARCHAR(20)	NULL	Identifies the policy to which the document applies
CLIENTGUID	CHARACTER(36)	NULL	Foreign key into AsClient
CLIENTTAXID	VARCHAR(20)	NULL	Social Security Number
COMPANYGUID	CHARACTER(36)	NULL	Foreign key into AsCompany
PLANGUID	CHARACTER(36)	NULL	Foreign key into AsPlan
FUNDGUID	CHARACTER(36)	NULL	Foreign key into AsFund
DOCUMENTNAME	VARCHAR(255)	NOT NULL	Name of the document
FROMDATE	TIMESTAMP	NULL	First date the document covers
TODATE	TIMESTAMP	NULL	Last date the document covers
STATUSCODE	VARCHAR(50)	NOT NULL	From asCode.CodeValue where CodeName = 'AsCodeStatus'
CLIENTNUMBER	VARCHAR(50)	NULL	Identifies the client to which the document pertains

ASDOCUMENT			
Name	Datatype	Null Option	Comment
DATEPRINTED	TIMESTAMP	NULL	Date the document was printed
ACTIVITYGUID	CHARACTER(36)	NULL	Foreign key into AsActivity
SPAWNEDBYGUID	CHARACTER(36)	NULL	Identifies the transaction that created this document
MODECODE	VARCHAR(10)	NULL	From asCode.CodeValue where CodeName = AsCodeMode; defines the frequency with which the document should be printed
TYPECODE	VARCHAR(10)	NULL	From asCode.CodeValue where CodeName = 'AsCodeUploadType'
PRINTSTATUSCODE	VARCHAR(2)	NULL	From AsCode.CodeValue where Codename = AsCodePrintStatus (01-Printed, 02-Pending, 03-Suspended)
XMLDATA	CLOB(1048576)	NULL	User defined data

ASENGINEMATH			
Name	Datatype	Null Option	Comment
CALCULATIONGUID	CHARACTER(36)	NOT NULL	Primary key
CALCULATIONDATETIME	TIMESTAMP	NOT NULL	Date/time of the activity
CLIENTNUMBER	VARCHAR(20)	NOT NULL	Person executing the activity
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Link to AsActivity
XMLDATA	CLOB(1048576)	NULL	Math section, with values, of the activity

ASENGINESEGMENT			
Name	Datatype	Null Option	Comment
CALCULATIONGUID	CHARACTER(36)	NOT NULL	Primary key
CALCULATIONDATETIME	TIMESTAMP	NOT NULL	Date/time of the calculation
CALCULATIONSTATUSCODE	VARCHAR(2)	NOT NULL	Result code
CALCULATIONSTATUSMESSAGE	VARCHAR(100)	NULL	Result message
CLIENTNUMBER	VARCHAR(50)	NOT NULL	User ID
POLICYGUID	CHARACTER(36)	NOT NULL	Link to AsPolicy
SEGMENTGUID	CHARACTER(36)	NOT NULL	Link to AsSegment
XMLDATA	CLOB(1048576)	NULL	User defined data

ASERRORCATALOG			
Name	Datatype	Null Option	Comment
ERRORNUMBER	VARCHAR(10)	NOT NULL	Primary key
ERRORMESSAGE	VARCHAR(255)	NULL	Error text
ERRORFIXTIP	VARCHAR(255)	NULL	How to recover

ASEXCHANGE			
Name	Datatype	Null Option	Comment
BASECURRENCYGUID	CHARACTER(36)	NOT NULL	"From" currency
INTOCURRENCYGUID	CHARACTER(36)	NOT NULL	"To" currency
EXCHANGEVALUE	DECIMAL(5,0)	NOT NULL	Value
UPDATEDGMT	TIMESTAMP	NOT NULL	Last update

ASFILE			
Name	Datatype	Null Option	Comment
FILEGUID	CHARACTER(36)	NOT NULL	FILEGUID
COMPANYGUID	CHARACTER(36)	NULL	COMPANYGUID
FILENAMEFORMAT	DECIMAL(5,0)	NOT NULL	FORMAT OF THE FILE
FILEID	VARCHAR(3)	NULL	FILEID
XSLT	CLOB(1048576)	NULL	XSLT
XMLDATA	CLOB(1048576)	NULL	XMLDATA

ASFILETRACKING			
Name	Datatype	Null Option	Comment
FILETRACKINGGUID	CHARACTER(36)	NOT NULL	FILEGUID
COMPANYGUID	CHARACTER(36)	NULL	COMPANYGUID
FILENAMEFORMAT	DECIMAL(5,0)	NOT NULL	FORMAT OF THE FILE
FILEID	VARCHAR(3)	NULL	FILEID
XSLT	CLOB(1048576)	NULL	XSLT
XMLDATA	CLOB(1048576)	NULL	XMLDATA

ASFILETRACKINGEVENT			
Name	Datatype	Null Option	Comment
FILEGUID	CHARACTER(36)	NOT NULL	FILEGUID

ASFILETRACKINGEVENT			
Name	Datatype	Null Option	Comment
FILETRACKINGGUID	CHARACTER(36)	NOT NULL	FileTrackingGUID
EVENTGMT	TIMESTAMP	NOT NULL	Event GMT
EVENTTYPECODE	VARCHAR(3)	NULL	Type Code
EVENTDATA	CLOB(1048576)	NULL	Data

ASFILTER			
Name	Datatype	Null Option	Comment
FILTERGUID	CHARACTER(36)	NOT NULL	Primary key
RELATEDGUID	CHARACTER(36)	NOT NULL	If Company Level Filter then RelatedGUID = AsCompany.CompanyGUID  If Plan Level Filter then RelatedGUID = AsPlan.PlanGUID  If User Level Filter then RelatedGUID = AsClient.ClientGUID  If SecurityRole Level Filter then RelatedGUID = AsSecurityRole.SecurityRoleGUID
FILTERNAME	VARCHAR(50)	NOT NULL	Name of the filter
TYPECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = AsCodeFilterType 01:Plan Level Filter 02:Company Level Filter 03:Security Role Level Filter 04:User Level Filter 05:Plan Level Filter 06:Company Level Filter 07:Security Role Level Filter 08:User Level Filter
XMLDATA	CLOB(1048576)	NULL	Contents of the filter

ASFUND			
Name	Datatype	Null Option	Comment
FUNDGUID	CHARACTER(36)	NOT NULL	Primary Key
PLANGUID	CHARACTER(36)	NOT NULL	Link to AsPlan
FUNDNAME	VARCHAR(100)	NOT NULL	Fund name
STATUSCODE	VARCHAR(2)	NOT NULL	01-Active, 02-Inactive
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeFundType 01:Fixed Fund 02:Variable Fund 03:ABL Fund 04:Unbundled Variable 05:Loan Fund 06:MVA Fund 07:DCA+ Fund
XMLDATA	CLOB(1048576)	NULL	Fund short name
REMOVALPRECEDENCE	INT	NULL	Removal Precedence
REMOVALMETHODCODE	VARCHAR(2)	NULL	Removal Method Code

ASFUNDCLASS			
Name	Datatype	Null Option	Comment
COMPANYGUID	CHARACTER(36)	NOT NULL	Primary key
FUNDCLASSNAME	VARCHAR(100)	NOT NULL	Foreign key into AsCompany
FUNDCLASSGUID	CHARACTER(36)	NOT NULL	Name of fund class

ASFUNDCLASSALLOCATION			
Name	Datatype	Null Option	Comment
FUNDCLASSALLOCATIONGUID	CHARACTER(36)	NOT NULL	Primary key
GROUPGUID	CHARACTER(36)	NOT NULL	
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeFundType 01:Fixed Fund 02:Variable Fund 03:ABL Fund 04:Unbundled Variable 05:Loan Fund 06:MVA Fund

			07:DCA+ Fund
RELATEDGUID	CHARACTER(36)	NOT NULL	Either PolicyGUID, ActivityGUID or PlanGUID
FUNDCLASSGUID	CHARACTER(36)	NOT NULL	Foreign key into AsFundClass
ALLOCATIONPERCENT	DECIMAL(18,10)	NOT NULL	Percent
EFFECTIVEDATE	TIMESTAMP	NULL	As of date
SORTORDER	INT	NULL	Sort Order

ASFUNDFAMILY			
Name	Datatype	Null Option	Comment
FUNDCLASSGUID	CHARACTER(36)	NOT NULL	Primary key
FUNDGUID	CHARACTER(36)	NOT NULL	Foreign key into AsFundClass
FUNDFAMILYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsFund

ASFUNDFIELD			
Name	Datatype	Null Option	Comment
FIELDNAME	VARCHAR(50)	NOT NULL	Primary Key
FUNDGUID	CHARACTER(36)	NOT NULL	Name of each Fund Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASFUNDGROUP			
Name	Datatype	Null Option	Comment
FUNDGROUPGUID	CHARACTER(36)	NOT NULL	Primary key
PARENTFUNDGUID	CHARACTER(36)	NOT NULL	Link to AsFund for parent fund
CHILDFUNDGUID	CHARACTER(36)	NOT NULL	Link to AsFund for child fund
XMLDATA	VARCHAR(2000)	NULL	User defined data

ASFUNDSTATE			
Name	Datatype	Null Option	Comment
FUNDSTATEGUID	CHARACTER(36)	NOT NULL	Primary key
FUNDGUID	CHARACTER(36)	NOT NULL	Foreign key into AsFund
STATECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where Codename = 'AsCodeState'
EFFECTIVEDATE	TIMESTAMP	NULL	Effective Date
EXPIRATIONDATE	TIMESTAMP	NULL	Date at which it expires

ASFUNDSTATUS			
Name	Datatype	Null Option	Comment
FUNDSTATUSGUID	CHARACTER(36)	NOT NULL	Primary key
FUNDGUID	CHARACTER(36)	NOT NULL	Foreign key into AsFund
STATUSCODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where Codename = 'AsCodeStatus'
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Creation date of the fund
ACTIVEFROMDATE	TIMESTAMP	NULL	Date at which fund was opened
ACTIVETODATE	TIMESTAMP	NULL	Date at which fund was closed

ASFUNDWEIGHT			
Name	Datatype	Null Option	Comment
RELATEDGUID	CHARACTER(36)	NOT NULL	Link to AsFund or AsPolicy
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeFundWeight 01:Weight for a Fund 02:Weight for a Policy
WEIGHT	DECIMAL(18,10)	NOT NULL	

ASHELPSCREEN			
Name	Datatype	Null Option	Comment
HELPSCREENGUID	CHARACTER(36)	NOT NULL	Primary key
PAGENAME	VARCHAR(50)	NULL	Application page on which help screen is displayed
DIALOGNAME	VARCHAR(50)	NULL	Name on the help screen
SCREENOBJECTNAME	VARCHAR(50)	NULL	On screen object that help screen refers to
TYPECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = 'AsCodeHelpType'
TITLE	VARCHAR(255)	NULL	Title of help screen
DESCRIPTION	VARCHAR(2000)	NULL	Description of what the screen object is

ASHELPSCREEN			
Name	Datatype	Null Option	Comment
IMAGENAME	VARCHAR(50)	NULL	Name of attached image
XMLDATA	VARCHAR(50)	NULL	User defined data
RELATEDGUID	CHARACTER(36)	NULL	CompanyGUID, PlanGUID

ASHIERARCHY			
Name	Datatype	Null Option	Comment
AGENTGUID	CHARACTER(36)	NOT NULL	Unique GUID
HIERARCHYGUID	CHARACTER(36)	NULL	Relates to the Role file linking the policy to the agent
AGENTSEQUENCE	INTEGER	NULL	If multiple agents exist, this would identify the number agents
AGENTNUMBER	VARCHAR(100)	NULL	Number associated with the customer's agent number
XMLDATA	CLOB(1048576)	NULL	Free Form information amount the agent stored on this table

ASHISTORY			
Name	Datatype	Null Option	Comment
HISTORYGUID	CHARACTER(36)	NOT NULL	Primary key
RELATEDGUID	CHARACTER(36)	NOT NULL	Identifies the changed item
HISTORYTYPECODE	VARCHAR(2)	NOT NULL	Type code
EFFECTIVEDATE	TIMESTAMP	NULL	Date of change
CLIENTNUMBER	VARCHAR(50)	NULL	User ID
UPDATEDGMT	TIMESTAMP	NULL	Date and time of update
XMLDATA	CLOB(1048576)	NULL	Value of XML data prior to change

ASHISTORYDETAIL			
Name	Datatype	Null Option	Comment
HISTORYGUID	CHARACTER(36)	NOT NULL	Primary Key
FIELDNAME	VARCHAR(50)	NOT NULL	Field Name
DATATYPECODE	CHARACTER(2)	NOT NULL	Data type code
FROMDATA	VARCHAR(255)	NULL	Old Value
TODATA	VARCHAR(255)	NULL	New Value
TOOPTIONTEXT	VARCHAR(50)	NULL	Option text value to
FROMOPTIONTEXT	VARCHAR(50)	NULL	Option text value from

ASIMPORTLOG			
Name	Datatype	Null Option	Comment
IMPORTREPORTGUID	CHARACTER(36)	NOT NULL	Primary key
RELATEDGUID	CHARACTER(36)	NOT NULL	Link to AsActivity (ActivityGUID)
ERRORNUMBER	VARCHAR(10)	NULL	Generated error number
UPDATEDGMT	TIMESTAMP	NOT NULL	Date/Time of occurrence
XMLDATA	CLOB(1048576)	NULL	User defined data

ASINQUIRYSCREEN			
Name	Datatype	Null Option	Comment
INQUIRYSCREENGUID	CHARACTER(36)	NOT NULL	Primary key
COMPANYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsCompany
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = 'AsCodeInquiryScreenType'
SCREENNAME	VARCHAR(50)	NULL	Name of screen
RELATEDGUID	CHARACTER(36)	NULL	PolicyGUID or ClientGUID depending on screen type
XMLDATA	CLOB(1048576)	NULL	User defined data that controls the display of the Inquiry Screen

ASLINKREQUIREMENT			
Name	Datatype	Null Option	Comment
LINKVALUE	VARCHAR(6)	NOT NULL	Primary key
SHORTDESCRIPTION	VARCHAR(50)	NOT NULL	Description of the requirement
LONGDESCRIPTION	VARCHAR(100)	NOT NULL	Description of the requirement
STARTDATE	TIMESTAMP	NOT NULL	Date requirement was created
ENDDATE	TIMESTAMP	NULL	Date requirement was removed
PLANGUID	CHARACTER(36)	NULL	Link to AsPlan; restricts requirements to certain plans
XMLINDICATOR	SMALLINT	NULL	
XMLDATA	CLOB(1048576)	NULL	User defined data
CATEGORYCODE	VARCHAR(6)	NULL	Category of the Link Requirement

ASLIQUIDITYUNITS			
Name	Datatype	Null Option	Comment
LIQUIDITYUNITSGUID	CHARACTER(36)	NOT NULL	Primary key
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Links to AsActivity
FUNDGUID	CHARACTER(36)	NOT NULL	Links to AsFund
TYPECODE	VARCHAR(2)	NOT NULL	Liquidity Unit Type
MONEYTYPECODE	VARCHAR(2)	NULL	Type of money
AMOUNT	DECIMAL(9,18)	NULL	Amount
UNITS	DECIMAL(9,18)	NOT NULL	Units

ASLISTBILL			
Name	Datatype	Null Option	Comment
LISTBILLGUID	CHARACTER(36)	NOT NULL	Primary key
TRANSACTIONGUID	CHARACTER(36)	NOT NULL	Link to AsTransaction
POLICYGUID	CHARACTER(36)	NOT NULL	Link to AsPolicy
BATCHNUMBER	VARCHAR(50)	NOT NULL	System generated number for a group of transactions processed simultaneously
EFFECTIVEDATE	TIMESTAMP	NULL	Date of the activity
XMLDATA	CLOB(1048576)	NULL	User defined data
STATUSCODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeStatus

ASLISTBILLALLOCATION			
Name	Datatype	Null Option	Comment
ALLOCATIONGUID	CHARACTER(36)	NOT NULL	Link to AsAllocation
GROUPGUID	CHARACTER(36)	NULL	ListBill Group GUID
TYPECODE	VARCHAR(2)	NOT NULL	ListBill TypeCode
LISTBILLGUID	CHARACTER(36)	NULL	Link to AsListBill
FUNDGUID	CHARACTER(36)	NOT NULL	Link to AsFund
ALLOCATIONMETHODCODE	VARCHAR(2)	NULL	Method of Allocation
ALLOCATIONPERCENT	DECIMAL(18,10)	NOT NULL	Percent
ALLOCATIONAMOUNT	DECIMAL(19,4)	NULL	Amount
ALLOCATIONUNITS	DECIMAL(18,10)	NULL	Number of units
PERCENTINALLOCATION	DECIMAL(18,10)	NOT NULL	Percent of the Allocation
EFFECTIVEDATE	TIMESTAMP	NULL	Effective date of the allocation

ASLISTBILLFIELD			
Name	Datatype	Null Option	Comment
LISTBILLGUID	CHARACTER(36)	NOT NULL	Primary key
FIELDNAME	VARCHAR(50)	NOT NULL	FieldName
FIELDTYPECODE	CHARACTER(2)	NOT NULL	FieldTypeCode
DATEVALUE	TIMESTAMP	NULL	Date
TEXTVALUE	VARCHAR(7900)	NULL	Text
INTVALUE	INTEGER	NULL	Int
FLOATVALUE	DECIMAL(20,10)	NULL	Float Value

ASLOOKUPREQUIREMENT			
Name	Datatype	Null Option	Comment
RATEDESCRIPTION	VARCHAR(25)	NOT NULL	User defined category
DATECRITERIA	TIMESTAMP	NULL	Date criteria
CRITERIA1	VARCHAR(10)	NULL	User defined criteria
CRITERIA2	VARCHAR(10)	NULL	User defined criteria
CRITERIA3	VARCHAR(10)	NULL	User defined criteria
CRITERIA4	VARCHAR(10)	NULL	User defined criteria
CRITERIA5	VARCHAR(10)	NULL	User defined criteria
CRITERIA6	VARCHAR(10)	NULL	User defined criteria
CRITERIA7	VARCHAR(10)	NULL	User defined criteria
CRITERIA8	VARCHAR(10)	NULL	User defined criteria
CRITERIA9	VARCHAR(10)	NULL	User defined criteria
CRITERIA10	VARCHAR(10)	NULL	User defined criteria
CRITERIA11	VARCHAR(10)	NULL	User defined criteria
CRITERIA12	VARCHAR(10)	NULL	User defined criteria
CRITERIA13	VARCHAR(10)	NULL	User defined criteria
CRITERIA14	VARCHAR(10)	NULL	User defined criteria
CRITERIA15	VARCHAR(10)	NULL	User defined criteria



ASLOOKUPREQUIREMENT			
Name	Datatype	Null Option	Comment
CRITERIA16	VARCHAR(10)	NULL	User defined criteria
CRITERIA17	VARCHAR(10)	NULL	User defined criteria
CRITERIA18	VARCHAR(10)	NULL	User defined criteria
CRITERIA19	VARCHAR(10)	NULL	User defined criteria
CRITERIA20	VARCHAR(10)	NULL	User defined criteria
CRITERIA21	VARCHAR(10)	NULL	User defined criteria
CRITERIA22	VARCHAR(10)	NULL	User defined criteria
CRITERIA23	VARCHAR(10)	NULL	User defined criteria
CRITERIA24	VARCHAR(10)	NULL	User defined criteria
CRITERIA25	VARCHAR(10)	NULL	User defined criteria
CRITERIA26	VARCHAR(10)	NULL	User defined criteria
CRITERIA27	VARCHAR(10)	NULL	User defined criteria
CRITERIA28	VARCHAR(10)	NULL	User defined criteria
CRITERIA29	VARCHAR(10)	NULL	User defined criteria
CRITERIA30	VARCHAR(10)	NULL	User defined criteria
CRITERIA31	VARCHAR(10)	NULL	User defined criteria
CRITERIA32	VARCHAR(10)	NULL	User defined criteria
CRITERIA33	VARCHAR(10)	NULL	User defined criteria
CRITERIA34	VARCHAR(10)	NULL	User defined criteria
CRITERIA35	VARCHAR(10)	NULL	User defined criteria
CRITERIA36	VARCHAR(10)	NULL	User defined criteria
CRITERIA37	VARCHAR(10)	NULL	User defined criteria
CRITERIA38	VARCHAR(10)	NULL	User defined criteria
CRITERIA39	VARCHAR(10)	NULL	User defined criteria
CRITERIA40	VARCHAR(10)	NULL	User defined criteria
CRITERIA41	VARCHAR(10)	NULL	User defined criteria
CRITERIA42	VARCHAR(10)	NULL	User defined criteria
CRITERIA43	VARCHAR(10)	NULL	User defined criteria
CRITERIA44	VARCHAR(10)	NULL	User defined criteria
CRITERIA45	VARCHAR(10)	NULL	User defined criteria
CRITERIA46	VARCHAR(10)	NULL	User defined criteria
CRITERIA47	VARCHAR(10)	NULL	User defined criteria
CRITERIA48	VARCHAR(10)	NULL	User defined criteria
CRITERIA49	VARCHAR(10)	NULL	User defined criteria
CRITERIA50	VARCHAR(10)	NULL	User defined criteria
RESULT	VARCHAR(10)	NULL	Key into AsLinkRequirement
XMLDATA	CLOB(1048576)	NULL	Used to automatically generate system generated requirements with dates and to spawn transactions based on requirements

ASMAPCRITERIA			
Name	Datatype	Null Option	Comment
MAPVALUEGUID	CHARACTER(36)		Primary Key
MAPCRITERIANAME	VARCHAR(255)	NOT NULL	Map Name
MAPCRITERIATYPECODE	CHARACTER(3)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeMapCriteriaType
DATEVALUE	TIMESTAMP	NULL	Date Value
TEXTVALUE	VARCHAR(255)	NULL	Text Value
INTVALUE	INTEGER	NULL	Integer Value
FLOATVALUE	DECIMAL(20,10)	NULL	Float Value

ASMAPGROUP			
Name	Datatype	Null Option	Comment
MAPGROUPGUID	CHARACTER(36)	NOT NULL	Map Group GUID
MAPGROUPDESCRIPTION	VARCHAR(255)	NOT NULL	Description

ASMAPNAME			
Name	Datatype	Null Option	Comment
MAPNAME	VARCHAR(255)	NOT NULL	Name of stored data
MAPCODE	VARCHAR(255)	NOT NULL	Consists of a code value from AsCode or other defining characteristic
MAPVALUE	VARCHAR(255)	NOT NULL	Map Value
XMLDATA	CLOB(1048576)	NULL	XML Data

ASMAPVALUE			
Name	Datatype	Null Option	Comment
MAPVALUEGUID	CHARACTER(36)	NOT NULL	Map Value GUID
MAPGROUPGUID	CHARACTER(36)	NOT NULL	Map Group GUID
MAPVALUETYPECODE	CHARACTER(3)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeMapValueType
DATEVALUE	TIMESTAMP	NULL	Date Value
TEXTVALUE	VARCHAR(255)	NULL	Text Value
INTVALUE	INTEGER	NULL	Integer Value
FLOATVALUE	DECIMAL(20,10)	NULL	Float Value

ASMATHDEBUG			
Name	Datatype	Null Option	Comment
DEBUGGUID	CHARACTER(36)	NOT NULL	Primary key
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Link to AsActivity
CLIENTNUMBER	VARCHAR(50),	NULL	ClientNumber processed activity
SOURCECODE	CLOB(1048576),	NULL	Source
EXECUTIONGMT	TIMESTAMP,	NULL	Time of activity Execution
EXCEPTION	CLOB(1048576)	NULL	Exception

ASMATHDEBUGEVENT			
Name	Datatype	Null Option	Comment
DEBUGGUID	CHARACTER(36)	NOT NULL	Links to AsMathDebug
SOURCEGUID	CHARACTER(36),	NULL	SourceGUID
SEQUENCENUMBER	INTEGER	NOT NULL	sequence number
VARIABLEID	INTEGER,	NULL	variable
XMLDATA	CLOB(1048576)	NULL	XMLDATA

ASMIGRATION			
Name	Datatype	Null Option	Comment
MIGRATIONGUID	CHARACTER(36)	NOT NULL	Primary Key
VERSIONGUID	CHARACTER(36),	NULL	VersionGuid to Migrate
TYPECODE	CHARACTER(2),	NULL	TypeCode
CLIENTNUMBER	VARCHAR(50),	NULL	ClientNumber
ENTRYGMT	TIMESTAMP	NULL	Entry Date

ASMIGRATIONFIELD			
Name	Datatype	Null Option	Comment
MIGRATIONGUID	CHARACTER(36)	NOT NULL	Links to AsMigration
FIELDNAME	VARCHAR(50)	NOT NULL	FieldNmae
FIELDTYPECODE	CHARACTER(2)	NOT NULL	Field Type Code
DATEVALUE	TIMESTAMP,	NULL	Date
TEXTVALUE	VARCHAR(255),	NULL	Text
INTVALUE	INTEGER,	NULL	Int
FLOATVALUE	DECIMAL(20,10)	NULL	Float

ASNETASSETVALUE			
Name	Datatype	Null Option	Comment
NETASSETVALUEGUID	CHARACTER(36)	NOT NULL	Primary key
FUNDGUID	CHARACTER(36)	NOT NULL	Link to AsFund
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Date the asset value is effective
NETASSETVALUE	DECIMAL(19,4)	NULL	Dollar amount of the asset value
UNITVALUE	DECIMAL(18,10)	NULL	Dollar amount of a unit of the asset
DIVIDEND	DECIMAL(18,10)	NULL	Dividend amount
MORTALITYANDEXPENSE	DECIMAL(18,10)	NULL	The M&E for the asset on the effective date

ASOPTIONTEXT			
Name	Datatype	Null Option	Comment
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsActivity
FIELDNAME	VARCHAR(50)	NOT NULL	Field name from AsActivityField
OPTIONTEXT	VARCHAR(255)	NULL	Text Value of field from AsActivityField

ASPLAN			
Name	Datatype	Null Option	Comment
PLANGUID	CHARACTER(36)	NOT NULL	Primary key



ASPLAN			
Name	Datatype	Null Option	Comment
COMPANYGUID	CHARACTER(36)	NULL	Link to Ascompany
PLANNAME	VARCHAR(50)	NULL	Plan name
EFFECTIVEDATE	TIMESTAMP	NULL	Date the plan is active
EXPIRATIONDATE	TIMESTAMP	NULL	Date the plan expires

ASPLANFIELD			
Name	Datatype	Null Option	Comment
PLANGUID	CHARACTER(36)	NOT NULL	Plan GUID
FIELDNAME	VARCHAR(50)	NOT NULL	Name of each Plan Field
FIELDTYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(255)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	DECIMAL(20,10)	NULL	Contains value if FieldTypeCode = 04

ASPLANGROUP			
Name	Datatype	Null Option	Comment
PARENTPLANGUID	CHARACTER(36)	NOT NULL	Parent Plan GUID
CHILDPLANGUID	CHARACTER(36)	NOT NULL	Child Plan GUID

ASPOLICY			
Name	Datatype	Null Option	Comment
POLICYGUID	CHARACTER(36)	NOT NULL	Primary Key
POLICYNUMBER	VARCHAR(20)	NULL	Identifies the policy in a user-friendly format
POLICYNAME	VARCHAR(50)	NULL	User defined value for identifying a policy
CREATIONDATE	TIMESTAMP	NULL	Date the policy was created
ISSUESTATECODE	VARCHAR(2)	NULL	Value is from AsCode where CodeValue = value and CodeName = 'AsCodeState'
PLANDATE	TIMESTAMP	NULL	Effective date for the policy
STATUSCODE	VARCHAR(2)	NULL	From asCode.CodeValue where CodeName = AsCodeStatus
COMPANYGUID	CHARACTER(36)	NULL	Identifies the company issuing the policy
PLANGUID	CHARACTER(36)	NULL	Identifies the plan
XMLDATA	CLOB(1048576)	NULL	User defined policy data
UPDATEDGMT	TIMESTAMP	NULL	Date/time the policy record was updated

ASPOLICYFIELD			
Name	Datatype	Null Option	Comment
FIELDNAME	VARCHAR(50)	NOT NULL	Primary Key
POLICYGUID	CHARACTER(36)	NOT NULL	Name of each Policy Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From asCode.CodeValue where CodeName = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASPOSTALID			
Name	Datatype	Null Option	Comment
POSTALID	VARCHAR(30)	NULL	Postal code (zip code in the US)
CITY	VARCHAR(50)	NULL	City name
STATECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = 'AsCodeState'
COUNTY	VARCHAR(255)	NULL	County name

ASPREMIUM			
Name	Datatype	Null Option	Comment
PREMIUMGUID	CHARACTER(36)	NOT NULL	Primary key
POLICYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsPolicy
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsActivity
REMOVEDFROMPREMIUMGUID	CHARACTER(36)	NULL	If a premium was removed from a policy then that PremiumGUID would be populated here as well
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Date of premium
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue Where CodeName = 'AsCodeTransactionType'
MONEYTYPE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = 'AsCodeMoneyType'
ACTIVEFROMDATE	TIMESTAMP	NOT NULL	Date the premium started

ASPREMIUM			
Name	Datatype	Null Option	Comment
ACTIVETODATE	TIMESTAMP	NULL	Date the premium ended
PREMIUMAMOUNT	DECIMAL(19,4)	NOT NULL	Dollar amount of the premium
XMLDATA	CLOB(1048576)	NULL	

ASPRESETCOMMENTS			
Name	Datatype	Null Option	Comment
PRESETCOMMENTSGUID	CHARACTER(36)	NOT NULL	Primary Key
COMMENTNAME	VARCHAR(36)	NOT NULL	Comment Name
COMPANYGUID	CHARACTER(36),	NULL	Links to AsCompany
PLANGUID	CHARACTER(36),	NULL	Links to AsPlan
COMMENTTEXT	CLOB(1048576)	NULL	Text of the comment.

ASRATE			
Name	Datatype	Null Option	Comment
RATEGUID	CHARACTER(36)	NOT NULL	Unique identifier
RATEGROUPGUID	CHARACTER(36)	NOT NULL	Link into AsRateGroup
RATEDESCRIPTION	VARCHAR(25)	NOT NULL	User defined name that groups all rates used for a specific purpose
DATECRITERIA	TIMESTAMP	NULL	Date the rate becomes active
CRITERIA1	VARCHAR(10)	NULL	User defined criteria
CRITERIA2	VARCHAR(10)	NULL	User defined criteria
CRITERIA3	VARCHAR(10)	NULL	User defined criteria
CRITERIA4	VARCHAR(10)	NULL	User defined criteria
CRITERIA5	VARCHAR(10)	NULL	User defined criteria
CRITERIA6	VARCHAR(10)	NULL	User defined criteria
CRITERIA7	VARCHAR(10)	NULL	User defined criteria
CRITERIA8	VARCHAR(10)	NULL	User defined criteria
CRITERIA9	VARCHAR(10)	NULL	User defined criteria
CRITERIA10	VARCHAR(10)	NULL	User defined criteria
INTEGERCRITERIA	INTEGER	NOT NULL	Order of rates within a given RateDescription
RATE	DECIMAL(18,10)	NOT NULL	The rate being looked up

ASRATECRITERIA			
Name	Datatype	Null Option	Comment
RATECRITERIAGUID	CHARACTER(36)	NOT NULL	Primary key
RATEDESCRIPTORGUID	CHARACTER(36)	NOT NULL	Foreign key into AsRateDescriptor
EXCELCOLUMN	VARCHAR(2)	NULL	Excel column referenced
CRITERIA1CHOICE	VARCHAR(20)	NULL	Criteria chose from the user defined criteria i
CRITERIA2CHOICE	VARCHAR(20)	NULL	User defined criteria
CRITERIA3CHOICE	VARCHAR(20)	NULL	User defined criteria
CRITERIA4CHOICE	VARCHAR(20)	NULL	User defined criteria
CRITERIA5CHOICE	VARCHAR(20)	NULL	User defined criteria
CRITERIA6CHOICE	VARCHAR(20)	NULL	User defined criteria
CRITERIA7CHOICE	VARCHAR(20)	NULL	User defined criteria
CRITERIA8CHOICE	VARCHAR(20)	NULL	User defined criteria
CRITERIA9CHOICE	VARCHAR(20)	NULL	User defined criteria
CRITERIA10CHOICE	VARCHAR(20)	NULL	User defined criteria

ASRATEDESCRIPTOR			
Name	Datatype	Null Option	Comment
RATEDESCRIPTORGUID	CHARACTER(36)	NOT NULL	Primary key
RATEDESCRIPTORNAME	VARCHAR(50)	NULL	Name of rate descriptor
WORKBOOK	VARCHAR(300)	NULL	Excel workbook referred to
RATEGROUPGUID	CHARACTER(36)	NOT NULL	Foreign key into AsRateGroup
WORKSHEET	VARCHAR(50)	NULL	Excel worksheet referred to
TABLETYPE	VARCHAR(20)	NULL	From AsCode.CodeValue Where CodeName = 'AsCodeTableType'
INTEGERCRITERIACOLUMN	VARCHAR(2)	NULL	Defines which column on the excel worksheet will act as the IntegerCriteria
STARTROW	INTEGER	NULL	Row at which the IntegerCriteria starts on the excel worksheet
ENDROW	INTEGER	NULL	Row at which the IntegerCriteria ends on the excel worksheet
SECONDARYINDEX	VARCHAR(30)	NULL	The secondary criteria to reference the table by
SECONDARYINDEXROW	INTEGER	NULL	Row at which the SecondaryIndex is located on the excel worksheet
STARTCOLUMN	VARCHAR(2)	NULL	Column at which the SecondaryIndex starts on the excel worksheet
ENDCOLUMN	VARCHAR(2)	NULL	Column at which the SecondaryIndex start on the excel worksheet

ASRATEDESCRIPTOR			
Name	Datatype	Null Option	Comment
SELECTTYPE	VARCHAR(20)	NULL	From AsCode.CodeValue Where CodeName = 'AsCodeSelectType'
DURATIONATTAINED	INTEGER	NULL	
MAXMINPERIOD	INTEGER	NULL	

ASRATEGROUP			
Name	Datatype	Null Option	Comment
ACTIVEFROMDATE	TIMESTAMP	NOT NULL	Primary key
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Date the rate group was created
RATEGROUPGUID	CHARACTER(36)	NOT NULL	Date the rate group was created
RATEDESCRIPTION	VARCHAR(25)	NOT NULL	Name of the rate group
INTEGERCRITERIA	VARCHAR(20)	NOT NULL	Primary criteria for the rate group that is looked up by way of an integer value
CRITERIA1	VARCHAR(20)	NULL	User defined criteria
CRITERIA2	VARCHAR(20)	NULL	User defined criteria
CRITERIA3	VARCHAR(20)	NULL	User defined criteria
CRITERIA4	VARCHAR(20)	NULL	User defined criteria
CRITERIA5	VARCHAR(20)	NULL	User defined criteria
CRITERIA6	VARCHAR(20)	NULL	User defined criteria
CRITERIA7	VARCHAR(20)	NULL	User defined criteria
CRITERIA8	VARCHAR(20)	NULL	User defined criteria
CRITERIA9	VARCHAR(20)	NULL	User defined criteria
CRITERIA10	VARCHAR(50)	NULL	User defined criteria
STATUSCODE	VARCHAR(20)	NULL	From AsCode.CodeValue Where CodeName = 'AsCodeStatus'
TYPECODE	VARCHAR(20)	NULL	
ACTIVETODATE	TIMESTAMP	NULL	Date the rate group ends
XMLDATA	CLOB(1048576)	NULL	

AsRateUpdate			
Name	Datatype	Null Option	Comment
RateGUID	CHARACTER(36)	NOT NULL	Foreign key into AsRate
RateDescription	VARCHAR(25)	NOT NULL	Name of Rate from AsRate
DateCriteria	TIMESTAMP	NULL	User defined criteria
Criteria1	VARCHAR(10)	NULL	User defined criteria
Criteria2	VARCHAR(10)	NULL	User defined criteria
Criteria3	VARCHAR(10)	NULL	User defined criteria
Criteria4	VARCHAR(10)	NULL	User defined criteria
Criteria5	VARCHAR(10)	NULL	User defined criteria
Criteria6	VARCHAR(10)	NULL	User defined criteria
Criteria7	VARCHAR(10)	NULL	User defined criteria
Criteria8	VARCHAR(10)	NULL	User defined criteria
Criteria9	VARCHAR(10)	NULL	User defined criteria
Criteria10	VARCHAR(10)	NULL	User defined criteria
INTEGERCRITERIA	INT	NOT NULL	
RATE	DECIMAL(9,18)	NOT NULL	

ASREQUIREMENT			
Name	Datatype	Null Option	Comment
RELATEDGUID	CHARACTER(36)	NOT NULL	Links to AsPolicy (PolicyGUID)
REQUIREMENTLINK	VARCHAR(6)	NOT NULL	Key into AsLinkRequirement (form/requirement names)
REQUIREMENTGUID	CHARACTER(36)	NOT NULL	Primary key
GROUPGUID	CHARACTER(36)	NULL	Identifies requirements added as a group
TYPECODE	VARCHAR(2)	NOT NULL	01-System generated, 02-User added
REQUESTEDDATE	TIMESTAMP	NULL	Date/time the requirement was requested
RECEIVEDDATE	TIMESTAMP	NULL	Date/time the requirement was received
WAIVEDDATE	TIMESTAMP	NULL	Date/time the requirement was waived
DUE DATE	TIMESTAMP	NULL	Date/time the requirement is due
UPDATEDGMT	TIMESTAMP	NULL	Date/time the requirement was last saved
CLIENTNUMBER	VARCHAR(50)	NOT NULL	Foreign key into AsSecurity
XMLDATA	CLOB(1048576)	NULL	User defined data

ASROLE			
Name	Datatype	Null Option	Comment
ROLEGUID	CHARACTER(36)	NOT NULL	Primary key
COMPANYGUID	CHARACTER(36)	NULL	Link to AsCompany
POLICYGUID	CHARACTER(36)	NULL	Link to AsPolicy
SEGMENTGUID	CHARACTER(36)	NULL	Link to AsSegment
CLIENTGUID	CHARACTER(36)	NULL	Link to AsClient
HIERARCHYGUID	CHARACTER(36)	NULL	
STATECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = AsCodeState
ROLECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeRole
PERCENTDOLLARCODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = AsCodePercentDollar 01:Percentage Split 02:Dollar Split 03:Dollar/Percentage Split Dollar 04:Dollar/Percentage Split Sweeper 05:Dollar/Percentage Split Percentage
ROLEPERCENT	DECIMAL(9,6)	NULL	Percentage stake of this role relative to other clients in the same role on the same policy
ROLEAMOUNT	DECIMAL(19,4)	NULL	Dollar amount stake of this role relative to other clients in the same role on the same policy
XMLDATA	CLOB(1048576)	NULL	User defined data

ASROLEFIELD			
Name	Datatype	Null Option	Comment
FIELDNAME	VARCHAR(50)	NOT NULL	Primary Key
ROLEGUID	CHARACTER(36)	NOT NULL	Name of each Role Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From asCode.CodeValue where CodeName = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASROLOPTIONTEXT			
Name	Datatype	Null Option	Comment
ROLEGUID	CHARACTER(36)	NOT NULL	Link to AsRole
FIELDNAME	VARCHAR(50)	NOT NULL	Name of the field
OPTIONTEXT	VARCHAR(255)	NULL	Value of the Text

ASROLESEQUENCE			
Name	Datatype	Null Option	Comment
ROLEGUID	CHARACTER(36)	NOT NULL	From AsRole
POLICYGUID	CHARACTER(36)	NOT NULL	Relates this table to a Policy
ROLECODE	VARCHAR(2)	NOT NULL	AsCodeRole, identifies the type of role on the policy
ROLESEQUENCE	VARCHAR(3)	NOT NULL	The order of identical roles added for each policy

ASROLLBACK			
Name	Datatype	Null Option	Comment
ROLLBACKGUID	CHARACTER(36)	NOT NULL	Primary key
FUNDGUID	CHARACTER(36)	NOT NULL	Link to AsFund
CLIENTNUMBER	VARCHAR(50)	NOT NULL	User entering the rollback
PROCESSDATE	TIMESTAMP	NOT NULL	Date the rollback was processed
TARGETDATE	TIMESTAMP	NOT NULL	Date to rollback to
TOTALPOLICIESEFFECTED	INTEGER	NOT NULL	Number of policies affected
TOTALDOLLAREFFECT	DECIMAL(19,4)	NOT NULL	Cumulative cost affect
ESTIMATEDGAINLOSS	DECIMAL(19,4)	NULL	Estimated gain/loss caused by the rollback
XMLDATA	CLOB(1048576)	NULL	User defined data

ASROLLBACKNUV			
Name	Datatype	Null Option	Comment
ROLLBACKNUVGUID	CHARACTER(36)	NOT NULL	Primary key
ROLLBACKGUID	CHARACTER(36)	NOT NULL	Link to AsRollback
EFFECTIVEDATE	TIMESTAMP	NOT NULL	System date
FROMNUV	DECIMAL(18,10)	NOT NULL	Original NUV
TONUV	DECIMAL(18,10)	NOT NULL	New NUV

ASROLLBACKNUV			
Name	Datatype	Null Option	Comment
NETASSETVALUEGUID	CHARACTER(36)	NOT NULL	Link to AsNetAssetValue

ASROLLBACKPOLICY			
Name	Datatype	Null Option	Comment
ROLLBACKPOLICYGUID	CHARACTER(36)	NOT NULL	Primary key
ROLLBACKGUID	CHARACTER(36)	NOT NULL	Link to AsRollback
POLICYGUID	CHARACTER(36)	NOT NULL	Link to AsPolicy
POLICYDOLLAREFFECT	DECIMAL(19,4)	NOT NULL	Dollar amount removed from Policy as a result of rollback
POLICYUNIT EFFECT	DECIMAL(18,0)	NOT NULL	Fund units removed from Policy as a result of rollback
STATUSCODE	VARCHAR(50)	NOT NULL	From AsCode.CodeValue where CodeName = 'AsCodeStatus'
POLICYNUMBER	VARCHAR(20)	NOT NULL	System generated Policy Number

ASROUTINGNUMBER			
Name	Datatype	Null Option	Comment
BANKNAME	VARCHAR(50)	NOT NULL	
ROUTINGNUMBER	VARCHAR(25)	NOT NULL	

ASSCHEDULEDVALUATION			
Name	Datatype	Null Option	Comment
SCHEDULEDVALUATIONGUID	CHARACTER(36)	NOT NULL	Primary key
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsActivity
PLANGUID	CHARACTER(36)	NOT NULL	Foreign key into AsPlan
POLICYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsPolicy
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Date valuation was entered
ACTIVEDATE	TIMESTAMP	NOT NULL	Date valuation occurred
POLICYCASHVALUE	DECIMAL(19,4)	NOT NULL	Cash Value
TYPECODE	CHARACTER(2)	NOT NULL	Type Code
LIQUIDITYVALUE	DECIMAL(19,4)	NULL	Liquidity Value
LIQUIDITYVALUEGROUPA	DECIMAL(19,4)	NULL	Liquidity Value Group A
LIQUIDITYVALUEGROUPB	DECIMAL(19,4)	NULL	Liquidity Value Group B
REDEMPTIONAMOUNT	DECIMAL(19,4)	NULL	Redemption Amount

ASSCHEDULEDVALUATIONCHILD			
Name	Datatype	Null Option	Comment
SCHEDULEDVALUATIONCHILDGUID	CHARACTER(36)	NOT NULL	Primary key
SCHEDULEDVALUEATIONFUNDGUID	CHARACTER(36)	NOT NULL	Links to AsscheduledValuationFund
CHILD FUNDGUID	CHARACTER(36)	NOT NULL	Links to Asfund
FUNDUNITS	DECIMAL(19,10)	NULL	Number of units
FUND CASHVALUE	DECIMAL(19,4)	NOT NULL	Cash value of the fund

ASSCHEDULEDVALUATIONDEPOSIT			
Name	Datatype	Null Option	Comment
SCHEDULEDVALUATIONDEPOSITGUID	CHARACTER(36)	NOT NULL	Primary Key
SCHEDULEDVALUATIONGUID	CHARACTER(36)	NOT NULL	Links to AsScheduled Valuation
FUNDGUID	CHARACTER(36)	NOT NULL	Links to AsFund
DEPOSITVALUATIONGUID	CHARACTER(36)	NOT NULL	
DEPOSITEFFECTIVEDATE	TIMESTAMP	NOT NULL	
DEPOSITRATELOCKDATE	TIMESTAMP		
DEPOSITSEEDGUID	CHARACTER(36)		
DEPOSITMONEYTYPECODE	CHARACTER(2)	NOT NULL	
DEPOSITINITIALUNITS	DECIMAL(19,10)		
DEPOSITINITIALCASHVALUE	DECIMAL(19,4)	NOT NULL	
DEPOSITUNITS	DECIMAL(19,10)		
DEPOSITCASHVALUE	DECIMAL(19,4)	NOT NULL	
DEPOSITSURRENDERVALUE	DECIMAL(19,4)	NOT NULL	
DEPOSITPRINCIPAL	DECIMAL(19,4)	NOT NULL	
DEPOSITGAIN	DECIMAL(19,4) DEFAULT 0,	NOT NULL	
DEPOSITNETGAIN	DECIMAL(19,4) DEFAULT 0,	NOT NULL	

ASSCHEDULEDVALUATIONDEPOSIT			
Name	Datatype	Null Option	Comment
DEPOSITTRANSACTIONNAME	VARCHAR(100),	NULL	
DEPOSITMVAAMOUNT	DECIMAL(19,4),	NULL	
DEPOSITGUARANTEEDAMOUNT	DECIMAL(19,4)	NULL	
DEPOSITINTERESTBONUS	DECIMAL(19,4),	NULL	Deposit Bonus
CURRENTINTERESTRATE	DECIMAL(19,10),	NULL	Current Rate
CURRENTBONUSINTERESTRATE	DECIMAL(19,10)	NULL	Current Bonus Rate

ASSCHEDULEDVALUATIONFIELD			
Name	Datatype	Null Option	Comment
SCHEDULEDVALUATIONGUID	CHARACTER(36)	NOT NULL	Links to AsScheduledValuation
FIELDNAME	VARCHAR(50)	NOT NULL	Name of each ScheduledValuation Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASSCHEDULEDVALUATIONFUND			
Name	Datatype	Null Option	Comment
SCHEDULEDVALUATIONFUNDGUID	CHARACTER(36)	NOT NULL	Primary Key
SCHEDULEDVALUATIONGUID	CHARACTER(36)	NOT NULL	Links to AsScheduled Valuation
FUNDGUID	CHARACTER(36)	NOT NULL	Links to AsFund
FUNDTYPECODE	CHARACTER(2)	NOT NULL	Fund TypeCode
FUNDUNITS	DECIMAL(19,10),	NULL	Fund Units
FUND CASHVALUE	DECIMAL(19,4)	NOT NULL	Fund Cash Value
FUND SURRENDERVALUE	DECIMAL(19,4)	NOT NULL	Fund surrender value
FUNDPRINCIPAL	DECIMAL(19,4)	NOT NULL	Fund Principal
FUNDGAIN	DECIMAL(19,4)	NOT NULL	Fund Gain
FUNDNETGAIN	DECIMAL(19,4)	NOT NULL	Fund Net Gain
FUNDMVAAMOUNT	DECIMAL(19,4),	NULL	Fund MVA Amount
FUNDGUARANTEEDAMOUNT	DECIMAL(19,4)	NULL	Fund Guaranteed Amount
LIQUIDITYUNITSGROUPA	DECIMAL(19,4),	NULL	Liquidity
LIQUIDITYVALUEGROUPA	DECIMAL(19,4),	NULL	Liquidity
LIQUIDITYUNITSGROUPB	DECIMAL(19,4),	NULL	Liquidity
LIQUIDITYVALUEGROUPB	DECIMAL(19,4),	NULL	Liquidity
REDEMPTIONAMOUNT	DECIMAL(19,4),	NULL	Redemption Amount
SHORTTERMREDEMPTIONUNITS	DECIMAL(19,4)	NULL	Short Term Units

ASSEURITY			
Name	Datatype	Null Option	Comment
CLIENTGUID	CHARACTER(36)	NOT NULL	Foreign key into AsClient
CLIENTNUMBER	VARCHAR(50)	NOT NULL	Client logon ID
PERSONALID	VARCHAR(10)	NOT NULL	Client Password
SECURITYROLEGUID	CHARACTER(36)	NOT NULL	Links to AsSecurityRole

ASSEURITYROLE			
Name	Datatype	Null Option	Comment
SECURITYROLEGUID	CHARACTER(36)	NOT NULL	Primary key
COMPANYGUID	CHARACTER(36)	NOT NULL	Link to AsCompany
SECURITYROLENAME	VARCHAR(100)	NOT NULL	Security role name
XMLDATA	CLOB(1048576)	NULL	User defined data

ASSEMENT			
Name	Datatype	Null Option	Comment
SEGMENTGUID	CHARACTER(36)	NOT NULL	Primary key
POLICYGUID	CHARACTER(36)	NULL	Link to AsPolicy
SEGMENTNAMEGUID	CHARACTER(36)	NULL	Link to AsSegmentName
STATUSCODE	VARCHAR(2)	NULL	From AsCode.CodeValue wher CodeName = 'AsCodeStatus'



ASSEGMENT			
Name	Datatype	Null Option	Comment
			01:Active 02:Pending 03:Inactive 04:Cancelled 05:Grace 06:Suspended 07:Surrendered 08:Policy is Pending 09:Pending/Ready/Activities 10:Death 11:Death - Annuitized 12:Shadow 13:Active - NUVs needed to calculate units and gain/loss 14:Active - NUVs needed to calculate gain/loss 15:Open 16:Closed 17:Lapsed 18:Transfer Pending 19:Issued 20:Disability Waiver 21:FreeLooked 22:Not Taken 23:Error(Cancel) 24:Default Segment 27:Disbursement Recover 28:Disbursement Recover Pending 30:Death Claim Pending 31:Death Claim Pending - Annuitized 32:Reviewed 33:Claim Pending 34:Pending Shadow 35:Partially Funded 36:Right To Return Period 37:RestrictedFinancial 38:Ready To Annuitize 39:Annuitized 40:Death - Notified 41:Death Notified - Annuited claims 43:Unconfirmed 44:Recovered Suspense 45:RestrictedCOO 47:Due And Unpaid 48:Permanent 49:Active - FreeLook Period 52:Inactive Activity History 56:Restricted
EFFECTIVEDATE	TIMESTAMP	NULL	Date the record was created
XMLDATA	CLOB(1048576)	NULL	User defined data

ASSEGMENTFIELD			
Name	Datatype	Null Option	Comment
FIELDNAME	VARCHAR(50)	NOT NULL	Primary Key
SEGMENTGUID	CHARACTER(36)	NOT NULL	Name of each Segment Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASSEGMENTNAME			
Name	Datatype	Null Option	Comment
SEGMENTNAMEGUID	CHARACTER(36)	NOT NULL	Primary key
PLANGUID	CHARACTER(36)	NULL	Link to AsPlan
SEGMENTNAME	VARCHAR(100)	NULL	Name of the segment
TYPECODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = AsCodeSegmentType 01:Fixed Amount

ASSEGMENTNAME			
Name	Datatype	Null Option	Comment
			02:Option E - Specified Period Certain 03:Option C - Joint and Survivor Life Annuity 04:Base Coverage 05:DeferredAnnuity 06:Option A - Single Life Annuity 07:Option B - Single Life Annuity w/ Period Certain 08:Option J - Installment Refund Life Annuity 10:Option G - Cash Refund Life Annuity 11:Option D - Joint & Survivor w/ Period Certain 21:Old Base Life Insurance Coverage 22:Childrens Term Rider (CTR) 23:Family Term Rider (FTR) 24:Integrated Term Rider 30:Family Term Flat Extra 31:Base Flat Extra Amount 32:Integrated Term Flat Extra Amount 33:Guaranteed Purchase Rider 34:Accidental Death Benefit (ADB) 35:Disability Benefit Rider (DBR) 41:Conversion to Universal Life Rider 42:Living Benefits Rider 43:Life Plan Options Rider 88:Long Term Care (LTC) 89:Convalescent Care Benefit Rider (CCBR) 90:Extension Of Benefit Rider
XMLDATA	CLOB(1048576)	NULL	
VBOTYPECODE	CHARACTER(2)	NULL	VBO Type Code

ASSEQUENCE			
Name	Datatype	Null Option	Comment
SEQUENCENAME	VARCHAR(100)	NOT NULL	SequenceName partly identifies AsSequence to other functions
SEQUENCEINTEGER	INTEGER	NULL	Number to track
SEQUENCEDATE	TIMESTAMP	NULL	Date e.g. Cycle Date
SEQUENCEDESCRIPTION	VARCHAR(255)	NOT NULL	User defined field
CURRENTINDICATOR	VARCHAR(1)	NULL	Y/N indicator, used in batch
XMLDATA	CLOB(1048576)	NULL	User defined data

ASSTATEAPPROVAL			
Name	Datatype	Null Option	Comment
STATEAPPROVALGUID	CHARACTER(36)	NOT NULL	Primary Key
PLANGUID	CHARACTER(36)	NOT NULL	Link to AsPlan
STATECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where CodeName = 'AsCodeState'

ASSTATEAPPROVALTYPE			
Name	Datatype	Null Option	Comment
STATEAPPROVALGUID	CHARACTER(36)	NOT NULL	Links to AsStateApproval
TYPECODE	CHARACTER(2)	NULL	From AsCode.CodeValue where CodeName = 'AsCodeState'
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Date takes effect
EXPIRATIONDATE	TIMESTAMP	NULL	Date expires

ASSUSPENSE			
Name	Datatype	Null Option	Comment
SUSPENSEGUID	CHARACTER(36)	NOT NULL	Primary key
SUSPENSENUMBER	DECIMAL(18,0)	NOT NULL	Identifies the record
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeCOAType (01-Debit, 02-Credit)
STATUSCODE	VARCHAR(2)	NOT NULL	
AMOUNT	DECIMAL(19,4)	NOT NULL	Dollar amount of the money received
ATTACHEDAMOUNT	DECIMAL(19,4)	NULL	The portion of the amount that has been attached to a contract
COMPANYGUID	CHARACTER(36)	NOT NULL	Link to AsCompany
POLICYNUMBER	VARCHAR(50)	NULL	Identifies the policy to which this suspense applies
EFFECTIVEDATE	TIMESTAMP	NOT NULL	Date the money came in
EFFECTIVEFROMDATE	TIMESTAMP	NOT NULL	Date suspense record was created



ASSUSPENSE			
Name	Datatype	Null Option	Comment
EFFECTIVETODATE	TIMESTAMP	NULL	If activities that this is attached to are shadowed, contains the effective date of the activity
CLIENTNUMBER	VARCHAR(50)	NOT NULL	Link into AsSecurity
FIRSTNAME	VARCHAR(50)	NULL	First name of the payor
LASTNAME	VARCHAR(50)	NULL	Last name of the payor
ACCOUNTNUMBER	VARCHAR(50)	NULL	Account number of the bank
BANKNAME	VARCHAR(50)	NULL	Name of the bank
BANKNUMBER	VARCHAR(50)	NULL	Bank routing number
CHECKNUMBER	VARCHAR(50)	NULL	Check Number
XMLDATA	CLOB(1048576)	NULL	User defined data
BATCHNUMBER	VARCHAR(18)	NULL	Number referencing List Bill transactions

ASSUSPENSEFIELD			
Name	Datatype	Null Option	Comment
FIELDNAME	VARCHAR(50)	NOT NULL	Primary Key
SUSPENSEGUID	CHARACTER(36)	NOT NULL	Name of each Suspense Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASSUSPENSEOPTIONTEXT			
Name	Datatype	Null Option	Comment
SUSPENSEGUID	CHARACTER(36)	NOT NULL	Links to AsSuspense
FIELDNAME	VARCHAR(50)	NOT NULL	FieldName
OPTIONTEXT	VARCHAR(255)	NULL	Option text value

ASSYSTEMDATE			
Name	Datatype	Null Option	Comment
SYSTEMDATEGUID	CHARACTER(36)	NOT NULL	Primary Key
SYSTEMDATE	TIMESTAMP	NOT NULL	
BUSINESSDAYINDICATOR	VARCHAR(1)	NOT NULL	
CURRENTINDICATOR	VARCHAR(1)	NOT NULL	
MONTHENDINDICATOR	VARCHAR(1)	NOT NULL	
QUARTERENDINDICATOR	VARCHAR(1)	NOT NULL	
YEARENDINDICATOR	VARCHAR(1)	NOT NULL	
NEXTSYSTEMDATE	TIMESTAMP	NOT NULL	
PREVIOUSSYSTEMDATE	TIMESTAMP	NOT NULL	

ASSYSTEMDATEFIELD			
Name	Datatype	Null Option	Comment
SYSTEMDATEGUID	CHARACTER(36)	NOT NULL	Links to AsSystemDate
FIELDNAME	VARCHAR(50)	NOT NULL	Field Name
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04

ASTAXLOT			
Name	Datatype	Null Option	Comment
TAXLOTGUID	CHARACTER(36)	NOT NULL	Primary key
EFFECTIVEDATE	TIMESTAMP	NOT NULL	As of date
FUNDGUID	CHARACTER(36)	NOT NULL	Foreign key into AsFund
AMOUNTREQUESTED	DECIMAL(19,4)	NULL	Amount requested
AMOUNTTRADED	DECIMAL(19,4)	NULL	Amount traded
UNTRADEDPRE	DECIMAL(19,4)	NULL	
UNTRADEDPOST	DECIMAL(19,4)	NULL	

ASTRANSACTION			
---------------	--	--	--

Name	Datatype	Null Option	Comment
TRANSACTIONGUID	CHARACTER(36)	NOT NULL	Primary Key
PLANGUID	CHARACTER(36)	NOT NULL	Link to AsPlan
TRANSACTIONNAME	VARCHAR(50)	NOT NULL	Name of the transaction
STATUSCODE	VARCHAR(2)	NOT NULL	01-Active, 02-Inactive
TYPECODE	VARCHAR(2)	NOT NULL	From AsCode.CodeValue where CodeName = AsCodeTransactionType 01:Policy Level Financial Transaction 02:Policy Level Report 03:Policy Level Extract 04:Report (Nightly Cycle) 05:Extract (Nightly Cycle) 06:Policy Level Illustration 07:Plan Level Financial Transaction 08:Plan Level Report 09:Plan Level Data Extract 10:Import (Nightly Cycle) 11:Plan Level Import 12:Plan Level Batch Transaction
XMLDATA	CLOB(1048576)	NULL	Body of the transaction
PROCESSINGORDER	SMALLINT	NOT NULL	Relative order of operation of a transaction

ASTRANSACTIONQUOTE			
Name	Datatype	Null Option	Comment
TRANSACTIONQUOTEGUID	CHARACTER(36)	NOT NULL	Primary key
ACTIVITYGUID	CHARACTER(36)	NULL	Foreign key into AsActivity
TRANSACTIONGUID	CHARACTER(36)	NULL	Foreign key into AsTransaction
POLICYGUID	CHARACTER(36)	NULL	Foreign key into AsPolicy
STATUSCODE	VARCHAR(2)	NULL	From AsCode.CodeValue where CodeName = 'AsCodeStatus'
XMLDATA	CLOB(1048576)	NULL	User defined data

ASTRANSFERDETAIL			
Name	Datatype	Null Option	Comment
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsActivity
FROMVALUATIONGUID	CHARACTER(36)	NOT NULL	ValuationGUID from AsValuation
TOVALUATIONGUID	CHARACTER(36)	NOT NULL	ValuationGUID from AsValuation

ASTRANSLATION			
Name	Datatype	Null Option	Comment
DEFAULTDISPLAY	VARCHAR(255)	NOT NULL	Name of the screen on which the word appears (or "Common" if it appears on more than one page)
SCREENNAME	VARCHAR(255)	NOT NULL	The English word or phrase
TYPECODE	VARCHAR(2)	NOT NULL	The type code that corresponds to the foreign language
TRANSLATEDDISPLAY	VARCHAR(255)	NOT NULL	The translated word or phrase

ASUPLOAD			
Name	Datatype	Null Option	Comment
UPLOADGUID	CHARACTER(36)	NOT NULL	Primary key
UPLOADNAME	VARCHAR(50)	NOT NULL	Description of upload
UPLOADTYPECODE	VARCHAR(50)	NOT NULL	From AsCode.CodeValue where CodeName = 'AsCodeUploadType'
EFFECTIVEDATE	TIMESTAMP	NULL	As of date
CLIENTNUMBER	VARCHAR(20)	NOT NULL	ClientNumber from AsSecurity who uploaded the file
LOCALFILENAME	VARCHAR(255)	NOT NULL	Location where file was uploaded from
SERVERFILENAME	VARCHAR(255)	NOT NULL	File name as recognized on the server
XMLDATA	CLOB(1048576)	NULL	User defined data

ASUPLOADCONNECTIVITY			
Name	Datatype	Null Option	Comment
UPLOADGUID	CHARACTER(36)	NOT NULL	Foreign key into AsUpload
RELATEDGUID	CHARACTER(36)	NOT NULL	Link to AsActivity (ActivityGUID)

ASUPLOADRATE			
Name	Datatype	Null Option	Comment
UPLOADGUID	CHARACTER(36)	NOT NULL	Foreign key into AsUpload

ASUPLOADRATE			
Name	Datatype	Null Option	Comment
CRITERIA1	VARCHAR(10)	NOT NULL	
CRITERIA2	VARCHAR(10)	NULL	User defined criteria
CRITERIA3	VARCHAR(10)	NULL	User defined criteria
CRITERIA4	VARCHAR(10)	NULL	User defined criteria
CRITERIA5	VARCHAR(10)	NULL	User defined criteria
INTEGERCRITERIA	INTEGER	NOT NULL	Primary criteria for the rate group that is looked up by way of an integer value
RATE	DECIMAL(18,10)	NOT NULL	Rate value

ASVALUATION			
Name	Datatype	Null Option	Comment
VALUATIONGUID	CHARACTER(36)	NOT NULL	Primary key
FUNDGUID	CHARACTER(36)	NOT NULL	Link to AsFund
POLICYGUID	CHARACTER(36)	NOT NULL	Link to AsPolicy
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Link to AsActivity
EFFECTIVEDATE	TIMESTAMP	NOT NULL	As of date
ACTIVEFROMDATE	TIMESTAMP	NOT NULL	System date applied
ACTIVETODATE	TIMESTAMP	NULL	System date of reversal
RATELOCKDATE	TIMESTAMP	NULL	Date of rate lookup
MONEYTYPECODE	VARCHAR(2)	NOT NULL	Linked to AsCode.CodeValue where CodeName = 'AsCodeMoneyType' 01:Premium 02:Premium Tax 03:GMB Fee 04:Future 05:Transfer Fee 06:Interest 07:Surrender Charge 08:Annuity Payment 09:Federal Withholding 10:State Withholding 11:ALL 12:Not Taken Premium 13:Free Look Premium 14:Payout Adjustment 15:Mortality Adjustment 16:Fund Overflow Bucket 17:Cost of Insurance 18:Lapse Deficit 19:Lapse Recover 20:Loan 21:Loan Repayment 22:Death Benefit 23:Death Adjustment 24:Per Thousand Charges 25:Target Charge 26:Flat Charge 27:Not Taken Excess 28:Free Looked Premium Tax 29:Free Look Refund 30:Free Look GainLoss 31:Cash Refund Removal 32:Withdrawal 33:CDSC on Original Policy 34:Living Credit 35:MVA Charge 36:Bill Amount 37:NSF Charge 38:NSF Fee 39:Asset Fee 40:Premium Enhancement 41:Service Charge 42:Flat Extra 43:Annual Contract Fee 44:Death Benefit Guar 45:Death Interest 46:RTR Return

ASVALUATION			
Name	Datatype	Null Option	Comment
			47:Exception Fee 48:Personal Reimbursement 49:Disbursement NetAmount 50:1035 Exchange 51:First Year Premium 52:Renewal Premium 53:First Year Comission 54:Renewal Comission 55:Comission Offset 56:GMIB Charge 57:Free Look Principal 58:Free Look Interest 59:DB Offset 60:Sales Load 61:Risk Charge 62:Admin Fee 64:Loan Transfer 65:Loan Interest Charge 66:Loan Cap 67:Bonus Premium 68:Bonus Removal 74:Asset Tier Rebate 75:Living Benefit Cost 76:Purchase Payment Credit 77:ADB Fee 78:Premium 3 Year 79:Premium 5 Year 80:Premium 7 Year 81:Premium 10 Year 82:Sweep Transfer Adjustment 90:Premium Refund 95:GMDB Fee 96:ADD Rider Charge 97:COI Wavier Charge
REMOVEDFROMDEPOSITGUID	CHARACTER(36)	NULL	On removals identifies the deposit
SEEDDEPOSITGUID	CHARACTER(36)	NULL	Original deposit (used for transfers)
TAXLOTGUID	CHARACTER(36)	NULL	Foreign key into AsTaxLot
TAXLOTTRADEDATE	TIMESTAMP	NULL	
TAXLOTGAINLOSS	DECIMAL(19,4)	NULL	
VALUATIONAMOUNT	DECIMAL(19,4)	NULL	Amount from allocation
VALUATIONUNITS	DECIMAL(18,10)	NULL	Number of units, if variable
VALUATIONGAINLOSS	DECIMAL(19,4)	NULL	If valuation is backdated, the gain/loss on the amount
VALUATIONPRINCIPAL	DECIMAL(19,4)	NULL	Tracks original deposit
GAINLOSSONSHADOW	DECIMAL(19,4)	NULL	If valuation is backdated, the gain/loss on the amount if reversed
BUCKET	SMALINT	NULL	Bucket Number
DEPOSITDEPLETEDDATE	TIMESTAMP	NULL	Date Deposit Depleted

ASVALUATIONCHILD			
Name	Datatype	Null Option	Comment
VALUATIONGUID	CHARACTER(36)	NOT NULL	Linked to AsValuation
CHILDFUNDDGUID	CHARACTER(36)	NOT NULL	Linked to AsFund

ASVALUATIONXML			
Name	Datatype	Null Option	Comment
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsActivity
XMLDATA	CLOB(1048576)	NULL	

ASVALUESREQUEST			
Name	Datatype	Null Option	Comment
VALUESGUID	CHARACTER(36)	NOT NULL	Unique identifier
POLICYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsPolicy
ACTIVITYGUID	CHARACTER(36)	NOT NULL	Foreign key into AsActivity
STATUSCODE	VARCHAR(2)	NOT NULL	
STARTTIME	TIMESTAMP	NULL	Time started

ASVALUESREQUEST			
Name	Datatype	Null Option	Comment
ENDTIME	TIMESTAMP	NULL	Time ended

ASWEBREQUEST			
Name	Datatype	Null Option	Comment
WEBREQUESTGUID	CHARACTER(36)	NOT NULL	Primary key
STARTTIME	TIMESTAMP	NULL	Time started
ENDTIME	TIMESTAMP	NULL	Time ended
STATUSCODE	INTEGER	NOT NULL	
XMLDATA	CLOB(1048576)	NULL	

ASWEIGHTEDNAV			
Name	Datatype	Null Option	Comment
NETASSETVALUEGUID	CHARACTER(36),	NULL	Linked to AsNetAssetValue
WEIGHT	DECIMAL(18,10),	NULL	Weight
ASSETS	DECIMAL(19,4),	NULL	Assets
UNITS	DECIMAL(18,10),	NULL	Units
MORTALITYANDEXPENSE	DECIMAL(19,4),	NULL	Mortality Expense
UNITVALUE	DECIMAL(18,10)	NULL	Value of the Units

ASWITHHOLDING			
Name	Datatype	Null Option	Comment
WITHHOLDINGGUID	CHARACTER(36)	NOT NULL	Primary key
TYPECODE	VARCHAR(2)	NOT NULL	Where the relatedGUID is used (AsCode.AsCodeName=AsCodeWithholdingType)
RELATEDGUID	CHARACTER(36)	NOT NULL	Links to Client,Policy,Plan or Activity
XMLDATA	CLOB(1048576)	NULL	

ASWITHHOLDINGFIELD			
Name	Datatype	Null Option	Comment
FIELDNAME	VARCHAR(50)	NOT NULL	Primary Key
WITHHOLDINGGUID	CHARACTER(36)	NOT NULL	Name of each Withholding Field
FIELDTYPECODE	CHARACTER(2)	NOT NULL	From AsCode.CodeValue where Codename = AsCodeField
DATEVALUE	TIMESTAMP	NULL	Contains value if FieldTypeCode = 01
TEXTVALUE	VARCHAR(7900)	NULL	Contains value if FieldTypeCode = 02
INTVALUE	INTEGER	NULL	Contains value if FieldTypeCode = 03
FLOATVALUE	REAL	NULL	Contains value if FieldTypeCode = 04