
PeopleSoft Enterprise Environment Management Plug-in 8.50 for Oracle Enterprise Manager Implementation Guide

September 2009

Copyright © 2006, 2009, Oracle and/or its affiliates. All rights reserved.

Trademark Notice

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

License Restrictions Warranty/Consequential Damages Disclaimer

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

Hazardous Applications Notice

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Third Party Content, Products, and Services Disclaimer

This software and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third party content, products and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third party content, products or services.

Contents

Preface

PeopleSoft Environment Management Plug-in for Oracle Enterprise Manager Preface	ix
PeopleSoft Environment Management Plug-in Preface	ix

Chapter 1

Getting Started with PeopleSoft Environment Management Plug-in	1
Sources of Additional Information	1
PeopleSoft Environment Management Plug-in Installation	2
PeopleSoft Target Discovery	2
Monitoring and Managing Each of the PeopleSoft Target Types	3

Chapter 2

Understanding the PeopleSoft Environment Management Plug-in	5
PeopleSoft Environment Management Plug-in Overview	5
Common Terms Used in This Book	6
Features of the PeopleSoft Environment Management Plug-in	8
PeopleSoft Target Types	8
The Discovery Process	9
PeopleSoft Environment Management Plug-in Pages	9
The Enterprise Manager Homepage	10
The Targets Tab	11
The PeopleSoft Subtab	11
Target Homepages	12
Common Elements on Homepages	13
Target Administration Pages	14
Common Elements on Administration Pages	15
Target Log Management	20
Exporting a Log File	23
Searching for Strings in a Log File	23
Host Log Alert Settings	23
Log Management Setup	23
Schedule Purge and Archive Jobs	24

Chapter 3

Discovering PeopleSoft Targets	27
Understanding the Discovery Process	27
Understanding Steps in the Discovery Process	27
Understanding UNIX Login Shell Support	28
Adding PeopleSoft Targets	28
Registering Targets	32
Setting Environment Variables	35
Adding and Registering PS Process Monitor Targets	37
Configuring PROCESSREQUEST Web Service	38
Adding PS Process Monitor Targets From Discovery Results Page	39
Adding PS Process Monitor Targets From Process Monitor Setup Page	39
PS Process Monitor Configuration Variables	39

Chapter 4

PeopleSoft Application Database Targets	41
Understanding PeopleSoft Application Database Targets	41
The PS Application Database Homepage	41
The PS Application Database Configuration Page	43

Chapter 5

PS Application Server Domain Targets	45
The PS Application Server Domain Homepage	45
Creating PS Application Server Domain Targets	47
PS Application Server Domain Performance	49
PS Application Server Domain Administration	51
PS Application Server Domain Logs	53

Chapter 6

PS Process Scheduler Domain Targets	55
The PS Process Scheduler Domain Homepage	55
Creating PS Process Scheduler Domain Targets	57
PS Process Scheduler Domain Performance	57
PS Process Scheduler Domain Administration	57

Managing a Process Scheduler in PIA	59
PS Process Scheduler Domain Logs	59
 Chapter 7	
PS Process Monitor Targets	61
The PS Process Monitor Homepage	61
PS Process Monitor Performance	63
PS Process Monitor Administration	63
Scheduling Processes	64
Monitoring Processes	65
 Chapter 8	
PS PIA and PS Web Site Targets	67
PS PIA Targets	67
The PS PIA Homepage	67
PS PIA Target Performance	69
PS PIA Target Administration	69
PS PIA Target Logs	71
PS Web Site Targets	71
The PS Web Site Homepage	71
PS Web Site Performance	73
PS Web Site Administration	73
 Chapter 9	
PS Search Server Domain Targets	75
Understanding PS Search Server Domain Targets	75
The PS Search Server Domain Homepage	75
Creating a PS Search Server Domain	76
PS Search Server Domain Performance	76
PS Search Server Domain Administration	77
PS Search Server Domain Logs	78
 Chapter 10	
PeopleSoft Systems and Services	79
Understanding PeopleSoft Systems	79

Understanding Services	79
Creating PeopleSoft Systems	80
The PeopleSoft System Homepage	80
Automated PeopleSoft System Creation	81
Manual System Creation	83
Editing PeopleSoft Systems	84
Removing PeopleSoft Systems	85
Managing PeopleSoft Systems	85
PeopleSoft System Administration	85
PeopleSoft System Components	86
PeopleSoft System URLs	87
PeopleSoft System Topology	88

Chapter 11

Security for PeopleSoft Environment Management Plug-in	91
Understanding Enterprise Manager Security	91
Target Privileges	91
Target Preferred Credentials	92
Managing Preferred Credentials	92
Target Credentials	93

Chapter 12

Validating Policies	95
Understanding Policies	95
PeopleSoft Policy Definitions	95
Enterprise Manager's Policy Validation	95
Policy Violation Detail	96

Appendix A

Configuration and Metric Data Collected	99
Configuration Data Collected	99
Metric Data Collected	100

Appendix B

Roles and Privileges	103
-----------------------------------	------------

Target Actions and Privileges	103
Target Actions and Privileges Tables	103

Appendix C

Target Log Files	113
Default Target Log Files	113
PS PIA Log Files	113
PS Application Server Domain Log Files	114
PS Search Server Domain Log Files	114
PS Process Scheduler Server Log Files	115

Appendix D

Target Policies	117
PS Application Server Domain Policies	117
PS PIA Policy	118
PS Web Site Policies	118

Appendix E

Target Relationships	121
Links That Display on Homepages	121
Relationships on Topology Page	123

Index	125
--------------------	------------

PeopleSoft Environment Management Plug-in for Oracle Enterprise Manager Preface

This preface describes the PeopleSoft Environment Management Plug-in for Enterprise Manager.

PeopleSoft Environment Management Plug-in Preface

This product has been developed as an integration with Oracle Enterprise Manager Framework to enhance PeopleSoft system administration. By using Oracle Enterprise Manager Grid Control features, PeopleSoft environments can be monitored and managed from the centralized, graphical interface of the Oracle Enterprise Manager console.

This book assumes that you have a working knowledge of: , and that you have experience with PeopleSoft system administration utilities, such as PSADMIN, as well as all the elements of a People

- Oracle Enterprise Manager features, terms, and administration.
- PeopleSoft system administration utilities, such as PSADMIN.
- PeopleSoft system elements, such as databases, application servers, search servers, Process Scheduler servers, Process Monitor, web servers, PIA installations, and so on.

Note. The documentation for Oracle Enterprise Manager and all of the PeopleSoft system elements *is not* recreated in this guide. For information on specific details related to Oracle Enterprise Manager or a PeopleSoft target type, refer to the documentation associated with that specific product.

PeopleBooks and the Online PeopleSoft Library

A companion PeopleBook called PeopleBooks and the Online PeopleSoft Library contains general information, including:

- Understanding the PeopleSoft online library and related documentation.
- How to send PeopleSoft documentation comments and suggestions to Oracle.
- How to access hosted PeopleBooks, downloadable HTML PeopleBooks, and downloadable PDF PeopleBooks as well as documentation updates.
- Understanding PeopleBook structure.
- Typographical conventions and visual cues used in PeopleBooks.
- ISO country codes and currency codes.

- PeopleBooks that are common across multiple applications.
- Common elements used in PeopleBooks.
- Navigating the PeopleBooks interface and searching the PeopleSoft online library.
- Displaying and printing screen shots and graphics in PeopleBooks.
- How to manage the PeopleSoft online library including full-text searching and configuring a reverse proxy server.
- Understanding documentation integration and how to integrate customized documentation into the library.
- Glossary of useful PeopleSoft terms that are used in PeopleBooks.

You can find this companion PeopleBook in your PeopleSoft online library.

Chapter 1

Getting Started with PeopleSoft Environment Management Plug-in

This chapter discusses:

- Sources of additional information.
- PeopleSoft Environment Management Plug-in installation.
- PeopleSoft target discovery.
- Monitoring and managing each of the PeopleSoft target types.

Sources of Additional Information

The PeopleSoft Environment Management Plug-in runs within the framework of Oracle Enterprise Manager. Therefore, as you install and use the features of Enterprise Manager, you may need to get more information than is provided in this guide.

Many of the concepts and tasks described in this book relate to PeopleSoft system administration tasks.

See *Enterprise PeopleTools PeopleBook: System and Server Administration*

Oracle Documentation

Enterprise Manager provides a wide range of information for different types of users at many different levels of expertise.

These are the major information sources for Oracle Enterprise Manager:

- Online help screenwatches

Enterprise Manager comes with a comprehensive set of narrated tutorials (screenwatches) covering major functional areas of Enterprise Manager. Screenwatches are 10- to 15-minute-long narrated demonstrations that cover everything from performing routine tasks, such as creating blackouts, to using specialized features such as Application Service Level Management. Screenwatches can be accessed directly from the Enterprise Manager console, from the online help system, and from the Enterprise Manager product area on Oracle Technology Network.

- Oracle Technology Network (OTN)

The Enterprise Manager product center on OTN (available at <http://www.oracle.com>) is your source for the latest Enterprise Manager information. There you will find newly released documentation and screenwatches, white papers, tutorials, internet seminars, and technology/application-specific literature. Major product feature enhancements such as Enterprise Manager framework extensibility is also available.

- Printed documentation

Enterprise Manager books can help you install and configure Enterprise Manager, as well as provide you with important concepts that can save you time. You can find the complete Enterprise Manager documentation library on OTN at <http://www.oracle.com/technology/documentation/oem.html>.

- Online help

Online help is available from any Enterprise Manager page. In most cases, clicking Help displays a context-sensitive help topic that contains information about the features available on the current page and related topics. The online help system provides substantial technical and reference information such as a complete metric reference, detailed conceptual information, and procedural instruction on how to carry out both simple and complex administrative tasks with Enterprise Manager. Online help is a valuable resource for learning Enterprise Manager.

PeopleSoft Environment Management Plug-in Installation

You install the PeopleSoft Environment Management Plug-in after you have installed the Oracle Enterprise Manager software and Enterprise PeopleTools. The archive you downloaded containing the plug-in software also contains the PeopleSoft Environment Management Plug-in installation instructions in addition to a "readme" file. Read and understand both documents before beginning your installation.

For detailed information about Enterprise Manager hardware and software requirements, configurations, and certified web browsers, open the Oracle Technology Network Enterprise Manager Product Center site.

See <http://www.oracle.com/technology/products/oem/index.html>.

For information related to the version of Oracle Enterprise Manager Grid Control software that is required for the PeopleSoft Environment Management Plug-in, see the PeopleSoft certification information posted on My Oracle Support.

See <http://www.oracle.com/technology/products/oem/index.html>.

PeopleSoft Target Discovery

After you have installed all of the required software, you can begin the discovery of the PeopleSoft targets. PeopleSoft targets refer to the elements of a PeopleSoft environment, such as an application server, application database, PeopleSoft website, and so on.

The discovery process identifies and registers PeopleSoft targets in Enterprise Manager so that they can be monitored and managed.

Monitoring and Managing Each of the PeopleSoft Target Types

After the PeopleSoft targets have been discovered you can begin monitoring and managing PeopleSoft systems and targets. Concepts and tasks relating to systems and targets are discussed in individual chapters of this guide.

Chapter 2

Understanding the PeopleSoft Environment Management Plug-in

This chapter discusses:

- PeopleSoft Environment Management Plug-in overview.
- PeopleSoft Environment Management Plug-in features.
- PeopleSoft target types.
- The discovery process.
- Enterprise Manager Grid Control Console.
- PeopleSoft Environment Management Plug-in pages.
- Target homepages.
- Target administration.

PeopleSoft Environment Management Plug-in Overview

The PeopleSoft Environment Management Plug-in uses Oracle Enterprise Manager to provide an integrated, graphical user interface for monitoring and managing components of a PeopleSoft environment.

The entities that Enterprise Manager monitors and manages are called *managed targets*, which are separately manageable and named entities within the enterprise, such as databases, application servers, Process Scheduler servers, web servers, and so on.

The Oracle Enterprise Manager product includes the Management Agent, Oracle Management Service, Management Repository Database, and the Grid Control Console, which is a browser-based central console through which administrators can perform monitoring, administration, and configuration tasks for the enterprise.

Common Terms Used in This Book

Administrator Account	<p>Administrator accounts provide users permission to perform administrative tasks and access administrative information. You can set up each administrator account to have its own roles, privileges, and notification rules. There are two types of administrator accounts:</p> <ul style="list-style-type: none">• Super Administrator• Administrator
Alerts	<p>Indicates a potential problem; either a warning or critical threshold for a monitored metric has been crossed. An alert can also be generated for various target availability states. Enterprise Manager provides various options to respond to alerts. Administrators can be automatically notified when an alert triggers and can set up corrective actions to resolve an alert condition automatically.</p>
Beacon	<p>A special target installed on an agent that runs a defined service test and reports the results to the Oracle Management Service to determine the status and performance of a service.</p>
Dashboard	<p>Presents information using intuitive icons and graphics that let you spot recent changes and quickly identify and respond to problems.</p>
Discovery Process	<p>The process of identifying and registering targets in Enterprise Manager so that they can be monitored and managed from the Enterprise Manager console. Targets are discovered one host at a time.</p>
Enterprise Manager Grid Control Console	<p>The Oracle Enterprise Manager web-based user interface for centrally managing the entire PeopleSoft computing environment. It can be accessed from a client workstation that meets the minimum client requirements of the Enterprise Manager.</p>
Management Agent	<p>A process deployed as binaries on each of the monitored hosts. It is responsible for monitoring all targets in the host, communicating the information to the middle-tier management service, and managing and maintaining the host and its targets.</p>
Management Repository	<p>This is an Oracle database that contains all the available information about administrators, targets, and applications managed within Enterprise Manager. Captured data is uploaded to the repository through the Oracle Management Service. The Repository organizes the data and makes it available for retrieval—allowing the data to be shared between any administrators accessing the Grid Control Console.</p>
Oracle Management Service	<p>A web application (J2EE-compliant) that renders the user interface for the Oracle Enterprise Manager Grid Control Console. It works with all management agents to process monitoring and job information, and uses the Management Repository as its data store. The Oracle Management Service resides in the layer above an Oracle Application Server (OAS). Therefore, when the Oracle Management Service is installed, it also installs the application server.</p>

PeopleSoft System	A group of targets that are associated with a particular PeopleSoft application database. Depending upon how many PeopleSoft applications you have installed, you may have multiple PeopleSoft Systems to manage.
PeopleSoft Global Unique Identifier (GUID)	A unique identifier that ties each target to a database and defines all targets referencing the same GUID as a system. The GUID is generated and stored at the database layer. During the discovery process, the application server connects to the PeopleSoft application database and retrieves the GUID. This value is derived from the PeopleTools Options page (PSOPTIONS table).
Policies	Define the desired behavior or characteristics of systems. By using preconfigured or custom policies, automated assessments of systems and applications are performed. Through alerts, you are notified of any deviations, such as inappropriate settings or incorrect system configurations.
Preferred Credentials	Simplify access to managed targets by storing target login credentials in the Management Repository. With preferred credentials set, users can access a target that recognizes those credentials without being prompted to log in to the target's host machine. Preferred credentials are set on a per user per target basis, thus ensuring the security of the environment.
Roles	Enable you to group Enterprise Manager system and target privileges, and grant these to administrators or to other roles. Privileges give the administrator rights to perform management actions within Enterprise Manager. Creating roles is an easy way to grant a predefined set of privileges to a group of administrators. If you change a role, the changes are automatically propagated to all administrators who are assigned that role.
Service	An entity that models a business process or application. Examples of services are HCM applications, online banking, and email services. You can define services by creating one or more service tests that simulate common end-user functions. Using these service tests, you can measure the performance and availability of critical business functions, receive alerts when there is a problem, identify common issues, and diagnose causes of failures.
System	A set of targets (hosts, databases, application servers, and so on) that function together to host one or more applications or services.
Super Administrator Account	Can manage all other administrator accounts and set up all administrator credentials. In addition, the super administrator can: <ul style="list-style-type: none"> • Create privileges and roles. • Perform the initial setup of Enterprise Manager. • Add targets to Enterprise Manager. • Perform actions on targets in the system.

Note. Enterprise Manager is installed with a default super administrator account named SYSMAN. You use the SYSMAN account for the initial login to Enterprise Manager. Then, create new super administrator accounts as needed in your system.

Topology Viewer

Enables you to view the relationships between targets within the context of a system. You can perform some management actions from this view.

Features of the PeopleSoft Environment Management Plug-in

The PeopleSoft Environment Management Plug-in:

- Discovers and registers PeopleSoft targets.
- Monitors and manages PeopleSoft targets, including actions such as start, stop, configure, and other specific tasks relevant to each target type.
- Submits and monitors Process Scheduler requests.
- Displays configuration data in a graphical user interface that is driven by metadata.

This ensures that you enter appropriate values and helps limit potential errors in configuration.

- Provides log management for PeopleSoft targets, including the ability to search, view, export, and purge log files.
- Creates a PeopleSoft system in Enterprise Manager.

This enables you to see how all the targets in the system are related to the PeopleSoft application database.

- Generates a graphical topology that displays the relationships between targets.

You can execute selected actions on targets from this view.

- Creates a *service* that simulates a transaction, such as login and logout, to monitor the availability of an application.

Using the Enterprise Manager Service Level Monitoring feature, you can also check the availability of a system or a feature of an application.

The PeopleSoft Environment Management Plug-in delivers a login and logout transaction service for a PeopleSoft system.

- Provides custom policies to evaluate configuration data for PeopleSoft target types.

PeopleSoft Target Types

PeopleSoft-specific target types allow monitoring and management of a PeopleSoft environment. They are:

PS Application Database (PS App DB) Refers to the PeopleSoft application database—and contains a PeopleSoft application such as CRM or HCM. There can only be one PeopleSoft application for each installed application database.

PS Application Server Domain	Key target type of a PeopleSoft environment. It does all of the complex logic and computations and builds the contents that the web server uses to display pages.
PS Process Scheduler Domain	Enables batch job processing.
PS Process Monitor	Enables you to monitor and submit processes configured to run on a Process Scheduler server.
PS PIA	Allows Enterprise Manager to manage the PIA component. It corresponds to a <i>Web domain</i> in Weblogic, <i>server</i> in WebSphere, and <i>application/OC4J</i> in OAS. This target type contains one or more PS Web Site targets.
PS Web Site	Comprises the specific web application and its corresponding HTML files, image files and resource files. It also includes configurations and page content. PS Web Site targets always belong to a PS PIA target.
PS Search Server Domain	Refers to a remote server running Verity search requests for one or more application server domains.

The Discovery Process

Discovery is the process of searching for and registering PeopleSoft targets so that Enterprise Manager can monitor and manage them. It is the first step to be performed after you have installed all of the required software.

During this process, you use a series of Enterprise Manager screens to:

- Select the target types to be discovered.
- Enter credentials so that Enterprise Manager has access to the host where discovery is to be performed.
- Register the discovered targets in Enterprise Manager.
- Enter the information required to connect to the PROCESSREQUEST web service.
- Identify and register the Process Monitor target.
- Set environment variables needed to connect to the PeopleSoft application database.
- Identify and register the associated application database.
- Review the registered targets.

See [Chapter 3, "Discovering PeopleSoft Targets," Registering Targets, page 32.](#)

PeopleSoft Environment Management Plug-in Pages

This section discusses:

- The Enterprise Manager homepage
- The Targets tab
- The PeopleSoft subtab
- Target homepages
- Target administration pages

The Enterprise Manager Homepage

The Enterprise Manager homepage gives you an at-a-glance view of the overall status of all the targets being monitored. It summarizes key monitoring areas such as availability across all managed targets, open alerts, policy violations, and recent problems with job executions. Links on this page enable you to drill down to access detailed performance information.

The homepage is the first page that appears when you log on to Enterprise Manager.

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout
Home Targets Deployments Alerts Policies Jobs Reports

Page Refreshed Apr 13, 2006 3:36:14 PM PDT

View: All Targets

Overview
Total Monitored Targets **97**
[All Targets Status](#)

All Targets Alerts
Critical **173**
Warning **194**
Errors **4**

All Targets Policy Violations
Critical **69**
Warning **37**
Informational **4**

All Targets Jobs
Problem Executions (last 7 days) **2**
Suspended Executions (last 7 days) **0**

Target Search
Search: All [Go]

Security Policy Violations
Critical **64**
Warning **20**
Informational **1**
New in Last 24 Hours **1**

Critical Patch Advisories for Oracle Homes
Patch Advisories **1**
Affected Oracle Homes **5**
Job [RefreshFromMetalink](#)

Deployments Summary
View: Database Installations

Database Installations	Targets	Installations	Interim Patches Applied
Oracle Database 10g 10.1.0.2.0	0	1	No
Oracle Database 10g 10.1.0.4.0	1	3	No
Oracle Database 10g 10.2.0.1.0	0	1	No

Resource Center
[Documentation](#)
[Release Notes](#)
[Support](#)
[Oracle Technology Network](#)

Home | Targets | Deployments | Alerts | Policies | Jobs | Reports | Setup | Preferences | Help | Logout

Copyright © 1996, 2006, Oracle. All rights reserved.
Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.
[About Oracle Enterprise Manager](#)

Enterprise Manager Grid Control Console homepage

The Targets Tab

Select Targets to display a row of subtabs that further define targets by type, such as hosts, databases, application servers, and so on.

The PeopleSoft subtab is on the far right-hand side of the screen.

Note. Tabs can be reordered in Preferences, Target Subtabs.

The PeopleSoft Subtab

The PeopleSoft subtab provides the starting point for discovering and accessing PeopleSoft targets.

Select Targets, PeopleSoft to display a page listing all of the PeopleSoft targets discovered and registered in Enterprise Manager and a summary of their respective statuses. You can filter the view so that only specific target types are shown.

The target types that display depend on the access rights or privileges that have been set for the user.

Each target type appears within the expandable tree of the PeopleSoft System to which it belongs. That is, all of the server types associated with a particular PS Application Database appear within the expandable section of that database. For example

The screenshot shows the Oracle Enterprise Manager 10g Grid Control interface. The top navigation bar includes links for Home, Targets, Deployments, Alerts, Compliance, Jobs, and Reports. The main content area is titled 'All PeopleSoft Targets'. Below the title, there is a search bar and a 'Go' button. A 'Page Refreshed Jun 26, 2009 7:07:13 AM PDT' message is displayed. The main table shows a list of targets under the 'PS Application Server Domain'. The table has columns for 'Select Focus Name', 'Status', and 'Type'. The 'PeopleSoft Targets' section is expanded, showing targets like 'Q8508093.db', 'peoplesoft pia', 'ps.peoplesoft site', 'Q8508093.prcs', and 'prcs-mntr'. The 'Unlinked Targets' section is also expanded, showing targets like 't850u25i.app', 'prcs.prcs', 't850u25i.prcs', and 'newapp1.app'.

Select Focus Name	Status	Type
PeopleSoft Targets		
Q8508093.db.976fa27e-438e-11de-9c6d-957a47ca2219	↓	PS Application Database
peoplesoft pia.st-sun06.ds1.home_psoft_pt.850-809-R1	↑	PS PIA
ps.peoplesoft site.st-sun06.ds1.home_psoft_pt.850-809-R1	↑	PS Web Site
Q8508093.prcs.st-sun06.ds1.home_psoft_pt.850-809-R1	↓	PS Process Scheduler Domain
prcs-mntr.https.PTA137.10443.PROCESSREQUEST_1_wsdl	↑	PS Process Monitor
Unlinked Targets		
t850u25i.app.st-hpp03.ds1.home_psoft_pt.850-809-I1	%	PS Application Server Domain
prcs.prcs.st-hpp03.ds1.home_psoft_pt.850-809-I1	%	PS Process Scheduler Domain
t850u25i.prcs.st-hpp03.ds1.home_psoft_pt.850-809-I1	%	PS Process Scheduler Domain
newapp1.app.st-hpp03.ds1.home_psoft_pt.850-809-I1	%	PS Application Server Domain

PeopleSoft targets page

PeopleSoft targets not belonging to any PS Application Database target appear under Unlinked Targets. If, for example, a PS Application Database with child targets is removed from the environment, OEM moves child targets to Unlinked Targets to indicate that they are "orphaned."

Note. Just after discovery, PeopleSoft targets may appear under Unlinked Targets until after a successful configuration collection.

You can initiate the discovery process from this page by selecting Add PeopleSoft Targets.

From the PeopleSoft page, you can create domains for the PS Application Server, PS Search Server, and PS Process Scheduler targets. You can also remove targets registered in Enterprise Manager. Removing a target from Enterprise Manager does not delete it from its managed host.

The commands that you submit from the Enterprise Manager are handled by an API layer that captures the commands and submits the appropriate, native, command line options on the host for the server type. For example, submitting the "configure domain" causes the PSADMIN command `psadmin -c configure -d domain`.

If PS PIA or PS Web Sites are related and you want to remove them from Enterprise Manager, Oracle recommends that you remove them together to avoid status and functional inconsistencies.

Target Homepages

This section describes the fields or links that appear on PeopleSoft target homepages. Not all elements will appear on every target homepage. For example, some elements appear only for database targets, while others appear only for Process Scheduler targets.

Common Elements on Homepages

General	<p>Area that shows the general status of the target in terms of availability, CPU usage, memory usage and so on. If the host contains more than one CPU, CPU usage the value shown is the cumulative usage of all the CPUs.</p> <p>When relevant, this region also lists the related PS Application Database, PS Search Server, system, and host. Links that appear enable you to open either another page for more information or to access the page listed.</p>
Status	Indicates the target's availability.
Start	Select to start the target.
Stop	<p>Select to stop the target.</p> <p><i>See Enterprise PeopleSoft PeopleTools PeopleBook: System and Server Administration.</i></p>
Blackout	Select to manage or create a blackout for the target.
Availability % (availability percentage)	Shows the percentage of time, excluding any blackouts, that the target has been available since it was registered in Enterprise Manager.
Services Impacted	Shows the number of services that are impacted by the failure. (Displays only if a service is associated with the target and if the target's status is down because of a service failure).
Features	<p>(PS Application Server Domain and PS Process Scheduler Domain targets only).</p> <p>Area that displays all of the PeopleSoft features available for the domain such as Quick Server, PUBSUB, Master Process Scheduler, and so on. This list appears only after the target's configuration data is saved in Enterprise Manager.</p>
Alerts and Host Alerts	Area that lists any alerts that have been generated. When a metric threshold value is reached, an alert is generated. The most recent alerts are listed first. You can change the sorting by clicking the appropriate column header. By clicking a specific alert message, you can drill down to explicit details about the metric in alert.
Related Links	Area that lists all of the related links appearing on target homepages. Not all links will appear on every target homepage.
Policy Violations	Violations listed here reflect configuration issues that Enterprise Manager has detected. Click the links in this region to view the Policy Violations page where details about the violation appear.
Monitoring Configuration	Displays target properties such as domain name, PS_HOME, and PeopleTools version.

Note. Do not change these values unless instructed by technical support.

Alert History	Displays a complete alert history of the target.
Access	Displays access type and the privilege associated with the target.
All Metrics	Shows all of the metrics defined for the target.
Blackouts	Displays the blackouts that have been defined for the target history. You can also set up a blackout from this page.
Target Properties	Shows target properties such as line of business, location, and contact.
Metric and Policy Settings	Displays the metric thresholds and policies defined for the domain.
Reports	Displays standard Enterprise Manager reports available for the target.
Open Telnet Session	Enables the user to open an ad hoc telnet session to the host of the target. (Appears only if the host of the target is UNIX-based).
Policies	The PeopleSoft Environment Management Plug-in delivers policies and any deviations to your systems or applications are reported. Examples of deviations include inappropriate settings and incorrect system configurations.

Target Administration Pages

This section describes the links that appear on PeopleSoft target administration pages. Not all elements will appear on every target administration page.

Common Elements on Administration Pages

Configure Domain

Opens the Configure Domain page where an administrator can edit domain configurations and save the changes.

See *Enterprise PeopleSoft PeopleTools PeopleBook: System and Server Administration*, "Working With Domain Configurations"

- If this domain is up *and* the allow dynamic changes property is selected, only dynamic fields can be edited. All others are disabled.
- If this domain is down, all fields are enabled.

From the Configure Domain page, you can select Configure Environment Variables to edit settings that establish the connection from the domain to the application database. Depending on the database type of the domain, there are default required environment settings shown. However, you must enter the values.

- Configuration details region.
 - Move the mouse over the information icon to display a description of the field.
 - If the dynamic icon is present, it means that the field is dynamic and a restart of the domain is not necessary if there were changes (and if the allow dynamic changes option is set).
 - Enable check boxes display for some fields to accommodate any commented out properties within the configuration files. If desired, you can enable the commented out properties by selecting the check box.

Note. Refer to the section describing the importance of setting environment variables correctly.

See [Chapter 3, "Discovering PeopleSoft Targets," Setting Environment Variables, page 35.](#)

Create Like Domain

Equivalent to the Import Domain from another PS Application Server Domain or PS Process Scheduler Domain in the PSADMIN. You can create a like domain only within the same host referencing the same PS_HOME.

Compare Domain Configurations

Compares one domain configuration to another domain configuration.

Compare to Multiple Configurations (Jobs)

Compares one domain to two or more other domains or snapshots of saved domain configurations.

Last Collected Configuration	<p>Displays the latest configuration data gathered from the target. For example, if the target is an application server, this page shows its configuration properties collected from the psappsrv.cfg (Configuration tab) and psappsrv.ubx (Features tab) files and stored in the Management Repository.</p> <p>You can also select to save, compare, compare multiple options, and refresh.</p> <ul style="list-style-type: none"> • Save saves a copy of the configuration in the Management Repository. This may be retrieved later on using the View Saved Configurations link. • Refresh enables you to request an on-demand configuration collection. Configuration collection values display after a refresh.
View Saved Configurations	Enables you to retrieve previously saved configurations. Saving a configuration snapshot is done from the Last Collected Configuration page.
History	Enables you to view a historical log of configuration changes to the target. The Category field defaults to the target type from which the link was invoked, in this case the application server.
Copy Configurations	<p>Copies configuration files from one existing domain to other domains within the same host. To make the changes effective, you must select the Configure Domain action in the target domains after the configuration copy. This overwrites the configuration files on the managed host.</p> <hr/> <p>Note. This feature does not work on domains that are currently running.</p> <hr/>
Start Domain	<p>Starts the domain serially. This is the usual start process from the PeopleSoft administration utility.</p> <hr/> <p>Note. If needed, you can abort the start process from the processing page.</p> <hr/>
Start Domain (Parallel)	This option initiates the start for all processes at the same time, which speeds up the boot up process. To view the status of this start, click the Process Status link on the Administration tab.
Stop Domain	<p>This action shuts down the domain gracefully and is equivalent to the normal stop domain process in the PeopleSoft administration utility.</p> <hr/> <p>Note. If needed, you can abort the start process from the processing page.</p> <hr/>
Stop Domain (Forced)	Initiates a forced shutdown of the domain. This is useful for aborting processes that hang.

Purge/Archive Cache	<p>Enables you to purge and archive (optional) the server cache files of a domain. The domain does not need to be down.</p> <p>If you select Archive, enter the archive location. The default archive directory is %PS_HOME%/<domain>/archive. Ensure you have the fully qualified directory name; if the directory does not exist, the archive process will try to create it.</p> <hr/> <p>Note. If the domain is up, the output includes the Tuxedo boot process output for each application server process because this forces a restart of each application server process to remove memory cache.</p> <p>Sharing violation errors may occur on Windows machines during the file copy to the archive directory. These are normal.</p> <hr/>
Delete Domain	<p>The domain must be down before you can initiate a delete action. Selecting this action physically deletes the domain on the host and removes it from Enterprise Manager.</p>
Messaging Server	<p>(Link not available if the domain was created using the developer template.)</p> <p>Enables you to create dedicated publication and subscription (PUBSUB) servers for certain messaging queues. An administrator uses this feature if there are high volumes of messages for certain channels or queues, and there is a requirement for prioritization of messages.</p> <p>Full target privileges are required to create, configure, and delete messaging queues.</p> <p>When you click the Messaging Server link, the Messaging Server Administration page appears showing a summary of all messaging servers that were previously created. From this view, you can select a messaging server and remove or reconfigure it, or create a new messaging server.</p> <p>To create a messaging server, click Create. You are prompted for a messaging server name, messaging type (Publication Broker, Publication Contractor or Subscription Contractor), and at least one messaging queue.</p> <p>A unique messaging queue name is required for queues of the same type across different messaging servers.</p> <p>For changes to take effect, you must configure and restart the domain.</p>
Preload File Cache	<p>Enables you to preload server cache to the domain in order to achieve better performance in the application. The domain must be down and there must be a configured project file in the PreloadFileCache setting of the configuration file before performing this action.</p>
Clean IPC resources	<p>Enables you to free memory by cleaning IPC resources that may still be resident in the memory. This action requires the domain to be down; if not, the domain will be shut down.</p>
Access Tuxedo Command Line (TMADMIN)	<p>Enables you to execute certain Tuxedo commands in the Enterprise Manager agent. The Access Tuxedo Command Line page appears with a free text field where you can enter commands. Click Execute to initiate the command. The results display in the scrollable region below the command field. If needed, you can abort this process.</p>

Process Status	Shows the status of each process running within the PS Application Server, PS Process Scheduler, and PS Search Server Domains. This feature includes a View Status drop-down list that enables you to refresh the data being displayed either manually, every 30 seconds; every minute or every 5 minutes. This is equivalent to server status in the PeopleSoft administration utility.
Client Status	Displays the status, user name, and workstation name of all clients that are connected to the PS Application Server Domain or PS Search Server Domain. From this view, you can monitor the users connecting to your application server domain.
Queue Status	Shows the number of requests queued for each PS Application Server process, PS Process Scheduler process, and PS Search Server process. This data helps determine whether more handlers need to be started to accommodate a large backlog or queued requests.
Execute Host Command	<p>Allows for the use of customized scripts that help manage PeopleSoft environments. Any type of shell or batch script is supported.</p> <p>Enter the path, script name and parameters in the Command text box, then click Execute. The output of the script is shown in the Output text box.</p>
Windows Services Management	<p>(Available only for domains running on a Windows host.) Enables you to configure and install a Windows service that can start and stop your application servers and Process Scheduler servers automatically whenever the server machine boots.</p> <p>If selected, a Configure Windows Services page appears. You can edit the service for Service Start Delay.</p> <p>A table displays the domains that can be started from the Windows Service. You can add to or delete from this list.</p> <p>After adding the domains, you can click one of these:</p> <ul style="list-style-type: none"> • Save: To save the configuration changes to the psntsrv.cfg file. • Save & Install: To save the configuration changes to the psntsrv.cfg file and install the windows service at the same time. • Delete: To delete the Windows service. • Cancel: To return you to the Administration page without any further action.
Process Monitor	Launches the Process Monitor so that you can monitor processes running on the Process Scheduler server. (Applies to PeopleTools 8.50 and later.)
Schedule Process	Launches the Schedule Process interface so that you can submit processes to run on the Process Scheduler server. (Applies to PeopleTools 8.50 and later.)

Edit setEnv/ server.xml/ opmn.xml	<p>Click the link to access the file in text format using Enterprise Manager's Remote File Editor. Filenames depend on the web server type.</p> <p>The most common configuration adjusted in these files is the JVM heap size that is being used by PIA.</p> <ul style="list-style-type: none"> • Weblogic: setEnv.sh/setEnv.cmd • WebSphere: server.xml • OAS: opmn.xml <p>Click Save to have changes made to the file saved directly to the managed host. You can also select the Export to File feature. You must restart PIA for these changes to take effect.</p>
Start PIA	<p>Executes the delivered PeopleSoft start script unless you have a predefined custom script.</p> <hr/> <p>Note. Starting an OAS web server depends on the services managed by the Oracle Process Monitor (OPMN), which include an HTTP server service and the JVMs that host the PeopleSoft applications. These services are managed separately in Enterprise Manager. The OPMN and HTTP server services must be started to access and manage PIA.</p> <hr/>
Stop PIA	<p>Brings down the PS PIA target using either the delivered or a predefined custom PeopleSoft stop script.</p>
Weblogic Console/WebSphere Administration Console/(iAS) Console	<p>The link available depends on the type of web server installed. This URL link must be defined in the PeopleSoft System URL Setup link in a PeopleSoft System homepage.</p> <p>See Chapter 10, "PeopleSoft Systems and Services," PeopleSoft System URLs, page 87.</p>
Edit web.xml	<p>Launches the Enterprise Manager Remote File Editor to display the web.xml file. You can edit the file in text format, then save the changes. Also, you can export the configuration file to your local machine. However, changes made to web.xml are not available in the Enterprise Manager configuration management historical changes.</p>
Customize Start/Stop Scripts	<p>Enables users to change the startup and shutdown scripts used for each PS PIA target.</p> <p>Click this link to display a page to add or remove custom scripts. To add a script, select a file to search for or enter the path and filename in the field. Only one pair of start and stop scripts may be added.</p> <p>To revert to the PeopleSoft delivered scripts, delete the custom scripts.</p>

Configure Site	<p>Enables you to edit and save changes to your site configuration. The changes are saved to the configuration.properties file in the host.</p> <p>Click Save to save your changes to the file.</p> <p>You can configure PS Web Sites even when the site is running. However, you must restart PIA for configuration changes to take effect.</p>
Web Profile	<p>Opens a new browser window that accesses the Web Profile page in the PeopleSoft application. The URL for the Web Profile must be predefined in the PeopleSoft System URL page.</p> <p>See Chapter 6, "PS Process Scheduler Domain Targets," Managing a Process Scheduler in PIA, page 59.</p>
Integration Broker	<p>Opens a new browser window for the Integration Broker page in the PeopleSoft application. The URL must be predefined in the PeopleSoft System URL Systems page.</p>
PIA Signon	<p>Enables you to test the availability of PIA signon page and the PeopleSoft application as a whole. The URL for PIA Signon must be predefined in the PeopleSoft System URL page.</p>
Process Monitor Setup	<p>Launches the Process Monitor Setup page, where you provide the appropriate information to discover and register a Process Monitor target in Enterprise Manager.</p>

Target Log Management

The PeopleSoft Enterprise Management Plug-in log enables you to view PeopleSoft specific logs, traces or dumps for a target. Host credentials are required for this page to display.

Select Targets, PeopleSoft, <a target>, Logs. The Log page of the target type you selected appears. For example, if your target is a PS Application Server target, the PS Application Server Log page appears:

ORACLE Enterprise Manager 10g

Home | **Targets** | Deployments | Alerts | Policies | Jobs | Reports

Hosts | Databases | Application Servers | Web Applications | Services | Systems | Groups | All Targets | **PeopleSoft**

PS Application Server Domain: PSAPP1.app.psemgrid02.home_psft_PT848-805-I1

Page Refreshed Apr 11, 2006 1:38:07 PM PDT [Refresh](#)

Home | Performance | Administration | **Logs**

Select a file and enter search criteria to perform a detailed search.

Select	Filename	Path	Timestamp	File Size (bytes)	Purge
<input checked="" type="radio"/>	APPSRV_0411.LOG	/home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS	Tue Apr 11 13:11:14 PDT 2006	3967	
<input type="radio"/>	MONITORSRV_0411.LOG	/home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS	Tue Apr 11 13:11:15 PDT 2006	578	
<input type="radio"/>	TUXLOG.041106	/home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS	Tue Apr 11 13:11:16 PDT 2006	7959	
<input type="radio"/>	stderr	/home/psft/PT8.48-805-I1/appserv/PSAPP1	Tue Apr 11 11:39:35 PDT 2006	0	
<input type="radio"/>	stdout	/home/psft/PT8.48-805-I1/appserv/PSAPP1	Tue Apr 11 11:39:35 PDT 2006	0	

Related Link [Log Management Setup](#)

☒ Click the Log Management Setup link to define the types of log files that you want to manage for this target.

Search String

Search Results

Filename: [APPSRV_0411.LOG](#)

Line #	Date/Time	Process Name	Process ID	Text
4	04/11/06 11:39:37	PSAPPSRV.7925	7925	PSAPPSRV.7925 (0) [04/11/06 11:39:37](0) PeopleTools Release 8.48-805-I1 (Linux) starting
5	04/11/06 11:39:37	PSAPPSRV.7925	7925	PSAPPSRV.7925 (0) [04/11/06 11:39:37](0) Cache Directory being used: /home/psft/PT8.48-805-I1/appserv/PSAPP1/CACHE/PSAP
6	04/11/06 11:39:39	PSAPPSRV.7925	7925	PSAPPSRV.7925 (0) [04/11/06 11:39:39](3) (PublishSubscribe): PubSubSystem::InitializeServer(): Initialization succeeded.
7	04/11/06 11:39:39	PSAPPSRV.7925	7925	PSAPPSRV.7925 (0) [04/11/06 11:39:39](0) Server started
8	04/11/06 11:39:41	PSAPPSRV.7929	7929	PSAPPSRV.7929 (0) [04/11/06 11:39:41](0) PeopleTools Release 8.48-805-I1 (Linux) starting
9	04/11/06 11:39:41	PSAPPSRV.7929	7929	PSAPPSRV.7929 (0) [04/11/06 11:39:41](0) Cache Directory being used: /home/psft/PT8.48-805-I1/appserv/PSAPP1/CACHE/PSAP
10	04/11/06 11:39:42	PSAPPSRV.7929	7929	PSAPPSRV.7929 (0) [04/11/06 11:39:42](3) (PublishSubscribe): PubSubSystem::InitializeServer(): Initialization succeeded.
11	04/11/06 11:39:42	PSAPPSRV.7929	7929	PSAPPSRV.7929 (0) [04/11/06 11:39:42](0) Server started
16	04/11/06 12:09:20	PSAPPSRV.7925	7925	PSAPPSRV.7925 (1) [04/11/06 12:09:20 GetCertificate](3) Returning context. ID=PTWEBSERVER, Lang=ENG, UStreamId=120920 pgAAAAQDAgEBAAAAvAIAAAAAAAAAAAsAAAAABABTaGRyAk4AeQg4AC4AMQAwABTjzjuNx4g4ReylOR4tDw6GrBYQbGYAAAAFAF
17	04/11/06 12:09:22	PSAPPSRV.7929	7929	PSAPPSRV.7929 (1) [04/11/06 12:09:22 GetCertificate](3) Returning context. ID=PTWEBSERVER, Lang=ENG, UStreamId=120922 pgAAAAQDAgEBAAAAvAIAAAAAAAAAAAsAAAAABABTaGRyAk4AeQg4AC4AMQAwABT2Tq8isimNixKm+piQNQE1veY6G2YAAAAFAF
18	04/11/06 12:09:46	PSAPPSRV.7929	7929	PSAPPSRV.7929 (2) [04/11/06 12:09:46 GetCertificate](3) Returning context. ID=QEDMO, Lang=ENG, UStreamId=120946_7929_2_owAAAAQDAgEBAAAAvAIAAAAAAAAAAAsAAAAABABTaGRyAk4AbQg4AC4AMQAwABTcFXQ+HMSOoSyaKHK3/8rFG78ymMAAAAF
24	04/11/06 13:11:07	PSAPPSRV.1272	1272	PSAPPSRV.1272 (0) [04/11/06 13:11:07](0) PeopleTools Release 8.48-805-I1 (Linux) starting
25	04/11/06 13:11:07	PSAPPSRV.1272	1272	PSAPPSRV.1272 (0) [04/11/06 13:11:07](0) Cache Directory being used: /home/psft/PT8.48-805-I1/appserv/PSAPP1/CACHE/PSAP
26	04/11/06 13:11:09	PSAPPSRV.1272	1272	PSAPPSRV.1272 (0) [04/11/06 13:11:09](3) (PublishSubscribe): PubSubSystem::InitializeServer(): Initialization succeeded.
27	04/11/06 13:11:09	PSAPPSRV.1272	1272	PSAPPSRV.1272 (0) [04/11/06 13:11:09](0) Server started
28	04/11/06 13:11:10	PSAPPSRV.1284	1284	PSAPPSRV.1284 (0) [04/11/06 13:11:10](0) PeopleTools Release 8.48-805-I1 (Linux) starting
29	04/11/06 13:11:10	PSAPPSRV.1284	1284	PSAPPSRV.1284 (0) [04/11/06 13:11:10](0) Cache Directory being used: /home/psft/PT8.48-805-I1/appserv/PSAPP1/CACHE/PSAP
30	04/11/06 13:11:12	PSAPPSRV.1284	1284	PSAPPSRV.1284 (0) [04/11/06 13:11:12](3) (PublishSubscribe): PubSubSystem::InitializeServer(): Initialization succeeded.
31	04/11/06 13:11:12	PSAPPSRV.1284	1284	PSAPPSRV.1284 (0) [04/11/06 13:11:12](0) Server started

☒ Date and Time fields refer to the Date and Time log within the file and not the timestamp of the file.

Home | Performance | Administration | **Logs**

Home | **Targets** | Deployments | Alerts | Policies | Jobs | Reports | Setup | Preferences | Help | Logout

Copyright © 1996, 2006, Oracle. All rights reserved.
 Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.
[About Oracle Enterprise Manager](#)

PS Application Server Domain Log page

Select the Logs tab to display the Log Management page where you can view application logs and select other available features.

Note. CORE files cannot be viewed, exported locally, or searched against.

Viewing a Log File

To view a log file, click the log filename. The View Log File page appears.

View Log File : TUXLOG.041106

Path **/home/psft/PT8.48-805-11/appserv/PSAPP1/LOGS/**

Timestamp **Tue Apr 11 13:11:16 PDT 2006**

Page Refreshed **Apr 11, 2006 1:39:05 PM PDT** [Refresh](#)

[Export to file](#) [OK](#)

```

113921.psemgrid02ltmloadcf.7912.3086874304.-2: 04-11-2006: Tuxedo Version 8.1, 32-bit
113921.psemgrid02ltmloadcf.7912.3086874304.-2: CMDTUX_CAT:879: INFO: A new file system has been created. (size = 1048 512-byte blocks)
113921.psemgrid02ltmloadcf.7912.3086874304.-2: CMDTUX_CAT:871: INFO: TUXCONFIG file /home/psft/PT8.48-805-11/appserv/PSAPP1/PSTUXCFG has
been created
113927.psemgrid02IPADMIN.7863: Begin attempt on domain PSAPP1
113929.psemgrid02ltmadmin.7915.3086874304.-2: TMADMIN_CAT:1330: INFO: Command: boot -A
113931.psemgrid02ltmboot.7916.3086993088.-2: 04-11-2006: Tuxedo Version 8.1, 32-bit
113931.psemgrid02ltmboot.7916.3086993088.-2: CMDTUX_CAT:1851: INFO: TM_BOOTTIMEOUT is set to 60 seconds
113931.psemgrid02ltmboot.7916.3086993088.-2: CMDTUX_CAT:1855: INFO: TM_BOOTPRESUMEDFAIL option is selected
113933.psemgrid02IBBL.7917.3086993632.0: 04-11-2006: Tuxedo Version 8.1, 32-bit, Patch Level 175
113933.psemgrid02IBBL.7917.3086993632.0: LIBTUX_CAT:262: INFO: Standard main starting
113935.psemgrid02ltmboot.7918.3086874304.-2: 04-11-2006: Tuxedo Version 8.1, 32-bit
113935.psemgrid02ltmboot.7918.3086874304.-2: CMDTUX_CAT:1851: INFO: TM_BOOTTIMEOUT is set to 60 seconds
113935.psemgrid02ltmboot.7918.3086874304.-2: CMDTUX_CAT:1855: INFO: TM_BOOTPRESUMEDFAIL option is selected
113935.psemgrid02IPSWATCHSRV.7919.3086981344.-2: 04-11-2006: Tuxedo Version 8.1, 32-bit
113935.psemgrid02IPSWATCHSRV.7919.3086981344.-2: LIBTUX_CAT:262: INFO: Standard main starting
113937.psemgrid02IPSAPPSRV.7925.3086920448.0: 04-11-2006: Tuxedo Version 8.1, 32-bit
113937.psemgrid02IPSAPPSRV.7925.3086920448.0: LIBTUX_CAT:262: INFO: Standard main starting
113941.psemgrid02IPSAPPSRV.7929.3086920448.0: 04-11-2006: Tuxedo Version 8.1, 32-bit
113941.psemgrid02IPSAPPSRV.7929.3086920448.0: LIBTUX_CAT:262: INFO: Standard main starting
113943.psemgrid02IPSSAMSRV.7933.3086935744.0: 04-11-2006: Tuxedo Version 8.1, 32-bit
113943.psemgrid02IPSSAMSRV.7933.3086935744.0: LIBTUX_CAT:262: INFO: Standard main starting

```

[500 lines of the log file are displayed per page.](#)

[Export to file](#) [OK](#)

View Log File page

If you have searched for a string, you can also click the link by the line number or the string (in the results area) to display the View Log File page.

The initial view contains 500 lines and the string is the last one shown. Click Previous, Next, Top, or Bottom to navigate through the file.

The log filename is also available within the search results area.

Click Refresh to refresh the screen.

Exporting a Log File

To export the log file to your workstation, click Export to File on the View Log File page. Click OK to go back to the Log Management page.

Searching for Strings in a Log File

To search for a string in a log file, enter the desired search settings and click Search. When the string is found, the Log Management page appears with the results displayed in the lower part of the page. If needed, you can narrow the search criteria.

The log information displayed includes the line number in the log file in which the string is found, the date and time, the server process involved, and the phrase or sentence containing the string.

Host Log Alert Settings

To set a log alert, select Host, then Metric and Policy Setting in the Related Links region. From the Metric list, select Log File Pattern Matched Line Count and click Advanced Setting to adjust the patterns to be searched and their thresholds.

View the results by selecting Log File Alerts in the Related Links region in the homepage of the target's host.

Log Management Setup

The log management feature enables you to view PeopleSoft specific logs, traces or dumps for a target. You can also:

- Customize the type of log file patterns to manage.
- Schedule purge and archive of log files.

Click Log Management Setup in the Related Links region to display the Log Management Setup page where you can define the log file type to manage for each target. From this page you can also schedule purge and archive jobs.

ORACLE Enterprise Manager 10g Grid Control

Home Targets Deployments Alerts Policies Jobs Reports

Hosts | Databases | Application Servers | Web Applications | Services | Systems | Groups | All Targets | **PeopleSoft**

Log Management Setup: PS Application Server Domain: PSAPP1.app.psemgrid02.home_psft_PT848-805-I1

Home Performance Administration **Logs**

Log Patterns

These are the types of PeopleSoft logs for your target that you can manage. Add or Remove log types as necessary. OK

Remove | Add Schedule Purge and Archive Job

Select Log Paths and Patterns

- ☒ /home/psft/PT8.48-805-I1/appserv/PSAPP1/ULOG*. *
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/core
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/stderr
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/stdout
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/*. LOG
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/*. dmp
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/*. log
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/*. lp
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/*. mps
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/*. tracesql
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/*. trc
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/APPSRV_*. LOG
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/PS*
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/TUXLOG. *
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/peopletools_state*
- ☐ /home/psft/PT8.48-805-I1/appserv/PSAPP1/LOGS/process_state*
- ☐ /home/psft/PT8.48-805-I1/core
- ☐ /home/psft/PT8.48-805-I1/appserv/core

Remove | Add Schedule Purge and Archive Job

OK

Home Performance Administration **Logs**

Home | **Targets** | Deployments | Alerts | Policies | Jobs | Reports | Setup | Preferences | Help | Logout

Copyright © 1996, 2006, Oracle. All rights reserved.
 Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.
[About Oracle Enterprise Manager](#)

Log Management Setup page

Schedule Purge and Archive Jobs

To set up the schedule for a purge, click Schedule Purge and Archive Job. The Create PS Purge Archive Log Job page appears. From this page you can define the log patterns you want to purge, or archive and set a schedule.

General

Enter a name and description for the job. The targets available for a scheduled purge or archive are listed in the Targets region.

Parameters

Displays all of the log patterns being managed for a target. Select which log patterns to purge or archive.

The retention period is the length of time that the log file should be saved before being archived or purged. The default for purge is 7 days.

The remaining job options are standard Enterprise Manager features.

Chapter 3

Discovering PeopleSoft Targets

This section provides an overview and discusses how to:

- Add PeopleSoft targets.
- Register targets.

Understanding the Discovery Process

Discovery is the process of an agent identifying predefined target types, registering them in Enterprise Manager, and collecting their target properties and initial configuration data. The agent sends this data to the Oracle Management Service, which processes the data and loads it into the Management Repository. From there, Enterprise Manager can access data about the target to monitor and manage it.

Note. Discovery requires that you be assigned the role of a super administrator.

The following steps outline how to initiate the discovery of PeopleSoft targets:

- From the PeopleSoft subtab page, click Add PeopleSoft Targets, select the target types to be discovered. Specify the host, discovery path for PS_HOMEs, PS_CFG_HOMEs, and PIA_HOMEs, and subdirectory crawl depth.
- From the Target Credentials page, enter the user ID and password for the host where discovery executes.
- After discovery, register the specific target in Enterprise Manager.
- Enter the information required to connect to the PROCESSREQUEST web service.
- Identify and register the Process Monitor target.
- Set environment variables for platforms requiring them, and add a PeopleSoft application database (discovering a PS Application Database target).

See [Chapter 3, "Discovering PeopleSoft Targets," Registering Targets, page 32.](#)

Understanding Steps in the Discovery Process

The following steps outline how to initiate the discovery of PeopleSoft targets:

- From the PeopleSoft subtab page, click Add PeopleSoft Targets, select the target types to be discovered. Specify the host, discovery path for PS_HOMEs, PS_CFG_HOMEs, and PIA_HOMEs, and subdirectory crawl depth.

- From the Target Credentials page, enter the user ID and password for the host where discovery executes.
- After discovery, register the specific target in Enterprise Manager.
- Enter the information required to connect to the PROCESSREQUEST web service.
- Identify and register the Process Monitor target.
- Set environment variables for platforms requiring them, and add a PeopleSoft application database (discovering a PS Application Database target).

See [Chapter 3, "Discovering PeopleSoft Targets," Registering Targets, page 32.](#)

Understanding UNIX Login Shell Support

The PeopleSoft plug-in supports the login shell for the user who installed PeopleTools or created domains. This requires the user profile (.profile) to be set prior to discovery of PeopleSoft targets.

Login shell support provides these advantages:

- Automatic discovery of the PS Application Database.
- Setting environment variables for each Tuxedo-based domain is not required.
- Less environment related issues.

When considering using a login shell, consider the following:

- There is an additional step to create a user profile (if one does not exist).
- Only Bourne compatible shells (like sh, bash, and so on) are supported.
- Interactive login profiles are not supported

Adding PeopleSoft Targets

To begin discovery, select Targets, PeopleSoft. Click Add PeopleSoft Targets. The Add PeopleSoft Targets page appears:

ORACLE Enterprise Manager 10g
Grid Control

Hosts | Databases | Middleware | Web Applications | Services | Systems | Groups | All Targets | PeopleSoft

Home Targets Deployments Alerts Compliance Jobs Reports


Setup Preferences Help Logout

Add PeopleSoft Targets

This process will discover and register all valid PeopleSoft targets of your host in Enterprise Manager.

PeopleSoft Target Types

<input checked="" type="checkbox"/> PS_HOME/PS_CFG_HOME	<input checked="" type="checkbox"/> PS Search Server Domain
<input checked="" type="checkbox"/> PS Application Server Domain	<input checked="" type="checkbox"/> PS PIA and PS Web Site
<input checked="" type="checkbox"/> PS Process Scheduler Domain	

* Host 

* Discovery Path
Enter the fully-qualified path on the specified host. To include multiple paths, separate them with a semi-colon (;) e.g. c:\d\ UNC paths are not supported.

* Crawl Depth
Enter the number of directory levels deep that the discovery process should check. A large number may slow down the discovery process

☐ **Modify OS Group Permissions of PS_HOMEs**
This checkbox is applicable for PeopleTools 8.48 and 8.49. PeopleTools 8.50 and higher version comes with permission scripts and they need to be executed manually. If checked, Enterprise Manager will automatically change the group permissions. If unchecked, a script will be generated in the temp directory of the host that can be run independently by the system administrator. This is only available for UNIX and Linux based platforms

Add PeopleSoft Targets

From this page, you can select one or more target types for discovery within one host.

If you want to search for a host from which to discover targets, click the Host search icon to display the Select Host for Discovery page.

Select the appropriate host and click Select. Enter the remaining values on the Add PeopleSoft Targets page.

Note. The first discovery process should be run on a host containing any of the Tuxedo domain targets, which are PS Application Server, PS Process Scheduler, and PS Search Server Domains. The host should have the same time zone as the PS Application Database to which it's connected, and the same timezone of most of the other PeopleSoft servers or hosts. During this initial discovery, the system expects that the PS Application Database will be also be discovered.

The PeopleSoft Enterprise Manager Plug-in can monitor only PS Application Databases from Tuxedo domain targets that are in the same timezone. When the database is registered in Enterprise Manager, it must be the database of most of the Tuxedo domain targets.

For example, assume you have a PeopleSoft environment with four UNIX servers with PS Application Server domains in one timezone and one Windows server with a Process Scheduler domain in another timezone. You should execute the first discovery on one of the four UNIX servers. You should not execute the discovery first on the Windows server.

PeopleSoft Target Types

PS Target Types

All target types are selected by default. The PS_HOME target check box cannot be cleared because Enterprise Manager must discover it first. When the PS_HOME directory is found, the search continues for any PeopleSoft targets present (for example, an application server, web server, Process Scheduler, and so on).

A PS Web Site cannot be registered without a parent PS PIA target having been registered in a current or a previous discovery process.

Note. Beginning with PeopleTools 8.50, with decoupled PIA_HOMEs and PS_CFG_HOMEs, provide the path to PS_CFG_HOME or PIA_HOME. If PS_HOME is secure (read-only) it may not contain any targets. The discovery process will discover all the selected targets in the specified path.

Host

Select the host in which the target you want to discover reside.

Note. The list of host values only displays when Enterprise Manager agents have been installed and have been registered with the OMS.

By default, only hosts that have PeopleSoft installations are available. The system verifies that you have entered a valid host.

Discovery Path

Enter the paths from which the search (crawl) should begin. Separate multiple paths with a semicolon.

The path should include PS_HOME, PS_CFG_HOME, and PIA_HOME, (as appropriate for your installation). A path with spaces should be enclosed with double quotes. For example:

"c:\documents and settings\user\psft\pt\850"

Note. The discovery path does not support UNC mapping. The PeopleSoft Plug-in supports a remote/shared read-only PS_HOME (with a UNC path) for Windows (on PeopleTools 8.50 or later). PS_CFG_HOME should be a local folder and provided in the discovery path.

Note. When discovering PS PIA and PS Web Site targets in OAS, Enterprise Manager searches the directory structure of any existing OAS targets.

Crawl Depth

Specify the number of nested directories that an agent crawls during the discovery process. The default is 2. Crawl depth applies to each directory entered.

For example, if you specify a value of 3 and have more than one discovery path listed, the agent searches 3 levels in each directory.

Modify OS Group Permissions of PS_HOMEs

Allows the group of PS_HOMEs' user ID to read, write and execute permissions on all the PS_HOMEs that will be discovered. (Disabled in Windows).

- When the check box is selected, Enterprise Manager modifies the file system permission on discovered PS_HOMEs to:
 - User: read, write and execute
 - Group: read and execute
 - Other: read
 - UNIX: terms 754
- When the check box is not selected, a script is created in the <PS_HOME>/psem/permission.sh directory so that a system administrator can run the script manually.

Note. If you do not set the permissions correctly, Enterprise Manager cannot collect monitoring information and you may see unpredictable results.

Note. This option applies only to pre-PeopleTools 8.50 level targets, and applies only to UNIX and Linux based environments. PeopleTools 8.50 and higher versions come with permission scripts that need to be executed manually. If checked, Enterprise Manager will automatically change the group permissions. If unchecked, a script will be generated in the temp directory of the host that can be run independently by the system administrator.

Note. If Enterprise Manager detects any warnings during discovery, a Discovery Warnings link appears below the discovery results. Click the link to open a page that lists all the warnings encountered.

One common warning involves the psconfig.sh process being run before the Enterprise Manager agent has been started. In this case, discovery will be unsuccessful. The warning message instructs you to shut down the agent, restart it and then run psconfig.sh.

Using login shells can also cause issues during discovery (depending on the platform). You may need to set the profile correctly and restart the discovery process. If there are previous processes running then kill these before restarting the discovery process (kill <pid>, kill -9 <pid>).

Target Naming Conventions

Enterprise Manager requires that all discovered targets be assigned a unique name that serves as the target's key. The following table describes target naming conventions.

Target Type	Naming Convention	Example
PS Application Database	<DBName>+db.+<PeopleSoft GUID>	CRMPRD.db.66ce0b93-85bb-11d9-92af-fa37c30c4526 where DBName = CRMPRD, GUID = 66ce0b93-85bb-11d9-92af-fa37c30c4526

Target Type	Naming Convention	Example
PS Application Server Domain	<domain>+<app>+<host>+<PS_HOME>	CNVCRM.app.server1.usr_local where domain = CNVCRM Host = server1 PS_HOME = /usr/local
PS Process Scheduler Server Domain	<domain>+<prcs>+<host>+<PS_CFG_HOME>	CNVCRM.prcs.server1.usr_local
PS Search Server Domain	<domain>+<srch>+<host>+<PS_CFG_HOME>	CNVCRM.srch.server1.usr_local
PS PIA using Weblogic or WebSphere	<PIA domain name>+<pia>+<host>+<PS_HOME>	peoplesoft.pia.server1.usr_local where PIA domain name = peoplesoft
PS PIA using OAS	<domain>+<pia>+<host>+<OAS_ORA_HOME>	peoplesoft.pia.server1.usr_local_oas where OAS_ORA_HOME = /usr/local/oas
PS Web Sites using Weblogic or WebSphere	<site name.PIA domain name>+site+<host>+<PS_HOME>	ps.peoplesoft.site.server1.usr_local where site name = ps
PS Web Sites using OAS	<site name.PIA domain name>+site+<host>+WEBSERVER_ORA_HOME	ps.peoplesoft.site.server1.usr_local_oas
PS Process Monitor	prcs-mntr.<protocol>.<host>.<port>.<wsdl file name>	prcs-mntr.http.pta137.10180.PROCESSREQUEST_1_wsdl

Additional naming conventions:

- If the host name has the fully qualified DNS name, the name server1.peoplesoft.com becomes server1.
- A Windows path, for example C:\ptinstall\appserv, becomes c_ptinstall_appserver. Any dots (.) or colons (:) are removed, and backslashes (\) and spaces are replaced with an underscore (_).

Target Credentials

When you have entered all discovery values, click Next. The Credentials page appears.

Enter your operating system user name and password for the machine on which you want to run the discovery process. After your credentials are accepted, discovery begins. The screen displays the discovery processing message.

Registering Targets

After the discovery process completes, you must register the targets in Enterprise Manager.

The steps for registering targets are:

1. When discovery is finished, a page displays a list of the discovered PeopleSoft targets that are not yet registered in Enterprise Manager. Any targets previously discovered and registered are excluded from the list.

All listed targets are selected by default on the Add PeopleSoft Targets page. Clear any discovered targets that you do not want to register.

Note. A PS PIA target can be registered without a corresponding PS Web Site target. However, a PS Web Site target cannot be registered without also having a registered PS PIA (parent) target. To register a PS Process Monitor target, there must be a corresponding PS PIA target.

2. Click Next.

All targets selected are registered in Enterprise Manager. Their initial configuration values are collected and loaded into the repository.

The discovery process continues for the PS Application Databases.

Note. Before a PS Process Monitor target can be discovered, you need to configure the PROCESSREQUEST web service needs to be configured for use within Integration Broker and Process Scheduler.

See [Chapter 3, "Discovering PeopleSoft Targets," Adding and Registering PS Process Monitor Targets, page 37.](#)

3. The Add PeopleSoft Application Database page appears showing a list of targets for which environment variables may need to be set.

This step is optional with the PeopleTools 8.50 version of the PeopleSoft Plug-in. Verify that the user profile is correctly set with the required environment variables.

The list includes all PS Application Server Domains, PS Process Scheduler Domains, and PS Search Server Domains registered in Enterprise Manager in this or a previous discovery.

Set Environment Variables	Click to configure settings that enable connection to an application database—use this following your selection in the Select column.
Select	Check box to determine for which targets you want to allow editing of the environment variables.
Name	<p>Name of the PS Application Server Domain, Process Scheduler Domain, or PS Search Server Domain that can have a PS Application Database.</p> <p>This value displays as a hyperlink to the target homepage, which you can select to open in a new window.</p>
Target Type	The type of target being registered.
DB Type	The type of database to which the target is connecting.
Environment Set	<p>Shows a green check mark when environment variables have been set for the database (if required for a specific database type); shows a red X when environment variables have not been set.</p> <p>The environment variables referred to in this field are database connectivity parameters and vary depending on the database type.</p>
Databases Discovered	<p>Shows a green check mark when the application database is successfully discovered which means that Enterprise Manager can collect configuration data from the target and collect the PeopleSoft GUID from the application database.</p> <p>Shows a red X when discovery is unsuccessful. Possible reasons are:</p> <ul style="list-style-type: none"> • The environment variables have not been set correctly. Verify them on the Set Environment Variables page. • The database information is incorrect. Select the target to open it in a new window. Select the Administration tab, then Configure Domain to display configuration data. Validate database information here. • The configuration collection has failed. Select the hyperlink for the target in the Name column. The target homepage appears where you can check for metric collection errors displayed above the Alerts section.
Discover Related Databases	Click this icon to initiate discovery.

4. Click Next.

The green check mark indicates that the application database associated with that target is registered in Enterprise Manager.

Note. If you need to set environment variables, see the following section.

5. When prompted, click OK on confirmation pages. When finished, click Next.

The processing page for registering the specific application database appears. When complete, the system displays a page reporting the summary of discovery results.

6. The PeopleSoft subtab homepage appears showing the newly discovered targets.

Note. There is a difference between creating a target and adding a target. If you use the create feature, Enterprise Manager creates a new domain on the managed host. If you use the add feature (Add PeopleSoft Targets), Enterprise Manager searches for existing domains in the managed host that have not been registered in the Enterprise Manager.

Setting Environment Variables

Setting environment variables means specifying basic database connectivity parameters for the database type you are using. When you select Set Environment Variables for any target, the Set Environment Variables page appears showing two columns listing the required environment variables and corresponding values.

Note. Setting environment variable entries are applicable when the profile is not set for a login shell script.

After you have entered the values on the Set Environment Variables page, they are added to the Environment Variables list if they do not already exist. Therefore, based on the database type previously configured, the regions on this page may have tables prepopulated with the required environment variables.

<i>Database Type</i>	<i>Required Environment Variables</i>
Oracle	\$ORACLE_HOME
Informix	\$INFORMIXDIR \$INFORMIXSERVER
Sybase	\$SYBASE \$SYBASE_OCS
DB2OS390	\$DB2DIR \$DB2INSTANCE

Database Type	Required Environment Variables
DB2UNIX	<p>\$DB2DIR</p> <p>\$DB2INSTANCE</p> <p>Get the correct values of DB2DIR and DB2INSTANCE from the command console on the host machine. For example:</p> <pre>pt-ibm03:\$. ./psconfig.sh pt-ibm03:\$ echo \$DB2DIR /opt/IBM/db2/V9.1 pt-ibm03:\$ echo \$DB2INSTANCE db2udb9</pre>
Microsoft SQL Server	Entry of environment variables is not required. The default values from MSSQLSERVER are inserted.

Note. The environment variable values are not validated when you enter them. Furthermore, an agent does not inherit the environment variable values of the user initiating an action. For an action to be successful, values for environment variables must be set correctly.

By default, some environment variables appear on the Set Environment Variables page that displays during discovery (see table above), where you can set the values. However, other environment variables, such as LD_LIBRARY_PATH, PATH, SHLIB_PATH, and LIBPATH may also need to be set for each discovered domain.

If you have only one installed PeopleTools and Tuxedo version on a managed host machine, you can set environment variables for an agent prior to starting that agent. However, if you have multiple installed versions of PeopleTools or Tuxedo on a managed host machine, the environment variables must be set for each discovered domain as part of the discovery process.

When using a login shell script, the following variables are required to be defined in the \$HOME\.profile (similar to the table above).

- Common environment variables: LD_LIBRARY_PATH, PATH, SHLIB_PATH, LIBPATH
- Database-specific variables: ORACLE_HOME, ORACLE_SID, TNS_ADMIN, INFORMIXDIR, INFORMIXSERVER, SYBASE, SYBASE_OCS, DB2DIR, DB2INSTANCE
- Tuxedo: TUXDIR

Note. There are multiple ways to update \$HOME\.profile, the following is only an example.

To modify the \$HOME\.profile:

1. Start new telnet session as with the appropriate user ID (posft, emagent, and so on).
2. Select the correct values at the login prompt, database, SQR, COBOL, and so on.
3. Use <set> or <env> commands, retrieve the values of the necessary environment variables.
4. Update \$HOME/.profile with these environment variables, using the VAR=<value>; export VAR syntax.

5. Logout and log into a new telnet session as the same user ID and make sure you see a message indicating that a .profile exists.

For example:

```
WARNING: .profile exists, bypassing /etc/profile
```

The following example illustrates a sample .profile for a PeopleSoft user in a multiuser configuration:

```
TUXDIR="/tuxedo/prod/10gR3-j10gR3-64bit"; export TUXDIR
ORACLE_HOME="/products/oracle/10.2.0.1"; export ORACLE_HOME
ORACLE_SID="test10201"; export ORACLE_SID
TNS_ADMIN="/ds1/home/psoft"; export TNS_ADMIN
PATH="/ds1/home/psoft/pt/8.50-809-R1/jre/bin:$/jre/bin:/jre/prod/1.6.0/bin:/
bin:/sbin:/usr/
sbin:/usr/bin:/usr/local/bin:/usr/ccs/bin:/usr/local/etc:/usr/bin/
X11:/usr/ucb:./tuxedo/prod/
10gR3-j10gR3-64bit/bin:/cobol/prod/svrex-5.0_wp4-64bit/bin:/clrcase/
prod/7.0.1/bin:/products/oracle/
10.2.0.1/bin:/pt/bin:/pt/products/solaris-10-sparc/bin:/pt/products/
solaris-10-sparc/rational/bin:$/bin:
$/bin/sqr/ORA/bin:/ds1/home/psoft/pt/8.50-809-R1/bin:/ds1/home/psoft/
pt/8.50-809-R1/bin/sqr/ORA/
bin:/ds1/home/psoft/pt/8.50-809-R1/verity/solaris/_ssol26/bin"; export PATH
SHLIB_PATH="/lib:/usr/lib:/usr/local/lib:/usr/lib/X11:/tuxedo/prod/
10gR3-j10gR3-64bit/lib:/cobol/prod/
svrex-5.0_wp4-64bit/coblib:/products/oracle/10.2.0.1/lib32:/products/
oracle/10.2.0.1/lib:/pt/products/solaris-10-sparc/lib"; export SHLIB_PATH
LIBPATH="/lib:/usr/lib:/usr/local/lib:/usr/lib/X11:/tuxedo/prod/
10gR3-j10gR3-64bit/lib:/cobol/prod/
svrex-5.0_wp4-64bit/coblib:/products/oracle/10.2.0.1/lib32:/products/
oracle/10.2.0.1/lib:/pt/products/solaris-10-sparc/lib"; export LIBPATH
LD_LIBRARY_PATH="/ds1/home/psoft/pt/8.50-809-R1/jre/lib/sparcv9/
native_threads:/ds1/home/psoft/pt/
8.50-809-R1/jre/lib/sparcv9/server:/ds1/home/psoft/pt/8.50-809-R1/jre/
lib/sparcv9:/lib:/usr/lib:/usr/local/lib:/usr/lib/X11:/tuxedo/prod/
10gR3-j10gR3-64bit/lib:/cobol/prod/svrex-5.0_wp4-64bit/coblib:/
products/oracle/10.2.0.1/lib32:/products/oracle/10.2.0.1/lib:/pt/
products/solaris-10-sparc/lib:/ds1/home/psoft/pt/8.50-809-R1/
bin:/ds1/home/psoft/pt/8.50-809-R1/bin/interfacedrivers:/ds1/home/
psoft/pt/8.50-809-R1/bin/sqr/ORA/bin:/ds1/home/psoft/pt/8.50-809-R1/
optbin:/ds1/home/psoft/pt/8.50-809-R1/verity/solaris/_ssol26/bin:/products/
oracle/10.2.0.1/lib"; export LD_LIBRARY_PATH
```

Adding and Registering PS Process Monitor Targets

Before you can discover and register a PS Process Monitor target, at least one PS PIA target needs to be discovered, and the PROESSREQUEST web service must be published through the Integration Gateway.

You discover and register PS Process Monitor targets using:

- Add PeopleSoft Targets: Discovery Results page.
- Process Monitor Setup page.

The following information assumes that you have a working knowledge of PeopleSoft Integration Broker and have it configured in your environment.

Configuring PROCESSREQUEST Web Service

To configure the PROCESSREQUEST web service:

1. Configure Integration Broker for your environment.

Make sure to specify a *Secure Target Location*.
2. Select PeopleTools, Integration Broker, Integration Setup, Services, enter PROCESSREQUEST, and click Search.
3. Open each service operation and verify that Security Verification is set to one of the following:
 - *Encrypt/Digital Sign or SSL*
 - *Encrypt or SSL*
 - *Digital Sign or SSL*
 - *SSL*
4. Select PeopleTools, Integration Broker, Web Services, Provide Web Service, open PROCESSREQUEST on the Select Services page, and click Next.
5. On the Select Service Operations page, select Use Secure Target Location, (to create a secure end point address in WSDL), select all service operations, and click Next.
6. On the View WSDL page, click View WSDL to verify the generated WSDL, and click Next.
7. On the Specify Publishing page, click Finish, and copy the generated WSDL URL, which you will need when you discover and set up the PS Process Monitor target.
8. Configure the distribution agent.
 - a. Select PeopleTools, Process Scheduler, Report Nodes, select the Add a New Value tab,, enter *PRCSMNTRNODE*, and click Add.
 - b. Select Ftp/XCopy.
 - c. Enter the URL as *http://<host>:port/psreports/<site>*.
 - d. Enter Network Path as *\\host\psreports*.
 - e. Click Save.
9. Configure server definition.
 - a. Select PeopleTools, Process Scheduler, Servers.
 - b. Select the appropriate server (PSNT, PSUNIX, and so on).
 - c. Select the Distribution tab and enter Distribution Node Name as *PRCSMNTRNODE*.
 - d. Select the Transfer System Files to Report Repository check box.
 - e. Click Save.

Adding PS Process Monitor Targets From Discovery Results Page

During the typical discovery process, you have the option to add and register PS Process Monitor targets. The Add PS Process Monitor page can be launch only if a PS PIA target is discovered and selected.

Note. PeopleTools version for the PS PIA target must be at least PeopleTools 8.50.

Adding PS Process Monitor Targets From Process Monitor Setup Page

Access the Process Monitor Setup page by clicking a PS PIA target, selecting Administration, and clicking Process Monitor Setup (under Additional Utility).

If you did not add the PS Process Monitor target during the typical discovery process, you can use the Process Monitor Setup page.

Process Monitor Setup

Cancel

OK

This process will discover and register Process Monitor target in Enterprise Manager.

* PROCESSREQUEST WebService URL

* PS PIA Target

peoplesoft.pia.st-sun06.ds1_home_psoft_pt_850-809-R1

PS Application Credentials

* User ID

* Password

Cancel

OK

Home

|

Targets

|

Deployments

|

Alerts

|

Compliance

|

Jobs

|

Reports

|

Setup

|

Preferences

|

Help

|

Logout

Process Monitor Setup page

PS Process Monitor Configuration Variables

Using either method to add and register a PS Process Monitor target, you specify this required information:

PROCESSREQUEST WebService URL	<p>The Process Monitor target accesses the PeopleSoft system using a WSDL service managed by Integration Broker. Specify the URL for the WSDL file.</p> <p>http://host:port/ PSIGW/PeopleSoftServiceListeningConnector/<wsdl file name></p> <p>For example:</p> <p>http://pta123.bigcompany.com:10180/PSIGW/PeopleSoftServiceListeningConnector/PROCESSREQUEST.1.wsdl</p>
PS PIA Target	<p>Select the appropriate PIA installation.</p>
User ID/Password	<p>Enter the PeopleSoft user ID and password that the Process Monitor will use to access the PeopleSoft system.</p>

Chapter 4

PeopleSoft Application Database Targets

This chapter provides an overview and discusses:

- The PS Application Database homepage.
- PS Application Database configuration.

Understanding PeopleSoft Application Database Targets

The PeopleSoft Application Database target type refers to the database that contains the PeopleSoft application. The application database target type is not intended to manage the underlying database (RDBMS) itself. However, depending on your database type, Enterprise Manager may provide additional management and monitoring features.

If the database is Oracle, you can monitor and manage the database by selecting Targets, Database from the Enterprise Manager homepage.

Note. If you have backed up, and then restored a database, you must set the GUID in the database to blanks before attempting the discovery process.

To get the current value of the database GUID, execute the following SQL Statement:

```
select GUID from PSOPTIONS
```

Then, depending on your database syntax, execute the appropriate update statement to set the GUID column in PSOPTIONS to ''. For example:

```
update PSOPTIONS set GUID = ''
```

The PS Application Database Homepage

Select Targets, PeopleSoft, then click the application database link that you want to view. The PS Application Database homepage appears:

ORACLE Enterprise Manager 10g
Grid Control

Home **Targets** Deployments Alerts Policies Jobs Reports

Hosts | Databases | Application Servers | Web Applications | Services | Systems | Groups | All Targets | **PeopleSoft**

PS Application Database: Q8488012.db.5d8d1e70-9cce-11da-bebd-9bb0dac1bfcc

Page Refreshed **Mar 24, 2006 12:11:17 PM PST**

Home Configuration

General

 Status **Up** Black Out
Availability (%) **100**
(Last 24 Hours)
Database Name **Q8488012**
Database Type **MICROSFT**
PeopleTools Version **8.48-801.3**
PeopleSoft System **N/A**

Alerts

Metric	Severity	Alert Triggered	Last Value	Last Checked
No Alerts found.				

Related Links

Monitoring Configuration	All Metrics	Metric and Policy Settings
Alert History	Blackouts	Reports
Access	Target Properties	

Home Configuration

PS Application Database homepage

Fields listed in the General section are:

- Status
- Availability
- Database Name
- Database Type
- PeopleTools Version
- PeopleTools System

Links listed in the Related Links section are:

- Monitoring Configuration
- Alert History
- Access
- All Metrics
- Blackouts
- Target Properties
- Metric and Policy Settings
- Reports

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Common Elements on Homepages, page 13.](#)

The PS Application Database Configuration Page

This page shows standard configuration properties of the application database, such as release version, database name and type, and so on. It also displays the PeopleSoft application patches applied to this database.

Chapter 5

PS Application Server Domain Targets

This chapter discusses:


- The PS Application Server Domain homepage.
- How to create PS application server domains.
- PS application server domain performance.
- PS application server domain administration.
- PS application server domain logs.

The PS Application Server Domain Homepage

This target type enables an administrator to manage PeopleSoft application server domains.

Note. Many of the features and concepts in this section are described in *Enterprise PeopleSoft PeopleTools: System and Server Administration*.

Select Targets, PeopleSoft, then click the specific application server that you want to view.



PS Application Server Domain homepage

Fields listed in the General section are:

- Status
- Availability
- Domain
- PS_HOME
- PS_CFG_HOME
- PS Application Database
- PS Search Server
- PeopleTools Version
- Application Release
- PeopleSoft System
- Operating System
- IP Address
- Host

Links listed in the Related Links section are:

- Monitoring Configuration
- Alert History
- Access
- All Metrics
- Blackouts

- Target Properties
- Metric and Policy Settings
- Reports

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Common Elements on Homepages, page 13.](#)

Creating PS Application Server Domain Targets

This section discusses how to create an application server domain target in Enterprise Manager.

Note. You must have a super administrator account to create new application server domains.

There are predefined configuration templates based on the number of concurrent users expected to connect to the domain. The following provides a *general* guideline:

- Small (1-50 users)
- Medium (50-500 users)
- Large (500-1000 users)
- Developer (for a development or test system)

Note. You must set the correct environment variables for new domains created within Enterprise Manager. Refer to the section describing how to set environment variables.

See [Chapter 3, "Discovering PeopleSoft Targets," Setting Environment Variables, page 35.](#)

To create a PS Application Server Domain target:

1. Select Targets, PeopleSoft.
2. Select the value from the Create drop-down list, then click Go.

The Create PS Application Server Domain page appears.

3. Enter the appropriate values and select the desired check boxes, then click OK.

A processing page appears. You cannot abort this process and must wait for the process to finish.

4. If you do not import the configuration from a file, click OK.

The domain will be created without a configuration. You can configure the domain at a later time by selecting the Configure Domain link from the Administration tab of the target.





Depending on the options that you selected when creating the domain, any one of the following pages appear next, the:

- Configure Domain page.
- Administration page of the PS Application Server Domain that you just created.

- Homepage of the PS Application Server Domain that you just created.

Create PS Application Server Domain

Properties

Name	Value
* Domain	<input type="text" value="tsawyer1"/>
* Host <input checked="" type="checkbox"/> Case sensitive.	<input type="text" value="st-sun06"/> 
* PS_HOME	<input type="text" value="/ds1/home/psoft/pt/8.50-809-R1"/> 
	Existing <input type="text" value="/ds1/home/psoft/psft/pt/8.50-809-R1"/> 
PS_CFG_HOME	New <input type="text"/> <input type="checkbox"/> Same as PS_HOME
* Configuration Template	<input type="text" value="small"/> 

☒ Configure Domain

☐ Import Domain from Configuration File

☐ Import IB Master Domain from Configuration File

* Filename in Host

Create PS Application Server Domain page

Properties

- Domain Name

Enter a unique name (within the host) not greater than 8 characters and not containing any spaces or punctuations.
- Host

Click the icon to display the Host Target selection window and select the host where you want to create the domain.
- PS_HOME

Based on the host, the available list is limited to the PS_HOMEs on the host that contain the software necessary to create a domain.

You can discover additional PS_HOMEs to augment this list. If you click Discover PS_HOMEs in the Related Links region of this page, the Add PeopleSoft Targets page with the PS_HOMEs check box selected appears. Continue through the discovery process, when finished, control returns to this page.
- PS_CFG_HOME

Specify the location of PS_CFG_HOME.

 - Existing: To use an existing PS_CFG_HOME location, select the value from the drop-down list.
 - New: To enter a new location (as opposed to using the existing location) enter that value in the New field.
 - Same as PS_HOME: To install the PS_CFG_HOME within the PS_HOME location, select this checkbox and the system automatically populates the New field with the specified PS_HOME.

Configuration Template	<p>Select a template from the drop-down list.</p> <p>(Optional) Click Get Latest Configuration Templates in the Related Links region of this page to retrieve the latest template list from the host. You are required to enter your credentials in a subsequent page to connect with a managed host.</p> <p>The configuration template you select determines the default values of the domain.</p>
Configure Domain	<p>Default selection is to configure the domain. If selected, the Configure Domain page appears after the domain is created.</p>
Import Domain Configuration from file	<p>Select to enable the entry of the filename and path of the host's configuration file.</p> <p>Ensure that the source configuration file resides in the host or an error appears during the create process. Use the Find icon to verify the path or to populate this field by selecting the path to the file.</p> <p>The Browse and Select: File and Directory page opens in a separate browser. Select folders to drill down further until the desired file is found. Select the file and click Select.</p>
Import IB Master Domain from Configuration File	<p>For Integration Broker environments, you can implement master-slave configurations with the Integration Broker server domains. Select this option to import previously configured master domain configurations.</p> <p><i>See Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Integration Broker Administration</i></p>

Related Links

Discover PS_HOMEs	Select to open the Add PeopleSoft Targets page.
Manage PS_HOMEs	Select to open the Manage PS_HOMEs page where you can remove PS_HOMEs and PS_CFG_HOMEs from the Enterprise Manager repository.
Get Latest Configuration Template	Select to get the latest configuration template. Enter your credentials when prompted.

PS Application Server Domain Performance

The Performance tab shows a graphical view of the domain host's CPU, memory utilization, disk read/write frequency for the drive where the application logs reside, number of queued processes for PSAPPSRV, BROKER, SUBSCRIBER, and PUBLISHER, number of PSAPPSRV handlers spawned and total number of Tuxedo connections. You can select the time frame for which you want to view performance data.

If the PUBSUB feature is not active, the graphs for Broker, Subscriber, and Publisher are blank.

Click Performance to display the PS Application Server Domain Performance page.



PS Application Server Domain Performance page

The CPU and memory utilization shown on the PS Application Server Domain Performance page includes more detailed information than that on the homepage.

The frequency of the disk read/write indicates how much the application server is caching—this value may affect the performance of the application.

The amount of queuing on the main processes of a PS application server indicates if the defined handlers are sufficient for the domain. Greater queuing causes a slow response on application functions.

Note. A statement of no data found may appear in the graphic region. This occurs because there is no target data available in Enterprise Manager when this graph is rendered.

For more information about changing the view of performance data, see Enterprise Manager documentation.

PS Application Server Domain Administration

Most of the tasks available on the Administration page correspond to menu items in PSADMIN.

Select Administration to display the PS Application Server Domain Administration page.

Note. The links displayed on this page depend upon the target privileges associated with the user. All links are available to a super administrator account, or a user assigned full privileges *and* Add Target System privilege on this target. Users with operator or view target privileges will have fewer number of links available.

If a link appears available it does not mean that a particular user has automatic access to that action. Host credentials are still required for certain actions to execute on the target.

The screenshot displays the Oracle Enterprise Manager 10g Grid Control interface. The top navigation bar includes links for Setup, Preferences, Help, and Logout. Below this, a secondary navigation bar shows Home, Targets, Deployments, Alerts, Policies, Jobs, and Reports. The main content area is titled "PS Application Server Domain: PSAPP3.app.psemgrid02.home_psft_PT848-805-l1" and shows a page refresh timestamp of Apr 11, 2006 1:55:05 PM PDT. The interface is divided into four main sections: Configuration Management, Tuxedo Management, Domain Management, and Additional Utilities. Configuration Management includes links for Configure Domain, Create Like Domain, Compare Domain Configurations, Compare To Multiple Configurations (Jobs), Last Collected Configuration, View Saved Configurations, History, and Copy Configuration. Tuxedo Management includes links for Access Tuxedo Command Line (TMADMIN), Process Status, Client Status, and Queue Status. Domain Management includes links for Start Domain, Start Domain (Parallel), Stop Domain, Stop Domain (Forced), Purge/Archive Cache, Delete Domain, Preload File Cache, Clean IPC Resources, and Messaging Server. Additional Utilities includes a link for Execute Host Command. The bottom navigation bar shows Home, Performance, Administration, and Logs.

PS Application Server Domain Administration page

Configuration Management links that appear on this page:

- Configure Domain



Information icon that appears next to certain fields on the Configure Domain page. To display a description of the field, move your mouse over the icon.



Dynamic icon that appears next to certain fields on the Configure Domain page. Indicates the field is dynamic and does not require a domain restart of the domain if the field was changed. The allow dynamic changes option must be selected.

- Create Like Domain
- Compare Domain Configurations
- Compare to Multiple Configurations (Jobs)
- Last Collected Configuration
- View Saved Configuration
- History
- Copy Configuration

Domain Management links that appear on this page:

- Start Domain

- Start Domain (Parallel)
- Stop Domain
- Stop Domain (Forced)
- Purge/Archive Cache
- Delete Domain
- Preload File Cache
- Clean IPC Resources
- Messaging Server

Tuxedo Management links that appear on this page:

- Access Tuxedo Command Line (TMADMIN)
- Process Status
- Client Status
- Queue Status

Additional Utilities links that appear on this page:

- Execute Host Command
- Windows Service Management (Available only for targets that have a Windows host).

PS Application Server Domain Logs

The PS Application Server Domain log feature enables you to view PeopleSoft-specific logs, traces or dumps for a target. In addition, you can search the log for string patterns, schedule a purge and archive job, and export log files to your workstation. Host credentials are required for this page to display.

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Target Log Management, page 20.](#)

Chapter 6

PS Process Scheduler Domain Targets


This chapter discusses:

- The PS Process Scheduler Domain homepage
- How to create a PS Process Scheduler Domain target
- PS Process Scheduler Domain performance
- PS Process Scheduler Domain administration
- PS Process Scheduler Domain logs
- How to manage a Process Scheduler in PIA

The PS Process Scheduler Domain Homepage

You access and use the PS Process Scheduler Domain homepage in the same way that you access and use the PS Application Server Domain homepage. Minor differences include labels and alerts that are specific to a Process Scheduler domain.

Select Targets, PeopleSoft, then select the desired PS Process Scheduler Domain target.



PS Process Scheduler Domain Homepage

Fields listed in the General section are:

- Status
- Availability
- Domain
- PS_HOME
- PS_CFG_HOME
- PS Application Database
- PeopleTools Version
- Application Release
- PeopleSoft System
- Operating System
- IP Address
- Host

Links listed in the Related Links section are:

- Monitoring Configuration
- Alert History
- Access
- All Metrics
- Blackouts
- Target Properties

- Metric and Policy Settings
- Reports
- Open Telnet Session (Available only for targets that have a UNIX-based host)

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Common Elements on Homepages, page 13.](#)

Creating PS Process Scheduler Domain Targets

You create a PS Process Scheduler domain in the same way that you create a PS Application Server domain.

See [Chapter 5, "PS Application Server Domain Targets," Creating PS Application Server Domain Targets, page 47.](#)

PS Process Scheduler Domain Performance

The PS Process Scheduler Domain Performance page shows data that is similar to the PS Application Server Domain target.

Graphs shown on this page include the host CPU usage, host memory usage, PSPRCSRV, and PSDSTSRV queued processes.

See [Chapter 5, "PS Application Server Domain Targets," PS Application Server Domain Performance, page 49.](#)

PS Process Scheduler Domain Administration

Select Administration to display the PS Process Scheduler Server Domain Administration page.

The screenshot displays the Oracle Enterprise Manager 10g Grid Control interface. At the top, the Oracle logo and 'Enterprise Manager 10g Grid Control' are visible. A navigation bar includes links for Home, Targets, Deployments, Alerts, Policies, Jobs, Reports, Setup, Preferences, Help, and Logout. Below this, a breadcrumb trail shows Hosts | Databases | Application Servers | Web Applications | Services | Systems | Groups | All Targets | PeopleSoft. The main title is 'PS Process Scheduler Domain: P8488041.prcs.psemgrid02.home_psft_PT848-805-l1'. A status bar indicates 'Page Refreshed Apr 11, 2006 1:51:23 PM PDT'. The 'Administration' tab is selected, showing four sections: Configuration Management, Tuxedo Management, Domain Management, and Additional Utilities. Configuration Management includes links for Configure Domain, Create Like Domain, Compare Domain Configurations, Compare To Multiple Configurations (Jobs), Last Collected Configuration, View Saved Configurations, History, and Copy Configuration. Tuxedo Management includes Process Status and Queue Status. Domain Management includes Start Domain, Stop Domain, Stop Domain (Forced), Clean IPC Resources, Delete Domain, and Manage Process Scheduler In PIA. Additional Utilities includes Execute Host Command. A secondary navigation bar at the bottom shows Home | Targets | Deployments | Alerts | Policies | Jobs | Reports | Setup | Preferences | Help | Logout.

PS Process Scheduler Domain Administration page

Configuration Management links that appear on this page:

- [Configure Domain](#)
- [Create Like Domain](#)
- [Compare Domain Configurations](#)
- [Compare to Multiple Configurations \(Jobs\)](#)
- [Last Collected Configuration](#)
- [View Saved Configuration](#)
- [History](#)
- [Copy Configuration](#)

Domain Management links that appear on this page:

- [Start Domain](#)
- [Stop Domain](#)
- [Stop Domain \(Forced\)](#)
- [Clean IPC Resources](#)
- [Delete Domain](#)
- [Manage Process Scheduler in PIA](#)

Tuxedo Management links that appear on this page:

- Process Status
- Queue Status

Additional Utilities link that appears on this page is Execute Host Command.

Note. Windows Service Management link is available if the target's host is Windows.

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Target Administration Pages, page 14.](#)

Managing a Process Scheduler in PIA

You can manage several Process Scheduler configurations in PIA. For example, you can:

- Schedule specific processes
- Monitor processes with Process Monitor
- Run Application Engine programs

Select Administration, Manage Process Scheduler in PIA. A browser page opens showing the PIA login page. After you have successfully logged in, the Process Scheduler Administration page displays. (You should have previously defined the Process Scheduler URL in the PeopleSoft System URL Setup page).

See [Chapter 10, "PeopleSoft Systems and Services," PeopleSoft System URLs, page 87.](#)

PS Process Scheduler Domain Logs

The PS Process Scheduler Domain log feature is the same as in the PS Application Server Domain.

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Target Log Management, page 20.](#)

Chapter 7

PS Process Monitor Targets

This chapter discusses

- The PS Process Monitor homepage.
- PS Process Monitor performance.
- PS Process Monitor administration.
- Scheduling processes.
- Monitoring processes.

The PS Process Monitor Homepage

The PS Process Monitor homepage enables you to view and access PS Process Monitor information. For *Process Scheduler* information, access the PS Process Scheduler Domain homepage.

Select Targets, PeopleSoft, then select the desired PS Process Monitor target.

ORACLE Enterprise Manager 10g
Grid Control

Home Targets Deployments Alerts Compliance Jobs Reports


Hosts | Databases | Middleware | Web Applications | Services | Systems | Groups | All Targets | PeopleSoft

PS Process Monitor: prcs-mntr.http.pta137.10180.PROCESSREQUEST_1_wsdl


Page Refreshed Jun 30, 2009 6:19:39 AM PDT (Refresh)

Home Performance Administration

General


 Status **Up** (Process Monitor)
 Availability (%) **100** (Schedule Process)
 (Last 24 Hours)
 PS PIA [peoplesoft.pia.st-sun06.ds1.home_psoft.pt.850-809-R1](#)
 PROCESSREQUEST WebService URL [http://pta137.dsi-inet.peoplesoft.com:10180/PSIGW...](#)
 PeopleSoft System **N/A**
 Operating System **SunOS 5.10 Generic_120011-12 (64-bit)**
 IP Address **10.138.173.37**
 Host **st-sun06**

PS Process Count




■ Fail Count
 ■ Success Count
 ■ Run Count

Alerts

Metric	Severity	Message	Alert Triggered	Last Value	Last Checked
No Alerts found.					

Host Alerts

Metric	Severity	Message	Alert Triggered	Last Value	Last Checked
Filesystem Space Available (%) for /ds1		Filesystem /ds1 has 10.57% available space, fallen below warning (20) or critical (5) thre...	Jun 1, 2009 12:26:08 AM	7.01	Jun 30, 2009 10:44:45 AM

Related Links

Monitoring Configuration Alert History Access	All Metrics Blackouts Target Properties	Metric and Policy Settings Reports
---	---	---

PS Process Monitor homepage

Fields listed in the General section are:

- Status
- Availability
- PS PIA
- PROCESSREQUEST WebService URL
- PeopleSoft System
- Operating System
- IP Address
- Host

Links listed in the Related Links section are:

- Monitoring Configuration
- Alert History
- Access
- All Metrics
- Blackouts
- Target Properties
- Metric and Policy Settings
- Reports

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Common Elements on Homepages, page 13.](#)

PS Process Monitor Performance

Select Performance to monitor PS Process Monitor performance. The PS Process Monitor performance page shows these metrics to help you monitor the status of submitted process requests:

- Success Count: The number of processes completed successfully in the last hour.
- Fail Count: The number of processes failed in the last hour.
- Run Count: The total number of processes run in the last hour.

PS Process Monitor Administration

Select Administration for access to administrator tools and utilities relevant to PS Process Monitor management.



PS Process Monitor Administration page

The Configuration Management links that appear on this page are:

- Compare Configurations
- Compare to Multiple Configurations
- Last Collected Configuration
- View Saved Configuration
- History

The PS Process Management links that appear on this page are:

- Process Monitor
- Schedule Process

The Additional Utility link appearing on this page is Execute Host Command.

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Common Elements on Administration Pages, page 15.](#)

Scheduling Processes

PeopleSoft Enterprise Environment Management Plug-in for Oracle Enterprise Manager enables you to submit process requests to be run on the Process Scheduler server, just as you would from the PIA interface. The same fields and controls you use to submit process requests in PIA are available in the Oracle Enterprise Manager interface.

Note. This documentation assumes you have a working knowledge of scheduling processes to run within PeopleSoft systems.

ORACLE Enterprise Manager 10g
Grid Control

Home Targets Deployments Alerts Compliance Jobs Reports Setup Preferences Help Logout

Schedule Process Cancel OK

Schedule Info

*Run Control ID TSAWYER

Server Name PSNT Recurrence M-F at 5pm

Run Date 2009-07-06 Run Time HH.MM:SSAM/PM

Time Zone EST

Process Info

*Process Type SQR Report *Process Name PTSQRTST Set Runtime Parameter

PS Application Credentials

*User ID QEDMO *Password ***** Cancel OK

Related Links
Process Monitor

Home | Targets | Deployments | Alerts | Compliance | Jobs | Reports | Setup | Preferences | Help | Logout

Schedule Process page

To submit a process request from Oracle Enterprise Manager:

1. From the PS Process Monitor Administration page, select Schedule Process.
2. On the Schedule Process page, select all applicable values in the Schedule Info section, such as Run Control ID, Server Name, and so on.
3. In the Process Info section, select the process to run and any necessary runtime parameters.
 - a. Click the lookup prompt (flashlight) to open the Select Process Type and Process Name page, where you select the Process Type, click Go, and select the desired Process Name from the search results.
 - b. To set any runtime parameters, click the Set Runtime Parameter button.
4. In the PS Application Credentials section, enter the PeopleSoft user ID and password required to submit the process.

Note. The default credentials will be those provided during the discovery and setup process.

Monitoring Processes

PeopleSoft Enterprise Environment Management Plug-in for Oracle Enterprise Manager enables you to monitor process that have been submitted to run on the Process Scheduler server by displaying the Process List and Process Details interfaces. The same fields and controls you use to monitor process requests in PIA are available in the Oracle Enterprise Manager interface.

Note. This documentation assumes you have a working knowledge of monitoring processes to run within PeopleSoft systems.

ORACLE Enterprise Manager 10g Grid Control

Home | Targets | Deployments | Alerts | Compliance | Jobs | Reports | Setup | Preferences | Help | Logout

Process Monitor Cancel Prompt Refresh

Search Info

Process Type: Application Engine Process Name:

Process Instance: From To Server Name: PSNT

Last 30 Days Run Status: Success

Distribution Status: Posting

PS Application Credentials

*User ID: QEDMO *Password:

Search Clear

Search Results

Instance	Process Type	Process Name	User	Run Date/Time	Run Status	Distribution Status
9	Application Engine	PSXPARCHATTR	QEDMO	06/15/2009 02:45:34AM PDT	Success	Posting
12	Application Engine	PSXPARCHATTR	QEDMO	06/16/2009 01:01:07AM PDT	Success	Posting
10	Application Engine	AEMINTEST	QEDMO	06/15/2009 11:23:45PM PDT	Success	Posting
16	Application Engine	AEMINTEST	QEDMO	06/16/2009 03:23:55AM PDT	Success	Posting
8	Application Engine	PRCSYSPURGE	QEDMO	06/15/2009 02:44:10AM PDT	Success	Posting
11	Application Engine	PRCSYSPURGE	QEDMO	06/16/2009 01:00:54AM PDT	Success	Posting

Related Links
Schedule Process

Home | Targets | Deployments | Alerts | Compliance | Jobs | Reports | Setup | Preferences | Help | Logout

Process Monitor page

To monitor processes from Oracle Enterprise Manager:

1. From the PS Process Monitor Administration page, select Process Monitor.
2. On the Process Monitor page, in the Search Info section, enter the criteria for the processes you want to monitor, refining the search as needed.
3. In the PS Application Credentials section, enter the PeopleSoft user ID and password required to access the process list.

Note. The default credentials will be those provided during the discovery and setup process.

4. Click Search.
5. View the processes in the Search Results list.

To view the process details:

1. Locate an individual process in the process list.
2. Click the link in the Instance column.

- 3. Review process details.
- 4. (If needed) In the Update Process section, select any applicable options.
- 5. Click OK.

ORACLE Enterprise Manager 10g
Grid Control

HomeTargetsDeploymentsAlertsComplianceJobsReportsSetupPreferencesHelpLogout

Process Detail

CancelOK

Process Info

Process Instance	16	Process Type	Application Engine
Process Name	AEMINITEST	Run Status	Success
Distribution Status	Posting		

Run Info

Run Control ID	aj_test	Recurrence	
Server Name	PSNT		

Date/Time

Request Created On	06/16/2009 03:23:55AM PDT	Run Any Time After	06/16/2009 03:23:55AM PDT
Began Process At	06/16/2009 03:24:21AM PDT	Ended Process At	06/16/2009 03:24:36AM PDT

Update Process

☐ Hold Request☐ Queue Request☐ Cancel Request☒ Delete Request☐ Restart Request

CancelOK

Related Links

Process MonitorSchedule Process

Home | Targets | Deployments | Alerts | Compliance | Jobs | Reports | Setup | Preferences | Help | Logout

Process Detail page

Chapter 8

PS PIA and PS Web Site Targets

This chapter discusses:

- PS PIA targets
- PS Web Site targets

PS PIA Targets


This section discusses:

- The PS PIA homepage
- PS PIA target performance
- PS PIA target administration
- PS PIA target logs

The PS PIA Homepage

The PS PIA target acts as a container for one or more PS Web Site targets and together they are a PeopleSoft web server.

Select Targets, PeopleSoft, then select the desired PS PIA target.



PS PIA Homepage

The PS PIA target can be compared to a *domain* in Weblogic, a *server* in WebSphere, and an *application/OC4J* in OAS.

Note. Before attempting to discover or access a PS PIA and PS Web Site in Enterprise Manager, verify that your PeopleSoft application is running and that you can log in from a PIA page.

Fields listed in the General section are:

- Status
 - In Weblogic, represents the aggregate status of the different servers in a clustered environment. Up displays if there is at least one server in the cluster that is up; otherwise, a down displays. The Weblogic administration server must be running to retrieve an accurate status of the managed servers and for start or stop operation.
 - In OAS, the OPMN service must be up and running for an accurate retrieval of PS PIA status and for start or stop operation.
 - Start and Stop—By default these buttons call the delivered PeopleSoft start and stop scripts. However you can use customized scripts registered in Enterprise Manager. Customized scripts are important when the PeopleSoft web server architecture involves a cluster.
- Availability
- Name
- HTTP Port
- HTTPS Port
- PS_HOME/PIA_HOME
- Web Sites
- Web Server

- Reverse Proxy

A value of yes means that PS PIA is connected to a reverse proxy server.

See *Enterprise PeopleTools PeopleBook: Portal Technology*, "Understanding Reverse Proxy Servers"

See *Enterprise PeopleTools PeopleBook: System and Server Administration*: "Working with <Your Web Server>," Setting Up Reverse Proxy Servers

- PeopleTools Version
- PeopleSoft System
- Operating System
- IP Address
- Host

Links listed in the Related Links section are:

- Monitoring Configuration
- Alert History
- Access
- All Metrics
- Blackouts
- Target Properties
- Metric and Policy Settings
- Reports

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Common Elements on Homepages, page 13.](#)

PS PIA Target Performance

Select Performance to view metric data for the Host CPU Utilization and Host Memory Utilization.

See [Chapter 5, "PS Application Server Domain Targets," PS Application Server Domain Performance, page 49.](#)

PS PIA Target Administration

Select Administration for access to administrator tools and utilities relevant to PS PIA management.

PS PIA: peoplesoft.pia.st-sun06.ds1_home_psoft_pt_850-809-R1

Home	Performance	Administration	Logs
Configuration Management Edit setEnv.sh Edit web.xml Compare Configurations Compare To Multiple Configurations (Jobs) Last Collected Configuration View Saved Configurations History			Additional Utility Execute Host Command Customize Start/Stop Scripts Process Monitor Setup
PIA Management Start PIA Stop PIA Weblogic Console			

PS PIA Administration page

Configuration Management links that appear on this page:

- The first link varies depending on the target's web server type. Edit setEnv.cmd (Weblogic on Windows platform), Edit setEnv.sh (UNIX), Edit server.xml (WebSphere), or Edit opmn.xml (OAS).
- Edit web.xml
- Compare Configurations
- Compare to Multiple Configurations (Jobs)
- Last Collected Configuration
- View Saved Configuration
- History

PIA Management links that appear on this page:

- Start PIA
- Stop PIA
- Weblogic Console/WebSphere Administration Console/(iAS) Console (depends on web server type)

Additional Utilities links that appear on this page:

- Execute Host Command
- Customize Start/Stop Scripts
- Process Monitor Setup.

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Target Administration Pages, page 14.](#)

PS PIA Target Logs

The PS PIA Log page has the same features as the PS Application Server Domain Log page except that trace files are not supported in PS PIA.

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Target Log Management, page 20.](#)

PS Web Site Targets

This section discusses:


- The PS Web Site homepage
- PS Web Site performance
- PS Web Site administration

PS Web Site targets comprise the second part of a PeopleSoft web server. This level contains all of the PS PIA settings and files; hence, a PS Web Site target requires a tandem PS PIA target in order to be activated. There can be one or multiple sites attached to a PS PIA target. The PS Web Site's key role is configuration.

To access the PS Web Site target type, select Targets, PeopleSoft and select a PS Web Site target.

The PS Web Site Homepage

The PS Web Site homepage shows basic information for a web site. Select Targets, PeopleSoft, and select the desired PS Web Site target. The PS Web Site homepage appears.



PS Web Site Homepage

Fields listed in the General section are:

- Status

The status shown on this page reflects the status of the parent PS PIA.

You cannot perform stop or start from this page—you must do that on the PS PIA target page.

- Availability
- Site Name
- PS_HOME/PIA_HOME
- PS PIA
- PeopleTools Version
- PeopleSoft System
- Operating System
- IP Address
- Host

Links listed in the Related Links section are:

- Monitoring Configuration
- Alert History
- Access
- All Metrics
- Blackouts
- Target Properties
- Metric and Policy Settings
- Reports

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Common Elements on Homepages, page 13.](#)

PS Web Site Performance

The graphs and metrics displayed on the Performance page are similar to that of PS PIA showing the CPU and memory utilization of the host.

See [Chapter 8, "PS PIA and PS Web Site Targets," PS PIA Target Performance, page 69.](#)

PS Web Site Administration

Select Administration to display the PS Web Site Administration page.

ORACLE Enterprise Manager 10g
Grid Control

Home Targets Deployments Alerts Policies Jobs Reports

Hosts | Databases | Application Servers | Web Applications | Services | Systems | Groups | All Targets | PeopleSoft

PS Web Site: ps1Lnx.PSWEB1.site.psemgrid02.home_psft_PT848-805-11

Page Refreshed Apr 11, 2006 2:20:46 PM PDT

Home Performance Administration

Configuration Management

- [Configure Site](#)
- [Web Profile](#)
- [Integration Broker](#)
- [Compare Configurations](#)
- [Compare To Multiple Configurations \(Jobs\)](#)
- [Last Collected Configuration](#)
- [View Saved Configurations](#)
- [History](#)

Additional Utility

- [PIA Signon](#)

Home Performance Administration

Home | Targets | Deployments | Alerts | Policies | Jobs | Reports | Setup | Preferences | Help | Logout

PS Web Site Administration page

Configuration Management links that appear on this page:

- [Configure Site](#)
- [Web Profile](#)
- [Integration Broker](#)
- [Compare Configurations](#)
- [Compare to Multiple Configurations \(Jobs\)](#)
- [Last Collected Configuration](#)
- [View Saved Configuration](#)
- [History](#)

Additional Utilities link that appears on this page is [PIA Signon](#).

See Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Target Administration Pages, page 14.

Chapter 9

PS Search Server Domain Targets

This chapter provides an overview and discusses:

- The PS Search Server Domain homepage.
- How to create a PS Search Server Domain.
- PS Search Server Domain performance.
- PS Search Server Domain administration.
- PS Search Server Domain logs.

Understanding PS Search Server Domain Targets

The PS Search Server Domain target type allows for the application server search function in PeopleSoft applications.


The PS Search Server Domain enables you to:

- Centralize search functions.
- Implement a search server on a platform separate from the application server.
- Run application server domains on operating systems that may not be supported by Verity.

One search server domain can be associated with more than one application server domain, however, an application server domain can have just one search server.

The PS Search Server Domain Homepage

Select Targets, PeopleSoft, then select a PS Search Server Domain target. The homepage appears:



PS Search Server Domain Homepage

The elements that appear on the PS Search Server Domain homepage are similar to those found on application server and Process Scheduler homepages.

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Common Elements on Homepages, page 13.](#)

Creating a PS Search Server Domain

You can create a PS Search Server Domain in the PeopleSoft subtab. Select PS Search Server from the Create drop-down list and click Go. The Create PS Search Server Domain page appears. The Import Configuration from File option is not available when creating a PS Search Server Domain.

Note. Not all platforms support a separate search server domain. Therefore, the system checks whenever you try to create a search server domain manually. If a separate search server domain target type is not supported on your platform, an error occurs.

See [Chapter 5, "PS Application Server Domain Targets," Creating PS Application Server Domain Targets, page 47.](#)

PS Search Server Domain Performance

This page displays the same information as the PS Process Scheduler Domain Performance page except that the process in the Queued Process graph is the PSSRCHSRV.

See [Chapter 5, "PS Application Server Domain Targets," PS Application Server Domain Performance, page 49.](#)

PS Search Server Domain Administration

This page displays information similar to that displayed on the PS Application Server Domain Administration page.

ORACLE Enterprise Manager 10g
Grid Control

Home Targets Deployments Alerts Policies Jobs Reports

Hosts | Databases | Application Servers | Web Applications | Services | Systems | Groups | All Targets | **PeopleSoft**

PS Search Server Domain: PSSRCH1.srch.psemgrid02.home_psft_PT848-805-I1

Page Refreshed Apr 11, 2006 2:26:23 PM PDT

Home Performance Administration Logs

Configuration Management

- [Configure Domain](#)
- [Compare Domain Configurations](#)
- [Compare To Multiple Configurations \(Jobs\)](#)
- [Last Collected Configuration](#)
- [View Saved Configurations](#)
- [History](#)

Tuxedo Management

- [Access Tuxedo Command Line \(TMADMIN\)](#)
- [Process Status](#)
- [Client Status](#)
- [Queue Status](#)

Domain Management

- [Start Domain](#)
- [Stop Domain](#)
- [Stop Domain \(Forced\)](#)
- [Delete Domain](#)
- [Clean IPC Resources](#)

Additional Utilities

- [Execute Host Command](#)

Home Performance Administration Logs

Home | Targets | Deployments | Alerts | Policies | Jobs | Reports | Setup | Preferences | Help | Logout

PS Search Server Domain Administration page

Configuration Management links that appear on this page:

- [Configure Domain](#)
- [Compare Domain Configurations](#)
- [Compare to Multiple Configurations \(Jobs\)](#)
- [Last Collected Configuration](#)
- [View Saved Configuration](#)
- [History](#)

Domain Management links that appear on this page:

- [Start Domain](#)
- [Stop Domain](#)
- [Stop Domain \(Forced\)](#)
- [Delete Domain](#)
- [Clean IPC Resources](#)

Tuxedo Management links that appear on this page:

- Access Tuxedo Command Line (TMADMIN)
- Process Status
- Client Status
- Queue Status

Additional Utilities links that appears on this page are:

- Execute Host Command.
- Windows Service Management (available only for targets with a Windows host).

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Target Administration Pages, page 14.](#)

PS Search Server Domain Logs

This page displays the same features as the PS Application Server Domain Logs page.

See [Chapter 2, "Understanding the PeopleSoft Environment Management Plug-in," Target Log Management, page 20.](#)

Chapter 10

PeopleSoft Systems and Services

This chapter provides an overview and discusses how to:

- Define PeopleSoft systems.
- Edit PeopleSoft systems.
- Remove PeopleSoft systems.
- Manage PeopleSoft systems.

Understanding PeopleSoft Systems

PeopleSoft targets sharing the same application database can be grouped into a PeopleSoft system. A PeopleSoft system can comprise an application database, multiple PS PIA targets, PS Web Sites, PS Process Scheduler Domains, PS Process Monitor, PS Search Server Domains, and PS Application Server Domains. For example, a typical PeopleSoft system might be a production CRM application, which could include various PeopleSoft entities—like an application server, web server, search server, Process Scheduler, Process Monitor, and an application database. The PeopleSoft application database is the target that binds all of the other PeopleSoft targets together in the PeopleSoft system.

Note. If you use automated system creation PeopleSoft, all PeopleSoft targets that are associated with a particular PeopleSoft application database are added to this system. Only PeopleSoft targets that have been registered in Enterprise Manager can be in a system.

PS PIA and PS Web Site targets do not appear in an automatically generated system, unless they have been logged into previously.

Understanding Services

A *service* is defined as an entity that provides a useful function to its users; specifically, it models a business process or application. An administrator defines a *service test* to determine whether or not the service is available and performing. A *beacon* is a target type in Enterprise Manager that performs a service test.

The PeopleSoft Environment Management Plug-in delivers a service test that enables administrators to monitor the availability of a PeopleSoft application by simulating a login-logout activity.

Note. The delivered service test checks only the login and logout capability of the PeopleSoft application by simulating it (using the URL entered by the user). However, administrators can create their own services in Enterprise Manager to track specific areas of their applications, such as in payroll processing or call center services. They can also modify the generated service.


Creating PeopleSoft Systems

The section discusses:

- The PeopleSoft System homepage.
- Automated PeopleSoft system creation.
- Manual PeopleSoft system creation.

The PeopleSoft System Homepage

To view the Systems homepage, click Targets, Systems, then select a PeopleSoft system. The PeopleSoft System homepage appears.




PeopleSoft System Homepage

Automated PeopleSoft System Creation

To create a PeopleSoft system, select Targets, Systems. Select *PeopleSoft System* in the Add field and click Go.

The Create PeopleSoft System page appears:

ORACLE Enterprise Manager 10g  [Grid Control](#)

[Home](#) **[Targets](#)** [Deployments](#) [Alerts](#) [Policies](#) [Jobs](#) [Reports](#) [Setup](#) [Preferences](#) [Help](#) [Logout](#)

[Hosts](#) | [Databases](#) | [Application Servers](#) | [Web Applications](#) | [Services](#) | **[Systems](#)** | [Groups](#) | [All Targets](#) | [PeopleSoft](#)

Create PeopleSoft System

Automated PeopleSoft System Creation

* PS App DB Select the database that will be associated to the new system.


* System Name

Time Zone

Service Configuration


☒ Create Service

* Name of Service

* Beacon  Choose an existing beacon to associate with the service.

Time Zone

Enter a User ID and password that can login to the PeopleSoft Application. The User ID/password will be used to test availability of your PeopleSoft system.

PS Web Site	PeopleSoft Homepage URL	User ID	Password	Delete
ps1LnX.PSWEB1.site.psemgrid02.home_psft_PT848-805-11	lnx/EMPLOYEE/QE_LOCAL/h/?tab=DEFAULT	QEDMO	*****	

[Manual PeopleSoft System Creation](#)

[Cancel](#) [OK](#)

[Home](#) | [Targets](#) | [Deployments](#) | [Alerts](#) | [Policies](#) | [Jobs](#) | [Reports](#) | [Setup](#) | [Preferences](#) | [Help](#) | [Logout](#)

Create PeopleSoft System page

Automated PeopleSoft System Creation

PS App DB

Select the PeopleSoft database that should be associated to the new system. The list includes all the PS Application Databases that have been registered in Enterprise Manager.

System Name

Enter a new system name. Enterprise Manager automatically assigns a system name as `<DBName>+[01-99].PSSystem`. If there is already a system with that name, the new name is incremented by 1. You can change the system name to one that is more descriptive.

Timezone

Select the appropriate time zone. The default is the time zone of the Oracle Management Service.

Service Configuration

Create Service

(Optional) Select to configure the service that the PeopleSoft Environment Management Plug-in automatically creates for every valid PeopleSoft system. This service simulates the login-logout action to the PeopleSoft application. If you leave the check box cleared, the remaining fields are unavailable for selection.

Service Name

Enter a service name. The default is `<System Name>+. Service`.

Beacon	Click the icon to open a browser listing predefined beacons. Select the beacon you want associated with the service.
Timezone	Select the appropriate time zone for the service. The default is the time zone of the Oracle Management Service.
PS Web Sites and User IDs	<p>Lists the PS Web Sites detected in the PeopleSoft system. You must define the URL for the PeopleSoft page of each PS Web Site and specify login credentials.</p> <ol style="list-style-type: none"> 1. Enter the PeopleSoft application homepage URL (the first page to appear after the PeopleSoft login page). The format is <code><protocol>://<hostname>/ps/<web site>/<portal>/<node>/h/<tab ID></code> For example: <code>http://myserver.peoplesoft.com/ps/ps/EMPLOYEE/PT_LOCAL/h/?tab=DEFAULT</code> 2. Enter a user ID and password for use as the login to these URLs. 3. To remove a web site from the service, click Delete at the end of the row. <hr/> <p>Note. A service can be created only if there is at least one URL and one PS Web Site listed in the grid.</p> <hr/>

Click OK to proceed with the automated system creation.

Note. All system properties are defaulted when the system is created automatically.

There are no defaults for charts and metric data and they must be set up manually, if desired.

Manual System Creation

To select components individually for system creation, click the Manual PeopleSoft System Creation link in the lower left-hand part of the Create PeopleSoft System page.

Create PeopleSoft System

CancelOK

ComponentsTopologyChartsColumnsDashboard

* Name

Components

RemoveAdd

Select AllSelect None

Select Name

	Type
<input type="checkbox"/> peoplesoft.pia.st-sun06.ds1_home_psoft_pt_850-809-R1	PS PIA
<input type="checkbox"/> prcs-mntr.http.pta137.10180.PROCESSREQUEST_1_wsdl	PS Process Monitor
<input type="checkbox"/> ps.peoplesoft.site.st-sun06.ds1_home_psoft_pt_850-809-R1	PS Web Site
<input type="checkbox"/> Q8508093.app.st-sun06.ds1_home_psoft_psft_pt_850-809-R1	PS Application Server Domain
<input type="checkbox"/> Q8508093.db.976fa27e-438e-11de-9c6d-957a47ca2219	PS Application Database
<input type="checkbox"/> Q8508093.prcs.st-sun06.ds1_home_psoft_psft_pt_850-809-R1	PS Process Scheduler Domain

Time Zone

Time Zone (UTC-08:00) US Pacific Time (US/Pacific) (PST)

Create PeopleSoft System page

- Name

Enter a name for your new PeopleSoft system.
- Components

Click Add to display the Search and Select Targets page. Select the targets you want to add to the PeopleSoft system.
- Timezone

Select the appropriate time zone for this system.

1. Enter or select values for the fields listed above.

2. Because you are manually creating a system by adding targets, you must also manually specify the target associations.

To define the associations or relationships among the target types, click Topology.

3. There are several additional steps needed to create a PeopleSoft system manually. Refer to the Enterprise Manager documentation for more information.

4. Click OK when you have added all the desired components.

Editing PeopleSoft Systems

From the Edit PeopleSoft Systems page, you can add and remove targets from a PeopleSoft system and redefine associations shown in the topology.

Select Targets, Systems, then select the PeopleSoft system that you want to edit and click Configure. The Edit PeopleSoft System page appears:

The screenshot shows the Oracle Enterprise Manager 10g Grid Control interface. The top navigation bar includes links for Home, Targets, Deployments, Alerts, Compliance, Jobs, and Reports. The main title is 'Edit PeopleSoft System : Q8508093.PSSystem'. Below the title, there are tabs for Components, Topology, Charts, Columns, and Dashboard. The 'Components' tab is active, displaying a table of components for the selected system. The table has columns for Name and Type. The components listed are:

Select	Name	Type
<input type="checkbox"/>	peoplesoft.pia.st-sun06.ds1_home_psoft_pt_850-809-R1	PS PIA
<input type="checkbox"/>	prcs-mntr.http.pta137.10180.PROCESSREQUEST_1_wsdl	PS Process Monitor
<input type="checkbox"/>	ps.peoplesoft.site.st-sun06.ds1_home_psoft_pt_850-809-R1	PS Web Site
<input type="checkbox"/>	Q8508093.app.st-sun06.ds1_home_psoft_pstf_pt_850-809-R1	PS Application Server Domain
<input type="checkbox"/>	Q8508093.db.976fa27e-438e-11de-9c6d-957a47ca2219	PS Application Database
<input type="checkbox"/>	Q8508093.prcs.st-sun06.ds1_home_psoft_pstf_pt_850-809-R1	PS Process Scheduler Domain
<input type="checkbox"/>	ZOOSRCH.srch.st-sun06.ds1_home_psoft_pstf_pt_850-809-R1	PS Search Server Domain

Below the table, there is a 'Time Zone' section showing 'Time Zone (UTC-08:00) US Pacific Time'.

Edit PeopleSoft System page

Removing PeopleSoft Systems

Removing a PeopleSoft system means you are removing a grouping of targets in Enterprise Manager. However, you are not removing the targets from the Enterprise Manager or their installations from the server. The member targets remain in Enterprise Manager and can be managed and used for building other systems.

To remove a PeopleSoft system, select Targets, Systems, then the existing system that you want to remove. Click Remove.

Managing PeopleSoft Systems


This section discusses:

- PeopleSoft system administration
- PeopleSoft system components
- PeopleSoft system URL
- PeopleSoft system topology

PeopleSoft System Administration

You can create jobs and blackouts from the PeopleSoft System Administration page. Also, the PeopleSoft URLs that have been defined for a PeopleSoft system appear in the PeopleSoft URL section of the PeopleSoft System's Administration page. The URLs are listed as links and when selected, a new browser page opens showing the website that was defined.

Select Targets, Systems, a specific PeopleSoft system. From the homepage, select Administration.

ORACLE Enterprise Manager 10g  [Grid Control](#)

[Home](#) [Targets](#) [Deployments](#) [Alerts](#) [Policies](#) [Jobs](#) [Reports](#) [Setup](#) [Preferences](#) [Help](#) [Logout](#)

[Hosts](#) | [Databases](#) | [Application Servers](#) | [Web Applications](#) | [Services](#) | **[Systems](#)** | [Groups](#) | [All Targets](#) | [PeopleSoft](#)

PeopleSoft System: P8488041.06.PSSystem

Page Refreshed **Apr 11, 2006 2:41:13 PM PDT** [Refresh](#) [Launch Dashboard](#)

[Home](#) [Charts](#) [Administration](#) [Components](#) [Topology](#)

Job Activity

Create Job

Job executions scheduled to start no more than 7 days ago

Status	Submitted to the PeopleSoft System	Submitted to any member
Scheduled	0	0
Running	0	0
Suspended	0	0
Problem	0	0

Blackouts

Status	Submitted to the Group	Submitted to any Member
Scheduled	0	0
Active	0	0

PeopleSoft System URL


[ps1LnX.PSWEB1.site.psemgrid02.home_psft_PT848-805-I1 - PIA S...](#)
[ps1LnX.PSWEB1.site.psemgrid02.home_psft_PT848-805-I1 - Proce...](#)

Deployments Summary

View

Database Installations	Targets Installations	Interim Patches Applied
(No data found.)		

Configuration Searches


 No Configuration Searches available.

[Home](#) [Charts](#) [Administration](#) [Components](#) [Topology](#)

Related Links

[Access Reports](#) [Edit PeopleSoft System Target Properties](#) [PeopleSoft System URL Setup](#)

[Home](#) | [Targets](#) | [Deployments](#) | [Alerts](#) | [Policies](#) | [Jobs](#) | [Reports](#) | [Setup](#) | [Preferences](#) | [Help](#) | [Logout](#)

Copyright © 1996, 2006, Oracle. All rights reserved.
 Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.
[About Oracle Enterprise Manager](#) 

PeopleSoft System Administration page

PeopleSoft System Components

The PeopleSoft System Components page lists all of the PeopleSoft targets included in the system. You can click an individual target to display that target's homepage.

Select Targets, Systems and a specific PeopleSoft system. From the homepage, select Components.

Name	Type	Status	Alerts	Policy Violations
peoplesoft pia st-sun06.ds1_home_psoft_pt_850-809-R1	PS PIA	⊕	0 0	0 1 0
prcs-mntr.http.pta137.10180.PROCESSREQUEST_1_wsdll	PS Process Monitor	⊕	0 0	0 0 0
ps.peoplesoft.site.st-sun06.ds1_home_psoft_pt_850-809-R1	PS Web Site	⊕	0 0	0 2 0
Q8508093.app.st-sun06.ds1_home_psoft_psf_pt_850-809-R1	PS Application Server Domain	⊕	0 0	0 0 0
Q8508093.db.976fa27e-438e-11de-9c6d-957a47ca2219	PS Application Database	⊕	0 0	0 0 0
Q8508093.prcs.st-sun06.ds1_home_psoft_psf_pt_850-809-R1	PS Process Scheduler Domain	⊕	0 0	0 0 0
ZOOSRCH.srch.st-sun06.ds1_home_psoft_psf_pt_850-809-R1	PS Search Server Domain	⊕	0 0	0 0 0

PeopleSoft System Components page

PeopleSoft System URLs

You can define different system URLs to be accessed in Enterprise Manager. Only users who have full target privileges can manage PeopleSoft system URLs in Enterprise Manager.

PeopleSoft delivers the following system URL types for you to create and associate URLs to your PeopleSoft system.

Note. The system administrator is responsible for populating the correct URL fields. The system does not verify the URL and by default, the URL fields are blank.

- Process Scheduler Management

You can enter the URL for any of the submenus used in PeopleTools Process Scheduler; for example, Process Monitor and Application Engine. Once you have defined this system URL, you can access it by selecting Administration for the PS Process Scheduler Domain target, then click Manage Process Scheduler in PIA.

- Web Profile Search

This URL is associated with a PS Web Site target. Enter the URL from a PeopleSoft application to open its web profile page. The naming convention for this URL is <WebSite_Name>+_Web Profile Search.

- PIA Signon

You may have multiple values for PIA—however, the PS Web Site is the primary key. The PS Web Site drop-down list in the Create URL page shows only the PS Web Sites that have been defined in the PeopleSoft system. If there are no PS Web Sites present in the PeopleSoft system you cannot create a PIA Signon URL entry. The naming convention for this URL is <WebSite_Name>+_PIA Signon.

- Integration Broker Monitor Message

This URL is associated with a PS Web Site target. Enter the URL from a PeopleSoft application to open its Integration Broker profile page. The naming convention for this URL is <WebSite_Name>+_Integration Broker Monitor Message.

- Web Server Administration

This refers to WebSphere, Weblogic, or OAS web server administration site. Enter the URL here to access the web server administration site from Enterprise Manager. You may have multiple values here, while the PS PIA target is the primary key. The naming convention for this URL is <<PIA_Name>+_Web Server Administration.

- Performance Monitor

Enter the URL of the Performance Monitor system that is monitoring your PeopleSoft servers.

- PeopleBooks

Enter the URL of your PeopleBook web site for access from Enterprise Manager.

Click the PeopleSoft System URL Setup link in the Related Links region of the PeopleSoft System homepage. The PeopleSoft System URL page appears.

ORACLE Enterprise Manager 10g
Grid Control

Home Targets Deployments Alerts Policies Jobs Reports Setup Preferences Help Logout

Hosts Databases Application Servers Web Applications Services Systems Groups All Targets PeopleSoft

PeopleSoft System URL

Page Refreshed Apr 11, 2006 2:40:13 PM PDT Refresh

Edit Remove Create

Select	URL Type Name	URL
<input checked="" type="radio"/>	ps1Lnx.PSWEB1.site.psemgrid02.home_psf PT848-805-11 - PIA Signon	http://psemgrid02.peoplesoft.com:3080/psp/ps1Lnx/?cmd=login
<input type="radio"/>	ps1Lnx.PSWEB1.site.psemgrid02.home_psf PT848-805-11 - Process Scheduler Management	http://psemgrid02.peoplesoft.com:3080/psp/ps1Lnx/EMPLOYEE/QE_LOCAL/s/WEBLIB_PTPP_SC.HOMEPA pt_fname=PT_PEOPLETOLS&FolderPath=PORTAL_ROOT_OBJECT.PT_PEOPLETOLS&IsFolder=true

OK

Home Targets Deployments Alerts Policies Jobs Reports Setup Preferences Help Logout

Copyright © 1996, 2006, Oracle. All rights reserved.
Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.
[About Oracle Enterprise Manager](#)

PeopleSoft System URL page

Edit Select a URL , then click to enter changes to previously created PeopleSoft system URLs.

Remove Click to remove a PeopleSoft system URL.

Create Click to display the Create PeopleSoft System URL page. Select the URL type and make other appropriate selections. Click Save.

Note. By default, the system adds http:// to the front of the URL, if not already present, when saving the record.

PeopleSoft System Topology

The Topology page shows a graphical view of a PeopleSoft system and enables you to perform several tasks.

From the Topology page, you can:

- See the status of each target—icons are green (up), red (down), light gray (unknown), dark gray (blackout).
- Display data that is refreshed every 30 seconds, or manually if specified.
- Zoom in and out by clicking the icons in the left-hand column. Show summary information on the number of alerts and policy violations on a per target or system basis.
- You can initiate common PeopleSoft actions for a target by right-clicking on the target's icon.

The actions available depend on the target type and your target privileges. For example, if you have operator level target privileges, you can only start, stop and purge.

The actions available by target type with full target privileges are

- PS Application Database has no actions available, it is display only.
- PS Application Server Domain allows start, stop, configure, and purge/archive.
- PS Search Server Domain allows start, stop, and configure.
- PS Process Scheduler Domain allows start, stop, and configure.
- PS Process Monitor allows Process Monitor and Schedule Process.
- PS PIA allows start and stop.
- PS Web Site allows configure.

To view a PeopleSoft system in the Topology Viewer, select Targets, Systems and select a PeopleSoft system. The homepage appears, select Topology. The Topology Viewer opens.

ORACLE Enterprise Manager 10g
Grid Control

HomeTargetsDeploymentsAlertsPoliciesJobsReports

HostsDatabasesApplication ServersWeb ApplicationsServicesSystemsGroupsAll TargetsPeopleSoft


PeopleSoft System: P8488041.06.PSSystem

Page Refreshed Apr 11, 2006 2:45:11 PM PDTRefreshLaunch Dashboard

HomeChartsAdministrationComponentsTopology

View DataReal Time: Manual Refresh

Overview




Selection Details

Type: PS PIA
Name: PSWEB1.pia.psemgrid02.home_ps
Status: Up
Critical Alerts: 0
Warning Alerts: 0
Policy Violations: 1
Host: psemgrid02

Summary

Components 9 (↓6 ↑3)
Alerts 0 0
Policy Violations 0 4 0



Legend

HomeChartsAdministrationComponentsTopology

Related Links

AccessEdit PeopleSoft SystemPeopleSoft System URL Setup
ReportsTarget Properties

PS System Topology page

Chapter 11

Security for PeopleSoft Environment Management Plug-in

This chapter provides an overview and discusses:

- Target privileges.
- Target preferred credentials.
- Target credentials.

Understanding Enterprise Manager Security

The PeopleSoft Environment Management Plug-in relies on Oracle Enterprise Manager's security framework for most security features.

Enterprise Manager identifies *administrators* to manage the Enterprise Manager administration accounts. There are three administrator access categories:

Administrator	This is considered the regular Enterprise Manager administrator.
Super Administrator	This is considered the most powerful Enterprise Manager administrator with full access privileges to all targets and administrator accounts within the Enterprise Manager environment. Only super administrators can perform administrative operations on regular administrator accounts.
Repository Owner	This is the database administrator for the Management Repository. This account cannot be modified, duplicated, or deleted.

From the Enterprise Manager Grid Control Console, you can create and manage new administrator accounts. Each administrator account includes its own login credentials, and a set of roles and privileges that are assigned to the account.

Target Privileges

Target privileges enable an administrator to perform operations on a target. Certain privileges are automatically given to administrators based on other privileges. For example, granting any privileges on a target automatically grants the View target privilege on the host.

Target privileges are divided into three groups:

View	Enables the administrator to view properties, inventory and monitor information about a target. The view privilege is propagated to all members of aggregate targets such as groups and systems.
<hr/>	
Note. The view privilege must also be assigned to the agent of the target.	
<hr/>	
Operator	Enables the administrator to perform the following operations on a target: startup, shutdown, edit target properties, view the components of the system, modify system membership, add charts to the system, create or edit system topology, customize the dashboard associated with the system, change the columns that appear on the System Members page, black out the system and its components. The Operator Target privilege does not automatically propagate to members of the System.
Full	Implicitly grants all the target privileges and enables the administrator to delete a target and configure credentials for maintenance operations of a target. When you create a system, you become its owner and automatically receive full privileges for the system and view on all targets. Certain privileges are automatically given to administrators based on other privileges. For example, granting any privileges on a target automatically grants the View target privilege on the host.

Target Preferred Credentials

Target Preferred Credentials is a credential specifically applied to a single target for a particular user.

Note. PeopleSoft targets do not use host preferred credentials for PeopleSoft-specific actions.

Managing Preferred Credentials

Preferred credentials simplify access to managed targets by storing target login credentials in the Management Repository. With preferred credentials set, users can access an Enterprise Manager target that recognizes those credentials without being prompted to log into the target. Preferred credentials are set on a per user, per target basis, thus ensuring the security of the managed enterprise environment.

To manage Enterprise Manager preferred credentials:

1. Click Preferences at the top of any Enterprise Manager Grid Control page.
2. Click Preferred Credentials in the vertical navigation bar.

Enterprise Manager displays the Preferred Credentials page. The first column lists all the target types.

- Click the Set Credentials icon (last column) that corresponds to the target type for which you want to manage the preferred credentials.

The specific target type's preferred credentials page appears.

- Enter the host user name and host password, as desired.

If you need help using the Preferred Credentials page, click Help at any time.

Target Credentials

Each of the target privilege levels are assigned actions that can be performed whenever the privilege is assigned to a role or user.

See [Appendix B, "Roles and Privileges,"](#) page 103.

The Target Credentials page is used to verify credentials.

Depending on what actions you want to perform, you may be required to enter a user name and password in the Target Credentials page.

If desired, you can select the Saved Preferred Credentials check box, and the system will not prompt for credentials the next time you initiate the action for this target (when you are the current user in Enterprise Manager).

ORACLE Enterprise Manager 10g
Grid Control

Home Targets Deployments Alerts Setup Preferences Help Logout
Compliance Jobs Reports

Hosts | Databases | Middleware | Web Applications | Services | Systems | Groups | All Targets | PeopleSoft

Target Credentials

Target: **test.app.st-sun06.ds1_home_psoft_psft_pt_850-809-R1**
Action: **Start Domain**

Enter credentials for the target host Cancel OK

* Username
 * Password
 Run Privilege Run as Profile
☐ Save as Preferred Credential

Related Link
[Show Preferred Credentials](#)

Target Credentials page

Chapter 12

Validating Policies

This chapter provides an overview and discusses:

- Enterprise Manager policy validation.
- PeopleSoft policy definitions.

Understanding Policies

Policies define the optimal configurations of systems and any deviations to your systems or applications are reported. Examples of deviations include inappropriate settings and incorrect system configurations.

PeopleSoft Policy Definitions

The PeopleSoft Environment Management Plug-in delivers predefined policies.

See [Chapter 12, "Validating Policies," PeopleSoft Policy Definitions, page 95.](#)

Enterprise Manager's Policy Validation

The PeopleSoft Environment Management Plug-in uses the policy validation of Enterprise Manager. It enables you to verify the configurations of different targets and identify inconsistencies or possible issues.

Note. There are no policies for PS Application Database, PS Process Scheduler, or PS Search Server Domain targets.

Policy validation is initially set to run once every 24 hours. However, it occurs automatically when PeopleSoft targets are discovered. You can change the collection schedule of each policy by:

- Selecting the Metric and Policy Setting link for the target homepage.

The Metric and Policy Settings page appears.

- From the Policies tab, click the Collection schedule before each policy to change their individual schedules.

Click OK every time you change a policy setting, otherwise, Enterprise Manager does not update the changed values.

Once the collection is run on a scheduled basis, Enterprise Manager retrieves the corresponding metric in the repository and compares it to the condition defined in the policy. If the policy condition is met (identifies a violation), violation data is generated and you can view it in the Violation Summary region of the target homepage.

Violations can be viewed from the Policy Violations page. Select the Policies tab in Enterprise Manager, then Count from the Policy Violations. From this page, you can access the Policy Violation Detail page.

The count of violations can be viewed from a target's homepage in the Policy Violations section. Click the violation count link to open the Policy Violations page, then click the count to open the Policy Violation Detail page.

Policy Violation Detail

Access the Policy Violation Detail page by clicking a value in the Violation Count column of the Policy Violation page.

ORACLE Enterprise Manager 10g
Grid Control

Home | **Targets** | Deployments | Alerts | Policies | Jobs | Reports

Hosts | Databases | Application Servers | Web Applications | Services | Systems | Groups | **All Targets** | PeopleSoft


PS Application Server Domain: PSAPP2.app.psemgrid02.home_psf PT848-805-I1 >

Policy Violation Details: PSAPPSRV Recycle Count

Target Name **PSAPP2.app.psemgrid02.home_psf PT848-805-I1** Target Type **PS Application Server Domain**

This page shows objects in violation of this policy rule. Suppress the violations that you do not want to be included in the list of policy violations. Last Evaluation **Apr 11, 2006 12:50:04 PM PDT**

General

Severity 
Compliance Score (%) **76**
Importance **Normal**
Category **Configuration**
Description **Checks that the PSAPPSRV Recycle Count is not set too low.**

Objects with Violations

Objects with Violations **1**
Objects with Suppressed Violations **0**

Impact of Violation

Setting the recycle count to a lower number would cause the AppServers to restart unnecessarily and thereby impact performance.

Recommendation

Increase recycle count to recommended value

Violations

View Violations

[Add Comment](#) [Suppress Violation](#)

[Select All](#) | [Select None](#)

Select	PSAPPSRV Recycle Count	Non-Compliant Since	Automated Corrective Action Status	Comments
<input type="checkbox"/>	1000	Apr 11, 2006 12:47:53 PM PDT	Not Applicable	

Related Link

[Edit Policy Rule Settings](#)

Home | **Targets** | Deployments | Alerts | Policies | Jobs | Reports | Setup | Preferences | Help | Logout

Copyright © 1996, 2006, Oracle. All rights reserved.
Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.
[About Oracle Enterprise Manager](#)

Policy Violation Details page

The Policy Violation Details page shows detail about the violation; a graph showing the percentage of this violation within the target; the violation's impact; the recommended fix; and a grid listing the occurrences of each violation.

Click **Suppress Violation** to display the **Suppress Violation** page where you can specify which policies to suppress.

To edit policy definitions such as disabling the policy check for a target or changing its threshold select the **Edit Policy Rule Settings** from the **Related Links**.

Appendix A

Configuration and Metric Data Collected

This appendix discusses:

- Configuration data collected.
- Metric data collected.

Configuration Data Collected

Enterprise Manager collects configuration data from each target type's configuration. Configuration data is collected on a regular basis—the default is once a day—and is transmitted to the Oracle Management Service. The first configuration collection occurs after the initial discovery process.

For subsequent configuration collections, the Oracle Management Service receives and parses the data and saves updates to the Management Repository. In addition to the regularly scheduled configuration collection process, collections are triggered every time you change a target's configuration from within Enterprise Manager.

The following table shows the configuration data collected for each PeopleSoft target type.

<i>PeopleSoft Target Type</i>	<i>Data in These Files</i>
PS Application Database	PeopleTools tables
PS Application Server Domain	psappsrv.cfg, psappsrv.ubx
PS Process Scheduler Domain	psprcs.cfg, psprcs.ubx
PS Search Server Domain	pssrchsvr.cfg, pssrchsvr.ubx
PS PIA	piaInstallLog.xml, config_prop, setEnv.sh/cmd or opmn.xml or server.xml
PS Web Site	web.xml, configuration.properties, integrationGateway.properties, pstools.properties, config_prop

Metric Data Collected

This refers to the collection of data that changes frequently, such as status, memory, disk utilization, and so on. PeopleSoft delivers predefined metric types and default collection times for each target type.

The metric data collected is saved to the Management Repository and is compared to predefined thresholds for each target. If a threshold has been reached, the system generates an alert. The alerts display on each target's homepage.

The following table shows the metric data collected for each PeopleSoft target type.

Target Type	Attribute Name	Collection Schedule	Description
PS Application Database	Availability/Response	10 minutes	Checks the status of the PS Application Database
PS Application Server Domain	Availability/Response	1 minute	Checks the status of PS Application Server Domain
PS Application Server Domain	# of Process Queued for App Server	10 minutes	Monitors the number of PSAPPSRV processes queued for a PS Application Server Domain. Generates an alert if the defined threshold is reached.
PS Application Server Domain	# of Process Queued for BRK Dispatcher (if enabled)	13 minutes	Monitors the number of PSBRKDSP processes queued for a PS Application Server Domain. Generates an alert if the defined threshold is reached.
PS Application Server Domain	# of Process Queued for BRK Handler (if enabled)	14 minutes	Monitors the number of PSBRKHND processes queued for a PS Application Server Domain. Generates an alert if the defined threshold is reached.
PS Application Server Domain	# of Process Queued for PUB Dispatcher (if enabled)	12 minutes	Monitors the number of PSPUBDSP processes queued for a PS Application Server Domain. Generates an alert if the defined threshold is reached.

Target Type	Attribute Name	Collection Schedule	Description
PS Application Server Domain	# of Process Queued for PUB Handler (if enabled)	15 minutes	Monitors the number of PSPUBHND processes queued for a PS Application Server Domain. Generates an alert if the defined threshold is reached.
PS Application Server Domain	# of Process Queued for SUB Dispatcher (if enabled)	16 minutes	Monitors the number of PSSUBDSP processes queued for a PS Application Server Domain. Generates an alert if the defined threshold is reached.
PS Application Server Domain	# of Process Queued for SUB Handler (if enabled)	17 minutes	Monitors the number of PSSUBHND processes queued for a PS Application Server Domain. Generates an alert if the defined threshold is reached.
PS Application Server Domain	PSAPPSRV Handler Count	15 minutes	Monitors the number of active PSAPPSRV processes. Generates alerts if the number is below the specified minimum or above the maximum.
PS Application Server Domain	Tuxedo Connections	9 minutes	Counts the number of Tuxedo connections to the PS App Server Domain.
PS Process Scheduler Domain	Availability/Response	1 minutes	Checks the status of PS Process Scheduler Domain.
PS Process Scheduler Domain	# Queued Processes for Process Scheduler (PSPRCSRV)	15 minutes	Monitors the number of PSPRCSRV processes queued for a PS Process Scheduler Domain. Generates an alert if the defined threshold has been reached.
PS Process Scheduler Domain	# Queued Processes for Process Scheduler (PSPRCSRV)	15 minutes	Monitors the number of PSPRCSRV processes queued for a PS Process Scheduler Domain. Generates an alert if the defined threshold has been reached.

Target Type	Attribute Name	Collection Schedule	Description
PS Process Scheduler Domain	# Queued Processes for Distribution Server (PSDSTSRV)	15 minutes	Monitors the number of PSDSTSRV processes queued for a PS Process Scheduler Domain. Generates an alert if the defined threshold has been reached.
PS PIA	Availability/Response	1 minute	Checks the status of PS PIA.
PS Web Site	Availability/Response	1 minute	Checks the status of PS PIA where the PS Web Site is connected.
PS Search Server Domain	Availability/Response	1 minute	Checks the status of the PS Search Server Domain.
PS Search Server Domain	# Queued Processes for Search Server (PSSRCHSRV)	5 minutes	Monitors the number of PSSRCHSRV processes queued for a PS Search Server Domain. Generates an alert if the defined threshold has been reached.
PS Process Monitor	Availability/Response	1 minute	Checks the status of the PS Process Monitor.
PS Process Monitor	# of Failed PeopleSoft Processes	1 hour	Monitors the count of processes with errors (Run Status = Error) in the last 1 hour.
PS Process Monitor	# of Running PeopleSoft Processes	1 hour	Monitors the count of running processes (Run Status = Processing) in the last 1 hour.
PS Process Monitor	# of Successful PeopleSoft Processes	1 hour	Monitors the count of successfully completed processes (Run Status = Success) in the last 1 hour.

Appendix B

Roles and Privileges

This appendix discusses target actions and privileges.

Target Actions and Privileges

The following table lists target actions for each of the target types and actions for systems and logs.

Note. Users assigned a super administrator role can perform all actions for all target types, systems, and logs.

Target Actions and Privileges Tables

This section includes tables showing target actions, credentials, and roles.

PS Application Server Domain

<i>Target Actions</i>	<i>Target Credentials Required</i>	<i>Full Role</i>	<i>Operator Role</i>	<i>Viewer Role</i>
Create domain	Yes	Yes, with target system privileges		
Configure domain	Yes	Yes		
Import domain configuration from file	Yes	Yes, with target system privileges		
Create like domain	Yes	Yes, with target system privileges		
Compare domain configurations		Yes		
Compare to multiple configurations (jobs)		Yes		
Last collected configuration		Yes		

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
View saved configuration		Yes		
History		Yes		
Copy configurations	Yes	Yes		
Create service (Windows only)	Yes	Yes		
Create messaging server	Yes	Yes		
Configure messaging server	Yes	Yes		
Delete messaging server	Yes	Yes		
Create service (Windows only)	Yes	Yes		
Configure service (Windows only)	Yes	Yes		
Install service (Windows only)	Yes	Yes		
Delete service (Windows only)	Yes	Yes		
Start domain (parallel and serial)	Yes	Yes	Yes	
Stop domain (forced and normal)	Yes	Yes	Yes	
Access Tuxedo command line (TMADMIN)	Yes	Yes	Yes	
Purge/archive cache	Yes	Yes	Yes	
View domain processes status		Yes	Yes	Yes
View domain queue status		Yes	Yes	Yes

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
View domain client status		Yes	Yes	Yes
Delete domain	Yes	Yes		
Preload file cache	Yes	Yes	Yes	
Clean IPC resources	Yes	Yes	Yes	
Execute host command	Yes	Yes	Yes	
View domain status (stopped or running)		Yes	Yes	Yes

PS Search Server Domain

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Create domain	Yes	Yes, with target system privileges		
Configure domain	Yes	Yes		
Compare domain configurations		Yes		
Compare to multiple configurations (Job)		Yes		
Last collected configuration		Yes		
View saved configuration		Yes		
History		Yes		
Start domain	Yes	Yes	Yes	
Stop domain (forced and normal)	Yes	Yes	Yes	
Delete domain	Yes	Yes		
Clean IPC resources	Yes	Yes	Yes	

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Access Tuxedo command line (TMADMIN)	Yes	Yes	Yes	
Create service (Windows only)	Yes	Yes		
Configure service (Windows only)	Yes	Yes		
Install service (Windows only)	Yes	Yes		
Delete service (Windows only)	Yes	Yes		
View domain processes status		Yes	Yes	Yes
View domain queue status		Yes	Yes	Yes
View domain client status		Yes	Yes	Yes
View domain status (stopped or running)		Yes	Yes	Yes
Execute host command	Yes	Yes	Yes	

PS Process Scheduler Domain

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Create domain	Yes	Yes, with target system privileges		
Configure domain	Yes	Yes		
Import domain configuration from file	Yes	Yes, with target system privileges		
Create like domain	Yes	Yes, with target system privileges		

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Compare domain configurations		Yes		
Compare to multiple configurations (Job)		Yes		
Last collected configuration		Yes		
View saved configuration		Yes		
History		Yes		
Copy configurations	Yes	Yes		
Create service (Windows only)	Yes	Yes		
Configure service (Windows only)	Yes	Yes		
Install service (Windows only)	Yes	Yes		
Delete service (Windows only)	Yes	Yes		
Start domain	Yes	Yes	Yes	
Stop domain (forced and normal)	Yes	Yes	Yes	
Delete domain	Yes	Yes		
Clean IPC resources	Yes	Yes	Yes	
View domain processes status		Yes	Yes	Yes
View domain queue status		Yes	Yes	Yes
View domain status (stopped or running)		Yes	Yes	Yes
Execute host command	Yes	Yes	Yes	

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Manage Process Scheduler in PIA	Yes, also prompted for PIA login	Yes	Yes	

PS PIA

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Edit setEnv	Yes	Yes		
Edit web.xml	Yes	Yes		
Compare domain configurations		Yes		
Compare to multiple configurations		Yes		
Last collected configuration		Yes		
View saved configuration		Yes		
History		Yes		
Start PIA	Yes	Yes	Yes	
Stop PIA	Yes	Yes	Yes	
Web server type administration console	Yes, also prompted for PIA login	Yes	Yes	Yes
Customize start/stop scripts		Yes		
Execute host command	Yes	Yes	Yes	
View web domain status (if stopped or running)		Yes	Yes	Yes
Process Monitor Setup	Yes	Yes, with target system privileges		

PS Process Monitor

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Compare domain configurations		Yes		
Compare to multiple configurations		Yes		
Last collected configuration		Yes		
View saved configuration		Yes		
History		Yes		
Execute host command	Yes	Yes	Yes	
Process Monitor	Yes	Yes	Yes	
Schedule Process	Yes	Yes	Yes	

PS Web Site

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Configure site	Yes	Yes		
Web profile	Yes, also prompted for PIA login	Yes	Yes	
Integration Broker	Yes, also prompted for PIA login	Yes	Yes	
Compare configurations		Yes		
Compare to multiple configurations (jobs)		Yes		
Last collected configuration		Yes		
View saved configuration		Yes		
History		Yes		

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
PIA signon	Yes, also prompted for PIA login	Yes	Yes	Yes
View web site status		Yes	Yes	Yes

PS Application Database

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
View status		Yes	Yes	Yes

Log Management (All Targets Except PS Web Site, PS Process Monitor, and PS Application DB)

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Search logs	Yes	Yes	Yes	Yes
View logs	Yes	Yes	Yes	Yes
Purge logs	Yes	Yes	Yes	
Log management setup		Yes		

Management Actions

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Create PeopleSoft system (only super administrator)				
Edit PeopleSoft system		Yes, if target access granted	Yes, if target access granted	
Delete PeopleSoft system		Yes, with target system privileges		
View PeopleSoft system		Yes, if target access granted	Yes, if target access granted	Yes, if target access granted

Target Actions	Target Credentials Required	Full Role	Operator Role	Viewer Role
Add PeopleSoft URL		Yes		
Delete PeopleSoft URL		Yes		
Edit PeopleSoft URL		Yes		
Access PeopleSoft system URLs		Yes	Yes	Yes
Add PeopleSoft targets (super administrator)				
Remove target		Yes, with target system privileges		

Appendix C

Target Log Files

This appendix lists default target log file locations and types.

Default Target Log Files

This section lists default log file locations and types for:

- PS PIA targets.
- PS Application Server Domains.
- PS Search Server Domains.
- PS Process Scheduler Domains.

PS PIA Log Files

This table lists PS PIA log file locations and log file types.

<i>File Location</i>	<i>Log File Type</i>
If using Weblogic: <PIA_HOME>/webserv/<Domain>/applications/peoplesoft/PSEMHUB/envmetadata/logs If using WebSphere: <PIA_HOME>/webserv/<cellname>_<nodename>_<servername>/peoplesoft.ear/PSEMHUB/envmetadata/logs	*.txt
<PIA_HOME>/webserv/<Domain>/logs	*.log
<PIA_HOME>/webserv/<Domain>/logs/replaydump	*.bug
<OAS_HOME>/j2ee/<Domain>/log/<Domain>_default_island_1/	*.log
<WEBSPHERE_HOME>/logs/<server_name>	*.log
<WEBSPHERE_HOME>/logs	*.log

PS Application Server Domain Log Files

The PS Application Server Domain log directories and log file types are:

<i>File Location</i>	<i>Log File Type</i>
<PS_CFG_HOME>/appserv/<appserver_domain>/LOGS	*.LOG TUXLOG.* *.trc *.tracesql *.mps *.lp process_state* *.dmp peopletools_state*
<PS_CFG_HOME>/appserv/<appserver_domain>	ULOG.<date> stderr stdout
<PS_CFG_HOME>/appserv	core

PS Search Server Domain Log Files

The PS Search Server Domain log directories and log file types are:

<i>File Location</i>	<i>Log File Type</i>
<PS_CFG_HOME>/appserv/search/DOMAIN_NAME/LOGS	*.trc *.LOG *.log *.lp *.dmp process_state* peopletools_state*
<PS_CFG_HOME>/appserv/search/DOMAIN_NAME	stdout stderr ULOG*
<PS_CFG_HOME>/appserv	core

PS Process Scheduler Server Log Files

The PS Process Scheduler Server Domain log directories and log file types are:

File Location	Log File Type
<PS_CFG_HOME>/appserv/	core
<PS_CFG_HOME>/appserv/prcs/<prcs_domain>/	stderr stdout ULOG*
<PS_CFG_HOME>/appserv/prcs/<prcs_domain>/LOGS/	*.LOG process_state* peopletools_state* TUXLOG*
<PS_CFG_HOME>/appserv/prcs/<prcs_domain>/log_out put/	delete_*.txt
<PS_CFG_HOME>/appserv/prcs/<prcs_domain>/log_out put/_PSPRCSRLOG/	*.*
<PS_CFG_HOME>/appserv/prcs/<prcs_domain>/log_out put/_PSDSTSRVLOG	*.*
<PS_CFG_HOME>/appserv/prcs/<prcs_domain>/log_out put/_TUXLOG/	*.*
<PS_CFG_HOME>/appserv/prcs/<prcs_domain>/files/	*.*

Appendix D

Target Policies

This appendix discusses:

- PS Application Server Domain policies.
- The PS PIA policy.
- PS Web Site policies.

PS Application Server Domain Policies

This table lists the PS Application Server Domain policies:

<i>Policy</i>	<i>Definition</i>	<i>Severity</i>
Client Cleanup Timeout	The value should be ≤ 20 minutes. If it is greater than 20, a violation should be called out. Setting the value to 20 or less avoids having many idle client connections connected to the host. With client cleanup time out at a minimum value, it is a more effective use of the server's memory and CPU and improves performance.	Warning
PSAPPSRV Recycle Count	Value should be ≥ 5000 . Setting this at zero or too low may cause memory swapping.	Warning
Enable Server Caching	Recommend a setting of 2 to minimize the cost of recycling the application servers.	Informational
PSQRYSRV Min Handler	Set this to 1 if the PUBSUB server for the domain was activated.	Informational
PSBRKDSP Allowed Consec Service Failures	Set to > 1 to enable the system to recycle on its own in an event of a service failure.	Informational
PSPUBDSP Allowed Consec Service Failures	Set to > 1 to enable the system to recycle on its own in an event of a service failure.	Informational
PSSUBDSP Allowed Consec Service Failures	Set to > 1 to enable the system to recycle on its own in an event of a service failure.	Informational

Policy	Definition	Severity
PSBRKHND Allowed Consec Service Failures	Set to > 1 to enable the system to recycle on its own in an event of a service failure.	Informational
PSPUBHND Allowed Consec Service Failures	Set to > 1 to enable the system to recycle on its own in an event of a service failure.	Informational
PSSUBHND Allowed Consec Service Failures	Set to > 1 to enable the system to recycle on its own in an event of a service failure.	Informational

PS PIA Policy

This table lists the PS PIA policy.

Policy	Definition	Severity	Configuration File
JVM Heap size	Minimum and maximum heap size should be set to equal and it should be >= 256MB	Warning	SetEnv/opmn.xml/server.xml

PS Web Site Policies

This table lists PS Web Site policies.

Policy	Definition	Severity	Configuration File
Ig.isc.serverURL	The application server and WSL port combination should relate to a valid application server domain whose PUBSUB feature is set to active or true.	Warning	IntegrationGateway.properties
Ig.isc.toolsRel	The PeopleTools version specified should be equal to the PeopleTools version of the web server domain up to the patch level.	Warning	IntegrationGateway.properties
Compress Responses	Should be activated or set to true to enable faster transfer of transactional messages across the network.	Informational	Web Profile
Compress Response Reference	Should be activated or set to true to activate the compression from the web server to browser.	Informational	Web Profile

Policy	Definition	Severity	Configuration File
Cache Portal Objects	Should be activated to improve system performance by reducing service requests from the web server to the application server.	Informational	Web Profile
Cache Proxied Javascripts	These should be set to true for improved performance.	Informational	Web Profile
Cache Target Contents	These should be set to true for improved performance.	Informational	Web Profile
Cache homepage	These should be set to true for improved performance.	Informational	Web Profile
Cache Generated HTML	These should be set to true for improved performance.	Informational	Web Profile
METAXP	Should be equal to Cache Stale Interval. Cache Stale Interval value is seconds while METAXP is in minutes. So there should be a conversion that happens to detect a violation.	Warning	PeopleTools->Personalization->Personalization Options. Option Category Level = PPTL

Appendix E

Target Relationships

This appendix discusses:

- Links that display on homepages.
- Topology page relationships.

Links That Display on Homepages

This table lists links that display on target homepages:

<i>Link Displayed</i>	<i>Where</i>	<i>What It Means</i>
PS Application Database	Homepage of PS Application Server, PS Process Scheduler, PS Search Server	Successful discovery of the PS Application Database to which the target is connected.
PS Search Server	PS Application Server homepage	Valid entry in the Remote Search Server Credentials field (Search Section) in an application server domain configuration (psappsrv.cfg file that includes the domain ID, its fully qualified host name, and the search server port.
PeopleSoft System	Homepage of all targets	The target is an element of a PeopleSoft system.
Messaging Server	PS Application Server Administration page	Domain was created using a template (small, medium, large or custom) with these default sections of PUBSUB: PSBRKDSP_dlft, PSBRKHND_dlft, PSSUBDSP_dlft, PSSUBHND_dlft, PSPUBDSP_dlft, PSPUBHND_dlft
Windows Services Management	Administration page of PS Application Server, PS Process Scheduler, and PS Search Server	Host operating system is Windows
Manage Process Scheduler in PIA	PS Process Scheduler Administration page	PS Process Scheduler Domain is an element in a PeopleSoft system and has a URL defined for it.

Link Displayed	Where	What It Means
PS Application Server	PS Search Server homepage	PS Search Server Domain PSSRCHSRV section of configuration data has a valid entry for the application server credentials. The entry includes the domain ID, fully qualified host name and application server port (same value as the search server port).
Web Sites	PS PIA homepage	Successful discovery of PS Web Site, contained in this PS PIA target.
PS PIA	PS Web Site homepage PS Process Monitor homepage	Successful discovery of PS PIA in which the web site is contained.
PS Process Monitor	PS PIA homepage	Successful setup of Process Monitor with PS PIA.
PROCESSREQUEST WebService URL	PS Process Monitor homepage	Location of web service definition file configured using PeopleSoft Integration Broker. Process Monitor uses this web service to schedule and monitor PeopleSoft processes.
Reverse Proxy	PS PIA homepage	Yes value means the target is connected to a reverse proxy server. N/A value means the target is not connected to a reverse proxy server. Reverse proxy server data comes from the web profile's Virtual Addressing page.
Web Server Console	PS PIA Administration page	PS PIA is an element in a PeopleSoft system and has a Web Server Administration URL defined for it.
Web Profile	PS Web Site Administration page .	PS Web Site is an element of a PeopleSoft system and has a Web Profile URL defined for it.
Integration Broker	PS Web Site Administration page	PS Web Site is an element of a PeopleSoft system and has a Integration Broker URL defined for it.
PIA Signon	PS Web Site Administration page	PS Web Site is an element of a PeopleSoft system and has a PIA Signon URL defined for it.

Relationships on Topology Page

This table lists the target relationships shown on the topology page, and how they occur.

<i>Topology Page Relationships</i>	<i>Established How</i>
PS PIA and PS Web Site	Defined by a discovery search on web server directories and paths.
PS Web Site and PS Application Server	Depends on the psserver value in the PS Web Site's configuration.properties file. Valid entry is the application server's fully qualified host name and its Jolt port.
PS Application Server and PS Search Server	Depends on the remote search server credentials value in the application server domain's configuration (psappsrv.cfg) file. Valid entry includes the search server's domain ID, its fully qualified host name and the search server port.
PS Application Server and PS Application Database PS Process Scheduler and PS Application Database PS Search Server and PS Application Database	Defined by the database GUID, which is generated when an application server connects to the database the first time.
PS Process Monitor and PS PIA	Defined by user during Discovery or Process Monitor Setup. Process Monitor can be registered in repository with pre-discovered PS PIA target.

Index

A

- access (type) 14
- access Tuxedo command line 17
- add PeopleSoft targets 12, 28
- administration
 - Process Scheduler 57
 - PS Application Server 51
 - PS PIA 69
 - PS Process Monitor 63
 - PS Search Server Domain 77
 - PS Web Site 73
- administration page
 - common elements 15
 - target 14
- alert history 14
- alerts 13
- all metrics 14
- automated PeopleSoft system 81
- availability percentage 13

B

- beacon 83
- blackout 13
- blackouts 14

C

- clean IPC resources 17
- client status 18
- compare domain configurations 15
- compare to multiple configurations 15
- configuration
 - PS Application Database 43
 - template 49
- configure domain 15, 49
- configure site 20
- copy configurations 16
- crawl depth 30
- create like domain 15
- create service 82
- creating a PS Process Scheduler target 57
- creating a PS Search Server Domain target 76
- creating PS Application Server targets 47
- customize start/stop scripts 19

D

- databases discovered 34
- DB type 34
- delete domain 17
- discover PS_HOMEs 49
- discover related databases 34
- discovery

- overview 2
- discovery path 30
- discovery process 9, 27
- domain name 48

E

- editing PeopleSoft systems 84
- edit setEnv/ server.xml/ opmn.xml (link) 19
- edit web.xml (link) 19
- Enterprise Manager homepage 10
- environment set (check box) 33
- environment variables
 - set 35
 - table 35
- execute host command 18
- exporting a log file 23

F

- features (on homepage) 13

G

- general status 13
- get latest configuration template 49

H

- history 16
- homepage 55
 - common elements 13
 - Enterprise Manager 10
 - PeopleSoft system 80
 - PS Application Database 41
 - PS Application Server 45
 - PS PIA 67
 - PS Process Monitor 61
 - PS Search Server Domain 75
 - PS Web Site 71
 - target 12
- host 30, 48
- host alerts 13
- host log alert settings 23

I

- iAS console 19
- import domain configuration from file 49
- installing the PeopleSoft Environment
 - Management Plug-in 2
- Integration Broker 20

Integration Broker master domain 49

L

last collected configuration 16

log file

- exporting 23
- host alert settings 23
- searching for strings 23
- viewing 22

log management

- setup 23
- target 20

logs

- Process Scheduler 59
- PS Application Server 53
- PS PIA 71
- PS Search Server Domain 78

M

manage PS_HOMEs 49

managing a Process Scheduler in PIA 59

manual system creation 83

messaging server (link) 17

metric settings 14

modify OS group permissions of PS_HOMEs 31

monitoring configuration 13

N

name 34

naming conventions

- target 31

O

open telnet session 14

Oracle documentation

- online help 2
- sources 1
- where to find books 2

Oracle Technology Network (OTN) 2

overview of discovery 2

P

parameters for purging log files 24

PeopleSoft Environment Management Plug-in

- features 8
- installation 2
- Oracle sources of additional information 1
- overview 5
- pages 9

PeopleSoft subtab 11

PeopleSoft systems 79

- editing 84

removing 85

PeopleSoft targets

- add 28
- discovering 27

PeopleSoft target types 30

performance

- Process Scheduler 57
- PS Application Server 49
- PS PIA 69
- PS Process Monitor 63
- PS Search Server Domain 76
- PS Web Site 73

PIA signon 20

policies 14

policy

- settings 14
- violations 13

preload file cache 17

Process Monitor 18, 65

Process Monitor Setup 20

Process Scheduler 55

- administration 57
- creating a target 57
- homepage 55
- logs 59
- managing in PIA 59
- performance 57
- target 55

process status 18

PS_CFG_HOME 48

PS_HOME 48

PS App DB 82

PS Application Database

- configuration 43
- homepage 41
- target 41

PS Application Server

- administration 51
- creating a target 47
- homepage 45
- logs 53
- performance 49
- properties 48
- target 45

PS PIA

- administration 69
- homepage 67
- logs 71
- performance 69
- targets 67

PS Process Monitor

- administration 63
- homepage 61
- monitoring processes 65
- performance 63
- scheduling processes 64
- targets 61

PS Search Server Domain

- administration 77
- creating 76
- homepage 75
- logs 78
- performance 76
- target 75

PS Web Site

- administration 73
- homepage 71
- performance 73

- target 71
- PS Web Sites and User IDs 83
- purge/archive cache 17
- purge and archive
 - schedule job 24

Q

- queue status 18

R

- registering targets 32
- related links 13
- removing PeopleSoft systems 85
- reports 14

S

- Schedule Process 18, 64
- schedule purge and archive jobs 24
- searching for strings in log file 23
- select (checkbox) 34
- service name 82
- services 79
- services impacted 13
- set environment variables 34, 35
- setup logs 23
- start domain 16
- start PIA 19
- start target 13
- status 13
- stop domain 16
- stop PIA 19
- stop target 13
- subtab
 - PeopleSoft 11
- system name 82
- systems
 - PeopleSoft 79

T

- target 55
 - administration page 14
 - credentials for discovery 32
 - discovering a PeopleSoft 27
 - homepages 12
 - log management 20
 - naming conventions 31
 - properties 14
 - PS Application Database 41
 - PS PIA 67
 - PS Search Server Domain 75
 - PS Web Site 71
 - registering 32
 - types 30
- targets
 - PS Process Monitor 61

- targets tab 11
- target type 34
- target types
 - PeopleSoft, described 8
- timezone 82

V

- viewing a log file 22
- view saved configurations 16

W

- Weblogic console 19
- web profile 20
- WebSphere administration console 19
- Windows service management 18

