

# **Oracle® Solaris Cluster Data Service for SWIFTAlliance Gateway Guide**

SPARC Platform Edition

## **License Restrictions Warranty/Consequential Damages Disclaimer**

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

### **Warranty Disclaimer**

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

### **Restricted Rights Notice**

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

#### **U.S. GOVERNMENT RIGHTS**

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

### **Hazardous Applications Notice**

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

### **Trademark Notice**

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group in the United States and other countries.

### **Third Party Content, Products, and Services Disclaimer**

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

---

Ce logiciel et la documentation qui l'accompagne sont protégés par les lois sur la propriété intellectuelle. Ils sont concédés sous licence et soumis à des restrictions d'utilisation et de divulgation. Sauf disposition de votre contrat de licence ou de la loi, vous ne pouvez pas copier, reproduire, traduire, diffuser, modifier, breveter, transmettre, distribuer, exposer, exécuter, publier ou afficher le logiciel, même partiellement, sous quelque forme et par quelque procédé que ce soit. Par ailleurs, il est interdit de procéder à toute ingénierie inverse du logiciel, de le désassembler ou de le décompiler, excepté à des fins d'interopérabilité avec des logiciels tiers ou tel que prescrit par la loi.

Les informations fournies dans ce document sont susceptibles de modification sans préavis. Par ailleurs, Oracle Corporation ne garantit pas qu'elles soient exemptes d'erreurs et vous invite, le cas échéant, à lui en faire part par écrit.

Si ce logiciel, ou la documentation qui l'accompagne, est concédé sous licence au Gouvernement des Etats-Unis, ou à toute entité qui délivre la licence de ce logiciel ou l'utilise pour le compte du Gouvernement des Etats-Unis, la notice suivante s'applique :

U.S. GOVERNMENT RIGHTS. Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

Ce logiciel ou matériel a été développé pour un usage général dans le cadre d'applications de gestion des informations. Ce logiciel ou matériel n'est pas conçu ni n'est destiné à être utilisé dans des applications à risque, notamment dans des applications pouvant causer des dommages corporels. Si vous utilisez ce logiciel ou matériel dans le cadre d'applications dangereuses, il est de votre responsabilité de prendre toutes les mesures de secours, de sauvegarde, de redondance et autres mesures nécessaires à son utilisation dans des conditions optimales de sécurité. Oracle Corporation et ses affiliés déclinent toute responsabilité quant aux dommages causés par l'utilisation de ce logiciel ou matériel pour ce type d'applications.

Oracle et Java sont des marques déposées d'Oracle Corporation et/ou de ses affiliés. Tout autre nom mentionné peut correspondre à des marques appartenant à d'autres propriétaires qu'Oracle.

AMD, Opteron, le logo AMD et le logo AMD Opteron sont des marques ou des marques déposées d'Advanced Micro Devices. Intel et Intel Xeon sont des marques ou des marques déposées d'Intel Corporation. Toutes les marques SPARC sont utilisées sous licence et sont des marques ou des marques déposées de SPARC International, Inc. UNIX est une marque déposée concédée sous licence par X/Open Company, Ltd.

# Contents

---

- Preface .....5**
  
- 1 Installing and Configuring Oracle Solaris Cluster HA for Alliance Gateway ..... 11**
  - Oracle Solaris Cluster HA for Alliance Gateway Overview ..... 12
  - Overview of Installing and Configuring Oracle Solaris Cluster HA for Alliance Gateway ..... 12
  - Planning the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration ..... 13
    - Configuration Restrictions ..... 13
    - Configuration Requirements ..... 14
    - Configuration Considerations ..... 15
    - Configuration Planning Questions ..... 16
  - Installing and Configuring Alliance Gateway ..... 17
    - ▼ How to Install and Configure Alliance Gateway ..... 17
    - ▼ How to Verify the Alliance Gateway Installation and Configuration ..... 21
  - Installing the Oracle Solaris Cluster HA for Alliance Gateway Packages ..... 22
    - ▼ How to Install the Oracle Solaris Cluster HA for Alliance Gateway Packages ..... 22
  - Registering and Configuring the Oracle Solaris Cluster HA for Alliance Gateway ..... 24
    - ▼ How to Register and Configure Oracle Solaris Cluster HA for Alliance Gateway as a Failover Service ..... 24
  - Verifying the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration ..... 26
    - ▼ How to Verify the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration ..... 26
  - Tuning the Oracle Solaris Cluster HA for Alliance Gateway Fault Monitor ..... 27
  - Debugging Oracle Solaris Cluster HA for Alliance Gateway ..... 27
    - ▼ How to Set the Debug Flag for Oracle Solaris Cluster HA for Alliance Gateway ..... 27
    - ▼ How to Debug a Failed Restart for the Alliance Gateway Resource ..... 28

**Index .....31**

# Preface

---

*Oracle Solaris Cluster Data Service for SWIFT Alliance Gateway Guide* explains how to install and configure Oracle Solaris Cluster data services.

---

**Note** – This Oracle Solaris Cluster release supports systems that use the SPARC and x86 families of processor architectures: UltraSPARC, SPARC64, AMD64, and Intel 64. In this document, x86 refers to the larger family of 64-bit x86 compatible products. Information in this document pertains to all platforms unless otherwise specified.

---

This document is intended for system administrators with extensive knowledge of Oracle software and hardware. Do not use this document as a planning or presales guide. Before reading this document, you should have already determined your system requirements and purchased the appropriate equipment and software.

The instructions in this book assume knowledge of the Oracle Solaris Operating System and expertise with the volume-manager software that is used with Oracle Solaris Cluster software.

## Using UNIX Commands

This document contains information about commands that are specific to installing and configuring Oracle Solaris Cluster data services. The document does *not* contain comprehensive information about basic UNIX commands and procedures, such as shutting down the system, booting the system, and configuring devices. Information about basic UNIX commands and procedures is available from the following sources:

- Online documentation for the Oracle Solaris Operating System
- Oracle Solaris Operating System man pages
- Other software documentation that you received with your system

# Typographic Conventions

The following table describes the typographic conventions that are used in this book.

TABLE P-1   Typographic Conventions

Typeface	Meaning	Example
AaBbCc123	The names of commands, files, and directories, and onscreen computer output	Edit your <code>.login</code> file.  Use <code>ls -a</code> to list all files.  <code>machine_name%</code> you have mail.
<b>AaBbCc123</b>	What you type, contrasted with onscreen computer output	<code>machine_name% su</code>  Password:
<i>aabbcc123</i>	Placeholder: replace with a real name or value	The command to remove a file is <i>rm filename</i> .
<i>AaBbCc123</i>	Book titles, new terms, and terms to be emphasized	Read Chapter 6 in the <i>User's Guide</i> .  <i>A cache</i> is a copy that is stored locally.  Do <i>not</i> save the file.  <b>Note:</b> Some emphasized items appear bold online.

# Shell Prompts in Command Examples

The following table shows the default UNIX system prompt and superuser prompt for shells that are included in the Oracle Solaris OS. Note that the default system prompt that is displayed in command examples varies, depending on the Oracle Solaris release.

TABLE P-2   Shell Prompts

Shell	Prompt
Bash shell, Korn shell, and Bourne shell	\$
Bash shell, Korn shell, and Bourne shell for superuser	#
C shell	machine_name%
C shell for superuser	machine_name#

## Related Documentation

Information about related Oracle Solaris Cluster topics is available in the documentation that is listed in the following table. All Oracle Solaris Cluster documentation is available at <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

Topic	Documentation
Data service administration	<i>Oracle Solaris Cluster Data Services Planning and Administration Guide</i> Individual data service guides
Concepts	<i>Oracle Solaris Cluster Concepts Guide</i>
Software installation	<i>Oracle Solaris Cluster Software Installation Guide</i>
System administration	<i>Oracle Solaris Cluster System Administration Guide</i>
Hardware administration	<i>Oracle Solaris Cluster 3.3 Hardware Administration Manual</i> Individual hardware administration guides
Data service development	<i>Oracle Solaris Cluster Data Services Developer's Guide</i>
Error messages	<i>Oracle Solaris Cluster Error Messages Guide</i>
Command and function reference	<i>Oracle Solaris Cluster Reference Manual</i>

For a complete list of Oracle Solaris Cluster documentation, see the release notes for your release of Oracle Solaris Cluster at <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

## Related Third-Party Web Site References

Third-party URLs that are referenced in this document provide additional related information.

**Note** – Oracle is not responsible for the availability of third-party web sites mentioned in this document. Oracle does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Oracle will not be responsible or liable for any actual or alleged damage or loss caused or alleged to be caused by or in connection with use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

## Documentation and Support

See the following web sites for additional resources:

- [Documentation \(http://www.oracle.com/technetwork/indexes/documentation/index.html\)](http://www.oracle.com/technetwork/indexes/documentation/index.html)
- [Support \(http://www.oracle.com/us/support/systems/index.html\)](http://www.oracle.com/us/support/systems/index.html)

## Oracle Software Resources

[Oracle Technology Network \(http://www.oracle.com/technetwork/index.html\)](http://www.oracle.com/technetwork/index.html) offers a range of resources related to Oracle software:

- Discuss technical problems and solutions on the [Discussion Forums \(http://forums.oracle.com\)](http://forums.oracle.com).
- Get hands-on step-by-step tutorials with [Oracle By Example \(http://www.oracle.com/technetwork/tutorials/index.html\)](http://www.oracle.com/technetwork/tutorials/index.html).

## Getting Help

If you have problems installing or using Oracle Solaris Cluster, contact your service provider and provide the following information:

- Your name and email address (if available)
- Your company name, address, and phone number
- The model number and serial number of your systems
- The release number of the Oracle Solaris Operating System (for example, Oracle Solaris 10)
- The release number of Oracle Solaris Cluster (for example, Oracle Solaris Cluster 3.3)

Use the following commands to gather information about each node on your system for your service provider.

Command	Function
<code>prtconf -v</code>	Displays the size of the system memory and reports information about peripheral devices
<code>psrinfo -v</code>	Displays information about processors
<code>showrev -p</code>	Reports which patches are installed
<code>prtdiag -v</code>	Displays system diagnostic information
<code>/usr/cluster/bin/clnode show-rev</code>	Displays Oracle Solaris Cluster release and package version information



Also have available the contents of the `/var/adm/messages` file.



# Installing and Configuring Oracle Solaris Cluster HA for Alliance Gateway

---

This chapter explains how to install and configure Oracle Solaris Cluster HA for Alliance Gateway.

---

**Note** – In the current version, SWIFTAlliance Gateway is renamed as Alliance Gateway. You can use the Oracle Solaris Cluster HA for Alliance Gateway with both the product names. HA for Alliance Gateway 7.0 is supported for Oracle Solaris Cluster 3.3 only, and not for Oracle Solaris Cluster releases prior to 3.3.

---

This chapter contains the following sections.

- “Oracle Solaris Cluster HA for Alliance Gateway Overview” on page 12
- “Overview of Installing and Configuring Oracle Solaris Cluster HA for Alliance Gateway” on page 12
- “Planning the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration” on page 13
- “Installing and Configuring Alliance Gateway” on page 17
- “Installing the Oracle Solaris Cluster HA for Alliance Gateway Packages” on page 22
- “Registering and Configuring the Oracle Solaris Cluster HA for Alliance Gateway” on page 24
- “Verifying the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration” on page 26
- “Tuning the Oracle Solaris Cluster HA for Alliance Gateway Fault Monitor” on page 27
- “Debugging Oracle Solaris Cluster HA for Alliance Gateway” on page 27

# Oracle Solaris Cluster HA for Alliance Gateway Overview

The Oracle Solaris Cluster HA for Alliance Gateway data service provides a mechanism for orderly startup, shutdown, fault monitoring, switchover, and failover of the Oracle Solaris Cluster data service.

Oracle Solaris Cluster HA for Alliance Gateway provides software for fault monitoring by checking the status of the Alliance Gateway service. The values “started” and “partial” are considered healthy. Values other than these force a restart or failover to another node or zone in the cluster. By accepting a “partial” status, operators can temporarily disable portions of the service without informing the cluster. You do not need a user ID and password for monitoring.

For conceptual information about failover data services and scalable data services, see [Oracle Solaris Cluster Concepts Guide](#).

Each component of Alliance Gateway has a data service that protects the component when the component is configured in an Oracle Solaris Cluster environment. See the following table.

TABLE 1-1 Protection of Alliance Gateway Components

Component	Protected by
SWIFTNet Link	Oracle Solaris Cluster HA for Alliance Gateway
Alliance Gateway	Oracle Solaris Cluster HA for Alliance Gateway

## Overview of Installing and Configuring Oracle Solaris Cluster HA for Alliance Gateway

The following table summarizes the tasks for installing and configuring Oracle Solaris Cluster HA for Alliance Gateway and provides cross-references to detailed instructions for performing these tasks. Perform the tasks in the order that they are listed in the table.

TABLE 1-2 Tasks for Installing and Configuring Oracle Solaris Cluster HA for Alliance Gateway

Task	Instructions
Plan the Alliance Gateway installation	<a href="#">“Planning the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration” on page 13</a>
Install and configure Alliance Gateway	<a href="#">“Installing and Configuring Alliance Gateway” on page 17</a>
Install the Oracle Solaris Cluster HA for Alliance Gateway packages	<a href="#">“Installing and Configuring Alliance Gateway” on page 17</a>

TABLE 1–2 Tasks for Installing and Configuring Oracle Solaris Cluster HA for Alliance Gateway  
(Continued)

Task	Instructions
Register the Oracle Solaris Cluster HA for Alliance Gateway data service and configure the cluster for the data service	<a href="#">“Registering and Configuring the Oracle Solaris Cluster HA for Alliance Gateway” on page 24</a>
Verify Oracle Solaris Cluster HA for Alliance Gateway	<a href="#">“Verifying the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration” on page 26</a>
Tuning the Oracle Solaris Cluster HA for Alliance Gateway fault monitor	<a href="#">“Tuning the Oracle Solaris Cluster HA for Alliance Gateway Fault Monitor” on page 27</a>
(Optional) Debug Oracle Solaris Cluster HA for Alliance Gateway	<a href="#">“Debugging Oracle Solaris Cluster HA for Alliance Gateway” on page 27</a>

# Planning the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration

This section contains the information that you need to plan your Oracle Solaris Cluster HA for Alliance Gateway installation and configuration.

**Note** – Before you begin, consult your Alliance Gateway documentation for configuration restrictions and requirements that are not imposed by Oracle Solaris Cluster software. For information about restrictions that the Oracle Solaris Cluster software imposes, see the Oracle Solaris Cluster documentation.

## Configuration Restrictions

The configuration restrictions in this section apply only to Oracle Solaris Cluster HA for Alliance Gateway.



**Caution** – If your data service configuration does not conform to these restrictions, the data service configuration might not be supported.

For restrictions that apply to all data services, see [Oracle Solaris Cluster 3.3 Release Notes](#).

- Oracle Solaris Cluster HA for Alliance Gateway supports Alliance Gateway version 6.0, 6.1, 6.3, and 7.0.

- You can install the SWIFTNet Link and the Alliance Gateway software only on a failover file system. If WebSphere MQ client software is needed for the operation of Alliance Gateway, install WebSphere MQ client software on the local file system in the same path on each cluster node or zone that can master the resource group. The default path is `/opt/mqm`.
- You cannot configure Oracle Solaris Cluster HA for Alliance Gateway as a scalable data service.
- If the Alliance Gateway instance is started through the cluster resource, do not stop it manually. Instead, stop Alliance Gateway by disabling the corresponding cluster resource.

---

**Note** – The Oracle Solaris Cluster HA for Alliance Gateway can be configured to run in a whole root or sparse root non-global zone for Oracle Solaris Cluster HA for Alliance Gateway version 6.0, 6.1, 6.3, or 7.0 if required.

---

## Configuration Requirements

The configuration requirements in this section apply only to Oracle Solaris Cluster HA for Alliance Gateway.




---

**Caution** – If your data service configuration does not satisfy these requirements, the data service configuration might not be supported.

---

For requirements that apply to all data services, see “[Configuration Guidelines for Oracle Solaris Cluster Data Services](#)” in *Oracle Solaris Cluster Data Services Planning and Administration Guide*.

- You must configure Oracle Solaris Cluster HA for Alliance Gateway as a failover data service.
- Create the following groups with the same group ID on all cluster nodes or zones that can master the resource group: `sagsnlg`, `swnetg`.
 

```
# groupadd -g groupid1 swnetg
# groupadd -g groupid2 sagsnlg
```
- Create the following user with the same user ID on all cluster nodes or zones that can master the resource group: `swnet`.
 

```
# useradd -u userid -g swnetg -d /export/home/swnet -s /usr/bin/ksh swnet
```
- Create a Solaris project called `swift` on all cluster nodes or zones that can master the resource group.

For Alliance Gateway 6.3 and prior versions:

```
# projadd -U swnet swift
```

```
# projmod -s -K 'project.max-sem-ids=(privileged,1080,deny)' swift
# projmod -s -K 'process.max-sem-nsems=(privileged,512,deny)' swift
# projmod -s -K 'project.max-shm-memory=(privileged,4294967295,deny)' swift
# projmod -s -K 'project.max-shm-ids=(privileged,1200,deny)' swift
# projmod -s -K 'process.max-msg-qbytes=(privileged,10485760,deny)' swift
# projmod -s -K 'process.max-msg-messages=(privileged,8192,deny)' swift
```

For Alliance Gateway 7.0:

```
# projadd -U swnet swift
# projmod -s -K 'project.max-sem-ids=(privileged,1320,deny)' swift
# projmod -s -K 'process.max-sem-nsems=(privileged,512,deny)' swift
# projmod -s -K 'project.max-shm-memory=(privileged,4294967295,deny)' swift
# projmod -s -K 'project.max-shm-ids=(privileged,1500,deny)' swift
# projmod -s -K 'project.max-msg-ids=(privileged,800,deny)' swift
# projmod -s -K 'process.max-msg-qbytes=(privileged,10485760,deny)' swift
# projmod -s -K 'process.max-msg-messages=(privileged,8192,deny)' swift
# projmod -s -K 'process.max-sem-ops=(privileged,512,deny)' swift
```

The previous values are examples only. For more accurate values refer to the SWIFTNet Link and Alliance Gateway latest documentation release notes.

- Assign project `swift` as default project for `swnet` user by editing the `/etc/user_attr` file and adding the following line at the end of the file on all cluster nodes or zones that can master the resource group:

```
swnet:::project=swift
```

- Refer to the SWIFTNet Link and Alliance Gateway documentation Release Notes for the required setup in the `/etc/system` directory on all cluster nodes.

## Configuration Considerations

The configuration considerations in the subsections that follow affect the installation and configuration of Oracle Solaris Cluster HA for Alliance Gateway.

### Resource Dependencies

Configure Oracle Solaris Cluster HA for Alliance Gateway to protect an Oracle Solaris Cluster instance and its respective components. The following table outlines these components and their dependencies.

TABLE 1-3 Oracle Solaris Cluster Components

Component	Dependencies
Alliance Gateway  This component includes the SWIFTNet Link instance.	<ul style="list-style-type: none"><li>■ SUNW.LogicalHost resource</li><li>■ SUNW.HAStoragePlus resource</li></ul>

## Configuration Files and Registration Script

The Oracle Solaris Cluster component has a configuration file and a registration script.

<code>/opt/SUNWscsag/util/sag_config</code>	This configuration file contains settings to register the data service and the application in the Oracle Solaris Cluster framework.
<code>/opt/SUNWscsag/util/sag_register</code>	This registration script enables you to register the data service.

**Note** – The `/opt/SUNWscsag/etc/settings` configuration file is obsolete and is no longer necessary for new data service registrations. All necessary variables are included in the `/opt/SUNWscsag/util/sag_config` configuration file. Resources that were registered prior to this change will still use the `/opt/SUNWscsag/etc/settings` configuration file.

## Configuration Planning Questions

Use the questions in this section to plan the installation and configuration of Oracle Solaris Cluster HA for Alliance Gateway. Write the answers to these questions in the space that is provided on the data service worksheets in “[Configuration Worksheets](#)” in *Oracle Solaris Cluster Data Services Planning and Administration Guide*.

- Do you have a SWIFTNet connection and an Internet connection? The installation requires a secure server from SWIFT.
- Do you have your Alliance Gateway license key? If not, retrieve this information.
- Do you have your Alliance Gateway installation documentation? If not, refer the documentation available in the Alliance Gateway CD-ROM.
- Before you run Oracle Solaris Cluster HA for Alliance Gateway as a failover data service, answer the following questions:
  - Which resource groups will you use for the Alliance Gateway application resource and the logical host name resource?



- What is the logical hostname for the Alliance Gateway resource? Clients access the data service through this logical hostname.
- Where will the system configuration files reside?  
See “[Configuration Guidelines for Oracle Solaris Cluster Data Services](#)” in *Oracle Solaris Cluster Data Services Planning and Administration Guide* for the advantages and disadvantages of using the local file system instead of the cluster file system.

## Installing and Configuring Alliance Gateway

To enable Oracle Solaris Cluster HA for Alliance Gateway to make Alliance Gateway highly available, additional installation and configuration operations are required. These operations supplement the standard installation and standard configuration of Alliance Gateway.

During a standard installation, Alliance Gateway is installed with a physical hostname. To enable Alliance Gateway to run in a cluster, you must modify Alliance Gateway to use a logical hostname.

For information about the standard installation and standard configuration of Alliance Gateway, see the appropriate documentation available in the Alliance Gateway CD-ROM.

To perform this procedure, you need the server root directory (the path to the application binaries). You can install the binaries on the local disks or on the cluster file system. For a discussion of the advantages and disadvantages of each location, see [Chapter 1, “Planning for Oracle Solaris Cluster Data Services,”](#) in *Oracle Solaris Cluster Data Services Planning and Administration Guide*.

### ▼ How to Install and Configure Alliance Gateway

#### 1 Create a resource group for Alliance Gateway.

```
# clresourcegroup create [-n node-zone-list] sag-rg
```

-n node-zone-list

Specifies a comma-separated, ordered list of zones that can master the resource group. The format of each entry in the list is node. In this format, node specifies the node name and zone specifies the name of a non-global Solaris zone. To specify the global zone, or to specify a node without non-global zones, specify only node. This list is optional. If you omit this list, the global zone of each cluster node can master the resource group.

#### 2 Create a logical host.

A logical host is required before you install Alliance Gateway.

- a. Add the hostname and the IP address in the `/etc/inet/hosts` file on all cluster nodes or zones that can master the resource group.

**b. Register the logical host, and then add the logical host resource to the resource group.**

```
# clreslogicalhostname -g sag-rg -h swiftgatewayhost sag-lh-rs
```

**3 Create the device group and file systems.**

Although you can use a global file system, create an HAStoragePlus failover resource to contain the Alliance Gateway application and configuration data.

- To create a device group and a file system for Alliance Gateway, see [“Planning the Global Devices, Device Groups, and Cluster File Systems” in Oracle Solaris Cluster Software Installation Guide](#).
- To create an HAStoragePlus failover resource, see [“Enabling Highly Available Local File Systems” in Oracle Solaris Cluster Data Services Planning and Administration Guide](#).

This procedure uses `/swift` as the path that contains the Alliance Gateway application and configuration data.

```
# clresource create -g sag-rg \
-t SUNW.HAStoragePlus -x filesystemMountPoints=/swift sag-ds
```

**4 Bring the resource group online to enable the IP address and access to the storage.**

```
# clresourcegroup online -M sag-rg
```

**5 Create the following directories and symbolic links before the installation.**

Without these symbolic links, the Alliance Gateway application will not be installed in the correct location. You must install the Alliance Gateway application in the correct location to ensure failover capabilities.

Perform this procedure on the node where the resource group for Alliance Gateway is online.

For Alliance Gateway 6.3 and prior versions:

```
# mkdir -p /swift/etc/opt/swnet
# chown root:swnetg /swift/etc/opt/swnet
# chmod -R 0555 /swift/etc
# chmod 0775 /swift/etc/opt/swnet
# mkdir -p /swift/var/opt/swnet
# chown root:swnetg /swift/var/opt/swnet
# chmod -R 0555 /swift/var
# chmod 0775 /swift/var/opt/swnet
# mkdir -p /swift/home/swnet
# chown swnet:swnetg /swift/home/swnet
```

For Alliance Gateway 7.0:

```
# mkdir -p /swift/etc/opt/swnet /swift/etc/opt/secrets_backup
# chown swnet:swnetg /swift/etc/opt/swnet /swift/etc/opt/secrets_backup
# chmod -R 0555 /swift/etc
# chmod 0775 /swift/etc/opt/swnet /swift/etc/opt/secrets_backup
# mkdir -p /swift/var/opt/swnet /swift/var/opt/swift
# chown swnet:swnetg /swift/var/opt/swnet /swift/var/opt/swift
# chmod -R 0555 /swift/var
```

```
# chmod 0775 /swift/var/opt/swnet /swift/var/opt/swift
# mkdir -p /swift/home/swnet
# chown swnet:swnetg /swift/home/swnet
```

Perform this procedure on all cluster nodes.

For Alliance Gateway 6.3 and prior versions:

```
# ln -s /swift/home/swnet /export/home/swnet
# ln -s /swift/etc/opt/swnet /etc/opt/swnet
# ln -s /swift/var/opt/swnet /var/opt/swnet
```

For Alliance Gateway 7.0:

```
# ln -s /swift/home/swnet /export//home/swnet
# ln -s /swift/etc/opt/swnet /etc/opt/swnet
# ln -s /swift/etc/opt/secrets_backup /etc/opt/secrets_backup
# ln -s /swift/var/opt/swnet /var/opt/swnet
# ln -s /swift/var/opt/swift /var/opt/swift
```

## 6 Install the WebSphere MQ client packages, if required.

WebSphere MQ client software is software that guarantees and load-balances connections between the gateway and remote SWIFTNet Link systems. If you chose this type of Alliance Gateway installation and have the appropriate license, install the WebSphere MQ client packages. The WebSphere MQ client package must be installed locally by using the same installation directory on all cluster nodes or zones that can master the resource group.

## 7 Install SWIFTNet Link.

You must install SWIFTNet Link on the node or zone where the resource group for Alliance Gateway is online. You must also install SWIFTNet Link in the directory on the file system managed by the HASStoragePlus resource that you created in [Step 3](#).

- Follow the instructions in your SWIFTNet Link documentation. To refer the SWIFTNet Link documentation, obtain the SWIFTNet Link CD-ROM.
- Specify the directory on which to install the failover data service: `/swift/snl`.
- Install any patches for SWIFTNet Link, if required.
- The Hardware Security Module (HSM) Installation/Configuration wizard starts up automatically when you click Finish at the end of SWIFTNet Link installation. Click Cancel to exit the HSM Installation/Configuration wizard.
- Verify that connectivity with SWIFTNet Switch is established by running the SWIFTNet Link `selftest` command. For more information, see *SWIFTNet Admin Services: Operational Interface* on the Alliance Gateway CD-ROM.
- Stop the SWIFTNet Link instance by running the SWIFTNet Link `stop` command.

## 8 Configure and register HSM on the primary node as follows.

- Log on to the primary node or zone as the SWIFTNet Link instance owner with the `swnet` account.

- Run the following command:  

```
# perl SwHSMDiskClone.pl -a SETUP
```
- Log off.
- Log on as the SWIFTNet Link instance owner with the `swnet` account.
- Use the HSM administration tool SwHSM to configure and register the HSM boxes connected to the primary node. See the *SWIFTNet Link Installation and Administration Guide for UNIX* for details.

---

**Note** – During the configuration and registration of the HSM, you must enter the boot IP address of the primary node in the SWIFTNet Link host IP address field of the Register screen. This source IP address is used to establish the connection. Do not use the logical host address that is used by the service.

---

## 9 Register HSM on the secondary node or zone.

- Switch the resource group for Alliance Gateway to the secondary node or zone.  

```
# clresourcegroup switch -n node2 sag-rg
```
- Log on to the secondary node as the SWIFTNet Link instance owner with the `swnet` account.
- Run the following command:  

```
# perl SwHSMDiskClone.pl -a SETUP
```
- Log off.
- Log on as the SWIFTNet Link instance owner with the `swnet` account.
- Use the HSM administration tool SwHSM to register the HSM boxes connected to the secondary node or zone. See the *SWIFTNet Link Installation and Administration Guide for UNIX* for details.

---

**Note** – During the registration of the HSM, you must enter the boot IP address of the secondary node or zone in the SWIFTNet Link host IP address field of the Register screen. This source IP address is used to establish the connection. Do not use the logical host address that is used by the service.

---

---

**Note** – You must be aware that the only difference between [Step 8](#) and this step is that you configure and register the HSM on the first node or zone in [Step 8](#), whereas you only register the HSM on the secondary node or zone in this step.

---

**10 Install Alliance Gateway software.**

You must install Alliance Gateway on the node or zone where the resource group for Alliance Gateway is online. You must also install Alliance Gateway in a directory on the file system managed by the HASToragePlus resource that you created in [Step 3](#). In this procedure, `/swift/SWIFTAlliance/Gateway` is being used as the directory. You might install the Alliance Gateway patches, if necessary.

- Follow the instructions in your Alliance Gateway documentation. To refer the Alliance Gateway documentation, obtain the Alliance Gateway CD-ROM.
- Use the logical IP address as the IP with which the Alliance Gateway software communicates with remote hosts.

**11 Synchronize all nodes or zones with installation-specific changes to user files and system files.**

- For Alliance Gateway 6.3 and prior versions: The `~root/vpd.properties` directory has been replaced by the `~root/InstallShield` directory structure. This directory structure needs to be copied on all cluster nodes or zones that can master the resource group. It enables you to install patches in the future. Moreover, after every SWIFTNet Link or Alliance Gateway patches installation or uninstallation, the synchronization of the `~root/InstallShield` directory has to be redone.
- Add all entries in `/etc/system` and `/etc/services` added by the installation on the first node to the secondary node or zone that can master the resource group. The entries in `/etc/system` must be applied to the global zone.

**Next Steps** Go to [“How to Verify the Alliance Gateway Installation and Configuration”](#) on page 21.

## ▼ How to Verify the Alliance Gateway Installation and Configuration

Perform this procedure on each node or zone that can master the Alliance Gateway resource group.

- 1 Log in as superuser to a node or zone that can master the Alliance Gateway resource group.**
- 2 Switch the Alliance Gateway resource group to the node or zone that you logged in to in [Step 1](#).**

```
# clresourcegroup switch -h node sag-rg
```

`sag-rg` Specifies that the Alliance Gateway resource group is to be switched to another node or zone

`-h node` Specifies the node or node:zone to which the Alliance Gateway resource group is to be switched

**3 Confirm that the Alliance Gateway instance can be started.**

```
# su - swnet
$ cd /swift/SWIFTAlliance/Gateway/bin
$ ./sag_bootstrap -startsag start
$ ./sag_system -- status system
```

---

**Note** – The application starts successfully if the preceding command returns a started status. This status indicates that the Alliance Gateway is operational.

---

**4 Create another Alliance Gateway operator with an operating profile that contains only the functions to start and stop the application.**

**5 Confirm that the Alliance Gateway instance can be stopped.**

```
# su - swnet
$ cd /swift/SWIFTAlliance/Gateway/bin
$ ./sag_bootstrap stop
```

**Next Steps** Go to [“Installing the Oracle Solaris Cluster HA for Alliance Gateway Packages”](#) on page 22.

## Installing the Oracle Solaris Cluster HA for Alliance Gateway Packages

If you did not install the Oracle Solaris Cluster HA for Alliance Gateway packages during your initial Oracle Solaris Cluster installation, perform this procedure to install the packages. To install the packages, use the `installer` program.

---

**Note** – You need to install the Oracle Solaris Cluster HA for Alliance Gateway packages in the global cluster and not in the zone cluster.

---

### ▼ How to Install the Oracle Solaris Cluster HA for Alliance Gateway Packages

Perform this procedure on each cluster node where you want the Oracle Solaris Cluster HA for Alliance Gateway software to run.

You can run the `installer` program with a command-line interface (CLI) or with a graphical user interface (GUI). The content and sequence of instructions in the CLI and the GUI are similar.

---

**Note** – Even if you plan to configure this data service to run in non-global zones, install the packages for this data service in the global zone. The packages are propagated to any existing non-global zones and to any non-global zones that are created after you install the packages.

---

**Before You Begin** Ensure that you have the Oracle Solaris Cluster installation media.

If you intend to run the installer program with a GUI, ensure that your DISPLAY environment variable is set.

- 1 On the cluster node where you are installing the data service packages, become superuser.**
- 2 Load the Oracle Solaris Cluster installation media into the DVD-ROM drive.**

If the Volume Management daemon `vold(1M)` is running and configured to manage DVD-ROM devices, the daemon automatically mounts the DVD-ROM on the `/cdrom` directory.
- 3 Change to the installation wizard directory of the DVD-ROM.**
  - If you are installing the data service packages on the SPARC platform, type the following command:  

```
# cd /cdrom/cdrom0/Solaris_sparc
```
  - If you are installing the data service packages on the x86 platform, type the following command:  

```
# cd /cdrom/cdrom0/Solaris_x86
```
- 4 Start the installation wizard.**  

```
# ./installer
```
- 5 When you are prompted, accept the license agreement.**
- 6 From the list of Oracle Solaris Cluster agents under Availability Services, select the data service for Alliance Gateway.**
- 7 If you require support for languages other than English, select the option to install multilingual packages.**

English language support is always installed.
- 8 When prompted whether to configure the data service now or later, choose Configure Later.**

Choose Configure Later to perform the configuration after the installation.

**9 Follow the instructions on the screen to install the data service packages on the node.**

The installation wizard displays the status of the installation. When the installation is complete, the wizard displays an installation summary and the installation logs.

**10 (GUI only) If you do not want to register the product and receive product updates, deselect the Product Registration option.**

The Product Registration option is not available with the CLI. If you are running the installation wizard with the CLI, omit this step.

**11 Exit the installation wizard.**

**12 Unload the installation media from the DVD-ROM drive.**

a. To ensure that the DVD-ROM is not being used, change to a directory that does *not* reside on the DVD-ROM.

b. Eject the DVD-ROM.

```
# eject cdrom
```

## Registering and Configuring the Oracle Solaris Cluster HA for Alliance Gateway

This section contains the procedures that you need to configure Oracle Solaris Cluster HA for Alliance Gateway.

To enable Oracle Solaris Cluster HA for Alliance Gateway to make Alliance Gateway highly available, configure the Oracle Solaris Cluster HA for Alliance Gateway data service as a failover data service.

Before you perform this procedure, ensure that the Oracle Solaris Cluster HA for Alliance Gateway data service packages are installed.

### ▼ How to Register and Configure Oracle Solaris Cluster HA for Alliance Gateway as a Failover Service

Use this procedure to configure the Oracle Solaris Cluster HA for Alliance Gateway data service as a failover service.

**1 Become superuser on one of the nodes in the cluster that is the host for Alliance Gateway.**



**2 Register the SUNW.gds resource type.**

```
# clresourcetype register SUNW.gds
```

**3 Register the SUNW.HAStoragePlus resource type.**

```
# clresourcetype register SUNW.HAStoragePlus
```

**4 Create the failover resource group.**

```
# clresourcegroup create [-n node-zone-list] sag-rg
```

```
-n node-zone-list
```

Specifies a comma-separated, ordered list of zones that can master the resource group. The format of each entry in the list is `node`. In this format, `node` specifies the node name and zone specifies the name of a non-global Solaris zone. To specify the global zone, or to specify a node without non-global zones, specify only `node`. This list is optional. If you omit this list, the global zone of each cluster node can master the resource group.

**5 Create a resource for the Oracle Solaris Cluster Disk Storage.**

```
# clresource create -g sag-rg \  
-t SUNW.HAStoragePlus \  
-x FilesystemMountPoints=/swift sag-ds-rs
```

```
sag-ds-rs
```

Specifies that the resource that you are creating is named *sag-ds-rs*.

```
-g sag-rg
```

Specifies that the resource is to be added to the Alliance Gateway resource group.

```
-x FilesystemMountPoints=mountpoint-list
```

Specifies a list of valid mount points for the file system.

**6 Create a resource for the Oracle Solaris Cluster logical hostname.**

```
# clreslogicalhost create -g sag-rg \  
-h gatewayhostname sag-lh-rs
```

**7 Enable the failover resource that contains the Oracle Solaris Cluster Disk Storage and the Logical hostname resources.**

```
# clresourcegroup online -eM sag-rg
```

**8 Create a resource for Alliance Gateway.****a. Change the variables in the `/opt/SUNWscsag/util/sag_config` file.**

For information about this file, see [“Configuration Files and Registration Script”](#) on page 16.

**b. Run the registration script to register the data service and application.**

For information about this script, see [“Configuration Files and Registration Script” on page 16.](#)

```
# /opt/SUNWscsag/util/sag_register
```

**9 Enable the Alliance Gateway resource.**

```
# clresource enable sag-resource-rs
```

**Next Steps** Go to [“Verifying the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration” on page 26.](#)

## Verifying the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration

This section contains the procedure to verify that you installed and configured your data service properly.

### ▼ How to Verify the Oracle Solaris Cluster HA for Alliance Gateway Installation and Configuration

**1 Become superuser on one of the nodes or zones in the cluster that hosts Alliance Gateway.**

**2 Ensure that all the Oracle Solaris Cluster resources are online.**

```
# cluster status
# clresource enable resource
```

**3 Move the Oracle Solaris Cluster resource group to another cluster node or zone, such as *node1*.**

```
# clresource group switch -h node1 sag-rg
```

**4 Ensure that Alliance Gateway stopped on *node1* and that the application started on another node or zone, such as *node2*.**

When using a failover file system, the file system disappears on *node1* and mounts on *node2*.

**Next Steps** Go to [“Tuning the Oracle Solaris Cluster HA for Alliance Gateway Fault Monitor” on page 27.](#)

## Tuning the Oracle Solaris Cluster HA for Alliance Gateway Fault Monitor

Oracle Solaris Cluster HA for Alliance Gateway provides software for fault monitoring by checking the status of the Alliance Gateway service. The values “started” and “partial” are considered healthy. Values other than these force a restart or failover to another node in the cluster. By accepting a “partial” status, operators can temporarily disable portions of the service without informing the cluster. You do not need a user ID and password for monitoring.

The Oracle Solaris Cluster HA for Alliance Gateway fault monitor is contained in the resource that represents Alliance Gateway. You create this resource when you register and configure Oracle Solaris Cluster HA for Alliance Gateway. For more information, see [“Registering and Configuring the Oracle Solaris Cluster HA for Alliance Gateway” on page 24](#).

System properties and extension properties of this resource control the behavior of the fault monitor. The default values of these properties determine the preset behavior of the fault monitor. The preset behavior should be suitable for most Oracle Solaris Cluster installations. Therefore, tune the Oracle Solaris Cluster HA for Alliance Gateway fault monitor *only* if you need to modify this behavior.

Tuning the Oracle Solaris Cluster HA for Alliance Gateway fault monitor involves the following tasks:

- Setting the interval between fault monitor probes
- Setting the timeout for fault monitor probes
- Defining the criteria for persistent faults
- Specifying the failover behavior of a resource

Perform these tasks when you register and configure Oracle Solaris Cluster HA for Alliance Gateway. For more information, see the following sections:

- [“Registering and Configuring the Oracle Solaris Cluster HA for Alliance Gateway” on page 24](#)
- [“Tuning Fault Monitors for Oracle Solaris Cluster Data Services” in \*Oracle Solaris Cluster Data Services Planning and Administration Guide\*](#)

## Debugging Oracle Solaris Cluster HA for Alliance Gateway

### ▼ How to Set the Debug Flag for Oracle Solaris Cluster HA for Alliance Gateway

Oracle Solaris Cluster HA for Alliance Gateway has an option file in `/opt/SUNWscsag/etc` directory that enables you to set a debug flag.

Normally, the debug information for Oracle Solaris Cluster software does not reside in the log files. You must edit the `syslog.conf` file to enable logging of messages of level debug. You can edit the `syslog.conf` to log those messages in another file.

## 1 Edit the `/etc/syslog.conf` file.

### a. Change `daemon.notice` to `daemon.debug`.

The following output from the `grep daemon /etc/syslog.conf` command shows that `daemon.debug` has not been set.

```
grep daemon /etc/syslog.conf
*.err;kern.debug;daemon.notice;mail.crit
/var/adm/messages
*.alert;kern.err;daemon.err
operator
```

### b. Restart `syslogd`.

```
# pkill -1 syslogd
```

The `syslogd` command forces `syslog` to reread its configuration file and account for changes.

The following output from the `grep daemon /etc/syslog.conf` command shows that `daemon.debug` has been set.

```
grep daemon /etc/syslog.conf
*.err;kern.debug;daemon.debug;mail.crit
/var/adm/messages
*.alert;kern.err;daemon.err
operator
```

## 2 Edit the `/opt/SUNWscsag/etc/config` file.

Change the line `DEBUG=` to `DEBUG=ALL` or `DEBUG=resource`.

## ▼ How to Debug a Failed Restart for the Alliance Gateway Resource

If the Alliance Gateway instance failed to restart on a cluster node or zone, but the instance did successfully fail over to another cluster node or zone, perform the following steps on the node or zone where the restart failed.

### 1 Log in as the Alliance Gateway UNIX user `swnet`.

### 2 Use the `ipcs(1)` command to determine if there are active inter-process communication (IPC) facilities for the `swnet` user.

```
$ ipcs -opqs | grep swnet
```

- 3 If you see output for the command you ran in [Step 2](#), verify that there is no Alliance Gateway instance running on this node or zone.**

To clean up the IPC resource from the swnet user, either use the `ipcrm(1)` command for each facility for the swnet user, or reboot the node or zone.

You can switch the resource group with the Alliance Gateway instance back to this node or zone only if there are no IPC resources left for the swnet user.



# Index

---

## A

- Alliance Gateway application
  - configuring, 17–22
  - fault monitor, 27
  - installing, 17–22
  - protection by data services, 12
  - resource group for
    - enabling, 21
    - planning, 16
  - versions supported, 13–14

## C

- `clnode` command, 8
- commands, node information, 8
- configuration files, 16
- configuration requirements, 14–15
- configuring
  - Alliance Gateway application, 17–22
  - Oracle Solaris Cluster HA for Alliance Gateway
    - performing, 24–26
    - planning, 13–17

## D

- `daemon.debug`, 28
- `daemon.notice`, 28
- debug, failed restart, 28–29
- debug flag, 27–28
- dependencies, resource, 15–16

## F

- failed restart, debug, 28–29
- fault monitors
  - Alliance Gateway
    - resource type for, 27
  - tuning, 27
- files, system configuration, 17

## G

- global zone, 23

## H

- help, 8–9

## I

- installing
  - Alliance Gateway application, 17–22
  - Oracle Solaris Cluster HA for Alliance Gateway, 22–24
    - verifying installation, 26

## L

- local zones, *See* non-global zones

**logical host names**

- resource group for
  - enabling, 21
  - planning, 16
- resources
  - planning, 17

**M**

messages file, 9

**N**

network addresses, *See* logical host names  
non-global zones, 23

**O**

/opt/SUNWscsag/util/sag\_config file, 16, 25  
/opt/SUNWscsag/util/sag\_register script, 16, 26  
Oracle Solaris Cluster HA for Alliance Gateway

- overview, 12
- configuration
  - performing, 24–26
  - planning, 13–17
- fault monitors, 27
- installing, 22–24
  - verifying installation, 26
- software packages, installing, 22–24

**P**

packages, 22–24  
protection, Alliance Gateway application, 12  
prtconf -v command, 8  
prtdiag -v command, 8  
psrinfo -v command, 8

**R**

registering during initial setup, SUNW.gds resource type, 25  
registration files, 16  
resource groups

- Alliance Gateway
  - enabling, 21
  - planning, 16
- logical hostname
  - enabling, 21
  - planning, 16

resource types

- fault monitors, 27
- SUNW.gds, initial registration, 25

resources

- dependencies, 15–16
- logical hostname
  - planning, 17

restrictions, 13–14  
zones, 23

**S**

show-rev subcommand, 8  
showrev -p command, 8  
software packages, 22–24  
SUNW.gds resource type, registering during initial setup, 25  
SWIFTNet Link, 19  
syslog.conf file, 27  
system configuration files, location, 17  
system properties, effect on fault monitors, 27

**T**

technical support, 8–9  
tuning, fault monitors, 27

**V**

/var/adm/messages file, 9  
versions supported, 13–14



**W**

WebSphere MQ client software, 14

**Z**

zones, 23

