

**Sun Virtual Desktop Infrastructure**  
Update Guide for Version 3.1

April 2011

**ORACLE®**

Copyright © 2011, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners. Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark licensed through X/Open Company, Ltd.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

# VDI 3.1 Update Installation (All Topics)

## Contents


- About Updating to VDI 3.1
- How to Update to VDI 3.1 (Single VDI Host)
- How to Update to VDI 3.1 (High Availability with Bundled MySQL Database)
- How to Update to VDI 3.1 (High Availability with Remote Database)
- How to Update to VDI 3.1 (VirtualBox and vCenter Virtualization Platforms)
- How to Back Up and Restore Data (Bundled MySQL Database)
- How to Back Up and Restore Data (Remote MySQL Database)

## VDI 3.1 Update Installation (All Topics)

### About Updating to VDI 3.1

Because of the various supported databases and virtualization platforms in VDI 3, it's necessary to follow specific instructions for updating to version 3.1. The following update paths are currently supported:

- VDI 3 to VDI 3.1 (Single Host Configuration)
- VDI 3 to VDI 3.1 (High Availability with Bundled MySQL Database)
- VDI 3 to VDI 3.1 (High Availability with Remote Database)



In addition to updating the VDI Core setup, the virtualization platform will also require an update.

If your VDI 3 installation has a VirtualBox virtualization platform, it's required that you update to the [supported version](#) of VirtualBox for VDI 3.1. The VirtualBox server should be updated after updating the VDI Core hosts to avoid communication issues with the VDI Core. Besides updating the VirtualBox server, you'll also need to update the VirtualBox Guest Additions on all the desktops to correspond to the VirtualBox version on the VirtualBox host.

If your VDI 3 installation has a VMware vCenter virtualization platform, you'll need to update the VDA Tools on each of the desktops.

For more details about how to update VirtualBox and VMware vCenter virtualization platforms for VDI 3.1, refer to the [How to](#)


Update to VDI 3.1 (VirtualBox and vCenter Virtualization Platforms) page.

## How to Update to VDI 3.1 (Single VDI Host)



### Outage Implications

Updating the VDI single host will cause a full VDI Core outage.



### Before You Begin



#### Back up!

Use the following checklist to be sure all important data has been backed up properly.



**Database** - It is highly recommended to back up the database before starting the update process if, for some reason, the update process were to fail. For more information about backing up data on a remote database, refer to the [How to Back Up and Restore Data \(Remote MySQL Database\)](#) page.



**Customized `pam.conf` files** - The update process will regenerate the content of the file `/etc/pam.conf` (an SRSS access configuration file). If you have customized the file, you will need to back it up before updating, and re-add the customization to the newly generated file.



#### Making Changes with VDI Manager and CLI

Making changes to the VDI Core through the VDI Manager or CLI is strictly forbidden while updating to VDI 3.1.

### Steps

1. Run the update installation and configuration on the single VDI host.
  - a. As root user, unzip the VDI archive, and change to the corresponding directory.

```
# unzip vda_3.1_amd64.zip
# cd vda_3.1_amd64
```

or

```
# unzip vda_3.1_sparc.zip
# cd vda_3.1_sparc
```

- b. Run the installation.

```
# ./vda-install
```

The `vda-install` script will recognize if VDI 3 is installed and will ask if you want to update. By answering 'y', the installation part of the update process will be started. The old VDI 3 packages will be un-installed and replaced by the new VDI 3.1 packages.

- c. Once the `vda-install` script has finished, reboot the single VDI host, and wait until the host is up again.

```
# reboot
```

- d. Run the configuration.

```
/opt/SUNWvda/sbin/vda-config
```


The `vda-config` script will recognize if the VDI Single Host is in the middle of the update process, and will conclude the update process by running the update configuration. The configuration will turn on all VDI-related services again.

## How to Update to VDI 3.1 (High Availability with Bundled MySQL Database)



### Outage Implications

Updating the VDI Primary host and the first two VDI Secondary hosts will cause a VDI Core outage on these hosts. Additional secondary VDI hosts will stay functional throughout the update process. Once the first phase of the migration has been started you must not restart any of the SQL nodes running on any of the VDI hosts.



### Before You Begin



#### Back up!

Use the following checklist to be sure all important data has been backed up properly.



**Database** - It is highly recommended to back up the database before starting the update process if, for some reason, the update process were to fail. For more information about backing up data on the bundled MySQL Cluster database, refer to the [How to Back Up and Restore Data \(Bundled MySQL Database\)](#) page.



**Customized `my.cnf` files** - The update process for any host within a MySQL (embedded) cluster setup will regenerate the content of the file `/etc/opt/SUNWvda/my.cnf` (a database configuration file). If you have customized the file, you will need to back it up before updating, and re-add the customization to the newly generated file.



**Customized `pam.cnf` files** - The update process will regenerate the content of the file `/etc/pam.cnf` (an SRSS access configuration file). If you have customized the file, you will need to back it up before updating, and re-add the customization to the newly generated file.



#### Making Changes with VDI Manager and CLI

Making changes to the VDI Core through the VDI Manager or CLI is strictly forbidden while updating to VDI 3.1.

### Steps

1. Run the update installation on the Primary VDI host.
  - a. As root user, unzip the VDI archive, and change to the corresponding directory.

```
# unzip vda_3.1_amd64.zip
# cd vda_3.1_amd64
```

or

```
# unzip vda_3.1_sparc.zip
# cd vda_3.1_sparc
```

b. Run the installation.

```
# ./vda-install
```

The `vda-install` script will recognize if VDI 3 is installed and will ask if you want to update. By answering 'y' phase 1 of the update process will be started. The installation part of the update process will back up several settings on your Primary and prepare the VDI database to support new VDI 3.1 features. The first update phase will also shut down the MySQL Cluster management node and, because the Primary has been configured to host VDI sessions, will turn down all VDI related services. Next, the old VDI 3 packages will be un-installed and replaced by the new VDI 3.1 packages.

c. Once the `vda-install` script has finished, reboot your Primary, and wait until the host is up again.

```
# reboot
```

2. Run the update installation on the first VDI Secondary host.

In order to safely update your two Secondary hosts, install the VDI Core on the first Secondary completely, and then install the VDI Core on your second Secondary completely. Installing the VDI Core on both Secondary hosts at the same time is not supported.

a. As root user, unzip the VDI archive, and change to the corresponding directory.

```
# unzip vda_3.1_amd64.zip
# cd vda_3.1_amd64
```

or

```
# unzip vda_3.1_sparc.zip
# cd vda_3.1_sparc
```

b. Run the installation.

```
# ./vda-install
```

The `vda-install` script will recognize if VDI 3 is installed and will ask you whether you want to update or not. By answering 'y' phase 1 of the update process will be started. The installation part of the update process will back up several settings on your Secondary and prepare the VDI database to support new VDI 3.1 features. The first update phase will also turn down all VDI-related services on the host. Next, the old VDI 3 packages will be un-installed and replaced by the new VDI 3.1 packages.

c. Once the `vda-install` script has finished, reboot your first Secondary and wait until the host is up again.

```
# reboot
```

- d. Check that the MySQL database has been fully started again by running the following command.

```
/opt/SUNWvda/sbin/vda-db-status
```

All nodes must be in the 'up' state.

3. Run the update installation on the second VDI Secondary host by following Step 2 above.
4. Run the update configuration on the VDI Primary host.  
Once the installation part of the update process is complete on the VDI Primary and first two Secondaries, you are ready to start the configuration part of the update process.
  - As root user, run the following command.

```
/opt/SUNWvda/sbin/vda-config
```

The `vda-config` script will recognize if the VDI Primary is in the middle of the update process, and will conclude the update process by running the update configuration. If the VDI Primary host was configured to act as a full functional VDI host, the configuration will turn on all VDI-related services again.

5. Run the update configuration on the first VDI Secondary host.  
After the update configuration has finished on the VDI Primary, you can start the update configuration on the first two VDI Secondaries. Like the update installation, you must completely configure the first VDI Secondary, then completely configure the second VDI Secondary. Configuring the VDI 3.1 Core on both Secondary hosts at the same time is not supported.
  - As root user, run the following command.

```
/opt/SUNWvda/sbin/vda-config
```

The `vda-config` script will recognize if the VDI Secondary is in the middle of the update process, and will conclude the update process by running the update configuration. The configuration will turn on all VDI-related services again.

6. Run the update configuration on the second VDI Secondary host by following Step 5 above.
7. Run the update installation and configuration on additional (optional) VDI Secondary hosts.  
After you have completely updated the VDI Primary host and first two VDI Secondary hosts, you can update the additional VDI Secondaries in any sequence. To start the update process, run the following steps.
  - a. As root user, unzip the VDI archive, and change to the corresponding directory.

```
# unzip vda_3.1_amd64.zip  
# cd vda_3.1_amd64
```

or

```
# unzip vda_3.1_sparc.zip  
# cd vda_3.1_sparc
```

- b. Run the installation.

```
# ./vda-install
```

The `vda-install` script will recognize if VDI 3 is installed and will ask you whether you want to update or not. By answering 'y' the migration process will be started. It will un-install the old VDI 3 packages, and replace them with the new VDI 3.1 packages.

- c. Once `vda-install` script has finished, reboot your VDI host, and wait until the host is up again.

- d. Run the configuration.

```
/opt/SUNWvda/sbin/vda-config
```


The `vda-config` script will recognize if the VDI Secondary is in the middle of the update process, and will conclude the update process by executing the update configuration. The update configuration will turn on all VDI related services again.

## How to Update to VDI 3.1 (High Availability with Remote Database)



### Outage Implications

Updating the VDI Primary host and the first two VDI Secondary hosts will cause a VDI Core outage on these hosts. Additional secondary VDI hosts will stay functional throughout the update process. Once the first phase of the migration has been started you must not restart any of the SQL nodes running on any of the VDI hosts.



Before You Begin

**Back up!**

Use the following checklist to be sure all important data has been backed up properly.



**Database** - It is highly recommended to back up the database before starting the update process if, for some reason, the update process were to fail. For detailed information about backing up data on a remote database, refer to the [How to Back Up and Restore Data \(Remote MySQL Database\)](#) page.



**Customized `pam.conf` files** - The update process will regenerate the content of the file `/etc/pam.conf` (an SRSS access configuration file). If you have customized the file, you will need to back it up before updating, and re-add the customization to the newly generated file.

**Making Changes with VDI Manager and CLI**

Making changes to the VDI Core through the VDI Manager or CLI is strictly forbidden while updating to VDI 3.1.

**Steps**

1. Run the update installation and configuration on the VDI Primary host.

a. As root user, unzip the VDI archive, and change to the corresponding directory.

```
# unzip vda_3.1_amd64.zip
# cd vda_3.1_amd64
```

or

```
# unzip vda_3.1_sparc.zip
# cd vda_3.1_sparc
```

b. Run the installation.

```
# ./vda-install
```

The `vda-install` script will recognize if VDI 3 is installed and will ask if you want to update. By answering 'y' phase 1 of the update process will be started. The installation part of the update process will back up several settings on your Primary and prepare the VDI database to support new VDI 3.1 features. The first update phase will also shut down the MySQL Cluster management node and, because the Primary has been configured to host VDI sessions, will turn down all VDI related services. Next, the old VDI 3 packages will be un-installed and replaced by the new VDI 3.1 packages.

c. Once the `vda-install` script has finished, reboot your Primary, and wait until the host is up again.

```
# reboot
```

d. Run the configuration.

```
/opt/SUNWvda/sbin/vda-config
```

The `vda-config` script will recognize if the VDI Primary is in the middle of the update process, and will

conclude the update process by running the update configuration. If the VDI Primary host was configured to act as a full functional VDI host, the configuration will turn on all VDI-related services again.

2. Run the update installation and configuration on the VDI Secondary host.

In order to safely update your two Secondary hosts, install the VDI Core on the first Secondary completely, and then install the VDI Core on your second Secondary completely. Installing the VDI Core on both Secondary hosts at the same time is not supported.

a. As root user, unzip the VDI archive, and change to the corresponding directory.

```
# unzip vda_3.1_amd64.zip
# cd vda_3.1_amd64
```

or

```
# unzip vda_3.1_sparc.zip
# cd vda_3.1_sparc
```

b. Run the installation.

```
# ./vda-install
```

The `vda-install` script will recognize if VDI 3 is installed and will ask you whether you want to update or not. By answering 'y' the migration process will be started. It will un-install the old VDI 3 packages, and replace them with the new VDI 3.1 packages.

c. Once `vda-install` script has finished, reboot your VDI host, and wait until the host is up again.

d. Run the configuration.

```
/opt/SUNWvda/sbin/vda-config
```

The `vda-config` script will recognize if the VDI Secondary is in the middle of the update process, and will conclude the update process by executing the update configuration. The update configuration will turn on all VDI related services again.

## How to Update to VDI 3.1 (VirtualBox and vCenter Virtualization Platforms)

When updating from VDI 3 to VDI 3.1, it will necessary to perform some tasks on the virtualization platform. VDI installations with a VirtualBox virtualization platform will require a newer version of VirtualBox to be to use the new features in VDI 3.1, and the corresponding Guest Additions will need to be installed on the VirtualBox virtual machines. VMware vCenter virtualization platforms will not require updating since the VDI 3.1 supports all the versions of vCenter and ESX Server as in VDI 3.

### Before You Begin

The VDI Core hosts should be updated before the virtualization platform. If you have not already updated the VDI Core hosts, refer to the [About Updating to VDI 3.1](#) page for more details.

### Steps for Sun VirtualBox Virtualization Platforms

1. Update the VirtualBox version on the VirtualBox host.

- a. Un-install the previous version of VirtualBox by changing to the VirtualBox installation directory, and running the following command as root user.

```
# ./vb-install -u
```

- b. When VirtualBox has been successfully removed, install the [currently supported](#) version of VirtualBox by running the following command.

```
# ./vb-install
```

2. Update the Guest Additions on VirtualBox virtual machines.

## Steps for VMware vCenter Virtualization Platforms

The only requirement for updating the vCenter virtualization platform to work with VDI 3.1 is to update the VDA tools on each of the vCenter desktops.

- Update the VDA Tools on vCenter desktops.
  1. Remove the existing VDA Tools file from the virtual machine. The default location for the VDA Tools on Windows is `C:\Program Files\Sun\Virtual Desktop Access\Tools`.
  2. Copy the `vda-tools.msi` installer file from the `/var/tmp/vda_3.1_amd64/vda_3.1/Windows/Packages` directory to the virtual machine.
  3. Within the virtual machine's console, double-click the installer and follow the prompts to complete installation. The default target location for the VDA Tools on Windows is `C:\Program Files\Sun\Virtual Desktop Access\Tools`.
  4. The VM Services list should now contain a new service named Sun VDI Tools, running and set to start automatically.

## How to Back Up and Restore Data (Bundled MySQL Database)

In a typical VDI instance, using the bundled MySQL database, a back up is only necessary when updating to a new release of VDI. The integration of the bundled MySQL database already provides an assurance of fail-safety, that reduces the need for backups as a means for disaster recovery. Find further details about this topic in the official [MySQL documentation](#).



Please keep in mind that flexible desktop assignments existing at the time when the backup will be created might not be valid anymore when the VDI configuration has to be restored from this backup. This may lead to some unexpected side effects. For this reason you should consider replication as an alternative to regularly taken backups. Master-Slave replication is supported with the MySQL Cluster version coming along with VDI. Find details on the topic here: [MySQL Cluster Replication](#)

### Steps

The following procedure assumes that you have a functioning (installed and configured) VDI instance, using the bundled MySQL database.

1. Make a backup of the VDI database.
  - a. Open the `ndb_mgm` console by running the following command on the VDI Primary host.

```
# /opt/SUNWvda/mysql/bin/ndb_mgm
```

- b. Start the back up by running the following command at the `ndb_mgm` prompt.

```
ndb_mgm> START BACKUP
```

- c. Verify that backups have been created by checking the following directory on the two VDI Secondary hosts:  
/var/opt/SUNWvda/mysql-cluster/BACKUP.
2. (Optional) Perform a VDI update.  
For more information about updating VDI, refer to the [About Updating to VDI 3.1](#) page.
3. Restore the backed up VDI database on the new VDI installation.

- a. On the first VDI Secondary host, run the following command.

```
/opt/SUNWvda/mysql/bin/ndb_restore -b <backup #> -n <nodeid #> -r
--backup_path=<path>
```

- b. On the second VDI Secondary host, run the following command.

```
/opt/SUNWvda/mysql/bin/ndb_restore -b <backup #> -n <nodeid #> -r
--backup_path=<path>
```

- c. Log into the VDI Manager, and check that all the data is restored.  
Go to <http://<server name>:1800> (or <http://localhost:1800> if remote administration has been disabled), and use root user credentials to log in.

## How to Back Up and Restore Data (Remote MySQL Database)

The following information should be used when backing up data on a remote database in either a Single Host or High Availability (Remote MySQL Database) configuration.

### Steps

1. Make a backup of the VDI database.
  - a. Log into the remote database.

```
# zlogin <MySQL server>
```

- b. Change to the `usr/local/mysql/bin/` directory and run `mysqldump`.

```
# cd usr/local/mysql/bin/
# ./mysqldump --user=root -u root --opt checkdb | gzip > /dumptest1.sql.gz
```

2. (Optional) Perform a VDI update.



During the un-configuration, answer 'yes' to deleting the remote database. Use the same values for "privileged administrator", "VDA database", "user name for the VDA database" used while executing `vda-config` for the re-configuration.

For more information about updating VDI, refer to the [About Updating to VDI 3.1](#) page.

3. Restore the backed up VDI database on the new VDI installation.
  - a. Log into the remote database.

```
# zlogin <MySQL server>
```

- b. Change to the `usr/local/mysql/bin/` directory and run the following command.

```
# cd usr/local/mysql/bin/  
# ./mysql --user=root checkdb < /primary-dump/dumptest1.sql
```