

Oracle® Insurance Policy Administration

WebLogic Deployment

Installation Instructions – Step 2

Version 9.4.1.0

Documentation Part Number: E23637_01

October 2011

Copyright © 2009, 2011 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are “commercial computer software” or “commercial technical data” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Where an Oracle offering includes third party content or software, we may be required to include related notices. For information on third party notices and the software and related documentation in connection with which they need to be included, please contact the attorney from the Development and Strategic Initiatives Legal Group that supports the development team for the Oracle offering. Contact information can be found on the Attorney Contact Chart.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your beta trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Software License and Service Agreement, which has been executed and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Table of Contents

INTRODUCTION	4
<i>Prerequisites</i>	<i>4</i>
INITIAL SYSTEM CONFIGURATION	5
Database Driver Setup	5
OIPA Setup	5
Web Application Utility Setup	6
CONFIGURING WEBLOGIC	7
Create a Machine	7
Create and Configure OIPA Server	7
Create and Configure Web Application Utility Server	8
Creating Data Sources	9
Deploy OIPA Application	12
Deploy the Web Application Utility	12
Start the Servers	12
TESTING THE DEPLOYMENTS	13
OIPA Deployment	13
Web Application Utility Deployment	13

INTRODUCTION

The Oracle Insurance Policy Administration (OIPA) application and the Oracle Insurance Rules Palette form a solution for configuring, managing and processing policy data. Both applications, along with the Web Application Utility, must be installed and then configured to work together.

This install guide will cover step two of the installation process, where the OIPA application and the Web Application Utility are configured using Web Logic. Please refer to the OIPA database installation instructions in the documentation library provided with the release to ensure the database is set up correctly.

Prerequisites

Before beginning the installation steps, you must have the following components:

- A server with a Windows or Linux operating system.
- WebLogic 11g (Version 10.3.3). It is recommended that the Sun JDK is used. This can be downloaded from the Oracle Technology Network at http://www.oracle.com/technology/software/products/middleware/htdocs/fmw_11_download.html.
- Administrative rights to the server.
- Oracle Insurance Policy Administration v9.4.1 Media Pack from E-Delivery.
- Oracle Insurance Rules Palette V9.4.1 Media Pack from E-Delivery.

INITIAL SYSTEM CONFIGURATION

Database Driver Setup

1. Create a directory on the WebLogic installation machine to store database driver jar files for OIPA (i.e., /opt/oracle/db_drivers/ or C:\oracle\db_drivers\).
2. Copy the database drivers for your database into this directory.
 - **Oracle 11.2** – The necessary driver, **ojdbc-11.2.0.2.jar**, is included in the **libs** directory of the OIPA Media Pack.
 - **Microsoft SQL Server 2005** – download the latest **jtids.jar** file.
 - a. Download **jtids** from the following site: <http://sourceforge.net/projects/jtids/>.
 - b. Click the green **Download** box on the right side of the screen. A pop-up window will open.
 - c. Save the download .zip file to the lib directory you created (i.e., /opt/oracle/lib).
 - d. Open the downloaded .zip file and extract the file **jtids-1.2.5** from the root of the .zip file.
 - e. Rename the file **jtids.jar**.
 - **IBM DB2** – The two necessary .jar files (**db2jcc** and **db2jcc_license_cu**) are included with the purchase of the DB2 software. These files are not available for download. Contact your IT department if you need assistance locating these files.

Note: Each version of DB2 requires specific drivers. The files above correspond with DB2 9.7.

OIPA Setup

1. Create a directory on the WebLogic server to store various configuration files for OIPA (i.e., /opt/oracle/oipa/ or C:\oracle\oipa\).
2. Create subdirectories inside the directory from Step 1 called **conf**, **libs** and **war**.
3. Copy the **PASJava-weblogic.war** file from the root directory extracted from the OIPA distribution zip file into the **war** subdirectory.
4. Copy the following files from the **properties files** directory into the **conf** directory:
 - AdminServerMessages.properties
 - APESMessages.properties
 - coherence-cache-config.xml
 - coherence-config.xml
 - DocumentGeneratorMessages.properties
 - [ESAPI.properties](#)
 - ExtensibilityMessages.properties
 - EXTMessages.properties
 - MathMessages.properties
 - PAS.properties
 - PASMessages.properties
 - ResourceBundleMessages.properties
 - SREMessages.properties
 - UtilMessages.properties
5. Copy the following files from the **ext jars** directory into the **libs** directory:
 - antlr-2.7.7.jar
 - commons-collections-3.2.1.jar
 - commons-logging-1.1.1.jar
 - el-api-1.0.jar
 - log4j-1.2.16.jar
 - spring-agent-2.5.6.SEC02.jar

6. Identify the database type and platform in the **PAS.properties** file. The property setting must match the type of database being used. The two properties that are used to do this are:
 - application.databaseType
 - jpa.databasePlatform

Note: Refer to the System Properties document in the Oracle Insurance Policy Administration E23637_01 Documentation Library on the OTN for a complete list of all properties and allowed values.

7. Identify the default locale in the PAS.properties file. The locale selected will determine the translation that is loaded in the database for OIPA when it launches.
 - application.defaultLocale
8. If using a DB2 database, you will need to modify the PAS.properties file to include configuration for case-insensitive searching. If using an Oracle or Microsoft SQL Server database, please skip this step and proceed to step 6.
 - a. Modify the PAS.properties file to include the following line:

```
search.field.text.caseInsensitive=true
```

Web Application Utility Setup

1. Create a directory on the WebLogic server to store various configuration files for the Web Application Utility (i.e., /opt/oracle/paletteconfig/ or C:\oracle\paletteconfig\).
2. Create subdirectories inside the directory from Step 1 called **conf**, **libs**, **uploads** and **war**.
3. Copy the **PaletteConfig.war** file into the **war** subdirectory.
4. Copy the **PaletteWebApplication.properties** file into the **conf** subdirectory.
5. Open the PaletteWebApplication.properties file and edit the **download.dir** property to point to the **uploads** subdirectory created in Step 2.
6. Copy the following file into the **libs** subdirectory:
 - el-api-1.0.jar

CONFIGURING WEBLOGIC

To configure WebLogic use the WebLogic Administration Console. By default the port number is 7001 and `/console` is the context root. Example: <http://hostname:7001/console>

Note: When selecting a menu option in the WebLogic Administrative Console, the names may differ depending on whether WebLogic is used in development mode or production mode.

Create a Machine

1. Select **Environment>Machines>New**.
2. Enter the name for the machine.
3. If the OS is not UNIX, select Other from the Machine OS drop-down list.
4. Click **Finish**.

Create and Configure OIPA Server

IMPORTANT: OIPA and the Web Application Utility can exist on the same WebLogic server if necessary.

Create the OIPA Server

1. Select **Environment>Servers**.
2. Click **New**.
3. Enter OIPA for the name of the server.
4. Set the listener port to a port that is not used by any other application.
5. Click **Next**.
6. Select **Finish**.

Add the OIPA Server to the Machine

1. Select **Environment>Machines**.
2. Select the machine that was created.
3. Select the **Servers** tab.
4. Select **Add**.
5. Select the name of the OIPA server created from the **Select a Server** drop-down box.
6. Click **Finish**.

Configure the OIPA Server

1. Select **Environment>Servers**.
2. Select the OIPA server that was created.
3. Select the **Server Start** tab.
4. Specify the class path. The path names will vary depending on the configuration.

```
/opt/oracle/Middleware/wlserver_10.3/server/lib/weblogic.jar:/opt/oracle/oipa/conf:/opt/oracle/oipa/libs/antlr-2.7.7.jar:/opt/oracle/oipa/libs/commons-collections-3.2.1.jar:/opt/oracle/oipa/libs/commons-logging-1.1.1.jar:/opt/oracle/oipa/libs/el-api-1.0.jar:/opt/oracle/oipa/libs/log4j-1.2.16.jar
```

Note: If using WebLogic on Windows, the separator for files/directories in the classpath is a semicolon.

5. Enter the following arguments. This will vary depending on the configuration.

```
-server -Xms512M -Xmx1024M -XX:PermSize=128M -XX:MaxPermSize=256M -
javaagent:/opt/oracle/oipa/libs/spring-agent-2.5.6.SEC02.jar -
Dtangosol.coherence.cacheconfig=/opt/oracle/oipa/conf/coherence-cache-
config.xml -Dtangosol.pof.config=com-adminserver-pas-web-pof-config.xml -
Dtangosol.coherence.override=/opt/oracle/oipa/conf/coherence-config.xml -
Dweblogic.wsee.skip.async.response=true
```

6. Select **Save**.

Create and Configure Web Application Utility Server

Create the Web Application Utility Server

1. Select **Environment>Servers**.
2. Click **New**.
3. Enter PaletteConfig for the name of the server.
4. Set the listener port to a port that is not used by any other application.
5. Click **Next**.
6. Select **Finish**.

Add the Web Application Utility Server to the Machine

1. Select **Environment>Machines**.
2. Select the machine that was created.
3. Select the **Servers** tab.
4. Select **Add**.
5. Select the name of the Web Application Utility server created from the **Select a Server** drop-down box.
6. Click **Finish**.

Configure the Web Application Utility Server

1. Select **Environment>Servers**.
2. Select the PaletteConfig server that was created.
3. Select the **Server Start** tab.
4. Specify the class path. The path names will vary depending on the configuration.

```
/opt/Oracle/Middleware/wlserver_10.3/server/lib/weblogic.jar:/opt/oracle/pal
etteconfig/conf:/opt/oracle/db_drivers/ojdbc11.2.0.2.jar:/opt/oracle/palett
econfig/libs/el-api-1.0.jar
```

Note: Make sure you are pointing to the correct directory for the Web Application Utility.

5. Enter the following arguments. This will vary depending on the configuration.

```
-server -Xms64M -Xmx128M
```

6. Select **Save**.

Creating Data Sources

Create the Data Source for ADMINSERVERDS

1. Select **Services>JDBC>Data Sources for WebLogic 11g (10.3)**.
2. In the configuration section on the right, select **New**.
3. In the JDBC Data Source Properties pane that appears:
 - a. Change the Name. This name can be anything, but has to be unique for the entire WebLogic server. If you have more than one OIPA instance on the server, each instance should have a unique name.
 - b. Change the JDNI Name to ADMINSERVERDS. This name cannot be anything other than ADMINSERVERDS.
 - c. Select the Oracle database type.
 - d. Click **Next**.
 - e. Keep the default driver.
4. Select **Next**.
5. Select **Next** again when Transaction options are displayed.
6. In the Connection Properties pane:
 - a. Enter the Database Name.
 - b. Enter the Host Name of the database server.
 - c. Enter the Port number of the database server.
 - d. Enter the Database User Name. This can be obtained from the database administration who installed the databases.
 - e. Enter both Password entries. This can be obtained from the database administration who installed the databases.
 - f. Select Next.

Figure 1-1: Connection Properties Pane

What is the name of the database you would like to connect to?

Database Name:

What is the name or IP address of the database server?

Host Name:

What is the port on the database server used to connect to the database?

Port:

What database account user name do you want to use to create database connections?

Database User Name:

What is the database account password to use to create database connections?

Password:

Confirm Password:

- g. Test the database connection.
- h. Select **Next**.
- i. In the **Select Targets** pane that appears, check the box for the OIPA application server. This links the data source to the servers that were created.
- j. Select **Finish**.

Create the Data Source for ADMINERVERRESOURCEDS

1. Select **Services>JDBC>Data Sources**.
2. In the configuration section on the right, select **New**.
3. In the JDBC Data Source Properties pane that appears:
 - a. Change the Name. This name can be anything, but has to be unique for the entire WebLogic server. If you have more than one OIPA instance on the server, each instance should have a unique name.
 - b. Change the JDNI Name to ADMINERVERRESOURCEDS.
 - c. Select the database type.
 - d. Select the driver type.
4. Select **Next**.
5. Select **Next** again when Transaction options are displayed.
6. In the Connection Properties pane:
 - a. Enter the Database Name.
 - b. Enter the Host Name of the database server.
 - c. Enter the Port number of the database server.
 - d. Enter the Database User Name. This can be obtained from the database administrator who installed the databases.
 - e. Enter both Password entries. This can be obtained from the database administrator who installed the databases.
 - f. Select Next.
 - g. Test the database connection.
 - h. Select Next.
 - i. In the Select Targets pane that appears, check the box for both servers created. This links the data source to the servers that were created.
 - j. Select Finish.

Create the Data Source for ADMINERVERSEARCHDS

1. Select **Services>JDBC>Data Sources**.
2. In the configuration section on the right, select **New**.
3. In the JDBC Data Source Properties pane that appears:
 - a. Change the Name. This name can be anything, but has to be unique for the entire WebLogic server. If you have more than one OIPA instance on the server, each instance should have a unique name.
 - b. Change the JDNI Name to ADMINERVERSEARCHDS.
 - c. Select the database type.
 - d. Select the driver type.
4. Select **Next**.
5. Select **Next** again when Transaction options are displayed.
6. In the Connection Properties pane:
 - a. Enter the Database Name.
 - b. Enter the Host Name of the database server.
 - c. Enter the Port number of the database server.
 - d. Enter the Database User Name. This can be obtained from the database administrator who installed the databases.
 - e. Enter both Password entries. This can be obtained from the database administrator who installed the databases.
 - f. Select Next.
 - g. Test the database connection.
 - h. Select Next.
 - i. In the Select Targets pane that appears, check the box for both servers created. This links the data source to the servers that were created.
 - j. Select Finish.

Create Data Source for ADMINSERVERREADONLYDS

1. Select **Services>JDBC>Data Sources**.
2. In the configuration section on the right, select **New**.
3. In the JDBC Data Source Properties pane that appears:
 - a. Change the Name to ADMINSERVERREADONLYDS.
 - b. Change the JDNI Name to ADMINSERVERREADONLYDS.
 - c. Select the database type.
 - d. Select the driver type.
4. Select **Next**.
5. Select **Next** again when Transaction options are displayed.
6. In the Connection Properties pane:
 - a. Enter the Database Name.
 - b. Enter the Host Name of the database server.
 - c. Enter the Port number of the database server.
 - d. Enter the Database User Name for the readonly user. This can be obtained from the database administrator who installed the databases.
 - e. Enter both Password entries. This can be obtained from the database administrator who installed the databases.
 - f. Select Next.
 - g. Test the database connection.
 - h. Select Next.
 - i. In the Select Targets pane that appears, check the box for both servers created. This links the data source to the servers that were created.
 - j. Select Finish.

Deploy OIPA Application

1. Using the navigation tree on the left, select **Deployments**.
2. In the configuration section on the right, select **Install**.
3. In the **Install Application Assistant**:
 - a. Locate PASJava-weblogic.war file.
 - b. Click **Next**.
 - c. For the **Targeting Style** keep the default of **Install this deployment as an application**.
 - d. Click **Next**.
 - e. For the **Deployment Target** select the checkbox for the server that will host the OIPA application.
 - f. Click **Next**.
 - g. Change the application name if needed.
 - h. Click **Next**.
 - i. Select **Finish**.

Deploy the Web Application Utility

1. Using the navigation tree on the left, select **Deployments**.
2. In the configuration section on the right, select **Install**.
3. In the **Install Application Assistant**:
 - a. Locate the **PaletteConfig.war** file. This file is in the Oracle Insurance Rules Palette V9.4.1 Media Pack in the PaletteConfig directory.
 - b. Click **Next**.
 - c. For the **Targeting Style** keep the default of **Install this deployment as an application**.
 - d. Click **Next**.
 - e. For the **Deployment Target** select the checkbox for the server that will host the Web Application Utility.
 - f. Click **Next**.
 - g. Change the application name if needed.
 - h. Click **Next**.
 - i. Select **Finish**.

Start the Servers

1. Select **Environment>Servers**.
2. In the configuration section on the right, select **Control** tab.
3. Select the checkbox next to the OIPA and PaletteConfig servers.
4. Select the **Start** option.

IMPORTANT: When configuring the rules palette environment use the host name and port number of the PaletteConfig server. The Web Application Utility must always be running in order for users to access the Rules Palette.

TESTING THE DEPLOYMENTS

OIPA Deployment

1. Open a new Internet Explorer window.
2. Navigate to <http://hostname:port/PASJava/>. If you change the context name, make sure that name is reflected in the URL.
3. Using the login screen that appears:
 - a. Type install for the Client ID.
 - b. Type install for the Password.
 - c. Select Login.

Web Application Utility Deployment

1. Open a new Internet Explorer window.
2. Navigate to <http://hostname:port/PaletteConfig/>. The only context name supported is PaletteConfig.
3. Using the login screen that appears:
 - a. Type **admin** for the **Client ID**.
 - b. Type **admin** for the **Password**.
 - c. Select **Login**.