

**Oracle® StorageTek Automated Cartridge System
Library Software**

Product Information

Release 8.1

E25010_03

January 2013

Oracle® StorageTek Product Book Type, Release 8.1

E25010_03

Copyright © 1989, 2013, Oracle and/or its affiliates. All rights reserved.

Primary Author:

Contributing Author:

Contributor:

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Revision

Date	Revision	Description
December 2011	E25010-01	This release supports ACSLS 8.1.
April 2012	E25010-02	Updated Co-Hosting.
January 2013	E25010-03	Added HP and IBM LTO-6 support.

Table of Contents

Revision	iii
List of Tables	vii
Preface	ix
Access to Oracle Support	ix
1 Overview	1
Requirements	1
Software Requirements	1
System Requirements	2
Browser Requirements	2
Co-Hosting	2
What's New	3
Overview of ACSLS	5
Library Management	5
Graphical User Interface	6
Logical Libraries	6
Open Format (Volser)	7
SCSI Media Changer over Fibre Client Interface	7
ACSAPI Client Interface	7
Command Line Interface	8
Utilities	8
No Longer Requires Software Licenses	8
testports Utility	9
2 Library, Tape Drive and Media Support	11
Current Libraries Supported	12
Legacy Libraries Supported	13
Tape Drives Supported	13
Tape Drive and Media Compatibility Supported	20
Index	1

List of Tables

TABLE 2-1	Current Libraries Supported	12
TABLE 2-2	Legacy Libraries Supported.....	13
TABLE 2-3	Tape Drives Supported	14
TABLE 2-4	Tape Media Supported.....	18
TABLE 2-5	Drive and Media Compatibility	20

Preface

StorageTek Automated Cartridge System Library Software (ACSL) is Oracle's StorageTek UNIX server software that controls a StorageTek Automated Cartridge System (ACS). The StorageTek ACS family of products consists of fully automated, tape cartridge-based data storage and retrieval systems. StorageTek ACSL supports network access to different client systems that can range from workstations to mainframes to supercomputers running on a variety of operating systems.

This guide is for the individual responsible for administering StorageTek ACSL. It is expected that you already have a working knowledge of the following:

- UNIX file and directory structure
- How to use UNIX commands and utilities for your platform
- UNIX system files
- How to do typical UNIX system administrator tasks, such as logging on as root and setting up user accesses to a UNIX application

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/support/contact.html> or visit <http://www.oracle.com/accessibility/support.html> if you are hearing impaired.

Overview

ACSL 8.1 includes several product enhancements and multiple fixes to bugs reported in Release 8.0.2.

Download ACSL from the Oracle Software Delivery Cloud website. Typical installations download the package to the `/opt` directory and extracts it from there. A separate zip file is created for Solaris SPARC and Solaris x86. If you need both platforms, you must download both zip files.

Requirements

Software Requirements

- ACSL 8.1 has been fully tested and verified on Oracle's Sun SPARC and X86 platforms running Solaris-10 Updates 7, 8, and 9. Other operating systems, including AIX and virtual environments, are not tested or supported.
- Because of special device driver requirements to enable virtual libraries, ACSL 8.1 cannot run in a Solaris Zoned environment. However, ACSL 8.1 can run in a logical domain on a SPARC system with Chip Multithreading (CMT) technology. ACSL 8.1 HA systems must be installed on their own dedicated platform pair.
- The graphical user interface and SMCE service in ACSL 8.1 requires Java 1.6 U14 or later. You cannot install ACSL unless this requirement is met.

The latest update for JDK 6 is available from the Oracle technetwork download site.

<http://www.oracle.com/technetwork/java/javase/downloads/index.html>

Please note that:

- Should you choose to install Java in a different directory, a soft link must be provided that points to the java binaries located in: `/usr/java/bin/java`
- To verify the version, enter the command: `java -version`.
- If you have an IPv4-based edge firewall, it should be configured to drop all outbound IPv4 protocol 41 packets and UDP port 3544 packets to prevent Internet hosts from using any IPv6-over-IPv4 tunnelled traffic to reach internal hosts.

Please check the website for any maintenance releases.

System Requirements

- Memory: 2GB minimum
- Swap: A minimum of 2GB swap is required. For systems configured with more than 6GB of memory, the rule of thumb for swap is approximately 30% of physical memory.
- File systems:
Installation fails if the following filesystems do not exist as separate filesystems.
 - /export/home - 5GB or greater
 - /export/backup - 5GB or greater
- Optional Fibre card
A fibre HBA is required if you intend to make use of the 'Logical Library' target feature in ACSLS 8.x.
 - To operate in target-mode, this HBA must be a contemporary QLogic fibre card (4GB or higher).
 - If you intend to operate a fibre-connected library such as the SL500, you can use any standard 2GB or higher fibre HBA.

Browser Requirements

ACSL 8.1 has been tested and fully verified on the following browsers:

- Internet Explorer 8 and 9
- FireFox 7 and 8
- Chrome 15

Co-Hosting

To ensure uninterrupted library service and to avoid unanticipated problems due to resource contention, it is generally recommended that ACSLS run in a stand-alone environment on a dedicated server. However, some systems are specifically designed to allow multiple applications to run in co-hosted fashion as though they are completely isolated from one another. Specifically, Solaris Containers and Oracle Solaris VM Server for SPARC enable conditional co-hosting possibilities for use with ACSLS.

The following details the conditions and limitations associated with the various co-hosting options for an ACSLS application.

- Solaris Containers (zones)

Solaris Containers (or zones) enable a system administrator to partition a standard, low cost server into four independent Solaris systems, each with its own isolated file system, and its own instance of Solaris. You can assign network resources to each container and you can reboot any local (non-global) zone without affecting applications in other zones on the same platform.

However, the ability to share kernel resources (such as device drivers) across multiple zones is tenuous at best. Ideally, an application that requires kernel drivers would reside in the global zone. However, it is generally not good practice to install an application in the global zone since any fatal condition with the application could impact all other applications running in the other zones.

ACSL 8.x can reside in a Solaris container only if it does not require drivers beyond the network interface. If you intend to use the target-mode fibre-channel driver (*qlt*) which is required for logical libraries, then your application should not be installed in a Solaris container. Or, if you intend to make use of a fibre-attached library which requires the *mchanger* driver, the application should not be installed in a Solaris container.

Note – There are no versions of ACSL-HA that are supported for use in Solaris Containers.

- Oracle VM Server for SPARC

Oracle VM Server for SPARC (formerly Logical Domains or LDOMs) is technology available on SPARC T-series servers with Chip Multithreading (CMT) technology. This technology offers significant advantages over Solaris Containers to the extent that each domain is in control of its own Solaris kernel.

A Solaris administrator can partition hardware resources across the system, assigning a specific resource to a specific domain. Network resources on this virtual machine can easily be shared across any of up to 128 'guest domains' on the server. But applications that require access to I/O devices through the PCIe bus must be installed in special 'I/O domains'. The number of I/O domains that you can create on the VM Server depends on the number of discrete PCIe busses on the SPARC platform. On a system with a single PCIe bus, you can have two I/O domains, and one of these must be the control domain.

Any ACSL application that relies solely on network connectivity to the library and for client applications can be installed in a guest domain on this server. The virtual network set-up procedure is described in the document, *Oracle VM Server for SPARC 2.1 Administration Guide* in the section, entitled "Using Virtual Networks".

If your ACSL 8.x application is intended for use with logical libraries, or if you intend to connect to a fibre-channel library such as the SL500 or L700, then ACSL must be installed in an I/O domain. Refer to the section "Setting up I/O Domains" in the *Oracle VM Server for SPARC 2.1 Administration Guide*.

Solaris Cluster Software is supported on the Oracle VM Server for SPARC and this platform can be employed in an ACSL-HA application. Refer to the *Oracle Solaris Cluster Data Service for Oracle VM Server for SPARC Guide*.

What's New

- Fast Load support for SCSI clients

ACSL provides Fast Load support for Fibre Channel (FC) SCSI clients. With Fast Load, an FC initiator that issues a mount operation receives a successful response once the operation has been validated and accepted by ACSL, but before cartridge movement begins. Confirming that the cartridge is loaded and available for use (for example, by issuing Test Unit Ready or Read Element Status requests) is the responsibility of the client.

To set Fast Load reporting, click the Preferences button on the masthead from any screen. Once the Preference screen displays, you can enable Fast Load reporting by selecting "Yes" from the pull down menu. The default value is "No".

Changes to this setting are effective for new mount operations that are received from FC clients, and any mount operations that were already in progress are unaffected by the change.

- Oracle's WebLogic replaces the Sun Java Web Console as the application server for the ACSLS GUI. The change assures on-going support for the GUI infrastructure.
- New `userAdmin.sh` utility

This utility allows the `acsls_admin` user to manage user accounts for the ACSLS GUI. With this utility, the `acsls_admin` user can create user accounts, delete user accounts, change passwords for any user account, and list all user accounts.

- New `fixVols.sh` utility

This utility lets you manually correct the status of a logical volume that is stuck with an 'in-transit' status when the physical volume is actually home or in the drive.

- Send Requests to SL8500 that processes the request

To optimize performance of a string of SL8500s connected by pass-thru-ports, send requests to a library that is the source or destination of a movement operation or will be responding to a status. For requests that are for any library and for requests whose library(s) are not connected, spread out these requests over all connected libraries. Make other changes to improve library performance.

- You can now change environment variables without having to logout/login before these variables are used the next time that ACSLS is enabled. The ACSLS start-up script was updated to source the static variables.
- The `LM_RP_TRAIL` dynamic variable provides a audit trail (in `$ACS_HOME/log/rpTrail.log`) of all ACSLS requests. The associated `RP_TRAIL_LOG_SIZE`, `RP_TRAIL_FILE_NUM`, and `RP_TRAIL_DIAG` variables let you configure this audit trail. Access the `RP_TRAIL` variables via `acsss_config` (Option 2: Set event logging variables), and see the help for more details.
- Set the `CSI_MULTI_HOMED_CL` (client) dynamic variable to `TRUE` when an ACSAPI client server has multiple host addresses, is behind NAT with a private IP address that is not accessible externally, or the client's server is connected to ACSLS via a VPN. Access `CSI_MULTI_HOMED_CL` via `acsss_config` (Option 1: Set CSI tuning variables), and see the help for more details.
- The STMF service is now under `acsss enable` and `acsss disable` control. This service is a prerequisite for the SMCE service and it is enabled whenever SMCE is enabled and it is disabled whenever SMCE is disabled.
- `psacs` now reports all ACSLS transient processes, including recovery, vary, audit, enter, eject, and config.
- ACSLS CAP enhancements include:
 - Improvements to automatic recovery:
 - During startup - detection of cartridges left in a CAP as it comes online.

- During runtime - recovery from unusual situations, such as an inoperative CAP.
- ACSLS no longer reports CAP as "in use" (although it appeared available and idle).

Now when ACSLS detects that the CAP is reserved, but that the reservation could be overridden (meaning it appears to be reserved by ACSLS, and no conflicting ACSLS operation is underway), the operation is now allowed to proceed instead of being rejected with "in use" as before.

- Improvements to SL3000 AEM eject:
 - When ejecting cartridges to an SL3000 AEM, skips over missing CAP magazines.
 - Directs ejected cartridges so they are easy to remove from the AEM by:
 - Filling up magazines in the front door first, because the front door is easier to access.
 - Filling up one magazine at a time, instead of striping cartridges across all columns.
- ACSLS GUI enhancements include:
 - Enhanced logical library volume counts. On the Logical Library Detail Information page, the total number of assigned volumes for a logical library is now provided as two separate counts:
 - Number of Volumes - This represents volumes that are assigned, are in the library, and are generally available for client use.
 - Number of Volumes Outside Library - This represents volumes that are assigned, but are not available for client use because they have been ejected – either physically ejected, or marked for eject by the FC client.
 - During ACSLS installation, you can choose whether to install the GUI or to delay installation.

The packages for the ACSLS GUI, etc. are still installed. Should you wish to install the GUI later, you need to: export the database and control files; rerun `install.sh` and install the GUI, etc.; then import your saved database and control files.

- 508 Accessibility: Alternate text tooltips have been added to support every graphic component in the GUI.

Overview of ACSLS

Library Management

ACSLs is automated library management software. It facilitates automated tape operations for multiple clients, providing services and support to enhance library ease-of-use, performance, and availability. One ACSLS server can control libraries connected into a library complex, individual libraries, or a mix of both.

ACSLS includes all library management capabilities available in the legacy ACSLS product at the ACSLS 7.3.1. Support is provided for ACSAPI clients, `cmd_proc` and ACSLS utilities (startup and shutdown have changed).

Graphical User Interface

The GUI is a browser-based web application which runs within the Java Web Console. This interface provides an alternative to the traditional `cmd_proc` interface from ACSLS.

- Runs as an application with the Oracle's WebLogic.
- Provides an alternative to the `cmd_proc` for library administration and operation. It provides the ability to perform most legacy `cmd_proc` operations, along with new operations related to logical library management.
- Provides real-time monitoring of tape library components.
- Provides a tree browser to navigate physical and logical configuration.
- Real time alerts are visible from each screen.
- Allows the customizing of filtering capabilities and the ability to download query results to a flat file.

Features

- Create, edit and delete logical library resources
- View physical and logical resources
- Audit physical and logical libraries
- Perform enters and ejects
- Perform mounts and dismounts
- Set clean and set owner for one or more volumes
- User-customized displays and custom filtering for volume and drive listings.
- Set the CAP mode and priority
- Vary operations for physical and logical components
- System Operations, including ability to cancel selected operations
- Log viewer for event logs

Logical Libraries

The ACSLS GUI enables you to create logical libraries which include a sub-set of the volumes and drives in a specific physical library. This allows you to define logical subsets of your physical libraries, which can be managed and utilized by client applications as if they were separate logical libraries. You can dedicate a portion (or all) of the volumes and drives in a given physical library to a logical library for use by a specific client application.

- A logical library can not span more than one physical ACS (or physical partition).

- Logical libraries are accessible to clients using the ACSLS 8.x SCSI Interface. They *are not* available to clients that use the legacy ACSAPI.
- Physical drives and cartridges that are allocated to logical libraries become inaccessible to ACSAPI clients. The physical libraries, along with any drives and volumes that are not allocated to logical libraries, remain accessible to ACSAPI clients.
- Drives and volumes that are allocated to logical libraries are allocated exclusively. There is no support for sharing of either drives or volumes across logical libraries.

Open Format (Volser)

Before ACSLS 8.x, support for longer volume labels in physical libraries relied on library firmware and configuration.

Now, the ACSLS SCSI Media Changer Interface allows ACSLS to support longer volume labels. You have visibility to the longer volume labels through the GUI, the CLI (`cmd_proc`), and utilities.

Longer volume labels are viewed by clients using the SCSI Medium Changer interface to access logical libraries. They are not accessible to ACSAPI clients.

SCSI Media Changer over Fibre Client Interface

ACSL 8.x provides a SCSI Media Changer over Fibre Channel Interface for allowing access to logical libraries. ACSLS can service multiple SCSI clients simultaneously. Each client has exclusive access to its assigned logical library.

This allows client software, such as NetBackup, to utilize the logical libraries as if they were separate physical libraries. Each logical library can be assigned to only one client, but a given client can access multiple logical libraries if desired. ACSLS 8.x does not allow direct SCSI client access to the backing physical libraries - only the volumes and drives assigned to the logical libraries are accessible.

SCSI client access can be established when creating or modifying logical libraries.

ACSAPI Client Interface

ACSL 8.x provides an ACSAPI client interface which is compatible with existing client applications. The ACSAPI interface is identical to that provided in the legacy ACSLS 7.3 product.

Access and Visibility

ACSAPI clients have neither visibility nor access to logical libraries.

Physical Drives and Cartridges

Physical drives and cartridges that are allocated to logical libraries become inaccessible to ACSAPI clients. The physical libraries, along with any drives and volumes that are NOT allocated to logical libraries, remain accessible to ACSAPI clients.

Command Line Interface

ACSL 8.x provides a command-line interface in the form of the legacy `cmd_proc` from ACSLS. This interface provides the same functionality as ACSLS 7.3 for managing physical library resources.

The `cmd_proc` interface does not provide access to logical libraries. But the physical resources which have been allocated to logical libraries do remain fully accessible through the `cmd_proc` administrative CLI (although they are not accessible to ACSAPI clients).

Utilities

ACSL 8.x provides a set of utilities which can be executed from a shell running on the ACSLS server. This includes most of the traditional utilities provided in the legacy ACSLS 7.3.1 product.

These utilities include the following:

- backup and restore operations for database tables
- import and export operations for database tables
- startup and shutdown operations
- dynamic configuration for physical libraries
- `volrpt`, `moving.sh`, and `ejecting.sh`

Differences and exceptions

- A new utility (`getHba.sh`) manages Fibre Channel (FC) ports. Ports can be configured to operate in target mode (supporting FC clients) or in initiator mode (managing FC-attached physical libraries).
- ACSLS provides a new command (`acsss`) for starting and stopping the library management application. This command is available from the shell prompt only, and is not accessible from the GUI.

The `acsss` command replaces the `db_command`, `rc.acsss`, `kill.acsss`, and `fix_rc.sh` commands used in ACSLS. The `acsss` command also provides the ability to monitor application status. For example, you use:

- `acsss enable` to start ACSLS
- `acsss disable` to stop ACSLS
- `acsss` to see the list of options

No Longer Requires Software Licenses

Beginning with StorageTek ACSLS versions 7.3.1 and 8.x, the right-to-use license is no longer enforced in StorageTek ACSLS, and ACSLS no longer checks for a valid license key. Messages regarding a soon-to-be-expired license key or library capacity license no longer appear on the system console or in the `acsss_event.log`.

The following utilities no longer function in their capacity to set and check for a valid license key:

- `licensekey.sh`
- `get_license_info.sh`

To view your library slot usage use the `free_cells.sh` utility.

testports Utility

Beginning with StorageTek ACSLS versions 7.3.1 and 8.x, a new testports utility tests the connection to TCP/IP libraries and whether the ACS and port connection is online or offline.

Library, Tape Drive and Media Support

This chapter provides you with a list of:

- [“Current Libraries Supported” on page 12](#)
- [“Legacy Libraries Supported” on page 13](#)
- [“Tape Drives Supported” on page 13](#)
- [“Tape Media Supported” on page 17](#)
- [“Tape Drive and Media Compatibility Supported” on page 20](#)

Current Libraries Supported

The following table provides the list of libraries supported by ACSLS. The second column in this table shows support for a library, and its features added, after ACSLS 7.0.

TABLE 2-1 Current Libraries Supported

Library and Library Feature	Support and Maintenance Level after 7.0
StorageTek SL8500	ACSL 7.1
StorageTek SL8500, Dual TCP/IP Connections	ACSL 7.1 with PUT0602
StorageTek SL8500, Connections to Multiple Libraries	ACSL 7.1 with PUT0701
StorageTek SL8500 Partitioning	ACSL 7.1 with PUT0701
StorageTek SL500	ACSL 7.1 with PUT0402
StorageTek SL500 Cartridge Expansion Module (CEM)	ACSL 7.1 with PUT0502
StorageTek SL3000	ACSL 7.3
StorageTek SL3000 AEM	ACSL 7.3 with PUT0801 (ejecting only 42 cartridges at a time) ACSL 8.0 (eject full AEM using the GUI)
StorageTek Virtual Tape Library (VTL)	ACSL 7.3 with PUT0801
Drive & Media Statistics from Library	ACSL 7.3. An improved display is provided with PUT0801.
SL3000 and SL8500 Redundant Electronics	ACSL 7.3.1 and 8.0.2
SL3000 IPv6 communication	ACSL 7.3.1 and 8.0.2

Legacy Libraries Supported

The following table lists the legacy libraries also supported by ACSLS.

Note – ACSLS is still coded to support several earlier StorageTek libraries, like the 4410s, 97xx, L20, L40, and L80 libraries. However, we have not been able to test our support for these libraries for several years.

TABLE 2-2 Legacy Libraries Supported

Library and Library Feature
StorageTek 9310
StorageTek 9360
StorageTek L180
StorageTek L700
StorageTek L700e PTP
StorageTek L5500

Tape Drives Supported

The following table is used to translate drive types between applications. The Drive Type Name represents the drive type in `cmd_proc` and event log messages. The ACSAPI Drive Type Number is used in ACSLS software operations and ACSAPI client communications.

The last column in the Tape Drives table describes when support for a tape drive and associated media was added after ACSLS 7.0.

Notes:

1. The library drive type for DLT and SDLT drives is in a different drive domain than Oracle StorageTek drives, and it overlays with the drive types of StorageTek drives. To avoid conflicts, it is incremented by 40 hexadecimal or 64 decimal when these drives are reported by Host/Library Interface libraries. The incremented or “offset” drive type is reported in parentheses.
2. The SL8500 supports LTO-5 drives starting with the 6.0.2 firmware. ACSLS must be at the 7.3.1 or 8.0.2+ update level to support the SL8500 6.0.2+ firmware.
3. To determine if a new tape drive is supported in your release and maintenance level, go to an ACSLS Product Information manual for a later ACSLS release and look at the "ACSLs Support if after 7.0" column in the Tape Drives Supported table.

We add support to new tape drives to ACSLS before the tape drives are released so:

- we can test with prototype versions of the drives, and
- you can install and use the drives without installing patches to ACSLS.

We cannot announce support for new tape drives in the release notes for an ACSLS release or update because at the time ACSLS is released, the new tape drive has not yet been released. We also cannot update the Readme files after an ACSLS package or patch is released.

TABLE 2-3 Tape Drives Supported

ACSAPI Drive Type Number	Drive Domain - hex and character, if applicable	Drive Type Reported by Library (decimal)	Drive Type Name	Tape Drive Description	ACSLs Support after 7.0
0	00h	64	4480	StorageTek 18-track	
1	00h	08	4490	StorageTek Silverton 36-track	
2	00h	32	9490	StorageTek TimberLine 36-track high performance	
3	00h	16	SD3	StorageTek Redwood Helical	
4	00h	04	4890	StorageTek Twin Peaks 36-track	
5	01h	01 (65)*	DLT2000	Quantum DLT2000	
6	01h	02 (66)*	DLT2000XT	Quantum DLT2000XT	
7	01h	03 (67)*	DLT4000	Quantum DLT4000	
8	01h	04 (68)*	DLT7000	Quantum DLT7000	
9	00h	02	9840	StorageTek T9840A	
10	00h	33	9491	StorageTek TimberLine EE 36-track	
11	01h	07 (71)*	DLT8000	Quantum DLT8000	
12	00h	03	9840-3590	T9840A with IBM 3590 emulation	
13	00h	05	T9940A	T9940A with SCSI/ Fibre or VSM3490	
14	00h	06	9940--3590	T9940A with 3590 emulation	
15	01h	20 (84)*	SDLT	Super DLT 220	
16	00h	01	T9840B	High Performance 9840 with SCSI/Fibre or VSM3490	
17	00h	07	T9840B35	T9840B with 3590 emulation	
18	4Ch ("L")	48	HP-LTO	HP LTO Generation 1	
19	4Ch ("L")	49	IBM-LTO	IBM LTO Generation 1	

TABLE 2-3 Tape Drives Supported

ACSAPI Drive Type Number	Drive Domain - hex and character, if applicable	Drive Type Reported by Library (decimal)	Drive Type Name	Tape Drive Description	ACSL S Support after 7.0
20	4Ch ("L")	50	CER-LTO	Certance LTO Generation 1	
21	00h	09	T9940B	T9940B with SCSI/Fibre or VSM3490	
22	00h	10	T9940B35	T9940B with 3590 emulation	
23				<i>reserved</i>	
24	01h	21 (85)*	SDLT-320	Super DLT 320	
25	00h	11	T9840C	T9840C with Fibre or VSM3490	
26	00h	12	T9840C35	T9840C with 3590 emulation	
27	4Ch ("L")	51	HP-LTO-2	HP LTO Generation 2	
28	4Ch ("L")	52	IBM-LTO-2	IBM LTO Generation 2	
29	4Ch ("L")	53	CER-LTO-2	Certance LTO Generation 2	
30	01h	23 (87)*	SDLT-600	Super DLT-600	ACSL S 7.1
31	54h ("T")	13	T1A	T10000A with Fibre or VSM3490	ACSL S 7.1 with PUT0501
32	54h ("T")	14	T1A35	T10000A with IBM 3592 emulation	ACSL S 7.1 with PUT0501
33	4Ch ("L")	54	HP-LTO-3	HP LTO Generation 3	ACSL S 7.1 with PUT0501
34	4Ch ("L")	55	IBM-LTO-3	IBM LTO Generation 3	ACSL S 7.1 with PUT0501
35	4Ch ("L")	56	CER-LTO-3	Certance LTO Generation 3	ACSL S 7.1 with PUT0501
36				<i>reserved</i>	
37	54h ("T")	24	T1AE	T10000A, fibre or VSM3490, with encryption enabled	ACSL S 7.1 with PUT0602
38	54h ("T")	25	T1AE35	T10000A - IBM 3592 emulation with encryption enabled	ACSL S 7.1 with PUT0602
39				<i>reserved</i>	
40				<i>reserved</i>	

TABLE 2-3 Tape Drives Supported

ACSAPI Drive Type Number	Drive Domain - hex and character, if applicable	Drive Type Reported by Library (decimal)	Drive Type Name	Tape Drive Description	ACSL S Support after 7.0
41	00h	18	T9840D	T9840D, fibre or VSM3490	ACSL S 7.1 with PUT0602
42	00h	19	T9840D35	T9840D - IBM 3592 emulation (MVS attach)	ACSL S 7.1 with PUT0602
43	00h	20	T9840DE	T9840D, fibre or VSM3490, with encryption enabled	ACSL S 7.1 with PUT0602
44	00h	21	T9840DE5	T9840D- IBM 3592 emulation (MVS attach) with encryption enabled	ACSL S 7.1 with PUT0602
45	01h	24 (88)*	DLT-S4	Quantum DLT-S4	ACSL S 7.1 with PUT0602
46	4Ch ("L")	57	HP-LTO4	HP LTO Generation 4	ACSL S 7.1 with PUT0701
47	4Ch ("L")	58	IBM-LTO4	IBM LTO Generation 4	ACSL S 7.1 with PUT0701
48				reserved	
49	54h ("T")	26	T1B	T10000B with Fibre or VSM3490	ACSL S 7.1 with PUT0701 and PTF or ACSL S 7.2 with PUT0702
50	54h ("T")	27	T1B35	T10000B with IBM 3592 emulation	ACSL S 7.1 with PUT0701 and PTF or 7.2 with PUT0702
51	54h ("T")	28	T1BE	T10000B with Fibre or VSM3490 and encryption	ACSL S 7.1 with PUT0701 and PTF or ACSL S 7.2 with PUT0702
52	54h ("T")	29	T1BE35	T10000B with encryption and IBM 3592 emulation	ACSL S 7.1 with PUT0701 and PTF or ACSL S 7.2 with PUT0702

TABLE 2-3 Tape Drives Supported

ACSAPI Drive Type Number	Drive Domain - hex and character, if applicable	Drive Type Reported by Library (decimal)	Drive Type Name	Tape Drive Description	ACSL S Support after 7.0
53	54h ("T")	34	T1C	T10000C with Fibre or VSM3480	ACSL S 7.3.1 or ACSLS 8.0.2
54	54h ("T")	35	T1C35	T10000C with IBM 3592 emulation	ACSL S 7.3.1 or ACSLS 8.0.2
55	54h ("T")	36	T1CE	T10000C with Fibre or VSM3480 and encryption	ACSL S 7.3.1 or ACSLS 8.0.2
56	54h ("T")	37	T1CE35	T10000C IBM 3592 emulation with encryption enabled	ACSL S 7.3.1 or ACSLS 8.0.2
57	4Ch ("L")	59	HP-LTO5	HP-LTO Generation 5	ACSL S 7.3.1
58	4Ch ("L")	60	IBM-LTO5	IBM LTO Generation 5	ACSL S 7.3.1
59	4Ch ("L")	61	HP-LTO6	HP LTO Generation 6	ACSL S 8.1
60	4Ch ("L")	62	IBM-LTO6	IBM LTO Generation 6	ACSL S 8.1

Tape Media Supported

The following table lists the compatible tape media supported for each transport type.

Notes:

- * Legacy StorageTek media do not have a media domain on the label. They are reported as media domain 0 (zero).
- ** 3480 cartridges do not have a media type label. They are reported as media type1.
- *** DLT cartridges do not have a media domain on the label. They are reported as media domain 1. SDLT cartridges with 7 character barcodes are also reported as media domain 1.
- **** When a media type is reported as cleaning cartridge "maybe", both data or cleaning cartridges can have this media type.
- ***** LTO-6 media types are reported as LTO-3.2T and LTO-3.2W in ACSLS 8.1. In ACSLS 8.2 and later releases, LTO-6 media types are reported as LTO-2.5T and LTO-2.5W. This was because the capacity of LTO-6 media changed before LTO-6 was announced.

TABLE 2-4 Tape Media Supported

ACSAPI Media Type Number	Media Type Name	Media Description	Media Domain (on label)	Media Type (on label)	Cleaning Cartridge ****
0	3480	3480 18 or 6-track	0*	1**	maybe
1	3490E	3490E 36-track	0*	E	no
2	DD3A	StorageTek Redwood (Helical) 10GB	0*	A	no
3	DD3B	StorageTek Redwood (Helical) 25GB	0*	B	no
4	DD3C	StorageTek Redwood (Helical) 40GB	0*	C	no
5	DD3D	StorageTek Redwood Cleaning Cartridge	0*	D	yes
6	DLTIII	Quantum DLT III -10GB	1***	C	maybe
7	DLTIV	Quantum DLT IV - 20GB or 35GB	1***	D	no
8	DLTIIIXT	Quantum DLT IIIxt - 15GB	1***	E	no
9	STK1R	T9840A, T9840B, T9840C or T9840D data cartridge	0*	R	no
10	STK1U	T9840A, T9840B, 9840C cleaning cartridge	0*	U	yes
11	EECART	9490EE 36-track	0*	Z	no
12		reserved			
13	STK2P	9940 data cartridge	0*	P	no
14	STK2W	9940 cleaning cartridge	0*	W	yes
15		reserved			
16	LTO-100G	LTO Generation 1 data cartridge	L	1	no
17	LTO-50GB	LTO Generation 1 data cartridge	L	A	no
18	LTO-35GB	LTO Generation 1 data cartridge	L	B	no
19	LTO-10GB	LTO Generation 1 data cartridge	L	C	no
20	LTO-CLN2	IBM cleaning cartridge	C	2	yes
21	LTO-CLN3	Certance cleaning cartridge	C	3	yes
22	LTO-CLN1	HP cleaning cartridge	C	1	yes
23	SDLT	Super DLT Generation I cartridge	1***	S	maybe
24		reserved			
25	LTO-CLNU	LTO universal cleaning cartridge	C	U	yes
26	LTO-200G	LTO Generation 2 data cartridge	L	2	no

TABLE 2-4 Tape Media Supported

ACSAPI Media Type Number	Media Type Name	Media Description	Media Domain (on label)	Media Type (on label)	Cleaning Cartridge ****
27	SDLT-2	Super DLT Generation II data cartridge	1***	2	no
28	T10000T1	T10000 data cartridge	T	1	no
29	T10000TS	T10000 “sport” data cartridge	T	S	no
30	T10000CT	T10000 cleaning cartridge	C	T	yes
31	LTO-400G	LTO Generation 3 data cartridge	L	3	no
32	LTO-400W	LTO Generation 3 WORM data cartridge	L	T	no
33		reserved			
34	SDLT-S1	Super DLT Generation I data cartridge in SDLT-220 format	S	1	maybe
35	SDLT-S2	Super DLT Generation I data cartridge in SDLT-320 format	S	2	no
36	SDLT-S3	Super DLT Generation II data cartridge	S	3	no
37	SDLT-S4	Super DLT Generation 4 data cartridge	S	4	no
38	SDLT-4	Super DLT Generation 4 data cartridge	1***	4	no
39	STK1Y	T9840D cleaning cartridge	0*	Y	yes
40	LTO-800G	LTO Generation 4 data cartridge	L	4	no
41	LTO-800W	LTO Generation 4 WORM data cartridge	L	U	no
42	T10000T2	T10000 Version 2 data cartridge	T	2	no
43	T10000TT	T10000 Version 2 “sport” data cartridge	T	T	no
44	T10000CC	T10000 Version 2 cleaning cartridge	C	C	yes
45	LTO-1.5T	LTO Generation 5 data cartridge	L	5	no
46	LTO-1.5W	LTO Generation 5 WORM data cartridge	L	V	no
47	T10000CL	T10000 Backwards compatible cleaning cartridge	C	L	yes
48	LTO-3.2T	LTO Generation 6 data cartridge	L*****	6	no
49	LTO-3.2W	LTO Generation 6 WORM data cartridge	L*****	W	no

Tape Drive and Media Compatibility Supported

The following table lists the compatible media for each drive type. Use these values as input to the `media media_type` and `drive drive_type` parameters on ACSLS commands.

Note – R/O identifies media types that are read-only by the specified drive type.

TABLE 2-5 Drive and Media Compatibility

Drive Type (<i>drive_type</i>)	Compatible Media for Data Cartridge	Compatible Media for Cleaning Cartridge
4480	3480,	3480
4490	3480, 3490E	3480
4890	3480, 3490E	3480
9490	3480, 3490E	3480
9490EE	3480 (read only), 3490E, EECART	3480
SD3	DD3A, DD3B, DD3C	DD3D
9840	STK1R	STK1U
9840-3590	STK1R	STK1U
T9840B	STK1R	STK1U
T9840B35	STK1R	STK1U
T9840C	STK1R	STK1U
T9840C35	STK1R	STK1U
T9840D	STK1R	STK1Y
T9840D35	STK1R	STK1Y
T9840DE	STK1R	STK1Y
T9840DE5	STK1R	STK1Y
T9940A	STK2P	STK2W
9940A-3590	STK2P	STK2W
T9940B	STK2P	STK2W
T9940B35	STK2P	STK2W
DLT2000	DLTIII	DLTIII
DLT2000XT	DLTIII, DLTIIIXT	DLTIII
DLT4000	DLTIII, DLTIIIXT, DLTIV	DLTIII
DLT7000	DLTIII, DLTIIIXT, DLTIV	DLTIII
DLT8000	DLTIII, DLTIIIXT, DLTIV	DLTIII
SDLT	SDLT, SDLT-S1, DLTIV	SDLT, SDLT-S1

TABLE 2-5 Drive and Media Compatibility

Drive Type (<i>drive_type</i>)	Compatible Media for Data Cartridge	Compatible Media for Cleaning Cartridge
SDLT-320	SDLT, SDLT-S1, SDLT-S2, DLTIV	SDLT, SDLT-S1
SDLT-600	SDLT (R/O), SDLT-2, SDLT-S1 (R/O), SDLT-S2 (R/O), SDLT-S3	SDLT, SDLT-S1
DLT-S4	SDLT-2, SDLT-4, SDLT-S2 (R/O), SDLT-S3, SDLT-S4	SDLT,
HP-LTO	LTO-100G, LTO-50GB, LTO-35GB, LTO-10GB	LTO-CLN1, LTO-CLNU
IBM-LTO	LTO-100G, LTO-50GB, LTO-35GB, LTO-10GB	LTO-CLN2, LTO-CLNU
CER-LTO	LTO-100G, LTO-50GB, LTO-35GB, LTO-10GB	LTO-CLN3, LTO-CLNU
HP-LTO-2	LTO-200G, LTO-100G, LTO-50GB, LTO-35GB, LTO-10GB	LTO-CLN1, LTO-CLNU
IBM-LTO-2	LTO-200G, LTO-100G, LTO-50GB, LTO-35GB, LTO-10GB	LTO-CLN2, LTO-CLNU
CER-LTO-2	LTO-200G, LTO-100G, LTO-50GB, LTO-35GB, LTO-10GB	LTO-CLN3, LTO-CLNU
HP-LTO-3	LTO-400G, LTO-400W, LTO-200G, LTO-100G (R/O), LTO-50GB (R/O), LTO-35GB (R/O), LTO-10GB (R/O)	LTO-CLN1, LTO-CLNU
IBM-LTO-3	LTO-400G, LTO-400W, LTO-200G, LTO-100G (R/O), LTO-50GB (R/O), LTO-35GB (R/O), LTO-10GB (R/O)	LTO-CLN2, LTO-CLNU
CER-LTO-3	LTO-400G, LTO-400W, LTO-200G, LTO-100G (R/O), LTO-50G (R/O), LTO-35GB (R/O), LTO-10G (R/O)	LTO-CLN3, LTO-CLNU
HP-LTO4	LTO-800G, LTO-800W, LTO-400G, LTO-400W, LTO-200G (R/O)	LTO-CLNU
IBM-LTO4	LTO-800G, LTO-800W, LTO-400G, LTO-400W (R/O), LTO-200G (R/O)	LTO-CLNU
HP-LTO5	LTO-1.5T, LTO-1.5W, LTO-800G, LTO-800W, LTO-400G (R/O), LTO-400W (R/O)	LTO-CLNU
IBM-LTO5	LTO-1.5T, LTO-1.5W, LTO-800G, LTO-800W, LTO-400G (R/O), LTO-400W (R/O)	LTO-CLNU

TABLE 2-5 Drive and Media Compatibility

Drive Type (<i>drive_type</i>)	Compatible Media for Data Cartridge	Compatible Media for Cleaning Cartridge
HP-LTO6	LTO-3.2T, LTO-3.2W, LTO-1.5T, LTO-1.5W, LTO-800G (R/O), LTO-800W (R/O)	LTO-CLNU
IBM-LTO6	LTO-3.2T, LTO-3.2W, LTO-1.5T, LTO-1.5W, LTO-800G (R/O), LTO-800W (R/O)	LTO-CLNU
T1A	T10000T1, T10000TS	T10000CT, T10000CL
T1A35	T10000T1, T10000TS	T10000CT, T10000CL
T1AE	T10000T1, T10000TS	T10000CT, T10000CL
T1AE35	T10000T1, T10000TS	T10000CT, T10000CL
T1B	T10000T1, T10000TS	T10000CT, T10000CL
T1B35	T10000T1, T10000TS	T10000CT, T10000CL
T1BE	T10000T1, T10000TS	T10000CT, T10000CL
T1BE35	T10000T1, T10000TS	T10000CT, T10000CL
T1C	T10000T1 (R/O), T10000TS (R/O), T10000T2, T10000TT	T10000CC, T10000CL
T1C35	T10000T1 (R/O), T10000TS (R/O), T10000T2, T10000TT	T10000CC, T10000CL
T1CE	T10000T1 (R/O), T10000TS (R/O), T10000T2, T10000TT	T10000CC, T10000CL
T1CE35	T10000T1 (R/O), T10000TS (R/O), T10000T2, T10000TT	T10000CC, T10000CL

Index

A

ACSLs
 overview 1

T

Tape Drive and Media Compatibility Supported 20
Tape Drives Supported 13
Tape Media Supported 17

W

What's New 3

