

Agile

Version e6.1

ORACLE

Oracle® Agile
Engineering Data Management
Web Services Manual for Agile e6.1.2.2

Part No. E28263-02

May 2012

Copyright and Trademarks

Copyright © 1995, 2012, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third party content, products and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third party content, products or services.

CONTENTS

Copyright and Trademarks	iii
Preface	vi
Introduction to Web Services	1
About Web Services	1
Core Technologies	2
Web Services Architecture	3
About Agile e6 Web Services	4
The Core Web Services	4
About Agile e6 Web Services Framework	5
Components of Agile e6 Web Services Framework	5
Getting Started with Web Services.....	7
Prerequisites.....	7
Operating Environment.....	7
Web Services Engines	7
Web Service Development Tools	8
Standards Compliance	8
Understanding Web Services Authentication and Performance	9
The Agile e6 EDM Session Handling.....	9
Understanding the Agile e6 Web Services Requests	11
Obtaining the Agile e6 Metadata	11
Understanding the Agile e6 Web Services Responses.....	11
Response Status Code.....	12
White-list Mechanism for Masks.....	12
Exceptions and Warnings.....	13
Counting the Objects	14
Setting up the Web Services Infrastructure	15
Installing the Agile e6 Web Services Framework.....	15
Creating the WebLogic Agile e6 Domain.....	15
Configuring the Agile e6 PLM Authentication Provider in the WebLogic Server	15
Configuring the Authentication Provider for Web Services Hotfix Package.....	20
Testing the Inbound Web Services	21
Testing with the WebLogic Test Client	21
Testing with the JDeveloper HTTP Analyzer	23

Using a Guest Account.....	24
Configuring Agile e6 Web Services Security	25
Setting up the Web Services Security Policies	25
Setting up the Web Services Security	30
Authenticating in a Web Service Client.....	31
Working with Agile e6 Web Services	39
Bulk Processing of Requests	39
Handling the Bulk Requests	39
Developing the Outbound Web Services Wrapper	40
The Web Services Wrapper Interface.....	40
Developing a Custom Wrapper	41
Calling a Custom Wrapper from Agile e6	50
Deploying a Custom Wrapper	51
Web Service Wrapper Log Messages	51
Agile e6 Core Web Services Operations	53
Business Object Web Services.....	53
Binary Data Transfer	54
Bulk Operations.....	54
Document Management Web Services	61
Bulk Operations.....	62
MetaData Web Services	67
Bulk Operations.....	67
Configuration Web Services	74
Bulk Operations.....	75

Preface

The Oracle documentation set includes Adobe® Acrobat™ PDF files. The [Oracle Technology Network \(OTN\) Web site](http://www.oracle.com/technology/documentation/agile.html) (<http://www.oracle.com/technology/documentation/agile.html>) contains the latest versions of the Oracle Agile e6 PDF files. You can view or download these manuals from the Web site, or you can ask your Agile administrator if there is an Oracle Documentation folder available on your network from which you can access the documentation (PDF) files.

Note To read the PDF files, you must use the free Adobe Acrobat Reader™ version 7.0 or later. This program can be downloaded from the [Adobe Web site](http://www.adobe.com) (<http://www.adobe.com>).

Note Before calling Agile Support about a problem with an Oracle Agile e6 manual, please have the full part number ready, which is located on the title page.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, 7 days a week. For TTY support, call 800.446.2398. Outside the United States, call +1.407.458.2479.

Readme

Any last-minute information about Oracle Agile e6 can be found in the Release Notes file on the [Oracle Technology Network \(OTN\) Web site](http://www.oracle.com/technology/documentation/agile_eseries.html) (http://www.oracle.com/technology/documentation/agile_eseries.html)

Agile Training Aids

Go to the [Oracle University Web page](http://www.oracle.com/education/chooser/selectcountry_new.html) (http://www.oracle.com/education/chooser/selectcountry_new.html) for more information on Agile Training offerings.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations

regarding the accessibility of these Web sites.

Introduction to Web Services

About Web Services

Web Services are technologies for building distributed applications. These services, which can be made available over the Internet, use a standardized XML messaging system and are not tied to specific operating systems or programming languages. Through Web Services, companies can encapsulate existing business processes, publish them as services, search for and subscribe to other services, and exchange information throughout and beyond the enterprise. Web Services are based on universally agreed upon specifications for structured data exchange, messaging, discovery of services, interface description, and business process design.

A Web Service makes remote procedure calls across the Internet using:

- HTTP/HTTPS or other protocols to transport requests and responses.
- Simple Object Access Protocol (SOAP) to communicate request and response information.

The key benefits provided by Web Services are:

- Service-oriented Architecture

Unlike packaged products, Web Services can be delivered as streams of services that allow access from any platform. Components can be isolated; only the business-level services need be exposed.

- Interoperability

Web Services ensure complete interoperability between systems.

- Integration

Web Services facilitate flexible integration solutions, particularly if you are connecting applications on different platforms or written in different languages.

- Modularity

Web Services offer a modular approach to programming. Each business function in an application can be exposed as a separate Web Service. Smaller modules reduce errors and result in more reusable components.

- Accessibility

Business services can be completely decentralized. They can be distributed over the Internet and accessed by a wide variety of communications devices.

▫ Efficiency

Web Services constructed from applications meant for internal use can be used for externally without changing code. Incremental development using Web Services is relatively simple because Web Services are declared and implemented in a human readable format.

Core Technologies

Oracle's Agile e6 Web Services use industry standard core technologies. These are:

1. Web Services Description Language (WSDL)
2. XML and XML Schema
3. Simple Object Access Protocol (SOAP)

Web Services Description Language (WSDL)

WSDL is an XML-based format for describing the interface of a Web Service. WSDL describes the endpoints, location, protocol binding, operations, parameters, and data types of all aspects of a Web Service:

- The WSDL that describes a Web Service has the following characteristics:
 - It is published by the service provider.
 - It is used by the client to format requests and interpret responses.
 - It can be optionally submitted to a registry or service broker to advertise a service.
- Additionally, WSDL describes the following:
 - The operations that are provided by a Web Service.
 - The input and output message structures for each Web Service operation.
 - The mechanism to contact the Web Service.

XML and XML Schema

A WSDL file is published via an XML file. Document/Literal is required as part of the WS-I interoperability standard. This standard sets the basis for modern Web Service usage.

▫ Document

The payload for an operation, however complex, must be defined in a single XML element.

▫ Literal

The definition of single XML element must be described by an XML Schema embedded in the WSDL file.

When using Document/Literal formatting, the WSDL file will contain an XML Schema definition that defines all messages and data types that are used for a particular service. The payload itself will consist entirely of XML data structures.

Simple Object Access Protocol (SOAP)

SOAP is a lightweight protocol intended for exchanging structured information in a decentralized, distributed environment. SOAP uses XML to define an extensible messaging framework.

SOAP messages consist of the following:

- An envelope for wrapping messages, including addressing and security information.
- A set of serialized rules for encoding data types in XML.
- Conventions for a procedure call and, or response.

Web Services Architecture

You can view Web Services architecture in terms of roles and the protocol stack:

- Roles:
 - Service provider – This provides the service by implementing it and making it available on the Internet.
 - Service requester – This is the user of the service who accesses the service by opening a network connection and sending an XML request.
 - Service registry – This is a centralized directory of services where developers can publish new services or find existing ones.
- Protocol Stack:
 - Service transport layer

This layer uses the HTTP protocol to transport messages between applications.
 - XML messaging layer

This layer encodes messages in XML format using SOAP to exchange information between computers. It defines an envelope specification for encapsulated data that is transferred, the data encoding rules, and remote procedure call (RPC) conventions.

- Service description layer

This layer describes the public interface to a specific Web Service using the Web Service Description Language (WSDL) protocol. With WSDL, it defines an XML grammar to describe network services. The operations and messages are described abstractly, and then bound to a network protocol and message format. WSDL allows description of endpoints and their messages regardless of what message formats or network protocols are used to communicate.

- Service discovery layer

This layer centralizes services into a common registry using the Universal Description, Discovery, and Integration (UDDI) protocol. UDDI is a platform-independent, XML-based registry for businesses worldwide to list themselves on the Internet.

About Agile e6 Web Services

Agile e6 Web Services expose a subset of the Product Lifecycle Management (PLM) functionalities of the Agile e6 Application. These services support functionalities provided by PLM modules in Agile e6 application, such as Item Management, Project Management and many other functions of Agile e6.

Implementation of Agile e6 Web Services adheres to the following principles:

- Well defined, standards based discoverable Interface
- Java based Web Services Framework using Oracle WebLogic
- Modularized Agile e6 Schema (XSD) and WSDL for easy maintenance
- Standards-based WSDL to ensure compatibility across various clients (.NET, Java, and BPEL)
- Bulk APIs wherever applicable for better performance

The Core Web Services

Agile e6 Core Web Services is a set of services for the following functionalities:

- [Business Object Web Services](#)
- [Document Management Web Services](#)
- [MetaData Web Services](#)
- [Configuration Web Services](#)


About Agile e6 Web Services Framework

The Web Service Framework is an additional layer on top of Agile e6, which supports inbound and outbound communication based on standard Web Services technology. It provides the means to call External Web Services from inside Agile e6 LogiView Procedures (outbound direction). In addition, it allows external applications (Web Service Clients) to call the Agile e6 APIs through Web Services.

The Web Service Framework comes with a set of predefined *core* web services, which, out of the box, support the most common integration scenarios like *create PLM object* or *get PLM object*.

In a future release, the Web Services framework will be enhanced with a customizing framework. This will allow the implementation of custom Web Services, which funnel inbound Web Service calls into API call to the Agile e6.

Components of Agile e6 Web Services Framework



The Agile e6 Web Services Framework comprises of the following:

- Web Service Wrapper – to support the outbound Web Service calls from LogiView Procedures.
- Core Web Services – to support the inbound Web Service calls mapped into the ECI-API calls.

Getting Started with Web Services

Prerequisites

Agile e6 Web Services are deployed on an Agile e6 WebLogic application domain.

To use the Agile e6 Web Services Framework for inbound and outbound Web Services based business data transaction, you are required to ensure the following:

- Operational Environment is set:
 - Oracle Agile e6, Release 6.1.2.2 is installed.
 - WebLogic Server is installed and
- Web Services Framework is configured for the following:
 - Authentication Provider in WebLogic.
 - Web Service Security.
- Test the Inbound Web Services.

Then you will be able to call the available Core Services or implement your own outbound Web Service Wrappers.

Operating Environment

Agile e6 Application	Release e6.1.2.2 or higher
Default Web Services Engine	Oracle WebLogic Server Note: The version of this server is the one that is released with the Agile e6 application.
Java 2 Platform Standard Edition Development Kit	6.0

Web Services Engines

All Application Server vendors, such as Oracle, IBM, have built-in Web Services infrastructure solutions that are integrated with their application servers. For non-Web Services integrated applications, there are stand-alone products, such as AXIS from Apache, which provide Web Services infrastructure that can be integrated with different application servers.

The Agile e6 Web Services Framework works on the following Web Service Engines:

- Oracle Apps Server Web Service Infrastructure
- Oracle SOA Suite
- WebLogic Web Service Infrastructure
- Axis version 2.0 to support JAX-WS features, especially the MTOM

Web Service Development Tools

To develop your own Web Services, you can use various tools. Development platforms vary in their SOAP implementations. Implementation differences in certain development platforms may prevent access to some or all of the features in the API. If you are using Visual Studio for .NET development, it is recommended that you use Visual Studio 2003 or higher.

In this documentation the development and test of Web Services is described using Oracle's JDeveloper. You can also use Oracle's Enterprise Pack for Eclipse (EPE).

For complete information on JDeveloper and Enterprise Pack for Eclipse, refer to Oracle Technology Network web site: <http://www.oracle.com/technetwork/developer-tools/index.html>

The Agile e6 web security framework provides tool objects (source codes) to retrieve security information from the Web Service call which can be used to initiate a PLM session.

Standards Compliance

The Agile e6 Web Services are implemented in compliance with the following standards:

Standard	Location
Simple Object Access Protocol (SOAP) 1.1/1.2	http://www.w3.org/TR/2000/NOTE-SOAP-20000508/
Web Service Description Language (WSDL) 1.2	http://www.w3.org/TR/2001/NOTE-wsdl-20010315
WS-I Basic Profile 1.1	http://www.ws-i.org/Profiles/BasicProfile-1.1-2004-08-24.html
XML Schema 1.1	http://www.w3.org/XML/Schema
SOAP Message Transmission Optimization Mechanism (MTOM)	http://www.w3.org/TR/soap12-mtom/
JAX-WS 2.0/2.1/2.2 (JSR 224)	http://java.sun.com/developer/technicalArticles/J2SE/jax_ws_2/
JAXB 2.0/2.1/2.2 (JSR-222)	http://jaxb.java.net/

Understanding Web Services Authentication and Performance

In the implementations where scalability is critical, a lightweight context management facility for authentication is available and its use is recommended. With this facility, authentication is managed using a combination of *user credentials* and a *sessionID* token (the standard HTTP session ID maintained by the web container):

- When user credentials are presented in the SOAP header of a Web Service request, formal authentication is performed prior to the application execution of the Web Service operation. If the authentication succeeds, the operation proceeds and a special SessionID token is placed in the SOAP header of the Web Service reply.
- Whenever the sessionID is included by the client in subsequent Web Service requests, that sessionID will be used to restore cached session information, thus bypassing the substantially more time consuming process of re-executing the authentication.

Note When presented with both the sessionID and a valid set of user credentials, an attempt will be made to use the sessionID before resorting to the user credentials and re-authentication. As expected, the session that is being tracked by the sessionID is subject to expiration and other security checks.

The facility is a distinct alternative to the basic authentication standard described by Web Services Security. Using the `UserName` token as provided in WS-Security, while fully supported as part of Agile e6 WSI Basic Profile compliance, will not yield the same benefit as using the higher-performance session optimization facility provided by the Agile e6 implementation.

The Agile e6 EDM Session Handling

Every call of an Agile e6 Core Web Service needs an Agile e6 EDM server instance. It is very important to limit the number of Agile e6 server instances to reduce the resource loading on the server. This is handled by the following mechanisms:

- HTTP Session – The Web Service first tries to find an Agile e6 server instance assigned to the HTTP session of the current Web Service call. If it is found, the Web Service call uses the existing Agile e6 server instance.
- PLM Ticket – A PLM ticket is returned in the response of a core Web Service operation. This ticket can be used to access the same Agile e6 server instance that created the ticket.

While authenticating a Web Service call, if a ticket is passed instead of the password, the session manager uses the Agile e6 server instance, even if no Agile e6 server is assigned to the HTTP session.


The PLM Ticket mechanism is the only way to let the calls to different core Web Services, such as Metadata or BusinessObject Web Services use the same Agile e6 server instance.

A Web Service client should use the PLM ticket as soon as it has called the first operation.

This is the only way to share an Agile e6 session between two different Core Services.

To free an Agile e6 server instance assigned to a Web Service session, the client calls one of the *closeSession* operations (every core Web Service provides this function) with the PLM ticket as the *password*. This shuts down the Agile e6 server instance and frees up the server resources.

The Agile e6 EDM Session Manager



The Agile e6 EDM Session Manager lets you manage the EDM Session objects which are used to keep the existing connections and user contexts to the Agile e6 server.

The key to an existing EDM Session object is the session ID, which is generated by EDM Session Manager.

The EDM Session provides connection to Agile e6 server.

To retrieve a EDM Session, PlmTicket is provided. When a new EDM Session is created, the PlmTicket is set to the EDM Session, which is then set into the SOAP message to the client side.

The life cycle of EDM Session is as same as the given HttpSession. The timeout of an HttpSession is specified in web.xml with the following information:

```
<session-config>
    <session-timeout><time-in-second></session-timeout>
</session-config>
```

The PLM Ticket

A Response contains a string that can be used in subsequent calls. This string is called the PLM Ticket. The ticket gives the caller access to the same Agile e6 instance (PLM server) that was used in the last request. The ticket is remains valid only as long as the Agile e6 instance is running. After obtaining a ticket, the client code needs to configure the port by setting the ticket string as password. See BindingProvider in the example given under Authenticating in a Web Service Client.

The PLM Ticket improves the Web Services performance and simplifies the session management, If different Web Services are used in a use-case flow, which is very likely, the ticket returned by the response(s) of one service operation (say Configuration.setUserContext) is used as a password when client makes a call for another service operation (say BusinessObject.getObjects).

The ticket sharing among different client ports eliminates the need for the server to start new Agile e6 sessions, which would result in new Agile e6 servers being started.

Understanding the Agile e6 Web Services Requests

In the Agile e6 Web Services framework, each operation has its own request data type, which is inherited from RequestHeaderType. The RequestHeaderType for all the requests has only the following elements:

- messageId (String, optional): Default value for the ID is the current system time in milliseconds.
- messageName (String, optional): Default value for the message name is the simple class name.

Obtaining the Agile e6 Metadata

You can obtain the basic Agile e6 metadata through Agile e6 Java Client. Look for the data model of the Agile e6 application.

To obtain Agile e6 metadata through a Web Services operation, use the Metadata service. This service requires an entity name and a mask name.

See Configuration Parameters for further information.

Understanding the Agile e6 Web Services Responses

The ResponseHeaderType has the following members:

messageId (String, required)	Default value for the ID is the current system time in milliseconds
messageName (String, required)	Default value for the message name is the simple class name
statusCode (ResponseStatusCode, required)	Default value for the status code is SUCCESS
exceptions (List<PlmExceptionType>, optional): warnings (List<PlmWarningType>, optional)	
ticket (String, optional)	

Response Status Code

The response obtained from every Web Service call contains a response statusCode, which indicates the success or failure of a Web Service operation.

These Response Status Codes are of four types:

SUCCESS	Indicates that all Web Services in the batch were executed successfully and that all operations worked as intended.
FAILURE	Indicates that all Web Services in the batch failed during execution, indicating the intended operations were not performed.
WARNING	Indicates that while Web Services in the batch were successfully executed, however certain warnings were also encountered during the execution. These warnings need to be analyzed by the client to verify that all operations worked as intended.
PARTIAL_SUCCESS	Indicates a partial success in the execution of batch Web Services when one or more but not all batch requests have failed. Even if a single Web Service fails among a batch of Web Services, the response status code will indicate PARTIAL_SUCCESS.

White-list Mechanism for Masks

To ensure that only the masks designed for the access of Web Services are used, all the mask names are checked against a White-list that is maintained by the administrator of the Agile e6 installation.

List of Mask Names

A configuration rubric named EDB-WSI-MASKS is used. It contains sub-parameters such as EDB-ARTICLE-WSI and each of these sub-parameters contain a mask name rule pattern. All rules for an entity are checked for an operation that involves an item as an entity (or as parent entity in case of a relation).


Important It is recommended to implement special masks designed for Web Services, instead of only adding the standard masks like EDB-ART-SLI (or “**”) to the white list.
--

Adding standard masks can have certain implications due to the following:

- The security check for masks is not strong enough.
- To be able to access invisible fields, you are required to first make them visible. These should be done as these are not opened to the customer.
- Performance suffers as the standard masks contain too many fields.

Configuration Parameters

The Configuration Parameters are entered as shown in the image below.



The rule pattern consists of valid mask name characters and may contain one or more asterisks (*) to indicate one or more mask name characters.

The Web Service session reads these configuration rules and checks each combination of entity and mask name passed by a client against the rules for the respective entity. If one of the rules accepts the mask name, access is granted, If not, the access to the mask is denied and an `IllegalAccessException` is thrown and marshaled back to the client.

The rules are cached by the session so that the subsequent operations don't have the overhead of reading the rules again. The rules can also be cached in the Business Service, for instance by enhancing the Permission Manager. This provides a domain wide cache, instead of a session based cache.

Exceptions and Warnings

The Agile e6 framework throws an exception (`WebFault`) only if a severe technical problem occurs, for instance, in an event of a connection loss to the Agile e6 server. When an operation is not successful, the system will throw an Exception or a Warning.

- In case of FAILURE, an exception is issued, while a warning may or may not be issued.
- In case of WARNING, only a warning is issued.

When the status is WARNING, the outcome of the operation is unknown. You are required to check it manually whether the operation was successful or not.

Counting the Objects

A count request is indicated by the flag `countOnly` in the query request object. The service then executes a count (which ignores the mask limit) and returns a pseudo `PlmObject` with a `COUNT` attribute and a `RECORD_LIMIT` attribute.

The value of the `COUNT` attribute is an Integer with the number of objects matching the query, and the value of the `RECORD_LIMIT` attribute is the record limit of the mask used for the count operation.

Setting up the Web Services Infrastructure

Installing the Agile e6 Web Services Framework

The Agile e6 Web Services Framework is installed during the basic installation of Agile e6 application. The WebLogic domains are created with the Agile e6 application installer and/or the Agile e6 Administration Client. By default, the installation has two WebLogic domains – one for an installation and an additional one for every application. Web Services are deployed on the application specific WebLogic domain.

For complete details, please refer to the Agile e6 Installation and Administration Documents, besides the Agile e6 Hot-fix Readme.

Creating the WebLogic Agile e6 Domain

You are required to obtain a WebLogic Agile e6 Domain name from the Agile e6 Administrator, or create a new domain. This is required as the Web Services are deployed into this WebLogic Agile e6 domain.

During the installation of the WebLogic Server two domains are created. Each domain consists of an AdminServer and an eSeries-01 server. The AdminServer is only for the administration of the domain, while the eSeries-01 contains the Agile e6 deployments.

For example, the domains directory C:\Oracle\Middleware\user_projects\domains contains the domain names eSeries_domain and eSeries_domain_plmref.


For complete details on how to install the WebLogic server and create a domain, please refer to the installation manual Agile e6.1.2.2 Server on Windows/Unix.

Configuring the Agile e6 PLM Authentication Provider in the WebLogic Server

The Agile e6 PLM Authentication Provider is required to authenticate the incoming Web Requests. It is also used for providing the PLM user name and PLM Password to the Web Services to connect to the Agile e6 application.

The authentication provider is called by the WebLogic Security Framework. The Security Realm of the domain has to be configured to use the Agile e6 PLM Authentication Provider.

The following diagram depicts the authentication mechanism:



The PLM authentication provider uses the standard mechanism of the WebLogic server and can be configured with the WebLogic Administration Console.

The Authentication Provider is installed at the time of Agile e6 application installation. During this installation, the PLM User and PLM password are set to an empty value. These cannot be set with the batch installer, hence, they have to be added manually with the WebLogic Console. For complete details on Agile e6 application installation, including the preliminary settings of the authentication provider, refer to the Agile e6 Server Installation Guides.


Note The user should be a special user with no manager rights.

To configure the Agile e6 Authentication Provider:

Important The application domain has to be configured while the installation domain remains unchanged.

1. Log in to the Administration Console for the application domain of the Oracle WebLogic Server.

Example: <http://server:7405/console/login/LoginForm.jsp>



2. Click the Security Realms in the Domain Structure window.

The Summary of Security Realms window opens, displaying the available realms. The default realm is myrealm.



3. Click on myrealm.

The Settings for myrealm window opens.

Settings for myrealm

Configuration Users and Groups Roles and Policies Credential Mappings Providers Migration

General RDBMS Security Store User Lockout Performance

Save

Use this page to configure the general behavior of this security realm.

Note:
If you are implementing security using JACC (Java Authorization Contract for Containers as defined in JSR 115), you must

Name: myrealm

Security Model Default: DD Only

Combined Role Mapping Enabled

Use Authorization Providers to Protect JMX Access

Advanced

Save

- Go to the Providers tab.

The PLM authentication providers are listed in the Authentication sub-tab.

Settings for myrealm

Configuration Users and Groups Roles and Policies Credential Mappings Providers Migration

Authentication Password Validation Authorization Adjudication Role Mapping Auditing Credential Mapping Certification Path Keystores

An Authentication provider allows WebLogic Server to establish trust by validating a user. You must have one Authentication provider in a security realm, and you servers or DBMS. You can also configure a Realm Adapter Authentication provider that allows you to work with users and groups from previous releases of WebLogic.

Customize this table

Authentication Providers

New Delete Reorder

<input type="checkbox"/>	Name	Description
<input type="checkbox"/>	DefaultAuthenticator	WebLogic Authentication Provider
<input type="checkbox"/>	DefaultIdentityAsserter	WebLogic Identity Assertion provider
<input type="checkbox"/>	PlmAuthenticator	Oracle Agile PLM e6 Authentication Provider

New Delete Reorder

- Click PlmAuthenticator in the Name column.

This opens the Settings for PlmAuthenticator window, displaying the Authentication Configuration.

Settings for PlmAuthenticator

Configuration

Common Provider Specific

Save

This page allows you to define the general configuration of this provider.

Name: PlmAuthenticator

Description: Oracle Agile PLM e6 Authentication Provider

Version: 1.0

Control Flag: SUFFICIENT

Save

- In the Common sub-tab, select the Control Flag value.

This value allows the configuration of the JAAS (Java Authentication and Authorization Service) login module of the provider.

The JAAS Control Flag values are:

REQUIRED	The Authentication provider is always called, and the user must always pass its authentication test. If authentication succeeds or fails, the authentication still continues down the list of providers.
REQUISITE	The user is required to pass the authentication test of the Authentication provider. If the user passes the authentication test of this Authentication provider, subsequent providers are executed but can fail (except for Authentication providers with the JAAS Control Flag set to REQUIRED).
SUFFICIENT	[Recommended Value] The user is not required to pass the authentication test of the Authentication provider. If authentication succeeds, no subsequent Authentication providers are executed. If authentication fails, authentication continues down the list of providers.
OPTIONAL	The user is allowed to pass or fail the authentication test of this Authentication provider. However, if all Authentication providers configured in a security realm have the JAAS Control Flag set to OPTIONAL, the user must pass the authentication test of one of the configured providers.

- In the Provider Specific sub-tab, configure the following values:

The PLM authenticator delegates the authentication request to the PLM server which is specified in the Provider Specific tab. These data are used by the PLM authenticator to connect to that PLM server.

The user and password in the admin UI are used to configure the PLM authenticator. The PLM authenticator needs a valid PLM user and password from the PLM application belonging to its domain. It will start one Agile e6 server and use this server then to check the user credentials in incoming HTTP(S) requests.

The authenticator's main purpose is to have a fail-fast mechanism in case the HTTP(S) request contains wrong credentials. The authenticator just needs an ECI call to check the credentials. Without the authenticator, the Web Service session manager starts a new Agile e6 server (this takes some time and valuable resources) just to notice that the credentials are incorrect.

It is OK to run a Web Service domain without authenticator, but you will have a performance penalty if many HTTP request with wrong credentials are coming in.

Settings for PlmAuthenticator

Configuration

Common **Provider Specific**

Save

This page allows you to configure additional attributes for this security provider.

Plm Application Name: yinwipS604_test

Plm Password:

Please type again To confirm:

Plm Host: khe-java

Plm User: DEMOEP_M

Plm Port: 61640

Save

Plm Application Name	Name of PLM Application
Plm Password	PLM User password
Plm Host	Host name of the PLM Server
Plm User	Name of the PLM user
Plm Port	Port number of the Java Daemon for the PLM Server

Configuring the Authentication Provider for Web Services Hotfix Package

That is the only way right now by opening the WebLogic Admin console of the application domain.

1. Open Security Realms.
2. Open myrealm.
3. Open PlmAuthenticator.
4. Go to Provider Specific tab.

Here you can set the Plm Password and Plm User values.

Note If you carry out the modifications for this application domain with Agile e6 Admin Client, the existing values are replaced with the default values that were used during the creation of this application domain.

You are required to repeat the steps given above each time you modify the application domain with the Agile e6 Admin Client or after you create a new application domain with the Agile e6 Admin Client where you need the Authenticator.

The values of Plm Password and Plm User are usually empty.

To configure the Authentication Provider in the case nothing was configured during Agile e6 installation, you have to use the WebLogic Administration Console for the application domain. It is only possible to configure the PLM User and Password without HF2 installed when the initial installation was done.

The Agile e6 Administration Client does not support the creation or modification of a new application where you can specify the user and password for this authenticator.

Testing the Inbound Web Services

Testing with the WebLogic Test Client

Once the Web Services Framework is set up and configured, you can test the functionality with the WebLogic Test Client.

With the WebLogic test client, you cannot call Web Service operations as you cannot pass the user credentials. However, it allows you to look at the WSDL and the schema files.

To map the calls without the user credentials, you can setup and use a Guest Account. See Using a Guest Account for more details.

The Guest Account should not be used in the production environment.

Note WebLogic test client does not work with the Web Services Security policies.

1. Log in to the Administration Console of the Oracle WebLogic Server

For example, `http://server:7405/console/login/LoginForm.jsp`

2. In the left pane, click Deployments under the Domain Structure.

The Summary of Deployments page appears displaying a table that lists out the Deployments.

3. In the Summary of Deployments list, click WebServices.

The Settings for MetadataService page appears. By default, the Overview tab is open.

4. Scroll down to the Modules and Components list.
5. In the Modules and Components list, select the Web Service you wish to test.

In the following example, we will test the ConfigurationService Service.

The Settings for ConfigurationService page appears.

The screenshot shows the 'Settings for ConfigurationService' page with the 'Overview' tab selected. It contains introductory text about Web services and a table with three rows: 'Deployment Name', 'Module Name', and 'Service Name', each with its value and a 'More Info...' link.

Property	Value	Description
Deployment Name:	WebServices	Name of the Web service as it appears in the Deployments table. More Info...
Module Name:	agile-ws-e6-jws-core.war	Name of the Web service archive file, either a WAR file or EJB JAR file depending on the Web service features it implements. More Info...
Service Name:	ConfigurationService	Name of this Web service. This name appears in the WSDL file that defines the public contract of this Web service. More Info...

6. Go to the Testing tab.

The Deployment Tests list appears.

The screenshot shows the 'Settings for ConfigurationService' page with the 'Testing' tab selected. It contains instructions on how to use the page and a 'Deployment Tests' table with one row for 'ConfigurationService'.

Name	Test Point	Comments
<input type="checkbox"/> ConfigurationService		Test points for this Webservice module.

- Expand the entry ConfigurationService.

The Test Points are displayed.

The screenshot shows a web interface titled "Settings for ConfigurationService". It has several tabs: Overview, Configuration, Security, Testing (selected), and Monitoring. Below the tabs is a paragraph of instructions: "Use this page to test that your Web service is deployed and that it is working as expected. In the table, expand the name of the Web service to see a list of its test points. Click **?WSDL** to view its dynamic WSDL in a separate browser window. Click **Test Client** to invoke a new browser window where you can test each operation individually by entering parameter values, executing the operation, and viewing the results."

Below the instructions is a section titled "Deployment Tests" with a table. The table has three columns: Name, Test Point, and Comments. The first row is expanded to show two sub-rows. Navigation links "Showing 1 to 1 of 1 Previous | Next" are present above and below the table.

Name	Test Point	Comments
[-] ConfigurationService		Test points for this Webservice module.
/CoreServices/ConfigurationService	?WSDL	WSDL page on server eSeries-01
/CoreServices/ConfigurationService	Test client	Test client on server eSeries-01


Testing with the JDeveloper HTTP Analyzer

The Web Service operations can also be called and tested using the JDeveloper HTTP Analyzer.

You are required to use HTTPS for the basic authentication with the HTTP analyzer otherwise you cannot call an operation. See the chapter Configuring the Agile e6 Web Services Security for more details.

To test the Web Services from the JDeveloper HTTP Analyzer:

- Launch the JDeveloper IDE
- Open the HTTP Analyzer screen
- Enter the URL of the WSDL of the Web Service which you want to call.
- In the Request area on the left, enter the input parameters for name:string and mask:string, such as EDB-ARTICLE and EDB-ART-SLI.
- Click on Send Request.
- Upon successful call of the Web Service, the result data is displayed in the Response area of the console.



Using a Guest Account

The PLM session manager supports a Guest Account feature which allows you to map the incoming requests without requiring the credentials to a PLM guest user.

This feature is needed to support the WebLogic Server test client, which does not support passing user credentials".

Important The Guest Account feature is not intended to be used in a production environment.

The guest account is configured by adding the following credentials into the application.properties file:

```
PlmUser=<plm.application.ws.guestuser>
PlmPwd=<plm.application.ws.guestpassword>
```

The password should be encrypted using the Agile e6 installation encryption tool.

Note Do not enter plain text passwords into configuration files.

The entry PlmScope tells the session manager if the Guest sessions should share an Agile e6 PLM server (PlmScope=PUBLIC) or if each Guest session should have its own Agile e6 server instance (PlmScope=PRIVATE).

Configuring Agile e6 Web Services Security

The Web Services configuration can be used to configure the Web Services security. Since Web Services are not secured by default, it is required to configure/establish a Web Service policy that meets your security strategy requirements.

Note The Agile e6 Web Service needs user credentials to connect to the Agile e6 application server. These credentials are provided by the Agile e6 authentication provider which stores this information into the Agile e6 principal. This Agile e6 principal is populated to the Web Service by the Web Service framework. If the Web Service is not configured to be secure, the Agile e6 principal will not be available for the Agile e6 Web Service. An insecure Web Service cannot work.

Note The SSL port needs to be activated for the domain where the Web Services are deployed. The standard Listen port (non-SSL) should be disabled for the domain where the Web Services are deployed.

In the examples used in this chapter, a Web Service security policy is used to secure the entire Web Service. The client has to provide the WSS: SOAP message security user name token encrypted with a X.509 certificate.

Note The certificate itself will also be authenticated. The certificate must be valid and the certificate name must be available in the system.

Setting up the Web Services Security Policies

Note In the current release of Agile e6 core Web Services, DocumentManagementService does not support Web Services security policies. The file streaming only works with SSL (by using HTTPS). It does not work if HTTPS is enforced by adding a policy. All other Web Services can be controlled by the Web Services security policies.

To set up a Web Service Security Policy:

1. In the left pane, click Deployments under Domain Structure.

The Summary of Deployments page appears with Control tab.

Summary of Deployments

Control | Monitoring

This page displays a list of Java EE applications and stand-alone application modules that have been installed to this domain. Installed applications and modules can be started, stopped, updated (redeployed), or deleted from the domain by first selecting the application name and using the controls on this page.

To install a new application or module for deployment to targets in this domain, click the Install button.

Customize this table

Deployments

Install | Update | Delete | Start ▾ | Stop ▾ | Showing 1 to 3 of 3 | Previous | Next

<input type="checkbox"/>	Name ↕	State	Health	Type	Deployment Order
<input type="checkbox"/>	agile-ws-e6-custom	Active		Library	100
<input type="checkbox"/>	BusinessService	Active	OK	Enterprise Application	100
<input type="checkbox"/>	WebServices	Active	OK	Enterprise Application	100

Install | Update | Delete | Start ▾ | Stop ▾ | Showing 1 to 3 of 3 | Previous | Next

2. In the Name column, expand the WebServices.

All the Deployed Web Services are listed.

Deployments

Install Update Delete Start Stop Showing 1 to 3 of 3 Previous | Next

<input type="checkbox"/>	Name	State	Health	Type	Deployment Order
<input type="checkbox"/>	agile-ws-e6-custom	Active		Library	100
<input type="checkbox"/>	BusinessService	Active	OK	Enterprise Application	100
<input type="checkbox"/>	WebServices	Active	OK	Enterprise Application	100
	Modules				
	CoreServices			Web Application	
	EcdServices			Web Application	
	EJBs				
	None to display				
	Web Services				
	BusinessObjectService			Web Service	
	ConfigurationService			Web Service	
	DocumentManagementService			Web Service	
	EcdService			Web Service	
	MetadataService			Web Service	

Install Update Delete Start Stop Showing 1 to 3 of 3 Previous | Next

3. Click a Web Service.

For our further instructions, we will use ConfigurationService.

The Settings for ConfigurationService page appears, displaying the Service Endpoints and Operations and corresponding Policies.

4. Go to the WS-Policy sub-tab in the Configuration tab and expand ConfigurationPort in Service Endpoints and Operations.

Settings for ConfigurationService

Overview **Configuration** Security Testing Monitoring

General Handlers **WS-Policy** Ports

This page lists the policy files that are attached to the endpoints and operations of this Web service. The operations are listed below the endpoint; click on the + sign to view them. Click on the endpoint or operation name to attach a policy file. For example, you can specify that the policy file applies only for inbound (request) SOAP messages, and so on.

WS-Policy Files Associated With This Web Service

Showing 1 to 1 of 1 Previous | Next


Service Endpoints and Operations	Policies
<input type="checkbox"/> ConfigurationPort	
closeSession	
getConfigurationVersion	
getDefault	
getDefaultBulk	
getUserContext	
setUserContext	

Showing 1 to 1 of 1 Previous | Next

The WS-Policy files associated with the ConfigurationService are listed.

5. Click an Operation, say getDefault.

The Configure a Webservice Policy page to Configure the WS-Policy for the SOAP Message of an Operation appears.



6. Select the desired Operation Message Policies from the Available Message Policies box and move them to the Chosen Message Policies box.

7. Click Next.

The Configure a Webservice Policy page to Configure the WS-Policy for the Inbound SOAP Message of an Operation appears.

8. Select the desired Operation Message Policies from the Available Message Policies box and move them to the Chosen Inbound Message Policies box.

9. Click Next.

The Configure a Webservice Policy page to Configure the WS-Policy for the Outbound SOAP Message of an Operation appears.

10. Select the desired Operation Message Policies from the Available Message Policies box and move them to the Chosen Outbound Message Policies box.

11. Click Finish.

The Save Deployment Plan Assistant page appears.

12. Click OK to save the policies and return to the Settings for ConfigurationServices page.

Setting up the Web Services Security

- X.509 Authentication

For X.509 authentication, a Web Service Security Configuration must be configured.

Settings for e6base_domain

Configuration Monitoring Control Security **Web Service Security** Notes

This page lists the Web Service security configurations that have been created for this domain. Click on the security configuration name to update it, such as create new credential providers, new token handlers, or configure the timestamp properties.

Web Service Security Configurations

New Delete Showing 1 to 1 of 1 Previous | Next

<input type="checkbox"/>	Web Service Security Configuration Name ^
<input type="checkbox"/>	default_wss

New Delete Showing 1 to 1 of 1 Previous | Next

The WebLogic server provides default providers which can be used. In this example, clicking on the default Web Service default_wss opens the Settings for default_wss mask. On the Credential Provider tab, a number of available default providers are listed that have been created for the Web Service security configuration.

Settings for default_wss

General **Credential Provider** Token Handler Timestamp

This page lists the credential providers that have been created for the Web Service security configuration. Click on the credential provider name to modify its configuration and to add properties. Click New to create a new credential provider. To delete a credential provider, check the box next to its name and click Delete.

Credential Providers

New Delete Showing 1 to 2 of 2 Previous | Next

<input type="checkbox"/>	Credential Provider Name ^	Class Name	Token Type
<input type="checkbox"/>	default_dk_cp	weblogic.wsee.security.wssc.v200502.dk.DKCredentialProvider	dk
<input type="checkbox"/>	default_x509_cp	weblogic.wsee.security.bst.ServerBSTCredentialProvider	x509

New Delete Showing 1 to 2 of 2 Previous | Next

The x509 server certificate has to be stored in a Java keystore and can be configured as follows:

Settings for default_x509_cp

Configuration | Notes

Save

Use this page to configure a credential provider of a Web Service security configuration. In particular, you can change the classname that implements the credential provider, change the type of token, and add or delete properties of the credential provider.

Name: default_x509_cp The user-specified name of this MBean instance. [More Info...](#)

Class Name: weblogic.wsee.security The fully qualified name of the class that implements a particular credential provider or token handler. [More Info...](#)

Token Type: x509 Specifies the type of token used for the particular credential provider or token handler. [More Info...](#)

Save

[Customize this table](#)

Credential Provider Properties

New Delete Showing 1 to 8 of 8 Previous | Next

<input type="checkbox"/>	Name	Value	Is Encrypted
<input type="checkbox"/>	ConfidentialityKeyAlias	identity	false
<input type="checkbox"/>	ConfidentialityKeyPassword	*****	true
<input type="checkbox"/>	ConfidentialityKeyStore	C:\oracle\Middleware\sample_security_providers\ServerIdentity.jks	false
<input type="checkbox"/>	ConfidentialityKeyStorePassword	*****	true
<input type="checkbox"/>	IntegrityKeyAlias	identity	false
<input type="checkbox"/>	IntegrityKeyPassword	*****	true
<input type="checkbox"/>	IntegrityKeyStore	C:\oracle\Middleware\sample_security_providers\ServerIdentity.jks	false
<input type="checkbox"/>	IntegrityKeyStorePassword	*****	true

New Delete Showing 1 to 8 of 8 Previous | Next

Authenticating in a Web Service Client

The caller of an Agile e6 Web Service has to provide user credentials to gain access to the Agile e6 application. The attributes of these credentials depend on the used Web Service policy. The following is an example of an unauthenticated Web Service call:

```
<?xml version='1.0' encoding='UTF-8'?>
<S:Envelope xmlns:S="http://schemas.xmlsoap.org/soap/envelope/">
  <S:Body>
    <ns4:getVersion
xmlns:ns2="http://xmlns.oracle.com/Agile/e6/Metadata/v0"
xmlns:ns3="http://xmlns.oracle.com/Agile/e6/plm"
xmlns:ns4="http://xmlns.oracle.com/Agile/e6/HelloWorld/v0" />
  </S:Body>
</S:Envelope>
```

A Sample of HTTP Authentication

You can use the basic authentication of HTTP to secure a Web Service. With this basic authentication of HTTP, the user credentials are stored in the HTTP header. The SOAP message does not carry any security information.

Basic authentication without SSL should not be used in a production environment as the passwords and data are transferred in plain text. Ideally, HTTP/S should be configured.

For complete details on WebLogic Security Fundamentals and Transport Level Security, refer to the WebLogic documentation on OTN.

Here is a sample of basic HTTP authentication:

```
POST /agile-ws-e6/HelloWorldService HTTP/1.1
Authorization: Basic RURCQ1VTVE86T1RTVUNCREU=
SOAPAction: ""
Accept: text/xml, multipart/related, text/html, image/gif, image/jpeg,
*; q=.2, */*; q=.2
Content-Type: text/xml;charset="utf-8"
User-Agent: Oracle JAX-WS 2.1.4
Host: localhost:7002
Connection: keep-alive
Content-Length: 315

<?xml version='1.0' encoding='UTF-8'?>
<S:Envelope xmlns:S="http://schemas.xmlsoap.org/soap/envelope/">
  <S:Body>
    <ns4:getVersion
      xmlns:ns2="http://xmlns.oracle.com/Agile/e6/Metadata/v0"
      xmlns:ns3="http://xmlns.oracle.com/Agile/e6/plm"
      xmlns:ns4="http://xmlns.oracle.com/Agile/e6/HelloWorld/v0" />
  </S:Body>
</S:Envelope>
```

To add the HTTP basic authentication to a SOAP request, the code may look like the following example:

```
MetadataService service = new MetadataService(wsdlURL, serviceName);

BindingProvider bindingProvider = (BindingProvider) service.getPort();

bindingProvider.getRequestContext().put(BindingProvider.USERNAME_PROPERTY, username);
bindingProvider.getRequestContext().put(BindingProvider.PASSWORD_PROPERTY, password);
bindingProvider.getRequestContext().put(BindingProvider.SESSION_MAINTAIN_PROPERTY, Boolean.TRUE);
```

Note The last line in the example code given above configures HTTP session handling. If this code is not added, each Web Service call will create a new HTTP session which will lead to a new Agile e6 server instance starting up.

A Sample of Web Services Security

In the following example, a WS-Policy (Web Services policy) is used for the WSS: SOAP Message Security.

You are required to provide the username token and a client certificate. The complete security information is embedded into the SOAP message.

Note By configuring WSS: SOAP Message Security, the WSDL gets modified.

```
<?xml version='1.0' encoding='UTF-8'?>
<S:Envelope xmlns:S="http://schemas.xmlsoap.org/soap/envelope/">
  <S:Header>
    <wsse:Security xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
      S:mustUnderstand="1">
      <ns1:EncryptedKey
xmlns:ns1="http://www.w3.org/2001/04/xmlenc#" Id="JOLZ6aDu8pt9PRPe">
        <ns1:EncryptionMethod
Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-oaep-mgf1p">
          <ns2:DigestMethod
xmlns:ns2="http://www.w3.org/2000/09/xmldsig#"
Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
            </ns1:EncryptionMethod>
          <ns3:KeyInfo
xmlns:ns3="http://www.w3.org/2000/09/xmldsig#">
            <wsse:SecurityTokenReference
xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
wsu:Id="str_kNu7Vfo6pZLqdYcv">
              <X509Data
xmlns="http://www.w3.org/2000/09/xmldsig#">
                <X509IssuerSerial>
                  <X509IssuerName>CN=CertGenCAB, OU=FOR
TESTING ONLY, O=MyOrganization, L=MyTown, ST=MyState, C=US</X509IssuerName>
                  <X509SerialNumber>-
135694037818432800534509206009756866711</X509SerialNumber>
                </X509IssuerSerial>
              </X509Data>
            </wsse:SecurityTokenReference>
          </ns3:KeyInfo>
        <ns1:CipherData>
```

```

<ns1:CipherValue>JHUAfXjSBYxXKAGrpQ.....NUWGQ9IPL9M1uODqmnQ8Nlk=
</ns1:CipherValue>
  </ns1:CipherData>
  <ns1:ReferenceList>
    <ns1:DataReference URI="#PJr5jO7puKh50L5b" />
  </ns1:ReferenceList>
</ns1:EncryptedKey>
  <wsse:BinarySecurityToken xmlns:wsse="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
    xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
    EncodingType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-soap-message-security-
1.0#Base64Binary"
    ValueType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-1.0#X509v3"
    wsu:Id="bst_GpDR1niRFucsZsbm">MIICKzCc.....KMuSA1XAQ==</wsse:BinarySe
curityToken>
  <dsig:Signature
xmlns:dsig="http://www.w3.org/2000/09/xmldsig#">
    <dsig:SignedInfo>
      <dsig:CanonicalizationMethod
Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
      <dsig:SignatureMethod
Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
      <dsig:Reference URI="#Timestamp_KKvWCLdlrCRB2SNF">
        <dsig:Transforms>
          <dsig:Transform
Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
        </dsig:Transforms>
        <dsig:DigestMethod
Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <dsig:DigestValue>xndjH7PWB/yinv/uFzmElQzAezI=</dsig:DigestValue>
    </dsig:Reference>
    <dsig:Reference URI="#Body_0lUdcO0zqWY2bBvU">
      <dsig:Transforms>
        <dsig:Transform
Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
      </dsig:Transforms>
      <dsig:DigestMethod
Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
    <dsig:DigestValue>gt0av56Xh/gca30jxtDChJkFZck=</dsig:DigestValue>
  </dsig:Reference>
  <dsig:Reference URI="#unt_UROJpKRFSAlZLKff">
    <dsig:Transforms>
      <dsig:Transform
Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </dsig:Transforms>
    <dsig:DigestMethod
Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
  </dsig:Reference>

```

```

<dsig:DigestValue>QBSH0z6BxmZgEM56+g3ZS2w00lg=</dsig:DigestValue>
    </dsig:Reference>
    <dsig:Reference URI="#bst_GpDR1niRFucsZsbm">
        <dsig:Transforms>
            <dsig:Transform
Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
        </dsig:Transforms>
        <dsig:DigestMethod
Algorithm="http://www.w3.org/2000/09/xmlsig#sha1" />
    </dsig:Reference>
</dsig:SignedInfo>

<dsig:SignatureValue>TfFLyCR9MF4ZepqwmnCned7mj5TavfwjDg69.....MIFR3kB
U=</dsig:SignatureValue>
    <dsig:KeyInfo>
        <wsse:SecurityTokenReference
xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
wssecurity-secext-1.0.xsd"

xmlns:wsse11="http://docs.oasis-open.org/wss/oasis-wss-wssecurity-
secext-1.1.xsd"

xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
wssecurity-utility-1.0.xsd"

wsse11:TokenType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-
wss-x509-token-profile-1.0#X509v3"

wsu:Id="str_KVJy1AtKNAXVYsKq">
            <wsse:Reference URI="#bst_GpDR1niRFucsZsbm"
                ValueType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-1.0#X509v3" />
        </wsse:SecurityTokenReference>
    </dsig:KeyInfo>
</dsig:Signature>
    <ns1:EncryptedData
xmlns:ns1="http://www.w3.org/2001/04/xmlenc#" Encoding="UTF-8"
Id="PJr5jO7puKh5OL5b" MimeType="text/xml "

Type="http://www.w3.org/2001/04/xmlenc#Element">
        <ns1:EncryptionMethod
Algorithm="http://www.w3.org/2001/04/xmlenc#aes256-cbc" />
        <ns1:CipherData>

<ns1:CipherValue>yG4ULSKvJFL8.....OgqkcPmY6yhdpoE=</ns1:CipherValue>
        </ns1:CipherData>
        </ns1:EncryptedData>
        <wsu:Timestamp xmlns:wsu="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
            wsu:Id="Timestamp_KKvWCLdlrCRB2SNF">
            <wsu:Created>2010-02-03T14:44:31Z</wsu:Created>
            <wsu:Expires>2010-02-03T14:45:31Z</wsu:Expires>
        </wsu:Timestamp>
    </ns1:EncryptedData>
</ns1:EncryptedData>

```

```
        </wsu:Timestamp>
    </wsse:Security>
</S:Header>
    <S:Body xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-utility-1.0.xsd"
        wsu:Id="Body_01Udc00zqWY2bBvU">
        <ns4:hello
xmlns:ns2="http://xmlns.oracle.com/Agile/e6/Metadata/v0"
        xmlns:ns3="http://xmlns.oracle.com/Agile/e6/plm"

xmlns:ns4="http://xmlns.oracle.com/Agile/e6/HelloWorld/v0" />
    </S:Body>
</S:Envelope>
```

In the following example, WSS: SOAP Message Security information is provided for the SOAP request:

```
MetadataService service = new MetadataService(wsdlURL, serviceQName);
BindingProvider bindingProvider = (BindingProvider) service.getPort();
List<CredentialProvider> credProviders = new
ArrayList<CredentialProvider>();
try {
    // Load server certificate
    X509Certificate serverCert =
(X509Certificate) CertUtils.getCertificate(serverCertFile);

    // Check server certificate
    serverCert.checkValidity();

    // Create a new certificate credential provider
    CredentialProvider cp = new
ClientBSTCredentialProvider(clientKeyStore,
        clientKeyStorePass, clientKeyAlias, clientKeyPass,
"JKS", serverCert);

    // Add certificate credential provider to the array list
    credProviders.add(cp);

    // Create a new username token credential provider
    CredentialProvider up = new
ClientUNTCredentialProvider(username.getBytes(), password.getBytes());

    // Add certificate username token credential provider to the array
list
    credProviders.add(up);

    Map<String, Object> rc =
((BindingProvider)portName).getRequestContext();

    // Add the credential providers to the request context
    rc.put(WSSecurityContext.CREDENTIAL_PROVIDER_LIST, credProviders);
```

```
// Add a trust manager to the request context, you can do here some
validation tests on the return certificate of the SOAP message
rc.put(WSSecurityContext.TRUST_MANAGER,
        new TrustManager() {
            public boolean
certificateCallback(X509Certificate[] chain, int validateErr){
                return true;
            }
        } );
} catch (Exception e) {
    log.printStackTrace(e);}
```


Working with Agile e6 Web Services

Bulk Processing of Requests

Most of the Agile e6 Web Service operations support bulk processing of requests. The operations with one request input object and one response output object can be configured to process multiple or bulk requests and corresponding responses.

Handling the Bulk Requests

A bulk request contains a list of requests for the non-bulk operation. These requests are executed one by one, and each response is stored in the result list of the bulk response object. All requests contained in the bulk request list are executed in sequence using the order of the list. The bulk requests can be configured to either stop on the first failure, or to continue regardless of a failing request.

If a request fails with a response FAILURE, the loop will be aborted if the stopOnFailure member of the bulk request is set. If stopOnFailure is not requested, the status of the bulk response is set to PARTIAL_SUCCESS. This requires you to look into each response in the list to check the individual status.

However, if a request fails with a PlmFault (or any other exception), the bulk processing is aborted and the list of requests processed until the fault occurred is returned. Additionally, the causing fault is returned in the bulk response.

If the bulk request does not contain any request, a WARNING response is returned.

The content of the response object depends on the status code, as listed below:

SUCCESS	A list with all response objects matching the list of requests. All requests succeeded.
FAILURE	A list with all response objects matching the list of requests. One or more requests failed, check the respective responses. The last executed request failed with an exception, which is returned as the fault in the bulk response. If one request fails due to lack of mask in White-list, status code would be FAILURE instead of PARTIAL_SUCCESS even if other services should be successful.
WARNING	The bulk request does not contain any request.
PARTIAL_SUCCESS	A list with all response objects matching the list of requests. One or more requests failed, check the respective responses. If stopOnFailure was requested, the list ends with the first response that failed.

Developing the Outbound Web Services Wrapper

The Web Services Wrapper Interface

Each wrapper has to implement the `WebServiceWrapper` interface, which prescribes the following method:

```
StringList callWebService(WrapperContext context, CallableParam args)
```

The context contains all relevant information for the wrapper to perform the call. The wrapper then transforms the arguments to an XML payload for the outbound Web Service and finally makes the call.


If it is an asynchronous Web Service, the wrapper returns a string list with the correlation ID. Otherwise, it transforms the XML payload returned by the Web Service into a string list that is expected by the calling Agile e6 server process.

In case the wrapper is implemented in BPEL (or in any other external Web Service language), you require a special wrapper called the *ExternalWrapper*. This wrapper delegates the call to the respective external Web Service wrapper.

The BPEL Facade

For the outbound calls, you are required to use the *ExternalWrapper* to call an external Web Service or a BPEL process. However, you need to first implement an interface to adapt the External Wrapper. This interface is called as BPEL facade.

Normally, this facade should be a BPEL process that you implement. In this facade, you can invoke an external Web Service or BPEL process and create their business logic. All the facades should implement a standard WSDL. The External wrapper uses this standard WSDL to generate the proxy. Then it can use different endpoints to call different BPEL facades.



Endpoint Configurations for the External Wrapper

All the endpoints for the External wrapper are defined in the properties file `ExternalWrapper.properties`. This file resides in the `APP-INF/classes` directory alongside the `application.properties` file for the Web Services.

Example:

```
bpel.wrapper.SampleExternalService2.wsdl=http://<server><port>/soa-  
infra/services/default/SOAComposite2/BPELFacadeService?WSDL
```

In the above example, when we pass the service name as `SampleExternalService2` in `xutil_call_ws`, the wrapper manager first looks for an internal wrapper named as `SampleExternalService2`. If this internal wrapper does not exist, then the wrapper manager calls the external wrapper and gets the endpoint with the key value `bpel.wrapper.SampleExternalService2.wsdl` in the `ExternalWrapper.properties` file.

Note You are required to use the custom staging mechanism of the Agile e6 Installer to add your own mappings to the `ExternalWrapper.properties` file.

Session Management Integration

In the `ExternalWrapper`, the user name & ticket should be passed to the BPEL façade. The BPEL facade uses this information to invoke the Agile e6 core Web Services and reconnect to the same Agile e6 PLM session to get more data.

Developing a Custom Wrapper

In order to compile a custom wrapper, you need the libraries contained in the Web Services application. These libraries can be found at `${ep_root}/staging/product/WebServices/WebServices.ear/APP-INF/lib`.

If your wrapper calls an external or internal Web Service, you also need to add the generated client classes or any other infrastructure classes needed. This depends on the Web Service client framework that you use.

<p>Important It is highly recommended to use the WebLogic Web Service framework when implementing a wrapper for a Web Service because the wrapper is runs inside WebLogic.</p>

The name of the wrapper class should be `<ID>Wrapper`, as the wrapper manager looks for this string when the Agile e6 server tries to call it.

The imports used by the wrapper are in the libraries contained in the `lib` directory inside the `WebServices.ear` file (at `APP-INF/lib`). By default, the wrapper class should be in the package `com.agile.ws.e6.wrappers` so that the wrapper manager can find it at the runtime. However, it is also possible to add other package names to the search path by adding them to the `application.properties` file of the Web Services application:

```
WrapperPackage.Custom.1 = some.custom.wrapperpackage
```

```
WrapperPackage.Custom.2 = another.custom.wrapperpackage
```

Example: EchoServiceWrapper.java

This wrapper does not call an outbound Web Service. It returns the arguments that have been passed. This wrapper is already contained inside the Web Services application and can be used to test the infrastructure.

```
/*
 * $Id: EchoServiceWrapper.java,v 1.3 2010/10/15 15:11:56 brg Exp $
 *
 * Copyright (c) 1992, 2010, Oracle. All rights reserved.
 */
package com.agile.ws.e6.wrappers;

import com.agile.eci.EciConnection;
import com.agile.eci.EciPar;
import com.agile.eci.EciParBuffer;
import com.agile.share.callable.CallableParam;
import com.agile.share.trace.Logger;
import com.agile.share.trace.Trace;
import com.agile.share.util.StringArray;
import com.agile.share.util.StringList;
import com.agile.ws.e6.PlmSession;
import com.agile.ws.e6.wrappersupport.WrapperContext;

import java.net.InetAddress;

/**
 * A simple echo wrapper to test the wrapper mechanism.
 */
public class EchoServiceWrapper extends AbstractWrapper {

    private static Logger log =
Trace.getLogger(EchoServiceWrapper.class);

    /**
     * The name of this service wrapper.
     */
    public static final String NAME =
EchoServiceWrapper.class.getSimpleName();

    /**
     * Creates a new echo service.
     */
    public EchoServiceWrapper() {
        super(NAME);
    }

    /** {@inheritDoc} */
```

```
@Override
public StringList callWebService(WrapperContext context,
CallableParam args) {

    log.enter("callWebService", "context="+context+", args="+args);
    PlmSession session = null;
    String userName = "<unknown>";
    String processId = "<unknown>";

    try {
        session = createPlmSession(context);
        EciConnection con = session.getConnection();

        EciPar par = con.call("eci_rea_edb_usr");

        userName = par.get(1);
        log.info("My name is " + userName + ", " +
            "\nI belong to the group " + par.get(2) +
            ".\nMy user ID is " + par.get(3) + ", " +
            "\nmy group ID is " + par.get(4) +
            "\nand I am " + ("y".equals(par.get(5)) ? "" : "not ") +
"a manager" +
            ".\n" +
            "\nOur session is " + session + ".\n");

        par = con.call("eci_get_pid");
        processId = par.get(1);

        EciParBuffer buf = new EciParBuffer();
        buf.add("EDB-BAS-WARNING");
        buf.addNew("This is the e6 EchoService running inside WebLogic
on host " +
            InetAddress.getLocalHost().getHostName() + "\n\n" +
            "You are " + userName + " and your process ID is " +
processId);
        buf.end();
        con.call("eci_mes_wri", buf);
    }
    catch (Exception e) {
        log.error("Unable to reconnect to e6: ", e);
    }
    finally {
        if (session != null) {
            session.close();
        }
    }
    StringList result = new StringArray(args.getParam());
    log.leave("callWebService", "result=" + result);
    return result;
}
}
```

Example: SampleWrapper.java

This wrapper calls an Agile e6 core service as an example. The generated client code needed to call the Agile e6 core service is not included. The generated classes belong to the wrapper and need to be deployed along with it.

The SampleWrapper class needs a property file, SampleWrapper.properties, which contains the URL of the Web Service.

When Agile e6 application wants to call a wrapper called Sample, it will pass Sample as the first argument to `xutil_call_ws`. The wrapper manager will then look for a class called SampleWrapper in all the packages in its search path. To call the EchoServiceWrapper, pass EchoService to `xutil_call_ws`.

```
/*
 * $Id: SampleWrapper.java,v 1.1.2.2 2011/06/30 15:53:27 brg Exp $
 *
 * Copyright (c) 1992, 2011, Oracle. All rights reserved.
 */

package com.agile.ws.e6.wrappers;

import com.agile.eci.EciConnection;
import com.agile.eci.EciPar;
import com.agile.eci.EciParBuffer;
import com.agile.security.tickets.plm.PlmTicket;
import com.agile.share.callable.CallableException;
import com.agile.share.callable.CallableParam;
import com.agile.share.trace.Logger;
import com.agile.share.trace.Trace;
import com.agile.share.util.StringArray;
import com.agile.share.util.StringList;
import com.agile.ws.e6.PlmSession;
import com.agile.ws.e6.WebServiceEnum;
import com.agile.ws.e6.client.core.common.PlmUserContext;
import com.agile.ws.e6.client.core.common.PlmUserContextUserInfo;
import com.agile.ws.e6.client.core.configuration.Configuration;
import com.agile.ws.e6.client.core.configuration.ConfigurationService;
import
com.agile.ws.e6.client.core.configuration.GetUserContextRequestType;
import
com.agile.ws.e6.client.core.configuration.GetUserContextResponseType;
import com.agile.ws.e6.wrappersupport.WrapperContext;

import java.net.InetAddress;
import java.net.MalformedURLException;
import java.net.URL;
import java.net.UnknownHostException;
import java.util.Properties;
```

```
import javax.xml.namespace.QName;
import javax.xml.ws.BindingProvider;

/**
 * A simple example of a wrapper for an out-bound web service call.
 *
 * <p>It extends the abstract wrapper implementation, which is shipped
 * in the library agile-ws-e6-callables as part of the WebServices.ear
 * file.
 *
 * <p>At the customer site, the new wrapper classes need to be put into
 * the
 * agile-custom shared library, which is referenced by the WebServices
 * application.
 *
 * <p>Alternatively, a JAR file containing the wrapper can be added to
 * the
 * WebServices application into the APP_INF/lib directory,
 * so that it is deployed as part of the WebServices application.
 */
public class SampleWrapper extends AbstractWrapper {
    /** The Logger used to print trace messages */
    private static Logger log = Trace.getLogger(SampleWrapper.class);

    /** The name of our properties file */
    private static final String SAMPLE_PROPERTIES =
"SampleWrapper.properties";
    /** Property containing the URL of the external web service */
    private static final String PROP_ENDPOINT = "Sample.endPoint";

    /**
     * The service we want to contact.
     *
     * <p>This class - and all the others in the package
     com.agile.ws.e6.client.core - is
     * generated by the WebLogic clientgen Ant task.
     */
    private ConfigurationService configurationService;
    /** The URL to the Configuration service */
    private String configurationEndPoint;

    /**
     * The name of this service wrapper.
     */
    public static final String NAME = "Sample";

    /**
     * Creates a new HelloWorld service.
     */
    public SampleWrapper() {
        super(NAME);
    }
}
```

```
    }

    /**
     * @return the RCS information of this object's class (polymorphic)
     */
    @Override
    public final String getRCSId() {
        return getClassRCSId();
    }

    /**
     * @return the RCS information of this class (static)
     */
    public static String getClassRCSId() {
        return "$Id: SampleWrapper.java,v 1.1.2.2 2011/06/30 15:53:27 brg
Exp $";
    }

    /**
     * Creates the port to access the Configuration service.
     *
     * @param endPoint the WSDL URL of the service.
     * @param ticket the PLM ticket provided by the e6 server
     *
     * @return the port to call the Configuration service
     */
    private Configuration getConfigurationPort(PlmTicket ticket) throws
MalformedURLException {
        if (configurationService == null) {
            configurationService = new ConfigurationService(
                new URL(configurationEndPoint),
                new QName(WebServiceEnum.CONFIGURATION.getNamespace(),
WebServiceEnum.CONFIGURATION.getServiceName()));
        }

        Configuration port = configurationService.getConfigurationPort();

        BindingProvider binding = (BindingProvider) port;

        // Add authentication, we have a ticket so we do not need the
password

        binding.getRequestContext().put(BindingProvider.USERNAME_PROPERTY,
ticket.getUserName());

        binding.getRequestContext().put(BindingProvider.PASSWORD_PROPERTY,
String.valueOf(ticket.getRawTicket()));

        // Maintain the HTTP session, in case we do several calls to the
server
    }
}
```

```
binding.getRequestContext().put(BindingProvider.SESSION_MAINTAIN_PROPER
TY, Boolean.TRUE);

    return port;
}

/**
 * Calls the web service.
 *
 * @param context the context that contains the reference to the e6
server
 * @param args arguments passed by the e6 server
 * @return list of return values, or null
 *
 * @throws CallableException Web service call failed
 */
@Override
public final StringList callWebService(final WrapperContext context,
final CallableParam args) throws CallableException {
    log.enter("callWebService", "context="+context+", args="+args);

    // Try to load our properties
    Properties sampleProps = new Properties();

    try {
        sampleProps.load(getClass().getResourceAsStream("/" +
SAMPLE_PROPERTIES));
        configurationEndPoint =
sampleProps.getProperty(PROP_ENDPOINT);
    }
    catch (Exception e) {
        String msg = "Unable to load SampleWrapper.properties";
        log.error(msg, e);
        throw new CallableException(this, msg);
    }
    if (configurationEndPoint == null) {
        log.error("No WSDL URL found in " + SAMPLE_PROPERTIES);
        throw new CallableException(this, "No web service URL
configured for the Sample wrapper");
    }

    log.info("Using WSDL at " + configurationEndPoint);

    Configuration port = null;
    StringList result = new StringArray();

    try {
        // Create a session object:
        //
```

```
        // It gives us access to an ECI connection to the same e6
server instance that called us,
        // and - if needed - it will create an AxalantRepository
instance for us,
        // if we want to make use of the high level Java ECI (JET
layer).
        PlmSession session = createPlmSession(context);

        // First some ECI calls
        callEciDemo(session);

        // Now the "external" web service call.
        //
        // Here, we would normally call an external service of another
system,
        // but for demo purposes, we just call an e6 Core service.
        port = getConfigurationPort(context.getPlmTicket());
        log.info("Port created with PLM ticket");

        GetUserContextRequestType request = new
GetUserContextRequestType();
        GetUserContextResponseType response =
port.getUserContext(request);
        log.info("Web method getUserContext() returned with status
code " + response.getStatusCode());

        PlmUserContext e6Context = response.getPlmUserContext();
        PlmUserContextUserInfo userInfo = e6Context.getPlmUserInfo();

        result.add("User name = " + userInfo.getUserName());
        result.add("Group name = " + userInfo.getGroup());
        result.add("Language = " + userInfo.getUserLanguage());
        result.add("Locale = " + userInfo.getUserLocale());

    }
    catch (Exception e) {
        log.error("Unable to call web service", e);
        throw new CallableException(this, "Web service call failed",
e);
    }
    finally {
        if (port != null) {
            try {
                // Tell the server that we no longer need the e6
session.
                port.closeSession();
            }
            catch (Exception e) {
                log.error("Unable to close port", e);
            }
        }
    }
}
```

```

        return result;
    }

    /**
     * Calls some ECI functions to demonstrate how to get additional
     data.
     *
     * @param session the e6 PLM session
     */
    private void callEciDemo(PlmSession session) {
        String userName = null;
        String processId = null;
        String host;

        try {
            host = InetAddress.getLocalHost().getHostName();
        }
        catch (UnknownHostException e) {
            host = "unknown host";
        }

        EciConnection con = session.getConnection();

        EciPar par = con.call("eci_rea_edb_usr");

        userName = par.get(1);
        log.info("My name is " + userName + "," +
            "\nI belong to the group " + par.get(2) +
            ".\nMy user ID is " + par.get(3) + "," +
            "\nmy group ID is " + par.get(4) +
            "\nand I am " + ("y".equals(par.get(5)) ? "" : "not ") + "a
manager" +
            ".\n" +
            "\nOur session is " + session + ".\n");

        par = con.call("eci_get_pid");
        processId = par.get(1);

        EciParBuffer buf = new EciParBuffer();
        buf.add("EDB-BAS-WARNING");
        buf.addNew("This is the e6 SampleWrapper running inside WebLogic
on host " +
            host + "\n\n" +
            "You are " + userName + " and your process ID is " +
processId);
        buf.end();
        // Prints a message on the client that contacted us
        con.call("eci_mes_wri", buf);
    }
}

```

Calling a Custom Wrapper from Agile e6

A new C/C++ userexit is needed that can be called from LogiView or C/C++ to make an outbound Web Service call. The request is sent as an ECI call to the ECI server embedded in the application server, which then calls the respective wrapper for XML processing.

To limit any XML parsing in LogiView and C/C++, the userexit sends a string containing a userexit parameter as an input to the wrapper and it expects a list of string as a result from the wrapper.

The userexit accepts an input argument that uses the syntax prescribed by CallableParam and zag_cnv_arg. This argument is passed to the ECI callable Eci_call WebService in the application server.

This userexit is called xutil_call_ws and can be used in LogiView as follows:

```

EP_APP_CMD = "EchoService"
EP_APP_CID_STRING = ""
EP_APP_CONTENTS = "Please echo: something"
RES = #xutil_call_ws(EP_APP_CMD, EP_APP_CID_STRING, EP_APP_CONTENTS,
EP_APP_RESULT, EP_APP_ERROR)
if (RES == 0)
put(strprint("Web service %s returned: %s", EP_APP_CMD, EP_APP_RESULT))
else
put(strprint("Error %d when calling web service %s, error message
is:\n%s", RES, EP_APP_CMD, EP_APP_ERROR))
endif

```

This LogiView code uses four existing string variables and two new ones to call the wrapper for the EchoService. The EchoService returns the input arguments as a result, which is provided as a standard wrapper to test the infrastructure.

The userexit xutil_call_ws consists of the following parameters:

EP_APP_CMD	Wrapper Name
EP_APP_CID_STRING	Correlation ID. This is used to correlate a later response, which may come in asynchronously, to the initiating request.
EP_APP_CONTENTS	Any string value that the wrapper should interpret.
RES	Result string from the Wrapper
EP_APP_RESULT	A new string variable that needs to be created to call the wrapper for the EchoService.
EP_APP_ERROR	A new string variable that needs to be created to call the wrapper for the EchoService.
The userexit provides a return code - "0" for success and any other number for errors.	

Deploying a Custom Wrapper

1. Identify the classes you need for your wrapper and create a JAR file containing them. Give your JAR files proper names to avoid naming conflicts with existing wrapper implementations.

For example, use a unique prefix that identifies your company.

2. If you need third party JAR files, ensure that they are not already provided by WebLogic server or the Agile e6 Web Services application. Do not use JAR files that duplicate features or come in conflict with the WebLogic server, like using different Web Service client frameworks.

Be aware that your wrapper implementation will run inside and as part of a Web Service application deployed into WebLogic server.

3. Copy all JAR files needed by your wrapper implementation to the custom staging directory for the Web Services application. This should be:

```
${ep_root}/staging/custom/WebServices/${app_name}.ear/APP-INF/lib.
```

Note Do not copy any library that is already part of the Web Services application into the custom staging area. These libraries are only replaced by updates from Oracle, and are always put in the product staging area.

4. Redeploy the Web Services into the WebLogic server.

See the *Agile e6 Administration Manual* or the *Hotfix Readme* for complete details on how to deploy an application.

Web Service Wrapper Log Messages

A log file looks similar to the one shown below, depending on what has been implemented in the Java based Wrapper for message logging.

```

INFO 2010-09-27 13:51:30.465 [pool-70-thread-1 - JpcServerRunnable] - [EciServer$EciServerRunnable@1dc2b7bd] Entering function callWebService
INFO 2010-09-27 13:51:30.526 [pool-70-thread-1 - JpcServerRunnable] - [Eci_callWebService@1de124bb] Calling web service EchoService [correlationId=42] with [-arg:Hello
Service!-/arg->-arg:88006-/arg->]
INFO 2010-09-27 13:51:30.545 [pool-70-thread-1 - JpcServerRunnable] - [AbstractWrapper] No wrapper properties found
INFO 2010-09-27 13:51:30.552 [pool-70-thread-1 - JpcServerRunnable] - [AbstractWrapper] Connecting back to e6 using ticket: PLM-
TICKET:3tv11QsijwTAEgICAgICAgCAxADeYODU1ODpyOTAAlCAgICAgODU4MgAgICAgICAgCA4AEVEOkIVU1RPICAgICAgICAgMwAvMjc1NTowNDY0Mjc3ICAgICAgDE3MgBNI
WdEMG4VWlktZG1nRlM0OXk5bXk1WFQwVXNlSlp0k1HcVfVNU3fTdnIVT0dtUnVtMlVlREI2enYrbVvIQVfHfMkxGNXhYcOh5Y1jMSjFXRfVRzZhMzdjRGE1VGdUZXJSanZuUmJSO
UH8WHIKK2kwTmY5bnh1dTI0S1puWzIipZk2IijA0N18SVfPzFRKk1Zx5VvaYndTys2RvhwjNsektYwkiBdg2RYIE9
INFO 2010-09-27 13:51:30.696 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Entering eci_get_cer
INFO 2010-09-27 13:51:30.710 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Leaving call to eci_get_cer
INFO 2010-09-27 13:51:30.726 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Entering eci_chk_pwd
INFO 2010-09-27 13:51:30.772 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Leaving call to eci_chk_pwd
INFO 2010-09-27 13:51:30.775 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Entering eci_rea_edb_usr
INFO 2010-09-27 13:51:30.775 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Leaving call to eci_rea_edb_usr
INFO 2010-09-27 13:51:30.777 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Entering eci_set_enc
INFO 2010-09-27 13:51:30.777 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Leaving call to eci_set_enc
INFO 2010-09-27 13:51:30.778 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Entering eci_rea_edb_usr
INFO 2010-09-27 13:51:30.779 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Leaving call to eci_rea_edb_usr
INFO 2010-09-27 13:51:30.779 [pool-70-thread-1 - JpcServerRunnable] - [EchoServiceWrapper] My name is EDBCUSTO.

I belong to the group EDB.
My user ID is 101.
my group ID is 100
and I am a manager.

Our session is com.arite.ws.e6.impl.PlmSessionImpl@1e05ae16.
INFO 2010-09-27 13:51:30.779 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Entering eci_get_pid
INFO 2010-09-27 13:51:30.780 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Leaving call to eci_get_pid
INFO 2010-09-27 13:51:30.780 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Entering eci_mes_wri
INFO 2010-09-27 13:53:36.617 [pool-70-thread-1 - JpcServerRunnable] - [EciClient@1e044ef1] Leaving call to eci_mes_wri
INFO 2010-09-27 13:53:36.634 [pool-70-thread-1 - JpcServerRunnable] - [EciServer$EciServerRunnable@1dc2b7bd] Leaving function callWebService
INFO 2010-09-27 13:53:36.636 [pool-70-thread-1] - [EciServer$EciServerRunnable@1dc2b7bd] Entering function end

```

Agile e6 Core Web Services Operations

This section describes the Agile e6 Core Web Services Operations. The use of these operations to process the bulk requests is described in section Bulk Processing of Requests.

Some of the operations, such as `getRelations`, require counting the number of records. For more information on these, refer to Counting the Objects in this document.

For additional information on these Web Services and operations, refer to the documentations in the zip files:

- Agile e6.2.2 Web Services Schema Documentation (including the PLM Data Types document)
- Agile e6.2.2. Web Services SOAP Samples

Business Object Web Services

The Business Object Web Services enable you to create and retrieve Agile e6 PLM objects belonging to an entity, an entity type and a relation.

All operations require one Request object as input and return one Response object.

- The request contains attribute values used to search or create a PLM object.
- The response contains the data of the respective objects.
- Bulk operations allow you to execute a whole list of requests with a single Web Service call. The response of a bulk operation contains a list of responses matching the list of requests.

The PLM objects are read from the Agile e6 application using the mask specified in the request. It is only possible to access PLM attributes that are visible in this mask, with the exception of the ID fields `EDB_ID` and `C_ID`. Only the masks listed in the Web Service White List of the Agile e6 application can be accessed.

- Use the `EDB_ID` if you need to keep the reference to a PLM object, especially if it is stored in another system.
- The `C_ID` should only be used to build internal object graphs, for instance when filling a UI element.

Note Not all PLM objects have an `EDB_ID` or a `C_ID`. Check the customization of the respective Agile e6 system before deciding how to make external references to PLM objects of that system.

All operations allow you to specify the attributes that you require to return from the PLM object. If no return attributes are specified, all the accessible attributes are returned, which corresponds to all visible fields of the mask. Optionally, all languages of multi-language attributes can be returned. Be aware that this may result in a considerably larger response object.

Binary Data Transfer

It is possible to request the transfer of binary data (BLOBs), however, by default, binary data is not transmitted. Be aware that the binary attributes to transfer need to be visible in the underlying Agile e6 mask. BLOBs are transferred using the MTOM feature of JAX-WS.

Bulk Operations

The following are the bulk operation names of the single request operations for Business Object Web Services described the concurrent sections. See [Processing the Bulk Requests](#) for complete details on how to handle the bulk operations.

- createObjectBulk
- getObjectBulk
- createRelationBulk
- getRelationsBulk
- updateObjectBulk

createObject

Service	To create a new object in the Agile e6 application.
Usage	<p>The request object contains the Class name and an optional list of attribute names. On success, the response object returns the newly created object name including all its attributes defined in Agile e6.</p> <p>Only existing and visible attributes are returned.</p> <p>If the object already exists in Agile e6, or an error occurs during the creation of the object, an error message will be returned.</p>
Request Type	<p>CreateObjectRequestType</p> <ul style="list-style-type: none"> ▫ messageId (String): ID to be returned in the response (optional) ▫ messageName (String) : Name to be returned in the response (optional) ▫ plmObject: The PLM class reference and a list of object attributes (name/value pairs) used to create the new object. <ul style="list-style-type: none"> ▫The metadata of the plmObject is currently ignored by this operation, so you can pass empty values for these elements. ▫Only the list of attribute values is used to fill the new record in Agile e6. ▫ plmResult: This describes how the result of the operation is returned to the client.

	attributeNames (Boolean)	List of field names to be returned	<ul style="list-style-type: none"> ▫ Optional ▫ Default <ul style="list-style-type: none"> ▫ All visible fields and ID fields 						
	includeBinaryValues (Boolean)	Include binary values?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 						
	includeAllLanguages (Boolean)	Include all languages?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 						
Request Type	<p>CreateObjectResponseType</p> <ul style="list-style-type: none"> ▫ statusCode (ResponseStatusCode): <table border="1"> <tr> <td>SUCCESS</td> <td>The new created PLM object including all attributes defined by the PLM result of the request</td> </tr> <tr> <td>PARTIAL_SUCCESS</td> <td>The new created PLM object including some of the attributes defined by the PlmResult of the request</td> </tr> <tr> <td>FAILURE</td> <td>A fault description including error message and kind of error</td> </tr> </table> <ul style="list-style-type: none"> ▫ ticket (String) : A PLM ticket. <ul style="list-style-type: none"> ▫ The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫ The ticket is only valid for the PLM server instance that generated it. ▫ messageId (String): copied from the request, or generated. ▫ messageName (String): copied from the request, or the operation name. ▫ warnings: List of warnings (PlmWarningType) that occurred during the operation. ▫ exceptions: List of exceptions (PlmExceptionType) that occurred during the operation. ▫ object (PlmObject): the object created by this operation. ▫ It contains the attributes requested in the PlmResult, or all visible attributes if no attributes have been requested. 			SUCCESS	The new created PLM object including all attributes defined by the PLM result of the request	PARTIAL_SUCCESS	The new created PLM object including some of the attributes defined by the PlmResult of the request	FAILURE	A fault description including error message and kind of error
SUCCESS	The new created PLM object including all attributes defined by the PLM result of the request								
PARTIAL_SUCCESS	The new created PLM object including some of the attributes defined by the PlmResult of the request								
FAILURE	A fault description including error message and kind of error								

getObject

Service	To retrieve the requested PLM objects from Agile e6 application.
Usage	<p>It executes a query on the Agile e6 application and returns the matching objects. The operation will use the mask that is specified in the request to retrieve the data (search in mask).</p> <p>Response information can be restricted by defining the list of fields that should be returned. Be aware that you can get the values only for fields that are available in the mask.</p> <p>The sorting of data determines the settings of the mask.</p> <p>Date values are returned in UTC, based on the assumption that the data returned by the PLM server is in Server Local Time.</p>

	<p>By default, only the current language value will be retrieved for multi-language fields. However the Web Service client can request to retrieve all language values in the same call. The request member <i>plmQuery</i> controls this behavior, along with other settings that need to be described.</p> <p><i>PlmQuery</i> extends <i>PlmResult</i>, which provides the flag "<i>includeAllLanguages</i> (boolean, optional)". This flag indicates if all languages of multi-language fields should be returned, or just the current language of the session.</p> <p>The <i>countOnly</i> flag of the request is very important here. For more information on this, refer to Counting the Objects in this document.</p>															
Request Type	<p>GetObjectsRequestType</p> <ul style="list-style-type: none"> ▫ <i>messageId</i> (String): ID to be returned in the response (optional) ▫ <i>messageName</i> (String) : Name to be returned in the response (optional) ▫ <i>plmQuery</i> (PlmQuery): ▫ <i>plmClass</i>: The object type as a PlmClassRef (PLM class reference, as provided by the Metadata service). ▫ <i>selection</i>: A list of PlmCondition objects representing the search criteria for object attributes. <table border="1" data-bbox="488 852 1409 1350"> <tr> <td><i>ignoreRecordLimit</i> (Boolean)</td> <td>Ignore the record limit?</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False </td> </tr> <tr> <td><i>countOnly</i> (Boolean)</td> <td>Count only?</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False </td> </tr> <tr> <td><i>attributeNames</i> (Boolean)</td> <td>List of field names to be returned</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default ▫ All visible fields and ID fields </td> </tr> <tr> <td><i>includeBinaryValues</i> (Boolean)</td> <td>Include binary values?</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False </td> </tr> <tr> <td><i>includeAllLanguages</i> (Boolean)</td> <td>Include all languages?</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False </td> </tr> </table>	<i>ignoreRecordLimit</i> (Boolean)	Ignore the record limit?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 	<i>countOnly</i> (Boolean)	Count only?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 	<i>attributeNames</i> (Boolean)	List of field names to be returned	<ul style="list-style-type: none"> ▫ Optional ▫ Default ▫ All visible fields and ID fields 	<i>includeBinaryValues</i> (Boolean)	Include binary values?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 	<i>includeAllLanguages</i> (Boolean)	Include all languages?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False
<i>ignoreRecordLimit</i> (Boolean)	Ignore the record limit?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 														
<i>countOnly</i> (Boolean)	Count only?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 														
<i>attributeNames</i> (Boolean)	List of field names to be returned	<ul style="list-style-type: none"> ▫ Optional ▫ Default ▫ All visible fields and ID fields 														
<i>includeBinaryValues</i> (Boolean)	Include binary values?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 														
<i>includeAllLanguages</i> (Boolean)	Include all languages?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 														
Response Type	<p>GetObjectsResponseType</p> <ul style="list-style-type: none"> ▫ <i>statusCode</i> (ResponseStatusCode): <table border="1" data-bbox="488 1451 1409 1728"> <tr> <td>SUCCESS</td> <td>The query was executed without any problem. The list of objects might be empty.</td> </tr> <tr> <td>PARTIAL_SUCCESS</td> <td>One or more attributes, defined by the PlmResult of the request, were not found in the queried objects. Details can be found in the list of warnings (see below)</td> </tr> <tr> <td>FAILURE</td> <td>A fault description including error message and kind of error.</td> </tr> </table> <ul style="list-style-type: none"> ▫ <i>ticket</i> (String) : A PLM ticket. <ul style="list-style-type: none"> ▫ The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a 	SUCCESS	The query was executed without any problem. The list of objects might be empty.	PARTIAL_SUCCESS	One or more attributes, defined by the PlmResult of the request, were not found in the queried objects. Details can be found in the list of warnings (see below)	FAILURE	A fault description including error message and kind of error.									
SUCCESS	The query was executed without any problem. The list of objects might be empty.															
PARTIAL_SUCCESS	One or more attributes, defined by the PlmResult of the request, were not found in the queried objects. Details can be found in the list of warnings (see below)															
FAILURE	A fault description including error message and kind of error.															

	<p>backward flow - if there is no HTTP session.</p> <ul style="list-style-type: none"> ▫ The ticket is only valid for the PLM server instance that generated it. ▫ messageId (String): copied from the request, or generated. ▫ messageName (String): copied from the request, or the operation name. ▫ warnings: List of warnings (PlmWarningType) that occurred during the operation. ▫ exceptions: List of exceptions (PlmExceptionType) that occurred during the operation. ▫ recordLimitHit (Boolean) : Indicates whether the query result has hit the mask limit. ▫ objects: List of objects (PlmObject) found including all the object attribute values listed in the PlmResult of the request <p>▫ If a count request was made, the response will have one PlmObject with an Integer attribute named COUNT containing the number of objects matching the query, and an Integer attribute called RECORD_LIMIT containing the current record limit of the mask used for the count operation.</p>
--	---

createRelation

Service	To create a relation between two PLM objects.					
Usage	It returns the data of the new relation object. The request object queries for the parent object, the query for the child object and the metadata that defines the relation type. The request must contain the object type, i.e. a PLM class reference.					
Request Type	<p>CreateRelationRequestType</p> <ul style="list-style-type: none"> ▫ messageId (String): ID to be returned in the response (optional) ▫ messageName (String) : Name to be returned in the response (optional) ▫ relationObject (PlmObject): the relation Object with the PLM class reference and a list of relationship attributes (name/value pairs) used to create the new object. . ▫ The meta data of the relationObject is currently ignored by this operation, so you can pass empty values for these elements. ▫ Only the list of attribute values is used to fill the new relation record in Agile e6. ▫ parent (PlmObjectRef): object reference : This is either a PlmObject as returned by the BusinessService.getObjects operation, or a PlmObjectReference containing the query for the record, ▫ child (PlmObjectRef): as object reference : This is either a PlmObject as returned by the BusinessService.getObjects operation, or a PlmObjectReference containing the query for the record, ▫ relation (PlmMetaRelation): a relationship meta data: This is a PlmMetaRelation as returned by the MetadataService.getRelation operation. It defines the relation of the parent and the child object. ▫ plmResult (PlmResult): This describes how the result of the operation is returned to the client. <table border="1" style="width: 100%; margin-top: 10px;"> <tr> <td style="width: 33%;">attributeNames (Boolean)</td> <td style="width: 33%;">List of field names to be returned</td> <td style="width: 33%;"> <ul style="list-style-type: none"> ▫ Optional ▫ Default <ul style="list-style-type: none"> ▫ All visible fields and ID fields </td> </tr> </table>			attributeNames (Boolean)	List of field names to be returned	<ul style="list-style-type: none"> ▫ Optional ▫ Default <ul style="list-style-type: none"> ▫ All visible fields and ID fields
attributeNames (Boolean)	List of field names to be returned	<ul style="list-style-type: none"> ▫ Optional ▫ Default <ul style="list-style-type: none"> ▫ All visible fields and ID fields 				

	includeBinaryValues (Boolean)	Include binary values?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 						
	includeAllLanguages (Boolean)	Include all languages?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 						
Response Type	<p>CreateRelationResponseType</p> <ul style="list-style-type: none"> ▫ statusCode (ResponseStatusCode) <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">SUCCESS</td> <td>The new created PLM object including all attributes defined by the PImResult of the request.</td> </tr> <tr> <td>PARTIAL_SUCCESS</td> <td>The new created PLM object including some of the attributes defined by the PImResult of the request.</td> </tr> <tr> <td>FAILURE</td> <td>A fault description including error message and kind of error.</td> </tr> </table> ▫ ticket (String) : A PLM ticket. <ul style="list-style-type: none"> ▫The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫The ticket is only valid for the PLM server instance that generated it. ▫ messageId (String): copied from the request, or generated. ▫ messageName (String): copied from the request, or the operation name. ▫ warnings: List of warnings (PImWarningType) that occurred during the operation. ▫ exceptions: List of exceptions (PImExceptionType) that occurred during the operation. ▫ relationObject (PImObject): The created PLM relation object contains the attributes listed in the PImResult of the request. <ul style="list-style-type: none"> ▫Additionally the ID attributes for of the parent and the child record are add. ▫The parent IDs are named PARENT.EDB_ID and PARENT.C_ID, the attributes for child IDs are named CHILD.EDB_ID and CHILD.C_ID. ▫This is necessary to prevent name clashes if the parent and child entity are the same (for instance in a item BOM). 			SUCCESS	The new created PLM object including all attributes defined by the PImResult of the request.	PARTIAL_SUCCESS	The new created PLM object including some of the attributes defined by the PImResult of the request.	FAILURE	A fault description including error message and kind of error.
SUCCESS	The new created PLM object including all attributes defined by the PImResult of the request.								
PARTIAL_SUCCESS	The new created PLM object including some of the attributes defined by the PImResult of the request.								
FAILURE	A fault description including error message and kind of error.								

getRelations

Service	To get the relationship between two or more PLM objects.
Usage	<p>The operation executes a query on the Agile e6 application and returns the matching PLM objects. The operation uses the mask that is specified in the relation to retrieve the data (search in mask).</p> <p>By default the response returns values of all visible fields (plus some important ID fields like EDB_ID and C_ID) that are contained in the mask. Response information can be restricted by defining the list of fields that should be returned, but be aware that you can only return values for fields which are available in the mask. The settings of the mask will determine the sorting of the data. Return values will be provided in a standardized format as marshaled by the JAXB framework. Date values will be in UTC, based on the assumption that the data returned by the PLM server is in server local time.</p>

	<p>By default, only the current language value will be retrieved for multi-language fields. However the Web Service client can request to retrieve all language values in the same call.</p> <p>Objects for which the current user does not have access will not show up in the response.</p> <p>The <i>countOnly</i> flag of the request is very important here. For more information on this, refer to Counting the Objects in this document.</p>															
Request Type	<p>CreateRelationRequestType</p> <ul style="list-style-type: none"> ▫ <i>messageId</i> (String): ID to be returned in the response (optional) ▫ <i>messageName</i> (String) : Name to be returned in the response (optional) ▫ <i>plmRelationQuery</i> (PlmRelationQuery): ▫ <i>PlmObject</i> or <i>PlmObjectReference</i>: To get the parent record of the relation. (<i>PlmObject</i> as returned by the <i>BusinessObjectService</i>) ▫ <i>PlmMetaRelationRef</i>: The object type is a PLM relation reference (parent, child, type, view). ▫ <i>selection</i>: A list of <i>PlmCondition</i> objects representing the search criteria for object attributes. <table border="1" data-bbox="488 831 1409 1335"> <tr> <td><i>ignoreRecordLimit</i> (Boolean)</td> <td>Ignore the record limit?</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False </td> </tr> <tr> <td><i>countOnly</i> (Boolean)</td> <td>Count only?</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False </td> </tr> <tr> <td><i>attributeNames</i> (Boolean)</td> <td>List of field names to be returned</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default ▫ All visible fields and ID fields </td> </tr> <tr> <td><i>includeBinaryValues</i> (Boolean)</td> <td>Include binary values?</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False </td> </tr> <tr> <td><i>includeAllLanguages</i> (Boolean)</td> <td>Include all languages?</td> <td> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False </td> </tr> </table>	<i>ignoreRecordLimit</i> (Boolean)	Ignore the record limit?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 	<i>countOnly</i> (Boolean)	Count only?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 	<i>attributeNames</i> (Boolean)	List of field names to be returned	<ul style="list-style-type: none"> ▫ Optional ▫ Default ▫ All visible fields and ID fields 	<i>includeBinaryValues</i> (Boolean)	Include binary values?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 	<i>includeAllLanguages</i> (Boolean)	Include all languages?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False
<i>ignoreRecordLimit</i> (Boolean)	Ignore the record limit?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 														
<i>countOnly</i> (Boolean)	Count only?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 														
<i>attributeNames</i> (Boolean)	List of field names to be returned	<ul style="list-style-type: none"> ▫ Optional ▫ Default ▫ All visible fields and ID fields 														
<i>includeBinaryValues</i> (Boolean)	Include binary values?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 														
<i>includeAllLanguages</i> (Boolean)	Include all languages?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 														
Response Type	<p>GetRelationsResponseType</p> <ul style="list-style-type: none"> ▫ Status code (SUCCESS, PARTIAL_SUCCESS, WARNING or FAILURE). ▫ A PLM ticket (String) <ul style="list-style-type: none"> ▫ The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫ The ticket is only valid for the PLM server instance that generated it. ▫ Message ID (copied from the request, or generated). ▫ Message name (copied from the request, or the operation name). ▫ List of warnings (<i>PlmWarningType</i>) that occurred during the operation. ▫ List of errors (<i>PlmExceptionType</i>) that occurred during the operation. ▫ Record limit hit? [true/false] : Indicates whether the query result has hit the mask limit. ▫ List of objects (<i>PlmObject</i>) found including all the object attribute values listed in the <i>PlmResult</i> of the request. 															

	<ul style="list-style-type: none"> ▫ Additionally the ID attributes for of the parent and the child record are added. The parent IDs are named PARENT.EDB_ID and PARENT.C_ID, the attributes for child IDs are named CHILD.EDB_ID and CHILD.C_ID. ▫ This is necessary to prevent name clashes if the parent and child entity are the same (for instance in a item BOM). ▫ If a count request was made, the response will have one PlmObject with an Integer attribute named COUNT containing the number of objects matching the query, and an Integer attribute called RECORD_LIMIT containing the current record limit of the mask used for the count operation.
--	--

updateObject

Service	To update an object in the EDM system.					
Usage	<p>The operation supports an automatic creation of an object if it was not found. The flag autoCreate in the request controls this behavior.</p> <p>By default, the response will return values of all visible fields (plus some important ID fields like EDB_ID and C_ID) that are contained in the mask. The response information can be restricted by defining the list of fields that should be returned in the PlmResult of the request, but be aware that you can only return values for fields which are available in the mask. The settings of the mask will determine the sorting of the data. Return values will be provided in a standardized format as marshaled by the JAXB framework. Date values will be in UTC, based on the assumption that the data returned by the PLM server is in server local time.</p> <p>By default, only the current language value will be retrieved for multi-language fields. However, the Web Service client can request to retrieve all language values in the same call.</p> <p>If an error occurred during creation of the object, an error message will be returned.</p> <p>Note To ensure that only masks designed for Web Service access are used, all mask names are checked against a Whitelist that is maintained by the administrator of the Agile e6 installation.</p>					
Request Type	<p>UpdateObjectRequestType</p> <ul style="list-style-type: none"> ▫ messageId (String): ID to be returned in the response (optional) ▫ messageName (String) : Name to be returned in the response (optional) ▫ plmObject: The PLM class reference, the ID of the object to update and a list of object attributes (name/value pairs) used to update or create the object. <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">autoCreate (Boolean)</td> <td style="width: 30%;">Automatically create the object if it does not exist?</td> <td style="width: 40%;"> <ul style="list-style-type: none"> ▫ Optional ▫ Default - False ▫ False = Returns a FAILURE code in case the object ID does not match the existing Agile e6 record. ▫ True = Object will be created with the attributes passed in the request, in </td> </tr> </table>			autoCreate (Boolean)	Automatically create the object if it does not exist?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False ▫ False = Returns a FAILURE code in case the object ID does not match the existing Agile e6 record. ▫ True = Object will be created with the attributes passed in the request, in
autoCreate (Boolean)	Automatically create the object if it does not exist?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False ▫ False = Returns a FAILURE code in case the object ID does not match the existing Agile e6 record. ▫ True = Object will be created with the attributes passed in the request, in 				

			case the object ID does not match an existing Agile e6 record.						
	<ul style="list-style-type: none"> ▫ plmResult: This describes how the result of the operation is returned to the client. 								
	attributeNames (Boolean)	List of field names to be returned	<ul style="list-style-type: none"> ▫ Optional ▫ Default <ul style="list-style-type: none"> ▫ All visible fields and ID fields 						
	includeBinaryValues (Boolean)	Include binary values?	<ul style="list-style-type: none"> ▫ Optional ▫ Default – False 						
	includeAllLanguages (Boolean)	Include all languages?	<ul style="list-style-type: none"> ▫ Optional ▫ Default - False 						
Response Type	<p>UpdateObjectResponseType</p> <ul style="list-style-type: none"> ▫ statusCode (ResponseStatusCode): <table border="1"> <tr> <td>SUCCESS</td> <td>The new created PLM object including all attributes defined by the PLM result of the request.</td> </tr> <tr> <td>PARTIAL_SUCCESS</td> <td>The new created PLM object including some of the attributes defined by the PlmResult of the request.</td> </tr> <tr> <td>FAILURE</td> <td>A fault description including error message and kind of error.</td> </tr> </table> <ul style="list-style-type: none"> ▫ ticket (String) : A PLM ticket. <ul style="list-style-type: none"> ▫ The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫ The ticket is only valid for the PLM server instance that generated it. ▫ messageId (String): copied from the request, or generated. ▫ messageName (String): copied from the request, or the operation name. ▫ warnings: List of warnings (PlmWarningType) that occurred during the operation. ▫ exceptions: List of exceptions (PlmExceptionType) that occurred during the operation. ▫ object (PlmObject): the object updated or created by this operation. <ul style="list-style-type: none"> ▫ It contains the attributes requested in the PlmResult, or all visible attributes if no attributes have been requested. ▫ autoCreated (Boolean): This flag is true, if the object has been created by this operation, and false if the object has been updated. 			SUCCESS	The new created PLM object including all attributes defined by the PLM result of the request.	PARTIAL_SUCCESS	The new created PLM object including some of the attributes defined by the PlmResult of the request.	FAILURE	A fault description including error message and kind of error.
SUCCESS	The new created PLM object including all attributes defined by the PLM result of the request.								
PARTIAL_SUCCESS	The new created PLM object including some of the attributes defined by the PlmResult of the request.								
FAILURE	A fault description including error message and kind of error.								

Document Management Web Services

A Document is a business object that specifies one or more files that are stored in the Agile e6 File Vault. You can load a document and add one or more files to its Files table. You can also search for a document and its files, just as you would search for an Item.

The Document Management Web Services supports the management of the document-file assignment and the upload/download of files.

Note To create a document, use the Business Object Web Services.

Streaming support, which is mandatory for the getFileCopy and checkInFile operations to work

Bulk Operations

The following are the bulk operation names of the single request operations for Document Management Web Services described the concurrent sections:

- getFileBulk
- getFileCopyBulk
- checkInFile

See [Processing the Bulk Requests](#) for complete details on how to handle the bulk operations.

getFiles

Service	To get a list of files assigned to a specific document.													
Usage	The request object contains the document handle that identifies the files which are assigned to the document. The response is a list of all files assigned to a document, or an error code.													
Request Type	GetFilesRequestType <ul style="list-style-type: none"> ▫ messageId (String, optional) ▫ messageName (String, optional) ▫ plmDocumentFileQuery (PlmDocumentFileQuery): <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">document (PlmObjectRef, required)</td> <td>An object reference to the document (the parent).</td> </tr> <tr> <td>documentFileMaskName (String, required)</td> <td>The maskname of the document-file relation.</td> </tr> <tr> <td>selection (List<PlmCondition>, required)</td> <td>Search criteria for object attributes in documentFileMaskName (name/value pairs).</td> </tr> <tr> <td>plmDfmSite (String, optional)</td> <td>Not supported in this version, ignored if EDB-DFM-ACTIVE=0</td> </tr> <tr> <td>ignoreRecordLimit (boolean, optional, default=true)</td> <td>Obey record limit? [true/false]</td> </tr> <tr> <td>excludeVaultValues (boolean, optional, default=false)</td> <td>Should vault name, vault type, vault kind, vaultNode, vaultPath, vaultNetRef and filename in vault of the file not be read and returned? [true/false]</td> </tr> </table>		document (PlmObjectRef, required)	An object reference to the document (the parent).	documentFileMaskName (String, required)	The maskname of the document-file relation.	selection (List<PlmCondition>, required)	Search criteria for object attributes in documentFileMaskName (name/value pairs).	plmDfmSite (String, optional)	Not supported in this version, ignored if EDB-DFM-ACTIVE=0	ignoreRecordLimit (boolean, optional, default=true)	Obey record limit? [true/false]	excludeVaultValues (boolean, optional, default=false)	Should vault name, vault type, vault kind, vaultNode, vaultPath, vaultNetRef and filename in vault of the file not be read and returned? [true/false]
document (PlmObjectRef, required)	An object reference to the document (the parent).													
documentFileMaskName (String, required)	The maskname of the document-file relation.													
selection (List<PlmCondition>, required)	Search criteria for object attributes in documentFileMaskName (name/value pairs).													
plmDfmSite (String, optional)	Not supported in this version, ignored if EDB-DFM-ACTIVE=0													
ignoreRecordLimit (boolean, optional, default=true)	Obey record limit? [true/false]													
excludeVaultValues (boolean, optional, default=false)	Should vault name, vault type, vault kind, vaultNode, vaultPath, vaultNetRef and filename in vault of the file not be read and returned? [true/false]													

	attributeNames (List<String>, optional)	List of field names to be returned - (optional for the generic result, the attributes which are always returned see in Response section).		
	includeAllLanguages (boolean, optional, default=false)	Include all languages? [true/false]		
	includeBinaryValues (boolean, optional, default=false)	Include binary values? [true/false]		
Response Type	GetFilesResponseType <ul style="list-style-type: none"> ▫ messageId (String, required) ▫ messageName (String, required) ▫ statusCode(ResponseStatusCode, required) <ul style="list-style-type: none"> ▫ SUCCESS, PARTIAL_SUCCESS, WARNING or FAILURE ▫ exceptions (List<PlmExceptionType>, optional) <ul style="list-style-type: none"> ▫ List of exceptions that occurred during the operation. ▫ warnings (List<PlmWarningType>, optional) <ul style="list-style-type: none"> ▫ List of warnings that occurred during the operation. ▫ ticket (String, optional) <ul style="list-style-type: none"> ▫ The Plm ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫ The ticket is only valid for the PLM server instance that generated it. ▫ recordLimitHit (boolean, required) <ul style="list-style-type: none"> ▫ [true false] Indicates whether the query result has hit the mask limit. ▫ objects (List<PlmDocumentFileObject>) <ul style="list-style-type: none"> ▫ List of PlmDocumentFileObjects found including all the object attribute values within the generic part as defined in the request <table border="1" data-bbox="527 1302 1404 1873" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%; padding: 5px;"> <ul style="list-style-type: none"> ▫ PlmDocumentFileObject </td> <td style="padding: 5px;"> <ul style="list-style-type: none"> ▫ plmObject(PlmObject) ▫ fileOrgName (String), (origin filename) ▫ fileOrgNode (String) ▫ fileOrgPath (String) ▫ fileSize (String) ▫ fileModifyDate (Date) ▫ fileOs (String) (operating system) (empty_string) ▫ fileType (String) (empty_string) ▫ fileFormat (String) (empty_string) ▫ fileStepCreSystem (String) ▫ fileCryptName (String), (empty if excludeVaultValues = true) ▫ vaultName (String), (empty if excludeVaultValues = true) </td> </tr> </table>		<ul style="list-style-type: none"> ▫ PlmDocumentFileObject 	<ul style="list-style-type: none"> ▫ plmObject(PlmObject) ▫ fileOrgName (String), (origin filename) ▫ fileOrgNode (String) ▫ fileOrgPath (String) ▫ fileSize (String) ▫ fileModifyDate (Date) ▫ fileOs (String) (operating system) (empty_string) ▫ fileType (String) (empty_string) ▫ fileFormat (String) (empty_string) ▫ fileStepCreSystem (String) ▫ fileCryptName (String), (empty if excludeVaultValues = true) ▫ vaultName (String), (empty if excludeVaultValues = true)
<ul style="list-style-type: none"> ▫ PlmDocumentFileObject 	<ul style="list-style-type: none"> ▫ plmObject(PlmObject) ▫ fileOrgName (String), (origin filename) ▫ fileOrgNode (String) ▫ fileOrgPath (String) ▫ fileSize (String) ▫ fileModifyDate (Date) ▫ fileOs (String) (operating system) (empty_string) ▫ fileType (String) (empty_string) ▫ fileFormat (String) (empty_string) ▫ fileStepCreSystem (String) ▫ fileCryptName (String), (empty if excludeVaultValues = true) ▫ vaultName (String), (empty if excludeVaultValues = true) 			

		<ul style="list-style-type: none"> ▫ vaultType (String), (empty if excludeVaultValues = true) ▫ vaultKind (String), (empty if excludeVaultValues = true) ▫ vaultNode (String), (empty if excludeVaultValues = true) ▫ vaultNetRef (String), (empty if excludeVaultValues = true) ▫ vaultPath (String), (empty if excludeVaultValues = true) <p>▫The created objects contain the attributes listed in the request.</p> <p>▫In case one or more of the requested attributes do not exist, PARTIAL_SUCCESS will be returned.</p> <p>▫In case one or more of the requested attributes are not accessible, a WARNING will be returned.</p> <p>▫If no attributes have been requested (attribute list is missing), the whole object including all visible attributes and the ID attributes (EDB_ID and C_ID) will be returned. If none of the requested attributes exists or the list is empty, only the ID attributes (EDB_ID and C_ID) will be returned.</p>
--	--	--

getFileCopy

Service	To get a copy of a file that is assigned to a specific document.
Usage	<p>This operation does not require any reservation or checking-out of the specified file. The request object contains the document handle, file handles and site ID. The response is the file attributes and link/URL to the files, or an error code.</p> <p>Note DFM is not supported in this release of Web Services. Hence, the getFileCopy operation downloads the file from the specified site even when the file at that site is not current.</p>
Request Type	<p>GetFileCopyRequestType</p> <ul style="list-style-type: none"> ▫ messageId (String, optional) ▫ messageName (String, optional) ▫ plmDocumentFile (PlmDocumentFileObject, required) <p>▫Describes the file to get. This is a PlmDocumentFileObject as returned by the DocumentManagementService.getFiles operation.</p>
Response Type	<p>GetFileCopyResponseType</p> <ul style="list-style-type: none"> ▫ messageId (String, required) ▫ messageName (String, required) ▫ statusCode(ResponseStatusCode, required) ▫SUCCESS, PARTIAL_SUCCESS, WARNING or FAILURE ▫ exceptions (List<PlmExceptionType>, optional) ▫List of exceptions that occurred during the operation. ▫ warnings (List<PlmWarningType>, optional)

	<ul style="list-style-type: none"> ▫ List of warnings that occurred during the operation. ▫ ticket (String, optional) <ul style="list-style-type: none"> ▫ The Plm ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫ The ticket is only valid for the PLM server instance that generated it. ▫ plmDocumentFile (PlmDocumentFileObject, required) <ul style="list-style-type: none"> ▫ The file information. ▫ This is the same PlmDocumentFileObject that was passed in the request. ▫ fileData (a javax.activation.DataHandler, optional). <ul style="list-style-type: none"> ▫ The file data as a binary MTOM stream with content type "application/octet-stream". ▫ Use the Streaming API of your JAX-WS implementation to transfer the file. ▫ If streaming is not used, the file is transferred in the XML data, which takes considerably longer, leads to huge SOAP messages and might even result in an OutOfMemoryException on the server or the client.
--	--

checkInFile

Service	To check in a new file.			
Usage	<p>The request object specifies the document handle, file handles, Site ID, etc of the file that.</p> <p>A previously checked out files cannot be checked-in with this operation as the request type is completely different.</p> <p>There is full DFM support for check-in of files via Web Service. The DFM capabilities apply the same way as if the file would have been checked in via Java Client.</p>			
Request Type	CheckInFileRequestType <ul style="list-style-type: none"> ▫ messageId (String, optional) ▫ messageName (String, optional) ▫ plmDocumentFileQuery (PlmDocumentFileQuery): <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%; padding: 5px;"> <ul style="list-style-type: none"> ▫ PlmDocumentFileQuery </td> <td style="padding: 5px;"> <ul style="list-style-type: none"> ▫ document (PlmObjectRef, required): An object reference to the document (the parent). ▫ documentFileMaskName (String, required): The maskname of the document-file relation. ▫ selection (List<PlmCondition>, required): Search criteria for object attributes in documentFileMaskName (name/value pairs). ▫ plmDfmSite (String, optional): Not supported in this version, ignored if EDB-DFM-ACTIVE=0 ▫ ignoreRecordLimit (boolean, optional, default=true): Obey record limit? [true/false] ▫ excludeVaultValues (boolean, optional, default=false): Should vault name, vault type, vault kind, vaultNode, vaultPath, vaultNetRef and filename in vault of the file not be read and </td> </tr> </table> 	<ul style="list-style-type: none"> ▫ PlmDocumentFileQuery 	<ul style="list-style-type: none"> ▫ document (PlmObjectRef, required): An object reference to the document (the parent). ▫ documentFileMaskName (String, required): The maskname of the document-file relation. ▫ selection (List<PlmCondition>, required): Search criteria for object attributes in documentFileMaskName (name/value pairs). ▫ plmDfmSite (String, optional): Not supported in this version, ignored if EDB-DFM-ACTIVE=0 ▫ ignoreRecordLimit (boolean, optional, default=true): Obey record limit? [true/false] ▫ excludeVaultValues (boolean, optional, default=false): Should vault name, vault type, vault kind, vaultNode, vaultPath, vaultNetRef and filename in vault of the file not be read and 	
<ul style="list-style-type: none"> ▫ PlmDocumentFileQuery 	<ul style="list-style-type: none"> ▫ document (PlmObjectRef, required): An object reference to the document (the parent). ▫ documentFileMaskName (String, required): The maskname of the document-file relation. ▫ selection (List<PlmCondition>, required): Search criteria for object attributes in documentFileMaskName (name/value pairs). ▫ plmDfmSite (String, optional): Not supported in this version, ignored if EDB-DFM-ACTIVE=0 ▫ ignoreRecordLimit (boolean, optional, default=true): Obey record limit? [true/false] ▫ excludeVaultValues (boolean, optional, default=false): Should vault name, vault type, vault kind, vaultNode, vaultPath, vaultNetRef and filename in vault of the file not be read and 			

	<table border="1" data-bbox="526 195 1408 520"> <tr> <td data-bbox="526 195 834 520"></td> <td data-bbox="834 195 1408 520"> <p>returned? [true/false]</p> <ul style="list-style-type: none"> ▫ attributeNames (List<String>, optional): List of field names to be returned - (optional for the generic result, the attributes which are always returned see in Response section). ▫ includeAllLanguages (boolean, optional, default=false): Include all languages? [true/false] ▫ includeBinaryValues (boolean, optional, default=false): Include binary values? [true/false] </td> </tr> </table> <ul style="list-style-type: none"> ▫ documentFileObject (PlmObject, required) <ul style="list-style-type: none"> ▫ List of new relationship attributes . The values must be typed values in form of a PlmAttributeChoice. ▫ The meta data of the relationObject is currently ignored by this operation, so you can pass empty values for these elements. ▫ Only the list of attribute values is used to fill the new relation record in Agile e6. ▫ At least following fields and their values must be provided: <ul style="list-style-type: none"> ▫ * T_FILE_DAT.STORAGE_AREA (Vault) ▫ * T_FILE_DAT.ORG_NAME (Original File Name) ▫ * T_FILE_DAT.ORG_NODE (Node) ▫ * T_FILE_DAT.ORG_DISCPATH (Original Disk+Path) ▫ fileData (a javax.activation.DataHandler, optional). <ul style="list-style-type: none"> ▫ The file data as a binary MTOM stream with content type "application/octet-stream" 		<p>returned? [true/false]</p> <ul style="list-style-type: none"> ▫ attributeNames (List<String>, optional): List of field names to be returned - (optional for the generic result, the attributes which are always returned see in Response section). ▫ includeAllLanguages (boolean, optional, default=false): Include all languages? [true/false] ▫ includeBinaryValues (boolean, optional, default=false): Include binary values? [true/false]
	<p>returned? [true/false]</p> <ul style="list-style-type: none"> ▫ attributeNames (List<String>, optional): List of field names to be returned - (optional for the generic result, the attributes which are always returned see in Response section). ▫ includeAllLanguages (boolean, optional, default=false): Include all languages? [true/false] ▫ includeBinaryValues (boolean, optional, default=false): Include binary values? [true/false] 		
Response Type	<p>CheckInFileResponseType</p> <ul style="list-style-type: none"> ▫ messageId (String, required) ▫ messageName (String, required) ▫ statusCode(ResponseStatusCode, required) <ul style="list-style-type: none"> ▫ SUCCESS, PARTIAL_SUCCESS, WARNING or FAILURE ▫ exceptions (List<PlmExceptionType>, optional) <ul style="list-style-type: none"> ▫ List of exceptions that occurred during the operation. ▫ warnings (List<PlmWarningType>, optional) <ul style="list-style-type: none"> ▫ List of warnings that occurred during the operation. ▫ ticket (String, optional) <ul style="list-style-type: none"> ▫ The Plm ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫ The ticket is only valid for the PLM server instance that generated it. ▫ PlmDocumentFileObject (PlmDocumentFileObject, required): <table border="1" data-bbox="526 1650 1408 1892"> <tr> <td data-bbox="526 1650 834 1892"> <ul style="list-style-type: none"> ▫ PlmDocumentFileObject </td> <td data-bbox="834 1650 1408 1892"> <ul style="list-style-type: none"> ▫ plmObject(PlmObject) ▫ fileOrgName (String) ▫ fileOrgNode (String) ▫ fileOrgPath (String) ▫ fileSize (String) ▫ fileModifyDate (Date) </td> </tr> </table> 	<ul style="list-style-type: none"> ▫ PlmDocumentFileObject 	<ul style="list-style-type: none"> ▫ plmObject(PlmObject) ▫ fileOrgName (String) ▫ fileOrgNode (String) ▫ fileOrgPath (String) ▫ fileSize (String) ▫ fileModifyDate (Date)
<ul style="list-style-type: none"> ▫ PlmDocumentFileObject 	<ul style="list-style-type: none"> ▫ plmObject(PlmObject) ▫ fileOrgName (String) ▫ fileOrgNode (String) ▫ fileOrgPath (String) ▫ fileSize (String) ▫ fileModifyDate (Date) 		

			<ul style="list-style-type: none"> ▫ fileOs (String) (operating system) (empty_string) ▫ fileType (String) (empty_string) ▫ fileFormat (String) (empty_string) ▫ fileStepCreSystem (String) ▫ fileCryptName (String), (empty if excludeVaultValues = true) ▫ vaultName (String), (empty if excludeVaultValues = true) ▫ vaultType (String), (empty if excludeVaultValues = true) ▫ vaultKind (String), (empty if excludeVaultValues = true) ▫ vaultNode (String), (empty if excludeVaultValues = true) ▫ vaultNetRef (String), (empty if excludeVaultValues = true) ▫ vaultPath (String), (empty if excludeVaultValues = true)
--	--	--	---

MetaData Web Services

The Metadata Service enables you to read the definition of Agile e6 classes like entities, entity types and relations.

All operations need one request object as input and return one response object.

- The request contains at least the name of Agile e6 class and a mask name.
- The response contains the metadata of the respective Agile e6 class.
- Bulk operations allow you to execute a whole list of requests with one Web Service call. The response of a bulk operation contains a list of responses matching the list of requests.

The Agile e6 metadata is read from the Agile e6 application using the mask specified in the request.

It is only possible to access Agile e6 attributes that are visible in this mask, with the exception of the ID fields EDB_ID and C_ID.

Only masks listed in the so called Web Service White List of the Agile e6 application can be accessed.

Bulk Operations

The following are the bulk operation names of the single request operations for MetaData Web Services described the concurrent sections. See Processing the Bulk Requests for complete

details on how to handle the bulk operations.

- getEntityBulk
- getEntityTypeBulk
- getEntityRelationBulk

getEntity

Service	To get the metadata of a PLM entity.					
Usage	The data is based on the mask used to access the data. If the request does not pass a specific mask name, the default mask of the entity will be used. The response contains the definition of all visible attributes in the mask. If an attribute has mode specific access, it will be returned regardless of the mode specific access value.					
Request Type	<p>GetEntityRequestType</p> <ul style="list-style-type: none"> ▫ name (String): The entity name. ▫ mask (String): The mask name to use to read this entity. (optional) <ul style="list-style-type: none"> ▫If empty, the default list of the entity will be used. ▫As all other mask names, the mask is checked against the white list for masks. If it is not listed, the access is denied. ▫ messageId (String): ID to be returned in the response (optional) ▫ messageName (String) : Name to be returned in the response (optional) 					
Response Type	<p>GetEntityResponseType</p> <ul style="list-style-type: none"> ▫ statusCode (ResponseStatusCode) : SUCCESS or FAILURE. ▫ ticket (String) : A PLM ticket. <ul style="list-style-type: none"> ▫The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫The ticket is only valid for the PLM server instance that generated it. ▫ messageId (String): copied from the request, or generated. ▫ messageName (String): copied from the request, or the operation name. ▫ warnings: List of warnings (PlmWarningType) that occurred during the operation. ▫ exceptions: List of exceptions (PlmExceptionType) that occurred during the operation. ▫ entity (PlmEntity): contains the entity definition (all information is returned with type String, unless noted otherwise): : <table border="1" style="width: 100%; margin-top: 5px;"> <tr> <td style="width: 33%;"> <ul style="list-style-type: none"> ▫ Entity ID. ▫ Entity name. ▫ Mask name. ▫ Default form. ▫ Default list. ▫ Table name. ▫ Join table name. </td> <td style="width: 33%;"></td> <td style="width: 33%;"></td> </tr> </table> 			<ul style="list-style-type: none"> ▫ Entity ID. ▫ Entity name. ▫ Mask name. ▫ Default form. ▫ Default list. ▫ Table name. ▫ Join table name. 		
<ul style="list-style-type: none"> ▫ Entity ID. ▫ Entity name. ▫ Mask name. ▫ Default form. ▫ Default list. ▫ Table name. ▫ Join table name. 						

		<ul style="list-style-type: none"> ▫ Entity title (in the current session language). ▫ Mask title (in the current session language). ▫ Record limit. ▫ Number of significant fields. 		
		<ul style="list-style-type: none"> ▫ List of attribute definitions (PImMetaAttribute) containing: 	<ul style="list-style-type: none"> ▫ Attribute name ▫ Attribute type. ▫ Attribute title (in the current session language), ▫ Attribute description (in the current session language). ▫ Attribute format. ▫ Attribute default value. ▫ Attribute Checkstring 	
			<ul style="list-style-type: none"> ▫ Attribute access (visible/invisible/mandatory/read-only/mode specific): 	<ul style="list-style-type: none"> ▫ Query mode specific attribute access (if applicable). ▫ Update mode specific attribute access (if applicable). ▫ Insert mode specific attribute access (if applicable).
			<ul style="list-style-type: none"> ▫ Data size of the attribute in this mask. ▫ Visible field width in this mask. (useful if a UI is generated from this meta data) ▫ Visible field height in this mask. (useful if a UI is generated from this meta data) ▫ Attribute visible? Tells you if the attribute is visible in this mask. 	
		<ul style="list-style-type: none"> ▫ List of relation meta data (PImMetaRelation) defined for this 	<ul style="list-style-type: none"> ▫ The name of the parent entity. ▫ The name of the child entity. ▫ The relation type. 	<ul style="list-style-type: none"> ▫

	entity:	<ul style="list-style-type: none"> ▫ The name of the view. ▫ The name of the relation. ▫ The internal ID of the relation. ▫ The table name. ▫ The title of the relation (in the current session language). ▫ The default list. ▫ The default form (empty for most relations). ▫ The mask name used to read the meta data. <ul style="list-style-type: none"> ▫ This data can later be used to call <code>MetadataService.getEntityRelation</code> to get all attribute meta data for one specific relation. 	
	<ul style="list-style-type: none"> ▫ List of type meta data (PImMetaType) defined for this entity: 	<ul style="list-style-type: none"> ▫ The name of the master entity. ▫ The type name. ▫ The table name. ▫ The title of the type. ▫ The default list. ▫ The default form. ▫ The mask name used to read the metadata. <ul style="list-style-type: none"> ▫ This data can be used later to call <code>MetadataService.getEntityType</code> to get all attribute metadata for one specific type. 	

getEntity Type

Service	To get the metadata of a PLM entity type.
Usage	<p>The data is based on the mask used to access the data. If the request does not pass a specific mask name, the default mask of the entity type will be used. The response contains the definition of all visible attributes in the mask. If an attribute has mode specific access, it will be returned regardless of the mode specific access value.</p> <p>If the mask contains visible multi-language attributes, all generated invisible multi-language attribute siblings are returned.</p>
Request Type	<p>GetEntityTypeRequestType</p> <ul style="list-style-type: none"> ▫ name (String): the name of the master entity for this type ▫ type (String): the name of the type ▫ mask (String): The mask name to use to read this entity. (optional)

	<p>▫ If empty, the default list of the entity will be used. As all other mask names, the mask is checked against the white list for masks. If it is not listed, the access is denied.</p> <ul style="list-style-type: none"> ▫ messageId (String): ID to be returned in the response (optional) ▫ messageName (String) : Name to be returned in the response (optional) 								
Response Type	<p>GetEntityTypeResponseType</p> <ul style="list-style-type: none"> ▫ statusCode (ResponseStatusCode) : SUCCESS or FAILURE. ▫ ticket (String) : A PLM ticket. <ul style="list-style-type: none"> ▫ The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫ The ticket is only valid for the PLM server instance that generated it. ▫ messageId (String): copied from the request, or generated. ▫ messageName (String): copied from the request, or the operation name. ▫ warnings: List of warnings (PlmWarningType) that occurred during the operation. ▫ exceptions: List of exceptions (PlmExceptionType) that occurred during the operation. ▫ An entity type definition of type PlmEntityType (all information is returned with type String, unless noted otherwise): <table border="1" data-bbox="527 903 1409 1890"> <tr> <td data-bbox="527 903 787 1617"> <ul style="list-style-type: none"> ▫ Entity name ▫ Type name ▫ Mask name ▫ Table name ▫ Join table name ▫ Entity type title (in the current session language). ▫ Mask title (in the current session language). ▫ Mask limit. ▫ Number of significant fields ▫ Master: the reference to the master entity as a PlmClassRef </td> <td data-bbox="787 903 1193 1617"></td> <td data-bbox="1193 903 1409 1617"></td> </tr> <tr> <td data-bbox="527 1617 787 1890"> <ul style="list-style-type: none"> ▫ List of attribute definitions containing: </td> <td data-bbox="787 1617 1193 1890"> <ul style="list-style-type: none"> ▫ Attribute type. ▫ Attribute title (in the current session language), ▫ Attribute description (in the current session language). ▫ Attribute format. ▫ Attribute default value. </td> <td data-bbox="1193 1617 1409 1890"></td> </tr> </table> 			<ul style="list-style-type: none"> ▫ Entity name ▫ Type name ▫ Mask name ▫ Table name ▫ Join table name ▫ Entity type title (in the current session language). ▫ Mask title (in the current session language). ▫ Mask limit. ▫ Number of significant fields ▫ Master: the reference to the master entity as a PlmClassRef 			<ul style="list-style-type: none"> ▫ List of attribute definitions containing: 	<ul style="list-style-type: none"> ▫ Attribute type. ▫ Attribute title (in the current session language), ▫ Attribute description (in the current session language). ▫ Attribute format. ▫ Attribute default value. 	
<ul style="list-style-type: none"> ▫ Entity name ▫ Type name ▫ Mask name ▫ Table name ▫ Join table name ▫ Entity type title (in the current session language). ▫ Mask title (in the current session language). ▫ Mask limit. ▫ Number of significant fields ▫ Master: the reference to the master entity as a PlmClassRef 									
<ul style="list-style-type: none"> ▫ List of attribute definitions containing: 	<ul style="list-style-type: none"> ▫ Attribute type. ▫ Attribute title (in the current session language), ▫ Attribute description (in the current session language). ▫ Attribute format. ▫ Attribute default value. 								

			<ul style="list-style-type: none"> ▫ Attribute access (visible/invisible/mandatory/read-only/mode specific): 	<ul style="list-style-type: none"> ▫ Query mode specific attribute access (if applicable). ▫ Update mode specific attribute access (if applicable). ▫ Insert mode specific attribute access (if applicable).
			<ul style="list-style-type: none"> ▫ Data size of the attribute in this mask. ▫ Visible field width in this mask. (useful if a UI is generated from this meta data) ▫ Visible field height in this mask. (useful if a UI is generated from this meta data) ▫ Attribute visible? Tells you if the attribute is visible in this mask. 	
		<ul style="list-style-type: none"> ▫ List of relation meta data (PImMetaRelation) defined for this entity: 	<ul style="list-style-type: none"> ▫ The name of the parent entity. ▫ The name of the child entity. ▫ The relation type. ▫ The name of the view. ▫ The name of the relation. ▫ The internal ID of the relation. ▫ The table name. ▫ The title of the relation (in the current session language). ▫ The default list. ▫ The default form. ▫ This data can be used later to call <code>MetadataService.getEntityRelation</code> to get all attribute metadata for one specific relation. 	

getEntityRelation

Service	To get the metadata of a PLM constraint, refine or aggregate relation.									
Usage	The meta relation object can either be taken from the response of a call to getEntity/getEntity type, or it can be created using hard coded default values. The request attributes – parent, child, type and view are needed to identify the relation data.									
Request Type	<p>GetEntityRelationRequestType</p> <ul style="list-style-type: none"> ▫ metaRelation (PlmMetaRelation): Describes the relation to read and must contain at least the following information: <table border="1" data-bbox="527 537 1409 732"> <tr> <td data-bbox="527 537 646 583">parent:</td> <td data-bbox="646 537 1409 583">The name of the parent entity. (e.g. "EDB-ARTICLE")</td> </tr> <tr> <td data-bbox="527 583 646 630">child:</td> <td data-bbox="646 583 1409 630">The name of the child entity (e.g. "EDB-DOCUMENT")</td> </tr> <tr> <td data-bbox="527 630 646 676">type:</td> <td data-bbox="646 630 1409 676">The relation type. (e.g. PlmRelationTypeEnum.REFINE)</td> </tr> <tr> <td data-bbox="527 676 646 732">view:</td> <td data-bbox="646 676 1409 732">The name of the view. (e.g. "STR").</td> </tr> </table> ▫ The meta relation object can either be taken from the response of a call to getEntity/getEntity type, or it can be created using hard coded default values. The four attributes listed above are needed to identify the relation data, the rest of the attributes in PlmMetaRelation are not relevant. ▫ messageId (String): ID to be returned in the response (optional) ▫ messageName (String) : Name to be returned in the response (optional) 		parent:	The name of the parent entity. (e.g. "EDB-ARTICLE")	child:	The name of the child entity (e.g. "EDB-DOCUMENT")	type:	The relation type. (e.g. PlmRelationTypeEnum.REFINE)	view:	The name of the view. (e.g. "STR").
parent:	The name of the parent entity. (e.g. "EDB-ARTICLE")									
child:	The name of the child entity (e.g. "EDB-DOCUMENT")									
type:	The relation type. (e.g. PlmRelationTypeEnum.REFINE)									
view:	The name of the view. (e.g. "STR").									
Response Type	<p>GetEntityRelationResponseType</p> <ul style="list-style-type: none"> ▫ statusCode (ResponseStatusCode) : SUCCESS or FAILURE. ▫ ticket (String) : A PLM ticket. <ul style="list-style-type: none"> ▫ The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫ The ticket is only valid for the PLM server instance that generated it. ▫ messageId (String): copied from the request, or generated. ▫ messageName (String): copied from the request, or the operation name. ▫ warnings: List of warnings (PlmWarningType) that occurred during the operation. ▫ exceptions: List of exceptions (PlmExceptionType) that occurred during the operation. ▫ plmRelation (PlmRelation) : The relation definition containing: <table border="1" data-bbox="527 1444 1409 1881"> <tr> <td data-bbox="527 1444 792 1881"> <ul style="list-style-type: none"> ▫ Relation name. ▫ PlmMetaRelation: Detailed meta information of the relation. ▫ Mask name. ▫ Table name. ▫ Entity type title (in the current session language). ▫ Mask title (in the </td> <td data-bbox="792 1444 1198 1881"></td> <td data-bbox="1198 1444 1409 1881"></td> </tr> </table> 		<ul style="list-style-type: none"> ▫ Relation name. ▫ PlmMetaRelation: Detailed meta information of the relation. ▫ Mask name. ▫ Table name. ▫ Entity type title (in the current session language). ▫ Mask title (in the 							
<ul style="list-style-type: none"> ▫ Relation name. ▫ PlmMetaRelation: Detailed meta information of the relation. ▫ Mask name. ▫ Table name. ▫ Entity type title (in the current session language). ▫ Mask title (in the 										

	<ul style="list-style-type: none"> current session language). ▫ Mask limit. ▫ Number of significant fields. 		
	<ul style="list-style-type: none"> ▫ List of attribute definitions containing: 	<ul style="list-style-type: none"> ▫ Attribute type. ▫ Attribute title (in the current session language), ▫ Attribute description (in the current session language). ▫ Attribute format. ▫ Attribute default value. 	
		<ul style="list-style-type: none"> ▫ Attribute access (visible/invisible/mandatory/read-only/mode specific): 	<ul style="list-style-type: none"> ▫ Query mode specific attribute access (if applicable). ▫ Update mode specific attribute access (if applicable). ▫ Insert mode specific attribute access (if applicable).
		<p>Data size of the attribute in this mask.</p> <p>Visible field width in this mask. (useful if a UI is generated from this meta data)</p> <p>Visible field height in this mask. (useful if a UI is generated from this meta data)</p> <p>Attribute visible? Tells you if the attribute is visible in this mask.</p>	

Configuration Web Services

The Configuration Web Service enables you to retrieve PLM objects from the Agile e6 application. It retrieves configuration data of a PLM object, such as Default, User Context, etc specified by its name.

The requests include the value(s) for specifying the requested object. Responses include the requested objects.

Bulk operations require a list of requests to execute. These return with a list of responses.

Bulk Operations

The following are the bulk operation names of the single request operations for Configuration Web Services described the concurrent sections. See Processing the Bulk Requests for complete details on how to handle the bulk operations.

- getUserContext
- setUserContext
- getDefaultBulk

getUserContext

Service	To get all the information of the current user context of a PLM session.					
Usage	The request object carries current PLM user's details and only an optional message ID and name. The response object delivers the user attributes, all group assignments attributes, current view (Released, Global etc.), current context (DSG, ENG), current project assignment (Project ID) and current Org assignment (Org ID).					
Request Type	GetUserContextRequestType <ul style="list-style-type: none"> ▫ messageId (String): ID to be returned in the response (optional). ▫ messageName (String) : Name to be returned in the response (optional). 					
Response Type	GetUserContextResponseType <ul style="list-style-type: none"> ▫ statusCode (ResponseStatusCode) : SUCCESS or FAILURE. <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%; text-align: center;">SUCCESS</td> <td>All objects from user context are returned, if they are available. There could be some warnings in the message block, if some objects (e.g. currentJob, currentRole) are not available. It could make sense for setUserContext, but is not necessary to check for getUserContext.</td> </tr> <tr> <td style="text-align: center;">FAILURE</td> <td>There was a connection problem.</td> </tr> </table> ▫ ticket (String) : A PLM ticket. <ul style="list-style-type: none"> ▫The ticket can be used instead of the password in subsequent calls. It allows the client to reference the PLM session, even if the HTTP session has been closed, or - in case of a backward flow - if there is no HTTP session. ▫The ticket is only valid for the PLM server instance that generated it. ▫ messageId (String): copied from the request, or generated. ▫ messageName (String): copied from the request, or the operation name. ▫ warnings: List of warnings (PlmWarningType) that occurred during the operation. 		SUCCESS	All objects from user context are returned, if they are available. There could be some warnings in the message block, if some objects (e.g. currentJob, currentRole) are not available. It could make sense for setUserContext, but is not necessary to check for getUserContext.	FAILURE	There was a connection problem.
SUCCESS	All objects from user context are returned, if they are available. There could be some warnings in the message block, if some objects (e.g. currentJob, currentRole) are not available. It could make sense for setUserContext, but is not necessary to check for getUserContext.					
FAILURE	There was a connection problem.					

	<ul style="list-style-type: none"> ▫ exceptions: List of exceptions (PlmExceptionType) that occurred during the operation. ▫ plmUserContext (PlmUserContext): 										
	<table border="1"> <tr> <td>plmUserInfo (PlmUserContextUserInfo):</td> <td> <ul style="list-style-type: none"> ▫ userName ▫ userID ▫ group ▫ groupID ▫ userLanguage ▫ userLocale </td> </tr> <tr> <td>plmViewInfo (PlmUserContextView):</td> <td> <ul style="list-style-type: none"> ▫ preliminaryFlag (Boolean.TRUE, Boolean.False, null) ▫ referenceDate (yyyy-MM-dd HH:mm:ss, @NOW, empty_string) ▫ versionViewTitle (Current, Production, Global, Development_extended) ▫ versionView (PlmVersionViewEnum) </td> </tr> <tr> <td>plmChangeManagementInfo (PlmUserContextChg):</td> <td> <ul style="list-style-type: none"> ▫ currentChgFlag (Boolean.TRUE, Boolean.False, null) ▫ currentWorkOrder (EDB_ID, empty_string) ▫ currentWorkSet (EDB_ID, empty_string) </td> </tr> <tr> <td>plmMoaMpaInfo (PlmUserContextMoaMpa) :</td> <td> <ul style="list-style-type: none"> ▫ moaMpaConfFlag(PlmUserContextMOAEnum, null) ▫ currentJob (empty_string) ▫ currentRole (empty_string) ▫ currentProjectOrOrganisation (empty_string) ▫ currentProjectOrOrganisationCid (empty_string) </td> </tr> <tr> <td>plmDFMInfo (PlmUserContextDFM):</td> <td> <ul style="list-style-type: none"> ▫ dfmConfigFlag (Boolean.TRUE, Boolean.False, null) ▫ site (Reserved for future use) </td> </tr> </table>	plmUserInfo (PlmUserContextUserInfo):	<ul style="list-style-type: none"> ▫ userName ▫ userID ▫ group ▫ groupID ▫ userLanguage ▫ userLocale 	plmViewInfo (PlmUserContextView):	<ul style="list-style-type: none"> ▫ preliminaryFlag (Boolean.TRUE, Boolean.False, null) ▫ referenceDate (yyyy-MM-dd HH:mm:ss, @NOW, empty_string) ▫ versionViewTitle (Current, Production, Global, Development_extended) ▫ versionView (PlmVersionViewEnum) 	plmChangeManagementInfo (PlmUserContextChg):	<ul style="list-style-type: none"> ▫ currentChgFlag (Boolean.TRUE, Boolean.False, null) ▫ currentWorkOrder (EDB_ID, empty_string) ▫ currentWorkSet (EDB_ID, empty_string) 	plmMoaMpaInfo (PlmUserContextMoaMpa) :	<ul style="list-style-type: none"> ▫ moaMpaConfFlag(PlmUserContextMOAEnum, null) ▫ currentJob (empty_string) ▫ currentRole (empty_string) ▫ currentProjectOrOrganisation (empty_string) ▫ currentProjectOrOrganisationCid (empty_string) 	plmDFMInfo (PlmUserContextDFM):	<ul style="list-style-type: none"> ▫ dfmConfigFlag (Boolean.TRUE, Boolean.False, null) ▫ site (Reserved for future use)
	plmUserInfo (PlmUserContextUserInfo):	<ul style="list-style-type: none"> ▫ userName ▫ userID ▫ group ▫ groupID ▫ userLanguage ▫ userLocale 									
	plmViewInfo (PlmUserContextView):	<ul style="list-style-type: none"> ▫ preliminaryFlag (Boolean.TRUE, Boolean.False, null) ▫ referenceDate (yyyy-MM-dd HH:mm:ss, @NOW, empty_string) ▫ versionViewTitle (Current, Production, Global, Development_extended) ▫ versionView (PlmVersionViewEnum) 									
	plmChangeManagementInfo (PlmUserContextChg):	<ul style="list-style-type: none"> ▫ currentChgFlag (Boolean.TRUE, Boolean.False, null) ▫ currentWorkOrder (EDB_ID, empty_string) ▫ currentWorkSet (EDB_ID, empty_string) 									
	plmMoaMpaInfo (PlmUserContextMoaMpa) :	<ul style="list-style-type: none"> ▫ moaMpaConfFlag(PlmUserContextMOAEnum, null) ▫ currentJob (empty_string) ▫ currentRole (empty_string) ▫ currentProjectOrOrganisation (empty_string) ▫ currentProjectOrOrganisationCid (empty_string) 									
plmDFMInfo (PlmUserContextDFM):	<ul style="list-style-type: none"> ▫ dfmConfigFlag (Boolean.TRUE, Boolean.False, null) ▫ site (Reserved for future use) 										

setUserContext

Service	To set the current user context to be used in the next operations for the current PLM session.
Usage	This operation is used to set current job in MOA/MPA environment. The request object carries the user context details, such as the new view, new assignment, new Org assignment and new Project assignment. The response object delivers the user attributes, group assignments, new current view, new current context, new current project assignment, new current org assignment.
Request Type	SetUserContextRequestType <ul style="list-style-type: none"> ▫ messageID (String): ID to be returned in the response

	<ul style="list-style-type: none"> ▫ messageName (String) : Name to be returned in the response ▫ plmUserContext (PlmUserContext): <table border="1" data-bbox="521 279 1408 1579"> <tr> <td data-bbox="521 279 852 632"> <p>plmUserInfo (PlmUserContextUserInfo):</p> </td> <td data-bbox="852 279 1408 632"> <ul style="list-style-type: none"> ▫ userName (not changeable by current user) ▫ userID (not changeable by current user) ▫ group (Reserved for future use : currently there is no API to implement it.) ▫ groupID (Reserved for future use : currently there is no API to implement it.) ▫ userLanguage (e.g. ENG, GER, FRA) ▫ userLocale (always changed with user language) </td> </tr> <tr> <td data-bbox="521 632 852 867"> <p>plmViewInfo (PlmUserContextView):</p> </td> <td data-bbox="852 632 1408 867"> <ul style="list-style-type: none"> ▫ preliminaryFlag (Boolean.TRUE, Boolean.FALSE) ▫ referenceDate (in the form of yyyy-MM-dd HH:mm:ss) ▫ versionViewTitle (ignored) ▫ versionView (PlmVersionViewEnum) </td> </tr> <tr> <td data-bbox="521 867 852 1094"> <p>plmChangeManagementInfo (PlmUserContextChg):</p> </td> <td data-bbox="852 867 1408 1094"> <ul style="list-style-type: none"> ▫ currentChgFlag (not changeable by current user) ▫ currentWorkOrder (EDB-ID of work order, no check of currentChgFlag) ▫ currentWorkSet (EDB-ID of work set, no check of currentChgFlag) </td> </tr> <tr> <td data-bbox="521 1094 852 1467"> <p>plmMoaMpaInfo (PlmUserContextMoaMpa) :</p> </td> <td data-bbox="852 1094 1408 1467"> <ul style="list-style-type: none"> ▫ moaMpaConfFlag (not changeable by current user) ▫ currentJob EDB_ID of the job, access will be checked by Agile e6 server ▫ currentProjectOrOrganisation - ignored in the request, filled by the response ▫ currentProjectOrOrganisationCid - ignored in the request, filled by the response ▫ currentRole - ignored in the request, filled by the response </td> </tr> <tr> <td data-bbox="521 1467 852 1579"> <p>plmDFMInfo (PlmUserContextDFM):</p> </td> <td data-bbox="852 1467 1408 1579"> <ul style="list-style-type: none"> ▫ dFMConfigFlag (not changeable by current user) ▫ site (Reserved for future use) </td> </tr> </table> 	<p>plmUserInfo (PlmUserContextUserInfo):</p>	<ul style="list-style-type: none"> ▫ userName (not changeable by current user) ▫ userID (not changeable by current user) ▫ group (Reserved for future use : currently there is no API to implement it.) ▫ groupID (Reserved for future use : currently there is no API to implement it.) ▫ userLanguage (e.g. ENG, GER, FRA) ▫ userLocale (always changed with user language) 	<p>plmViewInfo (PlmUserContextView):</p>	<ul style="list-style-type: none"> ▫ preliminaryFlag (Boolean.TRUE, Boolean.FALSE) ▫ referenceDate (in the form of yyyy-MM-dd HH:mm:ss) ▫ versionViewTitle (ignored) ▫ versionView (PlmVersionViewEnum) 	<p>plmChangeManagementInfo (PlmUserContextChg):</p>	<ul style="list-style-type: none"> ▫ currentChgFlag (not changeable by current user) ▫ currentWorkOrder (EDB-ID of work order, no check of currentChgFlag) ▫ currentWorkSet (EDB-ID of work set, no check of currentChgFlag) 	<p>plmMoaMpaInfo (PlmUserContextMoaMpa) :</p>	<ul style="list-style-type: none"> ▫ moaMpaConfFlag (not changeable by current user) ▫ currentJob EDB_ID of the job, access will be checked by Agile e6 server ▫ currentProjectOrOrganisation - ignored in the request, filled by the response ▫ currentProjectOrOrganisationCid - ignored in the request, filled by the response ▫ currentRole - ignored in the request, filled by the response 	<p>plmDFMInfo (PlmUserContextDFM):</p>	<ul style="list-style-type: none"> ▫ dFMConfigFlag (not changeable by current user) ▫ site (Reserved for future use)
<p>plmUserInfo (PlmUserContextUserInfo):</p>	<ul style="list-style-type: none"> ▫ userName (not changeable by current user) ▫ userID (not changeable by current user) ▫ group (Reserved for future use : currently there is no API to implement it.) ▫ groupID (Reserved for future use : currently there is no API to implement it.) ▫ userLanguage (e.g. ENG, GER, FRA) ▫ userLocale (always changed with user language) 										
<p>plmViewInfo (PlmUserContextView):</p>	<ul style="list-style-type: none"> ▫ preliminaryFlag (Boolean.TRUE, Boolean.FALSE) ▫ referenceDate (in the form of yyyy-MM-dd HH:mm:ss) ▫ versionViewTitle (ignored) ▫ versionView (PlmVersionViewEnum) 										
<p>plmChangeManagementInfo (PlmUserContextChg):</p>	<ul style="list-style-type: none"> ▫ currentChgFlag (not changeable by current user) ▫ currentWorkOrder (EDB-ID of work order, no check of currentChgFlag) ▫ currentWorkSet (EDB-ID of work set, no check of currentChgFlag) 										
<p>plmMoaMpaInfo (PlmUserContextMoaMpa) :</p>	<ul style="list-style-type: none"> ▫ moaMpaConfFlag (not changeable by current user) ▫ currentJob EDB_ID of the job, access will be checked by Agile e6 server ▫ currentProjectOrOrganisation - ignored in the request, filled by the response ▫ currentProjectOrOrganisationCid - ignored in the request, filled by the response ▫ currentRole - ignored in the request, filled by the response 										
<p>plmDFMInfo (PlmUserContextDFM):</p>	<ul style="list-style-type: none"> ▫ dFMConfigFlag (not changeable by current user) ▫ site (Reserved for future use) 										

getDefault

Service	To get the contents of a PLM Default value.							
Usage	The request object carries only the default name. In case the value cannot be parsed (e.g. letter instead of number as integer), this value is taken as 'null'.							
Request Type	GetDefaultRequestType <ul style="list-style-type: none"> ▫ defaultName (String): Name of the DataView default. ▫ messageId (String): ID to be returned in the response (optional) ▫ messageName (String) : Name to be returned in the response (optional) 							
Response Type	GetDefaultResponseType <ul style="list-style-type: none"> ▫ Status Code <table border="1" style="margin-left: 20px; width: 100%;"> <tr> <td>SUCCESS</td> <td></td> </tr> <tr> <td>PARTIAL_SUCCESS</td> <td>Typed default value is NULL</td> </tr> <tr> <td>FAILURE</td> <td>Default "Non-existent" - PLM Object is NULL~</td> </tr> </table> ▫ PLM Default as complex data type (String, Integer, Float, Boolean) 		SUCCESS		PARTIAL_SUCCESS	Typed default value is NULL	FAILURE	Default "Non-existent" - PLM Object is NULL~
SUCCESS								
PARTIAL_SUCCESS	Typed default value is NULL							
FAILURE	Default "Non-existent" - PLM Object is NULL~							