
PeopleSoft 9.1 PeopleBook: Integration Interfaces

May 2012

Copyright © 2001, 2012, Oracle and/or its affiliates. All rights reserved.

Trademark Notice

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

License Restrictions Warranty/Consequential Damages Disclaimer

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Third Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface

Integration Interfaces Preface	xi
Overview of Integration Interfaces	xi
PeopleBooks and the PeopleSoft Online Library	xi

Part 1

Credit Card Interfaces

Chapter 1

Setting Up the Credit Card Interface	3
Understanding XML-Based Integration Using Integration Broker	3
Setting Up Credit Card Integration for Integration Broker	12
Configuring Integration for Integration Broker	12
Setting Up Credit Card Interface Elements	15
Pages Used to Set Up Credit Card Interface Elements	15
Defining Connection Parameters	16
Defining Accepted Credit Card Types	18
Testing the Credit Card Interface	19
Testing Credit Card Transactions	20

Part 2

PeopleSoft Directory Interfaces

Chapter 2

Using PeopleSoft Directory Interface	27
Understanding PeopleSoft Directory Interface	27
Understanding Implementing PeopleSoft Directory Interface	28
Overview of Using PeopleSoft Directory Interface	29

Setting Up in PeopleSoft Application Designer and PeopleSoft Integration Broker	29
Using the Directory Configurations Component	30
Common Elements Used in This Chapter	31
Defining and Configuring the Directory	31
Pages Used to Define and Configure the Directory	32
Configuring the Directory Connection	32
Caching the Schema	35
Deleting the Directory Configuration	36
(Optional) Setting Up Directory Authentication	36
Pages Used to Set Up Directory Authentication	37
Using Map Authentication	37
Viewing User Properties	38
Setting Up Mappings	40
Understanding Mapping	40
Pages Used to Set Up Mappings	40
Creating Mappings	41
Modifying the Distinguished Name	44
Specifying Distinguished Name Details	45
Translating or Performing Functions with Database Values	46
Specifying Distinguished Name Defaults	49
Mapping Data to Directory Object Class Attributes	50
Locating Delivered Messages	52
(Optional) Setting Up Entry Membership Rules	52
Pages Used to Set Up Entry Membership Rules	52
Creating Entry Definitions	53
Specifying Entry Membership Rules	55
Loading Data into the Directory	56
Understanding Directory Load Behavior	57
Loading the Directory with PeopleSoft Data	57

Chapter 3

Reviewing Directory Data and Generating Reports	59
Reviewing LDAP Directory Data	59
Pages Used to Review LDAP Directory Data	59
Running a Directory Audit	59
Running a Directory Search	60
Viewing PeopleSoft Directory Interface Reports	62
Pages Used to View PeopleSoft Directory Interface Reports	63
Viewing the Directory Audit Report	63
Viewing the Business Interlink Status Report	64
Managing Transaction Audit History	64
Pages Used to Manage Transaction Audit History	65

Generating a Transaction History Report	65
Searching for a Transaction History	66
Purging Transaction History	68

Part 3

Enterprise Integration Utilities

Chapter 4

Using the Error Handling Utility	73
Understanding the Error Handling Utility	73
Error Management Process	73
Setting Up and Maintaining Message Errors	75
Pages Used to Set Up and Maintain Message Errors	75
Creating Error-Correction Pages	75
Setting Up the Error Handling Utility	77
Setting Up Row Security	78
Setting Up Workflow Notification in PeopleSoft Application Designer	79
Testing the Error Handling Utility	79
Correcting Message Errors	80
Understanding the Workflow Notification Process	81
Correcting Message Errors	81

Chapter 5

Using the Publish Utility	83
Understanding the Publish Utility	83
Understanding Publishing Rules	84
Pre-Processing and Post-Processing	84
Data Sources	85
Message Chunking	85
Record Mapping	86
Output Format	86
Publishing Data in Related Languages	87
Prerequisites for Using the Publish Utility	88
Common Elements Used in This Chapter	88
Using Sequential and Parallel Processing	89
Understanding Using Sequential and Parallel Processing	89
Prerequisites for Using Parallel Processing	90

Using Sequential Processing	90
Using Parallel Processing	90
Changing Processing Modes	91
Assigning Full Table Publishing Rules	91
Pages Used to Assign Full Table Publishing Rules	91
Associating Full Table Publishing Rules with Messages	92
Mapping Full Table Message Records to Other Records	93
Specifying Languages in Which to Publish Messages	94
Assigning Batch Publishing Rules	94
Pages Used to Assign Batch Publishing Rules	95
Associating Batch Publishing Rules with Messages	95
Mapping Batch Publishing Message Records to Other Records	96
Assigning Application Programs to Batch Publishing Rules	97
Performing Pre-Processing and Post-Processing Tasks	98
Setting General Pre-Processing and Post-Processing Options	98
Coding Pre-Processing and Post-Processing Tasks	99
Setting Up Message Chunking	102
Understanding Message Chunking	102
Pages Used to Set Up Message Chunking	103
Identifying When to Use Chunking	104
Selecting Chunking Fields	104
Creating Chunking Rules	106
Defining the Chunking Rule Description	107
Maintaining Chunking Data for Business Units	108
Maintaining Chunking Data for SetIDs	109
Maintaining Chunking Data for Record Groups	110
Adding Nodes to Existing Chunking Rules	111
Assigning Business Units or SetIDs to a Chunking Rule	112
Assigning Chunking Rules to a Business Unit	113
Assigning Chunking Rules to a SetID	114
Creating Custom Chunking Tables	114
Creating a Custom Chunking Table	115
Creating a View for the Component Search Record	115
Creating Maintenance Pages	116
Creating a Component	117
Creating Routing PeopleCode	117

Chapter 6

Using the Inbound Data Error Scan Utility	121
Understanding the Inbound Data Error Scan Utility	121
Running the Inbound Data Error Scan Utility	121
Launching the Inbound Data Error Scan Utility	121

Chapter 7

Using the Effective Date Publish Utility	123
Understanding the Effective Date Publish Utility	123
Performing a Full Data Publish of Current Effective Data	125
Pages Used to Perform a Full Data Publish of Current Effective Data	125
Creating Effective-Dated Messages	126
Creating the Service Operation	127
Defining the Node and Target Connector	127
Defining Chunking Rules and Ordering Views	128
Creating Publish Rule Definitions	128
Creating Run Controls for the Full Data Publish Program	129
Defining Routing	130
Publishing Incremental Messages of Current Effective Data	131
Creating Service Operations for Publishing Incremental Messages of Current Effective Data	131
Creating Subscription Processes That Open the Generic Effective-Dated Delay Function	131
Publishing Effective-Dated Rows from the Delay Table	132
Understanding Effective-Dated Row Publishing	132
Page Used to Publish Effective-Dated Rows from the Delay Table	133
Running the Effective Date Publish Utility	133
Publishing Effective-Dated Rows and Prior-Dated Rows from the Delay Table	134
Understanding Publishing Effective-Dated Rows and Prior-Dated Rows from the Delay Table	134
Page Used to Publish Effective-Dated Rows and Prior-Dated Rows from the Delay Table	134
Running the Effective Date and Prior Publish Utility	134

Chapter 8

Using the Flat File Utility	137
Understanding the Flat File Utility	137
Processing Inbound Flat Files	138
Initiating File Processing	139
Pages Used to Initiate File Processing	139
Setting Up Inbound Flat File Processing	139
Initiating Inbound Flat File Processing	142
Testing Inbound Flat File Processing	144

Chapter 9

Using the XML Schema Utility	145
Understanding the XML Schema Utility	145

Generating the XML Schema	145
Page Used to Generate the XML Schema	146
Generating the XML Schema	146
Interpreting Sample Output	147
Chapter 10	
Using Desktop Integration	155
Understanding Desktop Integration	155
Prerequisites	156
Setting Up Desktop Integration	157
Pages Used to Set Up Desktop Integration	157
Setting Up the Integration Broker	157
Setting Up Pages and Web Service Security	159
Setting Up the System	160
Setting Up Tasks	161
Pages Used to Set Up Tasks	162
Setting Up Task Registration	162
Setting Up the Task Queue	164
Composing Task Contents	167
Registering Address Books	168
Understanding Address Book Registration	168
Page Used to Register Your Address Book	169
Registering Your Address Book	169
Registering Internal Address Books	171
Registering an Internal Address Book	172
Setting Up Appointments	173
Pages Used to Set Up Appointments	173
Setting Up Appointment Registration	173
Reviewing the Appointment Queue	176
Setting Up Meeting Scheduling Criteria	178
Setting Up Meeting Criteria	179
Setting Up File Transfers	183
Pages Used to Set Up File Transfers	183
Setting Up File Transfer Registration	183
Reviewing the File Transfer Queue	185
Defining Dynamic Displays	186
Understanding Dynamic Displays	186
Pages Used to Define Dynamic Displays	186
Defining General Dynamic Display Options	187
Defining Field and Layout Options for Dynamic Displays	191
Using the Display Log	194
Page Used to View the Display Log	194

Viewing the Display Log	194
Using the PeopleSoft Outlook Menu	196
Understanding the PeopleSoft and Outlook Integration	196
Defining Settings and Options	196
Using the PeopleSoft Scheduler and Scheduling Assistant	201
Replicating Appointments, Meetings, Tasks and Address Books	204

Part 4

Enterprise Integration

Chapter 11

Understanding Enterprise Integration	209
Understanding PeopleSoft Business Interlinks	209
Understanding PeopleSoft Component Interfaces	209
Understanding File Layouts	209
Understanding PeopleSoft Integration Broker	210

Chapter 12

Understanding Integration Points	211
Overview of Integration Points	211

Chapter 13

Activating Integration Points	213
Setting Up PeopleSoft Integration Points	213
Pages Used to Set Up PeopleSoft Integration Points	213
Setting Up Publication Rules	214
Mapping Nodes to a Chunking Rule	215
Assigning Business Units or SetIDs to a Chunking Rule	216
Specifying OnRoute PeopleCode	216
Setting Up Related Languages	217
Understanding Related Language Tables	217
Understanding Related Language Guidelines for Messaging	218
Interpreting Component Processor Behavior	219
Publishing a Message from a Component	220
Publishing a Message from Batch Programs	220

Subscribing to Data in a PeopleSoft Multilingual Environment	220
Subscribing to Data in a Non-Multilingual Environment	220
Examining Related-Language Messaging Scenarios	222
Publishing a Non-Base Language Message to a Subscribing System with a Different Base Language and No Prior Data	222
Switching the Preferred Language to Japanese and Updating the Same Employee's Name and Address	222

Appendix A

Integration Point Naming Standards	225
Standard Action and Event Verbs	225
Standard Business Object Nouns	227

Appendix B

PeopleSoft Design Patterns	231
List of Design Patterns	231

Index	235
--------------------	------------

Integration Interfaces Preface

This preface provides an overview of Oracle's PeopleSoft Enterprise Components Integration Interfaces documentation included in this PeopleBook.

Overview of Integration Interfaces

This PeopleBook describes PeopleSoft integration technologies related to integrations from one PeopleSoft product to another, as well as integration between PeopleSoft and third-party production. The features and utilities that you use will depend on your PeopleSoft application.

This PeopleBook includes the following parts:

- *Credit Card Interfaces*. Describes how to use the PeopleSoft credit card processing interface to integrate with credit card processing vendors.
- *PeopleSoft Directory Interfaces*. Describes how to enhance the integration between PeopleSoft and your LDAP directory service by providing a single, centralized user profile for PeopleSoft and non-PeopleSoft applications.
- *Enterprise Integration*. Provides an overview of PeopleSoft integration technologies for integration between PeopleSoft and third-party integration partners. Also describes how to set up and activate integration points.
- *Enterprise Integration Utilities*. Describes several PeopleSoft utilities that you can use to implement and troubleshoot integrations.

Note. Some of the page elements and colors that your product uses may differ from the screen shots presented in this PeopleBook. This book uses a generic style sheet for the purposes of illustration only.

PeopleBooks and the PeopleSoft Online Library

A companion PeopleBook called *PeopleBooks and the PeopleSoft Online Library* contains general information, including:

- Understanding the PeopleSoft online library and related documentation.
- How to send PeopleSoft documentation comments and suggestions to Oracle.
- How to access hosted PeopleBooks, downloadable HTML PeopleBooks, and downloadable PDF PeopleBooks as well as documentation updates.
- Understanding PeopleBook structure.
- Typographical conventions and visual cues used in PeopleBooks.
- ISO country codes and currency codes.

- PeopleBooks that are common across multiple applications.
- Common elements used in PeopleBooks.
- Navigating the PeopleBooks interface and searching the PeopleSoft online library.
- Displaying and printing screen shots and graphics in PeopleBooks.
- How to manage the locally installed PeopleSoft online library, including web site folders.
- Understanding documentation integration and how to integrate customized documentation into the library.
- Application abbreviations found in application fields.

You can find *PeopleBooks and the PeopleSoft Online Library* in the online PeopleBooks Library for your PeopleTools release.

Part 1

Credit Card Interfaces

Chapter 1

Setting Up the Credit Card Interface

Chapter 1

Setting Up the Credit Card Interface

This chapter provides an overview of credit card integration using Integration Broker and discusses how to:

- Set up credit card integration for Integration Broker.
- Set up credit card interface elements.

See Also

PeopleTools: PeopleSoft Integration Broker PeopleBook

Understanding XML-Based Integration Using Integration Broker


You can use PeopleSoft Integration Broker to process your PeopleSoft credit card transactions with the third-party credit card processing vendor of your choice. Oracle delivers messages and a synchronous service for you to use to set up a synchronous connection with your third-party vendor. Because each third-party vendor requires a different format for communication, PeopleSoft applications do not deliver transformations to your third-party vendor. This is because each third-party vendor has different requirements for inputs and outputs to their services. Therefore, part of setting up an integration involves writing your own transformation programs for the request and response message. The transformation programs are a mapping between the fields in the PeopleSoft system and the fields in your third-party vendor's service. You also need to set up a node in the PeopleSoft application to process the response from your third-party vendor.

Oracle delivers XML messages for use with XML-based credit card processing vendors. You must build your own XML message transformation into the format that the vendor is expecting.

You can use PeopleSoft Application Engine to perform your transformations. You use the delivered EOEC_CCI_SYNC message for the request transaction and the delivered EOEC_CCI_RESPONSE message for the response transaction. The messages are detailed later in this section.

Note. If you have upgraded from a PeopleTools 8.47 or earlier release, the upgrade program creates service operations for these messages. The service operation names and message names are the same.

The diagram shows the process flow for integration with a third-party credit processing vendor.



EOEC_CCI_SYNC and EOEC_CCI_RESPONSE is used to integrate with a third-party credit processing vendor

EOEC_CCI_Sync Message

The EOEC_CCI_SYNC message is a synchronous request that the credit card interface sends to the third-party vendor. The request can be for an authorize, bill, authorize and bill, credit transaction, or authorization reversal. The PeopleCode that supports this message is located in App Package EOEC_CCI. The following tables describe the request fields and how they are populated by the PeopleSoft system.

Level 0 Record: EOEC_CCI_XMLPAY:

Message field	Alias	Populated with
EOEC_CCI_UNIQUE_ID	UNIQUEID	Unique ID generated for each transaction.

Level 1 Record: EOEC_CCI_RQST:

Message field	Alias	Populated with
EOEC_CCI_MERCHANT	VENDOR	Populated from the merchant ID set up on the Credit Card Interface Installation page.
EOEC_CCI_PARTNER	PARTNER	Hardcoded to "PeopleSoft".

Level 2 Record: EOEC_CCI_TRANS:

Message field	Alias	Populated with
EOEC_CCI_TRANSID	TRANSACTION_ID	Either blank or contains the request ID of a previous transaction (such as a prior authorization transaction).

Message field	Alias	Populated with
EOEC_CCI_MERCH_REF	TRANSACTION_CUSTREF	Contains a reference to the transaction such as an order or invoice number.
EOEC_CCI_RQSTTOKEN	N/A	Either blank or contains the request token of a previous transaction (such as a prior authorization transaction).

Level 3 Record: EOEC_CCI_TRNTYP:

Message field	Alias	Populated with
EOEC_CCI_TRANSACT	TRANSTYPE	The service to be performed: <ul style="list-style-type: none"> • 1=Authorize Only • 2=Authorize & Bill • 3=Bill Only • 4=Credit • 5=Authorize Reversal

Level 4 Record: EOEC_CCI_PAYDAT:

Message field	Alias	Populated with
EOEC_CCI_TRANSACT	N/A	N/A

Level 5 Record: EOEC_CCI_INV:

Message field	Alias	Populated with
EOEC_CCI_INV_NUM	INVNUM	Either blank or contains the request ID of a pervious transaction (such as a prior authorization transaction). Oracle recommends that you use TRANSACTION_ID instead of INVNUM in transformation programs because the field is only 20.
EOEC_DATE		N/A
DESCR254	DESCRIPTION	Hardcoded to "Description".
EOEC_CCI_DISC_AMT	DISCOUNTAMT	N/A
EOEC_CCI_SHIP_AMT	SHIPAMT	N/A
EOEC_CCI_DUTY_AMT	DUTYAMT	N/A

Message field	Alias	Populated with
EOEC_CCI_TAX_AMT	TAXAMT	N/A
EOEC_CCI_TAX_INCL	NATIONALTAXINCL	N/A
EOEC_CCI_TOTAL_AMT	TOTALAMT	The total amount of the transaction.
EOEC_CCI_COMMENT	COMMENT	N/A
CURRENCY_CD	N/A	N/A

Level 6 Record: EOEC_CCI_BILLFM:

Message field	Alias	Populated with
EOEC_CCI_FULLNAME	NAME	N/A
EOEC_EMAIL_ADDR	EMAIL	N/A
PHONE	N/A	N/A
FAX	N/A	N/A
URL	N/A	N/A

Level 7 Record: EOEC_CCI_ADDR1:

Message field	Alias	Populated with
ADDRESS1	STREET	N/A
ADDRESS2	N/A	N/A
ADDRESS3	N/A	N/A
ADDRESS4	N/A	N/A
CITY	N/A	N/A
STATE	N/A	N/A
POSTAL	ZIP	N/A
COUNTRY	N/A	N/A

Level 6 Record: EOEC_CCI_BILLTO:

Message field	Alias	Populated with
EOEC_CCI_CUSTID	CUSTOMERID	N/A
EOEC_CCI_FULLNAME	NAME	N/A
EOEC_EMAIL_ADDR	EMAIL	Email address of the consumer.
PHONE	N/A	Telephone number of the consumer.
FAX	N/A	N/A
EOEC_CCI_CUSTCODE	CUSTCODE	N/A
EOEC_CCI_PO_NUM	PONUM	N/A
EOEC_CCI_TAXEXEMPT	TAXEXEMPT	N/A

Level 7 Record: EOEC_CCI_ADDR2:

Message field	Alias	Populated with
ADDRESS1	STREET	Street address of the consumer.
ADDRESS2	N/A	N/A
ADDRESS3	N/A	N/A
ADDRESS4	N/A	N/A
CITY	N/A	City address of the consumer.
STATE	N/A	State address of the consumer.
POSTAL	ZIP	Postal address of the consumer.
COUNTRY	N/A	Country address of the consumer.

Level 6 Record: EOEC_CCI_SHIPFM:

Message field	Alias	Populated with
EOEC_CCI_FULLNAME	NAME	N/A
EOEC_EMAIL_ADDR	EMAIL	N/A
PHONE	N/A	N/A
FAX	N/A	N/A

Level 7 Record: EOEC_CCI_ADDR3:

Message field	Alias	Populated with
ADDRESS1	STREET	N/A
ADDRESS2	N/A	N/A
ADDRESS3	N/A	N/A
ADDRESS4	N/A	N/A
CITY	N/A	N/A
STATE	N/A	N/A
POSTAL	ZIP	N/A
COUNTRY	N/A	N/A

Level 6 Record: EOEC_CCI_SHIPTO:

Message field	Alias	Populated with
EOEC_CCI_FULLNAME	NAME	N/A
EOEC_EMAIL_ADDR	EMAIL	N/A
PHONE	N/A	N/A
FAX	N/A	N/A

Level 7 Record: EOEC_CCI_ADDR4:

Message field	Alias	Populated with
ADDRESS1	STREET	N/A
ADDRESS2	N/A	N/A
ADDRESS3	N/A	N/A
ADDRESS4	N/A	N/A
CITY	N/A	N/A
STATE	N/A	N/A
POSTAL	ZIP	N/A

Message field	Alias	Populated with
COUNTRY	N/A	N/A

Level 6 Record: EOEC_CCI_ITEM:

Message field	Alias	Populated with
EOEC_CCI_ITEM NUM	ITEM_NUMBER	N/A
EOEC_CCI_SKU	SKU	N/A
EOEC_CCI_UPC	UPC	N/A
DESCR254	DESCRIPTION	N/A
EOEC_CCI_QTY AMT TOTALAMT	QUANTITY	N/A
EOEC_CCI_UOM	UNITOFMEASURE	N/A
EOEC_CCI_UNITPRICE	UNITPRICE	N/A
EOEC__CCI_EXTAMT	EXTAMT	N/A
EOEC_CCI_DISC_AMT	DISCOUNTAMT	N/A
EOEC_CCI_TAX_AMT	TAXAMT _	N/A
EOEC_CCI_TOTAL	TOTALAMT	N/A

Level 4 Record: EOEC_CCI_TENDER:

Message field	Alias	Populated with
EOEC_CCI_TRANSACT	N/A	N/A

Level 5 Record: EOEC_CCI_CARD:

<i>Message field</i>	<i>Alias</i>	<i>Populated with</i>
EOEC_CCI_TYPE	CARDTYPE	Two-character code for the type of card used in the transaction. <ul style="list-style-type: none"> • 01=Visa • 02=MasterCard • 03=Diners Club • 04=American Express • 05=Discover
EOEC_CCI_NUMBER	CARDNUM	Credit card number used in the transaction.
EOEC_CCI_EXPYR	EXPYR	Expiration year of the card.
EOEC_CCI_EXPMO	EXPMO	Expiration month of the card.
EOEC_CCI_CVNUM	CVNUM	Card verification number.
EOEC_CCI_MAGDATA	MAGDATA	N/A
EOEC_CCI_FULLNAME	NAMEONCARD	First and last name of the consumer.
EOEC_CCI_FNAME	FIRSTNAME	First name of the consumer.
EOEC_CCI_LNAME	LASTNAME	Last name of the consumer.

Level 5 Record: EOEC_CCI_STATUS:

<i>Message field</i>	<i>Alias</i>	<i>Populated with</i>
EOEC_CCI_TRANS_REF	PNREF	N/A

Note. When writing your transformation program, use the alias name to reference the fields. When you view the "Request — Original" text of the message, the alias name is displayed.

EOEC_CCI_RESPONSE Message

The EOEC_CCI_RESPONSE message is a response to the request that the credit card interface receives from the third-party vendor. Your transformation should populate the response message fields as shown in the tables.

Level 0 Record: EOEC_CCI_XMLRSP:

<i>Message field</i>	<i>Alias</i>	<i>Populate with</i>
EOEC_CCI_UNIQUE_ID	UNIQUEID	N/A

Level 1 Record: EOEC_CCI_RSPNS:

Message field	Alias	Populate with
EOEC_CCI_MERCHANT	VENDOR	N/A
EOEC_CCI_PARTNER	PARTNER	N/A

Level 2 Record: EOEC_CCI_TRRSLT:

Message field	Alias	Populate with
EOEC_CCI_TRANSID	TRANSACTIONID	The request ID or identifier returned from the third-party vendor.
EOEC_CCI_RESULT	RESULT	<p>Map the appropriate return code for the transmission result in the following way:</p> <ul style="list-style-type: none"> • 0=Approve (no error) • 100-199=Decline <p>For self-service application, you can display the vendor return message to self-service users.</p> <ul style="list-style-type: none"> • 200-299=Decline <p>For self-service application, do not display the vendor return message to self-service users.</p> <ul style="list-style-type: none"> • 300-399=Connection Error
EOEC_CCI_AVS	AVS	N/A
EOEC_CCI_CVRESULT	CVRESULT	N/A
EOEC_CCI_RET_MSG	MESSAGE	Populate this with a text response from the vendor or this can be populated with text that explains to the user why a transaction was not successful.
EOEC_CCI_TRANS_REF	PNREF	N/A
EOEC_RET_AUTHCD	AUTHCODE	This should be populated with the authorization code returned from the vendor.
EOEC_CCI_HOSTCODE	HOSTCODE	N/A
EOEC_CCI_HOST_URL	HOSTURL	N/A

<i>Message field</i>	<i>Alias</i>	<i>Populate with</i>
EOEC_CCI_ORIGRSLT	ORIGRESULT	N/A
EOEC_RET_STATUS	TRSTATUS	N/A
EOEC_RET_STATUSMSG	N/A	N/A
EOEC_RET_AUTHDTTM	N/A	N/A
EOEC_CCI_RQSTTOKEN	N/A	N/A

Level 3 Record: EOEC_CCI_AVRSLT

<i>Message field</i>	<i>Alias</i>	<i>Populate with</i>
EOEC_MATCH_STREET	STREETMATCH	N/A
EOEC_MATCH_ZIP	ZIPMATCH	N/A

When writing the transformation program, use the alias name to reference the fields.

Note. The alias name is shown in the "Response — Original" message from within the Service Operations Monitor.

Agents can then process credit cards using their application-specific credit card transaction page to submit the transaction to the vendor for authorization, billing, authorization and billing, or credit. You can choose which types of transactions to permit.

See Also

PeopleTools: PeopleSoft Integration Broker PeopleBook

PeopleTools: Security Administration PeopleBook, "Setting up Digital Certificates and Single Signon"

PeopleTools: PeopleTools Portal Technologies PeopleBook

Setting Up Credit Card Integration for Integration Broker

This section discusses how to configure integration for Integration Broker.

Configuring Integration for Integration Broker

To set up Integration Broker for credit card processing:

1. Define the Integration Broker Gateway if it's not already done.

2. Activate the delivered service (EOEC_CCI_SYNC) that is used for the credit card integration.
3. Set up an external node to use when using the XML-based interface to which the XML messages should be sent and to indicate where the processor is located.

Also specify the authentication option that you arranged with the credit card processor.

4. Set up routings.

Use the Routings tab in the Node component to add the EOEC_CCI_SYNC service to the node. To see the XML data before and after transformations, set the log detail to Header & Detail. This is helpful when troubleshooting your new integration.

5. Test the integration.

You can use the test component described below.

If you receive error messages when using Integration Broker, see the Troubleshooting the Integration Broker Setup section below:

Troubleshooting the Integration Broker Setup

Several sources of information are available when the setup is not successful. These include but are not limited to:

- Error messages stored on the message instance (view with the message monitor).
- IB gateway error log (<http://<GatewayMachine>:<Port>/PSIGW/errorLog.html>).
- IB gateway message log (<http://<GatewayMachine>:<Port>/PSIGW/msgLog.html>).
- Application server log for the active IB domain server on the database.
- Web server logs.

You can also do the following:

- Increase the log fence on the gateway properties file. This file is located in the following directory:
PS_CFG_HOME\webserv\

If you set the log fence to five in the integration Gateway properties, you will receive more details in the error and message logs.

- Check the Service Operations Monitor to view the XML messages before and after the transformations (PeopleTools, Integration Broker, Monitor, Service Operations, Synchronous Services).

- Check the Header and Detail logs on the Synchronous Detail page (PeopleTools, Integration Broker, Service Operations Monitor, Monitor, Synchronous Details).

Problems are usually due to incorrect transformations between the two systems. Use these logs to ensure that your transformations are correct.

Your Response-Transformed message structure should look similar to this:

```
<?xml version="1.0"?>
<EOEC_CCI_RESPONSE xmlns:c="yourcompany.com">
  <FieldTypes>
    <EOEC_CCI_XMLRSP class="R"/>
    <EOEC_CCI_TRRSLT class="R">
      <RESULT type="NUMBER"/>
    </EOEC_CCI_TRRSLT>
    <EOEC_CCI_AVRSLT class="R"/>
    <EOEC_CCI_RSPNS class="R"/>
    <PSCAMA class="R"/>
  </FieldTypes>
  <MsgData>
    <Transaction>
      <EOEC_CCI_XMLRSP class="R">
        <UNIQUEID/>
        <EOEC_CCI_RSPNS class="R">
          <VENDOR/>
          <PARTNER/>
          <EOEC_CCI_TRRSLT class="R">
            <TRANSACTIONID>177</TRANSACTIONID>
            <RESULT>0</RESULT>
            <AVS/>
            <CVRESULT/>
            <MESSAGE/>
            <AUTHCODE>123456</AUTHCODE>
            <HOSTCODE/>
            <HOSTURL/>
            <ORIGRESULT/>
            <TRSTATUS/>
            <EOEC_RET_STATUSMSG/>
            <EOEC_RET_AUTHDTTM/>
            <EOEC_CCI_AVRSLT class="R">
              <STREETMATCH/>
            </EOEC_CCI_AVRSLT>
          </EOEC_CCI_TRRSLT>
        </EOEC_CCI_RSPNS>
      </EOEC_CCI_XMLRSP>
    </Transaction>
  </MsgData>
</EOEC_CCI_RESPONSE>
```

See Also

PeopleTools: PeopleSoft Integration Broker PeopleBook

PeopleTools: PeopleSoft Integration Broker Administration PeopleBook

PeopleTools: Security Administration PeopleBook, "Setting up Digital Certificates and Single Signon"

PeopleTools: PeopleTools Portal Technologies PeopleBook

Setting Up Credit Card Interface Elements

This section discusses how to:

- Define connection parameters.
- Define accepted credit card types.
- Test the credit card interface.
- Test credit card transactions.

Note. The information in this section is used for credit card integration using Integration Broker, or any manual processing that you have set up for credit card processing vendors.

Pages Used to Set Up Credit Card Interface Elements

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Credit Card Interface Installation	EOEC_CCI_INSTAL	Enterprise Components, Component Configurations, Credit Card Interface, Setup	Define connection parameters for credit card processing calls to a third-party vendor. Before you set up credit card processing options, establish your merchant account with a third-party vendor.
Card Type	EOEC_CCI_CARDTYPE	Enterprise Components, Component Configurations, Credit Card Interface, Credit Card Types	Define the types of credit cards you accept for credit card processing.
Test Credit Card Interface - Card Entry/Display	EOEC_CCI_TEST	Enterprise Components, Component Configurations, Credit Card Interface, Test Credit Card Interface, Card Entry/Display	Enter test credit card information that you can submit to verify that your credit card processing is functioning properly.
Test Credit Card Interface - Transaction	EOEC_CCI_TRANSACTION	Enterprise Components, Component Configurations, Credit Card Interface, Test Credit Card Interface, Transaction	Enter test credit card transaction information that you can submit to verify that your credit card processing is functioning properly.

Defining Connection Parameters

Access the Credit Card Interface Installation page (Enterprise Components, Component Configurations, Credit Card Interface, Setup).

Use the Credit Card Interface Installation (EOEC_CCI_INSTAL) page to set up connection parameters for credit card processing calls to a third-party vendor.

Note. Before you set up credit card processing options, establish your merchant account with a third-party vendor.

Note. Check the installation documentation for the product you are installing for specific details on setting up credit card interfaces.

Credit Card Interface Installation

Credit Card Merchant ID:

Credit Card Hist. Backup Days:

Credit Card Tracing: ▼

On-line Transmission Retries:

Address Verification Flag: ▼

Type of Interface: ▼

Allowed Transaction Types

***Credit Card Transaction Type:** ▼ **Process Credits?**

Connection Parameters

Credit Card Processing Server:

Credit Card IP Override:

Credit Card Interface Installation page

Verify connection requirements with your vendor.

Credit Card Merchant ID Enter the merchant ID supplied by your vendor.

Credit Card Hist. Backup Days (credit card history backup days) If you create a process that archives history records, specify the number of days that you retain credit card authorization history records.

Credit Card Tracing This field is currently not used.

- On-line Transmission Retries** Enter a value from 0 through 9 to specify how many times the system should attempt to retransmit transactions in the event of transmission failure.
- Address Verification Flag** Credit card transmissions can fail authorization if the address that you send doesn't exactly match the billing address for the credit card. Select from:
Add Vf ON (address verification on): Transactions fail when the address that you send does not match the credit card billing address. This is the default value.
Add Vf OFF (address verification off): Transactions do not fail when the address that you send does not match the billing address on the credit card.
- Type of Interface** Select to use *Integration Broker* as the interface type.

Allowed Transaction Types

- Credit Card Transaction Type** Select the types of transactions that your agents are allowed to submit. Disallowed transaction types are not available on the application-specific credit card transaction page. Select from:
Authorization Reversal: Your vendor can cancel the transaction after authorization and before payment is received. This makes the funds available if the transaction is cancelled.
Authorize Only: Your vendor verifies that the card is valid for the charge. For example, the customer has enough credit to pay for the order, the card is not stolen, and so forth. The vendor does not bill the credit card.
Bill Only: Your vendor bills the card without first verifying that the card is valid for the charge. Select this option if you have preauthorized the transaction and you want to submit the transaction for billing only.
Authorize and Bill: Your vendor performs both authorization and billing during the same transaction. The vendor charges the customer's credit card on receiving authorization.
Credit Only: Your vendor credits the customer's credit card.
- Process Credits** Select to permit agents to submit credit transactions as well as billing transactions. This option is available only if you selected either *Authorize and Bill* or *Bill Only* in the Credit Card Transaction Types field.

Connection Parameters

The third-party vendor that you integrate with will provide you with information to connect with their systems. Enter that information to enable your PeopleSoft system to make the connection when you submit a transaction for processing.

Defining Accepted Credit Card Types

Access the Card Type page (Enterprise Components, Component Configurations, Credit Card Interface, Credit Card Types).

Card Type

Credit Card Type:

Credit Card Name:

Credit Card Number Length: ***Credit Card Status:** ▼

Credit Card Valid Prefixes:

***Use Check Digit Algorithm:** ▼

Credit Card Expiration Days:

Card Type page

Use this page to define the types of credit cards that you accept for credit card processing.

Oracle delivers data for most popular credit card types. You can modify existing definitions and add new ones.

Credit Card Type	Enter a value for the credit card.
Credit Card Name	Enter a credit card name such as Visa or MasterCard. The name should match the credit card type so that you can identify the card without memorizing the credit card type codes.
Credit Card Number Length	Enter the card's standard credit card number length. Before transmitting a request to your vendor, the system validates the length of the credit card number against this number.
Credit Card Status	<p>Select <i>Active</i> if you accept this type of credit card. Select <i>Inactive</i> if you don't accept this type of credit card. Inactive credit card types do not appear on the application-specific credit card transaction page or in the Test Credit Card Interface component.</p> <p>The default value for this field is <i>Inactive</i>.</p>
Credit Card Valid Prefixes	<p>Enter all valid prefixes for this type of credit card. Enter multiple prefixes in comma-separated format with no spaces in between. The system removes any characters other than numbers and commas when you move to another field.</p> <p>Before transmitting a request to your vendor, the system validates that the credit card number starts with a valid prefix.</p>

Use Check Digit Algorithm Select *Y* (yes) to use the modulus (MOD) 10 check digit algorithm to validate credit card numbers before transmitting requests to your vendor. The MOD 10 check digit algorithm verifies whether card numbers you enter into the system are legitimate.

The default value for this field is *N*.

Credit Card Expiration Days Enter a four digit numerical expiration value.

Testing the Credit Card Interface

Access the Test Credit Card Interface - Card Entry/Display page (Enterprise Components, Component Configurations, Credit Card Interface, Test Credit Card Interface, Card Entry/Display).

Test Credit Card Interface - Card Entry/Display page

Use this page to enter test credit card information that you can submit to verify that your credit card processing is functioning properly.

The test that you can run on this page:

- Verifies that the card number you enter meets the requirements defined in the Credit Card Valid Prefixes field for the associated card type on the Card Type page.
- If you have set the Use Check Digit Algorithm field value to *Y*, verifies that the card number is valid based on the MOD 10 check digit algorithm.
- Verifies that you have entered values in the Exp. Month, Expiration Year, First Name and Last Name fields on this page.

You can use the following credit card sample data in your test transactions:

<i>Credit Card Type</i>	<i>Credit Card Number</i>
American Express	378282246310005
Diners Club/Carte Blanche	380000000000006
Discover	6011111111111117
MasterCard	5555555555554444
Visa	4111111111111111

Card Type	Select a card type to test. Available values are defined on the Credit Card Types page.
Credit Card Number	Enter the credit card number to test.
Exp. Month (expiration month), Expiration Year , Card Verification Number , First Name and Last Name	Enter card information to test. Card verification number is optional in running credit card tests.
Toggle Display	Click to switch between display-only and editable modes.
Test	Click to begin the test.
Test Results	The results of the test appear in this text box. If the card number is valid, the message VALID CARD NUMBER appears. If the card number is not valid, an explanatory message appears; the card number is incorrect or the card is expired, for example.

Testing Credit Card Transactions

Access the Credit Card Transaction Test page (Enterprise Components, Component Configurations, Credit Card Interface, Test Credit Card Interface, Transaction).

Test Credit Card Interface - Transaction page

Use this page to enter test credit card transaction information that you can submit to verify that your credit card processing is functioning properly.

The test that you can run on this page verifies that your environment is set up correctly to process online credit card transactions using XML Compliant integration.

Note. This does not test the environment that is set up for batch credit card transactions.

Sequence and Request ID	Display a combination of numbers that distinguishes the transaction from other transactions. The combination of numbers are similar to a run control or job number.
Amount	Enter a transaction amount and click the Look up button to select a transaction currency.
Token	The token is a response value that is returned from the Credit Card processing service. It is another validation that can be referenced in regards to a specific transaction.

Trans. Type (transaction type) Choose a transaction type to test:

Auth/Bill (Authorization/Bill): Perform both authorization and billing during the same transaction.

AuthRev (Authorization Reversal): Cancel the transaction after authorization and before payment is received.

Authorize: (default value) Verify that the card is valid for the charge.

Bill: Bill the card without first verifying that the card is valid for the charge.

Credit: Credit the customer's credit card.

Class ID

Select *TestTransaction* (the default) or one of the following interface types that has been specified on the Credit Card Interface Installation page.

ProcessBrokerTransaction: Select if you want to test your XML-based interface.

InterlinkTransaction: Select if you want to test your Business Interlink interface.

Process

Click to process the test transaction.

Return Code

Enter a return code to test whether proper error messages and results are returned. Available codes and their descriptions are discussed in the Return Codes section subsequently.

Test Results

The results of the transaction test appear in this text box. Test result interpretations are discussed in the following sections.

Return Codes

You can enter any of the following return codes and click Process to view the corresponding description and error message in the Test Results area. These return codes and their corresponding error messages can appear in multiple areas. For example, when you are using the Test Credit Card Interface component, they appear on this test page. In an application, they appear as appropriate for that application's method of interacting with the credit card interface.

Return Code	Description
-3	Error Opening Trace File
-4	Vendor Error – ICS_INIT failed
-5	Unsupported Service
-6	Credit card number is invalid

Return Code	Description
-7	Phone number is too long
-8	State field length is invalid
-9	Zip Code field is too long
-10	Amount must be greater than zero
-11	Vendor Error – ICS_SEND failed
-12	Decryption Failed
-15	Request ID is required
-16	Currency is required
-17	Phone is required
-18	Email ID is required
-19	Zip Code is required
-20	City is required
-21	Country code is required
-23	Address 1 is required
-99	Trace Run Only

Part 2

PeopleSoft Directory Interfaces

Chapter 2

Using PeopleSoft Directory Interface

Chapter 3

Reviewing Directory Data and Generating Reports

Chapter 2

Using PeopleSoft Directory Interface

This chapter provides an overview of PeopleSoft Directory Interface and discusses how to:

- Define and configure the directory.
- Set up directory authentication.
- Set up mappings.
- Set up entry membership rules.
- Load data into the directory.

Understanding PeopleSoft Directory Interface

PeopleSoft Directory Interface uses Lightweight Directory Access Protocol (LDAP) directory services to authenticate users of PeopleSoft applications.

PeopleSoft Directory Interface provides additional mappings and integration points, such as messages, that enable PeopleSoft data and LDAP data to stay synchronized. Most directory data, such as user ID, name, and email address, is also maintained in your PeopleSoft database. When you use PeopleSoft Directory Interface, you make selected PeopleSoft data available to the directory, and you maintain the data in the PeopleSoft database.

When information changes in the PeopleSoft database, PeopleSoft Directory Interface captures that updated information and automatically updates the equivalent information in the directory server, or it writes the updates to a file for you to apply at another time.

Understanding Data Mapping

PeopleSoft information is stored in tables according to a relational model. The information in your LDAP directory is stored in trees according to a hierarchical model. You use PeopleSoft Directory Interface to map selected PeopleSoft data to corresponding data in the directory service. When PeopleSoft Directory Interface receives user data from the PeopleSoft database, it can map the data objects to the corresponding objects in the directory.

For PeopleSoft Directory Interface to map PeopleSoft information to your directory, it needs information about the directory hierarchical structure, or *directory information tree*.

Entries are made up of a *distinguished name* (DN) and attribute and value pairs. The distinguished name identifies an entry's position in the tree, and the attributes hold the data that make up the entry.

Available attributes for an object class entry are specified in the directory schema. You must load the schema into the Directory Interface before you can map PeopleSoft data to the directory.

PeopleSoft Directory Interface mapping tables map LDAP attributes to PeopleSoft messages. Each message contains selected information about a PeopleSoft record and its fields.

Note. Refer to PeopleSoft application documentation for information about specific messages delivered by PeopleSoft applications.

Understanding Data Synchronization

After you have loaded PeopleSoft data into your LDAP directory, you can synchronize the data. To do this, use one of the following options:

- PeopleSoft Business Interlinks.

PeopleSoft Business Interlinks updates the data in real time, so that your directory information is always synchronized with PeopleSoft data.

- LDAP Data Interchange Format (LDIF) files.

You can load LDIF files as needed or defined by your system.

Note. The application server needs to be configured for receiving messages.

Delivered Business Interlinks

Oracle delivers the following business interlinks with PeopleSoft Directory Interface:

EO_DS_ADD	Adds a new entry to the directory by creating a distinguished name and its corresponding attributes.
EO_DS_BIND	Authenticates the information exchanged between the database and the directory.
EO_DS_DEL	Deletes an entry from the directory.
EO_DS_MODDN	Renames a directory entry. Changes its distinguished name by renaming the actual entry or changing its position in the directory entry.
EO_DS_MODIFY	Changes the attributes of an entry.
EO_DS_SEARCH	Searches for directory entries and their corresponding attributes.

Refer to *Enterprise PeopleTools 8.46 PeopleBook: PeopleSoft Business Interlinks* for more information on business interlinks.

Understanding Implementing PeopleSoft Directory Interface

Consider these PeopleSoft Directory Interface implementation guidelines for best results:

LDAP Searches	Some LDAP searches may generate LDAP referrals to other servers participating in your directory. You must be able to ping by hostname all servers in the directory from the application server. If any server is unreachable by hostname from the application server, you can add a line for the server to the hosts. Your directory information tree must have user entries at the leaf level. This is required when an entry needs to be moved from one branch to another. The entry needs to be at the leaf level so that the system can read user attributes, one of which is the password file on the application server.
Entry Limit	In the directory, configure the entry limit value to be larger than the number of rows that you expect will be returned. The default value is usually not sufficient.
Directory Tree	Your directory information tree must have user entries at the leaf level. This is required when an entry needs to be moved from one branch to another. The entry needs to be at the leaf level so that the system can read user attributes, one of which is the password.
Microsoft Active Directory	<p>The following items apply to implementations that use Microsoft Active Directory:</p> <ul style="list-style-type: none">• The registry key HKLM\System\CurrentControlSet\Services\NTDS\Parameters\Schema Update Allowed must be present and set to a nonzero DWORD on the Active Directory FSMO Role Owner.• When creating structural object classes in Microsoft Active Directory, you need to specify containment. PsftJobs can be children of the following classes of objects only: builtinDomain, organizationalUnit, and domainDNS.• You must add the server names in the Directory Setup component as they appear on the DNSHost Name attribute on the server entries under the CN=Sites entry.

Overview of Using PeopleSoft Directory Interface

This section briefly describes the steps needed to use PeopleSoft Directory Interface, including:

- Setting up in PeopleSoft Application Designer and PeopleSoft Integration Broker.
- Using the Directory Configurations component.

Setting Up in PeopleSoft Application Designer and PeopleSoft Integration Broker

Perform the following steps in PeopleSoft Application Designer and PeopleSoft Integration Broker.

Setting Up in PeopleSoft Application Designer

Access PeopleSoft Application Designer.

- Create authentication and user profile maps as needed.

If you are going to authenticate users with the directory server, a PeopleSoft user profile is required—that is, a row in the PSOPRDEFN table where PeopleSoft user information is stored. In this context, you cache LDAP user information inside your PeopleSoft system. Properties that you specify in the Mandatory and Optional Properties pages of the Mappings component are the columns in PSOPRDEFN that the system populates with values from your directory server. PeopleSoft applications use this cache of user information, not your directory server. Whenever a transaction requires user information, the application refers to the local PSOPRDEFN table instead of querying the directory server.

- Add Signon PeopleCode.

Directory authentication requires that Signon PeopleCode be enabled and configured with proper permissions. After a user signs onto the system and the Signon PeopleCode runs, the PeopleSoft system creates a row for the user in the user definition table by retrieving the LDAP information and creating a local cache. Signon PeopleCode maintains this row automatically and any changes made in the directory server are reproduced in the local cache. Using the Mappings component, set up mappings. To keep the data synchronized, you must map PeopleSoft data to the equivalent directory objects. PeopleSoft Directory Interface then associates the fields in the message with the attributes in the directory and updates the selected directory attributes with the field data from the message.

- Activate the DSCHNL channel.

Open the message channel and select *Run*.

See *PeopleTools: PeopleSoft Application Designer Developer's Guide*

Setting Up in PeopleSoft Integration Broker

Access PeopleSoft Integration Broker.

- Activate a relevant node.

This node should be the default local node.

- Define a service operation.

Note that the service operations, and messages to include in the service operations, depend on the application. For example, in an human resources implementation, you might want to include messages such as Dept, Location, Person, and Job in a service operation, in addition to core messages such as DSMINPUT.

See *PeopleTools: PeopleSoft Integration Broker PeopleBook*

Using the Directory Configurations Component

Access Directory Configurations component (PSDSSETUP) from the browser menu.

- Using the Directory Configurations component, configure the directory.

Enter appropriate connection information such as the server name (DNS or IP address) and the listening port number, the user DN, and associated password.

- Using the Schema Management page, select names of object classes and attribute types and then cache the schema.
- To keep the data synchronized, you must map PeopleSoft data to the equivalent directory objects.

Set up mappings using the Mappings component. After this is completed, PeopleSoft Directory Interface associates the fields in the message to the attributes in the directory and updates the selected directory attributes with the field data from the message.

- Using the Membership Rules component, create rules and memberships, if desired.
- Load data in the directory.
- Set directory search criteria.

Enter search parameters to query the directory and view the results.

Common Elements Used in This Chapter

Directory ID	Unique identifier for the directory.
Description	A brief description of the directory.
Directory Product	Select the directory product from the drop-down list box.
Default Connect DN	Displays the connect distinguished name associated with the directory ID that you selected. Use this ID to connect to the directory server.
Password	Password to access the directory.
LDAP Server	The name of the server where the directory resides.
Port	The LDAP server port associated with the LDAP server that you select.
SSL Port	The secure socket layer port.

Defining and Configuring the Directory

Use the Directory Configurations component (PSDSSSETUP) to define and configure the directory connection. This section discusses how to:

- Configure the directory connection.
- Cache the schema.

- Delete the directory configuration.

See Also

PeopleTools: Security Administration PeopleBook, "Employing LDAP Directory Services," Configuring the LDAP Directory

Pages Used to Define and Configure the Directory

Page Name	Definition Name	Navigation	Usage
Directory Setup	DSDIRSETUP	Enterprise Components, Directory Interface, Definitions, Directory Configurations, Directory Setup	Enter values to configure the directory.
Additional Connect DN's	DSSERVERID	Enterprise Components, Directory Interface, Definitions, Directory Configurations, Additional Connect DN's	Add values for additional connect DN's.
Schema Management	DSEXTINSTALL	Enterprise Components, Directory Interface, Definitions, Directory Configurations, Schema Management	Manage schema, and apply PeopleSoft schema extensions.
Test Connectivity	DSSRCHRSLT	Enterprise Components, Directory Interface, Definitions, Directory Configurations, Test Connectivity	Test the directory connectivity.
Cache Schema	DSSCHEMACACHE	Enterprise Components, Directory Interface, Definitions, Schema Cache	Cache the schema.
Delete Directory	DSPURGEDIRID	Enterprise Components, Directory Interface, Definitions, Directory Deletions	Delete the directory configuration.

Configuring the Directory Connection

This section discusses how to:

- Set up the directory connection.
- Connect additional DN's.

- Manage the schema.

Setting up the Directory Connection

Access the Directory Setup page (Enterprise Components, Directory Interface, Definitions, Directory Configurations, Directory Setup).

Use the Directory Setup (DSDIRSETUP) page to enter values to configure the directory.

Directory Setup | Additional Connect DN's | Schema Management | Test Connectivity

Directory ID: DEMO_DIRECTORY

Description: Demo Directory EXAMPLE

Directory Product: Novell NDS eDirectory

Default Connect DN: cn=admin,0=config

Password:

Server Name	LDAP Server	Port	SSL Port
	DIRDEVDS	389	

Directory Setup page

Connecting Additional DN's

Access the Additional Connect DN's page (Enterprise Components, Directory Interface, Definitions, Directory Configurations, Additional Connect DN's).

Directory Setup | Additional Connect DN's | Schema Management | Test Connectivity

Directory ID: DEMO_DIRECTORY

User DN	Password
Alternate ConnectDN

Additional Connect DN's page

Use this page to add values for additional connect DN's. Add more connect DN's and passwords, if needed.

Managing the Schema

Access the Schema Management page (Enterprise Components, Directory Interface, Definitions, Directory Configurations, Schema Management).

Directory Setup | Additional Connect DN's | **Schema Management** | Test Connectivity

Directory ID: DEMO_DIRECTORY

Select All | Deselect All

Apply PeopleSoft Schema Extensions [Customize](#) | [Find](#) | [View All](#) | [L2](#) | [Grid](#) | First | 1 of 1 | Last

Apply	Type	Name	Object Identifier	Revision	Details
<input type="checkbox"/>					Details

Details

[Apply](#)

Schema Cache Information

[Schema Cache Process](#)

Last Update Date/Time: by:


Schema Management page

Use this page to manage schema, and apply PeopleSoft schema extensions.

Activate the check boxes of those object classes or attribute types that you want applied to the cache schema.

Testing the Connectivity

Access the Test Connectivity page (Enterprise Components, Directory Interface, Definitions, Test Connectivity).



Test Connectivity page

Use this page to test the directory connectivity.

When you access the Test Connectivity page, the connection test launches automatically. The results appear in the page. A successful test shows the message *SUCCESS* in green.


The preceding example shows the message *FAILED* in red, confirming that the connection test failed.

Verify that your directory server configuration details contain the correct values (correct server name, port, and so on).

Caching the Schema

Access the Cache Schema page (Enterprise Components, Directory Interface, Definitions, Schema Cache).

Use the Cache Schema (DSSCHEMACACHE) page to cache the schema.




Cache Schema page

Enter the directory ID and server name of the schema to be cached and click the Cache Schema Now button.

Deleting the Directory Configuration

Access the Delete Directory page (Enterprise Components, Directory Interface, Definitions, Directory Deletions).

Use the Delete Directory (DSPURGEDIRID) page to delete the directory configuration.



Directory ID: DEMO_DIRECTORY

- Delete Associated Maps
- Delete Associated Searches
- Delete Associated Role Rules
- Delete Associated Entry Rules

Delete Directory Configuration

Delete Directory page

Select the check boxes for the desired directory configuration deletions.

(Optional) Setting Up Directory Authentication

This section discusses how to:

- Use map authentication.
- View user properties.

For information about setting up authentication servers, user profile maps, and role membership rules, refer to the following documentation.

See Also

PeopleTools: Security Administration PeopleBook, "Employing LDAP Directory Services," Creating the Authentication Map.

PeopleTools: Security Administration PeopleBook, "Employing LDAP Directory Services," Creating User Profile Maps.

Pages Used to Set Up Directory Authentication

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Authentication	DSSECMAPMAIN	Enterprise Components, Directory Interface, Mappings, Authentication	Create a mapping for the directory that the system relies on for authenticating users.
Mandatory User Properties	DSUSRPRFLMANMAP	Enterprise Components, Directory Interface, Mappings, User Profiles, Mandatory User Properties	Specify the attributes required for sign-in. You can have the system retrieve these mandatory values from the directory server, or you can enter default values.
Optional User Properties	DSUSRPRFLOPTMAP	Enterprise Components, Directory Interface, Mappings, User Profiles, Optional User Properties	Specify optional user properties to store in and retrieve from the directory. You can specify general, permission list, and workflow attributes. All these attributes appear in the User Profile component.

Using Map Authentication

Access the Authentication page (Enterprise Components, Directory Interface, Mappings, Authentication).

Authentication

Map Name: CSS_AUTH_MAP **Status:** Active Active

Directory Information

Directory ID: DEMO_DIRECTORY 🔍

Anonymous Bind Use Secure Socket Layer

Connect DN: cn=admin,0=config 🔍

User Search Information

Search Base: 0=CORP

Search Scope: Sub ▼

Search Attribute: cn 🔍

Search Filter: (cn=%SignonUserId)

List of Servers Customize | Find | View All | 📄 | 📊 | First ◀ 1 of 1 ▶ Last

SeqNum	LDAP Server	
	DIRDEVDS 🔍	+ -

Authentication page

Use this page to create a mapping for the directory that the system relies on for authenticating users.

Anonymous Bind If directory data required for authentication and user profile maintenance is visible to an anonymous connection, you can select this check box.

Use Secure Socket Layer Select if you are using SSL between the PeopleSoft system and the directory server.

Viewing User Properties

Access the Mandatory User Properties or Optional User Properties page (Enterprise Components, Directory Interface, Mappings, User Profiles, Mandatory User Properties).

Mandatory User Properties | Optional User Properties

User Profile Map: CSS_USER_PROFILE_MAP

*Authentication Map: **Status:** Active

Directory ID: DEMO_DIRECTORY

*User ID Attribute:

ID Type

*ID Type: None

*ID Type Attribute:

Default Role

Use default Role Role Name: Role Attribute:

Language

Use Default Language Code Language: LangCD:

Code: Attribute:

Mandatory User Properties page

Select Authentication Map and set check boxes and field values as needed.

Mandatory User Properties | **Optional User Properties**

User Profile Map: CSS_USER_PROFILE_MAP

*User Profile Property	Use Constant Value	Attribute Name	Constant Value	Always Update	
<input type="text"/>	<input type="checkbox"/>	<input type="text"/>		<input type="checkbox"/>	

Optional User Properties page

Use the Mandatory User Properties page or the Optional User Properties page to specify the attributes required for sign-in. You can have the system retrieve these mandatory values from the directory server, or you can enter default values.

The default shows the Attribute Name field available. If you select the Use Constant Value check box, the Constant Value field becomes available instead.

Setting Up Mappings

This section provides an overview of mapping and discusses how to:

- Create mappings.
- Modify a distinguished name.
- Specify distinguished name details.
- Translate or perform functions with database values.
- Specify distinguished name defaults.
- Map PeopleSoft data to directory object class attributes.
- Locate delivered messages.

Understanding Mapping

You map PeopleSoft data to the equivalent directory objects to keep the data synchronized. PeopleSoft Directory Interface receives PeopleSoft data from messages contained within service operation that you publish whenever a business event associated with the messages identified in the Directory Mapping component. Each message contains information about records and the most recent data for the record fields. Using the mapping information that you set up, PeopleSoft Directory Interface associates the fields in the message with the attributes in the directory and then updates the selected directory attributes with the field data from the message. Additionally, you can define a constant value or a PeopleCode function that returns a value to supply data used in building temporary Directory Information Trees when not all data exists for an entry.

Pages Used to Set Up Mappings

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Map Details	EO_DSMAP	Enterprise Components, Directory Interface, Mappings, Directory maps, Map Details	Set up a mapping and enter the data relationship details between PeopleSoft data and directory data.
Modify Connect DN - Directory Interface	EO_DSUSERDN	Click the Modify Connect DN button on the Map Details page.	Modify the Connect DN.
DN Details	EO_DSDN	Enterprise Components, Directory Interface, Mappings, Directory maps, DN Details	Set up the relationship between the data contained in the message that you selected on the Message Details page and the directory entry's distinguished name.

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
DN Defaults	EO_DS_DN_DEFAULTS	Enterprise Components, Directory Interface, Mappings, Directory maps, DN Defaults	Define a constant value or PeopleCode function that returns values that supply the blank values on the Directory Information Tree.
Attribute Details	EO_DS_ATTRIB	Enterprise Components, Directory Interface, Mappings, Directory maps, Attribute Details	Set up the relationship between the data in the message that you selected on the Message Details page and the directory object class attributes.

Creating Mappings

Access the Map Details page (Enterprise Components, Directory Interface, Mappings, Directory maps, Map Details).

Map Details
DN Details
DN Defaults
Attribute Details

Map Name: DEPARTMENT

***Description:** **Status:** Active ▼

Long Description:

Message Information

***Message Name:** **Function:**

Method Name:

Directory Connect Information

***Directory ID:**

LDAP Servers Sequencing Customize | Find | View All | First 1 of 1 Last

SeqNum	Server	Port
1	DIRDEVDS	389

Directory Search Base:

Default Connect DN: Modify Connect DN

Output Type: **File Format**

Retain Original Directory Data:

Map Object Class Find | View All | First 1 of 1 Last

Directory Object Class:

Map Details page

Use this page to set up mapping and enter the data relationship details between PeopleSoft data and directory data.

Status

Select the appropriate status from the following values.

- *Active:* The map is active and ready to be used.
- *Inactive:* The map is not ready to be used.
- *Remote:* The map is not used at this time, and may appear to be unavailable.

Message Information

Message Name	Select the message to associate with this mapping. The message contains the PeopleSoft records and fields that have the data that you want to associate with the attributes that make up the directory entry that you select in the Directory Connect Information group box. For example, if you select the output – DEPTID object class, select the department (DSDEPT_SYNC) message because it contains the fields relevant to the department object class.
Function	Enter the name of the PeopleCode function that you want to run using this message as an input parameter. The function can use any of the fields contained in the message to produce an output value for one or more of the fields that you map. This enables you to use a field in a function without mapping to it directly. For example, if you want the employee ID value sent to the directory to be a value combining the employee ID and the salary code, enter a function that produces that value. You then need to map only to the EmplID field to insert the derived employee ID in the directory.

Directory Connect Information

SeqNum (directory sequence number)	Indicate the order in which the server should be used when the system processes this mapping. If the first server is unavailable, the system attempts to access the other servers in sequence until it finds an available one. If you are using multiple servers, this enables you to distribute the load across servers.
Directory Search Base	Enter a directory search base. The search base is the entry in the directory information tree from which the system begins a search relating to this mapping. For example, if on the Attribute Details page you select to have a field value updated indirectly, PeopleSoft Directory Interface searches for and updates all instances of that field in entries from that point in the information tree down.
Modify Connect DN	Click to access the Modify Connect DN - Directory Interface page to modify the connect DN.
Output Type	Select the method that the system should use to send the mapped data to the directory data. Select <i>I</i> to send data to the directory directly through a business interlink. Select <i>F</i> to send data to an LDAP Data Interchange Format (LDIF) file to be manually updated in the directory. Use the same output type for all your mappings to keep data consistent in the directory.

Retain Original Directory Data

When you move data in your directory using the PeopleSoft Directory Interface, the Directory Interface copies the data to the new location and then deletes the old version. Select this check box to preserve the original data. You can select this check box at a later date provided that you do it before the data move.

Note. Select this check box if your directory contains binary data. Move the binary data with your directory administrative tool.

Map Object Class**Directory Object Class**

Select one or more directory object classes. The object classes that you select determine the attributes that you can map to PeopleSoft data.

Modifying the Distinguished Name

Access the Modify Connect DN - Directory Interface page (click the Modify Connect DN button on the Map Details page).

Directory ID: DEMO_DIRECTORY

Use Default (Admin) DN? (Y/N)

Customize Find First 1-2 of 2 Last	
User DN	Select
1	<input type="checkbox"/>
2 Alternate ConnectDN	<input type="checkbox"/>

Modify Connect DN - Directory Interface page

Use this page to modify the connect DN.

Use Default (Admin) DN? (Y/N) (use default [administrative] distinguished name)

Select to use the default connect distinguished name value that you set up in PeopleTools.

User DN (user distinguished name)

Displays the alternative IDs that you can use to connect to the specified directory ID. You can use a user ID (and password) other than the default one listed on the Directory Setup page in PeopleTools. Because the default user ID is most likely an administrative ID, you can set up a more secure user ID for the scope of the mapping.

Specifying Distinguished Name Details

Access the DN Details page (Enterprise Components, Directory Interface, Mappings, Directory maps, DN Details).

Attr Seq No	Attribute	Seq	Use Constant?	Record	Field Name	Constant Value			
1	ou	1	<input checked="" type="checkbox"/>			root,dc=DSI-DS			
2	ou	1	<input type="checkbox"/>	DEPT_TBL	LOCATION				

DN Details page

Use this page to define a constant value or PeopleCode function that returns values that populate the blank values on the Directory Information Tree.

Associate the data contained in the message that you selected on the Map Details page with the entry's distinguished name.

DN Details

Attr Seq No (attribute sequence number)

The system assigns an attribute sequence number to the attributes. Some directory attribute values consist of multiple values. The attribute sequence number distinguishes between the different attribute values and indicates to PeopleSoft Directory Interface the order in which the PeopleSoft values and constant values should be assigned to the attribute.

Attribute

Select the directory attributes associated with the mapping's distinguished name. For example, for the Department entry, map the o – Corporation first, the l – location second, and then the ou – Department attribute.

Seq (sequence)

Enter the sequence number of the directory attribute. The directory builds the entry's distinguished name using the attributes in sequential order.

Use Constant and Constant Value

Select to use the constant value that you enter in the Constant Value field to supply this attribute instead of a PeopleSoft field value.

Record and Field Name

Select the name of the record that contains the PeopleSoft field and the PeopleSoft field containing the value to assign to this attribute.



Click to access the DN Attribute Function - Directory Interface page and translate database values or instruct the system to perform functions with database values.

Note. Use this page when constructing distinguished names across active directory multiple domains.

Example Entry

An entry's distinguished name is built by applying the attributes in a sequential order. The order for the department entry example would be constructed using the data in the following table:

Sequence Number	Directory Attribute	Attribute Sequence Number	Use Constant Value	Record (Table) Name	Field Name	Constant Value
1	o	1	Yes			Corp
2	l	1	No	DEPT_TBL	LOCATION	NA
3	ou	1	No	DEPT_TBL	DEPTID	NA

Translating or Performing Functions with Database Values

Access the DN Attribute Function - Directory Interface page (Enterprise Components, Directory Interface, Mappings, Directory maps, Attribute Details).

Directory Interface

Transform the value using:

Translate Value
 Peoplecode Function
 Don't Tranform value

Scroll Area Find | View All First ◀ 1 of 1 ▶ Last

Database Value:	Attribute/Transformed Value:	
<input style="width: 90%;" type="text"/>	<input style="width: 90%;" type="text"/>	<input type="button" value="+"/> <input type="button" value="-"/>

PeopleCode Function Name:

DN Attribute Function - Directory Interface page

Use this page to set up the relationship between the data in the message that you selected on the Message Details page and the directory object class attributes.

- | | |
|---------------------------------|--|
| Translate Value | Select to replace the database value with the Distinguished Name field value for the selected attribute. |
| PeopleCode Function | Select to use the selected database object value as a parameter in a PeopleCode function. The system uses the resulting value as the attribute's distinguished name. |
| Don't Transform value | Select to instruct the system to keep the database value as is. This option is the default value for this field. |
| Database Value | <p>Enter the database value that you want the system to replace. For example, every time the database value <i>Vancouver</i> appears in the Location attribute, the system replaces it with the distinguished name <i>Van</i>.</p> <p>This field is available only when you select Translate Value as the transformation option.</p> |
| Distinguished Name | <p>Enter the distinguished name value to replace the database value.</p> <p>This field is available only when you select Translate Value as the transformation option.</p> |
| PeopleCode Function Name | <p>Enter the PeopleCode function that the system should use to calculate the distinguished name for the selected attribute.</p> <p>This field is available only when you select PeopleCode Function as the transformation option.</p> |

Setting Up PeopleCode Attribute-Level Functions

When the mapping function accesses the values in the selected field, the field value is passed into a PeopleCode function as a parameter and the output is assigned to the attribute in the directory.

Before you can enter a function on this page in the PeopleCode Function Name field, you must set up the function in the FUNCLIB_EO_DS.DSDYNFUNC FieldFormula.

To create a function:

1. Open the FUNCLIB_EO_DS.DSDYNFUNC FieldFormula.
2. Add a section in DSDynamicAttrFunc.
3. In the evaluate statement, add the following section for each function that you want to add (*FuncX* is equal to your function name):

```
When = 'FuncX'  
    FuncX(&AttrIn, &AttrRT);  
    Break;
```

4. Define a DSDynamicAttrFunc PeopleCode function.

The parameter list must contain two parameters, an attribute type string input and an attribute type string output.

PeopleCode Function Example

The following example displays the setup for functions FuncX, FuncY, and FuncZ.

DSDYNFUNC (field)
FieldFormula

```

Function FuncX(&AttrIN As string, &AttrRT As string)
End-Function;

Function FuncY(&AttrIN As string, &AttrRT As string)
End-Function;

Function FuncZ(&AttrIN As string, &AttrRT As string)
End-Function;

Function DSDynamicAttrFunc(&FuncName As string, &AttrIN As string, &AttrRT As string)
  Evaluate &FuncName
  When = "FuncX"
    FuncX(&AttrIN, &AttrRT);
    Break;
  When = "FuncY"
    FuncY(&AttrIN, &AttrRT);
    Break;
  When = "FuncZ"
    FuncZ(&AttrIN, &AttrRT);
    Break;
  When-Other
    Break;
  End-Evaluate;
End-Function;

```

Setup functions on the FUNCLIB_EO_DS.DSDYNFUNC FieldFormula

Specifying Distinguished Name Defaults

Access the DN Defaults page (Enterprise Components, Directory Interface, Mappings, Directory maps, DN Defaults).

Map Details
DN Details
DN Defaults
Attribute Details

Map Name: HR_PERSON Person Mapping

Status: Active

Distinguished Name: dn: uid={DSIDENTIFICTN.DSUID}, ou={JOB.DEPTID}, l={JOB.LOCATION}, dc=peoplesoft,dc=can,dc=com

Sequence Number	Record (Table) Name	Field Name	DN Attribute	Object Method	Constant/Parameter	Force		
1	JOB	LOCATION	l		POI	<input type="checkbox"/>		+ -
2	JOB	DEPTID	ou	HCDI_SERVICES:HCD		<input type="checkbox"/>		+ -

DN Defaults page

Use this page to define a constant value or PeopleCode function that returns values that populate the blank values on the Directory Information Tree.

This page enables you to define defaults for any Record.Field value that is left blank in the data rowset of the message that is used to populate the map. For example, you can enter defaults to enter the blanks left by the lack of Department/Location data for the Persons of Interest constructed by the PeopleSoft Directory Interface.

In the preceding sample page, the value for JOB.DEPTID is by default a method called HCDCI_SERVICES:HCDCIUtilities.DeptID. This method returns a DeptID constant.

Note. The syntax for the method needs to be fully qualified using the following format: Package_Name:App_Class_Name.Method_Name.

Seq (sequence number)	Displays the sequence number for this attribute.
Record (Table) Name	Select the record name for the value. This field is required.
Field Name	Select the field name for the value. This field is required.
DN Attribute	The name of the distinguished name attribute.
Object Method	Enter the object method you are using to supply the value, if applicable. Leave this field blank if you are using a constant or parameter to supply the value.
Constant/Parameter	Enter the values for the constant or the parameter, if applicable. Leave this field blank if you are using an object method to supply the value.
Force	Select to overwrite the Record.Field values at runtime, even if the values exist.

Mapping Data to Directory Object Class Attributes

Access the Attribute Details page (Enterprise Components, Directory Interface, Mappings, Directory maps, Attribute Details).

Map Details										DN Details										DN Defaults										Attribute Details									
Map Name: HR_PERSON																																							
Mandatory																				Customize Find First 1 of 1 Last																			
Attr Seq No	Attribute	Sequence	Use Constant?	Record	Field Name	Constant Value	Enable Indirect Update																																
1	ou	1	<input type="checkbox"/>	DEPT_TBL	DEPTID		<input type="checkbox"/>																																
Optional																				Customize Find First 1 of 1 Last																			
Attr Seq No	Attribute	*Sequence	Use Constant?	Record	Field Name	Constant Value	Enable Indirect Update																																
1	description	1	<input type="checkbox"/>	DEPT_TBL	DESCR		<input type="checkbox"/>																																

Attribute Details page

Use this page to set up the relationship between the data in the message that you selected on the Message Details page and the directory object class attributes.

On this page, associate the fields contained in the message that you selected on the Map Details page with the attributes that provide more detail about an entry. Some attributes are mandatory (an object class's mandatory attributes are defined in the directory schema) and must be mapped to either a constant value or record or field. For the department example, you would map PeopleSoft records and fields to the mandatory attributes (such as DeptID), and you could add additional attributes that would give you more information about the object class, such as description.

Note. The system does not update related-display field values unless the source field is also mapped. If the source field is not mapped, the audit process still indicates and enables you to update any discrepancies. For example, when you map to an employee's job code, the directory entry also includes the job code description. If you change the job code description on the Job Code component, the system updates the related-display description field on the employee's Job Data page, but it does not update to the directory, because it is not included in the mapping.

Warning! The fields that you map to mandatory attributes must contain data or the mapping will fail. You can guarantee that data will be in the fields by mapping mandatory attributes to required fields.

Attr Seq No (attribute sequence number)

Displays the attribute sequence number assigned to this attribute.

Attribute

In the Mandatory scroll area, the system displays the mandatory attributes for this object class.

In the Optional scroll area, select optional attributes.

Seq (sequence number)

Enter a sequence number for this attribute. Some directory attribute values are made up of multiple values. The attribute sequence number distinguishes between the different attribute values and indicates to PeopleSoft Directory Interface the order in which the PeopleSoft values and constant values should be assigned to the attribute.

Ind Upd (indirect update) Select if the field that you selected is used as an attribute in the directory outside of this mapping and you want it to be updated when this field is updated. The system updates attributes only in entries at lower levels on the directory information tree than this entry.

Locating Delivered Messages

Your PeopleSoft application that supports the PeopleSoft Directory Interface delivers a set of messages to be used to share information with your directory service.

Note. If you have upgraded from a PeopleTools 8.47 or earlier release, the upgrade program creates service operations for these messages. The service operation names and message names are the same.

For information about this delivered data and how it works in conjunction with the PeopleSoft Directory Interface, see your PeopleSoft application documentation.

(Optional) Setting Up Entry Membership Rules

This section discusses how to:

- Create entry definitions.
- Specify entry membership rules.

Entry membership rules enable you to modify a directory entry, such as a group, based on criteria stored in the PeopleSoft database. This feature provides a method to match any type of directory entry to rules that are meaningful in PeopleSoft applications. You can use membership rules to create any type of logical grouping in the directory. The groupings are not restricted to security purposes.

Pages Used to Set Up Entry Membership Rules

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Entry Definition	EO_DSCONTAINERDEFN	Enterprise Components, Directory Interface, Membership Rules, Entry Rules, Entry Definition	Create a directory entry definition.
Entry Membership Rules	EO_DSSECRULES	Enterprise Components, Directory Interface, Membership Rules, Entry Rules, Entry Membership Rules	Establish entry membership rules.

Creating Entry Definitions

Access the Entry Definition page (Enterprise Components, Directory Interface, Membership Rules, Entry Rules, Entry Definition).

The screenshot displays the 'Entry Definition' page with the following details:

- Entry Name:** IPLANET_ENTRIES
- Description:** IPLANET ENTRIES
- Directory ID:** DEMO_DIRECTORY
- Active Flag:** Active
- Directory Search Parameters:**
 - Search Base:** dc=corp,dc=peoplesoft,dc=com
 - Search Scope:** Sub
 - Build Filter:** (button)
 - Refresh Search Filter:** (button)
 - Clear Search Filter:** (button)
 - Search Filter:** (&(cn=Managers)(objectClass=groupOfUniqueNames))
- Search Attributes:** (Find | First | 1 of 1 | Last)
 - Directory Attribute:** (input field with search icon and +/- buttons)
- Trigger Map Names:** (Find | View All | First | 1 of 1 | Last)
 - Map Name:** (input field with search icon and +/- buttons)

Entry Definition page

Use this page to create a directory entry definition.

Entry Name Displays the entry name that you entered on the search page. The system uses this value for the entry name throughout the application, so it must be the name of an existing entry in the external directory. The PeopleSoft system assumes that the name is unique in the directory.

Active Flag Select to activate rules. Rules that are not active do not run.

Directory Search Parameters

Search Base	Enter the distinguished name of the base under which this entry will be located in the directory. The application performs an LDAP search to retrieve the distinguished name of the entry using this field as the base.
Search Scope	Select from: <i>Base</i> : The query searches only the value in the Search Base field. <i>One</i> : The query searches only the entries one level down from the value in the Search Base field. <i>Sub</i> : The query searches the value in the Search Base field and all entries beneath it.

Build Filter

()	Select the check boxes below the parentheses to group expressions. You can group more than one line together using the check box on the left for the first line and the check box on the right for the last line.
Attribute	Enter the name of the attribute that will store the members of the entry in the external directory. It is typically set to <i>member</i> , but the attribute name could be anything that you choose.
Operation	Assign an operator to your rule such as <, <=, <>, =, >, or >=.
Value	Assign a value to the attribute in your rule.
And/Or	To add another line to your rule, select <i>AND</i> or <i>OR</i> depending on your rule logic. Select <i>END</i> to signify the end of the search. Select <i>NONE</i> if you are not using this kind of filter.
Refresh	After you make changes using the Build Filter options, click this button to update the Search Filter edit box to reflect the changes.
Clear LDAP Filter	Click to delete all values from the Search Filter edit box and the Build Filter selections.
Search Filter	Displays the filter that the system applies to the search for the distinguished name of the defined entry. This field typically displays the directory object class of the entry in the form "objectclass = GroupOfUniqueNames", for example. This indicates what type of entry to search. To retrieve the correct entry distinguished names, the system adds the name of the entry to the search filter at runtime. The name retrieved by the LDAP search using this filter is tied to the rules defined in the Entry Membership Rules page. When these rules run, the employee that the system is currently processing is either added to or deleted from the distinguished name retrieved by the search.

Search Attributes

Directory Attribute

Select the attribute of the entry being defined that will contain all the members of this entry. This attribute must be valid for the current entry in the directory. The employees that satisfy the entry membership rules of this entry are added under this entry as a new value of this attribute. Because of this, as many attribute values may exist as employees satisfying the entry membership rules. If this field is left blank, the application uses *member* as a default attribute name.

Trigger Message Names

Map Names

Select the names of the maps to associate with the entry definition. Besides being a security feature, this also improves performance at runtime, because only applicable rules are evaluated.

Note. Run the directory audit if an entry rule has changed or if you want to initialize the directory entries.

Specifying Entry Membership Rules

Access the Entry Membership Rules page (Enterprise Components, Directory Interface, Membership Rules, Entry Rules, Entry Membership Rules).

The screenshot shows the 'Entry Membership Rules' page. At the top, there are two tabs: 'Entry Definition' and 'Entry Membership Rules'. Below the tabs, the 'Entry Rule Name' is 'IPLANET_ENTRIES' and the 'Description' is 'IPLANET ENTRIES'. The main section is titled 'Entry Membership Rules' and contains a table with one rule. The rule has a 'Sequence' of 1, is not a 'Record', and has a 'Field Name' of 'MANAGER_LEVEL' with a '<' operation. The 'Value' is 8. There are also 'AND/OR' options and a search bar at the top right of the table.

Entry Membership Rules page

Use this page to establish entry membership rules.

Entry Membership Rules

Sequence	Displays the sequence of a rule within a rule set. The sequence becomes significant when you enter more than one rule.
NOT	Select to negate the rule that you enter. This is similar to using the symbol <i>!</i> to reverse the truth value of an operand.
()	Select the check boxes to add parentheses around your rule. You can group more than one line together using the check box on the left for the first line and the check box on the right for the last line.
Record and Field Name	Enter the name of the PeopleSoft record and field containing the information to be tested.
Operation	Enter the appropriate operator, such as: <i><</i> , <i><=</i> , <i><></i> , <i>=</i> , <i>></i> , or <i>>=</i> .
Value	Enter the value on which the employee's data needs to be tested. This can be any value of the same type as the field used in the rule, such as String, number, date, and so on.
AND/OR	To add another line to your rule, select <i>AND</i> or <i>OR</i> depending on your rule logic. Select <i>END</i> to signify the end of the search. Select <i>NONE</i> if you are not using this kind of filter.

The entry rules are logical expressions that can be either true or false. They are composed of filters on database objects associated by logical operators. Rules have the following form:

```
[NOT] [ ( ] Record . Field operatorConstant [ ) ] [AND/OR]
```

The symbols between square brackets are optional. The operator can be *<*, *<=*, *<>*, *=*, *>*, or *>=*. A rule set is composed of single rules joined by AND or OR Boolean operators if necessary. The following example shows a series of single rules joined to make one compound rule.

```
( JOB.LOCATION = 'KC004' AND [1]
JOB.COMPRATE > 15000 ) OR [2]
NOT JOB.DEPTID = 'GBIY004' [3]
```

Note. No limits are imposed on the number of rules used within a rule set.

Loading Data into the Directory

This section provides an overview of how to load the directory and discusses how to load the directory with PeopleSoft data.

Understanding Directory Load Behavior

Use the Directory Load process when no existing data is in the directory. The process overwrites any data in the directory.

If you have data in your directory, use the Directory Audit process instead of the Directory Load process. The audit process compares the PeopleSoft data to your existing directory data and enables you to review and resolve any possible conflicts.

Note. For PeopleSoft Human Capital Management (HCM) customers only, an alternative process named DSMAPINPUT FullSync is available that you can use in place of the Directory Load process. This new process does not replace the Directory Load process; it is provided as an alternative to load the data if performance becomes an issue.

See *PeopleSoft HCM Application Fundamentals PeopleBook*

Loading the Directory with PeopleSoft Data

Access the Directory Load page (Enterprise Components, Directory Interface, Load Directory).

Directory Load

Run Control ID: DOCTEST_NS [Report Manager](#) [Process Monitor](#)

Map Name:

Description:

Run Option

LDIF File

Direct Update

Directory Load page

Use this page to run the Directory Load process.

- | | |
|----------------------|--|
| LDIF File | Select to have the process send the data to an LDIF file for you to load in the directory. |
| Direct Update | Select to have the process directly update the directory. |
| Run | Click to run the process using PeopleSoft Process Scheduler. |

Chapter 3

Reviewing Directory Data and Generating Reports

This chapter discusses how to:

- Review Lightweight Directory Access Protocol (LDAP) directory data.
- View PeopleSoft Directory Interface reports.
- Manage transaction audit history.

Reviewing LDAP Directory Data

This section discusses how to:

- Run a directory audit.
- Run a directory search.

Pages Used to Review LDAP Directory Data

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Directory Audit	EO_RUNCTL_DS_AUDIT	Enterprise Components, Directory Interface, Run Directory Audit	Run the Directory Audit process.
Directory Search	EO_DSSRCHDIRECTORY	Enterprise Components, Directory Interface, Search Directory	Define search parameters to query the directory. The page saves the search parameters for future use.

Running a Directory Audit

Access the Directory Audit page (Enterprise Components, Directory Interface, Run Directory Audit).

Directory Audit

Run Control ID: DOCTEST_NS [Report Manager](#) [Process Monitor](#)

Map Name:

Description:

Directory Audit page

Use this page to run the process to ensure that your directory database has the same data as your PeopleSoft database.

The Directory Audit process compares the data in the directory to the data in the PeopleSoft database identified in the selected map and creates an LDAP Data Interchange Format (LDIF) file containing any discrepancies using the PeopleSoft system as the authority. You can then use the LDIF file to update the directory.

Note. For PeopleSoft HCM customers only, an alternative process named DSMAPINPUT FullSync Audit is available that you can use in place of the Directory Audit process. This new process does not replace the Directory Audit process; it is provided as an alternative to audit the data if performance becomes an issue.

See *PeopleSoft HCM Application Fundamentals PeopleBook*

Map Name Select the name of the map that the audit should be run against.

Running a Directory Search

Access the Directory Search page (Enterprise Components, Directory Interface, Search Directory).

Directory Search

Search Name: DEPARTMENT_SEARCH

Description:

***Directory ID:** 

Directory Search Parameters

Search Base:

Search Scope: 

▶ Build Filter

Search Filter:

▼ Search Attributes
Find First  1 of 1  Last

Directory Attribute: 

Directory Search page

Use this page to define search parameters to query the directory and view the results. Search results are displayed on the Search Results page as they appear in the directory.

Search Name Enter the search name. The system saves the search parameters that you enter on this page and stores them under this name for future use.

Directory Search Parameters

Search Base Select the directory entry that is the search base for this search. The search base is the entry in the directory information tree at which the search begins querying.

Search Scope Select from:

Base: The query searches only the value in the Search Base field.

One: The query searches only the entries one level down from the value in the Search Base field.

Sub: The query searches the value in the Search Base field and all entries beneath it.

Build Filter

Use the fields in the Build Filter group box to create an attribute-specific filter. For example, if you want data on a single person, enter the attribute name *Person*, the operation =, and the person's name in the Value field. You can construct multiple filters.

()	Use parentheses to separate filter statements.
Attribute Name	Enter the name of the attribute data to which you want to filter.
Operation	Select an operator to determine how to filter the data.
Value	Select a value to compare against when filtering.
And/Or	Select from: <ul style="list-style-type: none"> • <i>And</i>: A search must meet the criteria of multiple statements. • <i>END</i>: This value marks the end of a query. This value applies parentheses appropriately. • <i>NoOp</i>: No operator is used. • <i>OR</i>: A search must meet the criteria of one of multiple statements.

Search Filter

You can narrow the search (for example, instruct the system to search for all attributes but one) by entering a search filter. Enter the search filter using standard LDAP protocol.

You can specify one or more attributes to search for. To search all attributes, enter an asterisk (*).

For more information about the LDAP protocol, see your directory documentation.

Search Attributes

Directory Attribute	Select the attributes to search for. Leave this field blank to search all attributes.
----------------------------	--

Viewing PeopleSoft Directory Interface Reports

This section discusses how to:

- View the directory audit report.
- View the business interlink status report.

Pages Used to View PeopleSoft Directory Interface Reports

Page Name	Definition Name	Navigation	Usage
Directory Audit Report	EO_RUNCTL_DS_AUDIT	Enterprise Components, Directory Interface, Audit Report	Generate the Directory Audit report.
Directory BI Status Report	EO_RUN_DS_BI_RPT	Enterprise Components, Directory Interface, Bus Interlink Status Report	Generate the Directory BI Status report.

Viewing the Directory Audit Report

Access the Directory Audit Report page (Enterprise Components, Directory Interface, Audit Report).

Directory Audit Report page

Use this page to generate the Directory Audit report.

The Directory Audit SQR report (EO_DS001) locates and reports discrepancies between the PeopleSoft database and your directory. Before you can generate the Directory Audit report, run the Directory Audit process. The Directory Audit process populates a comparison record containing the data that differs between the PeopleSoft database and the directory and creates an LDIF file with this data that can be used to update the directory. The Directory Audit report is based on this record, so you can verify what will be updated in the directory if you apply the LDIF file.

The report generates the following error messages:

- The distinguished name is not found in the directory.
- The distinguished name is not found in PeopleSoft.
- The attribute is in PeopleSoft but not in the directory.
- The attribute is in the directory but not in PeopleSoft.
- The value is in PeopleSoft but not in the directory.
- The value is in the directory but not in PeopleSoft.

Viewing the Business Interlink Status Report

Access the Directory BI Status Report page (Enterprise Components, Directory Interface, Bus Interlink Status Report).

Directory BI Status Report page

Use this page to generate the BI Status report.

If you selected an output type of Business Interlinks when setting up maps to associate PeopleSoft fields with directory attributes, the system uses PeopleSoft Business Interlinks to modify the directory. If errors occur as a result of the interlinks, the system writes the errors to an error record. The Business Interlink Status SQR report (EO_DS002) retrieves and presents the data contained in this error record.

Delete History Error Rows for MAP

Select to delete historical error rows for this map after reporting them. The PS_EO_BILOAD_ERR record retains error data for this map until you run the report with this check box selected.

Run

Click Run to generate the report using PeopleSoft Process Scheduler.

See Also

PeopleTools: PeopleSoft Process Scheduler PeopleBook

Managing Transaction Audit History

This section discusses how to:

- Generate a transaction history report.
- Search for a transaction history.
- Purge transaction history.

Pages Used to Manage Transaction Audit History

Page Name	Definition Name	Navigation	Usage
Transaction History Report	EODS_RUN_AUDIT	Enterprise Components, Directory Interface, Audit History, Run Report	Generate a transaction history report.
Transaction History Inquiry	EODS_AUDIT_HIS_IN	Enterprise Components, Directory Interface, Audit History, Transaction Inquiry	Search for a transaction history.
Purge Transaction History	EODS_RUN_ADT_PURGE	Enterprise Components, Directory Interface, Audit History, Purge Transactions	Purge audit history data.

Generating a Transaction History Report

Access the Transaction History Report page (Enterprise Components, Directory Interface, Audit History, Run Report).

Transaction History Report

Run Control ID: TEST [Report Manager](#) [Process Monitor](#)

Map Name:

User ID:

Status: Successful

Output Type: File Format

Transaction Type: Update

*From Date: *To Date:

Directory Attribute:

Transaction History Report page

Use this page to generate a Transaction History report.

- Map Name** Select a directory entry map name.
- User ID** Select the user ID.
- Status** Select the status of the transaction. Valid values are *Successful* and *No Success*.

- Output Type** Select the type of output. Valid values are *File Format* and *Business Interlink*.
- Transaction Type** Select a type of transaction. Valid values are *Add*, *Delete*, and *Update*.
- Directory Attribute** Select the attribute of the entry being defined that will contain all the members of this entry. This attribute must be valid for the current entry in the directory.

The employees who satisfy the entry membership rules of this entry are added under this entry as a new value of this attribute. Because of this, as many attribute values will exist as employees satisfying the entry membership rules. If this field is left blank, the application uses *member* as a default attribute name.

The following example shows the Process Scheduler Request page with Transaction Audit History Report in the process list. The system supports the creation of this report using Crystal Reports or Oracle Business Intelligent Publisher (BI Publisher or BIP).

Process Scheduler Request

User ID: PS Run Control ID: TEST

Server Name: Run Date: 10/11/2011

Recurrence: Run Time: 3:05:22PM

Time Zone:

Process List						
Select	Description	Process Name	Process Type	*Type	*Format	Distribution
<input type="checkbox"/>	Transaction Audit History Rpt	EODS_HIS	Crystal	Web <input type="button" value="v"/>	PDF <input type="button" value="v"/>	Distribution
<input checked="" type="checkbox"/>	Transaction Audit History Rpt	EODS_HIS	XML Publisher	Web <input type="button" value="v"/>	PDF <input type="button" value="v"/>	Distribution

Process Scheduler Request page showing the Transaction Audit History Report in the process list

Searching for a Transaction History

Access the Transaction History Inquiry page (Enterprise Components, Directory Interface, Audit History, Transaction Inquiry).

Transaction History Inquiry

Search Criteria

Map Name:

User ID:

Status: Successful

Output Type: File Format

Transaction Type: Update

From Date:
To Date:

Directory Attribute:

History Details

Customize | Find | View All | | First 1 of 1 Last

Transaction Information | Attributes | DN Details |

	Directory Entry Map Name	Transaction Type	Last Update Date/Time	User ID	Output Type	Status
1						

Transaction History Inquiry page

Use this page to run a query that appears in the browser rather than creating a report that runs using Process Scheduler.

- Map Name** Select a Directory Entry Map name.
- User ID** Select the user ID.
- Status** Select the status of the transaction. Valid values are *Successful* and *No Success*.
- Output Type** Select the type of output. Valid values are *File Format* and *Business Interlink*.
- Transaction Type** Select a type of transaction. Valid values are *Add*, *Delete*, and *Update*.
- Directory Attribute** Select the attribute of the entry being defined that will contain all the members of this entry. This attribute must be valid for the current entry in the directory.
- The employees who satisfy the entry membership rules of this entry are added under this entry as a new value of this attribute. Because of this, as many attribute values exist as employees satisfying the entry membership rules. If this field is left blank, the application uses *member* as a default attribute name.

Transaction Information Tab

The Transaction Information tab displays information about the transaction including the map name, the status, output type, and transaction type.

Attributes Tab

The Attributes tab displays information about the transaction including what directory audit action was performed, the type of directory attribute, and the attribute value.

DN Details Tab

The DN Details tab displays the distinguished name of the transaction.

Purging Transaction History

Access the Purge Transaction History page (Enterprise Components, Directory Interface, Audit History, Purge Transactions).

Purge Transaction History page

The following shows the Process Scheduler Request page with Purge Audit History in the process list:

Select	Description	Process Name	Process Type	*Type	*Format	Distribution
<input checked="" type="checkbox"/>	Purge Audit History	EODS_A_PURGE	Application Engine	Web	TXT	Distribution

Process Scheduler Request page showing Purge Audit History in the process list

Use the Purge Transaction History page to purge audit history data based on the date range that you enter in the run control page.

Part 3

Enterprise Integration Utilities

Chapter 4

Using the Error Handling Utility

Chapter 5

Using the Publish Utility

Chapter 6

Using the Inbound Data Error Scan Utility

Chapter 7

Using the Effective Date Publish Utility

Chapter 8

Using the Flat File Utility

Chapter 9

Using the XML Schema Utility

Chapter 10

Using Desktop Integration

Chapter 4

Using the Error Handling Utility

This chapter provides an overview of the Error Handling utility and discusses how to:

- Set up and maintain message errors.
- Correct message errors.

Understanding the Error Handling Utility

The Error Handling utility is a PeopleTools application that you use to view and correct messages that are received by the subscriber. You can also use this utility to correct data that is stored in staging tables.

Warning! Effective with the PeopleTools 8.48 release, the Integration Broker Service Operations Monitor supersedes the Error Handling utility.

See Also

PeopleTools: Integration Broker Service Operations Monitor PeopleBook

Error Management Process

PeopleSoft applications that receive flat file data from other systems through batch processes have built-in facilities to validate and correct data prior to updating the main application tables. Likewise, before updating core PeopleSoft application tables, the subscription process detects data errors in the messages that it receives. These error messages are stored in either message queues or staging tables.

In some cases, however, errors can't be sent back to the third party for correction (such as when data is in a flat file). In these cases, you must provide error processing on incoming data so that messages that contain information about business objects, such as items and vendors, can be corrected and reprocessed in the PeopleSoft system.

In many integration point implementations, especially those that involve huge transactions and complex data validations, subscription codes are written to run simple incoming data validations. Upon a successful outcome, the system performs these steps:

1. Writes incoming data to staging tables.
2. Runs more stringent data validation processes, usually in batch processes.

As a result of the first subscription process, entries are written to a special staging table (EO_EIP_CTL). The EO_EIP_CTL table is keyed by a single key, EIP_CTL_ID, and has messaging keys. The EO_EIP_CTL table maintains links between the source message and the staged data and ensures that the data maintenance program can identify the staging tables.

To find the particular message that you want to view:

1. Select a message by using standard selection criteria, including data maintenance programs, business unit or setID, data status, and staging table or message queue.
2. Click a detail button to access the application page related to the edited message.
3. Make your edits.
4. Save the message.

Note. Messages that are selected from a staging table are saved to the staging table. Before they're saved permanently (to the application table), the corrected messages that were selected from the message queue are assigned a status of *Changed* and saved to the same queue. The messages then undergo the subscription process data validation again, after which they're saved to an application table.

A data maintenance program corrects errors in data that enters the PeopleSoft system.

Note. Subscription error management does not apply to real-time data that enters the PeopleSoft system through PeopleSoft Business Interlinks.

Error management consists of the following sequential activities:

1. The PeopleSoft system receives XML messages from a third-party source.
2. Subscription processes validate the data and send the data to:
 - PeopleSoft application tables (if no errors were found).
 - Message queue (if errors were found).
 - PeopleSoft staging tables (if subscription logic requires).
3. The Error Handling utility interacts with:
 - Message queue.
 - Staging tables.
4. The user interacts with:
 - The Error Handling page (to select a message for review or correction).
 - Application pages (for editing data errors).
5. The PeopleSoft system updates:
 - Message queue (if the original message was selected from the queue).
 - Staging tables (if the original data was extracted for staging tables).

Setting Up and Maintaining Message Errors

This section discusses how to:

- Create error-correction pages.
- Set up the error handling utility.
- Set up row security.
- Set up workflow notification in PeopleSoft Application Designer.
- Test the error handling utility.

Warning! Effective with the PeopleTools 8.48 release, the Integration Broker Service Operations Monitor supersedes the Error Handling utility.

Pages Used to Set Up and Maintain Message Errors

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Data Maintenance	EO_EIP_CTL_SETUP1	Enterprise Components, Integration Definitions, Data Maintenance Utility	Set up the Error Handling utility and correct message errors.
Workflow/Security	EO_EIP_CTL_SETUP2	Enterprise Components, Integration Definitions, Data Maintenance Utility, Workflow/Security	Set up row security.
Data Maintenance	EO_EIP_CTL_MAINT	Enterprise Components, Integration Definitions, Review Centralized Error	<p>Test the error handling utility.</p> <p>Test subscription processes must error out. Create a message subcontract with <i>Error</i> status, or create a stage-based incoming transaction with a status value of <i>1</i> (Error).</p> <p>Note. Error conditions depend on processes that are specific to the application.</p>

Creating Error-Correction Pages

Use PeopleSoft Application Designer to create error-correction pages and components.

Note. The Header Details page and the Error Details page are applicable only if data resides in the messaging queues. Use one Header Details page and one Error Details page for each field.

When creating error-correction pages, follow these guidelines:

- Use EO_EIP_CTL as the main header table if you use staging tables.

Developers can use unique EIP_CTL_ID generator functions (Generate_EIP_CTL_ID and Increment_EIP_CTL_ID) available in the FUNCLIB_EOEIP.EIP_CTL_ID FieldFormula event.

- Use the generate EIP_CTL_ID function to generate a unique key value for EIP_CTL_ID, based on the subscription process instance.

The EIP_CTL_ID function is the sole key in the EO_EIP_CTL header table.

- Hook to EO_EIP_CTL to use the Error Handling utility for staging-table-based error handling.

See [Chapter 4, "Using the Error Handling Utility," Setting Up the Error Handling Utility, page 77.](#)

- Modify the record PeopleCode in the derived work record EO_EIP_CTL_WRK.

The derived work record called EO_EIP_CTL_WRK contains most of the processing logic for the utility. Although most of the codes are generic, you must write application-specific codes for the return button field (EIP_RETURN_BTN).

- Add codes to return the user to the main Error Handling page.

Use the EO_EIP_CTL_WRK derived record in your component and write component PeopleCode for the record to handle any unique requirements.

Note. This unique code belongs only to your component and cannot be shared.

FUNCLIB_XXEIP Codes

Functions are created and stored in product-specific FUNCLIB_XXEIP records, with XX representing the product. Application developers can look up these function libraries for possible use as templates.

Common integration-related functions are placed in the FUNCLIB_EOEIP record.

EIP_DETAIL_BTN FieldFormula

Function Copy_Detail_Errors (&WRK_FIELD, &J, &WRK_ROWSET) copies edit errors to a generic error subpage.

Function BuildQueueRowset (&WRK_ROWSET1 As Rowset, &WRK_ROWSET2 As Rowset, &MSG_ROWSET As Rowset, &SCROLL, &RECORD_FROM, &RECORD_TO) generically builds the queue-based transfer page. This function is useful for single record messages.

FUNCLIB_EOEIP.EIP_CTL_ID FieldFormula

You need an EIP_CTL_ID every time that you process a message to maintain error handling. Use Function Generate_EIP_CTL_ID and Increment_EIP_CTL_ID to create EIP_CTL_IDs based on a new subscription process instance. For the Generate_EIP_CTL_ID function, invoke method 4 from the list of process instances.

Note. Although in some cases a random number generator is used for creating a new EIP_CTL_ID by calling Generate_EIP_CTL_ID(1), you should use the subscription process instance if possible. Generate_EIP_CTL_ID(4) uses the identifier number of the message subscription process. Remember to activate this on the message subscription properties by selecting the Generate Subscription Process Instance check box.

Warning! The Generate_EIP_CTL_ID and Increment_EIP_CTL_ID functions call other functions in FUNCLIB_ININTFC (an FDM record). You must re-create these additional functions whenever you use Generate_EIP_CTL_ID and Increment_EIP_CTL_ID within applications.

Setting Up the Error Handling Utility

Access the Data Maintenance page (Enterprise Components, Integration Definitions, Data Maintenance Utility).

The screenshot shows the 'Data Maintenance' page with the 'Workflow/Security' tab selected. The page contains several configuration fields and options:

- Transaction Type:** ASNIN
- Description:** [Empty text box]
- Grid Selection:**
 - Queue Based
 - Stage Table
- BU / SetID Selection:**
 - Business Unit
 - Set ID
- *Component Name:** EIP_DTA_CTL
- *Prompt Table:** EO_EIP_ROW_VW1
- *Panel Transfer Code:** Next Panel
- Role:** [Empty text box]
- User ID:** [Empty text box]
- Name:** [Empty text box]
- Flags:**
 - Flag1 Flag3
 - Flag2 Flag4 Flag5

Data Maintenance page

Use this page to set up the Error Handling utility and correct message errors.

Queue Based and **Stage Table** PeopleTools messages are queue-based; bulk data or application data is usually staged.

Business Unit and **SetID** Select a business unit or setID on which to base the data.

Component Name	Select the name of the component for accessing the Error Handling/Data Maintenance page (EO_EIP_CTL_MAINT). This is the component that the user opens for error-correction activities. You should select <i>EIP_DTA_CTL</i> . This component uses the same fonts and images for all incoming data maintenance or error-correction activities within the PeopleSoft system for non-real-time integration.
Prompt Table	Follow the navigation path to use the Error Handling utility, and select a prompt table for the data maintenance program (EIP_PROGRAM). The PeopleSoft system includes a common error handling menu structure that points to the main component EIP_DTA_CTL. Based on user privileges, the Error Handling utility prompts from a selected list of data maintenance programs.
Panel Transfer Code	Select <i>Next Panel</i> to receive a transfer panel name prompt, which gives you a selection of pages that are part of the main data maintenance component that you selected in the Main Data Maint Panel Group field. Select one page. Selecting either <i>Transfer</i> or <i>Modal</i> opens additional fields.
Role Name	Select a name to set up workflow notification and to notify all role users listed.
User ID	Select to notify only specific role users.
Flag1, Flag2, Flag3, Flag4 and Flag5	Users often do not see these check boxes. Application developers use them for extra coding flexibility. Developers must create documentation for these check boxes to use them.

Setting Up Row Security

Access the Workflow/Security page (Enterprise Components, Integration Definitions, Data Maintenance Utility, Workflow/Security).

The screenshot displays the Workflow/Security page. At the top, there are two tabs: 'Data Maintenance' and 'Workflow/Security'. Below the tabs, the page shows 'Transaction Type: ASNIN' and 'Description: Advanced Shipping Receipt'. A 'Scroll Area' contains a search bar with the text 'ALLPAGES' and a magnifying glass icon. To the right of the search bar are '+' and '-' buttons. Below the search bar, the 'Permission List' section is empty.

Workflow/Security page

Use this page to set up row security.

Row Security Permission List Assign a row security class to the transaction type that you are setting up.

Note. The value that you select determines which user can see the given transaction type. You can enter multiple row security classes.

Setting Up Workflow Notification in PeopleSoft Application Designer

You can set up an EO_WF_ERR Application Engine process to scan the EO_EIP_CTL table periodically to look for rows with *ERROR* status. When the system finds errors, it generates workflow notifications and routes them to the role users that you designated in the User ID field on the Data Maint Setup1 page. Clicking the worklist item in the workflow notification transfers the user to the Error Handling/Data Maint (error handling/data maintenance) page.

To set up workflow notification:

1. Open an instance of PeopleSoft Application Designer.
2. Select File, Open.
3. Select *Business Process* from the Definition drop-down menu.
4. Open business process EC_MANAGE_ERRORS.
5. Right-click the MANAGE ERRORS icon and select *View Definition*.
6. Double-click the Correct Errors icon to open the Step Definition dialog box.
7. Click the Attributes button to open the Step Attributes dialog box.
8. Complete the required navigation information to the error correction page in the Step Attributes dialog box and click OK.

Testing the Error Handling Utility

Access the Data Maintenance page (EO_EIP_CTL_MAINT) (Enterprise Components, Integration Definitions, Review Centralized Error).

The screenshot shows a web interface titled "Data Maintenance". It contains several input fields for filtering data: "Transaction Type" with a search icon, "Grid Select" with a dropdown menu showing "Staged", "SetID", "Unit", "Reference" (a long text box), and "Status" with a dropdown menu. A "Search" button is located at the bottom right of the form area.

Data Maintenance page

Use this page to test the error handling utility.

Test subscription processes must error out. Create a message subcontract with *Error* status, or create a stage-based incoming transaction with a status value of 1 (*Error*).

Note. Error conditions depend on processes that are specific to the application.

The Review Centralized Error page features the following page elements:

Transaction Type	These values are provided by your application.
Grid Select	Select whether the errors you want to check are queue-based, stored in a staging table, or select and search for a specific error.
SetID	Enter a setID.
Unit	Enter the unit of measure.
Reference	Enter a reference name.
Status	Select from <i>Cancelled</i> , <i>Complete</i> , <i>Error</i> , <i>Hold</i> , <i>In Process</i> , <i>Incomplete</i> , <i>New</i> and <i>Reprocess</i> .
	Click the Show Detail Entry icon to transfer to the application page for necessary error-correction activities.

Correcting Message Errors

This section provides an overview of the Workflow Notification process and discusses how to correct message errors.

Warning! Effective with the PeopleTools 8.48 release, the Integration Broker Service Operations Monitor supersedes the Error Handling utility.

Understanding the Workflow Notification Process

Workflow error notification involves the following steps:

1. A process-scheduled Application Engine program scans data errors in the staging tables (or in the Subscription Contract Message queues) at a given interval.

Note. You can also run a separate Workflow Notification Application Engine program for messaging queues.

2. When the Application Engine program finds errors in the actual message queue or the staging summary table, it opens respective component interfaces that invoke the designated temporary components for inserting error data into the underlying temp tables.
3. Saving the temporary page (through component interface calls) triggers workflow PeopleCode to send worklist notifications to designated users, depending on the role name or user ID that you selected on the Data Maint Setup1 page.

Note. The Application Engine program traps only the first error for each field, but it can trap multiple errors for each record.

Correcting Message Errors

To correct message errors:

1. Access the Data Maint Setup1 page to open the worklist.
2. Open the worklist.

You are transferred to the Data Maintenance page (EO_EIP_CTL_MAINT) to correct the errors.

3. Find the error rows by using a combination of search criteria, such as transaction type, business unit or setID, and error status.
4. Click the Search icon.
5. Click the Show Detail Entry icon (to the left of each row) to select a specific transaction that represents a single message or a single row of header-level record from the staging table.
6. Correct the data.
7. Click the Return button to return to the Error Handling Summary page (EO_EIP_CTL_MAINT) and continue the session with other transactions.

Note. In this scenario, the corrected data does not update core PeopleSoft tables. Instead, it updates the message queue or staging tables.

Chapter 5

Using the Publish Utility

This chapter provides overviews of the Publish utility and publishing rules and discusses how to:

- Use sequential and parallel processing.
- Assign full table publishing rules.
- Assign batch publishing rules.
- Perform pre-processing and post-processing tasks.
- Set up message chunking.
- Create custom chunking tables.

Important! Using pre-processing and post-processing in conjunction with the parallel processing feature of the Publish Utility is currently available in the HCM application only. To use pre- and post-processing in conjunction with parallel processing you must apply one of the following resolutions to both the publishing and subscribing systems: HCM 9.0 systems – Resolution 827074; HCM 9.1 systems – Resolution 827350.

Understanding the Publish Utility

The Publish utility automates the process of copying the contents of an entire table into a remote database or legacy system.

Use the utility to synchronize data from an existing system when a new PeopleSoft system is installed.

The Publish utility is built upon the PeopleSoft Integration Broker services-oriented architecture and publishes service operations to target systems. The service operations published contain messages that store the table data.

Use the Publish utility to perform full table publish or batch publish processing. These process are defined as:

Full table publish

The full publish process seeds, or initially populates or repopulates, a copy of an entire table into a remote database or legacy system. The entire contents of the table are published to all systems that require a copy of the table.

Batch publish

This term describes jobs or processes that run independently of their initiating process. A batch process can also run at one or more predetermined times in the future from the initiating request. A batch process is appropriate for publishing incremental changes to data in a batch environment or for processing large volumes.

To use the utility you use the PeopleSoft Pure Internet Architecture to create publishing rules and then assign them to service operation messages to control how the utility manages the messages it is publishing.

Understanding Publishing Rules

You control the size and number of, and the frequency at which data full table or batch data is published by creating and using a series of data publishing rules.

The PeopleSoft Pure Internet Architecture component that you use to create publishing rules depends on the type of processing that you want to perform. For full table publish processing, use the Full Table Publish Rules component (EOIU_SOPUBFULL) to create publishing rules; for batch publish processes, use the Batch Process Rules component (EO_MSGPUBBATCH).

The pages in the Full Table Publish Rules and Batch Process Rules components are very similar. You use these components to specify:

- Pre-processing and post-processing tasks.
- The source of the data.
- Whether to chunk the message.
- Record mapping.
- Output format.
- Related languages in which to publish the data. (Full table publishing rules only)

Pre-Processing and Post-Processing

Often, performing pre-processing and post-processing tasks on the subscribing system before or after it processes a service operation message is desirable. Pre-processing tasks can include actions such as deleting existing data. Post-processing actions can include data clean-up.

Performing pre-processing and post-processing tasks is optional. However, if you choose to perform them, you must enable the Message Header or Message Trailer options on the Full Table Publish Rules or Batch Publish Rules page, as well as code the processing logic on the service operation handler.

You can perform pre-processing and post-processing tasks on service operations that are processed sequentially or in parallel.

Note. Using pre-processing and post-processing tasks in conjunction with the parallel processing feature of the Publish Utility is currently available in the HCM application only. To use pre- and post-processing tasks in conjunction with parallel processing you must apply one of the following resolutions to both the publishing and subscribing systems: HCM 9.0 systems – Resolution 827074; HCM 9.1 systems – Resolution 827350.

Using pre-processing and post-processing logic is discussed in greater detail elsewhere in this chapter.

See [Chapter 5, "Using the Publish Utility," Performing Pre-Processing and Post-Processing Tasks, page 98.](#)

Data Sources

The data to publish using the Publish utility can be from the following sources:

- A staging table.
- A temporary table.
- A view.

Message Chunking

This section discusses message chunking as it pertains to specifying chunking options in publishing rules. Setting up message chunking is discussed elsewhere in this chapter.

See [Chapter 5, "Using the Publish Utility," Setting Up Message Chunking, page 102.](#)

Chunking

Chunking refers to the automatic breaking of a message into several smaller messages based on values in fields in the level zero record.

You can perform chunking based on setID, business unit, or record group.

Chunking on business unit means that all transactions within the message are for the same business unit value.

The system chunks message data based on the MaxMessageSize parameter.

The MaxMessageSize (maximum message size) field in the PeopleSoft Option (PSOPTIONS) table limits the size of the message. Before processing each level zero record, the Full Table Publish utility compares the size of the message against the value in the MaxMessageSize field. When the message size exceeds the value in the MaxMessageSize field, the service operation publishes, and a new service operation starts.

You can also specify message chunking in the publish rules for the service operation, which enables the message to publish when the value of a chunk field changes.

Chunking Field

Chunking fields are key fields in the level zero record that are used to break the message into parts.

Chunking Table

A chunking table is a derived or Structured Query Language (SQL) table that contains the fields by which the message is chunked. SQL chunk tables define the valid values of the chunking fields and the nodes to which the message is published.

Oracle provides three standard chunking tables: EO_BUSUNIT_EOC for business unit values, EO_SETID_EOC for setID values and EO_RECGRP_EOC for record groups values. Oracle provides chunking tables for business unit, setID and record group that are maintained by a series of components (such as components that are created for maintaining the business unit chunking table).

Alternate Chunking Table

An *alternate chunking table* is a secondary chunk table. It provides a separate view of an existing chunk table, but with one or more field names customized. It enables you to reuse an existing chunk table. For example, if the record EO_BUSUNIT_EOC has BUSINESS_UNIT as the chunking field, you can create a view of this table that has BUSINESS_UNIT_IN as the chunking field.

When the field being chunked doesn't use the normal field names for business unit and setID, the alternate chunk table enables you to use the existing chunk tables and maintenance pages for business unit and setID. The alternate chunk table enables the user to use the existing chunk tables and maintenance pages for business unit and setID when the field being chunked doesn't use the normal field names for business unit and setID, for example, BUSINESS_UNIT_IN. Use the _EOV suffix for alternate chunk tables.

Chunking Rule

A chunking rule points to the chunking table. Multiple chunking rules can point to the same chunking table.

Record Mapping

You should use the record mapping feature in a publish rule because:

- The published data comes from staging tables or temporary tables.
Using staging tables is the only way to publish rows that have been deleted from application master tables.
- The published data needs an order sequence that differs from that of the records in the message.
- You must create a view that selects only current effective-dated rows in situations in which the application table is effective-dated and the subscribing database cannot process future-dated transactions.

Output Format

You can choose the output of the Full Table Publish utility to be in the following formats:

- Message (default value).
- Flat file.
- Flat file with control record.

You can create multiple publish rules with different output formats for the same service operation.

Flat File Output

You select the flat file option when you set up publish rule definitions for the service operation. If a file layout object exists with the same name as the message object, you can modify the output format field on the Publish Rule Definition page.

If you select flat file output, the header and trailer messages aren't created, and a single output flat file is created even if you already specified the chunking rule.

The file layout definition must have a record structure identical to that of the message; if the `AUDIT_ACTN` field does not exist in the record, you must add it to the file layout record definition.

The option becomes modifiable if a file layout object exists with the same name as the message definition.

The directory location of the flat file is determined by the value in the `OUTPUT` parameter in PeopleSoft Configuration Manager.

The flat file name is *messageName_SequenceNumber.out*, where *messageName* is the message name and *SequenceNumber* is the next available sequential number for files with that message name.

Publishing Data in Related Languages

The Publish utility provides the option to publish data in related languages.

If you choose to use the related language feature, the system creates the following related language messages:

- One message in the base language of the publishing system.
- One message for each language in the related language tables for the base tables.

The subscribing system receives the messages in the order in which they are published. For example, if the base language is English, with French and then German as related language tables, the Publish utility creates the messages in this order:

1. (Optional) Header message.
2. English message 1.
3. French message 1.
4. German message 1.
5. English message 2.
6. French message 2.
7. German message 2.
8. (Optional) Trailer message.

Prerequisites for Using the Publish Utility

The Publish Utility uses the PeopleSoft Integration Broker services-oriented architecture and to publish service operations to target systems. As such, to use the utility you must have:

- An understanding of PeopleSoft Integration Broker.
- PeopleSoft Integration Broker configured for your integration requirements.
- Service operations, including messages, handler, and routing definitions, setup on sending and receiving systems.
- Using pre-processing and post-processing tasks in conjunction with the parallel processing feature of the Publish Utility is currently available in the HCM application only. You must apply one of the following resolutions to both publishing and subscribing systems:
 - HCM 9.0 systems: Resolution 827074.
 - HCM 9.1 systems: Resolution 827350.

Common Elements Used in This Chapter

Alternate Chunk Table	(Optional.) Enter the name of an alternate chunk table. This field is disabled until you enter a value in the Chunk Rule ID field.
Service Operation	Click the link to view the service operation definition associated with the publish rule.
Chunking Rule ID	Associate a chunking method with the publish rule, if needed.
Message Options	<p>The valid options are:</p> <ul style="list-style-type: none"> • Create Message Header Select the check box to have the system create a message header when the publish rule is invoked. Clear the check box if you do not want a message header created when the publish rule is invoked. By default, the Create Message Header check box is selected. • Create Message Trailer Select the check box to have the system create a message trailer when the publish rule is invoked. Deselected the check box if you do not want a message trailer created when the publish rule is invoke. By default, the Create Message Trailer check box is selected.
Publish Rule ID	Enter the name of the publish rule to create and assign to the message.

(Publish Rule ID) Description	Enter a description for the publish rule.
Message.Version	Displays the message and message version associated with the service operation assigned to the publish rule.
Output Format	<p>Indicates the output format of the Publish utility.</p> <p>The valid output formats are:</p> <ul style="list-style-type: none"> • Message (default value). • Flat file. • Flat file with control record. <p>See and Chapter 5, "Using the Publish Utility," Flat File Output, page 87.</p>
Record Source Mapping	<p>Use this section to specify the source data for a record in a message.</p> <p>The page elements in this section are:</p> <ul style="list-style-type: none"> • Message Record Name: Enter the name of the record in the message that you want to map to another record. • Source/Order By Record Name: Enter the record name that the Publish utility uses to select data.
Service Operation	Displays the name of the service operation associated with the publish rule.
(Service Operation) Description	Displays the description of the service operation associated with the publish rule.
Status	<p>The valid values are:</p> <ul style="list-style-type: none"> • <i>Active:</i> Activates the publish definition. • <i>Inactive:</i> (Default) Inactivates the publish definition.

Using Sequential and Parallel Processing

This section discusses how to:

- Use sequential processing.
- Use parallel processing.
- Changing processing modes.

Understanding Using Sequential and Parallel Processing

Subscribing systems can process service operations sequentially or in parallel.

In *sequential processing*, the subscribing system processes messages defined in inbound service operations in the order received.

In *parallel processing*, the subscribing system processes messages defined in service operations in parallel, in no specific sequence.

You can use sequential or parallel processing when using either full table publishing or batch publishing.

You configure sequential or parallel processing at the queue level on the subscribing system.

Prerequisites for Using Parallel Processing

Note the following prerequisites for using pre-processing and post-processing tasks in conjunction with the parallel processing feature of the utility:

- The pre-processing and post-processing task functionality of the parallel processing feature of the Publish Utility is currently available in the HCM application only.
- To use pre-processing and post-processing tasks in conjunction with parallel processing you must apply the following resolutions to both the publishing and subscribing systems:
 - HCM 9.0 systems: Resolution 827074.
 - HCM 9.1 systems: Resolution 827350.

Using Sequential Processing

To implement sequential processing, on the subscribing system associate the message on the inbound service operation with an *ordered* queue.

See *PeopleTools: PeopleSoft Integration Broker PeopleBook*, "Managing Service Operations," Defining Service Operation Version Information, "Specifying Messages for Service Operations"

Using Parallel Processing

To implement parallel processing, on the subscribing system associate the message on the inbound service operation with an *unordered* queue. If the message is currently assigned to an ordered queue, assign it to a unordered queue.

In order to realize any performance gain from parallel processing, multiple subscription handlers must be set up for the subscription node to process messages on the unordered queue.

Only Messages that utilize functions inside the PeopleCode function library FUNCLIB_EOEIP for their pre-processing, post-processing and subscription handler logic will have the order of processing logic enforced when using the parallel processing mode.

See *PeopleTools: PeopleSoft Integration Broker PeopleBook*, "Managing Service Operations," Defining Service Operation Version Information, "Specifying Messages for Service Operations"

See *PeopleTools: PeopleSoft Integration Broker PeopleBook*, "Managing Service Operation Queues," Adding Queue Definitions

Changing Processing Modes

If your business requirements change, you can change the processing mode from sequential processing to parallel processing or vice versa, by moving the message associated with the service operation to the appropriate queue type.

If you have coded pre-processing or post-processing tasks, you must move the code for those tasks in the service operation message. More information is provided elsewhere in this chapter.

See [Chapter 5, "Using the Publish Utility," Coding Pre-Processing and Post-Processing Tasks, page 99.](#)

Assigning Full Table Publishing Rules

All PeopleSoft applications use common, centralized tables and pages to define how to publish full table messages. The Publish utility uses publishing rules to process the data.

This section discusses how to:

- Associate full table publishing rules with messages.
- Map a full table message record to another record.
- Specify languages in which to publish messages.

Note. You can create multiple publish rules for the same message. The Full Table Publish utility treats each publish rule as a separate publishing cycle.

Pages Used to Assign Full Table Publishing Rules

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Full Table Publish Rules	EOIU_SOPUBFULL	Enterprise Components, Integration Definitions, Full Data Publish Rules	Associate a rule with a message and characterize the rule.
Record Mapping	EOIU_SORECMAP	Enterprise Components, Integration Definitions, Full Data Publish Rules, Record Mapping	Map a message record to another record.
Languages	EOIU_SOLANGUAGE	Enterprise Components, Integration Definitions, Full Data Publish Rules, Languages	Specify languages in which to publish a message.

Associating Full Table Publishing Rules with Messages

Access the Full Table Publish Rules page (Enterprise Components, Integration Definitions, Full Data Publish Rules).

Full Table Publish Rules | Record Mapping | Languages

Service Operation: ACCOUNT_CHARTFIELD_FULLSYNC [Service Operation](#)

Operation Description: Account CF Full Sync | Message.Version: ACCOUNT_CHARTFIELD_FULLSYNC.VERSION_1

Publish Rule Definition | Find | View All | First | 1 of 1 | Last

*Publish Rule ID: ACCOUNT_CHARTFIELD_FULLSYNC

*Description: Account ChartField

*Status: Inactive

Chunking Rule ID:

Chunk Table:

Message Options

- Create Message Header
- Create Message Trailer

Output Format

- Message
- Flat File
- Flat File with Control Record

Full Table Publish Rules page

Use this page to associate a rule to a message and characterize the rule.

Message Options

The valid values are:

- *Create Message Header*. Use to initiate pre-processing tasks on the subscribing system.
- *Create Message Trailer*. Use to initiate post-processing tasks on the subscribing system.

By default, both options are enabled.

Ensure that the subscribing process does not need the header or trailer process before you deselect these check boxes for a Batch Publish message.

When sending messages sequentially, header messages trigger special logic (in a PeopleCode program) on the PeopleSoft full message subscription that deletes the existing application records. Also, some applications use the trailer message to indicate that all data messages have been received and to initiate the validation process. The documentation for the individual message should note whether headers and trailers are supported.

Create Delay Records

This check box appears only if the message name ends with *FULLSYNC_EFF* (such as *MESSAGENAME_FULLSYNC_EFF*). Select this check box to write all future-dated rows to the delay table. Also select this check box in conjunction with record mapping views that publish only the current effective-dated rows.

Mapping Full Table Message Records to Other Records

Access the Record Mapping page (Enterprise Components, Integration Definitions, Full Data Publish Rules, Record Mapping).

The screenshot displays the 'Record Mapping' page within the 'Full Table Publish Rules' section. The page is divided into two main sections: 'Publish Rule Definition' and 'Record Source Mapping'.
 In the 'Publish Rule Definition' section, the 'Service Operation' is 'ACCOUNT_CHARTFIELD_FULLSYNC' and the 'Operation Description' is 'Account CF Full Sync'. The 'Message.Version' is 'ACCOUNT_CHARTFIELD_FULLSYNC.VERSION_1'. Below this, there are two input fields: '*Publish Rule ID:' with the value 'ACCOUNT_CHARTFIELD_FULLSYNC' and '*Description:' with the value 'Account ChartField'.
 The 'Record Source Mapping' section contains two input fields: 'Message Record Name:' and 'Source/Order by Record Name:'. Both fields have a magnifying glass icon to the right, indicating a search function. There are also '+' and '-' buttons to the right of the 'Source/Order by Record Name:' field.

Record Mapping page

Use this page to map a message record to another record.

Regardless of which source table you use (staging table, temporary table, or a view), ensure that the source table field names are identical to the field names in the target message record. Key fields must also adhere to the parent and child relationship. (Keys of a parent record must exist in the child record, in the same sequence.) The Publish utility uses the Source/Order By Record Name field to select rows for publishing. You use key matching to find all child rows of a parent.

The chunk field should be the primary key field in all Source/Order By records. If the chunk field is not a key field of the level zero record, join the chunk field to all records in which the chunk field does not exist by using views in PeopleSoft Application Designer.

Enter only those message records with a different source or ordering record. If the message record name and the source or ordering record name are identical, do not insert a row for that record on the Record Mapping page.

Specifying Languages in Which to Publish Messages

Access the Languages page (Enterprise Components, Integration Definitions, Full Data Publish Rules, Languages).

The screenshot shows the 'Languages' page for a publish rule. At the top, there are tabs for 'Full Table Publish Rules', 'Record Mapping', and 'Languages'. The main content area displays the following information:

- Service Operation:** ACCOUNT_CHARTFIELD_FULLSYNC [Service Operation](#)
- Operation Description:** Account CF Full Sync
- Message.Version:** ACCOUNT_CHARTFIELD_FULLSYNC.VERSION_1

The 'Publish Rule Definition' section includes:

- *Publish Rule ID:** ACCOUNT_CHARTFIELD_FULLSYNC
- *Description:** Account ChartField
- Publish All Related Languages
- Publish Base Language

Below this is the 'Related Languages' section, which contains a 'Language Code' dropdown menu and '+' and '-' buttons.

Languages page

Use this page to specify languages in which to publish a message.

Publish All Related Languages	Select to indicate whether to publish the message in all of the related languages. If this option is selected, the scroll area that you use to enter individual related languages is unavailable. This check box is deselected by default.
Publish Base Language	Select to publish the message in the base language. This check box is selected by default.
Language Code	Select the related language in which to publish the message.

Assigning Batch Publishing Rules

All applications can use common, centralized tables and pages to define how to publish incremental messages from an application program. The Publish utility uses batch publish rules to process the data from the application program.

This section discusses how to:

- Associate a rule with a message and characterize the rule.

- Map a batch publishing message record to another record.
- Assign an application program to a publishing rule.

Note. You can link application programs to multiple publishing rules for the same message or different messages. The Publish utility treats each publishing rule as a separate publishing cycle.

Pages Used to Assign Batch Publishing Rules

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Batch Publish Rules	EOIU_SOPUBATCH	Enterprise Components, Integration Definitions, Batch Publish Rules	Associate a rule with a message and characterize the rule.
Record Mapping	EOIU_SORECMAP	Enterprise Components, Integration Definitions, Batch Publish Rules, Record Mapping	Map a message record to another record.
Batch Programs	EOIU_SOBATPGM	Enterprise Components, Integration Definitions, Batch Publish Rules, Batch Programs	Assign an application program (PROCESS_NAME) to the publish rule.

Associating Batch Publishing Rules with Messages

Access the Batch Publish Rules page (Enterprise Components, Integration Definitions, Batch Publish Rules).

Batch Publish Rules | Record Mapping | Batch Programs

Service Operation: ACCOUNT_CHARTFIELD_FULLSYNC [Service Operation](#)

Operation Description: Account CF Full Sync **Message.Version:** ACCOUNT_CHARTFIELD_FULLSYNC.VERSION_1

Publish Rule Definition Find | View All First 1 of 1 Last

*Publish Rule ID:

*Description:

*Status: Inactive

Chunking Rule ID:

Alternate Chunk:

Table:

Message Options	Output Format
<input checked="" type="checkbox"/> Create Message Header	<input checked="" type="radio"/> Message
<input checked="" type="checkbox"/> Create Message Trailer	<input type="radio"/> Flat File
	<input type="radio"/> Flat File with Control Record

Batch Publish Rules page


Use this page to associate a rule to a message and characterize the rule.

The page elements and controls that you use on the Batch Publish Rules page are described elsewhere in this chapter.

See [Chapter 5, "Using the Publish Utility," Common Elements Used in This Chapter, page 88.](#)

Mapping Batch Publishing Message Records to Other Records

Access the Record Mapping page (Enterprise Components, Integration Definitions, Batch Publish Rules, Record Mapping).



Record Mapping page

Use this page to map a message record to another record.

Note. When running a batch publish rule, the Publish utility runs cleanup logic, which either updates fields or deletes rows in the source tables. If the source table is a view that contains a join, then the option to delete published rows fails.

Message Record Name Enter the name of the record in the message that you want to map to another record.

Source/Order By Record Name Enter the record name that the Publish utility uses to select data.

This page specifies the source data for a record in a message. It works in the same manner and accomplishes the same purpose as the Record Mapping page for a full table publish.

Assigning Application Programs to Batch Publishing Rules

Access the Batch Programs page (Enterprise Components, Integration Definitions, Batch Publish Rules, Batch Programs).

Batch Programs page

Use this page to assign an application program (PROCESS_NAME) to the publish rule.

Process Name

Enter the name of the COBOL, Structured Query Report (SQR), or Application Engine program that is marking the records to be published.

The Publish utility initially receives the process name from the batch parameter record that is created by the application program. The program then retrieves and processes each publish rule for the application process name. The process name can be any 12-character string, as long as it matches what the application program inserts into the batch parameter record.

If you select a flat file format, the Publish utility does not create a header or trailer message, and the utility ignores any chunking rules. Instead, the utility creates a single flat file.

Performing Pre-Processing and Post-Processing Tasks

This section discusses how to:

- Set general pre-processing and post-processing options.
- Code pre-processing and post-processing tasks.

Setting General Pre-Processing and Post-Processing Options

To perform pre-processing and post-processing tasks, you must select the appropriate Message Header or Message Trailer option on the Full Table Publish Rules page or on the Batch Publish Rules page.

To set general pre-processing and post-processing options:

1. Access the Full Table Publish Rules page or the Batch Publish Rules page.
 - To access the Full Table Publish Rules pages, select Enterprise Components, Integration Definitions, Full Table Publish Rules.
 - To access the Batch Publish Rules pages, select Enterprise Components, Integration Definitions, Batch Publish Rules.
2. In the Message Options section, select the appropriate options:

Message Header	Select this option to perform pre-processing tasks on a service operation message.
Message Trailer	Select this option to perform post-processing tasks on a service operation message.

3. Click the Save button.

Coding Pre-Processing and Post-Processing Tasks

The type of processing that you are performing determines the location in the message where you insert the pre-processing and post-processing logic.

Using PeopleSoft-Delivered Functions for Pre-Processing and Post-Processing

Consider using the following PeopleSoft-delivered functions in pre-processing logic:

Delete_Existing_Data Function	The Delete_Existing_Data function loops through the default message definition records and deletes all the rows from each record. It also deletes all the rows from the related language record.
Subscribe_FullReplication Function	The Subscribe_FullReplication function is called from subscription processes that do full replication. This function checks the first instance of PSCAMA.BATREPFIRSTMSG and if this flag is set to yes, it invokes delete processing that deletes all the data from every record in the message as well as related language records. It then invokes the same Proc_Sub_Rowset processing that incremental replication processing uses. It loops through the message hierarchy and inserts the data into the appropriate tables based on PSCAMA.AUDIT_ACTION and the message definition records.

Coding Pre-Processing and Post-Processing Tasks

The type of processing that you are performing, sequential or parallel, determines the location in the message where you insert pre-processing and post-processing logic.

The following code example shows sample pre-processing and post-processing code. Section numbers have been entered as remarks to show the location to insert code based on the processing that you are performing.

<i>Processing</i>	<i>Task</i>	<i>Section</i>
Parallel	Pre-processing	Section 1
Sequential	Pre-processing	Section 2
Sequential	Post-processing	Section 3
Parallel	Post-processing	Section 4

Important! If you change processing modes from sequential processing to parallel processing or vice versa, you must move any pre-processing and post-processing code to the appropriate section in the message, as described in the table.

```

If &ParallelFS Then
    ...
    If &Pre_Process_Flg = "Y" Then

        rem ***** Begin Pre-Processing Logic for parallel-enabled FullSync *****;
        Delete_Existing_Data(&MSG);

        /*****
        /*
        /*          Section 1
        /*
        /*
        /*****

        rem ***** End Pre-Processing Logic for parallel-enabled FullSync *****;

    End-If;

End-If;

&MSG_ROWSET = &MSG.GetRowset();
&MSG_LANG_CD = &MSG_ROWSET(1).PSCAMA.LANGUAGE_CD.Value;
&MSG_BASE_LANG_CD = &MSG_ROWSET(1).PSCAMA.BASE_LANGUAGE_CD.Value;
&FULL_INCR = "FULL";

Evaluate &MSG_ROWSET(1).PSCAMA.MSG_SEQ_FLG.Value
When "H"
    If Not &ParallelFS Then

        rem ***** Begin Pre-Processing Logic for nonparallel-enabled FullSync *****;
        Delete_Existing_Data(&MSG);

        /*****
        /*
        /*          Section 2
        /*
        /*
        /*****

        rem ***** End Pre-Processing Logic for nonparallel-enabled FullSync *****;

        End-If;
        Break;
    When "T"
        If Not &ParallelFS Then

            /*****
            /*
            /*          Section 3
            /*
            /*
            /*****

            rem ** Insert Post-Processing Logic Here for nonparallel-enabled FullSync **;

            End-If;
            Break;
        When-Other
            Proc_Sub_Rowset(&MSG_ROWSET);
            rem ***** put additional process like editing here *****;

    If &ParallelFS Then

```

```

...

If &Post_Process_Flg = "Y" Then

    /*****
    /*
    /*          Section 4
    /*
    /*
    /*
    /*****

rem *** Insert Post-Processing Logic Here for parallel-enabled FullSync ***;

End-If;
...
Break;

End-Evaluate;

```

Setting Up Message Chunking

This section provides an overview of message chunking and discusses how to:

- Identify when to use chunking.
- Select chunking fields.
- Create chunking rules.
- Define the chunking rule description.
- Maintain chunking data for business units.
- Maintain chunking data for setIDs.
- Maintain chunking data for record groups.
- Add nodes to existing chunking rules.
- Assign business units or setIDs to a chunking rule.
- Assign chunking rules to a business unit.
- Assign chunking rules to a setID.

Understanding Message Chunking

If you publish to multiple nodes, you might want the messages to be routed based on a specific field. Chunking rules direct the message. You can use the same chunking fields for breaking a large message into smaller messages, as well as for associating messages with a node (based on those same fields). You set up this kind of relationship between nodes and the fields used to break the message apart (break fields) by using chunking message pages.

You can, depending on some XML content-based logic, use message chunking to route and deliver groups of transactions to different third-party nodes.

For example, consider purchase orders. If you run the full batch publish, each third-party node receives an XML message containing all purchase orders that are dispatched, regardless of whether any purchase orders are intended for that particular customer. With chunking, however, you can set up a chunking rule to chunk a message by customer ID. This creates an XML message for each customer that contains only purchase orders intended for that particular customer.

Note. Do not confuse message chunking with queue partitioning. You use queue partitioning to partition a queue by a level zero key field. If a field exists on level zero of the record in the message by which you can uniquely distinguish and group transactions to be processed in parallel, partitioning the message by this field increases performance. Without partitioning, a PeopleSoft subscribing system must process each incoming service operation and its associated message in the order in which the service operation is received according to the Publication ID (PUBID) field.

Pages Used to Set Up Message Chunking

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Chunking Rule	EO_CHUNKRULE	Enterprise Components, Integration Definitions, Map Chunking Rules, Define Chunking Rules	Define a chunking rule description.
BusUnit Mapping (business unit mapping)	EO_CHUNKBU	Enterprise Components, Integration Definitions, Map Chunking Rules, Business Units	Maintain chunking data for business units.
SetId Mapping	EO_CHUNKSETID	Enterprise Components, Integration Definitions, Map Chunking Rules, SetIds	Maintain chunking data for setIDs.
Eo Recgrp (Enterprise Component Record Group)	EO_RECGRP	Enterprise Components, Integration Definitions, Map Chunking Rules, Record Group	Maintain chunking data for record groups.
Add Nodes to Chunk Rule	EO_ADNODECHUNK_PNL	Enterprise Components, Integration Definitions, Map Chunking Rules, Node to ChunkRule	Add nodes to existing chunking rules.
Quick Map	EO_ADDSIDNODE_PNL	Click the Add button on the Add Notes to Chunk Rule page. This button is available after you have added nodes to the chunking rule.	Assign business units to a chunking rule.

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Map Business Unit	EO_ADDNODEBU_PNL	Enterprise Components, Integration Definitions, Map Chunking Rules, ChunkRule/Node to BU	Assign chunking rules to a business unit.
Map Set IDs	EO_ADDNODESID_PNL	Enterprise Components, Integration Definitions, Map Chunking Rules, ChunkRule/Node to Setid	Assign chunking rules to a setID.

Identifying When to Use Chunking

Use chunking when:

- The message data is large, and the subscriber is consistently interested only in part of the data.
- Subscribers can more efficiently process the message data by chunking messages.
- You have trading-partner-specific content and legally do not want data to be shared among vendors.

You can chunk messages by:

- Locations and inventory shipments by business unit.
- Customers by setID.
- Employees by department or company.
- Sales order acknowledgements by setID and customer ID.
- Purchase orders and purchase order changes by setID and vendor ID.

Selecting Chunking Fields

To maximize performance and prevent application developers from maintaining complicated views of the data, create staging or temporary tables that contain the chunking fields as the highest order key fields.

Chunking fields can affect performance and alter the options that are available to the Publish utility. The Publish utility creates SQL for each table that is defined in the message object. Tables that are defined in the message can be mapped to an alternative source table or viewed on the Record Mapping page under the Publish Rule Definition page.

The source table (or view) serves two purposes:

- It enables the data that must be published to come from a source other than the table that is defined in the message.
- It enables the data to be ordered so that the Publish utility can process rows in the correct sequence.

Because the SQL is run only once and includes a subquery against the values in the chunking table, you must define all chunking fields in every table that is used to retrieve data for the message. The SQL order-by clause is set according to the key fields that are defined in the table. The result is that chunking fields must be defined as key fields for the Publish utility to work.

Example of Generated SQL for Chunking

This is an example of SQL that is generated for chunking:

```
Select * from PS_INV_ITEMS A
where EXISTS (Select 'Y' from PS_EO_SETID_EOC B
where B.CHUNK_RULE_ID = 'SETID'
and B.EFFDT = '20000201'
and A.SETID = B.SETID)
order by A.SETID, INV_ITEM_ID, EFFDT
```

The field that you select to chunk on determines the view table that you must create:

Chunking Field Attribute	Corresponding View Table
Chunking field is a key field in level zero table.	By rule, the chunking fields are also key fields in the child tables. The key fields of a parent table must be key fields in the child table and in the same order. If the chunking fields are not the highest order key fields, create a view that consists of all fields in the source table, with the chunking fields as the highest order key fields, followed by the remaining key fields from the source table. Then map this view table to the source table on the Record Mapping page under the Publish Rule Definition page.
Chunking field is not a key field.	Create a view of the source data that consists of all fields in the source table, with the chunking fields as the highest order key fields, followed by the rest of the key fields from the source table. Then map this view table to the source table on the Record Mapping page under the Publish Rule Definition page.
Chunking field is not in a source table.	Create a view table that joins the source table to an existing table that contains the chunking fields. This view must consist of all fields in the source table and the chunking fields from the joined table. The chunking fields are the highest order key fields, followed by the rest of the key fields from the source table. Then map the view table to the source table on the Record Mapping page under the Publish Rule Definition page.

Example

The following sample SQL code creates a view table that joins the PS_OMECP_CP_OPT_DET source table to an existing PS_OMECHDR_OUT table that contains the chunking fields. The B.SETID_CUSTOMER and the B.CUST_ID chunking fields are the highest order key fields from the joined table (PS_OMECHDR_OUT), followed by the rest of the key fields from the source table (PS_OMECP_CP_OPT_DET).

```
SELECT B.SETID_CUSTOMER
, B.CUST_ID
, A.BUSINESS_UNIT
, A.ORDER_NO
, A.ORDER_INT_LINE_NO
, A.CP_MODE
, A.CP_COMP_SEQ
, A.OPTION_NAME
, A.OPTION_VALUE
, A.OPTION_DESC
, A.VAR_TYPE
, A.VAR_LENGTH
, A.VAR_DECIMAL
, A.PROCESS_INSTANCE
, A.AUDIT_ACTN
, A.IN_PROCESS_FLG
FROM PS_OMECP_CP_OPT_DET A
, PS_OMECHDR_OUT B
WHERE A.BUSINESS_UNIT = B.BUSINESS_UNIT
AND A.ORDER_NO = B.ORDER_NO
```

Creating Chunking Rules

The chunking rule consists of four tables:

Level	Table	Description
Level 0	EO_CHUNKRULE	A system table delivered with live data.
Level 1	EO_CHUNKEFFDT	A system table delivered with live data. When a chunking rule is saved, a row is added to this table with the effective date (EFFDT) field automatically populated from the current date and the effective status set to <i>Active</i> .
Level 2	EO_CHUNKNODE	This is not a system table and is delivered empty.
Level 3	NAME_EOC	A user-defined chunking table.

Note. All user-defined chunking table names must end in *_EOC*.

Oracle provides three standard tables: *EO_BUSUNIT_EOC* for business unit values, *EO_SETID_EOC* for setID values, and *EO_RECGRP_EOC* for record group values. The different types of user-defined chunking tables are:

<i>Table Type</i>	<i>Description</i>
Derived Table	Contains only the chunking fields. This table can be used by the Publish utility to chunk the message whenever the value of the chunking field changes. In derived tables, no relationship exists between the value of the chunking fields and message node names that are used to route the message. OnRoute PeopleCode needs hard-coded routing logic or additional tables to route the message to the appropriate nodes.
SQL Tables	Contains the following fields: <ul style="list-style-type: none"> • <i>CHUNK_RULE_ID</i> • <i>EFFDT</i> • <i>MSGNODENAME</i> • Chunking fields This table limits the published data to the values of the chunking fields in the chunking table and contains the message node name that is used to route the message.
Alternate Chunking Tables	Enables reuse of existing chunking tables. This table must end in <i>_EOV</i> .

Defining the Chunking Rule Description

Access the Chunking Rule page (Enterprise Components, Integration Definitions, Map Chunking Rules, Define Chunking Rules).

Chunking Rule ID: BUSINESS_UNIT

*Description: Chunk by Business Unit

*Chunk Table: EO_BUSUNT_EOC Business Unit Chunking Table

Chunk Fields	
Field Name	
1	BUSINESS_UNIT

Chunking Rule page

Use this page to define a chunking rule description.

Chunk fields are the chunking fields that are defined in the Chunk Table field.

The chunking fields appear in this scroll area to verify that the correct chunking table was entered. Oracle provides chunking rules for business unit and setID for all application databases. Adding a new chunking rule inserts a row into the EO_CHUNKEFFDT table, with a default effective date (EFFDT) of the current date.

Maintaining Chunking Data for Business Units

Access the BusUnit Mapping page (Enterprise Components, Integration Definitions, Map Chunking Rules, Business Units).

BusUnit Mapping

Chunking Rule ID: BUSINESS_UNIT Chunk by Business Unit

Effective Date Find | View All | First 1 of 1 Last

*Effective Date: 01/01/1900 *Status: Active

Message Node Find | View All | First 1 of 1 Last

*Node:

Business Unit Customize | Find | View All | First 1 of 1 Last

*Business Unit	Description
1 <input type="text"/>	

BusUnit Mapping page

Use this page to maintain chunking data for business units.

All four levels of the chunking rule tables appear.

Oracle provides chunking tables for business unit, setID and record group that are maintained by a series of components (such as components that are created for maintaining the business unit chunking table).

You can use each component to update the underlying relationship between the business unit and the subscribing nodes. You can maintain the data either by business unit or by node, individually or as a group, to reduce the amount of entry work.

Maintaining Chunking Data for SetIDs

Access the SetId Mapping page (Enterprise Components, Integration Definitions, Map Chunking Rules, SetIds).

The screenshot shows the 'SetId Mapping' page. At the top, it displays 'Chunking Rule ID: SETID' and 'Chunk by Setid'. Below this are three main sections:

- Effective Date:** A header bar with 'Find | View All | First | 1 of 1 | Last'. Below it, '*Effective Date:' is set to '01/01/1900' with a calendar icon, and '*Status:' is set to 'Active' with a dropdown arrow. There are '+' and '-' buttons to the right.
- Message Node:** A header bar with 'Find | View All | First | 1 of 1 | Last'. Below it, '*Node:' is followed by an empty search field with a magnifying glass icon. There are '+' and '-' buttons to the right.
- Setid:** A header bar with 'Customize | Find | View All | [grid icon] | First | 1 of 1 | Last'. Below it is a table with two columns: '*SetID' and 'Description'. The first row has '1' in the '*SetID' column and an empty 'Description' field. There are '+' and '-' buttons to the right of the table.

SetId Mapping page

Use this page to maintain chunking data for setIDs.

All four levels of the chunking rule tables appear.

Oracle provides chunking tables for business unit, setID and record group that are maintained by a series of components (such as components that are created for maintaining the business unit chunking table).

You can use each component to update the underlying relationship between the business unit and the subscribing nodes. You can maintain the data either by business unit or by node, individually or in a group, to reduce the amount of entry work.

Maintaining Chunking Data for Record Groups

Access the Eo Recgrp page (Enterprise Components, Integration Definitions, Map Chunking Rules, Record Group).

The screenshot displays the 'Eo Recgrp' page with the following configuration:

- Chunking Rule ID:** RECORD_GROUP
- Chunk by Record Group**
- Effective Date:** 01/01/1900 (with a calendar icon)
- *Status:** Active (with a dropdown arrow)
- Message Node:** (with an empty input field and a search icon)
- Record Group:** A table with one row:

*Record Group ID	Description
1	

Eo Recgrp page

Use this page to maintain chunking data for record groups.

All four levels of the chunking rule tables appear.

Oracle provides chunking tables for business unit, setID and record group that are maintained by a series of components (such as components that are created for maintaining the business unit chunking table).

You can use each component to update the underlying relationship between the business unit and the subscribing nodes. You can maintain the data either by business unit or by node, individually or in a group, to reduce the amount of entry work.

Adding Nodes to Existing Chunking Rules

Access the Add Nodes to Chunk Rule page (Enterprise Components, Integration Definitions, Map Chunking Rules, Node to ChunkRule).

Add Nodes to Chunk Rule

Chunking Rule ID: SETID

Effective Date: 02/15/2000

Status: Active

Select Node			
Add	Message Node Name	Description	Add Chunk Values
<input type="checkbox"/>	AIA	Internal Use. Do not modify.	
<input type="checkbox"/>	ANONYMOUS	Used internally by IB system.	
<input type="checkbox"/>	ASYNC_MDN	AS2 Node fore MDN's	
<input type="checkbox"/>	ATOM	Internal Use. Do not modify.	
<input type="checkbox"/>	BP	Portal Node - BP	
<input type="checkbox"/>	BPEL	Oracle BPEL PM Node	
<input type="checkbox"/>	CAMP	Portal Node - CAMP	
<input checked="" type="checkbox"/>	CRM	Portal Node - CRM	<input type="button" value="ADD"/>

Add Nodes to Chunk Rule page

Use this page to add nodes to existing chunking rules.

To add nodes to an existing chunking rule:

1. Select the check box in the Add column of the nodes that you defined earlier.
2. Click the Save button to display the Add Chunk Values column.

When you select a node and then click Save, the ADD button in the Add Chunk Values column appears.

3. Click the Add button in the Add Chunk Values column for the nodes that you want to add.

The Quick Map page appears.

Assigning Business Units or SetIDs to a Chunking Rule

Access the Quick Map page (Click the Add button on the Add Notes to Chunk Rule page. This button is available after you add nodes to the chunking rule).

Quick Map

Chunking Rule ID: SETID

Effective Date: 02/15/2000

Message Node Name: CRM

	Set ID	Description
<input type="checkbox"/>	001	Swish Hotels -Hourly
<input type="checkbox"/>	AA	Admin Conference of the US
<input type="checkbox"/>	AB	American Battle Monuments Comm
<input type="checkbox"/>	AC	Advisory Coms on Intrgvn Reltn
<input type="checkbox"/>	ACC	State of Accord
<input type="checkbox"/>	AD	U.S. Arms Control and Disarmam
<input type="checkbox"/>	AF	Department of the Air Force
<input type="checkbox"/>	AG	Department of Agriculture
<input type="checkbox"/>	AH	Nat'l Found on Arts & Humanit
<input type="checkbox"/>	AI	U.S. Institute of Peace

Quick Map page

Use this page to a Assign business units to a chunking rule.

If you previously accessed business unit chunking rules, you can add business units to a chunking rule. If you previously accessed setIDs, you can add setIDs to a chunking rule.

Note. You cannot access the Quick Map page without first using either the BusUnit Mapping page or the SetId Mapping page to add an effective-dated node to the chunking rule ID.

Select All and **Deselect All** Click to add or remove all business units that are assigned to the node. Add check boxes are selected for business units that are assigned to the node.

Assigning Chunking Rules to a Business Unit

Access the Map Business Unit page (Enterprise Components, Integration Definitions, Map Chunking Rules, ChunkRule/Node).

Map Business Unit

Business Unit: EGV01 EDUC & GVT - BU 1 Select All Deselect All

Select Node / Chunk Rule Customize | Find | View All | 1 of 1 First Last

Add	Message Node Name	Chunking Rule ID	Effective Date
<input type="checkbox"/>			06/25/2009

Map Business Unit page

Use this page to assign chunking rules to a business unit.

Select All and **Deselect All** Click to add or remove all nodes that are assigned to the business unit. Add check boxes are selected for nodes that are assigned to the business units.

Assigning Chunking Rules to a SetID

Access the Map Set IDs page (Enterprise Components, Integration Definitions, Map Chunking Rules, ChunkRule/Node).

Map Set IDs

Set ID: AB Select All Deselect All

Select Node / Chunk Rule Customize | Find | View All | 1 of 1 First Last

Add	Message Node Name	Chunking Rule ID	Effective Date
<input type="checkbox"/>	CRM	SETID	02/15/2000

Map Set IDs page

Use this page to assign chunking rules to a setID.

Select All and **Deselect All** Click to add or remove all message nodes that are assigned to the setID. Add check boxes are selected for message nodes that are assigned to the setIDs.

Creating Custom Chunking Tables

This section discusses how to:

- Create a custom chunking table.
- Create a view for the component search record.
- Create maintenance pages.
- Create a component.
- Create routing PeopleCode.

Creating a Custom Chunking Table

To create a custom chunking table:

1. Select File, Open in PeopleSoft Application Designer.
2. Select *Record* in the Definition drop-down menu.
3. Open the EO_BUSUNT_EOC record.
4. Save the record as *YOUR_TABLE_EOC*.
5. Remove the BUSINESS_UNIT field.
6. Insert the custom chunking fields at the bottom of the record.
7. Select File, Save.
8. Build the SQL table.

Creating a View for the Component Search Record

To create a view for the component search record:


1. Select File, Open in PeopleSoft Application Designer.
2. Select *Record* in the Definition drop-down menu.
3. Open the EO_CHUNKBU_VW record.
4. Save the record as *YOUR_TABLE_VW*.
5. Select the Record Type tab.
6. Open the SQL editor.
7. Modify the Where clause.

Change WHERE RECNAME_CHUNK=EO_BUSUNT_EOC to WHERE RECNAME_CHUNK=YOUR_TABLE_EOC.

8. Select File, Save.
9. Build the SQL view.

Creating Maintenance Pages

You can also create maintenance pages.



Grid Properties dialog box

To create maintenance pages:

1. Select File, Open in PeopleSoft Application Designer.
2. Select *Page* in the Definition drop-down menu.
3. Open the EO_CHUNKBU page.
4. Save the page as *YOUR_PAGE*.
5. Select the Order tab.
6. In the Type column, double-click Grid to open the Grid Properties dialog box.
7. Change the value in the Main Record and Page Field Name fields to *YOUR_TABLE_EOC*.
8. Click OK.

9. Delete the business unit and description columns.
10. Add chunking fields from `YOUR_TABLE_EOC`.
11. Select File, Save.

Creating a Component

To create a component:

1. Select File, New in PeopleSoft Application Designer.
2. Select *Component* in the New Definition box.
3. Select Insert, Page Into Component.
4. Enter `YOUR_PAGE`.
5. Click Close.
6. Select File, Definition Properties
7. Select the Use tab to edit component properties:
 - a. In the Search record field, enter `YOUR_TABLE_VW`.
 - b. Select the Update/Display, Update/Display All, and Correction check boxes.
8. Click OK.
9. Select File, Save As, and save the page group as `YOUR_COMPONENT`.
10. Add `YOUR_PAGE_GROUP` to `YOUR_MENU` that is used by your application.

Creating Routing PeopleCode

`OnRouteSend` (and `OnRouteReceive`) are PeopleCode methods that are tied to the message for routing, based on the message contents. If you want the contents of the message (such as a message chunking field value) to determine the subscribing nodes that should receive the message, `OnRouteReceive` PeopleCode must contain the logic to examine the message and return a list of subscribing nodes.

The `OnRouteSend` and `OnRouteReceive` methods are contained in the `IRouter` application class. The `IRouter` application class is located in PeopleSoft Application Designer in the Integration subpackage of the `PS_PT` application package.

PeopleCode functions provided by common components, `GetNodes` and `RtnNodes`, work with any message and chunking rule. For a given message, these nodes select the chunking rule for the publish rule that is assigned to the message.

The functions:

- Build SQL based on the chunking fields as defined in the chunking table.
- Extract chunking field values from the message.

- Run the associated SQL.
- Compare the array of nodes returned to the application server against the list of nodes for the message channel.
- Create a publish contract for nodes in both arrays.

You can override the publish rule from the message, specifying an optional parameter when calling the functions.

- Return an array of nodes that is based on the nodes that are assigned to the message channel if the publish rule is invalid or does not contain a chunking rule.

Returning an array of nodes enables the functions to work regardless of whether chunking is set up for the publish rule.

To route any message that uses chunking, use generic PeopleCode functions.

These functions are called from routing PeopleCode:

GetNodes	Returns an array of nodes to the application server. Use this function for integrations on PeopleTools 8.47 and earlier releases.
RtnNodes	Returns an array of nodes to the calling PeopleCode. Use this function for integrations on PeopleTools 8.47 and earlier releases.
RtnMsgNodes	Returns an array of nodes of datatype Any to the calling PeopleCode. Use this function for integrations on PeopleTools 8.48 and higher releases.

These functions are internal functions:

FndNodes	Builds an array of nodes for the message.
GetPubRule	Selects the chunking rule for the publish rule.
GetChunkInfo	Selects the chunk table for the chunking rule.
BuildSQL	Builds SQL to select nodes from the chunking table for specific chunking field values from the message.
GetValue	Gets the chunking field values from the message.
HasNodes	Determines whether a chunking field is mapped to any nodes for a particular chunking rule.

The following code example shows the logic that you can add to SavePostChange PeopleCode for the Customer_General component to verify that the setID can publish the message by calling the HasNodes() function:

```
Declare Function HasNodes PeopleCode FUNCLIB_EOEIP.PUBLISH_ROUTE_PC
FieldFormula;
Local Message &MSG;
Local Rowset &RS0;
Local string &PublishRule;
&MSG = CreateMessage(MESSAGE.CUSTOMER_MSG);
/* Check if message is active */
If &MSG.IsActive Then
    &RS0 = GetLevel0();
    &PublishRule = "CUSTOMER_SYNC";
    /* Call function passing publish rule and rowset, which returns
    true if this setID can publish the message */
    If (HasNodes(&PublishRule, &RS0)) Then
        &RS0 = GetLevel0();
        &MSG.CopyRowsetDelta(&RS0);
        &MSG.Publish();
    End-If;
End-If;
```

The following code example shows the logic that you can add to service operation APC handler PeopleCode to chunk the message by nodes as defined in the chunking rules by calling the RtnMsgNodes function:

```

import PS_PT:Integration:IRouter;

class ChunkSetidByNode implements PS_PT:Integration:IRouter
  method RoutingHandler();
  property array of any destinationNodes;
  method OnRouteSend(&_MSG As Message) Returns integer;
  method OnError(&_MSG As Message);
end-class;

Declare Function RtnMsgNodes PeopleCode FUNCLIB_EOEIP.PUBLISH_ROUTE_PC
FieldFormula;

/* constructor */
method RoutingHandler
end-method;

method OnRouteSend
  /*+ &_MSG as Message +/
  /*+ Returns Integer +/
  /*+ Extends/implements PS_PT:Integration:IRouter.OnRouteSend +/
  /* Variable Declaration */
  Local string &PublishRule;

  %This.destinationNodes = RtnMsgNodes(&PublishRule, &_MSG);

  If %This.destinationNodes.Len > 0 Then
    Return (%IntBroker_ROUTE_SOME);
  Else
    Return (%IntBroker_ROUTE_ALL);
  End-If;
end-method;

/** If an error occurs the OnError method if implemented will be automatically⇒
invoked. The type of exception can be viewed by using the Message object to⇒
retrieve the Exception object (&Message.IBException)
* @param MSG Message object containing the operation instance where⇒
the error occurred while being routed
*/
method OnError
  /*+ &_MSG as Message +/
  /*+ Extends/implements PS_PT:Integration:IRouter.OnError +/
end-method;

```

Chapter 6

Using the Inbound Data Error Scan Utility

This chapter provides an overview of the Inbound Data Error Scan utility and discusses how to run it.

Understanding the Inbound Data Error Scan Utility

The Inbound Data Error Scan utility launches the PeopleSoft Application Engine program EO_WF_ERR that scans the PSAPMSGSUBCON and EO_EIP_CTL tables for data errors on inbound asynchronous integrations and notifies respective users if errors are encountered.

See Also

[Chapter 4, "Using the Error Handling Utility," page 73](#)

Running the Inbound Data Error Scan Utility

This section discusses how to launch the Inbound Data Error Scan utility.

Launching the Inbound Data Error Scan Utility

Access the Incoming Data Error Scan page (Enterprise Components, Integration Definitions, Initiate Processes, Inbound Data Error Scan).

Use the Incoming Data Error Scan (EO_ERR_RUNCNTL) to start the EO_WF_ERR application engine program.

Incoming Data Error Scan

Run Control ID: TEST [Report Manager](#) [Process Monitor](#)

Process Request Parameters Find | View All | First 1 of 1 Last

Process Frequency

Once

Always

Don't Run

*Request ID:

Description:

Incoming Data Error Scan page

Request ID Enter the request ID of the integration on which to scan for errors.

Run Click to launch the EO_WF_ERR application engine program.

Chapter 7

Using the Effective Date Publish Utility

This chapter provides an overview of the Effective Date Publish utility and discusses how to:

- Perform a full data publish of current effective data.
- Publish incremental messages of current effective data.
- Publish effective-dated rows from the delay table.
- Publish effective-dated rows and prior-dated rows from the delay table.

Understanding the Effective Date Publish Utility

The Effective Date Publish utility enables you to design processes to update external systems that process only current data and don't use or recognize effective dating.

When working with effective dating and effective date publishing, you need to understand the following terms:

Current Row	The current row is the first row of data with an effective date equal to or prior to the system date. Only one row can be the current row.
Future Rows	Future rows have effective dates later than the system date (usually the current date).
Historical Rows	Historical rows have effective dates prior to the current row.
Effective Date	An effective date is when a table row becomes effective, or the date that an action begins. The PeopleSoft system supports the concept of effective-dated rows.

Note. The EFFDT field is almost always a key. Specify the descending key attribute to display the row with the most recent effective date first.

Effective Dating	Automated effective dating saves changed data in a staging table for subsequent processing when the effective date becomes current. (Although data can be historical, current, or future, some third-party applications may support only current data. Thus, if a future-dated row is created within the PeopleSoft system, it must be delayed before transmission to the other system.)
-------------------------	--

Effective Sequence

An effective sequence serves two purposes:

- If EFFSEQ is a required field, it enables the entry of more than one row with the same effective date when paired with EFFDT. The system assigns a unique sequence number to each row that has the same effective date. It also enables the first EFFSEQ to be zero.
- If EFFSEQ is not a required field, it is not paired with EFFDT, has no special function, and can be used as a simple sequencing field.

Effective Status

Effective status enables the system to select the appropriate effective-dated rows, when combined with the effective date field.

Full Data Publish

The full data publish process seeds, or initially populates or repopulates, a copy of an entire table onto a remote database or legacy system. The entire contents of the table are published to all systems that require a copy of the table. Generally, full data replication occurs with setup tables (relatively static, low-volume tables that are keyed by setID) and occurs in an asynchronous manner.

When a full copy of the table exists on the external system, an incremental update provides a mechanism to keep the copy up-to-date with changes made on the master.

Incremental Publish

The incremental publish process sends a message that contains only the rows where the data has been modified, plus the corresponding anchoring parent and grandparent rows. When a particular transactional event occurs, an incremental update of the transaction data is sent to other systems to notify them of the changes.

Nodes

Each node represents a publishing or subscribing system of a service operation. For example, the PeopleSoft Human Resources and PeopleSoft Financials databases are each defined as a node, even if they are both on the same server.

Service Operation Queues

Service operation queues group messages and the nodes to which they are published, so that messages are published sequentially. Each message must belong to only one queue. Queues control the ordering of messages and define timeout parameters and error thresholds. Assign nodes to a queue when you define the message in the service operation.

Message Chunking

Chunking automatically breaks a message into several smaller messages based on the values in one or more of the fields in the level zero record. When publishing the entire contents of a table, you can use message chunking to publish only certain sets of data if, for example, a particular subscriber is interested in only a portion of the table.

Request ID

Use the request ID to specify multiple requirements within the same run control.

Run Control

You use run controls to produce full messages for objects at the same time. Run controls also associate publish rule definitions with the scheduled full publish process run. For example, you can set up a run control to publish both customer full messages and sales order full messages on a daily schedule.

Performing a Full Data Publish of Current Effective Data

This section discusses how to:

- Create effective-dated messages.
- Create a service operation.
- Define the node and target connector.
- Define chunking rules and ordering views.
- Create publish rule definitions.
- Create run controls for the Full Data Publish program.
- (Optional) Define message routing.

For full data messages that are intended for vendors who do not handle effective dating, use the Effective Date Publish utility and a current full message to publish only those rows that are currently active. Any future-dated rows are written to the delay table.

This section discusses the process involved in a full data publish of current effective data. It uses the CUSTOMER_FULLSYNC_EFF service operation as an example, but the methods and procedures that are described here apply to creating any effective-dated service operation that contains effective-dated messages.

Pages Used to Perform a Full Data Publish of Current Effective Data

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Chunking Rule	EO_CHUNKRULE	Enterprise Components, Integration Definitions, Map Chunking Rules, Define Chunking Rules	Define the chunking rule description.

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Full Data Publish	EO_FULLDATAPUB	Enterprise Components, Integration Definitions, Initiate Processes, Full Data Publish	Create the run control for the Full Data Publish utility. The run control associates publish rule definitions with the scheduled Full Publish process run. For example, you can set up a run control to publish both customer and sales order full messages at the end of each day.

Creating Effective-Dated Messages

The structure of the current full message must be a clone of the original FullSync message structure. However, you must map effective-dated records to a record view that selects only those rows that contain current data.

This example uses the message CUSTOMER_FULLSYNC. The current full message for customer data, CUSTOMER_FULLSYNC, uses the following views that are created as ordering view records.

<i>Level</i>	<i>Target Records</i>	<i>Ordering View Records</i>
Level 0	CUSTOMER	CUSTOMER
Level 1	CUST_ADDR_CNTCTC	CUST_ADDR_CNTCTC
Level 1	CUST_ADDR_SEQ	CUST_ADDR_SEQ
Level 2	CUST_ADDRESS (effective-dated)	CUST_ADDR_EF2VW (current effective-dated view)
Level 1	CUST_CNTCT_SEQ	CUST_CNTCT_SEQ
Level 2	CUST_CONTACT (effective-dated)	CUST_CNCT_EF2VW (current effective-dated view)
Level 3	CUST_CNTCT_CARD (effective-dated)	CUST_CARD_EF_VW (current effective-dated view)
Level 3	CUST_CNTCT_DOC (effective-dated)	CUST_DOC_EF_VW (current effective-dated view)

<i>Level</i>	<i>Target Records</i>	<i>Ordering View Records</i>
Level 3	CUST_CNTCT_PHN (effective-dated)	CUST_PHN_EF_VW (current effective-dated view)
Level 3	CUST_CNTCT_TYPE (effective-dated)	CUST_TYPE_EF_VW (current effective-dated view)

See Also

PeopleTools: PeopleSoft Integration Broker PeopleBook, "Managing Messages," Managing Rowset-Based Messages

Creating the Service Operation

To complete a full data publish of effective dated data, you must create a service operation.

Note. The name of the service operation must end with *_EFF* suffix to be effective dated.

When you create a service operation:

- Specify the effective dated messages to publish.
- Specify a service operation queue for each message.
- Specify the directionality or routing of the integration.
- Define an OnRouteSend service operation handler, which contains the processing logic.

See Also

PeopleTools: PeopleSoft Integration Broker PeopleBook, "Managing Service Operations"

Defining the Node and Target Connector

Create a full message definition that contains the necessary records in the publishing system. You can also set up message routing by using OnRouteTo PeopleCode.

Note. Remember to insert the message version first, otherwise you can't add the tables that compose the message.

Begin by setting up the node and the transaction and connector details by using the Integration Profile setup function of PeopleSoft Integration Broker. To set up the node:

1. Create a node.

See *PeopleTools: PeopleSoft Integration Broker Administration PeopleBook*, "Adding and Configuring Nodes"

2. Set up the connector.

The default target is PSHTTP, but you can instead provide the HTTP address for another target.

See *PeopleTools: PeopleSoft Integration Broker Administration PeopleBook*, "Managing Integration Gateways"

Defining Chunking Rules and Ordering Views

Access the Chunking Rule page (Enterprise Components, Integration Definitions, Map Chunking Rules, Define Chunking Rules).

Chunking Rule							
Menu Mapping							
Chunking Rule ID:	BUSINESS_UNIT						
*Description:	Chunk by Business Unit						
*Chunk Table:	EO_BUSUNT_EOC  Business Unit Chunking Table						
<table border="1"> <thead> <tr> <th colspan="2">Chunk Fields</th> </tr> <tr> <th colspan="2">Field Name</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>BUSINESS_UNIT</td> </tr> </tbody> </table>		Chunk Fields		Field Name		1	BUSINESS_UNIT
Chunk Fields							
Field Name							
1	BUSINESS_UNIT						

Chunking Rule page

In message chunking, all data within the message contains the same break field. For example, if the break field is business unit, all transactions in the message are for the same business unit.

To ensure that the message publishes when you use chunking rules:

1. Add subscribing nodes to the chunking node table.
2. In PeopleSoft Application Designer, add OnRouteSend PeopleCode to return a list of subscribing nodes.

Creating Publish Rule Definitions

For creating the current full message, the publish rule defines these options:

- Message header and trailer creation.
- Chunking rules.
- Ordering views.

Create publish rule definitions for each current full message definition. Observe these guidelines:

- Specify only target records that are effective-dated.
- Select only the current effective row to list the ordering view record that should be used as an override when the message is published.
- The Effective Date Publish utility makes a logic pass through the data for each publish rule definition.

You can use this logic to order and chunk the data differently for each subscriber.

Note. When chunking a message, you must provide an ordering view for each record that includes the chunking fields. The fields in this view must appear in the same order as the primary keys, followed by any other keys that are needed for that record. If you override the normal key structure of the message records, you must provide the ordering views for each record to guarantee that the message is reconstructed with the correct chunking, parent, or child key relationships.

Creating Run Controls for the Full Data Publish Program

Access the Full Data Publish page (Enterprise Components, Integration Definitions, Initiate Processes, Full Data Publish).

The screenshot displays the 'Full Data Publish' interface. At the top, there is a 'Run Control ID: 1' and a 'Run' button. Below this, there are links for 'Report Manager' and 'Process Monitor'. The main section is titled 'Process Request' and includes a search bar with 'Find | View All' and a pagination indicator '1 of 1'. The configuration details are as follows:

- *Request ID:** 1
- Description:** COUNTRY_FULLSYNC_EFF
- Process Frequency:** Radio buttons for 'Once', 'Always' (selected), and 'Don't Run'.
- Parameters:** A field for '*Service Operation:' containing 'COUNTRY_SYNC' with a magnifying glass icon, and the text 'Country Table Sync.'

Full Data Publish page

Use this page to create the run control for the Full Data Publish utility.

Request ID Enter request IDs to group the Description, Process Frequency, and Message Name parameters under one unique process request. A single run control ID can encompass multiple request IDs.

Parameters Select the name of the message to publish.

The PeopleSoft system adds a run control for the currently effective FullSync message that is chunked by the setID CUSTOMER_FULLSYNC_EFF_SETID.

Note. If you insert a new row, the same run control component can publish more than one message, so you can produce both the full message and the current effective-dated full message from the same PeopleSoft Process Scheduler run.

Note. You must set up the run control parameters to start the Full Data Publish program.

Performing Full Table Replication

Access the Full Data Publish page (Enterprise Components, Integration Definitions, Initiate Processes, Full Data Publish).

Click the Run button on the Full Data Publish (EO_FULLDATAPUB) page to access and select the Full Table Data Publish check box and perform a full table replication.

The screenshot shows the 'Process Scheduler Request' page. At the top, it displays 'User ID: VP1' and 'Run Control ID: 1'. Below this, there are input fields for 'Server Name' (set to 'PSNT'), 'Run Date' (set to '08/19/2009'), 'Recurrence', and 'Run Time' (set to '4:49:52PM'). A 'Reset to Current Date/Time' button is located next to the Run Time field. A 'Time Zone' field with a search icon is also present. Below these fields is a table titled 'Process List' with columns: Select, Description, Process Name, Process Type, *Type, *Format, and Distribution. Two rows are visible in the table:

Select	Description	Process Name	Process Type	*Type	*Format	Distribution
<input type="checkbox"/>	EIR Full Table Data Publish	EOEL_FULLLPUB	Application Engine	Web	TXT	Distribution
<input type="checkbox"/>	Full Table Data Publish	EOP_PUBLISHT	Application Engine	Web	TXT	Distribution

Process Scheduler Request page showing the Full Table Data Publish option

Defining Routing

To define the message routing, you must create an OnRouteSend service operation handler and define the handler in the service operation.

Note. Perform this step only if you're chunking a message.

Example

You want to route the customer message to the nodes that are defined in the SetID/Nodes page within the Publish Setup component. Add the following PeopleCode to the OnRouteSend handler for the service operation:

```

Declare Function GETSETIDNODES PeopleCode FUNCLIB_EOEIP.PUBLISH_ROUTE_PC
    Field Formula;
Local Message &MSG;
/* Call Function that looks at Setid of first transaction in the message
and returns a list of subscribing nodes to route the message */
&MSG = GetMessage();
GETSETIDNODES(&MSG, %Date);

```

Publishing Incremental Messages of Current Effective Data

This section discusses how to:

- Create service operations for publishing incremental messages of current effective data.
- Create subscription processes that open the generic effective-dated delay function.

For incremental messages, use subscription PeopleCode to copy current effective rows to a current incremental message for immediate publication, to strip out historic data, and to store future effective rows in a delay table. A regularly scheduled Application Engine program uses the delay table data as a trigger to publish future data when that data becomes effective.

Creating Service Operations for Publishing Incremental Messages of Current Effective Data

You must create a service operation and associate an incremental message definition with it.

Note. The name of the service operation must end with the suffix *_EFF* to be effective dated.

The incremental message definition must contain the necessary records in the publishing system. Specify the message version first, otherwise you can't add the tables that compose the message. When the system requests a message channel, enter the queue definition that you previously selected.

Creating Subscription Processes That Open the Generic Effective-Dated Delay Function

The PeopleSoft system includes a function called `PROCESS_EFFDT_MSG`. This function reads through an incremental message and processes the past, current, future, or non-effective-dated information. `PROCESS_EFFDT_MSG` resides within the record `FUNCLIB_EOEIP`, in the `EFFDT_MSG_PC` field.

To create a subscription process that opens the generic effective-dated Delay function:

1. Open the `Process_Effdt_Msg` generic function stored in record `FUNCLIB_EOEIP`.
2. Pass it the name of the current effective-dated incremental message.
3. Indicate whether only rows with *Active* effective status should be selected as the current effective-dated rows.

If the `&ACTIVE_EFFSTATUS` parameter passed in is set to *False*, the current effective-dated row (whether active or inactive) is selected.

4. Pass the parameter set to *True* if only active effective-dated rows should be sent to the other system.

Note. The standard setting for the `&ACTIVE_EFFSTATUS` parameter is *False*.

Publishing Effective-Dated Rows from the Delay Table

This section provides an overview of effective-dated row publishing from the delay table and discusses how to run the Effective Date Publish utility.

Understanding Effective-Dated Row Publishing

Publishing effective-dated rows from a delay table requires:

- A future-dated entry in the delay table.
- The process request page.
- An Application Engine utility program that publishes future-dated information when it becomes current.

The Application Engine Effective Date Publish utility publishes effective-dated rows from a delay table by:

1. Retrieving from the delay table any entries that are effective within a date range.
2. Using the key strings from the delay table and record information for the current message to read the original application tables and retrieve the most current effective rows.
3. Publishing those rows to the current incremental message.

The third-party application subscribes to the current incremental messages.

The PeopleSoft system allows for an end date range on the Effective Date Publish utility if the utility was not run for one day. The end date range enables the program to run on the next date.

You can run the Effective Date Publish utility multiple times during the day, and it deletes the information from the delay queue when the future effective date data becomes current and the message for that data has been published. The Effective Date Publish utility retrieves only the latest delay table information since the prior run.

If the Effective Date Publish utility is invoked after not running for a period of time, it retrieves only the current row and publishes that as the active record. The presumption is that the subscribers want only the most current database information that is published.

Page Used to Publish Effective-Dated Rows from the Delay Table

Page Name	Definition Name	Navigation	Usage
Effective Date Pub	EO_EFFDATAPUB	Enterprise Components, Integration Definitions, Initiate Processes, Effective Date Publish	Run the Effective Date Publish utility.

Running the Effective Date Publish Utility

Access the Effective Date Pub page (Enterprise Components, Integration Definitions, Initiate Processes, Effective Date Publish).

The screenshot shows the 'Effective Date Pub' page. At the top, there is a 'Run Control ID: 1' and a 'Run' button. Below this are links for 'Report Manager' and 'Process Monitor'. The main content area is titled 'Process Request' and contains several sections:

- Process Request:** Includes a search bar with 'Find | View All | First | 1 of 1 | Last' and input fields for '*Request ID:' and 'Description:'.
- Process Frequency:** A section with three radio buttons: 'Once', 'Always', and 'Don't Run' (which is selected).
- Parameters:** Includes a search bar for '*Message Name:' and an 'End Date:' field with a calendar icon. A note below the End Date field says 'Leave blank to use Current Date'.

Effective Date Pub page

Message Name Select the current incremental message to publish.

End Date Select the latest effective date to process from the delay table.

Run

Click to run this request.

The Application Engine program uses the trigger records in the delay table and the end date parameter from the run control component to publish a current effective incremental message that contains all future-dated rows that are effective. This ensures that third-party systems that cannot manage future-dated records always receive currently active data on that data's effective date, even if that information was previously updated on the PeopleSoft system.

Publishing Effective-Dated Rows and Prior-Dated Rows from the Delay Table

This section provides an overview of publishing effective-dated rows and prior-dated rows from the Delay table, and discusses how to run the Effective Date and Prior Publish utility.

Understanding Publishing Effective-Dated Rows and Prior-Dated Rows from the Delay Table

Publishing effective-dated rows and prior-dated rows from the delay table is similar to publishing effective-dated rows. The difference is that in addition to publishing messages with a specified effective date or date range, the system also publishes all prior-dated rows with non-key changes.

See Also

Chapter 7, "Using the Effective Date Publish Utility," Understanding Effective-Dated Row Publishing, page 132

Page Used to Publish Effective-Dated Rows and Prior-Dated Rows from the Delay Table

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Effective Date Prior Publish	EO_EFFPRIORPUB	Enterprise Components, Integration Definitions, Initiate Processes, Effective Date Prior Publish	Run the Effective Date and Prior Publish utility.

Running the Effective Date and Prior Publish Utility

Access the Effective Date Prior Publish page (Enterprise Components, Integration Definitions, Initiate Processes, Effective Date Prior Publish).

Run Control ID: TEST [Report Manager](#) [Process Monitor](#)

Process Request Find | View All First 1 of 1 Last

*Request ID:

Description:

Process Frequency

Once
 Always
 Don't Run

Parameters

*Message Name:

End Date: Leave blank to use Current Date

Effective Date Prior Publish page

Message Name Select the current incremental message to publish.

End Date Select the highest effective date to process from the delay table.

Run Click to run this request.

Chapter 8

Using the Flat File Utility

This chapter provides an overview of the Flat File utility and discusses how to:

- Process inbound flat files.
- Initiate file processing.
- Test inbound flat file processing.

Understanding the Flat File Utility

When external systems send flat files to you for inbound transactions, you must develop complementary processes to translate incoming files into messages or translate outbound messages into files.

This is the flow for inbound file processing when you use the Flat File utility:

1. The utility receives a flat file in the form of a file layout object from an external system.

The flat file consists of one of the following items:

- The relevant data.
- An index file that contains pointers to the data.

Each index file lists the names of a set of data files to be processed. These files contain the application data, which is in one of the following formats: fixed record, Comma Separated Values (CSV), or XML.

2. The utility reads the file that is submitted for processing:

- If the file is an index file, the Flat File utility loads the list of data files that are associated with each index file to be processed into a parameter table.
- If it is a single data file, the utility inserts the single data file into a parameter table.

Note. If additional fields in the file layout are not in the message definition, the additional fields are ignored during the copying of the flat file data to the message and are not included in the message.

3. The utility loops through the list of data files to be processed and reads each data file.
4. The utility copies the row sets of the data files into the message.
5. The utility publishes the message.

6. The subscribing systems receive the message and initiate normal inbound data processing.

Processing Inbound Flat Files

You use the file layout definition to read and write from flat files.

To process inbound flat files:

1. Determine the necessary format of the inbound data.

If an industry standard exists, use it for your file definition.

If no industry standard exists, create a file layout object that mirrors your message object.

2. Identify the inbound process and its standard message.
3. Analyze the vendor's file structure and compare it to the standard message.

Answer these questions:

- Can you use an existing message, or do you need to create a new one?
- Can the customer conform to an existing integration point, or do you need to create one (along with corresponding subscription PeopleCode)?

4. Create the message definition.
5. Create a file layout definition with the same structure as the message definition to support the vendor file format.

The hierarchical structure of the data in the File Layout Definition must match that of the message definition. For example, suppose a message has three levels: level zero, containing record A, level one, containing records B and C, and level two, containing record D.

All file layouts that are associated with this message must also have record A in level zero, record B and C in level one, and record D in level two.

Note. The file layout does not need to contain the exact same fields as the message definition.

For every record in your file layout, add a new file field, `AUDIT_ACTN`, as the first field in the record (except when the field already exists in the application table).

You can associate more than one file layout with a single message. For example, vendor A may have a different number of fields than vendor B, so you may have two file layouts: one for A and one for B.

Specify the file ID uniquely to include a row in a file, which is necessary in mapping the data to its proper record. Include start and end points when dealing with more than one record in a file layout.

Note. Each record in the file layout has a file record ID attribute. Do not confuse this with the file layout ID. The file layout ID determines whether a new layout is encountered for multiple file layout processing.

When you subscribe to the message and normal inbound data processing begins, you can invoke the `SetDefault PeopleCode` function to set the default values for fields that were not present in the input file.

6. Update or create the inbound file rule pages.
7. Create subscription PeopleCode in PeopleSoft Application Designer to process the message.

Have the standard inbound process subscribe to and process the message normally. The standard message definition should have a subscription process that initiates the normal inbound processing for the object to which you hook your application logic to process the file data.

8. Test the inbound flat file processing.

Note. You can process multiple inbound flat files at one time. Specifying an inbound index file as part of the Flat File utility parameters causes the system to read all input files within the index file and to use the associated file layout object and message to convert the data. Similarly, specify a wildcard in the filename in the inbound file rule component, but make sure that all files that meet the wildcard criteria correspond to the file layout and message mapping that are defined.

Initiating File Processing

This section discusses how to:

- Set up inbound flat file processing.
- Initiate inbound flat file processing.

Pages Used to Initiate File Processing

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
File Inbound	EO_FILE_INBOUND	Enterprise Components, Integration Definitions, Inbound File Rule	Set up inbound flat file processing.
Inbound File	EO_FILETOMSG	Enterprise Components, Integration Definitions, Initiate Processes, Inbound File Publish	Initiate inbound flat file processing. This file-to-message processing function reads the file rowset and publishes it as a message.

Setting Up Inbound Flat File Processing

Access the File Inbound page (Enterprise Components, Integration Definitions, Inbound File Rule).

File Inbound

File Identifier: MARKET_RATE_LOAD

***Inbound File:** **Index Flag**

***Status:** ▼

File Layout ID:

LUW Size:

Program **Section:**

Name:

- Create Message Header**
- Create Message Trailer**

File Layout

[Customize](#) | [Find](#) | [View All](#) | | [First](#) ◀ | 1 of 1 | ▶ [Last](#)

	*Definition Name	*Message Name		
1	<input type="text" value="MARKET_RATE_LOAD"/>	<input type="text" value="MARKET_RATE_LOAD"/>	+	-

File Inbound page

Referencing Application Engine Program

The file inbound setup allows you to reference an AE program and section that gets called as soon as the data processing of the specified inbound file is completed. This functionality comes in handy if you wish to invoke customized actions after the flat file utility finishes processing data--simply build the custom AE program and specify it on this page for the corresponding file rule.

Below is a sample code for an AE program that removes entries of data files that have been processed from index files. Steps of this program are executed only if the input file is flagged as an Index file.

```

/* Open the index file in Read-only mode */
/* Initialize a string array and save all unprocessed file names from the Index=>
file */
/* Open the Index in Write mode, thereby clearing contents from previous=>
iteration, and write the contents of the array to the file */
/* When the last data file has been processed, write 'All Done' to the Index file=>
*/

Local string &Index_FileName, &LineString;
Local File &Index_File;
Local array of string &Inbound_Files;
Local number &I;
Local boolean &Found;
If EO_FILEPUB_AET.INDEX_FILE_FLG = "Y" Then
  /* Get index filename from the Inbound File Publish Rule */
  SQLExec("Select FILE_INBOUND from PS_EO_FLOINDEFN WHERE FILE_ID = :1", EO_=>
FILEPUB_AET.FILE_ID, &Index_FileName);

  /* Open Index file as Read-only */
  &Index_File = GetFile(&Index_FileName, "R", %FilePath_Absolute);

  /* Initialise string array */
  &Inbound_Files = CreateArrayRept("", 0);

  /* Save unprocessed filenames to array */
  While &Index_File.ReadLine(&LineString);
    If &LineString <> EO_FILEPUB_AET.FILE_INBOUND Then
      &Inbound_Files.Push(&LineString);
    End-If;
  End-While;
  &Index_File.Close();

  /* Open index file in Write mode */
  &Index_File = GetFile(&Index_FileName, "W", %FilePath_Absolute);

  /* Write unprocessed filenames to index file */
  &I = 0;
  While &Inbound_Files.Next(&I)
    &Found = True;
    &Index_File.WriteLine(&Inbound_Files [&I]);
  End-While;

  /* If all files processed, print Done */
  If Not &Found Then
    &Index_File.WriteLine("All Done!");
  End-If;

  &Index_File.Close();

End-If;

```

File Identifier	Displays the inbound file that you are associating with the rule.
Inbound File	Enter the index file name or the data file name. Specify the full path information. The PeopleCode program uses the <i>%filepath_absolute</i> variable when opening the file.
Index Flag	Select to distinguish between the index and the data file.

Status	Select whether this inbound file rule is <i>Active</i> or <i>Inactive</i> . The default value is <i>Inactive</i> .
File Layout ID	Select a layout to associate with the file.
LUWSize (logical unit of work size)	To limit the message size, enter the number of level zero rows that are in each message. The output message is normally determined by the <code>MaxMessageSize</code> system parameter.
Program and Section	Enter the name of a PeopleSoft Application Engine (AE) program and section to invoke when the utility finishes processing data.
Create Message Header	Select to create a header message. Use the header message as a trigger in the subscription process to initialize tables before they receive the data messages. This option is selected by default.
Create Message Trailer	Select to create a trailer message. Use the trailer message as a trigger in the subscription process to indicate that all the data messages have been received. This option is selected by default.

File Layout

Definition Name and Message Name	<p>If the File Layout ID field is blank, this field should contain only one entry.</p> <p>If the File Layout ID field is not blank, this scroll area must contain an entry for each file layout definition name that is specified in the inbound file.</p>
---	--

Note. Use the wildcards * and ? for the file name but not for the directory path. The file layout and message mapping must be valid for all files that meet the wildcard criteria.

Initiating Inbound Flat File Processing

Access the Inbound File page (Enterprise Components, Integration Definitions, Initiate Processes, Inbound File Publish).

Inbound File page

Use this page to initiate inbound flat file processing. This file-to-message processing function reads the file rowset and publishes it as a message.

Parameters

File Identifier Select or enter the name of the file identifier that you set up in the File Inbound page. The file identifier is tied to the publish rules.

Run Click to run this request.

Publishing a New Message

The Inbound File page runs an Application Engine process that initiates the file-to-message processing. The file-to-message processing function reads the file rowset and publishes it as a message.

If an index file exists when the inbound conversion process runs, the Application Engine program loads the list of files to be converted into a parameter table and completes a commit. The Application Engine program uses the list of files within the parameter table to restart the processing if a particular flat file fails. If a single data file is provided, then the rowset processing immediately begins.

The file publish process goes through each of the rowsets of the file layout and copies them into the message row sets.

If the audit action (AUDIT_ACTN) exists in the file, it is copied to the PSCAMA record. If the audit action does not exist in the file, the publishing process uses the default value that is specified in the file layout field property.

The Flat File utility publishes a new message when one of the following situations occurs:

- Maximum message size is exceeded.
- Logical unit of work publish size is reached.
- A new file layout is detected.
- End of file is reached.

The Application Engine program completes a commit every time a message is published from a file. After conversion, the flat file remains in the parameter table with a status of *Processed*.

Note. The file layout should exactly match the message layout (excluding the PSCAMA record) and should use the same character set as that used by the file: either American National Standards Institute or Unicode.

Testing Inbound Flat File Processing

To test inbound files:

1. Create a sample flat file, or ask the third-party vendor for a sample flat file.
2. Launch the Flat File utility.
 - a. Through the browser, sign in to PeopleSoft Internet Architecture.
 - b. Select Enterprise Components, Management, Inbound File Rule.
3. Run the Application Engine program to convert the sample flat file to a message by running Message Monitor.

Use Message Monitor to ensure that the inbound file processing created a publish message that contains the sample flat file data.

- a. Verify that the standard inbound subscription process received the message and processed it into the application tables.
- b. Determine whether the values become the inherited values (if you used the inherited value feature in file layout).
- c. Validate that the production or staging tables loaded with the correct field values.

For production tables, look in the PeopleSoft application pages.

For staging tables, use either the PeopleSoft application pages or run a query by using PeopleSoft Query.

- d. Ensure that the date formats conform.

Chapter 9

Using the XML Schema Utility

This chapter provides an overview of the XML Schema utility and discusses how to generate the XML Schema.

Note. The XML Schema utility has been superseded by PeopleTools Message Schema Builder, which is a part of PeopleSoft Integration Broker.

Understanding the XML Schema Utility

PeopleSoft Open Integration Framework enables near real-time messaging and transactions by using a format that is based on XML to convey information between diverse applications in a standard way. To take advantage of this standardization, you must obtain clear XML definitions (schemas) for each application message, component interface, or business interlink.

The XML Schema utility provides the following features:

- Output options for the XML Schema utility, document type definition (DTD), or BizTalk definition for all application messages.
- The ability to create an XML definition for a single object, for all of the objects, or for all of the objects by a specific owner.
- A single flat file for each XML definition that is written to your system's %TEMP directory (when you use the Microsoft Windows client) or the server's common access file directory (when you use PeopleSoft Internet Architecture).
- An application foundation for future standards of XML definitions.

Generating the XML Schema

This section discusses how to generate the XML Schema.

Page Used to Generate the XML Schema

Page Name	Definition Name	Navigation	Usage
Generate XML Schema	EO_GEN_XML_DATA	Enterprise Components, Integration Definitions, Review XML Schema	Generate DTDs, XML schemas, and BizTalk definitions.

Generating the XML Schema

Access the Generate XML Schema page (Enterprise Components, Integration Definitions, Review XML Schema).

Generate XML Schema page

- | | |
|---|--|
| App Msg Selection Criteria
(application message selection criteria) | Select application selection message criteria. Values are <i>All Msg</i> (all messages), <i>Channel</i> , <i>Owner ID</i> and <i>Single Msg</i> (single message). Depending on the selection criteria, you can enter the selection value (if already known) or search for the value. |
| Generate DTD Spec | Select for DTD spec output format. |
| Generate XML Schema | Select for XML schema output format. |
| Generate Biztalk Definition | Select for BizTalk definition output format. |
| Generate | Click to generate the selected output formats. |

The utility queries the relevant PeopleTools tables to generate the selected types of XML schemas and writes the results to the server's file directory or your system's Temp directory, depending on the client that you use.

To produce an XML schema, DTD, or BizTalk definition:

1. Define the selection criteria for application messages, component interfaces, and business interlinks.
2. Select XML schemas, DTDs, or BizTalk definitions for application message, component interface, and business interlink objects.

PeopleCode sends a query to the PeopleTools tables to create the selected types of XML definitions.

The XML Schema utility then writes the definitions to the file directory as specified by the PS_SERVDIR environment variable when you are using PeopleSoft Internet Architecture or the %TEMP directory of your system when you are using the Microsoft Windows client.

Interpreting Sample Output

The following code shows three samples of output for the same application message (in this case, MARKET_RATE_TYPE_FULLSYNC) in BizTalk, DTD, and XML schema formats.

Example: BizTalk

The following code shows MARKET_RATE_TYPE_FULLSYNC in BizTalk format:

```

<BizTalk xmlns="urn:schemas-biztalk-org:BizTalk/biztalk-0.81.xml">
<Body>
<xsd:schema xmlns:xsd="http://www.w3.org/2000/10/XMLSchema">
<xsd:element name="MARKET_RATE_TYPE_FULLSYNC"
  type="MARKET_RATE_TYPE_FULLSYNCType"/>

<xsd:complexType name="MARKET_RATE_TYPE_FULLSYNCType">
<xsd:sequence>
  <xsd:element name="FieldTypes" type="FieldTypesType"/>
  <xsd:element name="MsgData" type="MsgDataType"/>
</xsd:sequence>
</xsd:complexType>

<xsd:complexType name="FieldTypesType">
<xsd:sequence>
  <xsd:element name="RT_TYPE_TBL" type="FieldTypesRT_TYPE_TBLType"/>
  <xsd:element name="PSCAMA" type="PSCAMA"/>
</xsd:sequence>
</xsd:complexType>

<xsd:complexType name="FieldTypesRT_TYPE_TBLType">
<xsd:sequence>
  <xsd:element name="RT_TYPE" type="FieldTypesFieldType"/>
  <xsd:element name="DESCR" type="FieldTypesFieldType"/>
  <xsd:element name="DESCRSHORT" type="FieldTypesFieldType"/>
</xsd:sequence>
  <xsd:attribute name="class" type="xsd:string" use="required" value="R"/>
</xsd:complexType>

<xsd:complexType name="PSCAMA">
  <xsd:sequence>
    <xsd:element name="LANGUAGE_CD" type="LANGUAGE_CDType" minOccurs="0"
      maxOccurs="1"/>
    <xsd:element name="AUDIT_ACTN" type="AUDIT_ACTNType"/>
    <xsd:element name="BASE_LANGUAGE_CD" type="BASE_LANGUAGE_CDType"
      minOccurs="0" maxOccurs="1"/>
    <xsd:element name="MSG_SEQ_FLG" type="MSG_SEQ_FLGType" minOccurs="0"
      maxOccurs="1"/>
    <xsd:element name="PROCESS_INSTANCE" type="PROCESS_INSTANCEType"
      minOccurs="0" maxOccurs="1"/>
    <xsd:element name="PUBLISH_RULE_ID" type="PUBLISH_RULE_IDType"
      minOccurs="0" maxOccurs="1"/>
    <xsd:element name="MSGNODENAME" type="MSGNODENAMEType" minOccurs="0"
      maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="class" type="xsd:string" use="required" value="R"/>
</xsd:complexType>

<xsd:complexType name="LANGUAGE_CDType" >
  <xsd:attribute name="type" type="fieldtypes" use="optional"/>
</xsd:complexType>

<xsd:complexType name="AUDIT_ACTNType" >
  <xsd:attribute name="type" type="fieldtypes" use="optional"/>
</xsd:complexType>

<xsd:complexType name="BASE_LANGUAGE_CDType" >
  <xsd:attribute name="type" type="fieldtypes" use="optional"/>
</xsd:complexType>

<xsd:complexType name="MSG_SEQ_FLGType">
  <xsd:attribute name="type" type="fieldtypes" use="optional"/>
</xsd:complexType>

```

```

<xsd:complexType name="PROCESS_INSTANCEType">
  <xsd:attribute name="type" type="fieldtypes" use="optional"/>
</xsd:complexType>

<xsd:complexType name="PUBLISH_RULE_IDType">
  <xsd:attribute name="type" type="fieldtypes" use="optional"/>
</xsd:complexType>

<xsd:complexType name="MSGNODENAMEType">
  <xsd:attribute name="type" type="fieldtypes" use="optional"/>
</xsd:complexType>

<xsd:complexType name="MsgDataType">
  <xsd:sequence>
    <xsd:element name="Transaction">
      <xsd:complexType>
        <xsd:sequence>
          <xsd:element name="RT_TYPE_TBL" type="MsgDataRT_TYPE_TBLType"/>
          <xsd:element name="PSCAMA" type="PSCAMA"/>
        </xsd:sequence>
      </xsd:complexType>
    </xsd:element>
  </xsd:sequence>
</xsd:complexType>

<xsd:complexType name="MsgDataRT_TYPE_TBLType">
<xsd:sequence>
  <xsd:element name="RT_TYPE">
<xsd:simpleType>
<xsd:restriction base="xsd:string" >
  <xsd:pattern value="[A-Z]{1-5}" />
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
  <xsd:element name="DESCR">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
  <xsd:pattern value=".{1-30}" />
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
  <xsd:element name="DESCRSHORT">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
  <xsd:pattern value=".{1-10}" />
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
</xsd:sequence>
  <xsd:attribute name="class" type="xsd:string" use="required" value="R"/>
</xsd:complexType>

<xsd:complexType name="FieldTypesFieldType">
  <xsd:attribute name="type" type="fieldtypes"/>
</xsd:complexType>

<xsd:simpleType name="fieldtypes">
<xsd:restriction base="xsd:string">
  <xsd:enumeration value="CHAR"/>
  <xsd:enumeration value="NUMBER"/>
  <xsd:enumeration value="DATE"/>
  <xsd:enumeration value="DATETIME"/>
  <xsd:enumeration value="TIME"/>

```

```

</xsd:restriction>
</xsd:simpleType>

</xsd:schema>
</Body>
</BizTalk>

```

Example: DTD

The following code shows MARKET_RATE_TYPE_FULLSYNC in DTD format:

```

<!ELEMENT MARKET_RATE_TYPE_FULLSYNC (FieldTypes, MsgData)>

  <!ENTITY % recordtypes "class (R | SR) #REQUIRED" >
  <!ENTITY % fieldtypes "type (CHAR | NUMBER | DATE | TIME | DATETIME) #IMPLIED" >

<!ELEMENT FieldTypes (RT_TYPE_TBL, PSCAMA)>

<!ELEMENT PSCAMA (LANGUAGE_CD?, AUDIT_ACTN, BASE_LANGUAGE_CD?, MSG_SEQ_FLG?,
PROCESS_INSTANCE?, PUBLISH_RULE_ID?, MSGNODENAME?)>
  <!ATTLIST PSCAMA class (R | SR) #REQUIRED>
  <!ELEMENT LANGUAGE_CD (#PCDATA)>
    <!ATTLIST LANGUAGE_CD type (CHAR | NUMBER | DATE | TIME | DATETIME) #IMPLIED>
  <!ELEMENT AUDIT_ACTN (#PCDATA)>
    <!ATTLIST AUDIT_ACTN type (CHAR | NUMBER | DATE | TIME | DATETIME) #IMPLIED>
  <!ELEMENT BASE_LANGUAGE_CD (#PCDATA)>
    <!ATTLIST BASE_LANGUAGE_CD type (CHAR | NUMBER | DATE | TIME |
    DATETIME) #IMPLIED>
  <!ELEMENT MSG_SEQ_FLG (#PCDATA)>
    <!ATTLIST MSG_SEQ_FLG type (CHAR | NUMBER | DATE | TIME | DATETIME) #IMPLIED>
  <!ELEMENT PROCESS_INSTANCE (#PCDATA)>
    <!ATTLIST PROCESS_INSTANCE type (CHAR | NUMBER | DATE | TIME |
    DATETIME) #IMPLIED>
  <!ELEMENT PUBLISH_RULE_ID (#PCDATA)>
    <!ATTLIST PUBLISH_RULE_ID type (CHAR | NUMBER | DATE | TIME |
    DATETIME) #IMPLIED>
  <!ELEMENT MSGNODENAME (#PCDATA)>
    <!ATTLIST MSGNODENAME type (CHAR | NUMBER | DATE | TIME | DATETIME) #IMPLIED>
<!ELEMENT RT_TYPE_TBL (RT_TYPE, DESCR, DESCRSHORT)>
  <!ATTLIST RT_TYPE_TBL class (R | SR) #REQUIRED>

<!ELEMENT RT_TYPE (#PCDATA)>
  <!ATTLIST RT_TYPE type (CHAR | NUMBER | DATE | TIME | DATETIME) #IMPLIED>
<!ELEMENT DESCR (#PCDATA)>
  <!ATTLIST DESCR type (CHAR | NUMBER | DATE | TIME | DATETIME) #IMPLIED>
<!ELEMENT DESCRSHORT (#PCDATA)>
  <!ATTLIST DESCRSHORT type (CHAR | NUMBER | DATE | TIME | DATETIME) #IMPLIED>

<!ELEMENT MsgData (Transaction)>
<!ELEMENT Transaction (RT_TYPE_TBL, PSCAMA)>

```

Example: XML Schema

The following code shows MARKET_RATE_TYPE_FULLSYNC in XML schema format:

```

<xsd:schema xmlns:xsd="http://www.w3.org/2000/10/XMLSchema">

<xsd:element name="MARKET_RATE_TYPE_FULLSYNC"
  type="MARKET_RATE_TYPE_FULLSYNCType" />

<xsd:complexType name="MARKET_RATE_TYPE_FULLSYNCType">
<xsd:sequence>
  <xsd:element name="FieldTypes" type="FieldTypesType" />
  <xsd:element name="MsgData" type="MsgDataType" />
</xsd:sequence>
</xsd:complexType>

<xsd:complexType name="FieldTypesType">
<xsd:sequence>
  <xsd:element name="RT_TYPE_TBL" type="FieldTypesRT_TYPE_TBLType" />
  <xsd:element name="PSCAMA" type="PSCAMA" />
</xsd:sequence>
</xsd:complexType>

<xsd:complexType name="FieldTypesRT_TYPE_TBLType">
<xsd:sequence>
  <xsd:element name="RT_TYPE" type="FieldTypesFieldType" />
  <xsd:element name="DESCR" type="FieldTypesFieldType" />
  <xsd:element name="DESCRSHORT" type="FieldTypesFieldType" />
</xsd:sequence>
  <xsd:attribute name="class" type="xsd:string" use="required" value="R" />
</xsd:complexType>

<xsd:complexType name="PSCAMA">
  <xsd:sequence>
    <xsd:element name="LANGUAGE_CD" type="LANGUAGE_CDType" minOccurs="0"
      maxOccurs="1" />
    <xsd:element name="AUDIT_ACTN" type="AUDIT_ACTNType" />
    <xsd:element name="BASE_LANGUAGE_CD" type="BASE_LANGUAGE_CDType"
      minOccurs="0" maxOccurs="1" />
    <xsd:element name="MSG_SEQ_FLG" type="MSG_SEQ_FLGType" minOccurs="0"
      maxOccurs="1" />
    <xsd:element name="PROCESS_INSTANCE" type="PROCESS_INSTANCEType"
      minOccurs="0" maxOccurs="1" />
    <xsd:element name="PUBLISH_RULE_ID" type="PUBLISH_RULE_IDType"
      minOccurs="0" maxOccurs="1" />
    <xsd:element name="MSGNODENAME" type="MSGNODENAMEType" minOccurs="0"
      maxOccurs="1" />
  </xsd:sequence>
  <xsd:attribute name="class" type="xsd:string" use="required" value="R" />
</xsd:complexType>

<xsd:complexType name="LANGUAGE_CDType" >
  <xsd:attribute name="type" type="fieldtypes" use="optional" />
</xsd:complexType>

<xsd:complexType name="AUDIT_ACTNType" >
  <xsd:attribute name="type" type="fieldtypes" use="optional" />
</xsd:complexType>

<xsd:complexType name="BASE_LANGUAGE_CDType" >
  <xsd:attribute name="type" type="fieldtypes" use="optional" />
</xsd:complexType>

<xsd:complexType name="MSG_SEQ_FLGType">
  <xsd:attribute name="type" type="fieldtypes" use="optional" />
</xsd:complexType>

<xsd:complexType name="PROCESS_INSTANCEType">

```

```

    <xsd:attribute name="type" type="fieldtypes" use="optional" />
  </xsd:complexType>

  <xsd:complexType name="PUBLISH_RULE_IDType">
    <xsd:attribute name="type" type="fieldtypes" use="optional" />
  </xsd:complexType>

  <xsd:complexType name="MSGNODENAMEType">
    <xsd:attribute name="type" type="fieldtypes" use="optional" />
  </xsd:complexType>

  <xsd:complexType name="MsgDataType">
    <xsd:sequence>
      <xsd:element name="Transaction">
        <xsd:complexType>
          <xsd:sequence>
            <xsd:element name="RT_TYPE_TBL" type="MsgDataRT_TYPE_TBLType" />
            <xsd:element name="PSCAMA" type="PSCAMA" />
          </xsd:sequence>
        </xsd:complexType>
      </xsd:element>
    </xsd:sequence>
  </xsd:complexType>

  <xsd:complexType name="MsgDataRT_TYPE_TBLType">
    <xsd:sequence>
      <xsd:element name="RT_TYPE">
        <xsd:simpleType>
          <xsd:restriction base="xsd:string" >
            <xsd:pattern value="[A-Z]{1-5}" />
          </xsd:restriction>
        </xsd:simpleType>
      </xsd:element>
      <xsd:element name="DESCR">
        <xsd:simpleType>
          <xsd:restriction base="xsd:string">
            <xsd:pattern value=".{1-30}" />
          </xsd:restriction>
        </xsd:simpleType>
      </xsd:element>
      <xsd:element name="DESCRSHORT">
        <xsd:simpleType>
          <xsd:restriction base="xsd:string">
            <xsd:pattern value=".{1-10}" />
          </xsd:restriction>
        </xsd:simpleType>
      </xsd:element>
    </xsd:sequence>
    <xsd:attribute name="class" type="xsd:string" use="required" value="R" />
  </xsd:complexType>

  <xsd:complexType name="FieldTypesFieldType">
    <xsd:attribute name="type" type="fieldtypes" />
  </xsd:complexType>

  <xsd:simpleType name="fieldtypes">
    <xsd:restriction base="xsd:string">
      <xsd:enumeration value="CHAR" />
      <xsd:enumeration value="NUMBER" />
      <xsd:enumeration value="DATE" />
      <xsd:enumeration value="DATETIME" />
      <xsd:enumeration value="TIME" />
    </xsd:restriction>
  </xsd:simpleType>

```

```
</xsd:simpleType>
```

```
</xsd:schema>
```


Chapter 10

Using Desktop Integration

This chapter provides an overview of desktop integration and discusses how to:

- Set up desktop integration.
- Set up tasks.
- Register address books.
- Register internal address books.
- Set up appointments.
- Set up file transfers.
- Define dynamic displays.
- Use the display log.
- Use the PeopleSoft Outlook menu.

Understanding Desktop Integration

Desktop Integration provides seamless integration between Microsoft Office and your PeopleSoft applications, enabling your organization to schedule and track appointments, meetings, tasks, and corresponding documentation. This is accomplished through a framework to the Microsoft Office suite that enables PeopleSoft applications to extend functionality into the office suite through layers. A two-way communication is established between the PeopleSoft application and Microsoft Outlook and Word, with Outlook receiving the information from and sending updates to the PeopleSoft application.

The framework consists of the following components:

Microsoft Outlook and Word Add-In

Add-ins are supplemental programs that extend the functionality of Office applications, adding custom commands and custom features that plug into the application through well-known entry points. The Microsoft Outlook and Word Add-ins contain all of the pieces necessary for sending information to and receiving information from the PeopleSoft applications. Microsoft Office Add-ins invoke functions in this layer for user authentication, launching web services to receive and send data from the PeopleSoft application. On the PeopleSoft side, services and application classes exist that accept the requests from Microsoft Outlook and Word and perform the necessary actions and data retrieval. The Microsoft Outlook and Word Add-ins use a Secure Socket Layer (SSL) to connect to the PeopleSoft applications for secure and synchronous messaging.

See [Chapter 10, "Using Desktop Integration," Understanding the PeopleSoft and Outlook Integration, page 196.](#)

Integration Broker/Web Services Layer

Oracle uses the Integration Broker to connect Microsoft Outlook and Word to the PeopleSoft applications. Oracle delivers predefined interfaces and security classes. Desktop Integration does *not* require a dedicated server nor any additional hardware. To connect Microsoft Outlook and Word to PeopleSoft applications and ensure security, SSL is required.

Desktop Integration Layer

The Desktop Integration application classes are responsible for receiving the messages sent through Integration Broker from the Microsoft Office applications. The Desktop Integration layer creates, updates, and moves the data in and out of the PeopleSoft system and is responsible for responding to all events. As events are processed, control is optionally passed on to the PeopleSoft Application Layer for handling.

PeopleSoft Application Layer—for the PeopleSoft Applications to Use

Any application-specific functions are contained within the PeopleSoft Application Layer. When you are creating new integrations or customizing existing ones, all application-specific code is contained within the application layer.

Prerequisites

These are the prerequisites for using Desktop Integration:

- Microsoft Outlook 2007 or higher.

You must license and install Microsoft Outlook 2007 or higher. Oracle does not provide this software, you must purchase and license it separately.

- Microsoft Word 2007 or higher.

You must license and install Microsoft Word 2007 or higher. Oracle does not provide this software, you must purchase and license it separately.

- Integration Broker.

You do not need a dedicated server. Oracle delivers the interface predefined. Your Integration Broker must be configured and started.

- Secure Socket Layer (SSL).

This is used to connect to Microsoft Outlook. This is in the form of an https URL. Desktop Integration requires a secure connection for all communication.

- Unique System IDs.

System IDs must be unique across your organization to allow use against multiple databases.

Setting Up Desktop Integration

This section discusses how to set up Desktop Integration. Specifically, it discusses how to:

- Set up the Integration Broker.
- Set up pages and web service security.
- Set up the system.

Pages Used to Set Up Desktop Integration

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Service Operations - General page	IB_SERVICE	PeopleTools, Integration Broker, Integration Setup, Service Operations, General	Customize integration metadata to suit your particular business needs. However, note that integration metadata for this functionality (for example, service operations, routing definitions, service operations handlers, and so on) is delivered with your application; no additional configuration is required.
Web Service Access	WS_ACCESS_IB	Click the Service Operation Security link on the Service Operations - General page.	Define permissions and user access. Customize integration metadata to suit your particular business needs.
System Setup	EODI_SYSTEM_SETUP	Enterprise Components, Desktop Integration, System Setup	Configure Desktop Integration and the PeopleSoft system.

Setting Up the Integration Broker

Access the Service Operations - General page (PeopleTools, Integration Broker, Integration Setup, Service Operations, General).

General	Handlers	Routings
Service Operation: EODI_GET_SYSTEM_INFO		
Operation Type: Synchronous		
*Operation Description:	<input type="text" value="Get System Info"/>	
Operation Comments:	<input type="text"/>	
	<input checked="" type="checkbox"/> User/Password Required	
	*Security Verification:	<input type="text" value="None"/>
Object Owner ID:	<input type="text" value="Enterprise Components"/>	
Operation Alias:	<input type="text" value="EODI_GetSystemInfo"/>	
Service Operation Security		
Default Service Operation Version		
*Version:	<input type="text" value="V1"/>	<input checked="" type="checkbox"/> Default <input checked="" type="checkbox"/> Active
Version Description:	<input type="text" value="Get System Info"/>	
Version Comments:	<input type="text"/>	
	<input type="checkbox"/> Non-Repudiation	
	<input type="checkbox"/> Runtime Schema Validation	
Introspection		
<input type="button" value="Add Fault Type"/>		
Routing Status		
Any-to-Local:	Exists	
Local-to-Local:	Does not exist	
Routing Actions Upon Save		
<input type="checkbox"/> Regenerate Any-to-Local		
<input type="checkbox"/> Generate Local-to-Local		
<input type="checkbox"/> Transactional		
Warning: Regenerating sets all routing field values to their initial state.		
Message Information		
Type:	Request	
Message.Version:	<input type="text" value="EODI_REQUEST.V1"/>	<input type="button" value="View Message"/>
Type:	Response	
Message.Version:	<input type="text" value="EODI_SYSTEM_INFO.V1"/>	<input type="button" value="View Message"/>

Service Operations - General page

To use Desktop Integration functionality, PeopleSoft Integration Broker must be set up and running.

Integration metadata for this functionality (for example, service operations, routing definitions, service operation handlers, and so on) is delivered with your application; no additional configuration is required. However, you can customize integration metadata to suit your particular business needs. All Desktop Integration service definitions have names that begin with *EODI* and are grouped by function. By default, the default local node receives all inbound integrations.

This PeopleBook contains all the information for configuring and setting up the Integration Broker.


See *PeopleTools: PeopleSoft Integration Broker Administration PeopleBook*

This PeopleBook describes how to create and modify integration metadata.

See *PeopleTools: PeopleSoft Integration Broker PeopleBook*

Setting Up Pages and Web Service Security

Access the Web Service Access page (click the Service Operation Security link on the Service Operations - General page).



Web Service Access page

Oracle delivers these permission lists:

EODI1000

Administrator level service operations for the queue. Select the access that you want for the user group:

- Full Access
- Queue
- App Class

EODI1000 is the permission list that contains all of the pages under the Desktop Integration menu. Administrators need access to this list.

EODI_Administrator has EODI1000 defined as a role.

EODI2000

Service level service operations for the application classes. Select the access that you want for the user group:

- Full Access
- Queue
- App Class

EODI2000 is the permission list that contains all of the web services that Desktop Integration uses. Any user of the Microsoft Outlook and Word Add-Ins needs access to this list.

The permission list contains a list of all Integration Broker services that the add-ins use to communicate with PeopleSoft applications.

EODI_RemoteUser has EODI2000 defined as a role.

Setting Up the System

Access the System Setup page (Enterprise Components, Desktop Integration, System Setup).

The screenshot shows the 'System Setup' page with the following fields and values:

- *System ID:** TM910DVL
- Release Version:** 1
- *Description:** TM910DVL
- Last Task Transaction ID:** 0
- *Logging Level:** 3 - Information and above (dropdown menu)
- Last Appt. Transaction ID:** 4

The 'File Transfer Options' section includes:

- Last Transaction ID:** 0
- *File Chunk Size (Bytes):** 500000
- *Temporary Directory:** C:\temp

System Setup page

System ID

Enter a unique system ID. This ID must be unique across your organization to allow use across multiple data bases.

After being set, this ID is used internally as a key on different pieces of information.

For example, if you plan to connect to more than one PeopleSoft database, each database must have a unique ID. So if you have a Human Resources (HR) instance and a Financials/Supply Chain Management (FSCM) instance, each system should use a different system ID. When a transaction is passed to Microsoft Outlook, that transaction includes the system ID and the transaction ID from the database where it originated. Later, when the add-in needs to know the origin of that data, the information from the system ID and the transaction ID is used.

Release Version

The version of the system identified by the system ID. This number is predefined.

This number is used internally and is updated only when a new version of Desktop Integration is available.

Description

A description of the system that the system ID identifies. Enter a unique description.

The description can be a mixture of uppercase and lowercase with a maximum limit of 30 characters.

This description is visible within the Microsoft Office applications server configuration.

Logging Level

Specify the level of logging that you want. This controls the level of detail that is sent to the display log. Select a logging level from the drop-down list box. Values are:

- 0: No logging

This is the default. Due to minor performance impact, Oracle recommends that you select 0.

- 1: Errors
- 2: Warnings and above
- 3: Information and above

See [and Chapter 10, "Using Desktop Integration," Using the Display Log, page 194.](#)

Last Task Transaction ID

The transaction ID for the last task that keeps the tasks synchronous. This ID is auto incremented and should not normally be adjusted.

Last Appt. Transaction ID
(last appointment transaction identifier)

The date of the last appointment transaction.

This is autogenerated, tracked, and used for synchronization.

Last Transaction ID

This is autogenerated, tracked, and used for synchronization.

File Chunk Size (Bytes)

The file size with which to move data to a temporary directory. This value is predefined. Administrators can set up chunking size for performance purposes.

Temporary Directory

The temporary directory where you want to reassemble the data.

Files are spooled to a temporary directory and reassembled there before completing. This directory must be available on all application servers that may process the incoming Desktop Integration Broker messages.

See [and Chapter 10, "Using Desktop Integration," Using the Display Log, page 194.](#)

Setting Up Tasks

This section discusses how to:

- Set up task registration.
- Set up the task queue.
- Compose task contents.

Pages Used to Set Up Tasks

Page Name	Definition Name	Navigation	Usage
Task Registration	EODI_TSK_REG	Enterprise Components, Desktop Integration, Task Registration	Select a task to be queued up and put into the user's tasks.
Task Queue - Task	EODI_TSK_QUEUE	Enterprise Components, Desktop Integration, Task Queue, Task	Define the things that you want as defaults in the user's tasks.
Task Queue - Message	EODI_TSK_MESSAGE	Enterprise Components, Desktop Integration, Task Queue, Message	Compose the message body of tasks.

Setting Up Task Registration

Access the Task Registration page (Enterprise Components, Desktop Integration, Task Registration).

Task Registration

Task Process ID: REVIEW_PTO

*Description: Review Time Off

Object Owner ID: Enterprise Components Demo

*Source: Queue

*Package Name: EODI_EVENTS

*Path: Samples

*Class ID: TaskWorkListSample

Dynamic Displays Find First 1 of 1 Last

*ID: [Search]

Authorized Users Find First 1 of 1 Last

*Source: Role Name Manager [Search]

Assigned Users Find First 1 of 1 Last

User ID: [Search] Email Address: [Search]

Task Registration page

In a generic, no customization implementation, use this page to define the Authorized Users section (source ID). All other fields are prepopulated and defined here for your reference only.

A task is a way for something to be queued up and put into the user's tasks. Oracle delivers the tasks with the application. You can customize the tasks to suit your particular user groups and business needs.

The status of tasks is updated when you log into Microsoft Outlook.

Task Process ID	<p>Displays the prepopulated ID, which is delivered with the application and is unique across your system.</p> <p>You can create new IDs as a customization.</p>
Description	<p>Enter a text description of the task process.</p>
Object Owner ID	<p>Select the application that owns the object (for example, Enterprise Components). This drop-down list box that contains values for all of the available applications.</p> <p>This is not a required field.</p>
Source	<p>Select the source of the task. Values are:</p> <ul style="list-style-type: none"> • <i>Queue</i> <p>All task data is retrieved directly from the queue table. The PeopleSoft Application Layer for the particular process writes data into the queue tables. The data must be in the queue tables at the time of the request.</p> • <i>Application Class</i> <p>Task data is retrieved from the PeopleSoft Application Layer for the specific process. The process can retrieve its data from any available source within the PeopleSoft application. The data can be generated and retrieved at the time of the request.</p>
Package Name	<p>The name of the package that defines the PeopleSoft Application Layer for this process.</p> <p>This is unique for each process. The Application Class information and data here is where you point to the code that will be called for your specific PeopleSoft Application Layer functions. This is needed only if you are modifying or adding new integrations. Applications deliver these defined for their delivered integrations.</p> <p>The package name, path and class ID are specific to the registration. For delivered registrations, the fields are populated with application specific data.</p> <p>When creating new registrations, these classes are defined beforehand in PeopleSoft Application Designer. This applies to all registrations.</p>
Path	<p>The path to the PeopleSoft Application Layer code. Enter the path where samples can be found.</p>
Class ID	<p>The class ID for the PeopleSoft Application Layer code. Enter a unique ID for the class.</p>
<i>Dynamic Displays</i>	
ID	<p>Things that are supplied by default to the task. Select the ID of the display that you want as the default.</p>

Authorized Users

Source	The source of the authorized users. Select from the drop-down list box. Values are: <ul style="list-style-type: none"> • <i>User ID</i> • <i>Role Name</i> • <i>SQL User List</i>: An SQL user object that returns a list of operator IDs.
(the blank field to the right of the Source field)	Depending on the Source that you select in the Authorized User section (User ID, Role Name, SQL User List), a corresponding list of options becomes available for selection.

Assigned Users

User ID	This is generally assigned when the task is put into the queue. You can also assign by email selection. You do not need to create a user ID for each; you can simply use the email address. The user ID does not need to match the email or PeopleSoft user ID. You can also create generic user IDs. On the registration screens, these are the users that are assigned by default when something is added to the queue for this registration. For the actual processing, the assigned user on the actual queue item is used.
Email address	Alternatively, you can assign the Assigned User - User ID by email selection.

Setting Up the Task Queue

Access the Task Queue - Task page (Enterprise Components, Desktop Integration, Task Queue, Task).

Task Message
 Deleted?

Task Transaction ID: 1

*Task Process ID: REVIEW_PTO

Subject: Review PTO For March 2009

Start Date:

Due Date: 04/15/2009

*Task Status: Not Started

*Task Priority: Normal

Percent Complete: 0.00

Reminder: 04/19/09 8:00AM PDT

Total Work:

Actual Work:

Mileage:

Billing Info:

Company:

Updated: 05/29/2009 2:23:35PM Deleted On:

Package Name: EODI_EVENTS

Path: Samples

Class ID: TaskWorkListSample

Simulate Events

Update

Delete

Dynamic Displays

*ID	Description	
1	<input type="text"/>	+ -

Assigned Users

User ID	Description	Email ID	Last Accessed
1	HHDUSA_ADMIN	[PS] HRHD Administrator USA	<input type="text"/>

Task Queue - Task page

Use this page to monitor task integrations or manually add or update tasks for users.

Generally, you do nothing in the queue. The queue is essentially a view into the tables as data is moved back and forth. You can use the queue to manually add tasks to a user's Microsoft Outlook task list; however, that would normally be handled by an application-specific feature (through the PeopleSoft Application Layer for a process).

Task Transaction ID

The ID is generated and supplied beforehand from the System Setup page. This is a unique ID for everything that is put in the Task Queue. Enter the transaction ID for the transaction that you want.

To autonumber, leave the transaction ID as zero, and it will be updated when you save.

See [Chapter 10, "Using Desktop Integration," Setting Up the System, page 160.](#)

Deleted?

Select to flag for deletion.

Task Process ID

Displays the ID of the Task Process.

This is a prompt from the process ID for the registration. Select a Task Registration that you previously set up. The process ID is a 15-character, uppercase-only value. Enter the ID of the task process that you want.

Subject

Enter the task subject name.

All of the following fields correspond to the Microsoft Outlook fields that are displayed in a task. This is the information that is passed back and forth (updates in these fields are passed back and forth).

Start Date	Enter the date that you started the task or test.
Due Date	Enter the date that the task or test is due.
Task Status	<p>Select the status or state of the task. The status is updated only when you log back in to Microsoft Outlook again. Values are:</p> <ul style="list-style-type: none"> • <i>Completed</i> • <i>Deferred</i> • <i>In Progress</i> • <i>Not started</i> <p style="padding-left: 40px;">This is the default value.</p> <ul style="list-style-type: none"> • <i>Waiting on someone else.</i>
Task Priority	<p>Select the priority that is defined for the task. Values are:</p> <ul style="list-style-type: none"> • <i>High</i> • <i>Low</i> • <i>Normal</i> <p style="padding-left: 40px;">This is the default value.</p>
Percent Complete	Enter the percentage of the task that has been completed.
Reminder	<p>Enter any information or specifics that you want to recall, for example, the date and time to remind the user about this task.</p> <p>This is the reminder that you can set within Microsoft Outlook.</p> <p>For example, it might be an appointment reminder that pops up and sends you an email when a meeting is about to begin.</p>
Total Work	<p>Outlook task field.</p> <p>This is a free form field that is available in Microsoft Outlook Task.</p>
Actual Work	<p>Outlook task field.</p> <p>This is a free form field that is available in Microsoft Outlook Task.</p>
Mileage	<p>Outlook task field.</p> <p>This is a free form field that is available in Microsoft Outlook Task.</p>
Billing Info	<p>Outlook task field.</p> <p>This is a free form field that is available in Microsoft Outlook Task.</p>

Company	Outlook task field. This is a free form field that is available in Microsoft Outlook Task.
Updated	The date that this task information was last updated.
Deleted On	The date that this task was flagged for deletion. This field remains blank until or unless the task is flagged for deletion.

Dynamic Displays


ID	Select the ID of the dynamic display. Select any number of Dynamic Display IDs for the displays that you want to automatically show alongside a user's tasks.
Description	Displays the description of the dynamic display ID, which is automatically supplied with the ID selection.

Simulate Events

Update	You can use the Simulate Events section to trigger PeopleCode without using Microsoft Outlook. Click the Update button to update and test your process, or select Delete? to flag this process for deletion. This feature enables development to test code without Microsoft Outlook. The PeopleSoft Application Layer application classes are called for the particular process.
---------------	---

Composing Task Contents

Access the Task Queue - Message page (Enterprise Components, Desktop Integration, Task Queue, Message).



Task Queue - Message page

Use this page to further define the body of the message. This is the message body of the task that is created in Microsoft Outlook and contains any changes that are made in Microsoft Outlook.

Registering Address Books

This section provides an overview of address book registration and discusses how to register your address book.

Understanding Address Book Registration

Address books enable you to leverage PeopleSoft data to update Outlook users' local address lists or to control the email addresses that are available within the PeopleSoft Outlook Meeting Scheduler.

Several types of address books are available that you can define. The main difference between them is where the information originates. The type of address book determines which options are available in the registration page.

- *Internal address books*—These are derived from the Internal Address book page as defined within Desktop Integration.

The address can be entered manually through the Internal Address Book page, or the underlying record can be updated by some other process.

- *Record/View address books*—These pull all of their information for a record or view as defined in PeopleTools and must conform to a specific structure.

The record or view must contain the EODI_CON_SBR subrecord.

- *Application Class address books*—These pull all of their information from application classes and allow dynamic address books to be generated in PeopleCode.

Page Used to Register Your Address Book

Page Name	Definition Name	Navigation	Usage
Address Book Registration	EODI_CON_REG	Enterprise Components, Desktop Integration, Address Book Registration	Register your address book.

Registering Your Address Book

Access the Address Book Registration page (Enterprise Components, Desktop Integration, Address Book Registration).

The screenshot displays the 'Address Book Registration' page. At the top, it shows 'Process ID: SYSTEM ADMIN' and a 'Deleted?' checkbox. The 'Updated' timestamp is '05/29/2009 2:38:52PM'. The main form includes several sections:

- Description:** Text field containing 'System Administrators'.
- Object Owner ID:** Dropdown menu set to 'Enterprise Components Demo'.
- *Use:** Dropdown menu set to 'Personal Address Book'.
- *Source:** Dropdown menu set to 'RecordView'.
- Record:** Text field with 'EODI_DYN_CONTE' and a search icon.
- Join EMAILID:** Checked checkbox.
- Join OPRID:** Checked checkbox.
- Application Class:** A sub-section with:
 - *Package Name:** Text field with 'EODI_EVENTS' and a search icon.
 - *Path:** Text field with 'Samples' and a search icon.
 - *Class ID:** Text field with 'AddressBookSample' and a search icon.
- Authorized Users:** A section with a search bar and a dropdown menu set to 'Role Name', with 'Employee' entered in the adjacent text field.

 Navigation controls at the bottom right include 'Find', 'First', '1 of 1', and 'Last'.

Address Book Registration page

Use this page to register and define your available address book options.

Process ID	This ID is defined for delivered integrations.
Deleted?	Select to flag this address for deletion.
Updated	This is automatically populated with the latest update saved to this address book.

Description	Description of the address book. Enter a unique description.
Object Owner ID	<p>The application class that owns the object (for example, Enterprise Components).</p> <p>Select a value from the drop-down list box that contains all of the available applications.</p> <p>This is not a required field.</p>
Use	<p>Specifies where the address book is used:</p> <ul style="list-style-type: none"> • <i>Personal Address Book</i>: Replicated to the users' Outlook Address Book list. • <i>Meeting Invitees</i>: Only available if added to a meeting in the queue. <p>The Meeting Invitees option enables two additional fields: Join EMAILID (join email identification) and Join OPRID (join operator identification).</p>
Source	<p>The source of the address book or contact.</p> <p>Values are:</p> <ul style="list-style-type: none"> • <i>Application Class</i> • <i>Record/View</i> • <i>Internal</i> <p>See and Chapter 10, "Using Desktop Integration," Understanding Address Book Registration, page 168.</p>
Record	Enter the source record. This field appears if the selected source is <i>Record/View</i> .
Join EMAILID	<p>Select for Desktop Integration to automatically join the EMAILID field to the current users email address. This field appears if the selected source is <i>Record/View</i>.</p> <p>The EMAILID field must be present on the record selected.</p>
Join OPRID	<p>Select for Desktop Integration to automatically join the OPRID field to the current users operator ID. This field appears if the selected source is <i>Record/View</i>.</p> <p>The OPRID field must be present on the record selected.</p>

Application Class

Package Name

The name of the package that defines the PeopleSoft Application Layer for this process.

This is unique for each process. The Application Class information and data here is where you point to the code that will be called for your specific PeopleSoft Application Layer functions. This is needed only if you are modifying or adding new integrations. PeopleSoft Applications deliver these defined for their delivered integrations.

The package name, path and class ID are specific to the registration. For delivered registrations, the fields are populated with application specific data.

When creating new registrations, these classes are defined beforehand in PeopleSoft Application Designer. This applies to all registrations.

Path

(Samples) Select the path where Samples can be found.

Class ID

Select a unique ID for the Class.

Authorized Users

Source

The source of the authorized user. Select from the drop-down list box.

Values are:

- *User ID*
- *Role Name*
- *SQL User List*

You do not need to create a user ID for each; you can simply use the email address. The user ID does not need to match the email or PeopleSoft user ID. You can also create generic user IDs.

The field to the right is automatically supplied based on the source that you specify.

(the field to the right of the Source field)

Depending on the Source that you select in the Authorized User section (User ID, Role Name, SQL User List), a corresponding list of options becomes available for selection.

Registering Internal Address Books

This section discusses how to register and define your internal address book.

Registering an Internal Address Book

Access the Internal Address Book page (Enterprise Components, Desktop Integration, Internal Address Book).

Use the Internal Address Book (EODI_CON) page to register and define your available internal address book options.

Internal address books are derived from the Internal Address book page as defined within Desktop Integration. The address can be entered manually through the Internal Address Book page, or the underlying record can be updated by some other process.

Address Book Process ID	The ID is supplied as defined on the Address Book Registration page. Internal address books are derived from the Internal Address book page as defined within Desktop Integration. The address can be entered manually through the Internal Address Book page, or the underlying record can be updated by some other process.
Email Address	The email address of the contact.
Deleted?	Select to flag this email address or contact information for deletion.
Full Name	The full name of the person or contact.
Title	The title of the person or contact.
First Name	The first name of the person or contact.
Middle Name	The middle name of the person or contact.
Last Name	The family or sir name of the person or contact.
Suffix	The suffix for this person or contact.
Alt. Email (alternate email)	An alternate email address to the primary listed email address.
Alt. Email (alternate email)	An alternate email address to the secondary listed email address.
Company	The company where this person or contact works.
Job Title	The title of the position that this person or contact holds at the company.
Work Phone	The work phone number of this person or contact.
Home Phone	The home phone number of this person or contact.
Mobile Phone	The mobile or cell phone number of this person or contact.

Updated

This date is automatically updated with each saved revision to this address in the address book. This same date appears at the top of the page as well.

Setting Up Appointments

This section discusses how to:

- Set up appointment registration.
- Review the appointment queue.
- Set up meeting scheduling criteria.
- Set up meeting criteria.

Pages Used to Set Up Appointments

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Appointment Registration	EODI_APT_REG	Enterprise Components, Desktop Integration, Appointment Registration	Set up appointment registration and to define he defaults for the user's appointments, invitations, and calendar.
Appointment/Meeting Group	EODI_APT_QUEUE	Enterprise Components, Desktop Integration, Appointment Queue, Appointment/Meeting Group	Review the appointment queue, monitor integration transactions, or manually add or update meetings and appointments.
Availability	EODI_APT_TIMES	Enterprise Components, Desktop Integration, Appointment Queue, Availability	Specify the system parameters for scheduling meetings.
Meeting	EODI_APT_MEETINGS	Enterprise Components, Desktop Integration, Appointment Queue, Meeting	Specify criteria for your meeting invitations and attendees.

Setting Up Appointment Registration

Access the Appointment Registration page (Enterprise Components, Desktop Integration, Appointment Registration).

Appointment Registration page

This information is supplied by the applications for delivered integrations. You define the Authorized Users section here. As with tasks, if creating custom integrations, you create data here.

Process ID	The ID is supplied beforehand for delivered integrations.
Description	Description of the process. Enter a unique description.
Appointment Type	Type of appointment. Appointments are anything on a calendar. Values are: <ul style="list-style-type: none"> • <i>Appointment</i>: No invites, just an item on a calendar. • <i>Meeting</i>: Single, simple. • <i>Meeting Group</i>: Schedule multiple simultaneously. <p>For example, when scheduling an interview candidate, you have visibility to the entire series of interviews.</p>
Object Owner ID	The application class that owns the object (for example, Enterprise Components). Select a value from the drop-down list box that contains all of the available applications.
Address Book	Optionally, select a Desktop Integration address book to be available in the Outlook PeopleSoft Scheduler.
Restrict To Address Book	Select to restrict the available email address options to the address Book entered.

Package Name The name of the package that defines the PeopleSoft Application Layer for this process. This is unique for each process.

The Application Class information and data here is where you point to the code that will be called for your specific PeopleSoft Application Layer functions. This is needed only if you are modifying or adding new integrations. PeopleSoft Applications deliver these defined for their delivered integrations.

The package name, path and class ID are specific to the registration. For delivered registrations, the fields are populated with application specific data.

When creating new registrations, these classes are defined beforehand in PeopleSoft Application Designer. This applies to all registrations.

Path (Samples) Enter the path where Samples can be found.

Class ID (Address Samples) Enter a unique ID for the class.

Dynamic Displays

ID Things that are supplied by default to the appointment. Select the ID of the display that you want as the default.

Authorized Users

Source The source of the authorized user. Select from the drop-down list box. Values are:

- *User ID*
- *Role Name*
- *SQL User List*

Query from a list to obtain email addresses.

You do not need to create a user ID for each; you can simply use the email address. The user ID does not need to match the email or PeopleSoft user ID. You can also create generic user IDs.

(the blank field to the right of the Source field) Depending on the Source that you select in the Authorized User section (User ID, Role Name, SQL User List), a corresponding list of options becomes available for selection.

Assigned Users

User ID Generally assigned when the task is put into the queue. You can also assign by email selection.

Email Address

Alternatively, you can assign this field by email selection.

Reviewing the Appointment Queue

Access the Appointment Queue - Appointment/Meeting Group page (Enterprise Components, Desktop Integration, Appointment Queue).

Appointment/Meeting Group
Availability Meeting

Appt. Transaction ID: 1 Deleted? [Launch Scheduler](#)

*Appointment Process ID:

Subject:

*Appointment Type:

*Show Time As: Time Zone:

Package Name: HRS_EODI
 Path: ApplicantInterview
 Class ID: SchedulingHandler

Address Book: Restrict To Address Book

Updated: 05/29/2009 6:07:27PM EDT Deleted:

Message:

Please review the appointment details contained in this meeting request and respond in accordance with the options available to you.

The location for this interview is Building E in Pleasanton - First Floor.

If you are not sure of the address or exact location, please contact the person who scheduled the interview with you.

Dynamic Displays [Customize](#) | [Find](#) | | 1 of 1

*Dynamic Display ID	Description		
1	<input type="text"/>	<input type="button" value="Search"/>	<input type="button" value="+"/> <input type="button" value="-"/>

Assigned Users [Customize](#) | [Find](#) | | 1 of 1

User ID	Description	Email Address	Last Accessed	
1	PS	[PS] Peoplesoft Superuser	HCMGENUser1@ap6023fems.us.oracle.com	<input type="button" value="+"/> <input type="button" value="-"/>

Appointment/Meeting Group | [Availability](#) | [Meeting](#)

Appointment Queue - Appointment/Meeting Group page

Appointment Process ID The appointment process associated with this appointment or meeting.

Subject

- *Appointment*: The subject for the appointment in Outlook.
- *Meeting*: The description displayed in the Meeting Queue in the PeopleSoft Meeting Scheduler.

Appointment Type

- *Appointment*: Standard appointment.
- *Meeting*: Single meeting.
- *Meeting Group*: Multiple meetings to be scheduled on a single screen.

Show Time As	Status for the appointment. Values are: <ul style="list-style-type: none"> • <i>Busy</i> <p>This is the default value.</p> <ul style="list-style-type: none"> • <i>Free</i> • <i>Out Of Office</i> • <i>Tentative</i>
Start Date/Time	Start date and time for the appointment. This is not visible for meetings.
End Date/Time	End date and time for the appointment. This is not visible for meetings.
Address Book	The address book for the default on new meetings. This is not available for appointments.
Restrict To Address Book	Option supplied by default onto new meetings.
Message	<ul style="list-style-type: none"> • <i>Appointments</i>: Body of appointment. • <i>Meetings</i>: Master meeting body.
<i>Dynamic Displays</i>	
Dynamic Displays ID	The ID of the dynamic display. Select the ID of the display that you want as the default in the user's tasks.
Description	The description of the dynamic display that the ID identifies.
<i>Assigned Users</i>	
User ID	This is generally assigned when the task is put into the queue. You can also assign by email selection.

Setting Up Meeting Scheduling Criteria

Access the Appointment Queue - Availability page (Enterprise Components, Desktop Integration, Appointment Queue, Availability).

Appointment Queue - Availability page

Use this page to specify the system parameters that guide or restrict when you can schedule a meeting. This page is enabled for meetings only. The system considers meetings as a special type of appointment.

- Restrict Meeting Times** When this option is enabled, meetings can be scheduled only within the meeting windows that you define.
- Restrict to Single Day** When this option is enabled, all meetings in a meeting group must occur on the same day.
- Meeting Windows** The start date and time, end date and time, and time zone.

Setting Up Meeting Criteria

Access the Appointment Queue - Meeting page (Enterprise Components, Desktop Integration, Appointment Queue, Meeting).

Appointment/Meeting Group Availability Meeting

Appt. Transaction ID: 1 Interview Request - Nuclear Engineer - 290146

Appointment Process ID: HRS_INTERVIEW Recruitment Interview Tracking

Meetings Groups Find | View All First 1 of 1 Last

*Group: 1 Deleted?

*Status: Queued For Scheduling

Description: Interview Request - Nuclear Engineer - 29

Start Date/Time: 04/17/2009 12:30PM EDT Time Zone: EST

End Date/Time: 04/17/2009 1:30PM EDT Duration (Minutes):

Address Book:

Subject: Interview Request - Nuclear Engineer - 290146

Message:

Please review the appointment details contained in this meeting request and respond in accordance with the options available to you in Outlook.
 The location for this interview is Building E in Pleasanton - First Floor.
 If you are not sure of the address or exact location, please contact the person who scheduled the meeting with you.

Updated: 05/29/2009 3:28:09PM

Participants Find | View All First 1 of 1 Last

Email Address: john.smith@oracle.com *Response: No Response

Email Name: Faith Doe *Type: Required

Updated: 05/29/2009 3:28:09PM

Last Accessed:

Simulate Events Update

Simulate Events Delete

Simulate Events Response

Appointment Queue - Meeting page

This page is enabled for meetings only.

Update

In the Simulated Events section, click the Update button to test your integration process without using Microsoft Outlook.

This process updates all meeting groups.

Delete

In the Simulated Events section, click the Delete button to test your integration process without using Microsoft Outlook.

This process deletes the current meeting.

Status	<p>Select a value from the drop-down list box. Values are:</p> <ul style="list-style-type: none">• Awaiting Responses.• Canceled.• Initial - Not Visible. This is the default value.• On Hold - Do Not Schedule.• Queued for Canceling.• Queued for Scheduling.• Scheduled. <p>When you install the Microsoft Outlook Add-In program, the Status field is visible in your PeopleSoft application.</p>
Start Date/Time	<p>Enter the first date that you want to consider within a particular time frame or known availability.</p> <p>From the drop-down list box, select the time that you want the meeting to begin.</p>
Time Zone	<p>The attendee's time zone.</p> <p>When you select a time zone from the drop-down list box, you are ensuring that the time you enter on your calendar appears correctly on the attendee's invitation and calendar for his or her time zone.</p>
End Date/Time	<p>Enter the last date that you want to consider within a particular time frame or known availability.</p> <p>From the drop-down list box, select the time that you want the meeting to end. This field is automatically populated when you specify a value in the Duration field.</p>
Duration (Minutes)	<p>Duration of the meeting time in minutes. This field is automatically populated when you select the beginning and ending time.</p>
Address Book	<p>Select from your available Desktop Integration address books.</p> <p>Selecting a Desktop Integration address book enables you to make available an email address book that is sourced from the PeopleSoft application.</p>
Restrict To Address Book	<p>When you select this option, you can choose addresses only from the selected address book.</p>
Subject	<p>Enter a subject line. This can be the topic of the meeting, the call-in number, or whatever information you want.</p>

Require Unique Invitation	<p>Select to require a unique or custom invitation to a particular invitee or group.</p> <p>This option prevents the user from sending the Master Meeting invite information in the Outlook Scheduler.</p> <hr/> <p>Note. Within the PeopleSoft Outlook Meeting Scheduler, the user can define a single meeting invite message for multiple meetings, individual meeting invite messages, or a combination of the two. The Master Meeting is a shared meeting invite that can be used and its body is supplied by default from the Message as defined on the Appointment/Meeting Group page. Each individual meeting can also have a message body that is defined on the Meeting page. This text is used if the user chooses not to use the Master Meeting invite, or if its use is restricted.</p> <hr/>
Use Master Meeting	Select to use the content or text specified in the Master Meeting for everyone to whom you are sending an invitation.
Send as iCal Appointment (iCalendar appointment)	Select to send to an external invitee who is using another calendaring system or application.
Deleted?	Select to flag this meeting for deletion.
Message	<p>Enter the body of the invitation content or text into this pane for global visibility, unless otherwise specified.</p> <p>The system uses this message if the meeting is not using the Master Meeting (if you did not select the Master Meeting check box).</p>
Updated	This field is automatically populated with the date of the latest update.
Email Address	In the Participants section, enter the email address or D-list of the people you want to invite.
Email Name	<p>Alternatively, you can enter the invitee name or group name.</p> <p>Select from the list of available types and participant types:</p> <ul style="list-style-type: none"> • <i>Required:</i> User must be present at meeting. • <i>Optional:</i> User can optionally attend the meeting. • <i>Resource:</i> Used for room scheduling and resources.

Response

This is the current response received from the user. Values are:

- *Accepted*
- *Declined*
- *Deleted*
- *No Response*

The invitation has been sent but no reply has been received.

- *Not Sent*
- *Proposed New Time*
- *Tentative*

Simulate Events**Response**

In the Simulate Events section, click the Response button to simulate the event and test your process without using Microsoft Outlook.

Setting Up File Transfers

This section discusses how to:

- Set up file transfer registration.
- Review the file transfer queue.

Pages Used to Set Up File Transfers

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
File Transfer Registration	EODI_XFR_REG	Enterprise Components, Desktop Integration, File Transfer	Set up file transfer registration.
File Transfer Queue	EODI_XFR	Enterprise Components, Desktop Integration, File Transfer Queue	Review what you previously defined as defaults in your file transfers.

Setting Up File Transfer Registration

Access the File Transfer Registration page (Enterprise Components, Desktop Integration, File Transfer).

The screenshot shows a web form titled "File Transfer Registration". At the top, it displays "File Transfer Process ID: CONTRACT". Below this, there are several input fields:

- *Description: Supplier Contract
- Object Owner ID: Enterprise Components (dropdown menu)
- *Package Name: EODI_EVENTS
- *Path: Samples
- *Class ID: FileTransferSample

 At the bottom of the form, there is an "Authorized Users" section with a search bar containing "PeopleSoft User" and a dropdown menu for "Role".

File Transfer Registration page


- File Transfer Process ID** The ID is supplied beforehand.
- Description** Description of the File Process. Enter a unique description.
- Object Owner ID** The application class that owns the object (for example, Enterprise Components).
Select a value from the drop-down list box that contains all of the available applications.
- Package Name** The name of the package that defines the PeopleSoft Application Layer for this process. This is unique for each process.
The Application Class information and data here is where you point to the code that will be called for your specific PeopleSoft Application Layer functions. This is needed only if you are modifying or adding new integrations. PeopleSoft Applications deliver these defined for their delivered integrations.
The package name, path and class ID are specific to the registration. For delivered registrations, the fields are populated with application specific data.
When creating new registrations, these classes are defined beforehand in PeopleSoft Application Designer. This applies to all registrations.
- Path** (Samples) Enter the path where Samples can be found.
- Class ID** (Task Samples) Enter a unique ID for the class.

Authorized Users

Source	<p>The source of the authorized user. Select from the drop-down list box. Values are:</p> <ul style="list-style-type: none"> • <i>User ID</i> • <i>Role Name</i> • <i>SQL User List</i> <p>You do not need to create a user ID for each; you can simply use the email address. The user ID does not need to match the email or PeopleSoft user ID. You can also create generic user IDs.</p> <p>The field to the right is automatically populated based on the source that you specify.</p>
(the blank field to the right of the Source field)	<p>Depending on the Source that you select in the Authorized User section (User ID, Role Name, SQL User List), a corresponding list of options becomes available for selection.</p>

Reviewing the File Transfer Queue

Access the File Transfer Queue page (Enterprise Components, Desktop Integration, File Transfer Queue).



File Transfer Queue page

File Transfer Transaction ID	The numeric transaction ID that the PeopleSoft system assigns when you create the file transfer.
Unique System Filename	Upon processing of the file transfer, this field updates with the unique system file name assigned by the PeopleSoft system.

File Status	Displays the current status of this file transfer. Values are: <ul style="list-style-type: none"> • Receiving File • Assembling File • Processing Application Logic • Processing Complete
Updated	The date that this file transfer is updated with new or edited information.
Delete Attachment	Click to delete the attached file.
View Attachment	Click to view the attached file.
Detach Attachment	Click to detach the attached file.

Defining Dynamic Displays

This section provides an overview of dynamic displays and discusses how to:

- Define general dynamic display options.
- Define field and layout options for dynamic displays.

Understanding Dynamic Displays

Dynamic Displays allow the display of information from your PeopleSoft system alongside items in Microsoft Office. You can use Dynamic Displays to show any information contained within the PeopleSoft system and those displays can optionally be shown automatically alongside the Microsoft Office items. The information contained within a Dynamic Display can also be driven contextually by the current item. For example, customer information from the PeopleSoft system can be displayed alongside an inbound customer email, or contact in an address book.

Pages Used to Define Dynamic Displays

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Display Definition	EODI_DYN	Enterprise Components, Desktop Integration, Dynamic Display Definition, Display Definition	Define general dynamic display options.

Page Name	Definition Name	Navigation	Usage
Fields and Layout	EODI_DYN_FIELDS	Enterprise Components, Desktop Integration, Dynamic Display Definition, Fields and Layout	Define field and layout options for dynamic displays.

Defining General Dynamic Display Options

Access the Display Definition page (Enterprise Components, Desktop Integration, Dynamic Display Definition).

Display Definition
Fields and Layout

Dynamic Display ID: 123 Active

***Description:**

Object Owner ID:

***Display Action:**

***Display Position:** ***Display Restriction:**

Display In

Microsoft Outlook Main Page
 Microsoft Outlook Appointment
 Microsoft Outlook Email
 Microsoft Outlook Contact
 Microsoft Word
 Microsoft Outlook Task
 Scheduling Assistant

Display Layout

***Layout Type:**
Columns:
Column Width:
Display Width:
Rows:
Row Height:
Display Height:
Label Width:

Display Definition page (1 of 2)

*Package Name:

*Path:

*Class ID:

Control Record Name:

Authorized Users Find First 1 of 1 Last

*Source: User ID

Display Definition page (2 of 2)

Dynamic Displays dynamically set up the form and format with the required action fields, and then pass the information back to the form.

Dynamic Display ID The ID of the dynamic display is supplied as defined earlier. This must be a unique ID across your organization.

Description The name of the dynamic display. Enter a unique name for this display.

Display Action Select the display action. Values are:

- *Automatic*: The display is automatically shown if the transaction requests.
- *On Request*: The user must use the Display ribbon action item to display.

You must use the Display ribbon action or menu item to display.

Display Position Select the initial position of the Dynamic Display. Values are:

- *Right*
- *Left*
- *Top*
- *Bottom*
- *Floating*

Display Restriction Used to restrict the position change of the Dynamic Display. This is useful if the display layout does not function well in a particular mode.

- *None*
- *No Horizontal*: Display restricted to Right, Left or Floating.
- *No Vertical*: Display restricted to Top, Bottom or Floating.
- *Frozen*: Display cannot be moved.

Display In

Select the Microsoft Office application areas where the Dynamic Display is available. Values are:

- Microsoft Outlook Main Page: The main frame of Microsoft Outlook; not tied to any single Microsoft Outlook item.
- Microsoft Outlook Contact
- Microsoft Outlook Task
- Microsoft Outlook Appointment: Includes any appointment, including meetings.
- Microsoft Word
- Scheduling Assistant: The PeopleSoft Scheduling Assistant, used for PeopleSoft meetings.
- Microsoft Outlook Email

When you select Microsoft Outlook Email, *Email Mode* becomes available for optional selection.

- *Email Mode*: Controls which email modes the Dynamic Display is available in.

Values are:

- *Read and Compose*
- *Read*
- *Compose*

Layout Type

Controls the layout method for the Dynamic Display. Values are:

- *Automatic*: Display layout is computed automatically based on the Row and Column assigned to individual controls (recommended).
- *Custom*: Display layout is precisely controlled by the X and Y layout positions.

Display Width

Width of the Dynamic Display. This will be ignored for Top or Bottom Display Positions.

If a display is a LEFT or RIGHT display position, then it will *always* go from top to bottom of the current page (but you can control the width).

Display Height

Height of the Dynamic Display. This will be ignored for Top or Bottom Display Positions.

If a display is a TOP or BOTTOM display position, it will always go the entire width of the current page (but you can control the height).

Columns

Number of columns for the display layout.

Column Width	Width of columns for the display layout.
Rows	Number of rows for the display layout.
Row Height	Height of rows for the display layout.
Package Name	<p>The name of the package that defines the PeopleSoft Application Layer for this process. This is unique for each process.</p> <p>The Application Class information and data here is where you point to the code that will be called for your specific PeopleSoft Application Layer functions. This is needed only if you are modifying or adding new integrations. PeopleSoft Applications deliver these defined for their delivered integrations.</p> <p>The package name, path and class ID are specific to the registration. For delivered registrations, the fields are populated with application specific data.</p> <p>When creating new registrations, these classes are defined beforehand in PeopleSoft Application Designer. This applies to all registrations.</p>
Path	The path of the dynamic display sample. Select the path where the dynamic display samples can be found.
Class ID	Select a unique ID for the class.
Control Record Name	<p>Optional record name. Fields from this record name can be defined as defaults in the Fields and Layout information to quickly build a Dynamic Display.</p> <p>The properties of the record fields are also used.</p>
Authorized Users	
Source	<p>The source of the authorized user. Select from the drop-down list box. Values are:</p> <ul style="list-style-type: none"> • <i>User ID</i> • <i>Role Name</i> • <i>SQL User List</i> <p>You do not need to create a user ID for each; you can simply use the email address. The user ID does not need to match the email or PeopleSoft user ID. You can also create generic user IDs.</p> <p>The field to the right is automatically populated based on the source that you specify.</p>
(the blank field to the right of the Source field)	Depending on the Source that you select in the Authorized User section (User ID, Role Name, SQL User List), a corresponding list of options becomes available for selection.

Defining Field and Layout Options for Dynamic Displays

Access the Fields and Layout page (Enterprise Components, Desktop Integration, Dynamic Display Definition).

The screenshot displays the 'Fields and Layout' configuration page for a dynamic display. At the top, it shows 'Dynamic Display ID: 123' and three buttons: 'Default Positions', 'Sort Fields', and 'Refresh Fields'. Below this is a 'Fields' section with a search bar and a list of fields. The first field is selected, showing its configuration: *Field Name (empty), *Field Type (Text), Length (0), Prompt Table (empty), and checkboxes for Visible (checked), Display Only (unchecked), and Trigger Event On Field Change (unchecked). Below the Fields section is a 'Layout' section with dropdowns for Row Number (1) and Column Number (1), and input fields for Height (0), Width (0), Y Position (0), and X Position (0). To the right of the Layout section is a 'Label Type' section with radio buttons for None, Text, RFT Short, and RFT Long (selected), along with input fields for Field Label ID and Label Width (0), and a Text field.

Dynamic Displays - Fields and Layout page

Default Position

Click this button to set the default positions for the Row and Column numbers of all fields on the page. The system uses the row height and column width from the main page to calculate the X and Y position of the fields. This button is only visible when you select the *Custom* layout type on the Display Definition page.

See [Chapter 10, "Using Desktop Integration," Defining General Dynamic Display Options, page 187.](#)

Sort Fields

Click to sort the fields within the scroll by Row and Column number.

Refresh Fields

Click to refresh all fields within the scroll with the fields from the Control record defined on the Display Definition page.

Field Name

Enter or select a unique name (must be unique within this display). All code references to the field will use this name.

Field Type	Select a value from the drop-down list box: Values are: <ul style="list-style-type: none">• Button• Chart• Date• Drop-down List Box• Grid• Hyperlink• Number• Text• Tree
Length	Enter the length of the input data. This field is valid for <i>Text</i> and <i>Number</i> field types only.
Prompt Table	Select a prompt table record name for the text field. Only valid for <i>Text</i> field types. When you select a Prompt Table record name for Text field types, a Prompt Table edit check box becomes available. This option asks <i>Should Prompt Table be used as an edit table?</i> This is only valid for <i>Text</i> field types where a <i>Prompt Table</i> has been defined.
Visible	Select to define the control as visible.
Display Only	Select to define the control as visible in the display only.
Trigger Event On Field Change	Select to trigger a field change event on the server if the current field is changed.
Decimal Positions	Enter the number of decimal positions in the number. This field is valid and enabled for <i>Number</i> field types only.

Button Action

Select the action to be performed when the button is clicked. This field is valid and enabled for *Button* field types only.

Values are:

- Capture Document Contents
- Capture Document Selection
- File/Document Download
- File/Document Upload
- Insert Into Current Document
- None

Layout**Row Number**

Enter the number of rows for automatic layout.

Instead, you can click the Default Positions button to set the default positions for the Row and Column numbers of all fields on the page. The system uses the row height and column width from the main page to calculate the X and Y position of the fields. This button is only visible when you select the *Custom* layout type on the Display Definition page.

Column Number

Enter the number of columns for automatic layout.

Instead, you can click the Default Positions button to set the default positions for the Row and Column numbers of all fields on the page. The system uses the row height and column width from the main page to calculate the X and Y position of the fields. This button is only visible when you select the *Custom* layout type on the Display Definition page.

Height

Enter the height of the control. If you leave this value as 0, the system uses the current row height as the default.

Width

Enter the height of the control.

If this is a *Display Only* field and you leave the value as 0, the system will display the entire item.

If this is an *Input* field, you must specify the display *Width* of the input field.

X Position

Specify the absolute position for this control. This field is only visible when you select the *Custom* layout type on the Display Definition page.

Y Position

Specify the absolute position for this control. This field is only visible when you select the *Custom* layout type on the Display Definition page.

Label Type**None, Text, RTF Short or RTF Long**

Select one of these radio buttons as the label type:

- None
- Text: Uses the hardcoded text that is supplied.
- RTF Short: Looks up the internal short text for the field, based on the supplied Field Label.
- RTF Long: Looks up the internal long text for the field, based on the supplied Field Label.

RTF Long and RTF Short are only valid options if the field name provided exists as a valid field without PeopleSoft Application Designer.

Field Label ID

When you select either *RTF Short* or *RTF Long* for the label type, specify the Field Label ID.

Field Label ID is only a valid option if the field name provided exists as a valid field without PeopleSoft Application Designer.

Label Width

Specify the width reserved for the label for this item. To line up all items on a single Dynamic Display, keep this number consistent across all fields.

Text

When you select Text for the Label Type, specify the label text.

Using the Display Log

This section discusses how to use the display log.

Page Used to View the Display Log

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Desktop Integration Log	EODI_LOG	Enterprise Components, Desktop Integration, Display Log	View dynamic display log messages.

Viewing the Display Log

Access the Desktop Integration Log page (Enterprise Components, Desktop Integration, Display Log).

Desktop Integration Log

Date: Process ID: Transaction ID:

Find | View All | First | 1 of 1 | Last

Date/Time:	System:	Process ID:	Transaction ID:	Message:	Explanation:
				<input type="text"/>	<input type="text"/>

Desktop Integration Log page

The Desktop Integration Log helps you understand and troubleshoot the Desktop Integration processes. The amount of detail shown in the log is determined by the log level set in the System Setup. As Desktop Integration processes run, information is written to the log at each step.

The Desktop Integration Log enables you to select what you want to view, and then displays the details of that selection for the messages that are passed. All specified information is optional and only filters the log that is retrieved when you click the Refresh button.

Date	Select the date for which you want to view the log entries and events.
Process ID	Select the ID of the process for which you want to view the log entries and events.
Transaction ID	Enter the ID of the transaction for which you want to view the log entries and events.
Refresh	Click to refresh the log entries and events that appear.
Clear Log	Click to clear the log entries and events that appear.

Log

Date/Time	The date and time of the log entry and event.
System	The system for which the log entry and event are associated.
Process ID	The unique ID of the process.
Transaction ID	The ID of the transaction of the log entry and event.
Message	The message in the log entry and event.
Explanation	The explanation of the log entry and event.

Using the PeopleSoft Outlook Menu

This section provides an overview of the PeopleSoft and Outlook integration, and discusses how to:

- Define settings and options.
- Use the PeopleSoft Scheduler and Scheduling Assistant.
- Replicate appointments, meetings, tasks, and address books.

Understanding the PeopleSoft and Outlook Integration

Within Microsoft Outlook, the following two components are installed that enable all of the communication and interaction between Microsoft Outlook and the PeopleSoft system:

- The Microsoft Add-In—this is represented in the PeopleSoft Outlook menu and handles all of the communication and information within Microsoft Outlook.
- The PeopleSoft Outlook URL Handler—this is an external Windows application that allows you to drill into Microsoft Outlook directly from the PeopleSoft system.

Defining Settings and Options

When you select Settings & Options from the PeopleSoft menu in Microsoft Outlook, the following pages are available:

- Servers page—shows the server detail (such as the server URL, connectivity, and the server functions that you selected).
- Options page—shows the display options and frequency of updates.
- Status Log page—shows the send and receive data and errors in the log.

Note. After the Microsoft Outlook Add-In installation completes, you must go to the Settings and Options - Servers page (PeopleSoft Outlook menu, Settings & Options, Servers) and define the server URL and functions.

The server must show the Enable check box selected to attempt connectivity. If the server was determined to be online during the last connection attempt, the Online check box is selected.

Defining the Servers Page

Access the PeopleSoft Settings and Options - Servers page (PeopleSoft Outlook menu, Settings & Options, click the Servers page).

Use the PeopleSoft Settings and Options - Servers page to define the server URL that you want to connect to and the functions that you want to assign to the server.

PeopleSoft Settings & Options

Servers Options Status Log

Development Demo Database Enable Online 1 of 1

Server URL

User ID Save User ID

Password Save Password

Account

Features

<input checked="" type="checkbox"/> Scheduling	
<input checked="" type="checkbox"/> Dynamic Displays	
<input checked="" type="checkbox"/> Tasks	Last Replication
<input checked="" type="checkbox"/> Address Books	7/23/2009 9:17:47 AM
<input checked="" type="checkbox"/> Appointments	7/23/2009 9:20:31 AM
	7/23/2009 9:14:05 AM

Server Version: 1.0

Add Delete Previous Next

PeopleSoft Outlook Add-In Version: 1.0.0.0 OK Cancel

PeopleSoft Settings & Options - Servers page


Define the URL and functions to assign to the server:

Enable	The server must show this check box selected to attempt connectivity. If the server was determined to be online during the last connection attempt, the Online check box is selected.
Server URL	Enter the URL of the server that you want to connect to. This is your Integration Broker URL.
User ID	Enter your User ID.
Save User ID	Select to save your User ID in the system and avoid the need for future entry.
Password	Enter your password.
Save Password	Select to save your password in the system and avoid the need for future entry.
Account	Select an account in the form of the email address of the user. You can select from a list of multiple accounts. The selected account drives the information from the parameters that you defined in the Outlook setup.
Features	Select the features that you want to use. Values are: <ul style="list-style-type: none"> • Scheduling • Dynamic Displays • Tasks • Address Books • Appointments
Add	Click to add a new server option. <hr/> Note. This section of the PeopleSoft Settings & Options - Servers page shows the current version of the PeopleSoft Outlook Add-In and the server that you are using. <hr/>
Delete	Click to delete an existing server option. Alternatively, you can disable a server by clearing the Enable check box.

Defining the Options Page

Access the PeopleSoft Settings & Options - Options page (PeopleSoft Outlook menu, Settings & Options, click the Options page).

Use the PeopleSoft Settings & Options - Options page to review or select your display features and frequency of updates.



PeopleSoft Settings & Options - Options page

Auto open display in home page

Select to automatically open the display in your Microsoft Outlook home page.

Popup New Tasks

Select to be alerted by popup messages when a new task falls into your queue.

Connection Speed

Select to specify the connection speed. Values are:

- *Auto*: This is the default value.
- *Fast*
- *Average*
- *Slow*

You can adjust your connection speed which will adjust the chunk size when sending and receiving files.

In Desktop Integration's File Transfer page, an option exists to override your connection speed.

Check for new items every

Specify the frequency of system updates in minutes. This determines how often you want to replicate the PeopleSoft system information.

If set to 0, no replication will take place.

Display Working Days Only

Select to only display working days by default in the PeopleSoft Scheduling Assistant.

Display Working Hours Only

Select to only display working hours by default in the PeopleSoft Scheduling Assistant.

Ignore Missing Free/Busy Data


Select for the system to ignore missing free/busy data.

When you select this option you avoid unnecessary clutter from unavailable data.

Reviewing the Status Log Page

Access the PeopleSoft Settings & Options - Status Log page (PeopleSoft Outlook menu, Settings & Options, click the Status Log page).

Use the PeopleSoft Settings & Options - Status Log page to review the send and receive data and any errors in the log.



PeopleSoft Settings & Options - Status Log page


If you are experiencing any issues, you can access this page and clear the log or export and save the log information. This log is only available in the current session. If you exit Microsoft Outlook, and then log back in, the log information is erased and no longer visible. This page also displays the current version of the PeopleSoft Outlook Add-In that you are using.

Using the PeopleSoft Scheduler and Scheduling Assistant

Access the PeopleSoft Scheduler page (PeopleSoft Outlook menu, Scheduling Assistant).

Use the PeopleSoft Scheduler page and Scheduling Assistant to expand the functionality of your appointments, meetings, address books, and messages.

The PeopleSoft Scheduling Assistant helps you manage and schedule all of your PeopleSoft meetings.



PeopleSoft Scheduler page

The PeopleSoft Scheduler page and Scheduling Assistant provide the following features and functionality:

Meetings Group Actions

- | | |
|--------------------|--|
| Send | Click to send the selected meeting or group of meetings. |
| Cancel | Click to cancel the selected meeting or group of meetings. |
| Save Group | Click to save the selected meeting or group of meetings. |
| Add Meeting | Click to add a meeting. |
| Refresh | Click to refresh. This action retrieves the data from the PeopleSoft system. If you have unsaved data the system prompts you to save now, or your data will be lost. |

Selected Meeting Actions

Send Invitations	Click to send the selected invitation or group of invitations.
Cancel Meeting	Click to cancel the selected meeting or group of meetings.
Save Meeting	Click to save the selected meeting or group of meetings.
Address Book	Click to add someone from your address book to the selected meeting or group of meetings.
Check Names	Click to initiate the system to verify that your selected participants have valid email addresses.
Delete	Click to delete the selected meeting or group of meetings.
Send as iCal	Click to send the selected meeting as an iCalendar attachment.
Custom Message	Click to send a custom message, and then select Message to choose which message you want to use.
Message	Click to choose the message you want to use.

Options

Message To All Attendees	Click to send the same message to multiple people.
Display	From the drop-down list, select the features that you want to display in your Outlook homepage. Values are: <ul style="list-style-type: none">• Meeting Queue• Availability Window• Show Working Days Only• Show Working Hours Only

Meeting Queue

When you look in the Meeting Queue display, you see everything that is assigned to you to be scheduled. You can click a specific meeting (line item) to display the meeting details in your Outlook homepage.

These options enable you to filter what is visible in your Meeting Queue.

Filter	Select from the available options to display in your Outlook homepage: <ul style="list-style-type: none"> • <i>Ready to Schedule</i>: This is the first stage; in the Meeting Queue but nothing has been done. • <i>In Progress</i>: Select to display meetings that are in progress. Invitations may have been sent, but these meetings are incomplete. • <i>Scheduled Meetings</i>: Select to display meetings that have been scheduled. • <i>Past Meetings</i>: Select to display meetings that already occurred. • <i>Cancelled Meetings</i>: Select to display meetings that were cancelled. • <i>On Hold Meetings</i>: Select to display meetings that were in the Meeting Queue, then put on hold. • <i>Set Date Range</i>: Select to specify a date range for the options you want to display.
Save All	Click to save everything selected in your Meeting Queue.
Refresh	Click to refresh your Meeting Queue.
PeopleSoft	
Display	Displays Dynamic Displays for the current document.

Replicating Appointments, Meetings, Tasks and Address Books

The replication options in the PeopleSoft Outlook menu have no dialog or visual component. These items are replicated to and from PeopleSoft only. Therefore, only appointments, meetings, tasks, and address books that are also PeopleSoft items can be replicated. The menu options enable you to perform the replications manually.

Alternatively, you can set up a schedule for replication in the PeopleSoft Settings & Options pages.

See [Chapter 10, "Using Desktop Integration," Defining Settings and Options, page 196.](#)

Replicating Appointments and Meetings

Use the PeopleSoft Replicate Appointments/Meetings option to manually start the replication process for those items.

Replicating Tasks

Use the PeopleSoft Replicate Tasks option to manually start the replication process for those items.

Replicating Address Books

Use the PeopleSoft Replicate Address Books option to manually start the replication process for those items.

Part 4

Enterprise Integration

Chapter 11

Understanding Enterprise Integration

Chapter 12

Understanding Integration Points

Chapter 13

Activating Integration Points

Chapter 11

Understanding Enterprise Integration

This chapter discusses:

- PeopleSoft Business Interlinks.
- PeopleSoft Component Interfaces.
- File layouts.
- PeopleSoft Integration Broker.

Understanding PeopleSoft Business Interlinks

PeopleSoft Business Interlinks enables you to perform component-based, real-time integration from PeopleSoft applications to external systems. PeopleSoft Business Interlinks creates synchronous transactions that enable PeopleSoft applications to pass data to and receive data from the external system in real time. You can use PeopleSoft Business Interlinks to integrate PeopleSoft with third-party systems, with another PeopleSoft application, or with systems on the internet.

Understanding PeopleSoft Component Interfaces

A component interface is a set of application programming interfaces (APIs) that you can use to access and modify PeopleSoft database information using a program instead of the PeopleSoft client. PeopleSoft Component Interfaces exposes a PeopleSoft component (a set of pages grouped for a business purpose) for synchronous access from another application (PeopleCode, Java, C/C++, or Component Object Model [COM]). A PeopleCode program or an external program (Java, C/C++, or COM) can view, enter, manipulate, and access PeopleSoft component data, business logic, and functionality.

Understanding File Layouts

A file layout is a definition (or mapping) of a file to be processed. It identifies where fields are located in file data. Once you create a file layout, you can write PeopleCode programs that ultimately use the file layout, either to read data from or write data to a file.

In addition to manipulating transaction data, you can use file layouts and flat files to move data between your PeopleSoft database and external systems (data interchange).

Understanding PeopleSoft Integration Broker

PeopleSoft Integration Broker is a messaging system that enables you to synchronize data in one application or system with another.

PeopleSoft Integration Broker facilitates synchronous and asynchronous messaging among internal systems and trading partners, while managing message structure, message format, and transport disparities.

PeopleSoft Integration Broker comprises two high-level subsystems: the integration engine and the integration gateway. The integration engine runs on the PeopleSoft application server. It is tied closely to PeopleSoft applications and produces or consumes messages for these applications.

The integration gateway manages the receipt and delivery of messages passed among systems through PeopleSoft Integration Broker. It provides support for the leading TCP/IP protocols used in the marketplace today, and more importantly, provides extensible interfaces for the development of new connectors for communication with legacy and internet-based systems.

Chapter 12

Understanding Integration Points

This chapter discusses integration points.

Note. The term *integration point* and *Enterprise Integration Point (EIP)* are synonymous and may appear interchangeably in this documentation.

Overview of Integration Points

Provided by a PeopleSoft application, an integration point is an interface that is used to communicate with other PeopleSoft or external applications. An integration point provides integration details for PeopleSoft applications, including which technologies are involved, technology details, information for using PeopleSoft Integration Broker for messaging, and how different integration points are related.

The integration point consists of data rules for the applications that it supports. The integration points that are delivered with PeopleSoft applications provide generic functionality so that they can be adapted for use with as many programs as possible.

You can implement an integration point can be implemented by using different technologies available in PeopleTools, such as messaging, component interfaces, business interlinks, XML links, and electronic data interchange (EDI).

Integration points can be associated with or used by application groups. An application group is a logical grouping of applications that use an integration point in the same business manner.

Other than this grouping facility, an application group and an application mean the same thing. In the rest of the documentation, the words *application group* and *application* are used interchangeably unless clearly specified.

Every integration point is owned by at least one application, but can be used in multiple applications. Therefore, if an application sends an integration point, and another application can receive the same integration point, the two systems should be interoperable, assuming the data structure and the rules of the integration point are implemented the same in both places.

However, sometimes two applications might use the same integration point but implement it in different ways. For example, one application that uses the Customer integration point may need to transform the data before it can be sent to an external system, which has another data structure for its customer information.

An integration point can be a part of multiple application groups. For example, the Department Table integration point may be used by a number of application groups, including PeopleSoft Human Resources, Customer Relationship Management (CRM), and General Ledger.

For more information, refer to the Interactive Services Repository on the My Oracle Support website.

Chapter 13

Activating Integration Points

This chapter discusses how to:

- Set up PeopleSoft integration points.
- Set up related languages.
- Examine related-language messaging scenarios.

Setting Up PeopleSoft Integration Points

This section discusses how to:

- Set up publication rules.
- (Optional) Map nodes to a chunking rule.
- (Optional) Assign business units or setIDs to a chunking rule.
- Specify OnRoute PeopleCode.

Note. For more information and technical details about these integration points, and for information about how and with what applications to use them, consult the relevant application PeopleBook.

Pages Used to Set Up PeopleSoft Integration Points

<i>Page Name</i>	<i>Definition Name</i>	<i>Navigation</i>	<i>Usage</i>
Batch Publish Rules	EOIU_SOPUBATCH	Enterprise Components, Integration Definitions, Batch Publish Rules	Set up publication rules. You must activate a publication rule for the publication messages that you create to follow. This rule includes instructions on message chunking.
Add Nodes to Chunk Rule	EOIU_ADNODECHUNK_PNL	Enterprise Components, Integration Definitions, Map Chunking Rules, Node to ChunkRule	Map PeopleSoft message nodes to chunking rules.

Page Name	Definition Name	Navigation	Usage
Batch Publish	EOIU_BATCHPUB	Enterprise Components, Integration Definitions, Initiate Processes, Batch Publish	Create the run control for the batch publish process.

Setting Up Publication Rules

Access the Batch Publish Rules page (Enterprise Components, Integration Definitions, Batch Publish Rules).

You must activate a publication rule for the publication messages that you create to follow. This rule includes instructions on message chunking, if necessary.

Batch Publish Rules page

If the data that you're transmitting does not fit in a single message, or if you want to send different parts of the message to different target systems, set up the rules to chunk the message and associate it with the publish rule. The business unit and setID chunking rules are standard in PeopleSoft applications, but you can configure chunking rules.

Publish Rule ID Select the name of the message for which you're setting up rules.

Status Select *Active* to activate this publish rule definition for this message. Select *Inactive* to prevent this rule from applying to this message.

Chunking Rule ID and Alternate Chunk Table

Enter the unique chunking rule name that is set up when you created the chunking rule. The message that you publish is routed based on this field. If necessary, enter an additional field in the Alternate Chunk Rule ID field by which to chunk the message.

Message Options

Many PeopleSoft systems rely on a message header and message trailer to trigger subscription PeopleCode to discard old table data and insert the new incoming data. As a general rule, all FullSync messages should use a header and trailer. Sync messages don't need headers and trailers.

Output Format

The Application Engine program used to chunk messages can create either an XML message that flows through messaging architecture or a flat file that is generated in PeopleSoft Process Scheduler and not published elsewhere. Always select Message as the format when you send data to PeopleSoft systems.

Mapping Nodes to a Chunking Rule

Access the Add Nodes to Chunk Rule page (Enterprise Components, Integration Definitions, Map Chunking Rules, Node to ChunkRule).

Add Nodes to Chunk Rule

Chunking Rule ID: BUSINESS_UNIT

Effective Date: 02/24/2000

Status: Active Select All Deselect All

Add	Message Node Name	Description	Add Chunk Values
<input type="checkbox"/>	AIA	Internal Use. Do not modify.	
<input checked="" type="checkbox"/>	ANONYMOUS	Used internally by IB system.	ADD
<input type="checkbox"/>	ASYNC_MDN	AS2 Node fore MDN's	
<input type="checkbox"/>	ATOM	Internal Use. Do not modify.	
<input type="checkbox"/>	BP	Portal Node - BP	
<input type="checkbox"/>	BPEL	Oracle BPEL PM Node	
<input type="checkbox"/>	CAMP	Portal Node - CAMP	
<input type="checkbox"/>	CRM	Portal Node - CRM	

Save Return to Search Previous in List Next in List Notify

Add Nodes to Chunk Rule page

To map nodes to a chunk rule:

1. In the Add column, select the check box next to the nodes that you defined earlier.

After you select a node, use the Add button in the Add Chunk Values column to open the Quick Map page for the message you defined earlier.

2. Click Save.

Assigning Business Units or SetIDs to a Chunking Rule

See [Chapter 13, "Activating Integration Points," Assigning Business Units or SetIDs to a Chunking Rule, page 216.](#)

Specifying OnRoute PeopleCode

Create a service operation handler to route the message chunk to the correct subscriber node.

To do so, extend the IRouter application class and use the OnRouteSend method. Then in the appropriate service operation, define a handler and specify the application class.

See Also

PeopleTools: PeopleSoft Integration Broker PeopleBook, "Sending and Receiving Messages," Understanding Integration PeopleCode

PeopleTools: PeopleSoft Integration Broker PeopleBook, "Sending and Receiving Messages," Messaging Handlers

PeopleTools: PeopleSoft Integration Broker PeopleBook, "Managing Service Operations," Configuring Service Operation Definitions

Setting Up Related Languages

This section provides overviews of related language tables and related language guidelines for PeopleSoft messaging and discusses how to:

- Interpret component processor behavior.
- Publish a message from a component.
- Publish a message from batch programs.
- Subscribe to data in a PeopleSoft multilingual environment.
- Subscribe to data in a non-multilingual environment.

Understanding Related Language Tables

You can use several possible scenarios to familiarize yourself with related languages when setting up related languages for a message.

A department table, for example, must publish information in German as well as English. In the following example, the base application tables and related-language tables have a parent-child relationship. The related-language table has the same name as the parent table, but is suffixed with `_LANG`, in accordance with PeopleSoft naming conventions.

Num	Field Name	Type	Key	Ord	Dir	Cur	Srch	List	Sys
1	SETID	Char	Key	1	Asc		Yes	Yes	No
2	DEPTID	Char	Key	2	Asc		Yes	Yes	No
3	EFFDT	Date	Key	3	Desc		No	No	No
4	EFF_STATUS	Char					No	No	No
5	DESCR	Char					No	Yes	No
6	DESCRSHORT								
7	COMPANY								
8	SETID_LOCATION								
9	LOCATION								
10	TAX_LOCATION_CD								
11	MANAGER_ID								
12	MANAGER_POSN								
13	BUDGET_YR_END_DT								
14	BUDGET_LVL								

Num	Field Name	Type	Key	Ord	Dir	Cur
1	SETID	Char	Key	1	Asc	
2	DEPTID	Char	Key	2	Asc	
3	LANGUAGE_CD	Char	Key	3	Asc	
4	EFFDT	Date	Key	4	Desc	
5	DESCR	Char	Alt		Asc	
6	DESCRSHORT	Char				

Related-language record definitions

Consider the following points:

- The parent table, DEPT_TBL, has the related-language child table, DEPT_TBL_LANG.
- The child table has the same fields as the parent table, plus an additional field of LANGUAGE_CD.
- The attributes of the child table are all of the translatable textual fields of the parent record.

Understanding Related Language Guidelines for Messaging

When publishing a full message, generate messages that contain the contents of an entire table by first generating a message in the base language of the system that contains the full table contents. Then generate messages for each of the related languages that are supported by the publishing system. Each message should contain the full message structure for that message object (levels 0, 1, 2, and so on). The language-specific messages should contain the translatable field values for that language and include the base language fields that are not translatable.

When subscribing to a full message, specify the language code only at level 0 of the message. This captures and sets the user's preferred language to level 0 of the PeopleSoft Common Application Message Attributes (PSCAMA) message header. All data within the message must be in the same language. Follow these steps:

1. Delete the base language tables and related-language tables.
2. Replace these tables with data from the messages as appropriate.
3. Place only those related-language field values that are supported by the subscribing system into the related-language tables.
4. Add the related-language table entry only if the base language table entry already exists.

When publishing an incremental message, the PeopleSoft system generates base messages in the user's preferred language by using the language code of the user ID. Putting the user's preferred language code in the message header PSCAMA record defines the message language for the subscribing system.

When subscribing to an incremental message using PeopleSoft Component Interfaces, use a simple PeopleCode program that performs a SetLanguage (messagelanguage) call to a component interface with the message definition. This enables the subscribing system to process the data in the appropriate related or base language for that system.

When subscribing to an incremental message using PeopleCode only, the PeopleCode program must simulate what the component processor does. The PeopleSoft system provides a generic Subscribe_IncrReplication PeopleCode function that provides basic language-related ability for incremental message subscriptions.

Note. All PeopleSoft subscription processes that are associated with textual information work as if the content is related-language enabled; thus the processes provide support for customer related-language extensions and future PeopleSoft enhancements.

For PeopleSoft-to-PeopleSoft system integration, you do not need to specify the language-sensitive data on either system.

All of the PeopleCode functions that are needed for related language processing of incremental and full messages are in the FUNCLIB_EOEIP record. The record contains two functions:

- Subscribe_IncrReplication has related-language processing for an incremental message subscription process.
- Subscribe_FullReplication has related-language processing for a batch subscribe process.

Interpreting Component Processor Behavior

When you open a component, the component processor:

1. Compares the user's preferred language against the base language for the database.
2. Uses the record information from the base application table (DEPARTMENT_TBL).

If a record in the base application table exists for the user's preferred language, the fields on the related-language table (DEPARTMENT_LANG) overlay the record information. For example, a German user sees German descriptions even if the base language for the database is English.

When you change the user's preferred language and save the component:

1. The component processor writes all the data for related-language fields back to the related-language table.
2. The component processor writes the rest of the data back to the base application table.
3. The German user's entries for the DESCR and DESCRSHORT fields are saved back to the DEPARTMENT_LANG table with its key values and the LANGUAGE_CD field in German.
4. The data that was entered by the German user in the key fields, as well as MANAGER_NAME and ACCOUNTING_OWNER fields, are saved on the parent record DEPARTMENT_TBL.

Publishing a Message from a Component

The PeopleSoft system employs the user's preferred language to determine the language of a message that is published from a component. The default for LANGUAGE_CD is set to the preferred language code (OPERATOR.LANGUAGE_CD). The standard for incremental changes is to publish only the data that has changed, in the language to which it was changed. Changing the preferred language to translate data generates new messages appropriately.

Publishing a Message from Batch Programs

Application Engine and Structured Query Report incremental message programs should use the base language of the system. These programs perform their accesses and updates on the base tables only, even if related-language tables are supported for those business objects. Related-language tables are featured in batch program processing only in generating warnings or errors that use the message catalog.

When a batch application program runs, the processing is done in the base language of the system, and messages are generated in only the base language.

Subscribing to Data in a PeopleSoft Multilingual Environment

The subscription process sets the language for processing the message to the language needed by the subscriber system. For example, if the base language of the subscribing system is French, and the PeopleSoft system is sending German data, the subscription process must store the German data in a related-language table and the nontranslatable data in the French base application tables. Neither system's base language matters; only the base language of the subscribing system and the actual message language are used.

Subscribing to Data in a Non-Multilingual Environment

When handling subscribing systems that do not support multiple languages, you can subscribe to data in these ways:

- Setting message publish routing PeopleCode.
- Sending service operations to all appropriate nodes.
- Permitting the subscription to process itself.
- Subscribing to data that is specific to an external system.

Setting Message Publish Routing PeopleCode

Set message publish routing PeopleCode to send only messages in a particular language code to a subscribing node.

The subscribing node does not need to check the language in which the message was generated; any message that it receives in its language is automatically used to update the subscribing system's database. To implement this option:

- Determine the languages in which messages are published.

- Determine the message language that a subscribing node receives.
- Add PeopleCode routing logic on the publish side to check the language code of the first occurrence in the message record and return a list of subscribing nodes that should receive the message for that language.

The publish routing PeopleCode guarantees that the message is sent to the correct subscribing nodes by using the message language code.

Sending Service Operations to All Appropriate Nodes

Send service operations to all appropriate nodes regardless of the language and have the subscription routing PeopleCode filter out messages in different languages.

PeopleCode on the subscription routing checks the language code of the first occurrence in the message and controls whether the node should receive the message. To implement this option:

- Ensure that service operations in all languages are sent to all appropriate nodes.
- Add the PeopleCode to compare the message language against a hard-coded language value for the subscribing system.

The advantage of putting the logic within the subscription routing PeopleCode is that every message is checked for a language value match.

Permitting the Subscription to Process Itself

You can permit the subscription process itself, rather than the routing PeopleCode for the service operation and queue, to determine whether the message should be processed for the subscribing system.

The subscription process checks the language code of the PSCAMA record for the first instance of the message against a hard-coded value for the subscribing system. If the language code does not match, the message is ignored. If the message language code does match, it's considered a base language message, and it replaces all data on the subscribing system according to the audit action flags on the message records.

Note. To prevent data integrity issues, generic subscription processes should not filter messages based on language code.

Subscribing to Data That Is Specific to an External System

Subscribe to data that is specific to an external system for language code, business unit, or setID requirements that are specific to an external system.

Use the chunking rule and the routing control tables that Oracle supplies to select a portion of the data and send it to a specific node.

Use the PeopleSoft-supplied Publish Header (PublishHdr) component to enter the partitioning views and fields for a message. This chunks the message so that all contents within a single message contain the same partitioning value (such as business unit, setID, or application-specific fields).

Set up the routing control for the message so that the message is sent only to the appropriate nodes. The PeopleSoft system supplies a business unit routing control (BU Routing Control) component and a setID routing control component that enable applications to specify for each message which nodes should receive the partitioned message data.

After you set up the chunking rule and routing rules, both the full data publish and batch publish programs partition the data according to the appropriate value and route it accordingly. You can now publish and subscribe to the message.

Examining Related-Language Messaging Scenarios

Actual related-language messaging scenarios include publishing a non-base language message and switching a preferred language.

This section discusses how to:

- Publish a non-base language message to a PeopleSoft subscribing system with a different base language and no prior data.
- Switch the preferred language to Japanese and update the same employee's name and address.

Publishing a Non-Base Language Message to a Subscribing System with a Different Base Language and No Prior Data

In the following example, the publishing system base language is English, the subscriber base language is Japanese, and the user's preferred language is German.

This is the process for publishing:

1. An online user adds a new level 0 key on a page.

The data is stored in both the base language table (English) and the related-language table (German).

2. The system publishes a message in the user's preferred language (German).
3. The data is inserted into the subscribing system.

The data is inserted into both the base language table and related-language table (German) because it is added for the first time; data cannot reside in a related-language table without corresponding data being in the base table.

Switching the Preferred Language to Japanese and Updating the Same Employee's Name and Address

This is the process for switching a preferred language:

1. A user switches the preferred language from English to Japanese.

The user updates the same record as in the previous scenario. Data that is not language-sensitive is updated in the base table (English). Language-sensitive data is inserted into the related-language table (Japanese).

2. A system publishes a message in the user's preferred language (Japanese).
3. Data is inserted into the subscribing system.

All data goes to the base table (Japanese), because the message was sent in the same language as the subscribing system's base language.

Appendix A

Integration Point Naming Standards

Integration point names describe the business purposes of integration points and provide a virtual wrapper for packaging one or more integration technology objects.

Integration point names use an approved list of standard PeopleSoft business object nouns and action and event verbs.

Standard Action and Event Verbs

The following standard verbs are used in the names and descriptions of integration points:

Verb	Description
Acknowledge	Indicates receipt of a processing request. Also conveys the result of the original request. (For example, your application acknowledges a purchase order (PO) when a PO has been issued and the corresponding business application acknowledges the receipt of the PO and responds with an acceptance or counter offer.)
Add	Use when a complete entity has already been constructed and needs to be communicated for the first time to another business application, and when business implications go beyond what a Sync message would convey. Transactional messages may use Add; setup data should use Sync.
Adjust	Clarifies a specific process (for example, adjustment of inventory quantity on hand when neither Add, Change, or Delete conveys the full meaning).
Allocate	Clarifies a specific process (for example, allocating costs to different business applications when neither Add, Change, or Delete conveys the full meaning).
Approve	Use when an entity passes an approval process and is ready for the next business process step.
Cancel	Use when business implications go beyond a simple change or delete (for example, canceling a purchase order).

Verb	Description
Change	Use when an entity is changed based on a business event and the change needs to be communicated to another business application. Encompasses business implications beyond what a Sync message would convey (for example, SalesOrderChange). Transactional messages can use Change; setup data should use Sync.
Confirm	Responds to a request from the receiving application to confirm. This function conveys the result of the original request (for example, when an inventory issue must be confirmed in an application based on an event in a warehouse management business application).
Create	Use when the processing must initiate the building of the document rather than moving the document from one system to another.
Find	Requests a list of items from a business application. The response to this request is List. Equivalent to a search dialog box in which you pass the search criteria over as the message.
FullSync	Replicates a complete entity, including all record instances, between business applications to initially seed the receiving application with that data. Use with all full message definitions.
Get	Requests a specific data entity from a business application. The response to this request is Show. Differs from Find in that the specific entity's key values are known and its details are being requested, whereas Find checks for existence and returns a list of values that match the Find criteria.
Issue	Clarifies a specific process (for example, issue material from inventory in cases in which neither Add, Change, or Delete conveys the full meaning).
List	Use when sending a list of multiple data entities in a summary format. The List verb can be used to respond to a Find or Get request, or in a publish scenario, to push information to other applications based on a business event. The results of a List can be used as is, or they can be used to select a specific instance of a document or entity to issue a detail Get request.
Load	Initiates the addition of a data entity to another business application where maintenance of the document passes to the receiving application permanently. When the request is passed, the sending application no longer has direct control over the document or entity.
Post	Clarifies a specific process (for example, a posted journal entry, in cases in which neither Add, Change, or Delete conveys the full meaning).
Receive	Clarifies a specific process (for example, when you receive inventory against a PO, in cases in which Change is not detailed enough for the business context).

Verb	Description
Request	Requests specific data from a business application. The requested data should be passed back as a separate message.
Show	Sends information about a specific instance of a business entity. Can also be used to respond to a Get request, or in a publish scenario in which it pushes information to other applications based on a business event.
Sync	Communicates the need to update master files between business applications. Facilitates application integrity and ease of data entry for the business user by enabling a single point of input. Should contain only incremental messages of Add, Change, and Delete actions to the entity. Normally used for passing setup messages between applications.
Transfer	Clarifies a specific process (for example, in the event of a transfer of material from one inventory location to another, in cases in which neither Add, Change, or Delete conveys the full meaning).
Update	Clarifies a specific process (for example, in the event of an update of inspection information from one business application to another, in cases in which neither Add, Change, or Delete conveys the full meaning). The event is not adding a document or changing fields, but communicating the occurrence of an event as well as the corresponding data that accompanies the event. Transactional data may use Update; setup data should use Sync.

Standard Business Object Nouns

Business objects appear in uppercase with underscores between key words.

The following table lists examples of business object names only; it is not intended to list or set conventions.

Account_Chartfield	Deal	Names_Prefix_Suffix	Project_Category
Action_Reason	Department	Nations_Duevo	Project_Status
APE_Industry	Dept_Budget	Occupation_Illness	Project_Team
Applicant	Detail_Calendar	Par_Location	Project_Type_Cat_Link
Bank	DirectDeposit	Par_Location_Count	Purchase_Order
BOM	Earnings	Payroll	Rating_Model

<i>Account_Chartfield</i>	<i>Deal</i>	<i>Names_Prefix_Suffix</i>	<i>Project_Category</i>
Budget	Expense	Payroll_Paysheet	Regulatory_Region
Bus_Unit_FS	Expense_Advance	Pension_Fund	Resource_Category
Bus_Unit_GL	Expense_Report	Person_Accomplishment	Resource_SubCategory
Bus_Unit_HR	Expense_Sheet	Person_Competency	Resource_Type
Bus_Unit_PC	Fund	Person_Contract_Belgium	Review_Scale
Bus_Unit_PF	Grant	Person_Credit_Card	Salary
Carrier	Image	Person_Disability	Salary_Matrix
Company	Industry_Inspection	Person_Diversity	Salary_Plan
Company_Credit_Card	InterUnit	Person_Education	Salary_Structure
Company_Property	Inventory	Person_Names	SalesOrder
Competency	Item	Person_Property	Schedule
Consumer	Item_BusUnit	Person_PriorWork	State
Consumer_Usage	Item_Rev	Person_Visa_Citizen	State_Name
Contract	Item_Vendor	Position	Statute
ContractBelgium	Job_Code	Product_Chartfield	Statute_Belgium
Country	Journal	Product_Item	Vendor
Customer	Labor_Category	Product_Group	Visa_Permit
Credit_Card	Labor_Relations	Product_Price	Voucher

<i>Account_Chartfield</i>	<i>Deal</i>	<i>Names_Prefix_Suffix</i>	<i>Project_Category</i>
Credit_Card_Merchant	Location	Product_UOM	Union
Currency	Market_Price	Project	UOM
Customer	Market_Rate	Project_Activity	Workforce

Appendix B

PeopleSoft Design Patterns

Oracle delivers a group of design patterns with each application. The Design Patterns page lists available design patterns.

List of Design Patterns

The following table presents brief descriptions of the delivered design patterns:

<i>Design Pattern Name</i>	<i>Description</i>
AE Row By Row Publish (application engine row by row publish)	In this design pattern, the transaction or setup data that you want to send out of the PeopleSoft system is updated by use of an Application Engine program that performs procedural (row-by-row) processing; you want to publish these changes. Generally, messages are used with this design pattern.
Batch Publish	Use this design pattern to publish messages from a batch application. The batch application can be a COBOL or Structured Query Report program that takes either a procedural or set-based approach, or it can be an Application Engine set-based program.
Batch Subscribe	This design pattern enables you to perform edits against messages in sets. This can be a useful technique for high volume data, including millions of inbound rows. This design pattern is useful when you know that a single message definition may contain multiple instances of a transaction, or when you must reuse an existing batch program.
CI Subscribe (component interface subscribe)	This design pattern uses a component interface to edit incoming message data. This enables you to reuse existing business rules when processing data.

Design Pattern Name	Description
Component Publish	In this design pattern, the transaction or setup data that you want to send out of PeopleSoft is being updated by using a PeopleSoft component. In this case, the data is already in the component buffer, and the Publish PeopleCode function is used to publish a message.
EDI In	This design pattern is for inbound EDI documents. You should use EDI only for existing EDI manager inbound transactions that must be supplied to an EDI partner, and you want to allow subscription to an XML message, or when you need to comply with other industry standards, such as SWIFT, BAI, or HL7, that have an existing EDI manager inbound map, and you want to convert to subscribing to an XML message.
EDI Out	This design pattern is for outbound EDI documents. You should use EDI only for existing EDI manager inbound transactions that must be supplied to an EDI partner and you want to allow subscription to an XML message, or you need to comply with other industry standards, such as SWIFT, BAI, or HL7, that have an existing EDI manager inbound map, and you want to convert to publishing to an XML message.
Full Table Publish	Use this design pattern to populate an entire copy of a table onto a remote database or legacy system. Generally, full data replication occurs with setup tables, or relatively static, low-volume tables that are keyed by setID. When a copy of a table exists on the remote system, incremental updates can be used.
Full Table Subscribe	Use this design pattern to subscribe to messages that contain an entire copy of a table that is published from a remote database or legacy system. Generally, full data replication occurs with setup tables, or relatively static, low-volume tables that are keyed by setID. When a copy of a table exists on the remote system, incremental updates can be used.
No Pattern	No design pattern is specified.
PeopleCode Subscribe	Use this design pattern to subscribe to messages by using a PeopleCode program when additional processing is required. Use PeopleCode subscription when simple edits or no edits against the inbound data are needed before you insert the data into the application tables or staging tables.

<i>Design Pattern Name</i>	<i>Description</i>
Sync Reply	In this design pattern, another system initiates a request for information from the PeopleSoft system and waits for information to be returned. This information must be provided by the PeopleSoft system in a real-time synchronous mode and in a conversational style of interface before the other system can continue processing. Generally, business interlinks are used to satisfy this type of request.
Sync Request	Use this design pattern when a PeopleSoft application must call a third-party vendor's application to request information. This information must be provided in a real-time, synchronous mode. Generally, business interlinks are used to satisfy this type of request.
XML Reply	In this design pattern, another system initiates a request for information from the PeopleSoft system. This information must be provided by the PeopleSoft system in a real-time synchronous mode and in a conversational style of interface before the other system can continue processing. Generally, XMLDocs are used to satisfy this type of request.
XML Request	Use this design pattern when a PeopleSoft application must call a third party vendor's application to request information. This information must be provided in a real-time, synchronous mode. Generally, XMLDocs are used to satisfy this type of request.

Index

A

Additional Connect DN's page 32, 33
Add Nodes to Chunk Rule page
103, 111, 213, 216
Address Book Registration page 169
address books
 internal, registering 171
 registering 168, 169
 replicating 205
 types 168
Appointment/Meeting Group page 173
Appointment/Meeting Group page - Appointment
Queue 176
Appointment Queue
 reviewing 176
Appointment Registration page 173
appointments, setting up 173
appointments and meetings, replicating 204
Attribute Details page 41, 50
Authentication page 37
Availability page - Appointment Queue 173, 178
Availability page, using 178

B

Batch Programs page 95, 97
Batch Publish page 214
batch publish rules
 associating to a message 95
 characterizing 95
 pages used to assign 95
 setting up 214
Batch Publish Rules page 95, 213, 214
Business Interlinks, understanding 209
Business Interlink Status report 64
business units *See Also* chunking rules
BusUnit Mapping page 103, 108

C

Cache Schema page 32, 35
Card Entry/Display page - Test Credit Card
Interface 15, 19
Card Type page 15, 18
chunking
 alternate chunking table 86
 chunking field 85
 chunking rule 86
 chunking table 86
 data, maintaining 108
 defined 85
 tables, routing PeopleCode 117
chunking data 109, 110
Chunking Rule page 103, 107, 125, 128
chunking rules
 adding nodes to 111

 assigning business units to 112, 216
 assigning to a business unit 113
 assigning to a setID 114
 associating to publication rules 214
 creating 106
 defining 107
communication layer—Microsoft Outlook and
Word Add-In 155
Component Interfaces, understanding 209
credit card interface
 defining connection parameters 16
 defining credit card types 18
 describing error codes 22
 setting up 3, 15
 testing 19, 20
 understanding XML integrations 3
Credit Card Interface Installation page 15, 16
credit card types, defining accepted 18
custom chunking tables *See Also* chunking tables

D

Data Maintenance page 75, 77, 79
data subscription
 in multilingual environment 220
 in non-multilingual environment 220
data synchronization
 understanding for LDAP 28
 using LDIFs 28
Delete_Existing_Data Function 99
Delete Directory page 32, 36
Desktop Integration
 components 155
 configuring 160
 defining Dynamic Displays 187
 defining Fields and Layout 191
 defining the Address Book Registration page
 169
 defining the Appointment Registration page
 173
 defining the Internal Address Book page 172
PeopleSoft Application Layer— Desktop
Integration 156
prerequisites 156
reviewing the File Transfer Queue 185
setting up 157
setting up File Transfer Registration 183
setting up task registration 162
setting up the Integration Broker 157
setting up the Task Queue 164
setting up web service security 159
tools layer—PeopleSoft Applications utilize
156
understanding 155
understanding address book registration 168
using the Appointment/Meeting Group page
176
using the Availability page 178
using the Display Log 194
using the Meeting page 179

- web services layer—Integration Broker 156
- Desktop Integration Log page 194
- Directory Audit page 59
- Directory Audit report 63
- Directory Audit Report page 63
- Directory BI Status Report page 63, 64
- directory information trees, understanding 27
- Directory Interface
 - configuring the LDAP directory 31
 - considerations for implementing 28
 - delivered business interlinks 28
 - generating LDAP directory reports 59
 - reviewing LDAP directory data 59
 - setting up LDAP directory authentication for 36
 - setting up mappings for 40
 - steps to use 29
 - understanding 27
 - understanding data mapping 27
 - using the configuration component 30
- Directory Interface page - DN Attribute Function 46
- Directory Interface page - Modify Connect DN 40, 44
- Directory Interface setup
 - setting up in PeopleSoft Application Designer 29
 - setting up in PeopleSoft Integration Broker 29
- Directory Load page 56, 57
- Directory Search page 59, 60
- Directory Setup page 32, 33
- Display Definition page 186, 187
- display log, using 194
- distinguished name, modifying 44
- distinguished names, understanding 27
- distinguished names defaults 49
- DN *See* distinguished names
- DN Defaults page 41, 49
- DN Details page 40, 45
- dynamic displays, defining 186

E

- effective-dated and prior rows, publishing from the delay table 134
- effective-dated messages
 - See Also* full data publish
 - creating a publish rule definition 128
 - defining chunking rules 128
 - defining routing 130
- effective-dated rows, publishing from the delay table 132
- Effective Date Prior Publish page 134
- Effective Date Publish page 133
- effective date publish utility
 - definition 123
 - full data publish 125
- Effective Date Pub page 133
- Enterprise Integration Points
 - See Also* integration points
- Entry Definition page 52, 53
- entry membership rules, setting up 52
- Entry Membership Rules page 52, 55
- EOEC_CCI_RESPONSE message 3
- EOEC_CCI_SYNC message 3

- Eo Recgrp page 103, 110
- error correction
 - messages 81
 - message setup and maintenance pages 75
- error handling utility
 - creating error correction pages 75
 - definition 73
 - row security 78
 - setting up 77
 - testing 79
 - workflow notification 81
- error management process 73

F

- Fields and Layout page 187, 191
- File Inbound page 139
- file layouts, understanding 209
- file transfer
 - setting up 183
 - setting up registration 183
 - setting up the queue 185
- File Transfer Queue page 183, 185
- File Transfer Registration page 183
- flat file utility
 - about 137
 - inbound file processing 137, 142
 - inbound file processing pages 139
 - inbound file processing setup 139
 - inbound file processing testing 144
- full data publish
 - creating effective-dated messages 126
 - creating the run control 129
 - defining a service operation 127
 - defining connectors 127
 - defining nodes 127
- Full Data Publish page 126, 129
- Full Table Publish Rules page 91, 92

G

- General page - Service Operations 157
- Generate XML Schema page 146

I

- inbound data error scan utility 121
- Inbound File page 142
- incremental messages
 - creating the message definition 131
 - effective-dated delay function 131
- Integration Broker
 - setting up 157
 - understanding 210
- integration points
 - See Also* message integration points
 - naming standards, nouns 227
 - naming standards, verbs 225
 - setting up 213
 - setup pages 213
- Internal Address Book page 172

L

Languages page 91, 94
 LDAP data, synchronizing with PeopleSoft data 27
 LDAP Data Interface Format files
 synchronizing data using 28
 LDAP directory
 configuring for Directory Interface 31
 setting up authentication for Directory Interface 36
 setting up mappings for use with Directory Interface 40
 LDIF *See* LDAP Data Interface Format files

M

Mandatory User Properties page 37, 38
 Map Business Unit page 104, 113
 Map Details page 40, 41
 mapping, messages 52
 mappings, creating 41
 Map SetID page 114
 Map Set IDs page 104
 MaxMessageSize 85
 Meeting page 173
 Meeting page - Appointment Queue 179
 Meeting page, using 179
 Message - Task Queue page 162, 167
 message chunking *See* chunking
 creating a chunking rule 106
 overview 102
 pages used to set up 103
 selecting chunking fields 104
 when to use 104
 message headers, defined 84
 message publishing
 from batch programs 220
 from online component 220
 message record mapping
 batch publish 96
 full publish 93
 message routing 216
 messages, delivered 52
 message trailers
 defined 84

N

nodes *See Also* chunking rules, adding nodes to

O

Optional User Properties page 37, 38

P

page processor 219

pages

add nodes to chunk rule 215, 216
 batch publish rules 95, 214
 BusUnit mapping 108
 chunking rule 107, 125
 data maintenance 77, 79
 effective date publish 133
 Eo Recgrp 110
 file inbound 139
 full data publish 129
 full table publish rules 92
 inbound file 142
 languages 94
 map business unit 113
 map SetIDs 114
 quick map 112
 record mapping 93
 SetID mapping 109
 workflow/security 78
 parallel processing
 defined 89
 PeopleCode functions, setting up 48
 PeopleSoft Outlook integration
 understanding 196
 PeopleSoft Outlook menu
 defining the Settings & Options pages 196
 PeopleSoft Outlook menu, using 196
 PeopleSoft Scheduler, using 201
 PeopleSoft Settings & Options
 defining the Options page 198
 defining the Servers page 197
 defining the Status Log page 200
 PeopleSoft system, setting up 160
 prerequisites for Desktop Integration
 Generic Integration Broker 156
 Microsoft Outlook 2007 or higher 156
 Microsoft Word 2007 or higher 156
 Secure Socket Layer (SSL) 156
 unique system IDs 156
 publish rules
 assigning an application program to 97
 associating to a message 92
 characterizing 92
 full table, assigning 91
 languages, specifying 94
 understanding 84
 publish utility
 overview 83
 Purge Transaction History page 65, 68

Q

Quick Map page 103, 112

R

Record Mapping page 91, 93, 95, 96
 registering
 address books 168, 169
 internal address books 171
 related languages
 guidelines for messaging 218
 scenarios 222
 setup 217

- replicating
 - address books 205
 - appointments and meetings 204
 - tasks 204
- reviewing, Appointment Queue 176
- row security *See Also* error handling utility

S

- Scheduling Assistant, using 201
- Schema Management page 32
- sequential processing
 - defined 89
- SetId Mapping page 103, 109
- setting up
 - appointment registration 173
 - appointments 173
 - Desktop Integration 157
 - file transfer registration 183
 - file transfers 183
 - Integration Broker 157
 - task registration 162
 - tasks 161
 - the file transfer queue 185
 - the PeopleSoft system 160
 - the Task Queue 164
 - web services 159
- Subscribe_FullReplication Function 99
- System Setup page 157, 160

T

- Task - Task Queue page 162, 164
- task registration
 - setting up 162
- Task Registration page 162
- tasks, replicating 204
- Test Connectivity page 32, 34
- Transaction History Inquiry page 65, 66
- Transaction History Report page 65
- Transaction page - Test Credit Card Interface
 - 15, 20

W

- Web Service Access page 157, 159
- web services, setting up 159
- Workflow/Security page 75, 78
- workflow notification
 - See Also* error handling utility

X

- XML-based integrations, understanding credit
 - card processing with 3
- XML Schema utility
 - examples 147
 - extracting table relationship 145
 - overview 145