

StorageTek Tape Analytics

Data Reference Guide

Version 2.0

E39015-01

April 2014

StorageTek Tape Analytics Data Reference Guide, Version 2.0

E39015-01

Copyright © 2012, 2014, Oracle and/or its affiliates. All rights reserved.

Primary Author: Nancy Stevens

Contributing Author: Kris Vickland

Contributor:

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	vii
Audience	vii
Documentation Accessibility	vii
Related Documents	vii
Conventions	viii
What's New	ix
STA v2.0, April 2014	ix
1 Attribute Cross-Reference	
2 Attribute Definitions	
Symbols	2-1
A	2-1
B	2-9
C	2-9
D	2-11
E	2-21
F	2-24
H	2-24
I	2-24
L	2-25
M	2-28
MV	2-36
N	2-41
P	2-41
R	2-43
S	2-46
T	2-48
U	2-49
W	2-50
3 Complexes Overview Screen	
Complexes Overview Detail View	3-1

Title	3-2
Library Complex	3-2
Library Complex Activity Counts (Last 30 days)	3-2
Library Complex Auxiliary Counts	3-2
User-Provided Information	3-3
 4 Libraries Overview Screen	
Libraries Overview Detail View	4-2
Title	4-2
Library	4-2
Library Activity Counts (Last 30 days)	4-3
Library Auxiliary Counts	4-3
User-Provided Information	4-4
 5 Drives Overview and Analysis Screens	
Drives Overview Detail Views	5-2
Title	5-5
Drive	5-5
Media	5-6
Most Recent Exchange	5-6
Drive Activity Counts (Last 30 Days)	5-7
Additional Exchange Information for Enterprise Drives	5-7
Additional Exchange Information for LTO Drives	5-8
Drive Location	5-8
Library Complex	5-8
Media Validation Information for Enterprise Drives	5-9
User-Provided Information	5-9
 6 Media Overview and Analysis Screens	
Media Overview Detail Views	6-2
Title	6-5
Media Details	6-5
Most Recent Exchange	6-5
Media Data Activity Counts (Last 30 Days)	6-6
Current Home Media Location	6-6
Drive	6-7
Additional Exchange Information for Enterprise Media	6-7
Additional Exchange Information for LTO Media	6-8
Library Complex	6-8
Cleaning Usage	6-8
User-Provided Information	6-8
Media Validation Information for Enterprise Media	6-8
Calibration Information for Enterprise Media	6-9
 7 Robots Overview Screen	
Robots Overview Detail View	7-1

Title	7-1
Robot.....	7-2
Robot Activity Counts (Last 30 Days)	7-2
User-Provided Information	7-2
Library Complex.....	7-2
 8 CAPs Overview Screen	
CAPs Overview Detail View.....	8-1
Title	8-1
CAP	8-2
CAP Activity Counts (Last 30 Days)	8-2
User-Provided Information	8-2
Library Complex.....	8-2
 9 PTPs Overview Screen	
PTPs Overview Detail View	9-1
Title	9-1
PTP	9-2
PTP Activity Counts (Last 30 Days)	9-2
User-Provided Information	9-2
Library Complex.....	9-2
 10 Elevators Overview Screen	
Elevators Overview Detail View.....	10-1
Title	10-1
Elevator.....	10-2
Elevator Activity Counts (Last 30 Days)	10-2
User-Provided Information	10-2
Library Complex.....	10-2
 11 Alerts Screens	
Alerts Overview Detail View.....	11-1
Alert Details	11-1
Other Details	11-1
Alert Location Information.....	11-2
User-Provided Information	11-2
 12 Exchanges Overview Screen	
Exchanges Overview Detail Views.....	12-2
Title	12-7
Exchange Health and Activity.....	12-7
Drive	12-8
Media	12-8
Library Complex.....	12-9
Enterprise Specific Information	12-9

Additional Enterprise Exchange Information	12-10
LTO Specific Information.....	12-10
Drive Bay Location.....	12-11
Media Source Location.....	12-11
Media Destination Location.....	12-11
Enterprise Exchange Alerts – Severe	12-11
Enterprise Exchange Alerts – Warning.....	12-12
Enterprise Exchange Alerts – Informational	12-12
LTO Exchange Alerts – Severe.....	12-12
LTO Exchange Alerts – Warning.....	12-13
LTO Exchange Alerts – Informational	12-14
User-Provided Information	12-14

13 Drive Cleanings Overview Screen

Drive Cleanings Overview Detail View	13-2
Title	13-2
Drive	13-2
Cleaning Activity.....	13-3
Library	13-3
User-Provided Information	13-3

14 Media Validation Overview Screen

Media Validation Overview List View	14-1
Media Validation Attribute Definitions.....	14-1

15 Messages Screens

All Messages Overview Detail View	15-2
Title	15-2
Trap Details	15-2
Drive Trap Details.....	15-2
Library Trap Details.....	15-3
Library	15-3
Library Configuration Details	15-3
User-Provided Information	15-3

Preface

This document provides information about using and interpreting the data displayed by Oracle's StorageTek Tape Analytics (STA). It provides definitions for all library, drive, and media data fields displayed by STA. It also provides reference information for all STA toolbars and data input fields.

Audience

This document is intended for new and experienced users of STA.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

The STA documentation set consists of the following documents.

For users of the STA application

- *STA Quick Start Guide*—Use this guide to introduce yourself to the STA application and some features of the user interface.
- *STA User's Guide*—Use this guide for instructions on using STA application features, such as the Dashboard, templates, filters, alerts, Executive Reports, logical groups, and STA media validation.
- *STA Screen Basics Guide*—Use this guide for details about the STA user interface. It describes the screen navigation and layout, and the use of graphs and tables.
- *STA Data Reference Guide*—Use this guide to look up definitions for all STA tape library system screens and data attributes.

For installers and administrators of the STA server and application

- *STA Release Notes*—Read this document before installing and using STA. It contains important release information, including known issues. This document is provided with the STA media pack download.
- *STA Requirements Guide*—Use this guide to learn about minimum and recommended requirements for using STA. This guide includes the following requirements: library, drive, server, user interface, STA media validation, and IBM RACF access control.
- *STA Installation and Configuration Guide*—Use this guide to plan for installation of STA, install the Linux operating system, install the STA application, and then configure library connections, users, and email addresses.
- *STA Administration Guide*—Use this guide to learn about STA administrative tasks, such as error logging, server administration, database backup and restore, STA services configuration, password administration, and SNMP connection configuration.
- *STA Security Guide*—Read this document for important STA security information, including requirements, recommendations, and general security principles.
- *Third Party Licenses and Notices*—Read this document for information about use of third-party technology distributed with the STA product.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

What's New

This section summarizes new and enhanced features for StorageTek Tape Analytics v2.0.

STA v2.0, April 2014

New and enhanced features are described in the following manuals.

STA Requirements Guide

- New guide that includes all minimum requirements for installing STA and using selected features
- New minimum requirements to support STA v2.0
 - Oracle Enterprise Linux (OEL) or Red Hat Enterprise Linux (RHEL) 6.3 or 6.4
 - New minimum library firmware levels
 - New drive firmware levels
- Enhanced library and device support
 - Support for LTO-6 drives
 - Support for Oracle's StorageTek T10000D drives
 - Support for SNMP library traps 13 and 14, providing enhanced library data
 - Support for Tape Transport Interface (TTI) 5.40, providing enhanced data from StorageTek T10000C and T10000D drives

STA Installation and Configuration Guide

- Upgrade process to migrate STA v1.0.x database to STA v2.0
- New ability to create STA usernames from within the STA user interface
- New ability to assign user roles to STA usernames
- Enhanced information provided when performing a library SNMP Check/Test Connection or Get Latest Data

STA Quick Start Guide

- New guide that introduces new users to the STA application and some features of the user interface

STA User's Guide

- New guide that describes how to use STA application features and interpret the data displayed by STA
- New user roles that determine the screens and activities individual users can access
- Enhanced Dashboard
 - Over 50 new graph, table, and report Dashboard portlets provide summary views of your tape library system
 - Highly customizable Dashboard display allows up to 30 portlets, arranged and filtered according to your specifications.
 - Predefined Nearline Dashboard templates provide hourly, daily, weekly, or monthly system utilization summaries.
 - New mobile Dashboard display
- Enhanced template management
 - New and enhanced STA predefined templates
 - New Template Quick Links screen provides one-click access to predefined and custom templates.
 - New Templates Management screen provides system-wide management of all templates.
 - Users can assign their own default templates by screen.
 - Users can import and export templates for sharing with other users.
- Enhanced Filter dialog box, providing the following abilities:
 - Filter by multiple exclusive or inclusive criteria
 - Filter for blank attribute values
 - Filter by user-defined logical group
 - Reset an applied screen filter with one click
- New Executive Reports based on customized Dashboard templates
 - User-defined Executive Report policies allow you to specify report content and frequency.
 - Reports are run automatically or on demand.
 - Reports are generated in PDF format.
 - Reports can be automatically emailed to selected addresses.
- New logical groups for organizing drives and media
 - Manual logical groups are user-maintained.
 - Dynamic logical groups are automatically updated based on user-defined criteria.
 - Logical groups can be used in defining selected policies and filters.
- New alert policies and generated alerts notifying you of events and conditions in your tape library system
 - User-defined alert policies allow you to specify alert generation criteria and frequency.

- Alerts can be automatically emailed to selected addresses.
- New STA media validation feature for T10000 T1 and T2 media
 - Requires minimum library firmware levels and T10000C and T10000D drive firmware levels supporting TTI 5.40.
 - Provides automated media validations based on user-defined policies.
 - Provides on-demand manual validations of single or multiple media.
 - Media Validation Overview screen provides user management of validation requests.
 - Provides comprehensive reporting of validation results.
 - Optional automated drive calibration and qualification feature ensures validation drives are high performing.

STA Screen Basics Guide

- Reorganized Navigation Bar throughout
- New screen display best practices for avoiding and troubleshooting browser display issues
- New user Annotations for List View table records and Dashboard. Annotation History is displayed in the Detail View.
- Additional table Export formats—XLS, CSV, and PDF
- New spark charts graph type used in Dashboard table portlets

STA Data Reference Guide

- New screens for library hardware components—robots, cartridge access ports (CAPs), pass-thru ports (PTPs), and elevators
- New screens for Alerts and Media Validation activities
- Notifications Overview and Analysis screens have been renamed to All Messages Overview and Analysis
- New Messages screens for libraries, drives, and media
- New data attributes
 - Media and Drive Health Trends
 - Library and library complex capacities, including media slots and drive bays
 - Library and library complex host request data
 - Data for library hardware components—robots, cartridge access ports (CAPs), pass-thru ports (PTPs), and elevators
 - Drive tray serial number
 - Drive port speed
 - Alerts detail and counts
 - Media validation data
 - Tape Alerts received from drives are now consistently labeled and grouped

STA Administration Guide

- STA processes split into three managed servers, which can be managed individually
- Processed SNMP records are periodically purged from the database to minimize database growth.

Attribute Cross-Reference

Table 1–1 lists all STA attributes, in alphabetical order, and identifies the screens where each one is displayed. To view the definition of an attribute, click the link in the table cell.

The screens are abbreviated as follows:

- Cmpx – "[Complexes Overview Screen](#)" on page 3-1
- Library – "[Libraries Overview Screen](#)" on page 4-1
- Drive – "[Drives Overview and Analysis Screens](#)" on page 5-1
- Media – "[Media Overview and Analysis Screens](#)" on page 6-1
- Lib Comp – any of the following screens on the Library Components tab:
 - "[Robots Overview Screen](#)" on page 7-1
 - "[CAPs Overview Screen](#)" on page 8-1
 - "[PTPs Overview Screen](#)" on page 9-1
 - "[Elevators Overview Screen](#)" on page 10-1
- Alerts – "[Alerts Screens](#)" on page 11-1
- Exch – "[Exchanges Overview Screen](#)" on page 12-1
- Clean – "[Drive Cleanings Overview Screen](#)" on page 13-1
- Media Valid – "[Media Validation Overview Screen](#)" on page 14-1
- Msgs – "[Messages Screens](#)" on page 15-1

Table 1–1 STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
% Drive Utilization	X	X	X							
Agent Boot Date/Time										X
Alert Event Type						X				
Alert Policy Name						X				
Alert Policy Type						X				
Alert Reason						X				
Alert Severity						X				
Alert State						X				
Alert: Cleaning Media							X			

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
Alert: Drive Automated Interface							X			
Alert: Drive Clean Now							X			
Alert: Drive Clean Periodic Requested							X			
Alert: Drive Cooling Fan							X			
Alert: Drive Diagnostics Required			X				X			
Alert: Drive Dual-Port Interface							X			
Alert: Drive Dump Available							X			
Alert: Drive Event Log Near Full							X			
Alert: Drive Failure Predicted							X			
Alert: Drive FW Download							X			
Alert: Drive FW Failure							X			
Alert: Drive Hard Error							X			
Alert: Drive Hardware A							X			
Alert: Drive Hardware B							X			
Alert: Drive Interface Fault							X			
Alert: Drive Load Limit			X				X			
Alert: Drive Model Incompatible							X			
Alert: Drive Temperature							X			
Alert: Drive Voltage							X			
Alert: Forced Eject Attempted							X			
Alert: Invalid Cleaning							X			
Alert: Media Loading Failure							X			
Alert: Media Cart Memory Failure				X			X			
Alert: Media Clean Expired							X	X		
Alert: Media Diminished Capacity							X			
Alert: Media Directory Corrupt				X			X			
Alert: Media Directory Invalid							X			
Alert: Media Eject Failed							X			
Alert: Media End of Warranty							X			
Alert: Media Error							X			
Alert: Media Life Exceeded							X			
Alert: Media Load Limit				X			X			
Alert: Media Loading Failure							X			
Alert: Media Lost Statistics							X			
Alert: Media Maintenance							X			

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
Alert: Media Nearing End of Life				X			X			
Alert: Media No Start of Data							X			
Alert: Media Not Data Grade							X			
Alert: Media Recoverable Mechanical							X			
Alert: Media RFID Warning							X			
Alert: Media System Read Failure							X			
Alert: Media System Write Failure							X			
Alert: Media Unrecoverable Mechanical							X			
Alert: Media Unrecoverable Snapped							X			
Alert: MIR Invalid							X			
Alert: Permanent Error							X			
Alert: Read Failure							X			
Alert: Read Only							X			
Alert: Read Warning							X			
Alert: Unload Prevented							X			
Alert: Unrecoverable Unload							X			
Alert: Unsupported Format							X			
Alert: WORM Integrity Failure							X			
Alert: WORM Overwrite Attempted							X			
Alert: Write Failure							X			
Alert: Write Protect							X			
Alert: Write Warning							X			
Annotation History	X	X	X	X	X	X	X	X		X
Avg Mount R/W MB			X							
Avg Mount R/W MB/sec			X	X						
Avg Mount Read MB			X							
Avg Mount Read MB/sec			X	X						
Avg Mount Write MB			X							
Avg Mount Write MB/sec			X	X						
Base Model	X									
CAP					X					
CAP Accessibility					X					
CAP Alert Count					X					
CAP Count	X	X								
CAP Ejects	X	X			X					
CAP Enters	X	X			X					
CAP Identifier					X					

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
CAP Library Health					X					
CAP Library State					X					
CAP Physical Address					X					
CAP SNMP Traps					X					
Clean Volume Serial Number								X		
Cleaning Media			X	X			X			
Cleans			X							
Complex Physical Library Count	X									
Component ID						X				
Cumulative Library Uptime		X								
Current Cleaning Uses							X	X		
Data Compression Ratio			X	X			X			
Date Created/Updated						X				
Destination HLI Address							X			
Destination Library Number							X			
Destination Physical Address							X			
Destination Rail Number							X			
Destination SCSI Element ID							X			
Device Activity										X
Device Address										X
Device ID										X
Device Serial Number										X
Device State										X
Device Time										X
Dismounts	X	X								
Dismounts With Errors				X						
Drive			X							
Drive Alert Count			X							
Drive Bays Installed	X	X								
Drive Bays Occupied	X	X								
Drive Bays Unoccupied	X	X								
Drive Cleans	X	X								
Drive Dismounts			X							
Drive Errors			X							
Drive Exchange Status			X				X	X		
Drive Firmware Version			X				X			
Drive Health Indicator			X	X			X	X		
Drive Health Trend			X				X			
Drive HLI Address			X				X			
Drive Interface			X							
Drive Library Name			X				X			

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
Drive Library Number			X				X			
Drive Library Serial Number			X				X			
Drive Lifetime Cleans			X				X	X		
Drive Lifetime Hours in Motion			X				X			
Drive Lifetime Loads			X				X	X		
Drive Lifetime Meters			X				X	X		
Drive Lifetime Meters of Head Contact							X			
Drive Lifetime Meters Positioning							X			
Drive Lifetime Power Hours			X				X			
Drive Manufacturer			X							
Drive Model			X				X		X	
Drive Physical Address			X				X			
Drive Properties Updated			X							
Drive Rail Number			X				X			
Drive SCSI Element ID			X				X			
Drive Serial Number			X	X		X	X	X	X	X
Drive SNMP Trap Count			X							
Drive Start Tracking							X	X		
Drive Stop Tracking							X	X		
Drive Suspicion Level			X				X			
Drive Tray Serial Number			X				X			
Drive Type			X	X			X	X		X
Drive Vendor										X
Drive WWNN			X	X			X	X		
Drive WWPN (Port A)			X					X		
Drive WWPN (Port B)			X					X		
Duplicate Detected				X			X			
Elevator					X					
Elevator Alert Count					X					
Elevator Count	X	X								
Elevator Identifier					X					
Elevator Library Health					X					
Elevator Library State					X					
Elevator Physical Address					X					
Elevator Power LED State					X					
Elevator SNMP Traps					X					
Encryption Capable			X							
Exchange Drive Cleaning Required			X	X			X	X		
Exchange DSC			X	X			X		X	

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
Exchange Elapsed Time			X	X			X	X		
Exchange Encryption Used			X	X			X			
Exchange End							X	X		
Exchange FSC			X	X			X	X	X	
Exchange Mount Time			X	X			X	X		
Exchange Read Margin			X	X						
Exchange Read Marginal			X	X			X			
Exchange Recording Technique			X	X			X		X	
Exchange Start			X				X	X	X	
Exchange Tape Alerts – Info			X	X			X			
Exchange Tape Alerts – Severe			X	X			X			
Exchange Tape Alerts – Warning			X	X			X			
Exchange Write Efficiency			X	X						
Exchange Write Inefficient			X	X			X			
Formatted Density Code							X			
Host DB Sync Errors	X	X								
Host Request Timeouts	X	X								
HP Device Status			X				X			
HP Media Status				X			X			
IBM Drive Efficiency			X				X			
IBM Media Efficiency			X	X			X			
Interface Name										X
Last Drive Message			X							
Last Exchange Start				X						
Library		X								
Library Alert Count		X								
Library Complex	X									
Library Complex Alert Count	X									
Library Complex Name	X	X	X	X	X	X	X	X	X	X
Library Complex Number	X									X
Library Firmware Updated		X								
Library Firmware Version		X								
Library IP address #1		X								
Library IP address #2		X								
Library Last Booted		X								
Library Model		X	X	X	X		X	X	X	X
Library Name		X			X	X		X		X
Library Number		X								
Library Scan Completed		X								
Library Serial Number		X			X	X		X		X

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
Library SNMP Traps		X								
Library Top Level Condition										X
Library Top Level Indicator		X								
Library WWNN		X						X		
Lifetime Hours Incompatible							X			
Logical Group(s)			X	X						
MB R/W	X	X	X	X						
MB Read	X	X	X	X						
MB Received	X	X	X	X						
MB Sent	X	X	X	X						
MB Write	X	X	X	X						
Media				X						
Media Alert Count				X						
Media Auxiliary Memory Capacity				X			X			
Media Blank				X			X			
Media Capacity Utilization				X						
Media Dismounts				X						
Media Ejected from Library				X						
Media Entered Library				X						
Media EOL Percentage				X						
Media Exchange Status				X			X	X		
Media Health Indicator			X	X			X	X		
Media Health Trend			X	X			X			
Media HLI Address				X						
Media Length in Meters				X			X			
Media Library Name				X					X	
Media Library Number				X						
Media Library Serial Number				X					X	
Media Life Indicator				X						
Media Long Type				X						
Media Manufacturer Date				X			X			
Media Manufacturer Serial Number			X	X			X			
Media MB Avail Post				X			X			
Media MB Avail Pre				X			X			
Media MB Capacity				X			X			
Media Physical Address				X						
Media Rail Number				X						
Media Slot SCSI Element ID				X						
Media Slots Activated	X	X								
Media Slots Installed	X	X								

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
Media Slots Occupied	X	X								
Media Slots Unoccupied	X	X								
Media Start Tracking							X			
Media Stop Tracking							X			
Media Suspicion Level				X			X			
Media Type				X			X		X	
Media Write Efficiency				X			X			
Meters Between 2 Most Recent Cleans			X					X		
Meters since Last Clean			X							
Monitored since	X	X	X	X	X					
Mount R/W MB							X			
Mount R/W MB/sec			X	X			X			
Mount Read MB							X			
Mount Read MB/sec							X			
Mount Received MB							X			
Mount Sent MB							X			
Mount Write MB							X			
Mount Write MB/sec							X			
MV Calibration Attempts			X							
MV Calibration Current State				X						
MV Calibration Drive SN				X						
MV Calibration Drive Type				X						
MV Calibration Information			X							
MV Calibration Initial DQI				X						
MV Calibration Initial Suspicion				X						
MV Calibration Last DQI				X						
MV Calibration Library Complex				X						
MV Calibration Library Model				X						
MV Calibration Library SN				X						
MV Calibration Number of Wraps				X						
MV Calibration Request									X	
MV Calibration Starting Suspicion			X							
MV Calibration State			X							
MV Calibration Status Information				X						
MV Count				X						
MV Days Since Last Validation				X						
MV DQI				X					X	

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
MV Drive Allocated			X							
MV Drive Available			X							X
MV Drive Capable			X							
MV Drive In Use			X							X
MV Drive Last Calibrated			X							
MV Drive Reserved			X							
MV Estimated Time Remaining									X	
MV Incomplete									X	
MV Initiator									X	
MV Interrupted									X	
MV Last Calibration Date				X						
MV Last Calibration DQI			X							
MV Last Exchange Start										
MV Last Recommendation			X	X						
MV Last Recording Technique				X						
MV Last Activity			X	X						
MV Last State Update									X	
MV Last Test Type				X						
MV Library Error									X	
MV MB Tape Used				X						
MV Policy Name									X	
MV Primary Calibration Media				X						
MV Primary Qualification Start			X							
MV Priority Order									X	
MV Recommendation									X	
MV Request Start									X	
MV Request State									X	
MV Result									X	
MV Secondary Qualification Start			X							
MV Status Information									X	
MV Test Percentage							X		X	
MV Test Type							X		X	
MV Time Spent Validating									X	
New Property Effective										X
New Property Value										X
Partition Name			X	X			X			
Partition Number			X	X			X			
Partition Type			X	X			X			
Partitions	X	X								

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
Perm Read Errors							X			
Perm Write Errors							X			
Permanent Error				X			X		X	
Port Speed (Port A)			X							
Port Speed (Port B)			X							
Property Name										X
PTP					X					
PTP Alert Count					X					
PTP Count	X	X								
PTP Ejects	X	X								
PTP Enters	X	X								
PTP Identifier					X					
PTP Library Health					X					
PTP Library State					X					
PTP Physical Address					X					
PTP Power LED State					X					
PTP SNMP Traps					X					
RQI							X			
R/W MB/sec			X	X			X			
R/W Mount Ratio			X	X			X			
Read Margin							X			
Read MB/sec			X	X			X			
Read Mount Ratio			X	X			X			
Received on										X
Recorded on							X	X		
Repositioning Cycles							X			
Repositioning Cycles Non ERP							X			
Request ID										X
Result Code										X
Robot					X					
Robot Alert Count					X					
Robot Count	X	X								
Robot Get Retries					X					
Robot Get Totals					X					
Robot Identifier					X					
Robot Library State					X					
Robot Physical Address					X					
Robot Power LED State					X					
Robot Put Retries					X					
Robot Put Totals					X					
Robot SNMP Traps					X					

Table 1–1 (Cont.) STA Attribute Cross-Reference

Attribute	Cmpx	Lib	Drive	Media	Lib Comp	Alerts	Exch	Clean	Media Valid	Msgs
Robot STA Health					X					
Robot Library Health					X					
Servo Perm Errors							X			
Severity										X
SNMP Trap										X
Source HLI Address							X			
Source Library Number							X			
Source Physical Address							X			
Source Rail Number							X			
Source SCSI Element ID							X			
STA Start Tracking			X	X						
STA Stop Tracking			X	X						
STA Supported				X						
Text										X
Theoretical Maximum Usage Count								X		
Time Spent Loaded							X			
Time Spent R/W							X			
Time Spent Reading			X	X			X			
Time Spent Reading or Writing			X	X						
Time Spent Writing			X	X			X			
Total Host Requests	X	X								
Trap Type										X
Unload Errors							X			
Usage Perm Errors							X			
Username										X
Volume Serial Number			X	X		X	X		X	
WORM/VolSafe Media			X	X						
Write Efficiency							X			
Write MB/sec			X	X			X			
Write Mount Ratio			X	X			X			

Attribute Definitions

Click a link below to go directly to the section.

Section	Section
"Symbols" on page 2-1	"M" on page 2-28
"A" on page 2-1	"MV" on page 2-36
"B" on page 2-9	"N" on page 2-41
"C" on page 2-9	"P" on page 2-41
"D" on page 2-11	"R" on page 2-43
"E" on page 2-21	"S" on page 2-46
"F" on page 2-24	"T" on page 2-48
"H" on page 2-24	"U" on page 2-49
"I" on page 2-24	"W" on page 2-50
"L" on page 2-25	

Symbols

% Drive Utilization

Percentage of time all drives in the library were occupied. Does not include time drives are not available because of application reservation or library positioning.

A

Agent Boot Date/Time

Date and time the SNMP agent was started, in the library's local time.

Alert Event Type

Type of event or activity that was in process when the alert was triggered.

Options are as follows:

- AppMonitor – The alert was triggered during a restart of the STA application. This event type is not a selectable link.
- Exchange – The alert was triggered during an exchange. Click the link to navigate to the Exchanges Overview screen displaying detail about the exchange.
- MIB Walk – The alert was triggered during a Get Latest Data performed from the Configuration – SNMP Connections screen. This event type is not a selectable link.

- Robot Analytic – The alert was triggered by a change in robot health. This event type is not a selectable link.
- Trap – The alert was triggered by an SNMP trap from the library. Click the link to navigate to the All Messages – Overview screen displaying detail about the trap.
- blank – Either the alert was triggered by an internal STA calculation, or the triggering event is unknown. In either case, there is no detail to display.

Alert Policy Name

User-defined name assigned to the alert policy.

Alert Policy Type

Type of alert policy. Examples are: STA, Complex, MDV, Media, Move, Robot.

Alert Reason

Criteria of the alert policy that generated this alert.

Alert Severity

Severity level of the alert policy that generated this alert. Options are: Severe, Warning, Informative. The severity level of a policy determines how often alerts are triggered.

Alert State

Current state of the alert. Options are: New, Acknowledged, In-progress, Dismissed, Unknown. "New" and "Unknown" states are assigned by STA. All other states are user-assigned according to the optional alerts workflow implemented at your site.

Alert: Cleaning Media

LTO only

Cleaning media has been loaded in the drive.

Alert: Drive Automated Interface

LTO only

The drive has experienced an Automation Interface fault.

Alert: Drive Clean Now

Both enterprise and LTO

A media error has caused a cleaning request.

Alert: Drive Clean Periodic Requested

Both enterprise and LTO

A clean threshold has been exceeded. Set when a StorageTek enterprise or IBM LTO drive detects that it needs routine cleaning.

Alert: Drive Cooling Fan

LTO only

The drive has detected that a cooling fan is not operating within manufacturer-specified limits.

Alert: Drive Diagnostics Required

LTO only

A failure requiring diagnostics has occurred. Triggered by a tape alert 39. This alert is reset after diagnostics are run.

Alert: Drive Dual-Port Interface

LTO only

A redundant interface port on the drive has failed.

Alert: Drive Dump Available

Enterprise only

A drive dump created earlier is available. This alert is reset after the dump is downloaded.

Alert: Drive Event Log Near Full

Enterprise only

The drive event log is 75 percent or more full. This is an expected state, as the log is circular. Events may be overwritten unless they are collected. If Oracle Service Delivery Platform (SDP) is installed, the logs are cleared.

Alert: Drive Failure Predicted

Both enterprise and LTO

The drive firmware has predicted a drive hardware failure.

Alert: Drive FW Download

LTO only

A drive firmware download has failed because an invalid firmware file was used for this drive type.

Alert: Drive FW Failure

Both enterprise and LTO

The drive has detected a firmware fault and has reset itself. This alert remains active until all dumps are retrieved from the drive.

Retrieve the drive dumps.

Alert: Drive Hard Error

LTO only

Indicates an unrecoverable read, write, or positioning error. This alert is cleared internally when the media is ejected.

Check the following alerts for additional detail: Media Error, Read Failure, Write Failure.

Alert: Drive Hardware A

LTO only

The drive has experienced a hardware fault from which it can recover through a reset.

Alert: Drive Hardware B

LTO only

The drive has experienced a hardware fault from which it can recover through a power cycle. This alert is set if the tape drive fails its internal power-on self-tests and is cleared internally when the drive is powered off.

Alert: Drive Interface Fault

LTO only

The drive has experienced a problem with the host interface. Check cables and connections and restart the operation.

Alert: Drive Load Limit

Both enterprise and LTO

Indicates whether the drive exceeded its lifetime limit of media loads at the time of the exchange.

Alert: Drive Model Incompatible

Enterprise only

The drive is down-level for the media attempting to be loaded.

Alert: Drive Temperature

Both enterprise and LTO

The drive has experienced a cooling problem. This could impact media integrity.

Alert: Drive Voltage

LTO only

Drive voltage limit has been exceeded

Alert: Forced Eject Attempted

LTO only

A manual or forced eject occurred while the drive was reading or writing.

Alert: Invalid Cleaning

LTO only

The cleaning media is incompatible with the drive.

Alert: Media Cart Memory Failure

Indicates the cartridge memory failed during the exchange. This results in reduced performance.

Alert: Media Clean Expired

Both Enterprise and LTO

The drive firmware has determined that the cleaning media has already been used the maximum number of times and cannot be used for this cleaning exchange.

Alert: Media Diminished Capacity

LTO only

The volume state has been set not to allow partition 0 to use the full native capacity of the volume. For example, the volume is partitioned, or the available medium for use has been reduced by a SET CAPACITY command.

Alert: Media Directory Corrupt

Both Enterprise and LTO

The media directory on the tape media is corrupted, leading to degraded file search performance until the directory is rebuilt. This has occurred because the drive was powered down with media loaded, or a permanent error prevented the media directory from being updated.

Alert: Media Directory Invalid

Both Enterprise and LTO

The media directory has been corrupted. No data was lost, but media performance could be impacted.

The media directory can be rebuilt by reading all the data.

Alert: Media Eject Failed

LTO only

The eject operation has failed.

Eject the media, reload, and restart the operation.

Alert: Media End of Warranty

Enterprise only

The media has reached the end of its warranty period, and further use is not covered by warranty.

Alert: Media Error

Both enterprise and LTO

Media performance is severely degraded, or the media can no longer be read or written. This alert is set for any unrecoverable read, write, or positioning error caused by faulty media and is cleared internally when the media is ejected.

Alert: Media Life Exceeded

Both enterprise and LTO

The media has exceeded its expected useful life. Available for IBM LTO4 and above drives only.

Note: HP drives report the Nearing Media Life Alert attribute instead.

Alert: Media Load Limit

Both

The media has exceeded the recommended number of drive loads.

Alert: Media Loading Failure

Both

The drive was unable to load the media and thread the tape.

Alert: Media Lost Statistics

Both

Some previously existing media statistics have been lost due to a drive or library being powered down with media loaded.

Alert: Media Maintenance

Enterprise only

Media in the drive requires physical maintenance, which must be corrected before the cartridge can be loaded successfully. For example, the leader may be pulled into the cartridge.

Alert: Media Nearing End of Life

The media is approaching the end of its expected useful life. Available for HP drives only.

Alert: Media No Start of Data

Both

Start of customer data could not be found

Alert: Media Not Data Grade

LTO only

The drive has not been able to read the media recognition system stripes, indicating the media is not data-grade. Any data you write to the media is at risk.

Alert: Media Recoverable Mechanical

LTO only

The tape has snapped or suffered a mechanical failure in the drive, but the media can still be ejected.

Alert: Media RFID Warning

Enterprise only

The media RFID was found to be open at load time, indicating the drive was powered off before the media was unloaded on the previous mount. Results in degraded media performance. Writing is not allowed until End of Data is found.

Alert: Media System Read Failure

Both

The system area on the media could not be read from at load time. No data was lost, but media performance could be impacted.

Alert: Media System Write Failure

Both

The system area on the media could not be written to at unload. No data was lost, but media performance could be impacted.

Monitor the drive and media. If this error persists across multiple media, service the drive.

Alert: Media Unrecoverable Mechanical

LTO only

The tape has snapped or suffered a mechanical failure in the drive and cannot be extracted. Do not attempt to eject the media.

Alert: Media Unrecoverable Snapped

Enterprise only

The tape has snapped in the drive and cannot be extracted. Do not attempt to eject the media.

Alert: MIR Invalid

Enterprise only

The media information record (MIR) was not updated sometime in the past, resulting in degraded file search performance.

The MIR can be rebuilt by reading all the data.

Alert: Permanent Error

Enterprise only

A permanent media error occurred while the media was mounted. Check the exchange FSC or DSC for more information.

Alert: Read Failure

LTO only

Read has failed. The media is damaged or the drive is faulty.

Alert: Read Only

LTO only

Media of this type is read-only in this drive. The media appears as write-protected.

Alert: Read Warning

Both

The drive has experienced severe trouble reading from the media.

The media or drive require attention.

Alert: Unload Prevented

LTO only

The media cannot be ejected because the drive is in use.

Wait until the operation has completed before ejecting the media.

Alert: Unrecoverable Unload

LTO only

The drive reached the maximum number of unload retries and was unable to unload the media.

Alert: Unsupported Format

LTO only

Media of this type is not supported in this drive.

Alert: WORM Integrity Failure

LTO only

The drive has detected an inconsistency during the WORM volume integrity checks. The media may have been tampered with.

Alert: WORM Overwrite Attempted

LTO only

An attempt was made to overwrite user data on a WORM volume.

Alert: Write Failure

LTO only

The drive was unable to write data to the media. This alert is set for any unrecoverable write/positioning error, due to either faulty media or faulty drive hardware. The alert is cleared internally when the tape is ejected.

Alert: Write Protect

LTO only

A write command was attempted to write-protected media.

Alert: Write Warning

Both

The drive has experienced severe trouble writing to the media.

The media or drive require attention.

Annotation History

User-defined annotation assigned to the library resource or activity. List View shows the most recent annotation. Detail View shows full annotation history, in reverse chronological order.

Avg Mount R/W MB

Average megabytes read and written by the drive per exchange. Calculated as:

`total MB (read +written) /total completed exchanges`

Avg Mount R/W MB/sec

Average throughput rate for the drive, in megabytes per second. Calculated as:

`total MB (read +written) /total seconds mount time`

Note: This value may be affected by a variety of factors external to the drive, such as robot speed or application behavior—for example, some applications do not dismount media immediately upon completion of read/write operations, causing the drive to be idle for much of the mount. As a result, this value is not likely to represent the drive's maximum potential throughput rate.

Avg Mount Read MB

Average megabytes read by the drive per exchange. Calculated as:

`total MB read /total completed exchanges`

Avg Mount Read MB/sec

Average read rate for the drive, in megabytes per second. Calculated as:

`total MB read /total seconds mount time`

Note: This value may be affected by a variety of factors external to the drive, such as robot speed or application behavior—for example, some applications do not dismount media immediately upon completion of read/write operations, causing the drive to be idle for much of the mount. As a result, this value is not likely to represent the drive's maximum potential read rate.

Avg Mount Write MB

Average megabytes written by the drive per exchange. Calculated as:

`total MB written /total completed exchanges`

Avg Mount Write MB/sec

Average write rate for the drive, in megabytes per second. Calculated as:

`total MB written /total seconds mount time`

Note: This value may be affected by a variety of factors external to the drive, such as robot speed or application behavior—for example, some applications do not dismount media immediately upon completion of read/write operations, causing the drive to be idle for much of the mount. As a result, this value is not likely to represent the drive's maximum potential write rate.

B

Base Model

Library model.

C

CAP

Serial number of the CAP

CAP Accessibility

Current CAP accessibility state, as reported by the library. Options are: ALLOW, CLOSED ALLOW, PREVENT, CLOSED PREVENT.

CAP Alert Count

Total alerts generated for this CAP, AEM, or mailslot, based on defined STA alert policies

Note: This field links to the Alerts Overview screen, list view, which lists alerts for this CAP. See "[Alerts Screens](#)" on page 11-1.

CAP Count

Total CAPs, AEMs (SL3000 only), and mailslots (SL150 only)

CAP Ejects

For Complexes Overview and Libraries Overview: Total media ejected from the library or complex through all CAPs, AEMs (SL3000 only), and mailslots (SL150 only).

For CAPs Overview: Total media ejected through the CAP

CAP Enters

For Complexes Overview and Libraries Overview: Total media entered into the complex through all CAPs, AEMs (SL3000 only), and mailslots (SL150 only)

For CAPs Overview: Total media entered through the CAP

CAP Library Health

Current health of the CAP as reported by the library. Options are: DEGRADED, NORMAL, NOTOPERATIVE, UNKNOWN.

CAP Library State

Current CAP state, as reported by the library. Options are: OPEN or CLOSED. STA updates this value hourly. Additionally for SL3000 and SL8500 libraries, the value is updated as SNMP traps for the CAP are received from the library.

CAP Physical Address

Library internal address.

For SL150 libraries, the format is m,s,w,c (for example, 1,Left,1,2), where:

- m =module number; 1–10, from top (base module) to bottom
- s =side; Left or Right
- w =row number; 1–3, from top to bottom
- c =column number; 1–5, from front to back

For SL500 libraries, the format is l,m,r,c (for example, 0,2,2,3), where:

- l =for nonpartitioned libraries, this is the library ID (always 0); for partitioned libraries, this is the partition ID (1–8).
- m =module number; 1–5, from top to bottom of the rack
- r =drive row number; 1–2 (Base Module) or 1–4 (Drive Expansion Module), from top to bottom of the module
- c =column number; always 9 for drives

For SL3000 and SL8500 libraries, the format is l,r,c,s,w (for example, 1,1,2,2,3), where:

- l =library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).
- r =rail number. For SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.
- c =column number.
- s =side number.
- w =row number.

CAP Identifier

Unique identifier for the CAP

CAP SNMP Traps

Total CAP messages received from the library. A sudden increase in this number indicates a condition that should be investigated.

Clean Volume Serial Number

Volume serial number (VSN or volser) assigned to the media by its external label. If the library does not supply the volser, STA provides one composed of Library Serial Number:Physical Address.

Note: Not all cleaning media have a volser starting with "CLN".

Note: This field links to the Media – Overview screen, detail view, which displays all available detail for this media. See "[Media Overview and Analysis Screens](#)" on page 6-1.

Cleaning Media

For Drives Overview: Indicates whether cleaning media has been loaded in the drive.

For Media Overview and Exchanges Overview: Indicates whether this is a cleaning media, as determined by the media domain and type. Possible values: True or False.

Note: Not all cleaning media have a volser starting with "CLN".

Cleans

Total cleaning operations performed.

Note: This field links to the Drives – Cleaning Activities screen, list view, which lists this drive's cleaning activities. See "[Drive Cleanings Overview Screen](#)" on page 13-1.

Complex Physical Library Count

Total libraries in the complex (always "1" for non-SL8500 libraries).

Note: This field links to the Libraries – Overview screen, list view, which lists all libraries in this complex. See "[Libraries Overview Screen](#)" on page 4-1.

Component ID

Unique identifier for the resource involved in the alert. The type of ID depends on the alert. For example, a volume serial number (for media), drive serial number (for drives), library serial number (for libraries).

Cumulative Library Uptime

Total time the library has been running since the last reboot. Displayed as hh:mm:ss.

Current Cleaning Uses

Total times the cleaning media has been mounted in a drive. Some media types track this count, in which case, this value is as reported by the media itself. Other media types do not track this count, in which case, this value is as recorded by STA. Since the cleaning media may have been used prior to the start of STA monitoring, STA may not have exchange records for all drive cleanings done with the media.

D

Data Compression Ratio

Compression ratio for the exchange. Displayed as ratio, calculated as:

(Total uncompressed data sent or received by the drive / Total compressed data read or written to the media) :1

Date Created/Updated

Date and time when the alert was triggered.

Destination HLI Address

Host Library Interface (HLI) address of the location. Applies only to drives or media slots in HLI partitions or libraries. This address is assigned by the ACSLS or ELS host software.

Note: Available only for SL8500 libraries with firmware FRS_7.80 or higher or SL3000 libraries with firmware FRS_4.0 or higher. For all others, the value is left blank.

For media slots, format is l,p,w,c, where:

- l=logical storage manager (LSM) number. Possible values are 0, 1, 2, or 3.
- p=panel number.
- r=row number.
- c=column number.

For drives, format is l,p,t, where:

- l=logical storage manager (LSM) number. Possible values are 0, 1, 2, or 3.
- p=panel number
- t=transport number

Destination Library Number

Unique ID assigned to the library.

Destination Rail Number

Rail number. For SL150, SL500, and SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.

Destination Physical Address

Library internal address.

For SL150 libraries, the format is m,s,w,c (for example, 1,Left,1,2), where:

- m=module number; 1–10, from top (base module) to bottom
- s=side; Left or Right
- w=row number; 1–3, from top to bottom
- c=column number; 1–5, from front to back

For SL500 libraries, the format is l,m,r,c (for example, 0,2,2,3), where:

- l=for nonpartitioned libraries, this is the library ID (always 0); for partitioned libraries, this is the partition ID (1–8).
- m=module number; 1–5, from top to bottom of the rack
- r=drive row number; 1–2 (Base Module) or 1–4 (Drive Expansion Module), from top to bottom of the module
- c=column number; always 9 for drives

For SL3000 and SL8500 libraries, the format is l,r,c,s,w (for example, 1,1,2,2,3), where:

- l=library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).
- r=rail number. For SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.
- c=column number.
- s=side number.

- w=row number.

Destination SCSI Element ID

SCSI element ID of the destination location. Applies only to drives and media slots in SCSI partitions or libraries. See the applicable library *User's Guide* for details on how SCSI IDs are assigned.

A value of "-1" indicates the location is not a SCSI slot. For example, it may be in a SL8500 library, an HLI partition in a SL3000 library, or a slot not allocated to a partition in a partitioned library.

Device Activity

Internal library functionality that is producing the message. For example, "AuditDaemon" indicates logging information from the library audit function.

Device Address

Library internal address of the device associated with the SNMP trap.

For SL150 libraries, the format is m,s,w,c (for example, 1,Left,1,2), where:

- m=module number; 1–10, from top (base module) to bottom
- s=side; Left or Right
- w=row number; 1–3, from top to bottom
- c=column number; 1–5, from front to back

For SL500 libraries, the format is l,m,r,c (for example, 0,2,2,3), where:

- l=for nonpartitioned libraries, this is the library ID (always 0); for partitioned libraries, this is the partition ID (1–8).
- m=module number; 1–5, from top to bottom of the rack
- r=drive row number; 1–2 (Base Module) or 1–4 (Drive Expansion Module), from top to bottom of the module
- c=column number; always 9 for drives

For SL3000 and SL8500 libraries, the format is l,r,c,s,w (for example, 1,1,2,2,3), where:

- l=library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).
- r=rail number. For SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.
- c=column number.
- s=side number.
- w=row number.

Device ID

FRU ID of the device associated with the event.

Device Serial Number

Serial number or other unique identifier of the device associated with the event.

Device State

State of the device at the time the trap was sent. Varies by device type, as in the following examples:

- Drives – EMPTY, LOADED, NEEDS_CLEANING

- CAPs – OPEN, CLOSE, UNKNOWN
- Pass-thru ports (PTPs) – OK, ERROR, WARNING, INFO, TRACE

Device Time

Date and time of the event, in UTC standard format.

Dismounts

Total dismounts for all drives.

Note: This field links to the Libraries – Exchanges screen, list view, which lists exchanges for this library. See "[Exchanges Overview Screen](#)" on page 12-1.

Dismounts With Errors

Total dismounts with drive or media errors involving this media.

Note: This field links to the Libraries – Exchanges screen, list view, which lists this cartridge's exchanges with errors. See "[Exchanges Overview Screen](#)" on page 12-1.

Drive

Electronic serial number of the drive. *NO-SERIAL* indicates it is not known.

Note: This field links to the Drives – Overview screen, detail view, which displays all available details for this drive. See "Drives Overview and Analysis Screens".

Drive Alert Count

Total alerts generated for this drive, based on defined STA alert policies

Note: This field links to the Alerts Overview screen, list view, which lists alerts for this drive. See "[Alerts Screens](#)" on page 11-1.

Drive Bays Installed

Total drive slots installed but not necessarily activated for use. Calculated as:

Drive Slots Occupied + Drives Slots Unoccupied.

Drive Bays Occupied

Total drive slots with drives installed.

Note: This field links to the Drives – Overview screen, list view, which lists all drives for this complex. See "[Drives Overview and Analysis Screens](#)" on page 5-1.

Drive Bays Unoccupied

Total drive slots with no drives installed.

Drive Cleans

Total drive cleans performed.

Note: This field links to the Drives – Cleaning Activities screen, list view, which lists cleaning activities for this library. See "[Drive Cleanings Overview Screen](#)" on page 13-1.

Drive Dismounts

Total times media have been unloaded from this drive.

Note: This field links to the Libraries – Exchanges screen, list view, which lists this drive's exchanges. See "[Exchanges Overview Screen](#)" on page 12-1.

Drive Errors

Total drive errors recorded.

Note: This field links to the Libraries – Exchanges screen, list view, which lists this drive's exchanges with errors. See "[Exchanges Overview Screen](#)" on page 12-1.

Drive Exchange Status

Status of the drive upon completion of the exchange, as derived from a variety of factors, including drive errors, write efficiency, and read margin. Possible values:

- CART_MEM_FAILURE
- CLEAN_REQ – The drive is due for cleaning.
- DRIVE_ERROR
- EXPIRED_CLEAN_TAPE
- FAILED_MOUNT
- FW_DOWN_LEVEL
- GOOD
- INCOMPLETE_UNLOAD – The application requested that the media be unloaded. The tape drive has detected data still in its buffer and has asked for confirmation from the application.
- INSUFFICIENT_DATA(NULL) – STA has not received enough exchange data from the library to calculate drive health. It may be that the drive is not supported (LTO 2, for example) or the library firmware is downlevel.
- LOAD_ERROR
- LTO_NON_ADI_MODE –ADI mode has not been enabled on either the library, the drive, or both.
- MEDIA_ERROR
- NON_DRV_ERROR – This is neither a drive nor a media problem, so there is no effect on the suspicion of drive or media. If this exchange status is set, check the following for additional information which may help in determining the cause:

For Enterprise drives, check the exchange fault symptom code (FSC). For LTO drives, check tape alerts that have been set recently.

This status may be set at the following times:

* A Media Write Protect Tape Alert must be set. The host application is attempting to write to media that has been write protected.

* FSC 6142 has been set for a T10000B exchange. This code indicates there were difficulties obtaining an Oracle Key Manager (OKM) encryption key. This can be attributed to several scenarios, such as compromised network connectivity, the OKM has crashed, or the drive enrollment has expired and the drive must be re-enrolled. The drive may be used to read un-encrypted tapes until the OKM comes back online and starts to serve keys again.

* FSC has been set to 3627, 3629, 362A, or 362B. These FSC codes are set during a "normal operation," which checks that a piece of media is truly blank before labeling it. The host application will perform the following sequence: 1) mount new tape; 2) attempt to check for no label; 3) label the new tape.

- OTHER_ERROR
- PERM_ERROR
- READ_ERROR
- WRITE_ERROR
- UNKNOWN
- UNLOAD_ERROR

Drive Firmware Version

Drive firmware and host interface level. See the *STA Requirements Guide* for details on whether this firmware version supports rich data for STA.

Drive Health Indicator

Drive health. This is a point-in-time value computed by STA analytics based on data gathered from the drive during current and past exchanges. It reflects a variety of factors, such as the drive's error history, read margin, and write efficiency.

This value includes all data up to and including the last completed exchange. It is updated immediately after each completed exchange involving the drive.

Possible values, in order of degrading health:

- USE – The drive has had no failures or degradation in the last ten exchanges
- MONITOR – The drive has had multiple errors; there is a less than 80 percent chance that it needs service.
- EVALUATE – The drive has had multiple errors; there is a greater than 80 percent chance that it needs service.
- ACTION – The drive has had an error that requires attention. The drive may require service. You should investigate and determine a proper course of action.
- UNKNOWN – STA has not received enough data to compute health for the drive. This may be due to a variety of factors, including an unsupported drive model, downlevel drive firmware, or ADI mode not enabled for an LTO drive.

Note: STA only receives information about errors detected by a drive while performing read/write activity to a cartridge. STA does not receive information about errors that may occur in the data path or the host application.

Note: Cleaning exchanges have a neutral impact on drive health.

Drive Health Trend

Trend of drive health between the last two exchanges, as computed by STA analytics. Options are: BETTER, UNCHANGED, WORSE.

Drive HLI Address

Host Library Interface (HLI) address of the location. Applies only to drives or media slots in HLI partitions or libraries. This address is assigned by the ACSLS or ELS host software.

Note: Available only for SL8500 libraries with firmware FRS_7.80 or higher or SL3000 libraries with firmware FRS_4.0 or higher. For all others, the value is left blank.

For media slots, format is l,p,w,c, where:

- l =logical storage manager (LSM) number. Possible values are 0, 1, 2, or 3.
- p =panel number.
- r =row number.
- c =column number.

For drives, format is l,p,t, where:

- l =logical storage manager (LSM) number. Possible values are 0, 1, 2, or 3.
- p =panel number
- t =transport number

Drive Interface

Host interface type for the drive. Possible values:

- SAS – Serial Attached SCSI
- SCSI – Small Computer System Interface
- FIBRE – Fibre channel
- UNKNOWN – The library did not report the interface type.

Drive Library Name

User-assigned name for the library. Assigned in the Settings – SNMP Connections screen.

Drive Library Number

Unique ID assigned to the library.

Drive Library Serial Number

Library frame serial number.

Note: This field links to the Libraries – Overview screen, detail view, which displays all available details for this library. See "[Libraries Overview Screen](#)" on page 4-1.

Drive Lifetime Cleans

Total cleans performed on the drive over its life.

Note: The drive life may be longer than the time it has been monitored by STA.

Drive Lifetime Hours in Motion

Total hours the drive heads have been in motion over the life of the drive.

Note: The drive life may be longer than the time it has been monitored by STA.

Drive Lifetime Loads

Total media loads for the drive over its life. Available for all drive types but LTO3.

Note: The drive life may be longer than the amount of time it has been monitored by STA.

Drive Lifetime Meters

Total meters of tape that have passed through the drive heads over the drive's life. Available for all drive types but LTO3.

Note: The drive life may be longer than the amount of time it has been monitored by STA.

Drive Lifetime Meters of Head Contact

Total meters of media passed through the drive heads over the life of the drive.

Drive Lifetime Meters Positioning

Total positioning meters of media passed at high speed through the drive heads over the life of the drive. Positioning meters occur during locate, rewind, and spacing operations.

Drive Lifetime Power Hours

Total hours the drive has been powered on over its life.

Note: The drive life may be longer than the amount of time it has been monitored by STA.

Drive Manufacturer

Drive manufacturer.

For example, STK, IBM, QUANTUM, and so on.

Drive Model

Drive model short description. For example, T10000C, LTO4, and so on. UNKNOWN indicates a broken drive or a drive for which STA cannot determine the type.

Note: Type is UNKNOWN for all DLT and SDLT drives, for which STA does not compute health.

Drive Physical Address

Library internal address for the drive.

For SL150 libraries, the format is m,p (for example, Module 1,Bottom Drive), where:

- m =module number; 1–10, from top (base module) to bottom
- p =position; Top Drive or Bottom Drive

For SL500 libraries, the format is l,m,r,c (for example, 0,2,2,3), where:

- l =for nonpartitioned libraries, this is the library ID (always 0); for partitioned libraries, this is the partition ID (1–8).
- m =module number; 1–5, from top to bottom of the rack
- r =drive row number; 1–2 (Base Module) or 1–4 (Drive Expansion Module), from top to bottom of the module
- c =column number; always 9 for drives

For SL3000 and SL8500 libraries, the format is l,r,c,s,w, where:

- l =library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).
- r =rail number. For SL3000 libraries, this is always "1". For SL8500 libraries, this is the rail number (1–4).
- c =column number.
- s =side number.
- w =row number.

Drive Properties Updated

Date and time when the drive properties were last updated. Initially set to the date and time when STA first recognized the drive, and updated whenever subsequent updates occur, such as updating the drive firmware.

Drive Rail Number

Rail number. For SL150, SL500, and SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.

Drives used: Drives Overview, Exchanges Overview

Drive SCSI Element ID

SCSI element ID of the drive location. Applies only to drives in SCSI partitions or libraries. See the applicable library *User's Guide* for details on how SCSI IDs are assigned.

A value of "-1" indicates the drive is not in a SCSI slot. For example, it may be in a SL8500 library, an HLI partition in a SL3000 library, or a slot not allocated to a partition in a partitioned library.

Drive Serial Number

Electronic serial number of the drive. *NO-SERIAL* indicates it is not known.

Note: This field links to the Drives – Overview screen, detail view, which displays all available details for this drive. See "[Drives Overview and Analysis Screens](#)" on page 5-1.

Drive SNMP Trap Count

Total drive messages received from the library over the last 30 days. A sudden increase in this number indicates a condition that should be investigated.

Note: This field links to the Drives – Messages screen, list view, which lists SNMP traps for this drive. See "[Messages Screens](#)" on page 15-1.

Drive Start Tracking

Date and time when STA first began tracking this drive serial number.

Drive Stop Tracking

Date and time when STA stopped tracking this drive serial number. This is when STA determined the drive serial number no longer exists in any of the monitored libraries and updated the drive status from "missing" to "removed".

Drive Suspicion Level

Calculated suspicion level for the drive. Possible values: 0–100. Lower numbers are desirable. The higher the number, the higher the probability the drive needs attention.

Drive Tray Serial Number

Serial number of the drive tray, which must be entered manually by an Oracle support representative. Valid entries include alphanumeric characters only; no special characters are allowed. If the entry has not yet been entered, the value is "unknown."

This entry is referenced when a Service Request is submitted.

Drive Type

Drive type long description sent by the library. For example, T10000c-Enc, HpUltrium4, and so on. UNKNOWN indicates a broken drive or a drive for which STA cannot determine the type.

Note: Type is UNKNOWN for all DLT and SDLT drives, for which STA does not compute health.

Drive Vendor

Drive manufacturer

Drive WWNN

World Wide Node Name for the drive slot.

Drive WWPN (Port A)

World Wide Port Name for drive port A. This is automatically generated by the library controller during library initialization.

Drive WWPN (Port B)

World Wide Port Name for drive port B. This is automatically generated by the library controller during library initialization.

Duplicate Detected

STA has detected that the volume serial number (VSN or volser) of the media used in the exchange is a duplicate. This alert appears only on the exchange in which the duplicate is detected.

Duplicate volsers occur when two pieces of media with the same media type have the same volser and two different manufacturer serial numbers. If this alert appears multiple times for the same volser, it is likely there is more than one physical cartridge with the same media type and volser label in the tape environment. If it only appears once for the volser, it may be that the volser label from a retired cartridge has been re-used on a new cartridge.

E**Elevator**

Serial number of the elevator

Elevator Alert Count

Total alerts generated for this elevator, based on defined STA alert policies

Note: This field links to the Alerts Overview screen, list view, which lists alerts for this elevator. See "[Alerts Screens](#)" on page 11-1.

Elevator Count

Total elevators. Applies to SL8500 libraries only.

Elevator Library Health

Current health of the elevator as reported by the library. Options are: DEGRADED, NORMAL, NOTOPERATIVE, UNKNOWN.

Elevator Library State

Current elevator state, as reported by the library. Examples are: READY. STA updates this value hourly and as SNMP traps for the elevator are received from the library.

Elevator Physical Address

Library internal address.

For SL150 libraries, the format is m,s,w,c (for example, 1,Left,1,2), where:

- m =module number; 1–10, from top (base module) to bottom
- s =side; Left or Right
- w =row number; 1–3, from top to bottom
- c =column number; 1–5, from front to back

For SL500 libraries, the format is l,m,r,c (for example, 0,2,2,3), where:

- l =for nonpartitioned libraries, this is the library ID (always 0); for partitioned libraries, this is the partition ID (1–8).
- m =module number; 1–5, from top to bottom of the rack

- **r** =drive row number; 1–2 (Base Module) or 1–4 (Drive Expansion Module), from top to bottom of the module
- **c** =column number; always 9 for drives

For SL3000 and SL8500 libraries, the format is **l,r,c,s,w** (for example, 1,1,2,2,3), where:

- **l** =library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).
- **r** =rail number. For SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.
- **c** =column number.
- **s** =side number.
- **w** =row number.

Elevator Power LED State

Current state of the elevator power LED. Normal condition is ON. Options are: ON, OFF, or UNKNOWN.

Elevator Identifier

Unique identifier for the elevator

Elevator SNMP Traps

Total elevator messages received from the library. A sudden increase in this number indicates a condition that should be investigated.

Encryption Capable

Indicates whether the drive is capable of supporting encryption, but does not necessarily indicate that encryption has been enabled. Possible values are Yes or No.

Note: Additional hardware or software components may be necessary to actually enable encryption on the drive. For example HP LTO-4 drives require a Deoni card and IBM LTO-4 drives require a Belisarius card.

Exchange Drive Cleaning Required

Indicates whether the drive needed cleaning at the time of the exchange. Possible values: Yes or No.

Note: Additional detail may be available through the Clean Periodic Alert and Clean Now Alert attributes.

Exchange DSC

Data status code for the exchange. Available only for drives whose firmware supports TTI 5.40.

Exchange Elapsed Time

Total time the media is involved in the exchange, including transit time immediately before and after the mount. Starts at the beginning of the move to retrieve the media from a media slot and ends when the media is placed in the first available location after removal from the drive. For SL8500 libraries, the first available location after removal from the drive could be an elevator, but for all other libraries, it is always a media slot. Displayed in hh:mm:ss format.

Exchange Encryption Used

Encryption method used by the drive for the exchange. Available for StorageTek enterprise drives only. Possible values:

- Encrypted_ANSI_10 – ANSI encryption.
- Encrypted Sun KMS – Oracle Key Manager (OKM) encryption.
- Not Encrypted – Not encrypted.
- Unknown – The drive did not report encryption information.
- Blank (no value displayed) – STA did not receive any encryption information; the value is always blank for ADI/LTO exchanges.

Exchange End

Date and time when the exchange completed

Exchange FSC

Four-byte hexadecimal fault symptom code (FSC). For example, FD55, S053, and so on. Reported only if an error occurred during the exchange.

Exchange Library Name

User-assigned name for the library where the most recent exchange occurred. If the media has been ejected, you can use this value to determine the library from which the media was ejected. Enables reporting of library information if the media has been ejected.

Exchange Mount Time

Total time the media is mounted in the drive. Includes the total time between the start of the mount and the start of the dismount. Does not include transit time before and after the mount. Displayed in hh:mm:ss format.

If this attribute is blank, then it is likely that STA did not receive all the exchange data from the library.

Exchange Read Margin

Amount of error correction code (ECC) read margin remaining on the media, as reported by the drive during the last mount. Reported as a percentage. A high value is desirable. Available only for StorageTek T10000A and above drives.

If STA determines that this value has gone below a threshold for this drive type, the Exchange Read Marginal attribute is set to True.

Exchange Read Marginal

Indicates whether the drive met the read margin standard for the drive type. Possible values: True or False. Available only for StorageTek T10000A and above drives.

Exchange Recording Technique

Recording format used by the drive during the exchange or media validation. For Exchanges Overview, options include: T10000D, LTO5, and 9840B.

For Media Validation Overview, options are: T10000A, T10000B, T10000C, and T10000D only. T10000A and T10000B drives can write to T10000T1 media; T10000C and T10000D drives can write to T10000T2 media.

Exchange Start

Date and time when the drive was reserved for the exchange, cleaning activity, or media validation activity.

Note: This field links to the Libraries – Exchanges screen, detail view, which displays all available detail for this exchange. See "[Exchanges Overview Screen](#)" on page 12-1.

Exchange Tape Alerts – Info

Number of Informational tape alerts received in the exchange.

Exchange Tape Alerts – Severe

Number of Severe tape alerts received in the exchange.

Exchange Tape Alerts – Warning

Number of Warning tape alerts received in the exchange.

Exchange Write Efficiency

Write efficiency for the exchange, based on capacity over distance. Reported as a percentage. A high value is desirable. Available only for StorageTek T10000A and above drives.

Exchange Write Inefficient

Indicates whether the drive failed to meet the write efficiency standard for the drive type. Possible values: True or False. Available only for StorageTek T10000A and above drives.

F**Formatted Density Code**

Supported density for the drive, as reported by the SCSI Report Density Support command.

H**Host DB Sync Errors**

Total host database synchronization errors.

Host Request Timeouts

Total host requests that ended in timeouts.

HP Device Status

Four-byte hexadecimal code indicating the status of the drive. Available for HP drives only.

HP Media Status

Four-byte hexadecimal code indicating the status of the media. Available for HP media only.

I**IBM Drive Efficiency**

Three-byte hexadecimal code indicating the drive's efficiency over its life. Possible values are 01h (best) to FFh (worst); 00h indicates the efficiency is unknown. Available for IBM LTO4 and above drives only.

IBM Media Efficiency

Three-byte hexadecimal code indicating the media's efficiency over its life. Possible values are 01h (best) to FFh (worst); 00h indicates the efficiency is unknown. Available for IBM LTO4 and above drives only.

Interface Name

Interface type of the device associated with the event.

L

Last Drive Message

Condition of the drive as reported directly by the library. Updated whenever messages for the drive are received by STA from the library. Possible values:

- DEGRADED – The drive has experienced an error.
- NORMAL – The drive is functioning normally.
- NOTOPERATIVE – The library has lost communication with the drive, or the drive has experienced an error or mechanical failure.
- UNKNOWN – STA has not received any messages for the drive. This is the default value until the first message is received for the drive.

Last Exchange Start

Date and time when the drive was reserved for the most recent exchange.

Note: This field links to the Libraries – Exchanges Overview screen, detail view, which displays all available details for this exchange. See ["Exchanges Overview Screen"](#) on page 12-1.

Library

Library frame serial number.

Note: This field links to the Libraries – Overview screen, detail view, which displays all available details for this library. See ["Libraries Overview Screen"](#) on page 4-1.

Library Alert Count

Total alerts generated for this library, based on defined STA alert policies

Note: This field links to the Alerts Overview screen, list view, which lists alerts for this library. See ["Alerts Screens"](#) on page 11-1.

Library Complex

Name assigned to the complex by STA.

- For SL150, SL500, and SL3000 libraries, this value is formatted as library_model_library_serial_number. Examples: SL150_262960B+1234BA0018, SL500_522000001839, SL3000_571000020075
- For SL8500 libraries, this value is formatted as library_model_complex_ID. Examples: SL8500_1, SL8500_4

This field links to the Libraries – Complexes Overview screen, detail view, which displays all available details about this complex. See "Library Complexes Screen".

Library Complex Alert Count

Total alerts generated for this library complex, based on defined STA alert policies

Note: This field links to the Alerts Overview screen, list view, which lists alerts for this complex. See "[Alerts Screens](#)" on page 11-1.

Library Complex Name

Name assigned to the complex by STA.

- For SL150, SL500, and SL3000 libraries, this value is formatted as library_model_library_serial_number. Examples: SL150_262960B+1234BA0018, SL500_522000001839, SL3000_571000020075
- For SL8500 libraries, this value is formatted as library_model_complex_ID. Examples: SL8500_1, SL8500_4

Note: This field links to the Libraries – Complexes Overview screen, detail view, which displays all available details about this complex. See "[Complexes Overview Screen](#)" on page 3-1.

Library Complex Number

Library complex ID, as configured on the library. For SL150, SL500, and SL3000 libraries, the value is always "1". For SL8500 libraries, the value is set by your Oracle support representative and must be unique for each complex.

Library Firmware Updated

Date and time of last library firmware update.

Library Firmware Version

Current library firmware version.

Library IP address #1

IP address of the public port on the library. The attribute value is specified by the user or administrator when the library connection is configured. For SL150 libraries, it is the Network Port 1 port; for SL500 libraries, it is the 1B port; for SL3000 and SL8500 libraries, it is the 2B port.

Note: For SL3000 and SL8500 libraries using the Redundant Electronics feature, this should be the 2B port on the active controller card.

Library IP address #2

The attribute value is specified by the user or administrator when the library connection is configured. For and SL150 and SL500 libraries, this attribute is always blank.

For SL3000 and SL8500 libraries, this entry enables STA to maintain uninterrupted SNMP communications with the library if either a Redundant Electronics switch or a Dual TCP/IP failover occurs, and it may be any of the following:

- For libraries with the Redundant Electronics feature, it is the IP address of the 2B port on the alternate (standby) controller card.
- For libraries with the Dual TCP/IP feature, it is the IP address of the 2A port on the active controller card.
- For libraries with both features, it may be either of the above, depending on what the user or administrator has specified. See the *STA Installation and Configuration Guide* for detailed instructions on configuring the libraries for STA.
- For libraries with neither of these features, this attribute is blank.

Library Last Booted

Date and time the library was last rebooted. Provided only for SL150 and SL500 libraries.

Library Model

Library model number. Possible values: SL150, SL500, SL3000, or SL8500.

Library Name

User-assigned name for the library. Assigned in the Settings – SNMP Connections screen.

Library Number

Unique ID assigned to the library.

Library Scan Completed

Date and time when the most recent successful library configuration data collection was completed.

Library Serial Number

Library frame serial number.

Note: This field links to the Libraries – Overview screen, detail view, which displays all available details for this library. See "[Libraries Overview Screen](#)" on page 4-1".

Library SNMP Traps

Total SNMP traps received by STA from the library. Includes traps for any of the following: library, drive, CAP or mailslot, and pass-thru port (PTP) status, library environment checks, library logs, library connection tests, and library configuration data collections.

Note: This field links to the Libraries – Messages screen, list view, which lists SNMP traps for this library. See "[Messages Screens](#)" on page 15-1.

Library Top Level Condition

Current library health. Examples: DEGRADED, NOT OPERATIVE, NORMAL.

Library Top Level Indicator

Current library health. Examples:

- DEGRADED – In a degraded state.
- NONOPERATIVE – Not operating.

- NORMAL – Functioning as normal.
- Null (no value displayed) – STA has not received any information.

Library WWNN

Library World Wide Node Name.

Lifetime Hours Incompatible

Total head-motion hours during which incompatible media was loaded over the life of the drive.

Logical Group(s)

Logical groups to which the drive or media is assigned

M

MB R/W

For Complexes Overview and Libraries Overview: Total megabytes read and written by all drives in the library or complex.

For Drives Overview: Total megabytes read and written by the drive.

For Media Overview: Total megabytes read from and written to the media

MB Read

For Complexes Overview and Libraries Overview: Total megabytes read by all drives in the library or complex.

For Drives Overview: Total megabytes read by the drive.

For Media Overview: Total megabytes read from the media

MB Received

For Complexes Overview and Libraries Overview: Total megabytes uncompressed data received from hosts by all drives in the library or complex.

For Drives Overview: Total megabytes received by the drive from hosts during write operations. This could be compressed or uncompressed megabytes, depending on the host application.

For Media Overview: Total megabytes written to the media from hosts. The data could be compressed or uncompressed megabytes, depending on the host application.

MB Sent

For Complexes Overview or Libraries Overview: Total megabytes uncompressed data sent to hosts by all drives in the library or complex.

For Drives Overview: Total megabytes sent by the drive to hosts during read operations. This could be compressed or uncompressed megabytes, depending on whether compression has been enabled on the drive.

For Media Overview: Total megabytes sent from the media to hosts. This could be compressed or uncompressed megabytes, depending on whether compression has been enabled on the drive.

MB Write

For Complexes Overview or Libraries Overview: Total megabytes written by all drives in the library or complex.

For Drives Overview: Total megabytes written by the drive.

For Media Overview: Total megabytes written to the media

Media

Volume serial number (VSN or volser) assigned to the media by its external label. If the library does not supply the volser, STA provides one composed of Library Serial Number:Physical Address.

Note: This field links to the Media – Overview screen, detail view, which displays all available detail for this media. See "[Media Overview and Analysis Screens](#)" on page 6-1.

Media Alert Count

Total alerts generated for this media, based on defined STA alert policies

Note: This field links to the Alerts Overview screen, list view, which lists alerts for this media. See "[Alerts Screens](#)" on page 11-1.

Media Auxiliary Memory Capacity

Media's total auxiliary memory at the time of manufacture, in bytes

Media Blank

Indicates the media has never had data written to it.

Media Capacity Utilization

Percentage of the total media capacity that has been used by data. Calculated as:

Media MB Avail Pre / Media MB Capacity

Media Dismounts

Total dismounts for this media

Note: This field links to the Libraries – Exchanges screen, list view, which lists this cartridge's exchanges. See "[Exchanges Overview Screen](#)" on page 12-1.

Media Ejected from Library

Date and time when the media was last ejected from the library through a CAP

Media Entered Library

Date and time when the media was last entered into the library through a CAP

Media EOL Percentage

Percentage of the media's expected useful life that has elapsed

Media Exchange Status

Status of the media upon completion of the exchange, as derived from a variety of factors, including media errors, write efficiency, and read margin. Possible values:

- CART_MEM_FAILURE
- CLEAN_REQ – The drive is due for cleaning.
- DRIVE_ERROR

- EXPIRED_CLEAN_TAPE
- FAILED_MOUNT
- FW_DOWN_LEVEL
- GOOD
- INCOMPLETE_UNLOAD – The application requested that the media be unloaded. The tape drive has detected data still in its buffer and has asked for confirmation from the application.
- INSUFFICIENT_DATA(NULL) – STA has not received enough exchange data from the library to calculate drive health. It may be that the drive is not supported (LTO 2, for example) or the library firmware is downlevel.
- LOAD_ERROR
- LTO_NON_ADI_MODE –ADI mode has not been enabled on either the library, the drive, or both.
- MEDIA_ERROR
- NON_DRV_ERROR – This is neither a drive nor a media problem, so there is no effect on the suspicion of drive or media. If this exchange status is set, check the following for additional information which may help in determining the cause:
For Enterprise drives, check the exchange fault symptom code (FSC).
For LTO drives, check tape alerts that have been set recently.
This status may be set at the following times:
A Media Write Protect Tape Alert must be set. The host application is attempting to write to media that has been write protected.
FSC 6142 has been set for a T10000B exchange. This code indicates there were difficulties obtaining an Oracle Key Manager (OKM) encryption key. This can be attributed to several scenarios, such as compromised network connectivity, the OKM has crashed, or the drive enrollment has expired and the drive must be re-enrolled. The drive may be used to read un-encrypted tapes until the OKM comes back online and starts to serve keys again.
FSC has been set to 3627, 3629, 362A, or 362B. These FSC codes are set during a "normal operation," which checks that a piece of media is truly blank before labeling it. The host application will perform the following sequence: 1) mount new tape; 2) attempt to check for no label; 3) label the new tape.
- OTHER_ERROR
- PERM_ERROR
- READ_ERROR
- WRITE_ERROR
- UNKNOWN
- UNLOAD_ERROR

Media Health Indicator

Media health as computed by STA analytics. This value reflects a variety of factors, such as the media's error history, read margin, and write efficiency. It includes all data up to and including the last completed exchange and is updated immediately upon completion of the exchange.

Possible values, in order of degrading health:

- USE – The media has had no failures or degradation in the last ten exchanges.
- MONITOR – The media has had multiple errors; there is a less than 80 percent chance that it needs service.
- EVALUATE – The media has had multiple errors; there is a greater than 80 percent chance that it needs service.
- ACTION – The media has had an error that requires service.
- UNKNOWN – STA has not received enough data to compute health for the media. This may be due to a variety of factors, including exchanges on unsupported drive models, drives with downlevel firmware, or LTO drives with ADI mode not enabled.

Note: STA only receives information about errors detected by a drive while performing read/write activity to the media. STA does not receive information about errors that may occur in the data path or host applications.

Media Health Trend

Trend of media health between the last two exchanges, as computed by STA analytics. Options are: BETTER, UNCHANGED, WORSE.

Media HLI Address

Host Library Interface (HLI) address of the location. Applies only to drives or media slots in HLI partitions or libraries. This address is assigned by the ACSLS or ELS host software.

Note: Available only for SL8500 libraries with firmware FRS_7.80 or higher or SL3000 libraries with firmware FRS_4.0 or higher. For all others, the value is left blank.

For media slots, format is l,p,w,c, where:

- l=logical storage manager (LSM) number. Possible values are 0, 1, 2, or 3.
- p=panel number.
- r=row number.
- c=column number.

For drives, format is l,p,t, where:

- l=logical storage manager (LSM) number. Possible values are 0, 1, 2, or 3.
- p=panel number
- t=transport number

Media Length in Meters

Length of the media, in meters

Media Library Name

User-assigned name for the library. Assigned in the Settings – SNMP Connections screen.

Media Library Number

Unique ID assigned to the library.

Media Library Serial Number

Library frame serial number

Note: This field links to the Libraries – Overview screen, detail view, which displays all available details for this library. See "[Libraries Overview Screen](#)" on page 4-1.

Media Life Indicator

Indicates whether the media has reached the end of its expected useful life. Possible values: EOL, GOOD, UNKNOWN.

Media Long Type

Detailed media type as reported by the library. Examples include LtoGen5_1500GB, LtoGen6_2.5TB, T10000, T10000T2_Sport, and T10kUniv_Cleaning. UNKNOWN indicates media with a missing or unreadable external volume serial number (VSN or volser) label.

Media Manufacturer Date

Date when the media was manufactured, in yyyyymmdd format.

Note: This date is converted from UTC time to the time zone specified in the user's Preferences settings.

Media Manufacturer Serial Number

Media serial number assigned by the manufacturer.

Note: STA does not have this information until the media has been mounted in a drive.

Media MB Avail Post

Unused media capacity, in megabytes; this value is provided after the exchange completes. Available for StorageTek enterprise drives only.

Note: Reported value varies by drive vendor and other factors.

Media MB Avail Pre

Unused media capacity, in megabytes; this value is provided before the beginning of the exchange. Available for LTO drives only.

Note: Reported value varies by drive vendor and other factors.

Media MB Capacity

Maximum media capacity, in megabytes.

Note: Reported value varies by drive vendor and other factors.

Media Physical Address

Library internal address.

For SL150 libraries, the format is m,s,w,c (for example, 1,Left,1,2), where:

- m =module number; 1–10, from top (base module) to bottom
- s =side; Left or Right
- w =row number; 1–3, from top to bottom
- c =column number; 1–5, from front to back

For SL500 libraries, the format is l,m,r,c (for example, 0,2,2,3), where:

- l =for nonpartitioned libraries, this is the library ID (always 0); for partitioned libraries, this is the partition ID (1–8).
- m =module number; 1–5, from top to bottom of the rack
- r =drive row number; 1–2 (Base Module) or 1–4 (Drive Expansion Module), from top to bottom of the module
- c =column number; always 9 for drives

For SL3000 and SL8500 libraries, the format is l,r,c,s,w (for example, 1,1,2,2,3), where:

- l =library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).
- r =rail number. For SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.
- c =column number.
- s =side number.
- w =row number.

Media Rail Number

Rail number. For SL150, SL500, and SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.

Media Slot SCSI Element ID

SCSI element ID of the slot where the media is located. Applies only to media slots in SCSI partitions or libraries. See the applicable library *User's Guide* for details on how SCSI IDs are assigned.

A value of "-1" indicates the media is not in a SCSI slot. For example, it may be in a SL8500 library, an HLI partition in a SL3000 library, or a slot not allocated to a partition in a partitioned library.

Media Slots Activated

Total media slots activated through hardware activation.

Media Slots Installed

Total media slots installed but not necessarily activated for use.

Media Slots Occupied

Total occupied media slots. This count includes both activated storage slots and system slots.

Although system slots are not intended for long-term storage of data media, they may temporarily contain data media in certain situations. Following are examples of

situations in which media monitored by STA may reside in system slots. See your library *User's Guide* for complete details on the use of system slots.

- Data media may be moved to system slots during a library diagnostic self-test.
- Data media in transit at the time of a Redundant Electronics failover may be moved to system slots.
- Cleaning media may be stored in system slots if a library is using automatic cleaning,

Note: This attribute is updated only on completion of a library data collection. For example, if you enter media through a CAP, you may need to perform a manual data collection or wait for a scheduled collection to complete before this attribute reflects the new media count. See the *STA Installation and Configuration Guide* for details.

Note: This field links to the Media – Overview screen, list view, which lists all media for this library. See "[Media Overview and Analysis Screens](#)" on page 6-1.

Media Slots Unoccupied

Total media slots with no media. This count includes both activated storage slots and system slots.

Media Start Tracking

Date and time when STA first began tracking this volume serial number (VSN or volser). If the volser is used on more than one cartridge, this field reflects the earliest start date available.

Media Stop Tracking

Date and time when STA stopped tracking this volume serial number (VSN or volser). This is when STA determined the volser no longer exists in any of the monitored libraries and updated the volser status from "missing" to "removed".

Media Suspicion Level

Calculated suspicion level for the media. Possible values: 0–100. Lower numbers are desirable. The higher the number, the higher the probability the media needs attention.

Media Type

Media type short description. Examples include LTO4, LTO_CLNU, T10000T1, and T10000T2_CLN. UNKNOWN indicates media with a missing or unreadable external volume serial number (VSN or volser) label.

Note: Type is UNKNOWN for all DLT and SDLT media, for which STA does not compute health.

Media Write Efficiency

Write efficiency for all the data on the media, based on capacity over distance. Expressed as a percentage. Computed by comparing how many blocks it took to write the data compared to what it should take.

Available only if the drive firmware supports TTI 5.4.

This attribute is useful in selecting media to be used for drive calibration and qualification.

Meters Between 2 Most Recent Cleans

Total megabytes read and written by the drive between the two most recent cleanings.

Meters since Last Clean

Total megabytes read and written by the drive since its last cleaning.

Monitored since

Date and time when STA started tracking this resource (library, complex, drive, or media).

Mount R/W MB

Total megabytes read or written by the drive during the mount

Mount R/W MB/sec

Average throughput rate for the drive, in megabytes per second. Calculated as:

`total MB (read +written) /total seconds mount time`

Note: This value may be affected by a variety of factors external to the drive, such as robot speed or application behavior—for example, some applications do not dismount media immediately upon completion of read/write operations, causing the drive to be idle for much of the mount. As a result, this value is not likely to represent the drive's maximum potential throughput rate.

Mount Read MB

Total megabytes read by the drive during the mount.

Note: Some media transactions involve a very small amount of I/O. All values greater than 0.0 and less than 0.1 are displayed as 0.01. A value of 0.0 indicates no I/O.

Mount Read MB/sec

Average read rate for the drive, in megabytes per second. Calculated as:

`total MB read /total seconds mount time`

Note: This value may be affected by a variety of factors external to the drive, such as robot speed or application behavior—for example, some applications do not dismount media immediately upon completion of read/write operations, causing the drive to be idle for much of the mount. As a result, this value is not likely to represent the drive's maximum potential read rate.

Mount Received MB

Total uncompressed megabytes received by the application from the drive during the mount.

Mount Sent MB

Total uncompressed megabytes sent from the application to the drive during the mount.

Mount Write MB

Total megabytes written by the drive during the mount

Mount Write MB/sec

Average write rate for the drive, in megabytes per second. Calculated as:

total MB written /total seconds mount time

Note: This value may be affected by a variety of factors external to the drive, such as robot speed or application behavior—for example, some applications do not dismount media immediately upon completion of read/write operations, causing the drive to be idle for much of the mount. As a result, this value is not likely to represent the drive's maximum potential write rate.

MV

MV Calibration Attempts

Number of calibrations attempted on the drive during the most recent calibration or qualification cycle. A minimum of two attempts are required for a successful calibration or qualification. Possible values: 0, 1, 2, 3.

MV Calibration Current State

Current state of the media relating to drive calibration and qualification.

Applies only if the media is assigned to a validation drive as the primary or secondary calibration media. Options include: Assigned, Available, Calibrated, Not Suitable, Media in Calibration, Media in Qualification.

MV Calibration Drive SN

Serial number of the validation drive that was most recently calibrated or qualified with this media.

MV Calibration Drive Type

Drive type of the validation drive that was most recently calibrated or qualified with this media.

MV Calibration Information

Information about the most recent calibration or qualification of the drive. Options include: Calibration in progress, Completed.

MV Calibration Initial DQI

Data Quality Index (DQI) calculated during most recent drive calibration in which this media was used. DQI is a measure of the amount of error correction left on the media. A higher value is desirable.

Provided only for T10000T2 media assigned to the calibration media logical group and the validation drive firmware supports TTI 5.4.

MV Calibration Initial Suspicion

Media Suspicion Level of the most recent drive calibration in which this media was used. Possible values: 0–100. Lower numbers are desirable. The higher the number, the higher the probability the media needs attention.

Provided only if the media has been assigned as the primary or secondary calibration media for a validation drive.

MV Calibration Last DQI

Data Quality Index (DQI) calculated during the most recent drive qualification in which this media was used. DQI is a measure of the amount of error correction left on the media. A higher value is desirable.

Provided only for T10000T2 media that has been assigned as the primary or secondary calibration media for a validation drive and the drive firmware supports TTI 5.4.

MV Calibration Library Complex

Name of the library complex in which the most recent drive calibration or qualification was performed using this media.

MV Calibration Library Model

Model of the library in which the most recent drive calibration or qualification was performed using this media.

MV Calibration Library SN

Serial number of the library complex in which the most recent drive calibration or qualification was performed using this media.

MV Calibration Number of Wraps

Total wraps of data present on the media. Calculated based on the Media Type and the MV Calibration MB Used.

Used to determine whether the media has enough data to be used for drive calibration and qualification.

MV Calibration Request

Indicates the exchange was initiated by STA to fulfill one of the following processes:

- A drive calibration
- A drive qualification
- A Basic Verify performed on calibration media that has no STA history

MV Calibration Starting Suspicion

Drive suspicion level reported at the start of the most recent calibration of the drive. Possible values: 0–100. Lower numbers are desirable. The higher the number, the higher the probability the drive needs attention.

MV Calibration State

State of the most recent drive calibration or qualification performed on the drive. Options are:

- For both drives and media – Calibrated, Not calibrated, Not Suitable, Offline, Drive Calibration Needs Media, Media Make History.
- For drives only – Drive In Calibration 1, Drive In Calibration 2, Drive In Qualification 1, Drive In Qualification 2.
- For media only – Media In Calibration, Media In Qualification.

MV Calibration Status Information

Information about the current validation status of the media. Available only if the media has been assigned to the calibration media logical group.

MV Count

Total validations performed on the media.

MV Days Since Last Validation

Number of days since the media was last validated based on the last validation time. Null if the media has not yet been validated.

MV DQI

Data Quality Index (DQI) computed by STA analytics based on the results of the media validation. DQI is a measure of the amount of error correction left on the media. This value is specific to the media and, by factoring out the drive's contribution, provides a more targeted measure of media quality than Read Quality Index (RQI).

Provided only for validations involving T10000T2 media and validation drives with firmware supporting TTI 5.4.

DQI is reported as a percentage, and a higher value is desirable. It is not computed in the following situations:

- The validation is a Basic Verify.
- The Media Type of the validated media is T10000T1.
- The validation results in an media validation Perm Status of True.
- The validation results in an Invalid MIR error.

MV Drive Allocated

Indicates the drive has been assigned to the media validation drive pool through SL Console.

MV Drive Available

Indicates the drive is currently available to perform media validation exchanges, as determined by STA analytics. If this attribute is blank, the drive does not meet minimum requirements for STA media validation.

MV Drive Capable

Indicates STA can use this drive for validation activities. The drive has been assigned to a media validation drive pool through SL Console and has a Drive Type and Drive Firmware Version that support STA media validation.

MV Drive In Use

Indicates the validation drive is currently in use by STA, another application, or diagnostics operations.

MV Drive Last Calibrated

Date and time when the drive was most recently calibrated.

MV Drive Reserved

Indicates the validation drive is reserved by STA for use in a media validation.

MV Estimated Time Remaining

Estimated time remaining on the media validation as reported by the drive. The value is updated periodically. Available only for in-progress validations.

MV Incomplete

Indicates the validation has not completed. The validation may be pending or in-process. Options are True or False.

MV Initiator

Software application or device used to initiate the media validation activity. Options are: DRIVE, HOST, LIBRARY, SLC, STA.

MV Interrupted

Indicates the validation was interrupted by a host request for the media or canceled while in process. Options are True or False.

Validations for which this value is True can be resubmitted.

MV Last Activity

Start date and time of the most recent media validation. For Drives – Overview, this is the most recent validation performed by the drive. For Media – Overview, this is the most recent validation performed on the media.

MV Last Calibration Date

Date and time when the media was last used for drive calibration.

Available only if the media has been assigned to the calibration media logical group.

MV Last Calibration DQI

Data Quality Index reported upon completion of the most recent drive calibration. DQI is a measure of the amount of error correction left on the media. A higher value is desirable.

Provided only for validations involving T10000T2 media and validation drives with firmware supporting TTI 5.4.

MV Last Exchange Start

Start date and time of the most recent media validation performed by the drive.

MV Last Recommendation

Recommended user action for the most recently completed media validation. Determined by STA analytics, based on the results of the validation. Examples include: "Media OK: Continue using"; "Corrupted MIR: Rebuild MIR and Re-run Media Validation"; "Migrate the data and scratch the tape".

MV Last Recording Technique

Exchange Recording Technique used by the drive during the most recent calibration or qualification performed with this media.

MV Last State Update

Date and time when the status of this media validation was last updated. Updated whenever there is a change to the MV Request State.

MV Last Test Type

Type of verification test performed during the most recent validation on this media.

MV Library Error

Library event code for a library error that occurred during the media validation. A value indicates an operational issue with the media validation that prevented the test from completing; it does not imply there are issues with the media itself.

You can display the library event codes through the SL Console; see the *SL8500 User's Guide* for details.

MV MB Tape Used

Total amount of data that has been written to the media as determined by the drive during drive calibration.

Used with the Media Type to calculate the MV Calibration Number of Wraps for the media.

MV Operation

Indicates the type of media validation test performed. Options are: BASIC, COMPLETE, COMPLETE PLUS, REBUILD MIR, STANDARD. Applies only if the exchange is a media validation operation.

MV Policy Name

User-defined name assigned to the media validation policy.

MV Primary Calibration Media

Indicates this media is assigned to a validation drive as the primary calibration media. Possible values: True or False (blank).

- For primary calibration media, this attribute is True and the MV Calibration Drive SN attribute indicates the drive it is assigned to.
- For secondary calibration media, this attribute is False and the MV Calibration Drive SN attribute indicates the drive it is assigned to.
- For media not used for drive calibration, this attribute is False and there is no MV Calibration Drive SN entry.

MV Primary Qualification Start

Start date and time of the most recent qualification of the drive using the primary calibration media.

MV Priority Order

Order in which media validation requests are processed in the queue. Applies only to pending and in-process requests. This value is blank for completed validations.

MV Recommendation

Recommended user action determined by STA analytics based on the results of the media validation. Provided only for completed validations. Examples include: "Media OK: Continue using"; "Corrupted MIR: Rebuild MIR and Re-run Media Validation"; "Migrate the data and scratch the tape".

MV Request Start

Date and time when the media validation request was placed in the MV queue. Depending on the source of the request, this is either the time the MV request was initiated by STA, or the time STA recognized the request initiated by another application.

MV Request State

Status of the media validation request. Examples are: Completed, Error, In-Progress - Stop Requested, Pending, Starting, Unknown.

MV Result

Final result of the media validation as determined by STA analytics upon successful completion of the verification test. This attribute applies to the quality of the data on the media.

Options are: DEGRADED, FAILED, USE, UNKNOWN. The value is UNKNOWN if the validation was interrupted or did not complete successfully.

MV Secondary Qualification Start

Start date and time of the most recent qualification of the drive using the secondary calibration media.

MV Status Information

Provides information about issues with the media validation request. The information may explain the problem or suggest corrective action to take. This attribute is usually blank. Examples include: "Waiting for drive; all drives in use." and "Incompatible tape format for drive."

A value of "Drive Timeout; MDV manager cancel" indicates STA requested the library to return the media to a media slot because the validation took more than nine hours to complete. This is usually the result of a library operational error. If the Read Percentage attribute for the validation exchange is less than 100 percent, then the validation did not complete. If this status recurs for the media, there is probably an issue with the media; if it recurs for the drive, there is probably an issue with the drive.

MV Test Percentage

Percentage of the verification test that has been completed during this media validation. The value is updated periodically for in-progress validations.

A value of 100 indicates the test completed successfully. If the test was interrupted, the value remains less than 100.

MV Test Type

Type of verification test performed during the media validation. Examples are: Basic Verify, Cancel Validation, Complete Verify Plus, Standard Verify, Verify and Rebuild MIR.

MV Time Spent Validating

Total time the media validation has taken, as reported by the drive. The time starts when the validation test begins on the drive and ends when the test is complete. For in-progress validations, the value is updated periodically. For pending validation requests, the value is null.

N**New Property Effective**

Date and time when the new property value is effective.

New Property Value

New value assigned to the property.

P**Partition Name**

Unique name assigned to the partition by STA. Includes the library-assigned partition number. Formatted as: Library Complex Name:Partition Type:Partition Number

Partition Number

Unique partition ID assigned on the library. For nonpartitioned libraries, the value is always "0". For partitioned libraries, possible values are 1–8.

Partition Type

Type of host-partition connection. Possible values:

- HLI – HLI (Host Library Interface) protocol
- OTHER – System cells, used for storage of diagnostic cartridges.
- SCSI – SCSI protocol

Partitions

Total partitions defined in the complex or library. The maximum number of partitions per library is eight, and per complex, it is 16.

Note: This includes user-defined partitions only. The system partition (for storage of cleaning and diagnostic cartridges) is not included in the count.

Partitions for SL8500 complexes can extend across libraries. In such cases, the libraries in the same complex must all have the same partition count. For example, complex SL8500_1 includes 10 libraries and 4 partitions. On the Complexes Overview screen, the Partitions value for complex SL8500_1 is "4," and on the Libraries Overview screen, the Partition count for each of the 10 libraries in the complex is also "4."

Perm Read Errors

Number of permanent read errors

Perm Write Errors

Number of permanent write errors

Permanent Error

Indicates the exchange resulted in a permanent error. Available only if the drive firmware supports TTI 5.4. Options are True or False.

This status could be the result of an operational error, a bad drive, or bad media. For media validation exchanges, in most cases when this value is True, the MV Result is Unknown.

Port Speed (Port A)

Speed of Drive Port A. "Auto" indicates the speed is auto-negotiated between the drive and the switch. A value (FC-8Gb, for example) indicates a specific value has been assigned.

Port Speed (Port B)

Speed of Drive Port B. "Auto" indicates the speed is auto-negotiated between the drive and the switch. A value (FC-8Gb, for example) indicates a specific value has been assigned.

Property Name

Device property being changed.

PTP

Unique identifier of the pass-through port (PTP). Applies to SL8500 libraries only.

PTP Alert Count

Total alerts generated for this PTP, based on defined STA alert policies

Note: This field links to the Alerts Overview screen, list view, which lists alerts for this PTP. See "[Alerts Screens](#)" on page 11-1.

PTP Count

Total pass-through ports (PTPs). Applies to SL8500 libraries only.

PTP Ejects

Total cartridges ejected through all pass-through ports (PTPs) over the last 30 days. Applies to SL8500 libraries only; all other libraries show 0.

PTP Enters

Total cartridges entered through all pass-through ports (PTPs) over the last 30 days. Applies to SL8500 libraries only; all other libraries show 0.

PTP Library Health

Current health of the pass-through port (PTP) as reported by the library. Applies to SL8500 libraries only. Options are: DEGRADED, NORMAL, NOTOPERATIVE, UNKNOWN.

PTP Library State

Current pass-through port (PTP) state, as reported by the library. Applies to SL8500 libraries only. Examples are: READY. STA updates this value hourly and as SNMP traps for the PTP are received from the library.

PTP Physical Address

Library internal address of the pass-through port (PTP). Applies to SL8500 libraries only. The format is l,r,c,s,w (for example, 1,1,-6,1,0), where:

- l=library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).
- r=rail number. For SL8500 libraries, possible values are 1, 2, 3, or 4.
- c=column number. For PTPs, this value is always -6.
- s=side number. For PTPs, this value is always 1.
- w=row number. For PTPs, this value is always 0.

PTP Power LED State

Current state of the pass-through port (PTP) power LED. Normal condition is ON. Options are: ON, OFF, or UNKNOWN.

PTP Identifier

Unique identifier for the pass-through port (PTP)

PTP SNMP Traps

Total pass-through port (PTP) messages received from the library. A sudden increase in this number indicates a condition that should be investigated.

R

RQI

Measure of how much error correction is left on the media, as calculated from the last exchange or media validation. This value is specific to the exchange, with contributions from both the drive and the media. In comparison, the Data Quality Index (DQI) is a more targeted measure of media quality because STA factors out the drive's contribution.

RQI is reported as a percentage. A high value is desirable.

R/W MB/sec

Throughput rate for the time spent actively reading and writing; idle time is excluded. Expressed in megabytes per second. Available for StorageTek enterprise drives only.

Calculated as:

$(\text{compressed MB read} + \text{compressed MB written}) / (\text{read time} + \text{write time})$

R/W Mount Ratio

Ratio of read and write time to total mount time. Displayed as a percentage. A value close to 1.0 indicates the drive is active over the entire mount. Available for StorageTek enterprise drives only.

Calculated as:

$(\text{read time} + \text{write time}) / \text{total mount time}$

Read Margin

Amount of error correction code (ECC) read margin remaining on the media, as reported by the drive during the last mount. Available only for StorageTek T10000A and above drives. Reported as a percentage. A high value is desirable.

If STA determines that this value has gone below a threshold for this drive type, the Exchange Read Marginal attribute is set to Yes.

Read MB/sec

Read rate for the time spent actively reading; idle time is excluded. Expressed in megabytes per second. Available for StorageTek enterprise drives only.

Calculated as:

$\text{compressed MB read} / \text{total read time}$

Read Mount Ratio

Ratio of read time to total mount time. Calculated as:

$\text{read time} / \text{total mount time}$

Received on

Date and time when the STA server received the SNMP trap from the library.

Recorded on

Date and time when the exchange started.

Repositioning Cycles

Total times the media was repositioned for any reason

Repositioning Cycles Non ERP

Total times the media was repositioned due to non-ERP (error recovery process) reasons, such as data overrun or underrun.

Request ID

Unique ID for the SNMP request.

Result Code

Device result code for the event.

Robot

Serial number of the robot

Robot Alert Count

Total alerts generated for this robot, based on defined STA alert policies

Note: This field links to the Alerts Overview screen, list view, which lists alerts for this robot. See "[Alerts Screens](#)" on page 11-1.

Robot Count

Total number of robots

Robot Get Retries

Total robot *get* retries

Robot Get Totals

Total robot media *get* actions

Robot Identifier

Unique identifier for the robot

Robot Library State

Current robot state, as reported by the library. Options are: READY or INOPERATIVE. STA updates this value hourly. Additionally for SL3000 and SL8500 libraries, the value is updated as SNMP traps for the robot are received from the library.

Robot Physical Address

Library internal address.

For SL150 libraries, the format is m,s,w,c (for example, 1,Left,1,2), where:

- m =module number; 1–10, from top (base module) to bottom
- s =side; Left or Right
- w =row number; 1–3, from top to bottom
- c =column number; 1–5, from front to back

For SL500 libraries, the format is l,m,r,c (for example, 0,2,2,3), where:

- l =for nonpartitioned libraries, this is the library ID (always 0); for partitioned libraries, this is the partition ID (1–8).
- m =module number; 1–5, from top to bottom of the rack
- r =drive row number; 1–2 (Base Module) or 1–4 (Drive Expansion Module), from top to bottom of the module
- c =column number; always 9 for drives

For SL3000 and SL8500 libraries, the format is l,r,c,s,w (for example, 1,1,2,2,3), where:

- l =library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).
- r =rail number. For SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.
- c =column number.
- s =side number.

- W=row number.

Robot Power LED State

Current state of the robot power LED. Normal condition is ON. Options are: ON, OFF, or UNKNOWN.

Robot Put Retries

Total robot media *put* retries

Robot Put Totals

Total robot media *put* actions

Robot SNMP Traps

Total robot messages received from the library. A sudden increase in this number indicates a condition that should be investigated.

Robot STA Health

Current health of the robot as calculated by STA. Options are: ACTION, DEGRADED, ERROR, EVALUATE, MONITOR, USE, UNKNOWN.

Note: This attribute is updated only on completion of a library data collection. Regular data collections are done automatically, or you may initiate a manual data collection at any time. See the *STA Installation and Configuration Guide* for details.

Robot Library Health

Current health of the robot as reported by the library. Options are: DEGRADED, NORMAL, NOTOPERATIVE, UNKNOWN.

Note: This attribute is updated only on completion of a library data collection. Regular data collections are done automatically, or you may initiate a manual data collection at any time. See the *STA Installation and Configuration Guide* for details.

S

Servo Perm Errors

Number of permanent servo errors

Severity

Severity of the event.

SNMP Trap

Type of SNMP trap. Options are:

- CAP
- Drive
- Heartbeat
- Library Environment Check
- Library Log
- Library Status

- PTP
- SNMP Agent Start

Source HLI Address

Host Library Interface (HLI) address of the location. Applies only to drives or media slots in HLI partitions or libraries. This address is assigned by the ACSLS or ELS host software.

Note: Available only for SL8500 libraries with firmware FRS_7.80 or higher or SL3000 libraries with firmware FRS_4.0 or higher. For all others, the value is left blank.

For media slots, format is l,p,w,c, where:

- l=logical storage manager (LSM) number. Possible values are 0, 1, 2, or 3.
- p=panel number.
- r=row number.
- c=column number.

For drives, format is l,p,t, where:

- l=logical storage manager (LSM) number. Possible values are 0, 1, 2, or 3.
- p=panel number
- t=transport number

Source Library Number

Unique ID assigned to the library.

Source Physical Address

Library internal address.

For SL150 libraries, the format is m,s,w,c (for example, 1,Left,1,2), where:

- m=module number; 1–10, from top (base module) to bottom
- s=side; Left or Right
- w=row number; 1–3, from top to bottom
- c=column number; 1–5, from front to back

For SL500 libraries, the format is l,m,r,c (for example, 0,2,2,3), where:

- l=for nonpartitioned libraries, this is the library ID (always 0); for partitioned libraries, this is the partition ID (1–8).
- m=module number; 1–5, from top to bottom of the rack
- r=drive row number; 1–2 (Base Module) or 1–4 (Drive Expansion Module), from top to bottom of the module
- c=column number; always 9 for drives

For SL3000 and SL8500 libraries, the format is l,r,c,s,w (for example, 1,1,2,2,3), where:

- l=library number. For nonpartitioned libraries, this is the library ID; for partitioned libraries, this is the partition ID (1–8).

- **r** =rail number. For SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.
- **c** =column number.
- **s** =side number.
- **w** =row number.

Source Rail Number

Rail number. For SL150, SL500, and SL3000 libraries, this value is always 1. For SL8500 libraries, possible values are 1, 2, 3, or 4.

Source SCSI Element ID

SCSI element ID of the source location. Applies only to drives and media slots in SCSI partitions or libraries. See the applicable library *User's Guide* for details on how SCSI IDs are assigned.

A value of "-1" indicates the location is not a SCSI slot. For example, it may be in a SL8500 library, an HLI partition in a SL3000 library, or a slot not allocated to a partition in a partitioned library.

STA Start Tracking

For Drives Overview: Date and time when STA first began tracking this drive serial number.

For Media Overview: Date and time when STA first began tracking this volume serial number (VSN or volser). If the volser is used on more than one cartridge, this field reflects the earliest start date available.

STA Stop Tracking

For Drives Overview: Date and time when STA stopped tracking this drive serial number. This is when STA determined the drive serial number no longer exists in any of the monitored libraries and updated the drive status from "missing" to "removed".

For Media Overview: Date and time when STA stopped tracking this volume serial number (VSN or volser). This is when STA determined the volser no longer exists in any of the monitored libraries and updated the volser status from "missing" to "removed".

STA Supported

Indicates the media meets the minimum requirements for STA analytics. Possible values: True or False. The following media types usually have a value of True.

- StorageTek T10000T1 and higher
- StorageTek 9840
- LTO-3 and higher

STA tracks media for which this value is False, but it is not able to perform full analytics on them because it receives only minimal data about them.

See the *STA Requirements Guide* for details about supported media.

T

Text

Additional text regarding the event, sent by the subsystem.

Theoretical Maximum Usage Count

Manufacturer's recommended usage limit for the cleaning media.

Note: Not available for all media and drive types. This value may show as "0" or blank, which should be interpreted as not available or unknown.

Time Spent Loaded

Total time during this exchange that the drive has tension on the media. Does not include the time required to thread the media.

Time Spent R/W

Total time the drive spent reading and writing data during the exchange

Time Spent Reading

Total time the drive spent reading data during the exchange

Time Spent Reading or Writing

Total time the drive spent reading and writing data during the exchange

Time Spent Writing

Total time the drive spent writing data during the exchange

Total Host Requests

Total host requests received by this library or complex.

Trap Type

Entity type to which the trap pertains. One of the following:

- CAP – CAP, AEM, or mailslot status
- Drive – Drive status
- Heartbeat
- Library Environment Check
- Library Log
- Library Status

U

Unload Errors

Number of permanent unload errors

Usage Perm Errors

Number of unknown usage errors

Username

STA username associated with the event.

Volume Serial Number

Volume serial number (VSN or volser) assigned to the media by its external label. If the library does not supply the volser, STA provides one composed of Library Serial Number:Physical Address.

Note: This field links to the Media – Overview screen, detail view, which displays all available detail for this media. See "[Media Overview and Analysis Screens](#)" on page 6-1.

W

WORM/VolSafe Media

Indicates whether the media uses StorageTek VolSafe technology. STA does not know the status until the media has been mounted. Possible values: Yes or No. Blank indicates unknown.

Write Efficiency

Write efficiency for the exchange, based on capacity over distance.

Write MB/sec

Write rate for the time spent actively writing; idle time is excluded. Expressed in megabytes per second. Calculated as:

`compressed MB written /total write time`

Write Mount Ratio

Ratio of write time to total mount time. Calculated as:

`write time /total mount time`

Complexes Overview Screen

The Libraries – Complexes Overview screen shows attributes related to one or more selected library complexes.

The attributes are organized into the following sections.

- "Title" on page 3-2
- "Library Complex" on page 3-2
- "Library Complex Activity Counts (Last 30 days)" on page 3-2
- "Library Complex Auxiliary Counts" on page 3-2
- "User-Provided Information" on page 3-3

Complexes Overview Detail View

The screenshot displays the 'Complexes Overview' interface. At the top, it shows 'Format' options and a 'Templates' dropdown set to 'STA-Default'. The main content area is titled 'Details for Library Complex SL8500_51' and includes a timestamp 'Monitored since 2014-03-25 14:42:42'.

The interface is divided into four main sections:

- Library Complex:**
 - Library Complex Name: SL8500_51
 - Base Model: SL8500
 - Library Complex Number: 51
 - Complex Physical Library Count: 1
- Library Complex Activity Counts (Last 30 days):**
 - Dismounts: 7,194
 - CAP Enters: 0
 - CAP Ejects: 0
 - PTP Enters: 0
 - PTP Ejects: 0
 - Drive Cleans: 0
 - MB Read: 19,090.53
 - MB Write: 9,545.26
 - MB R/W: 28,635.79
 - MB Sent: 19,072.50
 - MB Received: 9,536.25
 - % Drive Utilization: 0.18%
 - Library Complex Alert Count: 1
 - Host DB Sync Errors: 0
 - Total Host Requests: 14,235
 - Host Request Timeouts: 0
- Library Complex Auxiliary Counts:**
 - Partitions: 0
 - Drive Bays Occupied: 32
 - Drive Bays Unoccupied: 32
 - Drive Bays Installed: 64
 - Media Slots Occupied: 79
 - Media Slots Unoccupied: 1,567
 - Media Slots Installed: 1,448
 - Media Slots Activated: 1,450
 - Robot Count: 8
 - CAP Count: 1
 - PTP Count: 0
 - Elevator Count: 2
- User-Provided Information:**
 - Annotation History: 2014-03-26 16:07:24 by admin-user: Sample annotation for complex SL8500_51.

Title

Values for these attributes are assigned when STA first starts tracking the library complex.

- [Library Complex](#)
- [Monitored since](#)

Library Complex

Details about the library complex. These attributes are rolled up for all libraries that share the same complex ID. These attributes come directly from the libraries and are updated with each library configuration data collection.

- [Library Complex Name](#)
- [Base Model](#)
- [Library Complex Number](#)
- [Complex Physical Library Count](#)

Library Complex Activity Counts (Last 30 days)

Activity totals for all libraries in the complex over the last 30 days. These are updated with each completed exchange.

- [Dismounts](#)
- [CAP Enters](#)
- [CAP Ejects](#)
- [PTP Enters](#)
- [PTP Ejects](#)
- [Drive Cleans](#)
- [MB Read](#)
- [MB Write](#)
- [MB R/W](#)
- [MB Sent](#)
- [MB Received](#)
- [% Drive Utilization](#)
- [Library Complex Alert Count](#)
- [Host DB Sync Errors](#)
- [Total Host Requests](#)
- [Host Request Timeouts](#)

Library Complex Auxiliary Counts

Total resource counts for all libraries in the complex. The summary fields are updated with each completed exchange. The asset fields are updated with each library data collection.

- [Partitions](#)
- [Drive Bays Occupied](#)
- [Drive Bays Unoccupied](#)
- [Drive Bays Installed](#)
- [Media Slots Occupied](#)
- [Media Slots Unoccupied](#)
- [Media Slots Installed](#)
- [Media Slots Activated](#)
- [Robot Count](#)
- [CAP Count](#)
- [PTP Count](#)
- [Elevator Count](#)

User-Provided Information

- [Annotation History](#)


Libraries Overview Screen

The Libraries – Overview screen shows attributes related to one or more selected libraries.

The library attributes are organized into the following sections.

- ["Title"](#) on page 4-2
- ["Library"](#) on page 4-2
- ["Library Activity Counts \(Last 30 days\)"](#) on page 4-3
- ["Library Auxiliary Counts"](#) on page 4-3
- ["User-Provided Information"](#) on page 4-4

Libraries Overview Detail View



Title

Values for these attributes are assigned when STA first starts tracking the library.

- [Library](#)
- [Monitored since](#)

Library

Details about the library. These attributes come directly from the library and are updated with each library configuration data collection.

- [Library Complex Name](#)

- [Library Name](#)
- [Library Number](#)
- [Library Model](#)
- [Library Serial Number](#)
- [Library WWNN](#)
- [Library Top Level Indicator](#)
- [Library Last Booted](#)
- [Library Firmware Updated](#)
- [Library Firmware Version](#)
- [Library IP address #1](#)
- [Library IP address #2](#)
- [Library Scan Completed](#)
- [Cumulative Library Uptime](#)

Library Activity Counts (Last 30 days)

Activity totals for the library over the last 30 days. These are updated with each completed exchange.

- [Library SNMP Traps](#)
- [Library Alert Count](#)
- [Dismounts](#)
- [CAP Enters](#)
- [CAP Ejects](#)
- [PTP Enters](#)
- [PTP Ejects](#)
- [Drive Cleans](#)
- [MB Read](#)
- [MB Write](#)
- [MB R/W](#)
- [MB Sent](#)
- [MB Received](#)
- [% Drive Utilization](#)
- [Host DB Sync Errors](#)
- [Total Host Requests](#)
- [Host Request Timeouts](#)

Library Auxiliary Counts

Library resource counts. The summary fields are updated with each completed exchange. The asset fields are updated with each library data collection.

- [Partitions](#)
- [Drive Bays Occupied](#)
- [Drive Bays Unoccupied](#)
- [Drive Bays Installed](#)
- [Media Slots Occupied](#)
- [Media Slots Unoccupied](#)
- [Media Slots Installed](#)
- [Media Slots Activated](#)
- [Robot Count](#)
- [CAP Count](#)
- [PTP Count](#)
- [Elevator Count](#)

User-Provided Information

- [Annotation History](#)

Drives Overview and Analysis Screens

The Drives – Overview and Drives – Analysis screens show attributes related to drives. There is one set of attributes for StorageTek enterprise drives and a slightly different set for LTO drives.

The drive attributes are organized into the following sections.

- ["Title"](#) on page 5-5
- ["Drive"](#) on page 5-5
- ["Media"](#) on page 5-6
- ["Most Recent Exchange"](#) on page 5-6
- ["Drive Activity Counts \(Last 30 Days\)"](#) on page 5-7
- ["Additional Exchange Information for Enterprise Drives"](#) on page 5-7
- ["Additional Exchange Information for LTO Drives"](#) on page 5-8
- ["Drive Location"](#) on page 5-8
- ["Library Complex"](#) on page 5-8
- ["Media Validation Information for Enterprise Drives"](#) on page 5-9
- ["User-Provided Information"](#) on page 5-9

Drives Overview Detail Views

Detail for Enterprise Drives (part 1)

The screenshot displays the 'Drives - Overview' web application. The main title is 'Drives - Overview'. Below the title, there is a 'Format' button and a 'Templates' dropdown menu set to 'STA-Default'. The main content area is titled 'Details for Drive 576004004877' and 'Monitored since 2013-04-24 12:28:51'. The interface is divided into several sections:

- Drive**:
 - Drive Serial Number: 576004
 - Drive Tray Serial Number: UNKNOWN
 - Drive WWNN: 50:01:04:F0:00:B0:BE:D3
 - Drive Type: T10000c-Enc
 - Drive Health Indicator: USE
 - Drive Health Trend: UNCHANGED
 - Last Drive Message: UNKNOWN
 - Drive WWPN (Port A): 50:01:04:F0:00:B0:BE:D3
 - Port Speed (Port A): FC-1Gb
 - Drive WWPN (Port B):
 - Port Speed (Port B):
 - Drive Model: T10000C
 - Drive Manufacturer: STK
 - Encryption Capable: Yes
 - Drive Interface: FIBRE
 - Drive Properties Updated: 2014-03-20 14:29:32
 - Drive Firmware Version: 1.53.316-5.30
 - STA Start Tracking: 2013-04-24 12:28:51
 - STA Stop Tracking:
- Media**:
 - Volume Serial Number: SG022
 - Media Manufacturer Serial Number: 81218601
 - Media Health Indicator: USE
 - WORM/VolSafe Media: No
 - Cleaning Media: No
- Most Recent Exchange**:
 - Exchange Start: 2014-03-26 11:28:22
 - Exchange Elapsed Time: 1:17:05
 - Exchange Mount Time: 1:16:46
 - Mount R/W MB/sec: 13.01
 - Exchange Recording Technique: T10000C
 - Drive Exchange Status: GOOD
 - Exchange Tape Alerts - Severe: 0
 - Exchange Tape Alerts - Warning: 0
 - Exchange Tape Alerts - Info: 0
 - Data Compression Ratio: 1.01 : 1
 - Alert: Drive Load Limit: No
 - Drive Suspicion Level: 0.00%
 - Exchange Drive Cleaning Required: No
 - Meters Between 2 Most Recent Cleans:
 - Meters since Last Clean:
 - Drive Lifetime Cleans: 0
 - Drive Lifetime Loads: 608
 - Drive Lifetime Meters: 2,702,979
 - Drive Lifetime Power Hours: 11,415
- Drive Activity Counts (Last 30 Days)**:
 - % Drive Utilization: 60.01%
 - Drive Dismounts: 255
 - Drive SNMP Trap Count: 0
 - Drive Alert Count: 0
 - Drive Errors: 0
 - Cleans: 0
 - MB Read: 605.65
 - MB Write: 15,656,743.89
 - MB R/W: 15,657,349.54
 - MB Sent: 2,803.65

Detail for Enterprise Drives (part 2)

Drives - Overview Templates: STA-Default

Format:

MB Received:	21,287,776.95
Avg Mount Read MB/sec:	0.00
Avg Mount Write MB/sec:	9.75
Avg Mount R/W MB/sec:	9.75
Avg Mount Read MB:	2.38
Avg Mount Write MB:	61,399.00
Avg Mount R/W MB:	61,401.40

Drive Location

Drive Library Name: sl3000-175
 Drive Library Serial Number: 57100
 Drive Library Number: **1**
 Drive Rail Number: **1**
 Drive Physical Address: **1,1,4,1,2**
 Drive HLI Address:
 Drive SCSI Element ID: **-1**

Library Complex

Library Complex Name: SL3000_57100
 Library Model: **SL3000**
 Partition Type: **HLI**
 Partition Name: SL3000_57100:HLI:0
 Partition Number: **0**

Additional Exchange Information for Enterprise Drives

Exchange FSC:
 Exchange DSC:
 Exchange Write Inefficient: **No**
 Exchange Read Marginal: **No**
 Exchange Write Efficiency: **100.00%**
 Exchange Read Margin: **93.74%**
 Time Spent Reading: **0:00:01**
 Time Spent Writing: **0:04:49**
 Time Spent Reading or Writing:
 Read MB/sec: **0.00**
 Write MB/sec: **207.41**
 R/W MB/sec: **206.70**
 Read Mount Ratio: **0.02%**
 Write Mount Ratio: **6.27%**
 R/W Mount Ratio: **6.30%**
 Exchange Encryption Used: **Encrypted Sun KMS**

Media Validation Information for Enterprise Media

MV Calibration Attempts:
 MV Calibration State:
 MV Calibration Information:
 MV Last Calibration DQI:
 MV Calibration Starting Suspicion:
 MV Drive Last Calibrated:
 MV Last Activity: **2014-03-26 10:50:42**
 MV Last Recommendation:
 MV Drive Allocated: **Yes**
 MV Drive Capable: **Yes**
 MV Drive Available: **Yes**
 MV Drive In Use: **No**
 MV Drive Reserved: **No**
 MV Secondary Qualification Start:
 MV Primary Qualification Start:

User-Provided Information

Logical Group(s): EDC Other
 Annotation History: **None**

Detail for LTO Drives (part 1)

Drives - Overview Templates: STA-Default

Format:


Details for Drive 1068002774 Monitored since 2014-03-25 14:46:48

Drive	Media
Drive Serial Number: 1068002774 Drive Tray Serial Number: unknown Drive WWNN: 50:01:04:F0:00:A0:E4:A2 Drive Type: IbmUltrium5 Drive Health Indicator: USE Drive Health Trend: UNCHANGED Last Drive Message: DEGRADED Drive WWPN (Port A): 50:01:04:F0:00:A0:E4:A3 Port Speed (Port A): FC-8Gb Drive WWPN (Port B): 50:01:04:F0:00:A0:E4:A4 Port Speed (Port B): Auto Drive Model: LT05 Drive Manufacturer: IBM Encryption Capable: Yes Drive Interface: FIBRE Drive Properties Updated: 2014-03-26 10:08:01 Drive Firmware Version: D2AC STA Start Tracking: 2014-03-25 14:46:48 STA Stop Tracking:	Volume Serial Number: LT5048 Media Manufacturer Serial Number: AA6ME23RMF Media Health Indicator: USE WORM/VolSafe Media: No Cleaning Media: No

Drive Activity Counts (Last 30 Days)	Most Recent Exchange
% Drive Utilization: 2.45% Drive Dismounts: 9 Drive SNMP Trap Count: 30 Drive Alert Count: 3 Drive Errors: 1 Cleans: 0 MB Read: 28,635.79 MB Write: 9,545.26 MB R/W: 38,181.05 MB Sent: 28,608.75 MB Received: 9,536.25 Avg Mount Read MB/sec: 0.44	Exchange Start: 2014-03-26 10:08:05 Exchange Elapsed Time: 0:15:17 Exchange Mount Time: 0:14:41 Mount R/W MB/sec: 10.83 Exchange Recording Technique: LT05 Drive Exchange Status: GOOD Exchange Tape Alerts - Severe: 0 Exchange Tape Alerts - Warning: 0 Exchange Tape Alerts - Info: 0 Data Compression Ratio: 1 : 1 Alert: Drive Load Limit: No Drive Suspicion Level: 0.00% Exchange Drive Cleaning Required: No Meters Between 2 Most Recent Cleans: Meters since Last Clean: Drive Lifetime Cleans: 0 Drive Lifetime Loads: 7,234 Drive Lifetime Meters: 274,976 Drive Lifetime Power Hours: 7,935

Additional Exchange Information for LTO Drives
Alert: Drive Diagnostics Required: No Drive Lifetime Hours in Motion: 21 IBM Drive Efficiency: 0x22 IBM Media Efficiency: 0x06 HP Device Status:

Detail for LTO Drives (part 2)



Title

Values for these attributes are assigned when STA first starts tracking the drive.

- [Drive](#)
- [Monitored since](#)

Drive

Information about the drive properties.

- [Drive Serial Number](#)
- [Drive Tray Serial Number](#)
- [Drive WWNN](#)
- [Drive Type](#)
- [Drive Health Indicator](#)
- [Drive Health Trend](#)
- [Last Drive Message](#)
- [Drive WWPN \(Port A\)](#)
- [Port Speed \(Port A\)](#)
- [Drive WWPN \(Port B\)](#)

- Port Speed (Port B)
- Drive Model
- Drive Manufacturer
- Encryption Capable
- Drive Interface
- Drive Properties Updated
- Drive Firmware Version
- STA Start Tracking
- STA Stop Tracking

Media

Details about the media used in the drive's most recent exchange that occurred during or before this aggregation period.

- Volume Serial Number
- Media Manufacturer Serial Number
- Media Health Indicator
- Media Health Trend
- WORM/VolSafe Media
- Cleaning Media

Most Recent Exchange

Details about the drive's most recent exchange that occurred during or before this aggregation period.

- Exchange Start
- Exchange Elapsed Time
- Exchange Mount Time
- Mount R/W MB/sec
- Exchange Recording Technique
- Drive Exchange Status
- Exchange Tape Alerts – Severe
- Exchange Tape Alerts – Warning
- Exchange Tape Alerts – Info
- Data Compression Ratio
- Alert: Drive Load Limit
- Drive Suspicion Level
- Exchange Drive Cleaning Required
- Meters Between 2 Most Recent Cleans
- Meters since Last Clean

- [Drive Lifetime Cleans](#)
- [Drive Lifetime Loads](#)
- [Drive Lifetime Meters](#)
- [Drive Lifetime Power Hours](#)

Drive Activity Counts (Last 30 Days)

Total activity counts for the drive over the last 30 days. These values are updated with each completed exchange involving the drive.

- [% Drive Utilization](#)
- [Drive Dismounts](#)
- [Drive SNMP Trap Count](#)
- [Drive Alert Count](#)
- [Drive Errors](#)
- [Cleans](#)
- [MB Read](#)
- [MB Write](#)
- [MB R/W](#)
- [MB Sent](#)
- [MB Received](#)
- [Avg Mount Read MB/sec](#)
- [Avg Mount Write MB/sec](#)
- [Avg Mount R/W MB/sec](#)
- [Avg Mount Read MB](#)
- [Avg Mount Write MB](#)
- [Avg Mount R/W MB](#)

Additional Exchange Information for Enterprise Drives

Additional details about the drive's most recent exchange. This section appears only for StorageTek enterprise drives, such as 9840D or T10000C.

- [Exchange FSC](#)
- [Exchange DSC](#)
- [Exchange Write Inefficient](#)
- [Exchange Read Marginal](#)
- [Exchange Write Efficiency](#)
- [Exchange Read Margin](#)
- [Time Spent Reading](#)
- [Time Spent Writing](#)
- [Time Spent Reading or Writing](#)

- [Read MB/sec](#)
- [Write MB/sec](#)
- [R/W MB/sec](#)
- [Read Mount Ratio](#)
- [Write Mount Ratio](#)
- [R/W Mount Ratio](#)
- [Exchange Encryption Used](#)

Additional Exchange Information for LTO Drives

Additional details about the drive's most recent exchange. This section appears only for LTO drives.

- [Alert: Drive Diagnostics Required](#)
- [Drive Lifetime Hours in Motion](#)
- [IBM Media Efficiency](#)
- [IBM Drive Efficiency](#)
- [HP Device Status](#)

Drive Location

Details about the location of the drive within the library. These attributes are updated whenever a library data collection is performed.

- [Drive Library Name](#)
- [Drive Library Serial Number](#)
- [Drive Library Number](#)
- [Drive Rail Number](#)
- [Drive Physical Address](#)
- [Drive HLI Address](#)
- [Drive SCSI Element ID](#)

Library Complex

Information about the library complex where the drive is located, as of the last completed library data collection.

- [Library Complex Name](#)
- [Library Model](#)
- [Partition Type](#)
- [Partition Name](#)
- [Partition Number](#)

Media Validation Information for Enterprise Drives

Information about media validation and drive calibration and qualification operations for this drive. This section appears only for drives that have been assigned to the media validation drive pool through SL Console.

- [MV Calibration Attempts](#)
- [MV Calibration State](#)
- [MV Calibration Information](#)
- [MV Last Calibration DQI](#)
- [MV Calibration Starting Suspicion](#)
- [MV Drive Last Calibrated](#)
- [MV Last Activity](#)
- [MV Last Recommendation](#)
- [MV Drive Allocated](#)
- [MV Drive Capable](#)
- [MV Drive Available](#)
- [MV Drive In Use](#)
- [MV Drive Reserved](#)
- [MV Secondary Qualification Start](#)
- [MV Primary Qualification Start](#)

User-Provided Information

- [Logical Group\(s\)](#)
- [Annotation History](#)

Media Overview and Analysis Screens

The Media – Overview and Media – Analysis screens show attributes related to media. There is one set of attributes for StorageTek enterprise media and a slightly different set for LTO media.

The media attributes are organized into the following sections.

- ["Title"](#) on page 6-5
- ["Media Details"](#) on page 6-5
- ["Most Recent Exchange"](#) on page 6-5
- ["Media Data Activity Counts \(Last 30 Days\)"](#) on page 6-6
- ["Current Home Media Location"](#) on page 6-6
- ["Drive"](#) on page 6-7
- ["Additional Exchange Information for LTO Media"](#) on page 6-8
- ["Additional Exchange Information for Enterprise Media"](#) on page 6-7
- ["Library Complex"](#) on page 6-8
- ["Cleaning Usage"](#) on page 6-8
- ["User-Provided Information"](#) on page 6-8
- ["Media Validation Information for Enterprise Media"](#) on page 6-8
- ["Calibration Information for Enterprise Media"](#) on page 6-9

Media Overview Detail Views

Detail for Enterprise Media (part 1)

Media - Overview Templates: STA-Default

Format:

Details for Media SG0088 Monitored since 2013-04-24 12:28:55

Media Details

Volume Serial Number: **SG0703**
Media Type: **T10000T2**
Media Long Type: **T10000T2**
STA Supported: **Yes**
Media Health Indicator: **USE**
Media Health Trend: **UNCHANGED**
WORM/VolSafe Media: **No**
Media Manufacturer Serial Number: **81218605022**
STA Start Tracking: **2013-04-24 12:28:55**
STA Stop Tracking:
Media Entered Library:
Media Ejected from Library:

Media DATA Activity Counts (Last 30 Days)

Media Dismounts: **12**
Dismounts with Errors: **0**
MV Count: **0**
Media Alert Count: **0**
MB Read: **881,962.21**
MB Write: **111.65**
MB R/W: **882,073.86**
MB Sent: **261.33**
MB Received: **729,043.69**
Avg Mount Read MB/sec: **0.01**
Avg Mount Write MB/sec: **18.03**
Avg Mount R/W MB/sec: **18.04**

Current Home Media Location

Media Library Name: **elib19**
Media Library Serial Number: **516000100633**
Media Library Number: **1**
Media Rail Number: **1**
Media Physical Address: **1,1,4,1,2**
Media HLI Address:
Media Slot SCSI Element ID: **-1**

Drive

Drive Serial Number: **57600400**
Drive WWNN: **50:01:04:F0:00:**
Drive Type: **T10000c-Enc**
Drive Health Indicator: **USE**

Most Recent Exchange





Last Exchange Start: **2014-03-26 11:28:22**
Exchange Elapsed Time: **1:17:05**
Exchange Mount Time: **1:16:46**
Exchange Library Name: **elib19**
Exchange Recording Technique: **T10000C**
Media Exchange Status: **GOOD**
Exchange Tape Alerts - Severe: **0**
Exchange Tape Alerts - Warning: **0**
Exchange Tape Alerts - Info: **0**
Media Suspicion Level: **0.00%**
Exchange Drive Cleaning Required: **No**
Media Life Indicator: **GOOD**
Media EOL Percentage: **1**
Mount R/W MB/sec: **13.01**
Data Compression Ratio: **1.01 : 1**
Duplicate Detected: **No**
Alert: Media Cart Memory Failure: **No**
Alert: Media Load Limit: **No**

Additional Exchange Information for Enterprise Media

Media MB Capacity: **5,242,880.00**
Media MB Avail Post: **3,823,620.94**
Media Capacity Utilization: **27.07%**
Exchange Encryption Used: **Encrypted Sun KMS**
Exchange FSC:
Exchange DSC:
Permanent Error:
Media Blank:
Exchange Write Inefficient: **No**
Exchange Read Marginal: **No**
Exchange Write Efficiency: **100.00%**
Exchange Read Margin: **93.74%**
Time Spent Reading: **0:00:01**
Time Spent Writing: **0:04:49**
Time Spent Reading or Writing: **0:04:50**
Read MB/sec: **0.00**
Write MB/sec: **207.41**
R/W MB/sec: **206.34**

Detail for Enterprise Media (part 2)

Media - Overview Templates: STA-Default

Format:    

Library Complex Library Complex Name: SL8500_2 Library Model: SL8500 Partition Type: HLI Partition Name: SL8500_2:HLI:0 Partition Number: 0	Read Mount Ratio: 0.02% Write Mount Ratio: 6.27% R/W Mount Ratio: 6.30%
Media Validation Information for Enterprise Media Media Write Efficiency: 100.60 MV DQI: 81.18% MV Days Since Last Validation: 0 MV Last Activity: 2014-03-26 10:49:22 MV Last Test Type: Standard Verify MV Recommendation: Media OK: Continue using.	Cleaning Usage Cleaning Media: No
Calibration Information for Enterprise Media MV Calibration Library Complex: MV Calibration Library SN: MV Calibration Library Model: MV Calibration Drive Type: MV Calibration Drive SN: MV Last Calibration Date: MV Calibration Initial DQI: MV Calibration Initial Suspicion: MV Calibration Last DQI: MV Last Recording Technique: MV MB Tape Used: MV Calibration Number of Wraps: MV Primary Calibration Media: MV Calibration Current State: MV Calibration Status Information:	User-Provided Information Logical Group(s): EDC-Other Annotation History: None

Detail for LTO Media (part 1)

Media - Overview Templates: STA-Default

Format:

Details for Media LT5048 Monitored since 2014-03-25 14:46:59


Media Details	Most Recent Exchange
Volume Serial Number: LT5048	Last Exchange Start: 2014-03-26 10:08:05
Media Type: LT05	Exchange Elapsed Time: 0:15:17
Media Long Type: LtoGen5_1500GB	Exchange Mount Time: 0:14:41
STA Supported: Yes	Exchange Library Name: SL8500-169
Media Health Indicator: USE	Exchange Recording Technique: LT05
Media Health Trend: UNCHANGED	Media Exchange Status: GOOD
WORM/VolSafe Media: No	Exchange Tape Alerts - Severe: 0
Media Manufacturer Serial Number: AA6ME23RMF	Exchange Tape Alerts - Warning: 0
STA Start Trading: 2014-03-25 14:46:59	Exchange Tape Alerts - Info: 0
STA Stop Trading:	Media Suspicion Level: 0.00%
Media Entered Library:	Exchange Drive Cleaning Required: No
Media Ejected from Library:	Media Life Indicator: GOOD
	Media EOL Percentage:
	Mount R/W MB/sec: 10.83
	Data Compression Ratio: 1 : 1
	Duplicate Detected: No
	Alert: Media Cart Memory Failure: No
	Alert: Media Load Limit: No

Media DATA Activity Counts (Last 30 Days)
Media Dismounts: 5
Dismounts with Errors: 0
MV Count: 0
Media Alert Count: 0
MB Read: 9,545.26
MB Write: 28,635.79
MB R/W: 38,181.05
MB Sent: 28,608.75
MB Received: 9,536.25
Avg Mount Read MB/sec: 0.00
Avg Mount Write MB/sec: 0.00
Avg Mount R/W MB/sec: 0.00

Current Home Media Location
Media Library Name: SL8500-169
Media Library Serial Number: 516000200164
Media Library Number: 1
Media Rail Number: 4
Media Physical Address: 1,4,2,1,4

Additional Exchange Information for LTO Media
Media MB Capacity: 1,449,585.00
Media MB Avail Pre: 1,440,038.00
Media Capacity Utilization: 0.66%
IBM Media Efficiency: 0x06
HP Media Status:
Media Length in Meters: 846
Media Manufacturer Date: 2010-07-19
Media Auxiliary Memory Capacity: 8,192
Alert: Media Directory Corrupt: No
Alert: Media Nearing End of Life: No

Cleaning Usage
Cleaning Media: No



- [Last Exchange Start](#)
- [Exchange Elapsed Time](#)
- [Exchange Mount Time](#)
- [Exchange Library Name](#)
- [Exchange Recording Technique](#)
- [Media Exchange Status](#)
- [Exchange Tape Alerts – Severe](#)
- [Exchange Tape Alerts – Warning](#)
- [Exchange Tape Alerts – Info](#)
- [Media Suspicion Level](#)
- [Exchange Drive Cleaning Required](#)
- [Media Life Indicator](#)
- [Media EOL Percentage](#)
- [Mount R/W MB/sec](#)
- [Data Compression Ratio](#)
- [Duplicate Detected](#)
- [Alert: Media Cart Memory Failure](#)
- [Alert: Media Load Limit](#)

Media Data Activity Counts (Last 30 Days)

Total activity counts for the media over the last 30 days. This section appears only for data media.

- [Media Dismounts](#)
- [Dismounts With Errors](#)
- [MV Count](#)
- [Media Alert Count](#)
- [MB Read](#)
- [MB Write](#)
- [MB R/W](#)
- [MB Sent](#)
- [MB Received](#)
- [Avg Mount Read MB/sec](#)
- [Avg Mount Write MB](#)
- [Avg Mount R/W MB/sec](#)

Current Home Media Location

Details about the media's current location, as of the last completed exchange.

- [Media Library Name](#)

- [Media Library Serial Number](#)
- [Media Library Number](#)
- [Media Rail Number](#)
- [Media Physical Address](#)
- [Media HLI Address](#)
- [Media Slot SCSI Element ID](#)

Drive

Details about the drive involved in the latest exchange.

- [Drive Serial Number](#)
- [Drive WWNN](#)
- [Drive Type](#)
- [Drive Health Indicator](#)

Additional Exchange Information for Enterprise Media

Appears for StorageTek enterprise media only.

- [Media MB Capacity](#)
- [Media MB Avail Post](#)
- [Media Capacity Utilization](#)
- [Exchange Encryption Used](#)
- [Exchange FSC](#)
- [Exchange DSC](#)
- [Permanent Error](#)
- [Media Blank](#)
- [Exchange Write Inefficient](#)
- [Exchange Read Marginal](#)
- [Exchange Write Efficiency](#)
- [Exchange Read Margin](#)
- [Time Spent Reading](#)
- [Time Spent Writing](#)
- [Time Spent Reading or Writing](#)
- [Read MB/sec](#)
- [Write MB/sec](#)
- [R/W MB/sec](#)
- [Read Mount Ratio](#)
- [Write Mount Ratio](#)
- [R/W Mount Ratio](#)

Additional Exchange Information for LTO Media

Appears for LTO media only.

- [Media MB Capacity](#)
- [Media MB Avail Pre](#)
- [Media Capacity Utilization](#)
- [IBM Media Efficiency](#)
- [HP Media Status](#)
- [Media Length in Meters](#)
- [Media Manufacturer Date](#)
- [Media Auxiliary Memory Capacity](#)
- [Alert: Media Directory Corrupt](#)
- [Alert: Media Nearing End of Life](#)

Library Complex

Details about the library complex where the media is located.

- [Library Complex Name](#)
- [Library Model](#)
- [Partition Type](#)
- [Partition Name](#)
- [Partition Number](#)

Cleaning Usage

- [Cleaning Media](#)

User-Provided Information

- [Logical Group\(s\)](#)
- [Annotation History](#)

Media Validation Information for Enterprise Media

Details about the most recent media validation for the media. Appears for StorageTek enterprise media only.

- [Media Write Efficiency](#)
- [MV DQI](#)
- [MV Days Since Last Validation](#)
- [MV Last Activity](#)
- [MV Last Test Type](#)
- [MV Last Recommendation](#)

Calibration Information for Enterprise Media

- [MV Calibration Library Complex](#)
- [MV Calibration Library SN](#)
- [MV Calibration Library Model](#)
- [MV Calibration Drive Type](#)
- [MV Calibration Drive SN](#)
- [MV Last Calibration Date](#)
- [MV Calibration Initial DQI](#)
- [MV Calibration Initial Suspicion](#)
- [MV Calibration Last DQI](#)
- [MV Last Recording Technique](#)
- [MV MB Tape Used](#)
- [MV Calibration Number of Wraps](#)
- [MV Primary Calibration Media](#)
- [MV Calibration Current State](#)
- [MV Calibration Status Information](#)

Robots Overview Screen

The Robots Overview screen shows attributes related to one or more library robots.

The elevator attributes are organized into the following sections:

- ["Title"](#) on page 7-1
- ["Robot"](#) on page 7-2
- ["Robot Activity Counts \(Last 30 Days\)"](#) on page 7-2
- ["User-Provided Information"](#) on page 7-2
- ["Library Complex"](#) on page 7-2

Robots Overview Detail View

The screenshot displays the 'Library Components - Robots Overview' window. The title bar includes a help icon, a 'Format' dropdown, and a 'Templates' dropdown set to 'STA-Default'. The main content area is titled 'Details for Robot 66005635' and 'Monitored since 2014-03-25 14:52:32'. It is divided into three sections:

- Robot**:
 - Robot Identifier: **66005635**
 - Robot Physical Address: **2,4,0,2,0**
 - Robot STA Health: **MONITOR**
 - Robot Library Health: **DEGRADED**
 - Robot Library State: **READY**
 - Robot Power LED State: **ON**
- Robot Activity Counts (Last 30 Days)**:
 - Robot Get Totals: **52**
 - Robot Get Retries: **0**
 - Robot Put Totals: **52**
 - Robot Put Retries: **0**
 - Robot Alert Count: **0**
 - Robot SNMP Traps: **5**
- User-Provided Information**:
 - Annotation History: 2014-03-26 16:54:46 by admin-user: **Sample annotation for robot 66005635.**
- Library Complex**:
 - Library Complex Name: **SL8500_1**
 - Library Name: **elib3**
 - Library Serial Number: **516000000436**
 - Library Model: **SL8500**

Title

Values for these attributes are assigned when the SNMP trap is received from the library.

- [Robot](#)

- [Monitored since](#)

Robot

Details about the robot. With the exception of Robot STA Health, these attributes come directly from the library and are updated with each library configuration data collection. Robot STA Health is an analytic calculated by STA.

- [Robot Identifier](#)
- [Robot Physical Address](#)
- [Robot STA Health](#)
- [Robot Library Health](#)
- [Robot Library State](#)
- [Robot Power LED State](#)

Robot Activity Counts (Last 30 Days)

Activity totals for the robot over the last 30 days. These are updated as each associated activity is completed.

- [Robot Get Totals](#)
- [Robot Get Retries](#)
- [Robot Put Totals](#)
- [Robot Put Retries](#)
- [Robot Alert Count](#)
- [Robot SNMP Traps](#)

User-Provided Information

- [Annotation History](#)

Library Complex

Information about the library complex where the robot is located, as of the last completed library data collection.

- [Library Complex Name](#)
- [Library Name](#)
- [Library Serial Number](#)
- [Library Model](#)

CAPs Overview Screen

The CAPs Overview screen shows attributes related to one or more library CAPs, Access Expansion Modules (AEMs – SL3000 libraries only), or mailslots (SL150 libraries only).

The CAP attributes are organized into the following sections:

- ["Title"](#) on page 8-1
- ["CAP"](#) on page 8-2
- ["CAP Activity Counts \(Last 30 Days\)"](#) on page 8-2
- ["User-Provided Information"](#) on page 8-2
- ["Library Complex"](#) on page 8-2

CAPs Overview Detail View



Title

Values for these attributes are assigned when the SNMP trap is received from the library.

- [CAP](#)
- [Monitored since](#)

CAP

Details about the CAP. These attributes come directly from the library and are updated with each library configuration data collection.

- [CAP Identifier](#)
- [CAP Physical Address](#)
- [CAP Library Health](#)
- [CAP Library State](#)
- [CAP Accessibility](#)

CAP Activity Counts (Last 30 Days)

Activity totals for the CAP over the last 30 days. These are updated as each associated activity is completed.

- [CAP Ejects](#)
- [CAP Enters](#)
- [CAP SNMP Traps](#)
- [CAP Alert Count](#)

User-Provided Information

- [Annotation History](#)

Library Complex

Information about the library complex where the CAP is located, as of the last completed library data collection.

- [Library Complex Name](#)
- [Library Name](#)
- [Library Serial Number](#)
- [Library Model](#)


PTPs Overview Screen

The PTPs Overview screen shows attributes related to one or more library pass-through ports (PTPs). It is applicable to SL8500 libraries only.

The elevator attributes are organized into the following sections:

- ["Title"](#) on page 9-1
- ["PTP"](#) on page 9-2
- ["PTP Activity Counts \(Last 30 Days\)"](#) on page 9-2
- ["User-Provided Information"](#) on page 9-2
- ["Library Complex"](#) on page 9-2

PTPs Overview Detail View



Title

Values for these attributes are assigned when the SNMP trap is received from the library.

- [PTP](#)
- [Monitored since](#)

PTP

Details about the PTP. These attributes come directly from the library and are updated with each library configuration data collection.

- [PTP Identifier](#)
- [PTP Physical Address](#)
- [PTP Library Health](#)
- [PTP Library State](#)
- [PTP Power LED State](#)

PTP Activity Counts (Last 30 Days)

Activity totals for the PTP over the last 30 days. These are updated as alerts are generated and SNMP messages are received from the library.

- [PTP Alert Count](#)
- [PTP SNMP Traps](#)

User-Provided Information

- [Annotation History](#)

Library Complex

Information about the library complex where the PTP is located, as of the last completed library data collection.

- [Library Complex Name](#)
- [Library Name](#)
- [Library Serial Number](#)
- [Library Model](#)

Elevators Overview Screen

The Elevators Overview screen shows attributes related to one or more library elevators. It is applicable to SL8500 libraries only.

The elevator attributes are organized into the following sections:

- ["Title"](#) on page 10-1
- ["Elevator"](#) on page 10-2
- ["Elevator Activity Counts \(Last 30 Days\)"](#) on page 10-2
- ["User-Provided Information"](#) on page 10-2
- ["Library Complex"](#) on page 10-2

Elevators Overview Detail View



Title

Values for these attributes are assigned when the SNMP trap is received from the library.

- [Elevator](#)
- [Monitored since](#)

Elevator

Details about the elevator. These attributes come directly from the library and are updated with each library configuration data collection.

- [Elevator Identifier](#)
- [Elevator Physical Address](#)
- [Elevator Library Health](#)
- [Elevator Library State](#)
- [Elevator Power LED State](#)

Elevator Activity Counts (Last 30 Days)

Activity totals for the elevator over the last 30 days. These are updated as alerts are generated and SNMP messages are received from the library.

- [Library Complex Alert Count](#)
- [Elevator SNMP Traps](#)

User-Provided Information

- [Annotation History](#)

Library Complex

Information about the library complex where the elevator is located, as of the last completed library data collection.

- [Library Complex Name](#)
- [Library Name](#)
- [Library Serial Number](#)
- [Library Model](#)

Alerts Screens

The Alerts Overview screen shows attributes related to one or more alerts.

The alert attributes are organized into the following sections:

- ["Alert Details"](#) on page 11-1
- ["Other Details"](#) on page 11-1
- ["Alert Location Information"](#) on page 11-2
- ["User-Provided Information"](#) on page 11-2

Alerts Overview Detail View

Alerts Overview Templates: STA-Alert-All

Format: [Icons]

Alert Detail Alert Date 2014-03-25 18:33:51

Alert Details	Other Details
<p>Date: 2014-03-25 18:33:51</p> <p>Created/Updated:</p> <p>Alert Policy Name: STA-Media-Health-Monitor</p> <p>Alert Severity: Warning</p>	<p>Alert Policy Type: Media</p> <p>Component ID: STA106</p> <p>Alert State: New</p> <p>Alert Event Type: Exchange</p> <p>Alert Reason: Media Health Indicator=MONITOR AND Media Health Trend=WORSE</p> <p>Drive Serial Number: 576004000119</p> <p>Volume Serial Number: STA106</p>
<p>Alert Location Information</p> <p>Library Serial Number: 516000100633</p> <p>Library Name: elib19</p> <p>Library Complex Name: SL8500_2</p>	<p>User-Provided Information</p> <p>Annotation History:</p> <p>2014-03-26 17:13:29 by admin-user: Sample annotation for alert 2014-03-25 18:33:51.</p>

Alert Details

Details about an alert that was triggered.

- [Date Created/Updated](#)
- [Alert Policy Name](#)
- [Alert Severity](#)

Other Details

- [Alert Policy Type](#)

- [Component ID](#)
- [Alert State](#)
- [Alert Event Type](#)
- [Alert Reason](#)
- [Drive Serial Number](#)
- [Volume Serial Number](#)

Alert Location Information

- [Library Serial Number](#)
- [Library Name](#)
- [Library Complex Name](#)

User-Provided Information

- [Annotation History](#)

Exchanges Overview Screen

The Exchanges Overview screen shows attributes related to one or more exchanges. There is one view for exchanges involving StorageTek enterprise media and a slightly different view for LTO media.

The exchange attributes are organized into the following sections.

- ["Title"](#) on page 12-7
- ["Exchange Health and Activity"](#) on page 12-7
- ["Drive"](#) on page 12-8
- ["Media"](#) on page 12-8
- ["Library Complex"](#) on page 12-9
- ["Enterprise Specific Information"](#) on page 12-9
- ["Additional Enterprise Exchange Information"](#) on page 12-10
- ["LTO Specific Information"](#) on page 12-10
- ["Drive Bay Location"](#) on page 12-11
- ["Media Source Location"](#) on page 12-11
- ["Media Destination Location"](#) on page 12-11
- ["Enterprise Exchange Alerts – Severe"](#) on page 12-11
- ["Enterprise Exchange Alerts – Warning"](#) on page 12-12
- ["Enterprise Exchange Alerts – Informational"](#) on page 12-12
- ["LTO Exchange Alerts – Severe"](#) on page 12-12
- ["LTO Exchange Alerts – Warning"](#) on page 12-13
- ["LTO Exchange Alerts – Informational"](#) on page 12-14
- ["User-Provided Information"](#) on page 12-14

Exchanges Overview Detail Views

Detail for Enterprise Media Exchanges (part 1)

Exchanges Overview Templates: STA-Default

Format:

Details for Exchange Recorded on 2014-03-26 11:28:22

Exchange Health and Activity

Exchange Start: **2014-03-26 11:28:22**
 Exchange End: **2014-03-26 12:45:27**
 Exchange Elapsed Time: **1:17:05**
 Exchange Mount Time: **1:16:46**
 Drive Exchange Status: **GOOD**
 Media Exchange Status: **GOOD**
 Exchange Tape Alerts - Severe: **0**
 Exchange Tape Alerts - Warning: **0**
 Exchange Tape Alerts - Info: **0**
 Mount Read MB/sec: **0.00**
 Mount Write MB/sec: **13.01**
 Mount R/W MB/sec: **13.01**
 Mount Read MB: **0.00**
 Mount Write MB: **59,943.00**
 Mount R/W MB: **59,943.00**
 Mount Sent MB: **6.00**
 Mount Received MB: **60,718.00**
 Exchange Drive Cleaning Required: **No**
 Current Cleaning Uses:

Enterprise Specific Information

Media MB Capacity: **5,242,880.00**
 Media MB Avail Post: **3,823,620.94**
 Exchange Write Inefficient: **No**
 Exchange Read Marginal: **No**
 Write Efficiency: **100.00%**
 Read Margin: **93.74%**
 Time Spent Loaded: **1:16:21**
 Time Spent Reading: **0:00:01**
 Time Spent Writing: **0:04:49**
 Time Spent R/W: **0:04:50**
 Read MB/sec: **0.00**
 Write MB/sec: **207.41**
 R/W MB/sec: **206.70**
 Read Mount Ratio: **0.02%**
 Write Mount Ratio: **6.27%**
 R/W Mount Ratio: **6.30%**

Drive

Drive Serial Number: **576004**
 Drive Tray Serial Number: **UNKNOWN**
 Drive WWNN: **50:01:04:F0:00**
 Drive Type: **T10000c-Enc**
 Drive Model: **T10000C**
 Drive Firmware Version: **1.53.316-5.30**
 Drive Health Indicator: **USE**
 Drive Suspicion Level: **0.00%**
 Drive Health Trend: **UNCHANGED**
 Drive Lifetime Cleans: **0**
 Drive Lifetime Loads: **608**
 Drive Lifetime Meters: **2,702,979**
 Drive Lifetime Power Hours: **11,415**
 Drive Start Tracking: **2013-04-24 12:28:51**
 Drive Stop Tracking:

Media

Volume Serial Number: **SG00**
 Media Type: **T10000T2**
 Cleaning Media: **No**
 Media Manufacturer Serial Number: **812186050**
 Media Health Indicator: **USE**
 Media Suspicion Level: **0.00%**
 Media Health Trend: **UNCHANGED**
 Data Compression Ratio: **1.01 : 1**
 Exchange Recording Technique: **T10000C**
 Exchange Encryption Used: **Encrypted Sun KMS**
 Duplicate Detected: **No**
 Media Start Tracking: **2013-04-24 12:28:55**
 Media Stop Tracking:

Library Complex

Library Complex Name: **SL3000_57100**
 Library Model: **SL3000**
 Partition Type: **HLI**
 Partition Name: **SL3000_57100:HLI:0**
 Partition Number: **0**

Detail for Enterprise Media Exchanges (part 2)

Exchanges Overview Templates: STA-Default

Format:

Repositioning Cycles: 40 Repositioning Cycles Non ERP: 10	Drive Bay Location Drive Library Name: s13000-175 Drive Library Serial Number: 57100 Drive Library Number: 1 Drive Rail Number: 1 Drive Physical Address: 1,1,4,1,2 Drive HLI Address: -1 Drive SCSI Element ID: -1
Additional Enterprise Exchange Information Exchange FSC: Exchange DSC: Media Blank: No Media Write Efficiency: RQI: Permanent Error: No MV Test Type: MV Test Percentage: Perm Read Errors: 0 Perm Write Errors: 0 Servo Perm Errors: 0 Unload Errors: 0 Usage Perm Errors: 0 Drive Lifetime Meters Positioning: 496,769 Drive Lifetime Meters of Head Contact: 2,702,979	Media Source Location Media Source Library Number: 1 Media Source Rail Number: 1 Media Source Physical Address: 1,1,7,2,6 Media Source HLI Address: Media Source SCSI Element ID: -1
Enterprise Exchange Alerts - Severe Alert: Drive Clean Now: No Alert: Drive Failure Predicted: No Alert: Drive Temperature: No Alert: Media Clean Expired: No Alert: Media Error: No Alert: Media Loading Failure: No Alert: Media Maintenance: No Alert: Media No Start of Data: No Alert: Media System Read Failure: No Alert: Media System Write Failure: No Alert: Media Unrecoverable Snapped: No Alert: Permanent Error: No	Media Destination Location Media Destination Library Number: 1 Media Destination Rail Number: 1 Media Destination Physical Address: 1,1,7,2,6 Media Destination HLI Address: Media Destination SCSI Element ID: -1
Enterprise Exchange Alerts - Warning Alert: Drive FW Failure: No	Enterprise Exchange Alerts - Informational Alert: Drive Dump Available: No Alert: Drive Event Log Near Full: No Alert: Drive Load Limit: No Alert: Drive Model Incompatible: No Alert: Media End of Warranty: No Alert: Media Life Exceeded: No Alert: Media Load Limit: No

Detail for Enterprise Media Exchanges (part 3)

The screenshot displays the 'Exchanges Overview' web application. At the top, there is a header bar with the title 'Exchanges Overview', a 'Templates' dropdown menu set to 'STA-Default', and some icons. Below the header, a navigation bar shows 'Format' options (list, grid, print) and an 'Applied Filter' text: 'Drive Type Starts With T10000, or Mount R/W MB Greater Than 0'. The main content area is divided into two panels. The left panel, titled 'Enterprise Exchange Alerts - Warning', lists various alerts with their status: 'Alert: Drive FW Failure: No', 'Alert: Hard Error: No', 'Alert: Load Failure: No', 'Alert: Media Cart Memory Failure: No', 'Alert: Media Directory Invalid: No', 'Alert: Media Lost Statistics: No', 'Alert: Media MER Invalid: No', 'Alert: Media RFID Warning: No', 'Alert: Read Warning: No', and 'Alert: Write Warning: No'. The right panel contains two sections: 'Exceeded:' with 'Alert: Media Load Limit: No', and 'User-Provided Information' with 'Annotation History: None'. A vertical scrollbar is visible on the right side of the main content area.

Exchanges Overview Templates: STA-Default

Format: [List] [Grid] [Print] Applied Filter: Drive Type Starts With T10000, or Mount R/W MB Greater Than 0

Enterprise Exchange Alerts - Warning

- Alert: Drive FW Failure: **No**
- Alert: Hard Error: **No**
- Alert: Load Failure: **No**
- Alert: Media Cart Memory Failure: **No**
- Alert: Media Directory Invalid: **No**
- Alert: Media Lost Statistics: **No**
- Alert: Media MER Invalid: **No**
- Alert: Media RFID Warning: **No**
- Alert: Read Warning: **No**
- Alert: Write Warning: **No**

Exceeded:

- Alert: Media Load Limit: **No**

User-Provided Information

- Annotation History: **None**

Detail for LTO Media Exchanges (part 1)

Exchanges Overview Templates: STA-Exchange-Base-Information

Format:

Details for Exchange Recorded on 2014-03-26 09:46:32

Exchange Health and Activity	Drive	Media	LTO Specific Information	Library Complex
Exchange Start: 2014-03-26 09:46:32 Exchange End: 2014-03-26 09:58:18 Exchange Elapsed Time: 0:11:46 Exchange Mount Time: 0:11:10 Drive Exchange Status: GOOD Media Exchange Status: GOOD Exchange Tape Alerts - Severe: 0 Exchange Tape Alerts - Warning: 0 Exchange Tape Alerts - Info: 0 Mount Read MB/sec: 14.25 Mount Write MB/sec: 0.00 Mount R/W MB/sec: 14.25 Mount Read MB: 9,545.26 Mount Write MB: 0.00 Mount R/W MB: 9,545.26 Mount Sent MB: 9,536.25 Mount Received MB: 0.00 Exchange Drive Cleaning Required: No Current Cleaning Uses:	Drive Serial Number: 1068002774 Drive Tray Serial Number: unknown Drive WWNN: 50:01:04:F0:00:A0:E4:A2 Drive Type: IbmUltrium5 Drive Model: LTO5 Drive Firmware Version: D8D4 Drive Health Indicator: USE Drive Suspicion Level: 0.00% Drive Health Trend: UNCHANGED Drive Lifetime Cleans: 0 Drive Lifetime Loads: 7,232 Drive Lifetime Meters: 273,090 Drive Lifetime Power Hours: 7,935 Drive Start Tracking: 2014-03-25 14:46:48 Drive Stop Tracking:	Volume Serial Number: LT5048 Media Type: LTO5 Cleaning Media: No Media Manufacturer Serial Number: AA6ME23RMF Media Health Indicator: USE Media Suspicion Level: 0.00% Media Health Trend: UNCHANGED Data Compression Ratio: 1 : 1 Exchange Recording Technique: LTO5 Exchange Encryption Used: Duplicate Detected: No Media Start Tracking: 2014-03-25 14:46:59 Media Stop Tracking:	Media MB Capacity: 1,449,585.00 Media MB Avail Pre: 1,440,038.00 Media Length in Meters: 846 Media Manufacturer Date: 2010-07-18 18:00:00 Media Auxiliary Memory Capacity: 8,192 Formatted Density: 88	Library Complex Name: SL8500_51 Library Model: SL8500 Partition Type: HLI Partition Name: SL8500_51:HLI:0 Partition Number: 0


Detail for LTO Media Exchanges (part 2)

Exchanges Overview Templates: STA-Exchange-Base-Information

Format:

Code: Lifetime Hours: 0 Incompatible: Drive Lifetime Hours in Motion: 20 IBM Drive Efficiency: 0x21 IBM Media Efficiency: 0x05 HP Device Status: HP Media Status:	Drive Bay Location Drive Library Name: SL8500-169 Drive Library Serial Number: 516000200164 Drive Library Number: 1 Drive Rail Number: 4 Drive Physical Address: 1,4,2,1,4 Drive HLI Address: 3,1,15 Drive SCSI Element ID: -1
LTO Exchange Alerts - Severe Alert: Drive Automated Interface: No Alert: Drive Clean Now: No Alert: Drive Cooling Fan: No Alert: Drive Failure Predicted: No Alert: Drive Hardware A: No Alert: Drive Hardware B: No Alert: Drive Interface Fault: No Alert: Drive Temperature: No Alert: Media Clean Expired: No Alert: Media Eject Failed: No Alert: Media Error: No Alert: Media Loading Failure: No Alert: Media No Start of Data: No Alert: Media Recoverable Mechanical: No Alert: Media System Read Failure: No Alert: Media System Write Failure: No Alert: Media Unrecoverable: No	Media Source Location Media Source Library Number: 1 Media Source Rail Number: 2 Media Source Physical Address: 1,2,15,2,10 Media Source HLI Address: 1,0,9,0 Media Source SCSI Element ID: -1
	Media Destination Location Media Destination Library Number: 1 Media Destination Rail Number: 2 Media Destination Physical Address: 1,2,15,2,10 Media Destination HLI Address: 1,0,9,0 Media Destination SCSI Element ID: -1
	LTO Exchange Alerts - Informational Alert: Cleaning Media: No Alert: Drive FW Download: No Alert: Drive Load Limit: No Alert: Forced Eject Attempted: No Alert: Invalid Cleaning: No Alert: Media Diminished Capacity: No Alert: Media Life Exceeded: No Alert: Media Load Limit: No Alert: Media Nearing End of Life: No Alert: Read Only: No Alert: Unload Prevented: No Alert: Unsupported Format: No Alert: Write Protect: No

Detail for LTO Media Exchanges (part 3)



Title

Values for these attributes are assigned at the start of the exchange.

- [Recorded on](#)

Exchange Health and Activity

Details about the media and drive health during the exchange

- [Exchange Start](#)
- [Exchange End](#)
- [Exchange Elapsed Time](#)
- [Exchange Mount Time](#)
- [Drive Exchange Status](#)
- [Media Exchange Status](#)
- [Exchange Tape Alerts – Severe](#)

- [Exchange Tape Alerts – Warning](#)
- [Exchange Tape Alerts – Info](#)
- [Mount Read MB/sec](#)
- [Mount Write MB/sec](#)
- [Mount R/W MB/sec](#)
- [Mount Read MB](#)
- [Mount Write MB](#)
- [Mount R/W MB](#)
- [Mount Sent MB](#)
- [Mount Received MB](#)
- [Exchange Drive Cleaning Required](#)
- [Current Cleaning Uses](#)

Drive

Details about the drive involved in the exchange.

- [Drive Serial Number](#)
- [Drive Tray Serial Number](#)
- [Drive WWNN](#)
- [Drive Type](#)
- [Drive Model](#)
- [Drive Firmware Version](#)
- [Drive Health Indicator](#)
- [Drive Suspicion Level](#)
- [Drive Health Trend](#)
- [Drive Lifetime Cleans](#)
- [Drive Lifetime Loads](#)
- [Drive Lifetime Meters](#)
- [Drive Lifetime Power Hours](#)
- [Drive Start Tracking](#)
- [Drive Stop Tracking](#)

Media

Details about the media involved in the exchange.

- [Volume Serial Number](#)
- [Media Type](#)
- [Cleaning Media](#)
- [Media Manufacturer Serial Number](#)

- [Media Health Indicator](#)
- [Media Suspicion Level](#)
- [Media Health Trend](#)
- [Data Compression Ratio](#)
- [Exchange Recording Technique](#)
- [Exchange Encryption Used](#)
- [Duplicate Detected](#)
- [Media Start Tracking](#)
- [Media Stop Tracking](#)

Library Complex

Information about the library complex where the exchange occurred. The information is current as of the last completed library data collection.

- [Library Complex Name](#)
- [Library Model](#)
- [Partition Type](#)
- [Partition Name](#)
- [Partition Number](#)

Enterprise Specific Information

Information specific to the StorageTek enterprise drive involved in the exchange. Appears only if the exchange involved an enterprise drive.

- [Media MB Capacity](#)
- [Media MB Avail Post](#)
- [Exchange Write Inefficient](#)
- [Exchange Read Marginal](#)
- [Write Efficiency](#)
- [Read Margin](#)
- [Time Spent Loaded](#)
- [Time Spent Reading](#)
- [Time Spent Writing](#)
- [Time Spent R/W](#)
- [Read MB/sec](#)
- [Write MB/sec](#)
- [R/W MB/sec](#)
- [Read Mount Ratio](#)
- [Write Mount Ratio](#)
- [R/W Mount Ratio](#)

- [Repositioning Cycles](#)
- [Repositioning Cycles Non ERP](#)

Additional Enterprise Exchange Information

Information about errors that occurred during the exchange. Appears only if the exchange involved a StorageTek enterprise drive.

- [Exchange FSC](#)
- [Exchange DSC](#)
- [Media Blank](#)
- [Media Write Efficiency](#)
- [RQI](#)
- [Permanent Error](#)
- [MV Test Type](#)
- [MV Test Percentage](#)
- [Perm Read Errors](#)
- [Perm Write Errors](#)
- [Servo Perm Errors](#)
- [Unload Errors](#)
- [Usage Perm Errors](#)
- [Drive Lifetime Meters Positioning](#)
- [Drive Lifetime Meters of Head Contact](#)

LTO Specific Information

Information specific to the LTO drive involved in the exchange. Appears only if the exchange involved an LTO drive.

- [Media MB Capacity](#)
- [Media MB Avail Pre](#)
- [Media Length in Meters](#)
- [Media Manufacturer Date](#)
- [Media Auxiliary Memory Capacity](#)
- [Formatted Density Code](#)
- [Lifetime Hours Incompatible](#)
- [Drive Lifetime Hours in Motion](#)
- [IBM Drive Efficiency](#)
- [IBM Media Efficiency](#)
- [HP Device Status](#)
- [HP Media Status](#)

Drive Bay Location

Location of the drive involved in the exchange.

- [Drive Library Name](#)
- [Drive Library Serial Number](#)
- [Drive Library Number](#)
- [Drive Rail Number](#)
- [Drive Physical Address](#)
- [Drive HLI Address](#)
- [Drive SCSI Element ID](#)

Media Source Location

Location of the media at the start of the exchange; the location immediately before the mount. Can be a media slot or drive.

- [Source Library Number](#)
- [Source Rail Number](#)
- [Source Physical Address](#)
- [Source HLI Address](#)
- [Source SCSI Element ID](#)

Media Destination Location

Location of the media at the completion of the exchange. This is the first location immediately after the dismount from the drive, therefore it is always in the same library where the exchange occurred. The location can be a media slot or drive.

- [Destination Library Number](#)
- [Destination Rail Number](#)
- [Destination Physical Address](#)
- [Destination HLI Address](#)
- [Destination SCSI Element ID](#)

Enterprise Exchange Alerts – Severe

Information about severe errors that occurred during the exchange. This section appears for enterprise drives only.

- [Alert: Drive Clean Now](#)
- [Alert: Drive Failure Predicted](#)
- [Alert: Drive Temperature](#)
- [Alert: Media Clean Expired](#)
- [Alert: Media Error](#)
- [Alert: Media Loading Failure](#)

- [Alert: Media Maintenance](#)
- [Alert: Media No Start of Data](#)
- [Alert: Media System Read Failure](#)
- [Alert: Media System Write Failure](#)
- [Alert: Media Unrecoverable Snapped](#)
- [Alert: Permanent Error](#)

Enterprise Exchange Alerts – Warning

Information about warning errors that occurred during the exchange. This section appears for enterprise drives only.

- [Alert: Drive FW Failure](#)
- [Alert: Drive Hard Error](#)
- [Alert: Media Loading Failure](#)
- [Alert: Media Cart Memory Failure](#)
- [Alert: Media Directory Invalid](#)
- [Alert: Media Lost Statistics](#)
- [Alert: MIR Invalid](#)
- [Alert: Media RFID Warning](#)
- [Alert: Read Warning](#)
- [Alert: Write Warning](#)

Enterprise Exchange Alerts – Informational

Information about informational errors that occurred during the exchange. This section appears for enterprise drives only.

- [Alert: Drive Dump Available](#)
- [Alert: Drive Event Log Near Full](#)
- [Alert: Drive Load Limit](#)
- [Alert: Drive Model Incompatible](#)
- [Alert: Media End of Warranty](#)
- [Alert: Media Life Exceeded](#)
- [Alert: Media Load Limit](#)

LTO Exchange Alerts – Severe

Information about severe errors that occurred during the exchange. This section appears for LTO drives only.

- [Alert: Drive Automated Interface](#)
- [Alert: Drive Clean Now](#)
- [Alert: Drive Cooling Fan](#)

- Alert: Drive Failure Predicted
- Alert: Drive Hardware A
- Alert: Drive Hardware B
- Alert: Drive Interface Fault
- Alert: Drive Temperature
- Alert: Media Clean Expired
- Alert: Media Eject Failed
- Alert: Media Error
- Alert: Media Loading Failure
- Alert: Media No Start of Data
- Alert: Media Recoverable Mechanical
- Alert: Media System Read Failure
- Alert: Media System Write Failure
- Alert: Media Unrecoverable Mechanical
- Alert: Read Failure
- Alert: Unrecoverable Unload
- Alert: Write Failure

LTO Exchange Alerts – Warning

Information about informational errors that occurred during the exchange. This section appears for LTO drives only.

- Alert: Drive Clean Periodic Requested
- Alert: Drive Diagnostics Required
- Alert: Drive Dual-Port Interface
- Alert: Drive FW Failure
- Alert: Drive Voltage
- Alert: Drive Hard Error
- Alert: Media Cart Memory Failure
- Alert: Media Directory Corrupt
- Alert: Media Directory Invalid
- Alert: Media Lost Statistics
- Alert: Media Not Data Grade
- Alert: Read Warning
- Alert: WORM Integrity Failure
- Alert: WORM Overwrite Attempted
- Alert: Write Warning

LTO Exchange Alerts – Informational

Information about informational errors that occurred during the exchange. This section appears for LTO drives only.

- [Alert: Cleaning Media](#)
- [Alert: Drive FW Download](#)
- [Alert: Drive Load Limit](#)
- [Alert: Forced Eject Attempted](#)
- [Alert: Invalid Cleaning](#)
- [Alert: Media Diminished Capacity](#)
- [Alert: Media Life Exceeded](#)
- [Alert: Media Load Limit](#)
- [Alert: Media Nearing End of Life](#)
- [Alert: Read Only](#)
- [Alert: Unload Prevented](#)
- [Alert: Unsupported Format](#)
- [Alert: Write Protect](#)

User-Provided Information

- [Annotation History](#)

Drive Cleanings Overview Screen

The Drive Cleanings Overview screen shows attributes related to drive cleaning exchanges.



Note: Cleaning media are not required to have a volser starting with "CLN".

The attributes are organized into the following sections.

- ["Title"](#) on page 13-2
- ["Drive"](#) on page 13-2
- ["Cleaning Activity"](#) on page 13-3
- ["Library"](#) on page 13-3
- ["User-Provided Information"](#) on page 13-3

Drive Cleanings Overview Detail View

Drive Cleanings Overview Templates: STA-Default

Format:  

Details about a drive clean Recorded on 2014-03-26 04:33:54

Drive	Cleaning Activity
Drive Type: T10000b-Enc Drive Serial Number: 572004 Drive WWNN: 50:01:04:F0:00 Drive WWPN (Port A): 50:01:04:F0:00 Drive WWPN (Port B): Drive Health Indicator: MONITOR Exchange Drive Cleaning Required: No Drive Lifetime Cleans: 96 Drive Lifetime Loads: 2,743 Drive Lifetime Meters: 16,797,530 Drive Start Tracking: 2013-04-05 10:24:56 Drive Stop Tracking:	Clean Volume Serial Number: CLN010 Media Health Indicator: USE Meters Between 2 Most Recent Cleans: 309,351 Current Cleaning Uses: 21 Theoretical Maximum Usage Count: 50 Alert: Media Clean Expired: No Exchange Start: 2014-03-26 04:33:54 Exchange End: 2014-03-26 04:38:34 Exchange Elapsed Time: 0:04:40 Exchange Mount Time: 0:00:06 Drive Exchange Status: GOOD Media Exchange Status: GOOD Exchange FSC:

Library	User-Provided Information
Library Complex Name: SL3000_5710 Library Name: aue Library Model: SL3000 Library Serial Number: 57100 Library WWNN: 50:01:04:F0:00	Annotation History: 2014-03-26 17:40:51 by Sample annotation for clean 2014-03-26 admin: 04:33:54.

Title

Values for these attributes are assigned when the cleaning action starts.

- [Recorded on](#)

Drive

Details about the drive involved in the cleaning action.

- [Drive Type](#)
- [Drive Serial Number](#)
- [Drive WWNN](#)
- [Drive WWPN \(Port A\)](#)
- [Drive WWPN \(Port B\)](#)
- [Drive Health Indicator](#)
- [Exchange Drive Cleaning Required](#)
- [Drive Lifetime Cleans](#)
- [Drive Lifetime Loads](#)
- [Drive Lifetime Meters](#)
- [Drive Start Tracking](#)
- [Drive Stop Tracking](#)

Cleaning Activity

Details about the drive clean exchange.

- [Clean Volume Serial Number](#)
- [Media Health Indicator](#)
- [Meters Between 2 Most Recent Cleans](#)
- [Current Cleaning Uses](#)
- [Theoretical Maximum Usage Count](#)
- [Alert: Media Clean Expired](#)
- [Exchange Start](#)
- [Exchange End](#)
- [Exchange Elapsed Time](#)
- [Exchange Mount Time](#)
- [Drive Exchange Status](#)
- [Media Exchange Status](#)
- [Exchange FSC](#)

Library

Details about the library where the drive clean took place.

- [Library Complex Name](#)
- [Library Name](#)
- [Library Model](#)
- [Library Serial Number](#)
- [Library WWNN](#)


User-Provided Information

- [Annotation History](#)

Media Validation Overview Screen

The Media Validation Overview screen shows details about media validation activity. This screen does not have a detail view.

Media Validation Overview List View



The screenshot shows the 'Media Validation Overview' window. At the top, it says 'Media Validation Status: Media Validation Enabled: Opted-out of Drive Calibration.' Below this is a table with the following columns: MV Priority Order, Volume Serial Number, MV Time Spent Validating, MV Estimated Time Remaining, Exchange Start, MV Test Type, and MV Request State. The table contains 10 rows of data, all with a 'Completed' state. A status bar at the bottom right indicates 'Displaying 65 of 65 record(s)'.

MV Priority Order	Volume Serial Number	MV Time Spent Validating	MV Estimated Time Remaining	Exchange Start	MV Test Type	MV Request State
	STA119	0:19:45.0		2014-03-25 18:17:00	Standard Verify	Completed
	STA110	0:16:30.7		2014-03-25 17:26:21	Standard Verify	Completed
	STA109	0:16:24.1		2014-03-25 18:45:42	Standard Verify	Completed
	TCS390	0:13:07.8		2014-03-25 16:05:19	Standard Verify	Completed
	STA118	0:12:44.8		2014-03-25 18:50:32	Standard Verify	Completed
	STA118	0:12:44.8		2014-03-26 10:36:47	Standard Verify	Completed
	STA104	0:12:28.6		2014-03-25 17:02:37	Standard Verify	Completed
	STA114	0:09:03.2		2014-03-25 17:32:27	Standard Verify	Completed
	STA115	0:07:39.1		2014-03-25 17:44:37	Standard Verify	Completed

Media Validation Attribute Definitions

- MV Priority Order
- Volume Serial Number
- MV Time Spent Validating
- MV Estimated Time Remaining
- Exchange Start
- MV Test Type
- MV Request State
- MV Result
- MV Interrupted
- MV Incomplete
- MV Status Information

- MV Recommendation
- MV DQI
- Permanent Error
- MV Initiator
- MV Policy Name
- Drive Serial Number
- Media Type
- Exchange Recording Technique
- MV Request Start
- MV Test Percentage
- MV Last State Update
- Exchange FSC
- Exchange DSC
- MV Library Error
- Drive Model
- MV Calibration Request
- Library Complex Name
- Media Library Name
- Library Model
- Media Library Serial Number

Messages Screens

The Messages screens show attributes relating to SNMP traps received by STA from the libraries. The following screens show different views of these attributes:

- Libraries – Messages
- Drives – Messages
- Media – Messages
- All Messages – Overview
- All Messages – Analysis

The attributes on the All Messages – Overview detail view are organized into the following sections.

- ["Title"](#) on page 15-2
- ["Trap Details"](#) on page 15-2
- ["Drive Trap Details"](#) on page 15-2
- ["Library Trap Details"](#) on page 15-3
- ["Library"](#) on page 15-3
- ["Library Configuration Details"](#) on page 15-3
- ["User-Provided Information"](#) on page 15-3

All Messages Overview Detail View

All Messages - Overview Templates: STA-Default

Format: [Icons]

Details for SNMP Trap Library Log Received on 2014-03-26 11:17:04

Trap Details

Trap Type: **Library Log**
 Device State:
 Device Address: **1.1.-2.1.2**

Library Trap Details

Library Top Level: **UNKNOWN**
 Condition:
 Device ID: **HBC 66000317**
 Device Time: **2014-03-26 04:48:04**
 Username: **root**
 Interface Name: **hli0**
 Device Activity: **queryDrive**
 Request ID: **26293001**
 Severity: **error**
 Result Code: **3955**
 Text: **"Error from device Code: 604 - Drive is not functional", Data="1833285" final="true">getStateIdentifier="1">error64061,1,-2,1,2: getState FAILED, resultCode = 6406 | |>604notCommunicatingtruefalsefalsefalse**
 Agent Boot Date/Time:

Drive Trap Details

Drive Type: **Stk9840b**
 Drive Vendor: **StorageTek**
 Device Serial Number: **461000027594**

Library

Library Complex Name: **SL8500_53**
 Library Complex Number: **53**
 Library Name: **sl8500-163**
 Library Model: **SL8500**
 Library Serial Number: **516000000442**

Library Configuration Details

Property Name:
 New Property Value:
 New Property Effective:

User-Provided Information

Annotation History:
 2014-03-26 17:18:23 by admin-user: **Sample annotation for message 2014-03-26 11:17:04.**

Title

Values for these attributes are assigned when the SNMP trap is received from the library.

- [SNMP Trap](#)
- [Received on](#)

Trap Details

Provides information about the type of SNMP trap and the device involved.

- [Trap Type](#)
- [Device State](#)
- [Device Address](#)

Drive Trap Details

- [Drive Type](#)
- [Drive Vendor](#)
- [Device Serial Number](#)

Library Trap Details

Provides detailed information from the SNMP trap.

- [Library Top Level Condition](#)
- [Device ID](#)
- [Device Time](#)
- [Username](#)
- [Interface Name](#)
- [Device Activity](#)
- [Request ID](#)
- [Severity](#)
- [Result Code](#)
- [Text](#)
- [Agent Boot Date/Time](#)

Library

Provides information about the library that sent the SNMP trap.

- [Library Complex Name](#)
- [Library Complex Number](#)
- [Library Name](#)
- [Library Model](#)
- [Library Serial Number](#)

Library Configuration Details

- [Property Name](#)
- [New Property Value](#)
- [New Property Effective](#)

User-Provided Information

- [Annotation History](#)

