

# **Oracle Health Insurance**

**Custom Development for**

**Oracle Health Insurance Back Office**

version 1.1

Part number: E54856-01

July 17, 2014

Copyright © 2014, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

#### **U.S. GOVERNMENT RIGHTS**

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are “commercial computer software” or “commercial technical data” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Where an Oracle offering includes third party content or software, we may be required to include related notices. For information on third party notices and the software and related documentation in connection with which they need to be included, please contact the attorney from the Development and Strategic Initiatives Legal Group that supports the development team for the Oracle offering. Contact information can be found on the Attorney Contact Chart.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your beta trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Software License and Service Agreement, which has been executed and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

# CHANGE HISTORY

Release	Version	Changes
10.14.1.0.0	1.0	Creation
10.14.1.0.0	1.1	Minor adjustments

---

# Contents

1.	Introduction.....	1
1.1.	Audience.....	1
1.2.	Scope .....	1
1.3.	Documentation .....	2
1.4.	References.....	2
2.	Overview .....	3
2.1.	Business Rules.....	4
2.2.	An Open Database.....	4
2.3.	Flex Fields .....	5
2.4.	Dynamic PL/SQL.....	5
2.5.	Business Event Framework.....	6
2.6.	Custom Batch Scripts .....	6
2.7.	HTTP Links .....	6
2.8.	OHI Back Office Business Services.....	6
3.	An Open database .....	7
3.1.	Tables and views .....	7
3.2.	Authorization.....	8
3.3.	Datamodel help .....	9
3.4.	Modification logging.....	11
3.5.	Tracing .....	18
4.	Flex fields.....	19
4.1.	Concepts .....	19
4.2.	Flex Field Characteristics.....	20
4.3.	Flex field definition .....	21
4.4.	Flex field maintenance .....	23
5.	Dynamic PLSQL .....	25
5.1.	Hooks for PL/SQL code.....	25
5.2.	Dynamic PLSQL Definition .....	25
5.3.	Column bound checks .....	27
5.4.	Writing custom code .....	32
6.	Business Event Framework.....	34
6.1.	Overview .....	34
6.2.	Signaling Events .....	34
6.3.	Responding to Events .....	35
6.4.	Combining Signaling and Response Types .....	35
6.5.	Framework Components.....	36
6.6.	Developing Your Own Business Events.....	40
6.7.	Processing Business Events.....	44
6.8.	Examples.....	45
7.	Custom Batch Scripts .....	52
7.1.	Approach .....	52
7.2.	Batch user .....	53

7.3.	Registration .....	53
7.4.	Export script definition.....	55
7.5.	Generator: Bulk Processing Batch - Overview .....	55
7.6.	Generator: Bulk Processing Batch - Details.....	57
7.7.	Generator: CSV Export Batch.....	62
7.8.	Generator: CSV Import Batch .....	63
7.9.	Generator: XML Import batch .....	63
7.10.	Other output scripts .....	63
8.	HTTP Links.....	64
8.1.	Configuration.....	64
9.	OHI Back Office Business Services.....	68
9.1.	Architecture.....	68
9.2.	Implementation.....	68
9.3.	Find, Get and Write Services.....	69
9.4.	Service consumers .....	69
9.5.	Write Services.....	70
9.6.	Error Handling.....	73
10.	Custom Development Practices.....	74
10.1.	Create a custom schema .....	74
10.2.	Use an abstraction layer.....	74
10.3.	Define your transactions.....	75
10.4.	Locking .....	76
10.5.	Use Named Parameters .....	76
10.6.	Profile your code .....	77
10.7.	Close open cursors .....	77
10.8.	Coding Standards.....	77
11.	Deprecated Interfacing options .....	78
12.	Appendix A - Business event framework datamodel.....	1
13.	Appendix B - Business event interface ALG_EVENT_INTERFACE_PCK.....	4
14.	Appendix C – Tracing .....	2
14.1.	Activation .....	2
14.2.	How to Access Trace Logs.....	2
14.3.	Instrumentation of Custom Code.....	3
15.	Appendix D – What you should know about CDM RuleFrame.....	4
16.	Appendix E – Modification Mechanism for Policies and Relations .....	5
17.	Appendix F – Dynamic PL/SQL Types.....	6

---

# 1. Introduction

One of the strengths of the Oracle Health Insurance Back Office application is the possibility to customize the application.

Much of the behavior of the application can be influenced through configuration parameters.

If this is not enough, the application offers facilities to

- Extend the standard data model with flex fields;
- Include custom developed code into the standard processes;
- Define and process custom-defined events;
- Develop custom applications to integrate with OHI Back Office through web services; or
- Develop PL/SQL code to directly access OHI Back Office data

The purpose of this document is to describe these options and help you decide how to customize OHI Back Office to your needs.

## 1.1. Audience

This document is primarily written as a technical reference for anyone who needs to integrate with OHI Back Office or to augment the standard process.

Since this document describes the various options to integrate with OHI Back Office it may also be of interest to application managers .

The document assumes familiarity with:

- Basic OHI Back Office functionality
- Relational database concepts
- SQL and PL/SQL

Also the document assumes access to the OHI Back Office Online Help.

## 1.2. Scope

Within scope:

- Best practices for custom development and customization
- SVL web services
- How to organize custom code.

Out of scope:

- Configuration of OHI Back Office
- Localization (translation, application code for local jurisdiction).
- Post-processing XML
- Client applications
- Interfacing with BI
- Self-service applications

- C2B web services
- Coding standards
- Version control for custom developed code.
- How to set up a custom schema and access rights.

### 1.3. Documentation

You may find more detailed documentation at <http://docs.oracle.com>:

- Browse <http://docs.oracle.com>
- Search 'Applications > Insurance > Health > Oracle Health Insurance Back Office Manuals'

Also use OHI Back Office Online Help to get:

- Functional information about the topics
- The menu path of the mentioned screens in this document


### 1.4. References

DocRef	Document
<b>Doc[1]</b>	Back Office Service Layer Installation & Configuration Manual (docs.oracle.com)
<b>Doc[2]</b>	Back Office Service Layer User Manual (docs.oracle.com)
<b>Doc[3]</b>	Oracle Health Insurance Back Office Installation, Configuration & DBA Manual (docs.oracle.com)

## 2. Overview

OHI Back Office is an 'all in one' engine to process claims for health care payers. The health care is provided by providers who may be contracted beforehand by the health care payer.


In most cases, the members are policy holders for which they pay premiums. So product definition, health care and collection of premiums are core processes as well.



**Figure 1: OHI Back Office 'all-in-one' core processes.**

We call OHI Back Office an 'all-in-one' application, because all data, business rules and logic to support the core processes reside in a single database. This all-in-one approach allows maximum consistency for OHI Back Office data and is instrumental for achieving a high 'straight-through processing' (STP) ratio.

The OHI Back Office GUI application allows back office personnel to perform data entry, adjudication and run background processes. Much of the application logic for these tasks is implemented in the database.



**Figure 2: OHI Back Office GUI components**

Although OHI Back Office is an 'all-in-one' application it is by no means a black box. To work for a given customer OHI Back Office provides several possibilities for customization. To work in an environment with other applications, OHI Back Office provides various integration facilities. This chapter gives you an overview of these customization and integration facilities.



## 2.1. Business Rules

### 2.1.1. CDM ruleframe

---

Business rules are used to keep the OHI Back Office data in a consistent state for every DML operation. The OHI Back Office has many thousands of business rules which are implemented through CDM RuleFrame. Their execution is largely controlled by database triggers. With so many business rules there are bound to be many interdependencies, which means that business rules must not be disabled except by OHI Back Office personnel.

Much of the processing of the business rules takes place when the transaction is committed to the database. This means that transactions should be defined as logical units to prevent that (seemingly) unrelated business rules are triggered by closing a transaction.

Because of their implementation in the database, business rules are tightly integrated with the data. This results in optimum performance. And, since the business rules apply to every DML operation on OHI Back Office objects, we created an 'Open Database' which you can access with (virtually) any tool.

Finally, business rules help to avoid redundant code. Since they are automatically applied, most application code does not need to be aware of the underlying business rules. This makes it easier for us to maintain and control our application code.

It also makes it viable for you to create custom code for OHI Back Office.

### 2.1.2. How to determine the set of rules on a table

---

There are many types of business rules like attribute rules, tuple rules, dynamic rules and static rules.

There are several ways to determine the set of business rules on a given table.

- When available use the repository object browser on top of Oracle Designer
- Check the constraint definitions in the data dictionary
- Look in alg#business\_rules for the more complex static business rules, these are rules that can be validated at any moment in time
- Query on the system messages, business rule messages have the following format:
  - Start with a three letter application system prefix
  - Followed by \_BR\_
  - Followed by the three letter table alias which can be found in the column table\_alias in ALG\_TABELLEN for the given tablename
  - Followed by a three digit sequence number.
  - Followed by the classification of the rule.
  - ```
SELECT *
FROM ALG_SYSTEEM_MELDINGEN
WHERE CODE like '%\_BR\_%' escape '\'
```

## 2.2. An Open Database

You may directly access the OHI Back Office database because the business rules, implemented in the database itself, work as a protective shield.

You can either use the PL/SQL API packages direct access to the tables to access the OHI BackOffice data, provided that you:

- Do not use the OHI Back Office schema owner to connect to the database (use a custom schema instead).
- Do not change the table definitions, types, packages or other database objects owned by the OHI Back Office schema.
- Do not create custom grants from OHI Back Office database objects to your own schema.
- Do not disable business rules.
- Do not insert, update or delete records from technical tables (including log and audit tables).

You can use and access every object which has been granted to you without violating the above rules.

You can use any tool or interface to access the OHI Back Office as long as the underlying interface is supported by Oracle (for example OCI, ODBC, JDBC, SQLNet, ODP.net).

## 2.3. Flex Fields

As a standard solution for healthcare payers, the OHI Back Office data model cannot be altered. However, the OHI Back Office data model can be extended with so-called flex fields to register additional customer-specific data, for example to record when members had their last health check or to register parameters for interfacing with providers.

These flex fields have the following benefits:

- The core data model stays unchanged, which means that OHI Back Office can support the application as sold to the customer.
- The customer does not need to create a secondary data model, the data of which must be kept in sync with the OHI Back Office database.

Historically, flex fields were used for claims line processing and to add extra data to policies and relation data. Soon after, flex field implementations were created for other tables.

Flex field support will be extended in future releases.

## 2.4. Dynamic PL/SQL

OHI Back Office's support for dynamic PL/SQL is a powerful mechanism which allows the customer to add customer-specific code to the core OHI Back Office product.

OHI Back Office has defined several 'hooks' in OHI Back Office where custom code can be added:

- Data entry validation.
- Address entry and formatting.
- Trigger conditions for business event framework.
- Core processes such as claims processing, policy collection and payment processing.

Apart from adding a high level flexibility to the customer our support of dynamic PL/SQL helps to keep the amount of code in the standard product under control.

## 2.5. Business Event Framework

With the Business Event Framework you can define customer-specific events and event handlers.

These events can be time-based, triggered by a change or created by your custom-designed detection mechanism.

The handlers can be run near real-time or in batch processing mode and are implemented through custom PL/SQL code.


## 2.6. Custom Batch Scripts

OHI Back Office allows you to create your own batch processing scripts and run them with the standard batch scheduler.

You are advised to use the built-in OHI Back Office script generator to generate a framework to control the execution of your custom code, especially if you expect to be processing large data volumes. The generated framework helps to process large volumes in manageable chunks and provide the same kind of feedback as the standard scripts.

## 2.7. HTTP Links

HTTP Links allow users of the OHI Back Office GUI Application to view or process related data in an external application. For each HTTP link you can configure a HTTP request template to the target application and the OHI screens which will display the HTTP link.



**Figure 3: Toolbar with HTTP links**

At runtime the HTTP link will open an extra browser window to send a HTTP request to the target application, substituting placeholders with runtime values derived from the current OHI screen.

Note that the target application must be an HTTP application!

## 2.8. OHI Back Office Business Services

The OHI Back Office Business Services add integration facilities for use in a service oriented environment. The business services are part of a service layer for retrieving and updating core OHI Back Office data.

The 'Find' and 'Get' services are used to retrieve data from OHI Back Office. 'Write' services are used to store data in the OHI Back Office database.

OHI BO Business Services are implemented as PL/SQL services and made available through synchronous SOAP/HTTP web services.

Note that the OHI Back Office Business Services are not related to the older OHI Connect2BackOffice (C2B) services.

### 3. An Open database

You may directly access the OHI Back Office database because the business rules, implemented in the database itself, work as a protective shield.

You may use DML, PL/SQL API packages, or database views to access the OHI BackOffice data, provided that you:

- Do not use the OHI Back Office schema owner to connect to the database (use a custom schema instead);
- Do not change the table definitions, types, packages or other database objects owned by the OHI Back Office schema;
- Do not create custom grants from OHI Back Office database objects to your own schema;
- Do not disable business rules;
- Do not insert, update or delete records from technical tables (including log and audit tables).

You can use and access every object which has been granted to you without violating the above rules.

You can use any tool or interface to access the OHI Back Office as long as the underlying interface is supported by Oracle (for example OCI, ODBC, JDBC, SQLNet, ODP.net).

#### 3.1. Tables and views

##### 3.1.1. Tables

These are the different table types in OHI Back Office:

- 'Functional' tables
  - All DML operations permitted
  - organized by functional area (aka sub system) like ALG, FSA, GEB or VER
- Technical tables: internal use only by OHI Back Office
- Logging tables:
  - used for tracking changes to the functional tables.
  - No DML operations permitted

The following naming convention is used to recognize each table type:

| Type       | Name format          | DML? | Characteristics                                                                                                 |
|------------|----------------------|------|-----------------------------------------------------------------------------------------------------------------|
| Functional | <SUB SYSTEM>_<NAME>  | Yes  | <ul style="list-style-type: none"><li>• Functional</li><li>• Rule layer</li><li>• Column level grants</li></ul> |
| Logging    | <SUB SYSTEM>\$<NAME> | No   | <ul style="list-style-type: none"><li>▪ Data changes</li><li>▪ On demand</li></ul>                              |
| Technical  | <SUB SYSTEM>#<NAME>  | No   | <ul style="list-style-type: none"><li>• Process</li></ul>                                                       |

### 3.1.2. Views

A similar naming convention is used for the different OHI Back Office view types:

| Type        | Name format                | Characteristics                                                                                                                                                               |
|-------------|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| System      | ALG_<NAME>_SVW             | <ul style="list-style-type: none"><li>• Fixed column list</li><li>• Customizable from and where clause</li></ul>                                                              |
| Financial   | FVS_<NAME>_Sn_VW           | <ul style="list-style-type: none"><li>▪ For determination of General Ledger data</li><li>▪ Per financial fact type</li><li>▪ At least three fixed mandatory columns</li></ul> |
| English     | <SUB SYSTEM>#<NAME>_       | <ul style="list-style-type: none"><li>▪ 1:1 view on functional table</li><li>▪ International (English) name and column names</li></ul>                                        |
| English     | <SUB SYSTEM>#<TABLENAME>\$ | <ul style="list-style-type: none"><li>▪ 1:1 view of logging table</li><li>▪ International (English) name and column names</li></ul>                                           |
| Translation | <SUB SYSTEM>_<ALIAS>_VW    | <ul style="list-style-type: none"><li>▪ Translated values</li><li>▪ Public synonym to underlying table</li></ul>                                                              |



**Tip:** Query the ALG\_TABELLEN table to find the international view name for each table.

## 3.2. Authorization

Authorization and access in OHI Back Office is handled on three different levels

1. Database level  
Column level grants provide a fine grained authorization for updating data in the database of OHI Back Office.
2. Application level  
Application roles can be used to group a set of modules and provide write and/or read access to this set of modules by assigning the application role to a user account.  
Multiple application roles can be assigned to one account.
3. Business level  
Per user the access to a financial unit or administration unit can be granted.  
Per role the access to a brand, broker or group contract can be granted.



**Note:** The application level and business level access is only enforced through the forms application.

### 3.2.1. Roles

Within OHI Back Office several database roles are present:

| Name    | Characteristics                                                                                                                                                                                                 |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OZG_ROL | <ul style="list-style-type: none"><li>▪ Secure application role for user interface</li><li>▪ May not be directly granted</li><li>▪ For internal use only</li><li>▪ OHI_ROLE_ALL is granted to OZG_ROL</li></ul> |

| Name           | Characteristics                                                                                                                                                                                                                                                               |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OZG_ROLE_ALL   | <ul style="list-style-type: none"> <li>▪ Rights to all objects needed for executing OHI BO</li> <li>▪ May not be directly granted.</li> <li>▪ Accounts / GUI users get temporary elevation when needed (arranged by application).</li> <li>▪ For internal use only</li> </ul> |
| OZG_ROL_DIRECT | <ul style="list-style-type: none"> <li>▪ Rights directly granted to account</li> <li>▪ Only used for custom interfaces or custom code accounts</li> <li>▪ Not to be used for normal / GUI users</li> </ul>                                                                    |
| OZG_ROL_SELECT | <ul style="list-style-type: none"> <li>▪ Read only/query rights</li> <li>▪ Not used by the application</li> </ul>                                                                                                                                                             |

### 3.2.2. Accounts

Each OHI Back Office environment has a set of accounts:

| Name           | Characteristics                                                                                                                                                                                                                              |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OZG_OWNER      | <ul style="list-style-type: none"> <li>• Owner of all OHI BO objects</li> </ul>                                                                                                                                                              |
| (GUI) USER     | <ul style="list-style-type: none"> <li>▪ Per user</li> <li>▪ Elevated to internal OZG_ROL when using forms application</li> </ul>                                                                                                            |
| BATCH          | <ul style="list-style-type: none"> <li>▪ Used by the batch scheduler</li> <li>▪ Elevated to internal OZG_ROL</li> </ul>                                                                                                                      |
| SVL_USER       | <ul style="list-style-type: none"> <li>▪ User used for the service layer webservice</li> </ul>                                                                                                                                               |
| SVS_OWNER      | <ul style="list-style-type: none"> <li>▪ Used for custom code development</li> <li>▪ Should receive same grants as for OZG_ROL_DIRECT for stored code</li> <li>▪ It is possible to create more than one custom development schema</li> </ul> |
| OHI_DPS_USER   | <ul style="list-style-type: none"> <li>• Used when executing dynamic sql from OHI</li> <li>• Has the same grants as OZG_ROL_DIRECT</li> </ul>                                                                                                |
| Query accounts | <ul style="list-style-type: none"> <li>▪ Elevated to OZG_ROL_SELECT</li> </ul>                                                                                                                                                               |

## 3.3. Datamodel help

One of the difficulties when starting to write custom code for OHI is the huge number of tables and relations between the tables. However, there are a few pointers to help you find your way around the data model.

### 3.3.1. Forms frontend

The first help for the programmer are the OHI screens themselves. If there is an item in a screen for which you want to know the location in the database, i.e. the table and the column, move the cursor to this field and select information from the help menu (Menu option: Help → Information), see Figure 4




Figure 4: Information in the forms frontend

In this example the focus is on the policy holder number in the add policy screen, which means that you will get specific information about this field.

In figure x we called up information about a policy product start date. The information screen shows information about the screen (e.g. its module code ZRG2202F) and the database. But most importantly it shows the table name and the column name for the start date, both in Dutch and in English. As a bonus, it shows the record ID of the data that is currently shown. This might very useful when debugging some code.

The screenshot shows the 'Information Screen' with the following data:

| System Information                                                                                                         |  | User Information   |                    | Table/Field Information |                      |
|----------------------------------------------------------------------------------------------------------------------------|--|--------------------|--------------------|-------------------------|----------------------|
| Oracle Health Insurance Back Office - RCS Version 4.0<br>Copyright (c) 1996-2014 Oracle Corporation<br>All Rights Reserved |  | User               | MANAGER            | Table                   | VER_POLISPRODUCTEN   |
|                                                                                                                            |  | Date               | 28-03-2014 15:52   | View (EN)               | VER#POLICY_PRODUCTS_ |
|                                                                                                                            |  | Subsystem          | Health Care System | Field                   | PLT_PLT.DATUM_INGANG |
|                                                                                                                            |  | Module             | ZRG2202F           | Field (EN)              | PLT_PLT.START_DATE   |
|                                                                                                                            |  | Module Version     | 4.308              | Record ID               | 10000000000001       |
|                                                                                                                            |  | Library Version    | 4.466              | Creation Source         | -1                   |
|                                                                                                                            |  | Menu Version       | 4.29 (OZGMENU)     | Created                 | 27-03-2014 13:23:54  |
|                                                                                                                            |  | Database           | vohi               | Created By              | MANAGER              |
|                                                                                                                            |  | Session Identifier | 5865627            | Modification Source     | -1                   |
|                                                                                                                            |  | Forms Version      | 11.1.2.1.0         | Modified                | 27-03-2014 14:22:20  |
|                                                                                                                            |  | Database Version   | 11.2.0.4.0         | Modified By             | MANAGER              |

Buttons at the bottom: OK, Table Information, Module Inform...

Figure 5: Detailed information per forms field

### 3.3.2. HTML overview

A more detailed picture can be created by using a procedure from OHI that creates a description of the tables and their columns. The package SYS\_GEN\_PCK contains the procedure *write\_html\_datamodel* with the following signature:

```
procedure write_html_datamodel
( pi_file_location          in varchar2
);
```

The parameter *pi\_file\_location* must refer to a database directory in which a zip file with HTML files will be created:

*DatamodelOHI\_<release\_number>.zip*

So calling the procedure on OHI Back Office database for release 10.14.1.0.0 in a way like:

```
begin
  sys_gen_pck.write_html_datamodel
  ( pi_file_location => 'OZG_TMP'
  );
end;
```

will generate the file *DatamodelOHI\_10.14.1.0.0.zip*. The zip file contains hundreds of HTML pages showing some simple but often needed information about the OHI tables that a programmer may access.

The pages are accessible through 5 different indexes:

- Dutch table index
- English table index
- Dutch sub systems
- English sub systems
- Aliases

Figure 6 shows a sample page. At the top of the page the indexes are listed. Clicking on any one of them will call the corresponding index. The page furthermore lists the columns with their English and Dutch names, any comments (which are currently still mostly in Dutch) and, if any, foreign keys. At the bottom of the page is a table showing all tables that link to this table. Dutch column names, and any table names are hyperlinks calling up another page or showing more detailed information.

Dutch Table Index - English Table Index - Dutch Subsystems - English Subsystems - Aliases

**RBH\_GEBIEDEN**

**RBH#FIELDS\_**

|             |     |
|-------------|-----|
| Table alias | GBD |
| Subsystem   | RBH |

| Dutch Column Name       | English Column Name | Comments                                                                                                    | Foreign Key |
|-------------------------|---------------------|-------------------------------------------------------------------------------------------------------------|-------------|
| POSTCODE_NR             | POSTAL_CODE_NO      | woonplaats code                                                                                             |             |
| ID                      | ID                  | (TECHNISCH) Systeemgegenereerde identificatie                                                               |             |
| CREATIE_BRON_ID         | CREATION_SOURCE_ID  | (TECHNISCH) Referentie naar de bron in ALG_BRONNEN waaruit deze rij ontstaan is.                            |             |
| CREATIE_MOMENT          | TIME_CREATED        | (TECHNISCH) Datum en tijd van creatie van deze rij.                                                         |             |
| CREATIE_DOOR            | CREATION_BY         | (TECHNISCH) Referentie naar de functionaris in ALG_FUNCTIONARISSEN die deze rij heeft ingevoegd.            |             |
| LAATSTE_MUTATIE_BRON_ID | LAST_MOD_SOURCE_ID  | (TECHNISCH) Referentie naar de bron in ALG_BRONNEN waaruit de laatste mutatie van deze rij afgeleid is.     |             |
| LAATSTE_MUTATIE_MOMENT  | LAST_MOD_MOMENT     | (TECHNISCH) Datum en tijd van de laatste mutatie van deze rij.                                              |             |
| LAATSTE_MUTATIE_DOOR    | LAST_MOD_BY         | (TECHNISCH) Referentie naar de functionaris in ALG_FUNCTIONARISSEN die deze rij het laatst heeft gemuteerd. |             |

**Foreign Keys**

**Referring Tables**

| Dutch Table Name         | English Table Name   |
|--------------------------|----------------------|
| RBH_ADRESSERINGSGEBIEDEN | RBH#ADDRESS_REGIONS_ |

OHI Release 10.14.1.0.0; Created on 10-MAR-14

Dutch Table Index - English Table Index - Dutch Subsystems - English Subsystems - Aliases

Figure 6: Example of an html page for a table

## 3.4. Modification logging

This chapter describes the operation of the modification logging functionality (logging of changes in data) that is available within the OHI BO application.

### 3.4.1. Why modification logging?

There are various reasons and requirements for equipping an application with modification logging. These can be summarized as follows:

- Traceability  
Allows to trace who performed a specific modification and when.
- Modification reports  
Provides input for simple overviews of the data modified within a specific period. This can serve a number of purposes.



- Interface support  
Save modification details for passing on to other applications in the correct sequence and manner.

Because the application is used by different organizations with varying requirements, modification logging within OHI BO is flexible, enabling fulfillment of the various requirements by means of configuration.

### 3.4.2. Operation summary

---

A generic type of modification logging activation has been implemented in the OHI Back Office application, which enables management of each individual table. Consequently, each OHI Back Office functional table has its own table. Furthermore, there is a central log table (ALG\_MUTATIE\_LOG) in which modifications to specific tables can be logged.

Specific modification logging levels can be activated by means of specific indicators that can be configured per table in the ALG\_TABELLEN table.

Modification logging is not activated by default. There is no screen for this activation. Consequently, the relevant columns will have to be updated using (PL/)SQL (with the aid of the ALG\_LOGGING\_PCK) if required.

There are three types of configuration settings:

1. SOORT\_LOGGING

If modification logging (insert, update and delete operations) must be performed in the log table for the table you should set SOORT\_LOGGING to: N(ot), B(asic), enabling retrieval of all modifications with the minimum of additional data storage, or U (for Extensive), such that complete records (both new and old values in the event of updates) are placed in the log table.

The latter is used to facilitate easier tracing of who performed which transactions. It is very useful and faster/easier to retrieve what kind of change has been executed but requires more storage space.

2. NIVEAU\_LOGGING

If modifications must be logged in the central log table ALG\_MUTATIE\_LOG set NIVEAU\_LOGGING to: N(ot), S(tatement) or for every R(ecord). As a result, the central table can be used to immediately establish the modification types performed, as well as the sequence, and which table(s), without all of the tables having to be examined separately.

3. NUMMERING\_LOGGING

If sequence numbers must be distributed set NUMMERING\_LOGGING to: N(ot), database T(ransaction) number per set of changes which are contained in one transaction, with a sequence number within transaction per record which is changed, or G(lobal). Global means that an overall modification ID is distributed per statement (insert, update or delete) in addition to the transaction ID and sequence numbers.

A transaction number is used to track a single Oracle transaction (commit) in detail, while the global (statement) numbers are used to determine the overall sequence of statements executed in different transactions.

### 3.4.3. Default auditing columns

---

Every 'standard' functional tables has the following set of columns which is also important for modification logging:

| Column                  | Characteristics                                                                                                                                                                                            |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ID                      | <ul style="list-style-type: none"> <li>• System generated ID</li> <li>• Uniquely identifies a row within the table</li> <li>• Lends itself for use in generic queries and interfaces.</li> </ul>           |
| CREATIE_DOOR            | <ul style="list-style-type: none"> <li>▪ The user who created the row</li> <li>▪ Refers to ALG_FUNCTIONARISSEN</li> </ul>                                                                                  |
| CREATIE_MOMENT          | <ul style="list-style-type: none"> <li>▪ The time when the row was created</li> <li>▪ Precision: one second</li> </ul>                                                                                     |
| CREATIE_BRON_ID         | <ul style="list-style-type: none"> <li>▪ The system or interface that was used to create row.</li> <li>▪ Refers to ALG_BRONNEN</li> <li>▪ Optional, set by alg_context_pck.set_bron_id</li> </ul>          |
| LAATSTE_MUTATIE_DOOR    | <ul style="list-style-type: none"> <li>▪ The user who last updated the row.</li> <li>▪ Refers to ALG_FUNCTIONARISSEN</li> </ul>                                                                            |
| LAATSTE_MUTATIE_MOMENT  | <ul style="list-style-type: none"> <li>• The time when the row was last updated</li> <li>• Precision: one second</li> </ul>                                                                                |
| LAATSTE_MUTATIE_BRON_ID | <ul style="list-style-type: none"> <li>▪ The system or interface that was last used to update the row.</li> <li>▪ Refers to ALG_BRONNEN</li> <li>▪ Optional, set by alg_context_pck.set_bron_id</li> </ul> |

An example of a table (ALG\_BRONNEN, see later) is displayed below (the first column and final six columns are the above - mentioned seven columns):

```

ID                NOT NULL  NUMBER ( 14 )
CODE              NOT NULL  VARCHAR2 ( 10 )
OMS              NOT NULL  VARCHAR2 ( 200 )
CREATIE_BRON_ID          NUMBER ( 14 )
CREATIE_MOMENT          DATE
CREATIE_DOOR           NUMBER ( 14 )
LAATSTE_MUTATIE_BRON_ID  NUMBER ( 14 )
LAATSTE_MUTATIE_MOMENT   DATE
LAATSTE_MUTATIE_DOOR     NUMBER ( 14 )

```

When a row is initially created the 'last modification' (LAATSTE\_MUTATIE) columns have the same values as the corresponding 'creation' (CREATIE) columns.

Because the references to ALG\_BRONNEN and ALG\_FUNCTIONARISSEN are nullable, the parent rows may be deleted even if there are still referenced.

Implementing a foreign key constraint at this low level would have too much impact on the performance. It is therefore the responsibility of the customer to keep the ALG\_BRONNEN and ALG\_FUNCTIONARISSEN tables aligned with the referencing tables.

### 3.4.4. Configurable modification logging

Because of the various configuration possibilities, the data model features an entity that contains the tables used in the application. This entity also enables entry of various settings per table.

Consequently, modification logging can be configured for each individual table.

However, this only applies to the regular 'functional' data tables (please see the paragraph about availability of modification logging later on). There is no modification logging for technical tables containing system maintained or temporary data, etc.

In general, it can be assumed that the greater the accessibility of the logging data, the higher the required overhead and the greater the storage space required.

Logging must also enable relatively rapid retrieval of specific modifications for disclosure to other parties, for example.

In the light of the above, an implementation method has been chosen that can meet the following configuration requirements which have served as base requirements by means of three settings:

1. Logging?  
Is it necessary to log modifications?
2. Log including complete record with new(est) values?  
In the event of logging, is it necessary to log only old and modifiable values during an update (after all, the current table contains the new values and fixed values), or is it necessary to log all of the new values in addition to the old values for the purpose of simplicity?

In such cases the records are immediately saved in the logging table with all of the new values in the event of inserts. Furthermore, in the event of updates, all new values are saved in the same record with the modifiable old values.

In the event of updates and deletions, the auditing values from the last update or deletion are placed in the modification record, in addition to the time stamp of the previous modification, regardless of the setting for logging new values.

This can be used to immediately determine the validity of the data (old modification timestamp up to and including the new modification timestamp). In the event of deletions the record is always saved in its entirety if logging is activated to avoid the values being lost.

The unique record ID is always recorded for every logging activity, regardless of the DML operation (insert/update/delete).

This approach enables recording of logging information with minimum overhead if required. This only applies to the previously modifiable values in old columns for which all modifications are traceable.

3. Log unique sequential modification ID in log record?  
Is it necessary to record a detailed modification ID in the log record that determines a unique sequence number for all modifications in the application? This number is required additional to a timestamp, as a large number of modifications can be performed within the same second.

Consequently, an ID of this type is necessary to determine the sequence of modifications over various records and/or tables.

Because this number must be generated for each SQL statement (DML) and each record across all tables, the ID generator, although well optimized, may become a 'hot spot', which means it should be used only if necessary.

4. Log statement ID in central overall modification table?  
Because the modifications performed within a specific period should easily be retrieved without the need to scan a lot or all of the tables, it is possible to indicate that DML statements that have actually resulted in a modification must be recorded in a central transaction log table (in which an entry is made stating that a record has been inserted in a specific table, for example).

The type of statement (insert, update, delete), executing user account and (optional, see next bullet) involved record are then recorded for the table concerned.

5. Should the modification ID also be logged centrally for all records?  
If the modification flow must be produced in greater detail for passing on modifications to another system in exactly the correct sequence, it is possible to indicate that the detailed modification ID must also be recorded centrally for each record, i.e. in the central table. This may result in a greater number of entries in the central table including a record ID.

Consequently, at this stage only the central table can be used to determine what record types are required from the modification tables in order to reconstruct an outgoing transaction without the various separate log tables having to be scanned (that would be very inefficient to reproduce transactions that span a set of unknown tables; all log tables would need to be scanned for each transaction).

6. Log commit ID in log table?  
For certain traceability activities (as well as software problems, for example) it can be desirable to establish which modifications were performed within a specific database transaction and in what sequence.

This can also be desirable in order to make it relatively easy to see by means of which transactions a user produced a specific modification.

This functionality can be activated by means of the generation of a commit ID (an ID for each transaction being committed) in the log table with a sequence number within the commit ID for each modified record (across the various tables).

Please note that commit IDs do not necessarily indicate the actual execution order (for example if multiple short transactions before a long transaction that was started earlier).

7. Should the commit ID also be logged in the central logging table for all records?  
The commit ID (commit ID + sequence number per record) can be included in the central table to facilitate easy establishment of the total composition of a logical transaction.

As you see, logging to a log takes place at record level, and not at column level. This is because logging at column level is harder to configure, hardly adds value and has a worse effect on performance.

### 3.4.5. Example

As an example, let us look at ALG\$BRONNEN, the log table for ALG\_BRONNEN:

|                            |          |               |
|----------------------------|----------|---------------|
| MUTATIE_OPERATIE           | NOT NULL | VARCHAR2(1)   |
| MUTATIE_ID                 |          | NUMBER(14)    |
| COMMIT_ID                  |          | NUMBER(14)    |
| SEQ_IN_COMMIT              |          | NUMBER(10)    |
| O\$OMS                     |          | VARCHAR2(200) |
| O\$LAATSTE_MUTATIE_BRON_ID |          | NUMBER(14)    |
| O\$LAATSTE_MUTATIE_MOMENT  |          | DATE          |
| O\$LAATSTE_MUTATIE_DOOR    |          | NUMBER(14)    |
| ID                         |          | NUMBER(14)    |
| CODE                       |          | VARCHAR2(10)  |
| OMS                        |          | VARCHAR2(200) |
| CREATIE_BRON_ID            |          | NUMBER(14)    |
| CREATIE_MOMENT             |          | DATE          |
| CREATIE_DOOR               |          | NUMBER(14)    |
| LAATSTE_MUTATIE_BRON_ID    |          | NUMBER(14)    |

|                        |               |
|------------------------|---------------|
| LAATSTE_MUTATIE_MOMENT | DATE          |
| LAATSTE_MUTATIE_DOOR   | NUMBER ( 14 ) |

The modification type (Insert, Update or Delete) contains the type of operation that led to the creation of the log record.

The modification ID and the commit ID are given values if so configured.

The columns in the table that can be modified by the user or by means of the code are included twice: once as old columns (the name is based on the column name in the original table, prefixed with O\$) and again as 'new' columns (same column names as in the original table).

Columns that cannot be modified are included as 'new' columns, for example the ID column.

When basic logging is activated for the sole reason of traceability, a record containing all modifiable columns with the values prior to the record modification (regardless of whether the modifiable column concerned has also been modified) is saved in the event of a modification to a modifiable column.

This makes it possible to reconstruct any past situation in combination with the current record (uniquely identified by means of its ID).

The name of a log table can be derived from the original table (see 'Tables and views'). For example ALG\$BRONNEN is the log table for ALG\_BRONNEN. Likewise, ALG#SOURCES\$ is the 1:1 view on ALG\$BRONNEN.

When the composition of a transaction, and the sequence in which modifications are performed across the various tables, needs to be established without large numbers of scans of all log tables, it is possible to use additional logging of references to the log tables in the central overall log table.

The central OHI BO log table ALG\_MUTATIE\_LOG is structured as follows:

|                  |                         |
|------------------|-------------------------|
| MUTATIE_OPERATIE | NOT NULL VARCHAR2 ( 1 ) |
| TAB_ID           | NOT NULL NUMBER ( 14 )  |
| RECORD_ID        | NUMBER ( 14 )           |
| COMMIT_ID        | NUMBER ( 14 )           |
| SEQ_IN_COMMIT    | NUMBER ( 14 )           |
| MUTATIE_ID       | NUMBER ( 14 )           |
| MUTATIE_DOOR     | NUMBER ( 14 )           |
| MUTATIE_MOMENT   | DATE                    |

This table contains a reference to the table containing the table names, which facilitates easy tracing of the table in which the centrally logged modification was performed. The column containing the Record ID refers to the unique number per table issued to each record.



**Note:** The COMMIT\_ID is not the same as the SYSTEM COMMIT NUMBER (SCN).



**Note:** The ID column contains the unique ID of the row in the original table. Note that since many modifications to the same row can be logged, this ID is not unique!



**Note:** There are no indexes on log tables.

### 3.4.6. Activation

---

The settings for modification logging are maintained in the ALG\_TABELLEN table.

The ALG\_LOGGING\_PCK package can be used to control the activation and deactivation of logging/journaling of functional tables.

Alternatively, these settings can be set by manually updating the ALG\_TABELLEN table.

The ALG\_LOGGING\_PCK offers the following routines that require a table name as parameter value to implement the functionality:

- `DISABLE_LOGGING` – disables logging to the central table but leaves logging/journaling records to the log table as specified earlier
- `DISABLE_JOURNALLING` – completely disables any kind of logging for the table, whether it is the central table or the table-specific log table
- `ENABLE_JOURNALLING_BASIC` – enable logging to the log table with the least amount of details (requires less space than full journaling)
- `ENABLE_JOURNALLING_FULL` – enable logging to the log table while storing the complete record and old and new values
- `ENABLE_LOGGING_STMT` – enables logging of statement executions on a table to the central log table with transaction id and modification id sequence numbers being assigned
- `ENABLE_LOGGING_ROW` – enable logging of each involved row that is changed by statement execution to the central log table with transaction id and modification id sequence numbers being assigned



**Note:** When specifying a table name, be sure to use the original table name, for example `ALG_BRONNEN` instead of `ALG#SOURCES_`

If you want to use other combinations, for example logging of statements to the central log table but without a global modification id being assigned, you should update the ALG\_TABELLEN table directly.

The best way to determine what is suitable for your situation is to just start with enabling logging on some tables, enforce some statements that generate logging and evaluate the results in the log tables and central log table.

Note that changes to the modification logging may not immediately effective:

- Of course you need to commit your changes in order to make them visible for other sessions.
- The settings for modification logging are cached at the session level. In order to force a reload, sessions must be restarted.

The above-mentioned configuration options per table are available for all regular functional tables that are directly available for executing inserts, update or deletes. These tables implement business rule validation through a series of triggers and constraint definitions. The business rule validation mechanism implements also this modification logging functionality.

This means that other tables, which cannot directly be modified, do not offer this functionality. Such tables are typically maintained by the application. These application-maintained (or code-maintained) tables are often referred as 'technical' tables in comparison with the user maintainable tables as 'functional' tables. The technical tables can be recognized as having a '#' sign on the fourth position of their name.

The standardized way of granting insert, update, delete and select privileges makes sure only the regular 'functional' tables can be changed.

#### **3.4.7. Impact of release upgrades**

---

When a new OHI release is installed an important requirement is to minimize the required installation time in order to have a minimal downtime of the application.

For that reason changes in the data structure or in the data as result of an OHI release installation (a single patch, a patch set or a major release) are often optimized. These optimizations may result in the following consequences for the logging data (although they often do not apply):

- Changes due to a scripted update are not logged
- The table structure is changed and the current contents are converted in the table (by adding for example a default value for a new column) while the logging table is not updated
- A table may be newly (re)created where the existing data is converted to the new structure; these changes will not be reflected in the logging table
- The log table might need to be recreated or dropped; in which situation the old contents are dropped

These consequences do not apply to the central logging table.

Although these consequences might look severe, the heavier the consequence the less often it occurs. And it must be considered that these are completely scripted repeatable operations. For a potential impact of these types of unlogged changes we advise to determine the 'delta' between the situations before and after a release installation to judge whether such modifications are relevant for the derived functionality. Only when there are consequences these must be implemented on the derived environment.

In the rare situation when traceability is required and a log table is cleared we advise to export the table contents before implementing the release installation on the production environment. The saved contents can be used for a custom conversion or later retrieval when necessary.

### **3.5. Tracing**

The application code of OHI Back Office has been instrumented to trace the PL/SQL code as it is executed. Both the CAPI packages, batch packages and underlying packages of the OHI Back Office Business Services have been instrumented.

By turning on tracing you get a detailed overview to help you analyze the program flow. This is useful if you want to understand a problem or need to send extra information to customer support.

Another use may be to instrument your custom code with trace calls.

See 'Appendix C – Tracing' for details.

## 4. Flex fields

As a standard solution for healthcare payers, the OHI Back Office data model cannot be altered. However, the OHI Back Office data model can be extended with so-called flex fields to register additional customer-specific data, for example to record when members had their last health check or to register parameters for interfacing with providers.

These flex fields have the following benefits:

- The core data model stays unchanged, which means that OHI Back Office can support the application as sold to the customer.
- The customer does not need to create custom tables, which must be kept in sync with the OHI Back Office database.

Historically, flex fields were used for claims line processing and to add extra data to policies and relation data. Soon after, flex field implementations were created for other tables as well.

Flex field support will be extended in future releases.

### 4.1. Concepts

At this moment (release 10.14.1.0.0) there are two implementations:

- The historic flex field implementation for policies and relations, supported by the 'modification mechanism' described in 'Appendix E - Modification Mechanism for Policies and Relatio'.  
These flex fields can be accessed in the GUI application through separate tabs in the maintenance screens for relations and policies.
- The current generic flex field implementation, introduced in release 10.13.1.0. These flex fields can be accessed in the GUI application through the key combination CTRL-SHIFT-F2.

Current support for flex fields:

|                                                                                        | Historic | Generic |
|----------------------------------------------------------------------------------------|----------|---------|
| Included in XML output                                                                 | X        | -       |
| Included in CSV output                                                                 | -        | -       |
| Access through GUI                                                                     | X        | X       |
| Query through GUI                                                                      | -        | -       |
| Create or drop flex fields through GUI                                                 | Y        | Y       |
| TAPI support for on-cascade delete of flex fields                                      | Y        | Y       |
| PLSQL supplied packages to support queries on flex fields and flex field values        | -        | -       |
| PLSQL supplied packages to support to perform DML on flex fields and flex field values | -        | -       |
| PLSQL supplied packages to support to create or                                        | -        | -       |



|                                           |   |   |
|-------------------------------------------|---|---|
| drop flex fields and flex field values    |   |   |
| Access through (SVL) web services         | X | X |
| Allow dynamic SQL to validate flex fields | - | - |

In time both flex field implementations will be consolidated into a single solution.

#### 4.1.1. Related

---

The claims processing code uses a specific flex field mechanism which is used to add context-specific data to the claims calculations. In time this mechanism may be migrated to the current generic flex field implementation.

## 4.2. Flex Field Characteristics

These characteristics apply to the current generic implementation.

### 4.2.1. Flex field Types

---

In practice there are two flex field types:

- attributes  
A number, character string or date value, which may be restricted to a range or set of values.
- key references  
The value contains a reference to an existing row in the OHI Back Office database.
- care role  
Key reference to a care provider.
- relation role  
Key reference to a relation

Both 'care role' and 'relation role' are precursors of the new key reference implementation and may be migrated to a key reference in due course.

### 4.2.2. Filters

---

There are two types of filters for flex fields:

- Flex field scope  
Indicates in which context a flex field value can be used (core processing).
- Flex field group  
Evaluates whether a group of flex fields can be set at all.

### 4.2.3. Flex Field Scope

---

Indicates for which context a flex field value can be used.

Possible contexts are:

- Benefit extent
- Benefit threshold
- Premium amount
- Registered
- Yearly deductible amount

A flex field may have multiple scope records.  
Note also that flex field scope records are temporal (time-valid).

#### **4.2.4. Flex Field Groups**

---

The flex field group definition can be used to restrict the use of a group of flex fields for a given row in the master table.

In that case, a dynamic PL/SQL unit, configured for this group definition, is evaluated to decide whether the group of flex fields can be set.

This evaluation takes place:

- When selecting from the REF\_EWE\_VW view (for example in the flex field maintenance screen (ZRG7205F))
- When inserting flex field values for the given master table (for example through PL/SQL or web services).

Note:

- This is a much more restrictive filter than the flex field scope (which allows the flex field to be set and allows its use in a given context).
- The dynamic PL/SQL code can access the columns of the master row through `tbl_rec.<column_name>`.
- Since the evaluation of the PL/SQL definition is done dynamically, a later evaluation may be more restrictive. In that case previously defined flex fields will still apply.

The flex field group definition is also used to display the flex fields in a group in ZRG7205F.

### **4.3. Flex field definition**

Screens:

- ZRG7027F – Maintaining Entity Flex Fields
- ZRG7019F – Flex Field
- ZRG7206F – Flex field Group

Typically you would start with ZRG7027F:

| No. | Flex Field               | M | C | V | S | U | Type          | Data Type    | Length | T | Overlap Scenario | Start Date | End Date   | List of Values | Cascade Delete |
|-----|--------------------------|---|---|---|---|---|---------------|--------------|--------|---|------------------|------------|------------|----------------|----------------|
| 1   | VERWIJZING NAAR RELATE   |   |   |   |   |   | Key reference |              |        |   |                  | 01-01-2013 |            | PERSONEN       | Yes            |
| 1   | AANDUIDING DIAGNOSECODE  |   |   |   |   |   | Attribute     | Numeric      | 3      | 0 | Not allowed      | 01-01-2013 |            |                |                |
| 1   | DEGREE OF DISABILITY     |   |   |   |   |   | Attribute     | Alphanumeric | 11     |   | Automatic        | 01-01-2009 |            |                |                |
| 1   | DETAILED DESCRIPTION     |   |   |   |   |   | Attribute     | Alphanumeric | 60     |   | Automatic        | 01-01-2009 |            |                |                |
| 1   | ELV_AANTAL DDD PER VERP  |   |   |   |   |   | Attribute     | Numeric      | 10     | 3 | Automatic        | 01-01-1989 |            |                |                |
| 2   | DETAILED DESCRIPTION (2) |   |   |   |   |   | Attribute     | Alphanumeric | 60     |   | Automatic        | 01-01-2009 |            |                |                |
| 2   | ELV_ATC CODE             |   |   |   |   |   | Attribute     | Alphanumeric | 8      |   | Automatic        | 01-01-1990 |            |                |                |
| 3   | ELV_BTW CODE             |   |   |   |   |   | Attribute     | Alphanumeric | 1      |   | Automatic        | 01-01-1990 |            |                |                |
| 4   | ELV_CODE TOESLAG ZFK TA  |   |   |   |   |   | Attribute     | Numeric      | 1      | 0 | Automatic        | 01-01-1990 | 30-06-1996 |                |                |
| 5   | ELV_DISPENSEERHONORARIU  |   |   |   |   |   | Attribute     | Numeric      | 4      | 2 | Automatic        | 01-01-1990 |            |                |                |
| 6   | ELV_IND VOORKEURSPRODUI  |   |   |   |   |   | Attribute     | Alphanumeric | 1      |   | Automatic        | 01-01-1990 |            |                |                |
| 7   | ELV_RIKOOPHOEVEELHEID    |   |   |   |   |   | Attribute     | Numeric      | 8      | 2 | Automatic        | 01-01-1990 |            |                |                |

Figure 7: Maintain Entity Flex Fields

#### 4.3.1. Candidate tables for flex fields

Run the following query which will list all tables for which flex fields can be defined by their English view name:

```
select english_name, name from alg#tables_
where flex_fields_ind = 'J' order by 1;
```

#### 4.3.2. Allowed values

You may specify the criteria for the value of a flex field, for example using ranges (lower + upper boundary) or allowed values (low value + description).

If you do not specify any allowed values, any valid value for the given data type is acceptable.

| No. | Flex Field             | M | C | V | S | U | Type          | Data Type    | Length | T | Overlap Scenario | Start Date | End Date | List of Values | Cascade Delete |
|-----|------------------------|---|---|---|---|---|---------------|--------------|--------|---|------------------|------------|----------|----------------|----------------|
| 1   | VERWIJZING NAAR RELATE |   |   |   |   |   | Key reference |              |        |   |                  | 01-01-2013 |          | PERSONEN       | Yes            |
| 1   | INDICATE GEHUIWD       |   |   |   |   |   | Attribute     | Alphanumeric | 1      |   |                  | 01-01-1995 |          |                |                |
| 1   | C359 IND_GEHUIWD       |   |   |   |   |   | Attribute     | Alphanumeric | 1      |   |                  | 01-01-1990 |          |                |                |
| 2   | PARTNER OPGENOMEN      |   |   |   |   |   | Attribute     | Alphanumeric | 1      |   |                  | 01-01-1995 |          |                |                |

Figure 8: Specify allowed values

### 4.3.3. Time-valid flex fields

If you define a flex field to be time-valid, you should also specify the overlap scenario (automatic, permitted, non-permitted).

Do not confuse the validity of the flex field value with the validity of the flex field definition.

### 4.3.4. Multi-value flex fields

A multi-value flex field is used to hold a set (or array) of values valid at the same point in time.

For example, for registering multiple parameters when registering details to connect with an interface.

### 4.3.5. Key Reference

The flex field value refers to a record in another table.

Use 'List of Values' to select a LOV query to present the runtime user with a LOV screen from which to select the FK reference.

Think about setting 'cascade delete':

- N : the deletion process for the parent of the key reference will only succeed if there are no flex field values referencing to it.
- Y : the deletion process for the parent will remove the flex field values referencing to it.

You may want the context menu to start the List Of Values Definitions Screen (SYS1152F):

| Items                               | No. | Prompt | Hint Text                       | Perc. | Column         | SQL Expression                                            |
|-------------------------------------|-----|--------|---------------------------------|-------|----------------|-----------------------------------------------------------|
| <input type="checkbox"/>            | 1   | Number | The unique number of a relation | 15    | NR             |                                                           |
| <input type="checkbox"/>            | 2   | Name   | The name of the relation        | 55    | NAAM           |                                                           |
| <input type="checkbox"/>            | 3   | Phone  | A persons phone number          | 15    | TELEFOONNUMMER |                                                           |
| <input checked="" type="checkbox"/> | 4   | Gender | A persons gender                | 15    |                | alg.translate_pck.get_fixed_text_translation(tbl.n_gesla) |
| <input type="checkbox"/>            |     |        |                                 |       |                |                                                           |
| <input type="checkbox"/>            |     |        |                                 |       |                |                                                           |
| <input type="checkbox"/>            |     |        |                                 |       |                |                                                           |
| <input type="checkbox"/>            |     |        |                                 |       |                |                                                           |
| <input type="checkbox"/>            |     |        |                                 |       |                |                                                           |
| <input type="checkbox"/>            |     |        |                                 |       |                |                                                           |

Figure 9: Set up a list of values

## 4.4. Flex field maintenance

Flex fields for the current generic implementation are maintained with ZRG7205F which is invoked through the CTRL-SHIFT-F2 key combination:



---

## 5. Dynamic PLSQL

OHI Back Office's support for dynamic PL/SQL is a powerful mechanism which allows the customer to add customer-specific code to the core OHI Back Office product.

OHI Back Office has defined several 'hooks' in OHI Back Office where custom code can be added e.g. for:

- Data entry validation
- Address entry and formatting
- Trigger conditions for business event framework
- Core processes such as claims processing, policy collection and payment processing.

Apart from adding a high level of flexibility to the customer our support of dynamic PL/SQL helps to keep the amount of code in the standard product under control.

### 5.1. Hooks for PL/SQL code

OHI Back Office has defined several 'hooks' in OHI Back Office where custom code can be added:

- Column value validation
- Commission calculation
- Claims Processing
- Policy Creation
- Policy Collection
- Population Register Check
- XML Processing
- Address Entry
- Address Display
- Trigger conditions for the business event framework
- Payment Processing
- ..

It is expected that this list will grow in time.

### 5.2. Dynamic PLSQL Definition

The process of adding dynamic PL/SQL boils down to this:

- Select the hook or 'scope' where you want to insert custom code.
- Create the custom code in the format required by the 'subtype' associated with the scope.
- Extend the application to specific tables or columns if you are adding a column validation.
- After testing, revise the debug level.

### 5.2.1. Setup

The PLSQL definition is maintained in the screen “Dynamic PL/SQL Definition” (SYS1139F)

| Table | Column | System Message | Insert                              | Update                              | Delete                   |
|-------|--------|----------------|-------------------------------------|-------------------------------------|--------------------------|
|       |        |                | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |

**Figure 11: Dynamic PL/SQL definition**

In addition to the online help for the SYS1139F screen, note:

- When making changes, ensure that ‘Active’ is unchecked.
- The upper part of the screen is used to define the custom PL/SQL code and in which context (scope/subtype) it is used.
- Make sure that the ‘name’ and ‘explanation’ clarify the purpose of your custom code.
- The ‘body’ attribute is initialized with sample PL/SQL code when you select the scope for the first time.
- The attribute ‘column bound type’ as well as the ‘tables’ and ‘columns’ tabs in the bottom part of the screen are meaningful only if you have selected the ‘column bound’ scope, ie. if you are going to validate database column values.

### 5.2.2. Scope and subtype

Dynamic PL/SQL is executed at runtime by the OHI Back Office code.

The ‘scope’ defines WHEN the PL/SQL code is executed.

The ‘subtype’ defines HOW the PL/SQL code should look like, i.e. the input and output parameters.

The scope and the sub type of a scope together constitute a Dynamic PL/SQL Usage Type or ‘usage type’ for short.

You cannot create new usage types, but you can query the predefined usage types in the SYS1138F screen (Dynamic PL/SQL Usage Type).

The SYS1138F screen is particularly useful to find the possible bind variables and output types.

Figure 12: Dynamic PL/SQL Usage Type



**Note: bind variables**

Some pieces of dynamic PL/SQL are defined to use bind variables. If you want to omit a bind variable from your code, OHI will fail to bind a value to your code at runtime and abort with an error. This means that the bind variable must be in the code, even if it is just in comments.

Please find a more detailed list with hooks in 'Appendix F - Dynamic PL/SQL Types'.

### 5.3. Column bound checks

Column-bound checks are executed when inserting, updating or updating records.

Many of these column-bound checks have been implemented by OHI Back Office, so you will only need to create additional checks.

Examples of column-bound checks:

- Syntax check of dynamic PL/SQL code
- Check whether an IBAN number is valid
- Validate that the end date of a record must be at least 14 days after the start date.
- ..

A column-bound check evaluates to 'true' or 'false'. There is no 'somewhat true'. If all column values for a given row are evaluated to 'true', the DML operation (insert, update, delete) will continue.

If one or more checks evaluate to 'false' the DML operation will abort and the error message defined for the failed column check will be shown.



Note that a single column-bound check can be applied to more than one table, provided that each column is of the same type and name as the column in your custom PL/SQL code.

### 5.3.1. Single column checks

A single column bound check uses one column to check. A typical example of a single column bound check is the validation of a format mask for the given column.

Let's use the following example in which a telephone number must always begin with a "+" sign. The telephone number is stored with a relation, so it is a check on a column in the relation screen. If the telephone number does not start with a "+" an error will be presented to the user.

#### 5.3.1.1. Error message definition

Custom error messages must be defined using the screen "System Messages" (Menu option: System / Management / General / System Messages), as shown in Figure x.

We will not discuss message creation here in depth, but will only mention a few points:

- Custom messages can have any code, but it is good practice to start them with the code "SVS". Although not enforced for messages most of the custom code(s) in OHI must start with SVS.
- Custom messages must belong to the subsystem "External batches".

| Code                 | Message                                        | W?                                  | S                                   | W                        | P                        | Subsystem        | Seq. No. |
|----------------------|------------------------------------------------|-------------------------------------|-------------------------------------|--------------------------|--------------------------|------------------|----------|
| SVS_PHONE_NUMBER_CHK | The phone number doesn't have the right format | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | External batches | 1850     |
|                      |                                                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |
|                      |                                                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |
|                      |                                                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |
|                      |                                                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |
|                      |                                                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |

Help Text: N/A      Legacy Code:

Work Instructions    Message Parameters    Context Menu Options

| Instruction | Batch |
|-------------|-------|
|             |       |
|             |       |
|             |       |
|             |       |
|             |       |
|             |       |
|             |       |
|             |       |

Figure 13: shows the definition of an error message for our example.

#### 5.3.1.2. PL/SQL definition

Next step is creating the Dynamic PL/SQL definition. This is done in four steps:

1. Create a Dynamic PL/SQL definition. This means we need to choose a Name (or Code), a Description, the Scope ("column bound" in this case), a Column Bound Type ("Single-Column" in this case) and the System Message that we defined in the previous paragraph.

Note that the Active check box must be unchecked. The reason for this is that the record must be saved before we can add Tables and Columns in the lower section. But saving the record with the Active flag checked will cause OHI to

check the syntax of the PL/SQL code which needs a reference to the tables and columns, which in turn have not been added yet. (See Figure 14).

| Table | Column | System Message | Insert                              | Update                              | Delete                   |
|-------|--------|----------------|-------------------------------------|-------------------------------------|--------------------------|
|       |        |                | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |

**Figure 14: step of creation of a Column Bound check.**

2. Add the tables and columns in the lower block, in the "single column" tab. In our case this means that we have to provide the Relations table and two columns, because there are two telephone numbers that can be stored in the Relations table.

Currently only the Dutch table and column names are accepted as input. In our example we only need to check the value upon insertion or update of the telephone number, so only the Insert and Update check boxes are checked. See Figure 15.

| Table        | Column           | System Message | Insert                              | Update                              | Delete                   |
|--------------|------------------|----------------|-------------------------------------|-------------------------------------|--------------------------|
| RBH_RELATIES | TELEFOONNUMMER   |                | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| RBH_RELATIES | TWEDE_TELEFOONNR |                | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
|              |                  |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |
|              |                  |                | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> |

**Figure 15: Adding table and columns to PL/SQL definition.**

3. Create the actual PL/SQL. See below for the code for our example.

```
-- declaration section
-- bind variable: :COLUMN_VALUE
l_retval boolean := true;
begin
  -- body section
  if :COLUMN_VALUE is not null
  then
    l_retval := substr(:COLUMN_VALUE,1,1) = '+';
```

```

end if;
return l_retval;
end;

```

Note:

- a. The code can use three variables:

The bind variable - :COLUMN\_VALUE, which contains the new value of the column.

The variables OLD\_REC and NEW\_REC which contain the old and new record for the same row. When inserting, the OLD\_REC contains only null values. When deleting, NEW\_REC is empty. Only in case of an update do both OLD\_REC and NEW\_REC have values.

- b. The code must return a boolean value. If the new value passes the test TRUE must be returned, in which case the new value will be committed to the database (if no other error occurs!). If FALSE is returned the message provided in the Dynamic PL/SQL definition will be displayed to the user, and the new value will not be committed to the database.
- c. :COLUMN\_VALUE is a read-only value. You cannot change this to fix a problem.
- d. Be aware of NULL values. When activated the column bound check is performed always regardless whether the column has a value or not, or whether it changed or not. Hence the check on the NULL value in the code in Figure x.

4. Activate the Dynamic PL/SQL (Figure x).




Figure 16: Activating the dynamic PL/SQL definition.

### 5.3.2. Multi column checks

A multi column bound check uses more than one column for its check, but is in all regards similar to a single column bound check.

Let's use the following example: an organization must have a web site. An organization is stored in the same Relations table as a regular person. There is, however, a column indicating whether a relation is an organization or a person. This column needs to be checked together with the field for the URL.

#### 5.3.2.1. Message definition

Just as for the single column check we need an appropriate error message. Figure 17 shows our message. Again we have the code of the message start with SVS.

| Code          | Message                               | W?                                  | S                        | W                        | P                        | Subsystem        | Seq. No. |
|---------------|---------------------------------------|-------------------------------------|--------------------------|--------------------------|--------------------------|------------------|----------|
| SVS_URL_CHECK | An organization must have a web site. | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | External batches | 1851     |
|               |                                       | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |
|               |                                       | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |
|               |                                       | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |
|               |                                       | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |                  |          |

**Figure 17: Error message for multi column bound check example.**

#### 5.3.2.2. PL/SQL Definition

The PL/SQL definition differs in only one field with a single column bound check. The Column Bound Type must be set to Multi-Column. See Figure 18.

Again we need to make sure that the check is not activated yet, in order to prevent OHI from checking the PL/SQL code syntax.

The message we provide is the one from the previous paragraph.

**Figure 18: Dynamic PL/SQL definition for Multi Column Bound Check.**

Next is the selection of tables and columns, on the second tab in the bottom of the screen (Figure 19). The table name must be provided in Dutch, as must the column names. The table is RBH\_RELATIES and the columns we are interested in are SUB\_TYPE and URL.

**Figure 19: Table and column definitions for multi column bound checks.**

Now for the PL/SQL code. This is shown in Figure x. Note that it is not needed to check new\_rec.sub\_type for a null value as this field is mandatory in OHI. If the sub\_type is equal to 'O', which means the relation is an organization, the return value is determined by checking the URL column for null. If it is not null a url has been provided for the organization and true will be returned, otherwise false.

Note that the bind variable :COLUMN\_VALUE cannot be used as OHI does not know which of the specified column values should be used. Only the variables OLD\_REC and NEW\_REC can be used. But even though the bind variable cannot be used it still must be mentioned in the code. So put it in the comments (which, by the way, is done by default).

Example code

```
-- declaration section
-- bind variable: :COLUMN_VALUE
l_retval boolean := true;
begin
```

After saving the dynamic PL/SQL definition can be activated in the same way as for single column bound checks, see Figure 16.

When unexpected code errors occur on screen, these may be related to the use of column bound checks, both single and multi column. To quickly determine whether such a column bound check is responsible for the error there are two ways:

- | Tables                                                 |                                          |                   |                                     |                                     |                                     |                                     |                          |                                     |
|--------------------------------------------------------|------------------------------------------|-------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|--------------------------|-------------------------------------|
| Table                                                  | RBH_RELATIES                             |                   | Description                         | Relations                           |                                     |                                     |                          |                                     |
| Column Bound Checks                                    |                                          | Event Definitions |                                     |                                     |                                     |                                     |                          |                                     |
| Name                                                   | Description                              | Column            | Type                                | Active                              | Insert                              | Update                              | Delete                   | Active                              |
| <input checked="" type="checkbox"/> SVS_PHONE_NUMBER_C | Check telephone number                   | TELEFOONNUMMER    | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| <input type="checkbox"/> SVS_PHONE_NUMBER_C            | Check telephone number                   | TWEEDE_TELEFOONNR | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| <input type="checkbox"/> SVS_URL_CHECK                 | Check that an organization has a web URL |                   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/> | <input type="checkbox"/>            |
| <input type="checkbox"/>                               |                                          |                   | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            |                                     |                          |                                     |

## 5.4. Writing custom code

Example:

```
-- :COLUMN_VALUE
    l_retval boolean := true;
begin
    if api_rbh_util_pck.get_rns_vrij_tekstveld(pi_rsn_id => new_rec.rsn_id) =
'IBAN CONTROLE'
    then
```

```

        l_retval := api_rbh_util_pck.check_iban(pi_rekeninggegeven =>
new_rec.rekeninggegeven);
    end if;

    return l_retval;
end;
```

You can create your own validation function and limit the dynamic PL/SQL code to:

```

-- :COLUMN_VALUE - reference to bind variable
begin
    return custom.validate_pck.check_iban(pi_erk => new_rec);
end;
```

The advantages:

- You can keep all your custom validations in one place.
- It is easier to move your code from one environment to another.
- You can use your favorite tools to develop and test your code.

---

## 6. Business Event Framework

With the Business Event Framework you can define customer-specific events and event handlers.

These events can be time-based, triggered by a change or created by your custom-designed detection mechanism.

The handlers can be run near real-time or in batch processing mode and are implemented through custom PL/SQL code.

### 6.1. Overview

Specific hooks are required in the OHI Back Office application for customers to develop custom event handling using the OHI Back Office database. The Business Event Framework can be used to signal specific events in the OHI Back Office application. These events can arise from creating or modifying data or by the passing of time. The framework is also used to define how an event should be handled.

Since the majority of custom development for OHI Back Office implementations is PL/SQL based, the framework is implemented in PL/SQL.

The Business Event Framework provides two options both for signaling and responding. These options can be combined for each business event to create the most suitable environment for handling the event.

An example of how the Business Event Framework can be used is when a member supplies the health care payer with their change of address after relocating. The health care payer has an integrated customer relationship management (CRM) system and uses the change of address event to automatically trigger an update to the CRM database.

### 6.2. Signaling Events

The Business Event Framework offers two options for signaling events and both are described in this section.

---

#### 6.2.1. Detected Events

Detected events are events that are signaled by querying the data in one or more tables. A decision to register the event is based on the results of the query. The event is registered based on the data that was found at the moment the data was queried. This moment can be controlled by scheduling Process Business Events (SYS5001S) batch (see Starting Business Event).

For example, a relation record is updated at 08.30, 11.15 and 14.50 hours. When the batch is scheduled to run at 15.00, the data from the last modification (14.50) will be evaluated. The data for the record as at 09.00 or 12.00 cannot be signaled by a detected event.

Detected events are best used in situations where the intermediate modifications are not important or where the passing of time is the trigger for the event.

---

#### 6.2.2. Triggered Events

Triggered events are signaled the moment they occur. Using database triggers an event is evaluated and registered. Unlike the detected events, intermediate changes can be signaled. In the relation record example, which is updated at 08.30, 11.15 and 14.50, a triggered event can be registered for all three updates.

Events can be signaled separately based how the data is modified, for example insert, update or delete.

Triggered events are used to signal data modifications immediately.

## 6.3. Responding to Events

The Business Event Framework offers two options for responding to events and both are described in this section.

### 6.3.1. Batch Response

To process signaled events in a batch the signaled events must be stored in an OHI Back Office table. The moment the event is signaled, either through a detected event or a triggered event, the event is saved to table ALG#EVENTS. The Process Business Events (SYS5001S) batch handles the events. The batch can be scheduled to run at the correct intervals (see Starting Business Event).



**Note:** No duplicate events

Duplicate events will not be stored when saving events to a table. In case a relation or policy is signaled multiple times for the same event, the table will hold only one occurrence of the event. If the same data manipulation type is performed twice for an event on a table and record, only the first will result in an event.

After successful processing the event, the same event could be detected again.

### 6.3.2. Near Real Time

When an event should be signaled the moment it occurs, events can be stored to a queue. An OHI Back Office background process is continuously listening to the queue. Events are taken from the queue and processed immediately.



**Note:** Queued events are processed by a separate process (with its own database session). This may result in locking issues if the handler and the originating process both want to update the same record.

## 6.4. Combining Signaling and Response Types

Four definitions result from the two types of events together with two storage options. This section describes the situations where each definition can be used.




Figure 21: Flows of an event process



#### **6.4.1. Detected Events, Storing to a Table**

---

This event definition is suitable when there is no urgency to act on specific events and individual data changes are not important. For example, there is an event that produces an overview of all policies modified in the previous week. A record of all the individual modifications does not have to be kept. A check on the last date the record was updated is sufficient in this example.

Detected events are also the only events able to act on situations not triggered by data manipulation but the passing of time. For example, a member reaches 18 years of age or a record having a specific status for a number of days. Triggered events are not suitable for this since no data is changed and therefore no database trigger will signal the event.

#### **6.4.2. Triggered Events, Storing to a Table**

---

This event definition is suitable when the action of the event has no urgency but the individual data modifications are important. For example, a triggered event can be used when an event should be registered when a policy reaches the final status. A detected event is less suitable for this because at the time the detection batch is running the policy could have been updated to another status. This results in the policy being skipped by the detection run and no event is registered.

#### **6.4.3. Detected Events, Storing to the Queue**

---

Although technically possible, this type of event is not practical. Detected events are processed in the same batch run. There is not much difference between the moment an event is registered and the moment it is processed. Therefore processing these events using the queue will not provide much of an advantage. The queue will have a large load to process when lots of events are detected.

When multiple occurrences of the same event are required storing to the queue should also be used.

#### **6.4.4. Triggered Events, Storing to the Queue**

---

This event type is best suited when individual updates are important and immediate action is required. For example, the member should receive a welcome email when their policy reaches the final status.

### **6.5. Framework Components**

This chapter describes all the components within the OHI Back Office application for setup, registering and responding to business events.

#### **6.5.1. Event Definition**

---

The Event Definition (SYS1149F) window is used for defining an event in OHI Back Office.

**Figure 22: Maintain Event Definitions**

Data in Event definitions

| Field                  | Description                                                                                                                |
|------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Name                   | The name of the event, maximum length 30 characters.                                                                       |
| Description            | The description of the event, maximum length 100 characters.                                                               |
| Type                   | How the event is signaled, allowable values Detected and Triggered.                                                        |
| Detector               | The (package) procedure for registering this event. Only applicable for detected events.                                   |
| Last Detection         | The timestamp of the last processing run. Only applicable for detected events.                                             |
| Storage                | Where are signaled events stored, allowed values Table and Queue.                                                          |
| Status                 | The status of a processing run. Only applicable for detected events.                                                       |
| Run Number             | The last number of the processing run. Only applicable for detected events.                                                |
| Begin Handler          | The (package) procedure for the begin handler. Only applicable for events with storage set to Table.                       |
| Handler                | The (package) procedure for handling the event. Applicable for all events.                                                 |
| End Handler            | The (package) procedure for the end handler. Only applicable for events with storage set to Table.                         |
| Active                 | Indicates whether the event is active or not.                                                                              |
| Purge Interval Success | The purge interval for events that have been successfully processed. Only applicable for events with storage set to Table. |
| Purge Interval Failure | The purge interval for events that have failed. Only applicable for events with storage set to Table.                      |

Data in Tables

| Field               | Description                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|
| Table               | Holds the name of the table the event is designed for.                                                                       |
| Insert              | Indicates whether events should be signaled when a new record in this table is created.                                      |
| Evaluation function | The name of the dynamic PL/SQL definition used to evaluate the event. Only allowed in case the Insert indication is checked. |
| Update              | Indicates whether events should be signaled when a record in this table is updated.                                          |
| Evaluation function | The name of the dynamic PL/SQL definition used to evaluate the event. Only allowed in case the Update indication is checked. |
| Delete              | Indication whether events should be signaled when a record in this table is deleted.                                         |

| Field               | Description                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|
| Evaluation function | The name of the dynamic PL/SQL definition used to evaluate the event. Only allowed in case the Delete indication is checked. |

The event tables block is only applicable for triggered events.

The event can be fine-tuned with the evaluation functions to only signal the desired situation. See the next section for a more detailed description of these functions.

### 6.5.2. Dynamic PLSQL Definition

The Dynamic PLSQL Definition (SYS1139F) window is used to maintain the dynamic PLSQL functions that are used to fine-tune the registering of a specific event.

**Figure 23: Add a trigger condition for an event**

The Scope must be set to Event for PL/SQL definitions used within the Business Event Framework. This window is also used to maintain PL/SQL definitions used elsewhere within OHI Back Office. Only the fields applicable for the Business Event Framework are described.

| Field       | Description                                                                                                    |
|-------------|----------------------------------------------------------------------------------------------------------------|
| Name        | The name of the PL/SQL definition, maximum length 20 characters.                                               |
| Description | The description of the PL/SQL definition, maximum length 50 characters.                                        |
| Scope       | Should be set to Event to be able to select the definition in the Event Definition (SYS1149F) window.          |
| Body        | The actual code of the PL/SQL definition. The event will be registered when the function returns a true value. |

The PLSQL Body contains the actual code used to evaluate whether an event should be registered. The code must return a Boolean value to indicate this. In case true is returned the event will be signaled. In case the function returns false, it will not. Two record variables are available for the old and new values (old\_rec and new\_rec).

These can be used to evaluate a specific situation, for instance only signal events in case the new status is equal to D.

The two tabs are not applicable for the Business Event Framework.



**Note: 'Active' indication**

When committing a dynamic PL/SQL definition with the indication 'Active' checked, OHI Back Office will try to validate the code of the Body section. When creating a new PL/SQL definition the table that will be used is unknown to OHI Back Office. Therefore the 'Active' indication should not be checked when first creating the PL/SQL definition. After linking it to a table in the Event Definition (SYS1149F) window it can be turned on.

### 6.5.3. Event Definition Package

---

The ALG\_EVENT\_INTERFACE\_PCK can be used to define event definitions. This offers the same functionality as the OHI Back Office Event Definition window with the exception of defining the tables for a Triggered event. The functionality for installing and de-installing an event is available for backward compatibility.

The package also holds procedures that are used for event handling and several utilities.

See Appendix IV for a full description of the parameters for each procedure and function in the package.

#### Event Definition

- **Install:** Available as a procedure and a function returning the ID of the event. This can be used for the event definition. When the given event already exists (based on the name of the event) it will update the event definition, otherwise a new event definition will be registered with the values supplied.
- **De-install:** This procedure is available twice. Once to remove an event with a given name and once to remove it based on the ID of the event definition.

#### Event Handling

- **Add\_event** Three procedures are available to store an event to the table. One receives the name of the event as a parameter, the second the ID of the event definition. The parameter code holds the identification of the record in OHI Back Office that caused the event. The third procedure stores an event to the Business Event Framework queue. It receives one parameter of type:

`ALG_EDE_PAYLOAD_TP`

To be able to change the storage clause of an event from table to queue the code should be a string with the following format:

`table_id##record_id##dml_type`, where `dml_type` can be 'I' (Insert), 'U' (Update) or 'D' (Delete)

- **purge\_all\_events** Available twice, based on the name of the event definition and based on the ID of the event definition. It will remove all events and event errors for the given event.
- **reapply\_failed\_event** Available twice, based on the name of the event definition and based on the ID of the event definition. It will change the status of a event stored in the table from 'Failed' to 'New'. This procedure should be called from within the detector plugin. Providing a specific event

will reset only the provided event for the given event definition. When no event is provided all failed events for the given definition will be reset.

#### Utility

- `type_payload_to_code` Can be used to transform object type `alg_edc_payload_tp` to the code parameter of the `add_event` procedure.
- `code_payload_to_type` Available twice, used to convert the code parameter of the `add_event` procedure to object type `alg_edc_payload_tp`. Available with the name and the ID of the event definition.

### 6.5.4. Event Handling Package

---

Events are handled by the framework package `ALG_EVENT_PCK`. This is an internal OHI Back Office package and is therefore not available for custom development. It contains the same functions and procedures as the `ALG_EVENT_INTERFACE_PCK`.

### 6.5.5. Process Business Event Batch

---

The Process Business Events (SYS5001S) batch has been developed to support starting the Business Event Framework by the OHI Back Office batch scheduler. The batch is needed to signal Detected events and to process events which are stored in the `ALG#EVENTS` table. The batch can be scheduled using OHI Back Office Submit Batch Request (SYSS003F) window. It has the name of the event as a parameter allowing for different run intervals per defined event.

### 6.5.6. Background Process

---

Background process `OHI_EVENT_JOB_x` is used to handle events with storage set to queue. The process is started and stopped simultaneously with the OHI Back Office batch process.

The process monitors the Business Event Framework queue. Events are taken from the queue and processed using the `ALG_EVENT_PCK` package.

With the Back Office parameter 'No. of processes for event framework' the number of processes listing to the event queue can be set.

## 6.6. Developing Your Own Business Events

First the business event should be analyzed to determine the best suited registering and handling types. Triggered events are best suited when the event signals data manipulation and it is important to signal each individual action. Detected events can be used for end-of-day status reports or for events not caused by data changes but by the passing of time.

The storage of the event should be set to Queue when, as soon as the event is signaled, immediate action is required. It can be set to Table when the action to the event is less urgent and can occur at a scheduled times.

### 6.6.1. Detected events

---

In the Event Definition window set the Type to Detected. The Detector field is mandatory for this type of event.

#### 6.6.1.1. Detector

The field holds the (package) procedure, which is used to register the business event. The procedure receives the timestamp of the last time it was started and the name of

the business event. The Business Event Framework will commit after executing the detector.

For example where an event should count the number of policies, the detector in the event definition could be:

```
my_event_pck.detect_nr_policies
```

The procedure definition could look like:

```
procedure detect_nr_policies
( pi_event_name in alg_event_definitions.naam%type
, pi_start_date in date
);
```

Each event occurrence can be stored using the add\_event procedure in the ALG\_EVENT\_INTERFACE\_PCK package.

#### 6.6.1.2. Adding events

Detected events should either be saved to the ALG#EVENTS table or to the Business Event Framework queue. This can be done by calling the add\_event procedure in the ALG\_EVENT\_INTERFACE\_PCK package.

Dependent on the storage clause for the event the appropriate add\_event can be called. For events stored in the table this would be:

```
alg_event_interface_pck.add_event
( pi_name in alg_event_definitions.naam%type
, pi_code in alg#events.code
, pi_date in alg#events.master_date%type
);
```

Or:

```
alg_event_interface_pck.add_event
( pi_edc_id in alg_event_definitions.id%type
, pi_code in alg#events.code
, pi_date in alg#events.master_date%type
);
```

For events stored in the queue this is:

```
alg_event_interface_pck.add_event
( pi_edc_payload in alg_edc_payload_tp
);
```

If the storage type of an event is modified in the Event Definition (SYS1149F) window the add\_event will continue to work and the received parameters will be converted to match the storage type. Although it can have a (minor) impact on performance it is not necessary to change the detector-program code.

#### 6.6.1.3. Example

The following code shows an example of an event to signal all new relations created since the last time this event was processed.

```
procedure my_detector
( pi_event_name in alg_event_definitions.naam%type
, pi_start_date in date
) is
  cursor c_events
  ( vi_date_from date
  ) is
    select rel.id
    from rbh_relations rel
    where rel.creatie_moment >= c_events.vi_date_from
  ;
```

```

    l_tab_id alg_tabellen.id%type;
    l_dml_type varchar2(1) := 'I';
begin
    -- Determine table id
    l_tab_id := rbh_rel_capi.g_tab_id;
    for r_rec in c_events ( pi_start_date )
    loop
        -- Store to a table
        alg_event_interface_pck.add_event
        ( pi_name => pi_event_name
          , pi_code => r_rec.id
          );
    end loop;
end my_detector;

```

### 6.6.2. Triggered events

---

In the Event Definition window set the Type to Triggered. For events of this type the Detector field is not available since the event is signaled using OHI Back Office database triggers.

#### 6.6.2.1. Tables

The second block is only available for triggered events. The table of the event can be defined and the action on the table can be set using the Insert, Update or Delete indications.

#### 6.6.2.2. Evaluation

Evaluation functions are available for defining additional criteria for registering an event. These functions can be set up in the Dynamic PL/SQL Definition window.

#### 6.6.2.3. Example

A triggered event can be set up to signal all policies that reach a final status. Since policies cannot be created with the final status, the only action to monitor is update. To prevent registering other updates to the policy the following dynamic PL/SQL can be created, the scope of the dynamic PL/SQL should be set to Event. The body can hold:

```

-- declaration section: define cursors and variables here
    l_retval boolean := true;
begin
    -- body section:
    -- return boolean value --
    return new_rec.status = 'D'
        and new_rec.status <> old_rec.status;
end;

```

Since this PL/SQL definition will be linked to the VER\_POLISSEN table in the event definition window the new\_rec and old\_rec variables will hold all fields available in that table.

### 6.6.3. Batch Handled Events

---

Events with storage clause set to table will be handled by the Process Business Events batch.

#### 6.6.3.1. Begin Handler

The (package) procedure defined for the begin handler in the event definition is called once. This can be used for example to open a file for writing log messages. The framework will commit after executing the begin handler.

The (package) procedure receives the following parameters:

- The name of the event
- The run number of the process
- The date of the last processed run

```
my_event_pck.begin_handler
( pi_name in varchar2
, pi_run_nr in number
, pi_date_detection in date
);
```

#### 6.6.3.2. *Handler*

The handler is called for each instance of the event. The framework will commit after executing the handler. The handler (package) procedure receives the following parameters:

- The code of the event
- The date that was passed when registering the event
- The date the event was registered

```
my_event_pck.handler
( pi_name in varchar2
, pi_date_source in date
, pi_date_detection in date
);
```

#### 6.6.3.3. *End handler*

The end handler is called once after processing all events. For example this can be used to save information about the process run such as the total number of events processed, the number of failed events or close the file opened in the begin handler. The framework will commit after executing the end handler.

```
my_event_pck.end_handler
( pi_name in varchar2
, pi_run_nr in number
, pi_date_detection in date
);
```

#### 6.6.3.4. *Purge intervals*

Purging old event records is a batch function. It is possible to set up the intervals in the Event Definition window. It is possible to have different values for failed events since investigation may take longer than successful events.

The batch will remove records from the ALG#EVENTS tables at the end of the run.

### 6.6.4. **Near Real Time Events**

---

Events stored to a queue are processed by a continuous Background Process. Since each event is processed individually no begin handler or end handler is available for these events. Only the handler is applicable.

#### 6.6.4.1. *Handler*

The OHI Back Office event package will take an event from the queue and call the handler defined in Event Definition window. The (package) procedure for this handler receives an object as parameter. This object contains the following information.

- The ID of the event definition



- The ID of the table the signaled record is stored in
- The record ID
- The DML type that caused the event

The handler can be defined as:

```
my_event_pck.queued_event_handler
( pi_load in alg_edc_payload_tp
);
```

#### 6.6.5. Custom Plug-ins

---

The event tables and event framework are pre-installed in the OHI Back Office database. The custom plug-ins for the detector and handlers of the events must be implemented in a separate database schema.

The following is assumed for the purpose of this installation procedure:

- The event definition is called my\_event
- The custom components are combined in a single package called my\_event\_pck
- The my\_event\_pck.install procedure creates and configures an event definition for my\_event
- The OHI components are owned by database schema ozg\_owner
- The database schema for bespoke software is called my\_schema
- The business event framework is started by the ozg\_batch schema.

The installation consists of the following steps:

- Ensure that public synonyms and access privileges are created for the ozg\_owner components that are accessed by the my\_event\_pck package (you may only use the objects granted by \$OZG\_ADMIN/OZG\_DIRECT.grt.<sid> sqlplus script for this)
- Ensure that my\_schema has execute privileges for ozg\_owner.alg\_event\_interface\_pck (should be taken care of in the previous step but in previous releases the grant was missing)
- Compile the package specification and package body for my\_event\_pck under the database schema my\_schema
- Create a public synonym my\_event\_interface\_pck for my\_schema.my\_event\_pck
- Grant execute privileges for my\_schema.my\_event\_pck to the ozg\_owner schema.
- Run my\_event\_interface\_pck.install under my\_schema to install the definition for my\_event or set up the event definition using the Event Definition window.

## 6.7. Processing Business Events

Processing business events is dependent of the business event definition. Detected events are registered by the Process Business Events batch. Triggered events are started by database triggers.

### 6.7.1. Process Business Events Batch

The Process Business Events (SYS5001S) batch has been developed to start up a business event processing run. The batch can be scheduled using the Submit Batch Request (SYSS003F) window.

The screenshot shows the 'Submit Batch Request' window for batch 'SYS5001S' (Process Business Events). The window is divided into several sections:

- Batch Request:** Contains fields for 'Number' (10000000015348), 'Printer', 'Processes', 'Max. Hours', 'Start Time' (28-08-2013 12:00), 'Frequency' (Every hour), 'Optimizer Mode' (ALL\_ROWS), 'Exceed' (checkbox), 'Trace' (checkbox), 'Exceeded Trace' (checkbox), and 'Debug' (checkbox). A 'Submit Request' button is located at the top right.
- Parameters:** A table with columns for 'Event definition', 'AZR\_MOD\_PRT', and three empty columns. The first row is selected.
- Dependencies:** A table with columns for 'Dependent on', 'Func', and 'Started Time'. The first row is selected.

**Figure 24: Sample of scheduling Process Business Events (SYS5001S) batch**

In the screenshot business event 'AZR\_MOD\_PRT' will start every hour.

The batch serves two purposes and is only needed for these types of events:

1. Signal Detected events. For detected events the program code defined by the Detector is executed once. See Detector for a more detailed description of the detector. This step is skipped for triggered events.
2. Process events stored in a table. Events stored in the table are processed. First the specified Begin Handler is called once. Per event the Handler is called to process the event. After processing all events the End Handler is called once. After the end handler the batch purges old events. This step is skipped for events stored in the queue.



**Note:** Detection and Processing in one run

For Detected events storing the events to a table and registering and processing the events happen in the same processing run.

### 6.7.2. Queued Events

Events stored to the queue are processed by a dedicated process monitoring the business event queue. Events are taken from the queue and the handler is called to process the event.

The dedicated process is started and stopped together with the OHI Back Office batch scheduler.

## 6.8. Examples

This chapter contains examples of how to set up events to be handled by the Business Event Framework.

### 6.8.1. Detected Event, Store to a Table

This example shows an event to signal all relations that have been updated since the last time the event was run. It writes the identification of the relations to a file. Since there is no need to act on individual updates and no immediate action is required upon the change, a detected event storing to a table will suffice.

#### 6.8.1.1. Event definition

The screenshot shows the 'Event Definition' window. The 'Name' field is 'OHI\_DEMO\_D\_T'. The 'Warning' dropdown is set to 'Detected'. The 'Surcharge' dropdown is set to 'Table'. The 'Begin Handler' is 'OHI\_EVENT\_DEMO\_PCK.START\_HANDL'. The 'Active' checkbox is checked. The 'Description' field contains 'Example detected to table'. The 'Detection' dropdown is set to 'OHI\_EVENT\_DEMO\_PCK.DETECT'. The 'Status' dropdown is set to 'OHI\_EVENT\_DEMO\_PCK.HANDLE'. The 'Processing' dropdown is set to 'OHI\_EVENT\_DEMO\_PCK.HANDLE'. The 'Purging Interval Processed' is set to 10. The 'Purging Interval Failed' is set to 32. The 'Last Detection' field is empty. The 'Run Number' field is empty. The 'End Handler' is 'OHI\_EVENT\_DEMO\_PCK.END\_HA'. Below the configuration fields is a table with columns: Table, Insert Check, Update Check, Delete Check, and Active. The first row is selected, and the 'Active' checkbox is checked.

Figure 25: Example event definition named OHI\_DEMO\_D\_T

Example OHI\_DEMO\_D\_T is a detected event (Type is set to Detected) and it will store events to the ALG#EVENTS table (Storage set to Table).

#### 6.8.1.2. Detector

The detector of the event in this example is OHI\_EVENT\_DEMO\_PCK.DETECTOR\_T. Typically the code of a detector consists of a query to select the records to be registered and a call the ALG\_EVENT\_INTERFACE\_PCK package to save the identification of the selected records:

```
procedure detector_t
( pi_name      in varchar2
, pi_date_from in date
) is
begin
    for l_rec in ( select rel.id
                  ,      rel.laatste_mutatie_moment
                  from    rbh_relaties rel
                  where   rel.laatste_mutatie_moment >=
pi_date_from
                  )
    loop
        alg_event_interface_pck.add_event
        (pi_name => pi_name
        ,pi_code => to_char(l_rec.id)
        ,pi_date => l_rec.laatste_mutatie_moment
        );
    end loop;
end detector_t;
```

#### 6.8.1.3. Begin handler

The begin handler OHI\_EVENT\_DEMO\_PCK.START\_HANDLER\_T in this example is used to open the file for writing the identifications of the relations.

```
procedure start_handler_t
( pi_name          in varchar2
, pi_run_nr        in number
, pi_date_detection in date
) is
  l_filename      varchar2(100);
  l_location      varchar2(100) := 'OZG_TMP';
  l_max_linesize  constant binary_integer := 32767;
begin
  l_filename := i_name||
               '_'||
               to_char(pi_run_nr)||
               '_'||
               to_char(pi_date_detection,'YYYYMMDDHH24MISS')||
               '.txt';
  a_file_handle := utl_file.fopen
                  ( l_location
                  , l_filename
                  , 'w'
                  , l_max_linesize
                  );
end start_handler_t;
```

#### 6.8.1.4. Handler

The handler OHI\_EVENT\_DEMO\_PCK.HANDLER\_T of the example writes the data to the opened file. The code parameter contains the identification of the relation record. It could be used to select more detailed information from the relation record. For instance who and when the last modification was made. Since this is a detected event the data would however only reflect the last modification.

```
procedure handler_t
( pi_code          in varchar2
, pi_date_source   in date
, pi_date_detection in date
) is
begin
  utl_file.put_line
  ( a_file_handle
  , pi_code||
    ' -> '||
    to_char(pi_date_detection,'YYYY-MM-DD HH24:MI:SS')||
    ' -> '||
    to_char(pi_date_source,'YYYY-MM-DD HH24:MI:SS')
  );
end handler_t;
```

#### 6.8.1.5. End handler

The end handler OHI\_EVENT\_DEMO\_PCK.END\_HANDLER\_T in this example is used to close the file.

```
procedure end_handler_t
( pi_name          in varchar2
, pi_run_nr        in number
, pi_date_detection in date
)
```

```

) is
begin
  if utl_file.is_open(a_file_handle)
  then
    utl_file.fclose(a_file_handle);
  end if;
end end_handler_t;

```

#### 6.8.1.6. Scheduling the event

All steps for the detected event have finished. The event can be scheduled to run using Submit Batch Request (SYSS003F) window.

Figure 26: Submit a batch request to run event OHI\_DEMO\_D\_T

### 6.8.2. Triggered Event, Store to the Queue

This example shows how to define an event that will be registered when a new record is created.

#### 6.8.2.1. Evaluation Function

First step is creating the evaluation function which will be used in the event definition. OHI Back Office will validate the entered PL/SQL code when it is saved. Since the PL/SQL Definition has not yet been linked to a table this validation will fail. Therefore the indicator 'Active' should not be checked. In that case the PL/SQL code is disabled and will not be validated.

Dynamic PL/SQL definition

Name: EVT\_CK\_40

Description: Check if value equals to 40

Scope: Event | Check

Column Bound Type:

System Message:

Explanation:

External Routine:

Body:

```
-- declaration section: define cursors and variables here
l_retval boolean := true;
begin
-- body section: implement custom code here: data manipulation is not allowed
```

Debug Mode:

Active ☒

Dynamic PL/SQL tables - single column | Dynamic PL/SQL tables - multi column

| Table | Column | System Message | Insert                   | Update                   | Delete                   |
|-------|--------|----------------|--------------------------|--------------------------|--------------------------|
|       |        |                | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|       |        |                | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

**Figure 27: Event evaluation function activation**

The complete Body of the PL/SQL definition is not visible, it contains:

```
cursor c_rel
( v_rel_nr in rbh_relaties.nr%type
) is
select rel.n_geslacht gender
from   rbh_relaties rel
where  rel.nr = c_rel.v_rel_nr
;
l_rel_gender rbh_relaties.n_geslacht%type;
l_retval     boolean := true;
begin
open  c_rel( v_rel_nr => new_rec.rel_nr );
fetch c_rel
into  l_rel_gender;
close c_rel;
l_retval :=      l_rel_gender = 1
               and new_rec.code = '40'
return l_retval;
end;
```

The example shows that when a record is created for a male relation and the code is equal to '40' the function will return true and an event will be registered.

Since it is linked to the RBH\_DERDEN\_CODERINGEN table in the event definition, the new\_rec will hold all the new values of the record. It can be used for more sophisticated evaluation than this example.

#### 6.8.2.2. Event definition

The screenshot shows example event definition named OHI\_DEMO\_T\_Q. It is a triggered event (Type is set to Triggered) and it will store events to Business Event Framework queue (Storage set to Queue). This type of event will be signaled by database triggers so a separate Detector is not needed. A begin handler and end handler are not required when the storage clause is set to Queue as the events will be handled.

| Table                 | Insert Check                                  | Update Check             | Delete Check             | Active                              |
|-----------------------|-----------------------------------------------|--------------------------|--------------------------|-------------------------------------|
| RBH_DERDEN_CODERINGEN | <input checked="" type="checkbox"/> EVT_CK_40 | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
|                       | <input type="checkbox"/>                      | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |

**Figure 28: Add a table and evaluation function to a triggered event**

The event will be signaled by the creation of a record in the RBH\_DERDEN\_CODERINGEN table when the dynamic PL/SQL definition EVT\_CK\_40 returns true.



**Note:** 'Active' indication

After the PL/SQL Definition has been linked to a table the 'Active' indication in the Dynamic PL/SQL Definition window must be checked to validate and enable the code.

### 6.8.2.3. Handler

The events are handled by OHI\_EVENT\_DEMO\_PCK.HANDLER\_Q. It takes the identification of the record from the object type it receives as parameter and sends an email to notify another department for instance.

```

procedure handler_q
( pi_load in alg_edc_payload_tp
) is
  l_conn utl_smtp.connection;
  l_code varchar2(100);

  procedure send_header
  ( pi_name in varchar2
    , pi_header in varchar2
  ) is
  begin
    utl_smtp.write_data
    ( l_conn
      , pi_name || ': ' ||
        pi_header || UTL_TCP.CRLF
    );
  end send_header;

begin
  l_code := alg_event_interface_pck.type_payload_to_code
    ( pi_edc_payload => pi_load
    );

  l_conn := utl_smtp.open_connection('smtpsrv.mycompany.com');
  utl_smtp.helo( l_conn, 'mycompany.com');

```

```

utl_smtp.mail( l_conn, 'sender@mycompany.com');
utl_smtp.rcpt( l_conn, 'recipient@mycompany.com');
utl_smtp.open_data(l_conn);

send_header('From', '"Sender" <sender@mycompany.com>');
send_header('To', '"Recipient" <recipient@mycompany.com>');
send_header('Subject', 'Relation created');

utl_smtp.write_data( l_conn
                    , UTL_TCP.CRLF ||
                      'Relation with code ' || l_code ||
                      ' has been created. '
                    );
utl_smtp.close_data( l_conn );
utl_smtp.quit( l_conn );
end;
```



## 7. Custom Batch Scripts

OHI Back Office allows you to create your own batch processing scripts and run them with the standard batch scheduler. Batches can be purely PL/SQL or they can be Perl or OS Shell scripts. They can be scheduled to run immediately or at a predetermined time.

For PL/SQL batches you are advised to use the built-in OHI Back Office script generator to generate a framework to control the execution of your custom code, especially if you expect to be processing large data volumes. The generated framework helps to process large volumes in manageable chunks and provide the same kind of feedback as the standard scripts.


### 7.1. Approach

A custom batch script is handled in the same way as a standard script.

This means that:

- Most batch scripts process a large amount of data, and report results, often after performing DML operations on the selected data.
- A custom batch script must be registered as a script
- A custom batch script is run under the BATCH account
- While creating a request for a custom batch script, the end user may enter script parameters.
- At runtime the custom batch script may evaluate the script parameters.
- When a custom batch script completes or aborts it must register its end state in the batch requests table.
- A script must be created to export the batch definition from the test database to the production database.

The typical flow for a batch script looks like this:



**Figure 29: Typical process for a batch script**

#### 7.1.1. Create or generate?

Although you may want to manually create all code for your batch script, you are strongly advised to start with a template created by the generator built into OHI Back Office and modify this to your needs.

The generator (SYS\_GEN\_PCK) creates a framework to process the data in small chunks with multiple parallel processes.

The framework helps you to define the data to be processed by defining the selection of the data, the so called process units, and process the data chunk by chunk which usually is record by record over multiple threads.

Note that the custom batch scripts based on these templates provide the same throughput statistics as standard batch scripts created by OHI Back Office.

The generator supports the following batch types:

- Bulk DML processing batches with support for parallel execution
- CSV file export
- CSV file import
- XML file import

## 7.2. Batch user

Note that the batch scheduler connects to the OHI Back Office database with the database user BATCH. This is not the user who created the batch request!

The user BATCH must be able to access all database objects needed to process the batch request.

The database objects for custom batches reside in a custom schema, for example SVS\_OWNER. The BATCH user must be granted access to these database objects.

## 7.3. Registration

### 7.3.1. Batch

The definition of a batch is maintained in the screen “Batch” (SYS1008F). In this screen you can define or check the main batch characteristics, like the batch code, whether it can spawn parallel processes, whether it is a PL/SQL, Perl or OS shell script etc.

The screenshot shows the 'Batch' (SYS1008F) screen with the following sections:

- Code:** Fields for Code, Layout, Processing Report, Data File, Batch Window, Output Group, Minimum Runtime, Output Description, Max. Subprocesses, and Overtime Allowed.
- Batch Type:** A dropdown menu set to 'File interface'.
- Output Type:** A dropdown menu set to 'ASCII'.
- Optional Sets:** Minimum and Maximum values.
- Print Automatically:** A checked checkbox.
- Output Control:** A dropdown menu set to 'ALL\_ROWS'.
- Optimizer Mode:** A dropdown menu.
- Service:** A dropdown menu.
- Errors:** A checked checkbox.
- Warnings:** A checked checkbox.
- Informational:** A checked checkbox.
- New Standard:** An unchecked checkbox.
- Lapsed:** An unchecked checkbox.
- Parallel Supported:** An unchecked checkbox.
- Overtime Trace:** An unchecked checkbox.
- Stopped:** An unchecked checkbox.
- Parallel:** An unchecked checkbox.
- Parameter Sets:** A table with columns: No., Set, Description, M, LOV, LOV Restriction, and Validation.
- System Message Exclusions:** A table with columns: No., Parameter, Description, M, E, Prompt, Name in Batch, Operator, and Column.
- XSD Versions:** A table with columns: No., Parameter, Description, M, E, Prompt, Name in Batch, Operator, and Column.
- Default Value:** A text field.
- Reference Date:** A dropdown menu.
- Correction Days:** A text field.
- Hint:** A text field.

**Figure 30: Batch definition**

Also the batch parameters can be defined or checked here. Parameter definitions can be shared between different batches, which means that if one is to use an already defined parameter, care has to be taken that the definition of the parameter is not inadvertently changed.

Parameters are always grouped in parameter sets. E.g. the location of a file might be specified by two grouped parameters: the directory and the file name. Most of the time, however, a parameter set will contain just one parameter.

Parameter sets have a few checks. If provided the values may only be chosen from a list of values, maybe with additional restrictions. They can also be checked using a parameter set validation.

Also a list of values can be set to be used. The restriction on the list of values depends on the particular list of values. It is best to look for the use of an actual list of values to see how it is used and how it can be restricted. Besides the predefined lists of values also a dynamic list of values can be used.



 **Note:** The LOV for the dynamic value list is SYS2019L and the LOV restriction should contain the name of the dynamic value list. The column field at last contains the sequence number of the column in the dynamic value list..

Figure 31 shows the screen for defining parameter set validations. It defines a validation as it might be used for selecting relations that are physical persons.



| Code    | Description | Table                                              | WHERE Clause | Time Valid |
|---------|-------------|----------------------------------------------------|--------------|------------|
| SVSPERS | Person      | <input checked="" type="checkbox"/> RBH#RELATIONS_ | sub_type='N' | No         |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |
|         |             | <input type="checkbox"/>                           |              |            |

**Figure 31: Defining a validation on the type of relation.**

Relations in OHI can be either persons or organizations. Both are stored in the same table and are distinguished based on the sub type. The parameter set validation here is called SVSPERS. The checkmark tells OHI that it is based on a table, which is given in the field Table. To make sure that the relation is a person (the actual validation) a where clause is specified, that checks the sub\_type which must be 'N' for (natural) persons.

### 7.3.2. Dynamic List of values

In the screen "List of Values" (SYS1152F) a custom list of values can be defined. This list of values uses tables of OHI Back Office. If the use of a custom table is required

than this table should be used in a “System view” (SYS4001F). This system view can be used as the “table” of the list of values.



**Note:** The table or (system) view used as table source in the list of values should also have one numeric column named ID. It is not required to use the ID column as a column in the list of values.

### 7.3.3. Batch Settings

---

For batches created with SYS\_GEN\_PCK a couple of settings are imported.

- Code and description: The code is the identifier of the batch and should start with SVS
- Batch type: defines the type of batch and should be
  - SQL\*Plus for standard mutating batches and CSV report files
  - CSV for incoming CSV files
  - XML for incoming XML files
- New Standard? Indicator must be activated
- Required parameters: Some batch scripts do have a set of required parameters. See SYS\_GEN\_PCK for the required set of parameters per type of script.
- The value of the field “Name in script” at the parameter set component should be the same as used in the definition of the parameter in the call to SYS\_GEN\_PCK

## 7.4. Export script definition

The definition of a batch as defined in the screen “Batch” (SYS1008F) can be extracted to an installation script that can be used to install this definition in other OHI environments, e.g. test or production.

The procedure write\_module\_ins\_file in SYS\_GEN\_PCK takes care of this.

```
Sys_gen_pck.write_module_ins_file  
( pi_module      => 'SVS0001S'  
  , pi_file_location => 'OZG_TMP'  
  );
```

The file will be placed in the database directory provided at the parameter pi\_file\_location and is called the provided module code (pi\_module) with the extension .ins.

Besides the batch module also the system message will be present in the file as long as the message(s) starts with the module code.

## 7.5. Generator: Bulk Processing Batch - Overview

The procedure SYS\_GEN\_PCK.BATCH\_SOURCES can be used to generate pre-defined templates for batch processing.

The generation results in a couple of files

- MODULE.sql
- MODULE.ins
- MODULE\_PCK.pck
- MODULE\_CUST\_PCK.pck

### 7.5.1. MODULE.sql

---

The sql file will be called by the batch scheduler when a batch request is created for this module. It will start the batch by executing the run procedure in the MODULE\_PCK package. This file should not be changed and be placed in the sql directory of the application server of the environment.

### 7.5.2. MODULE.ins

---

The ins file contains data that is used by some system messages and should be executed in a sql session in the database.

### 7.5.3. MODULE\_PCK.pck

---

This package contains all the generic code to run a batch. This file should not be modified and should be compiled in the database.

This package takes care of the initialization of the batch, the transaction and exception handling and makes callouts the MODULE\_CUST\_PCK package.

### 7.5.4. MODULE\_CUST\_PCK.pck

---

This package contains all the custom code of the batch and is the one source that must be provided with the required business logic for this batch.

### 7.5.5. Basic PL/SQL Batch flow

---

A PL/SQL batch generated with SYS\_GEN\_PCK typically follows the flow as shown in figure x




Figure 32: batch process flow


The green blocks contain the batch specific code and have to be implemented. These units are present in the MODULE\_CUST\_PCK. The red units contain the generic batch code and are present in the MODULE\_PCK.

## 7.6. Generator: Bulk Processing Batch - Details

### 7.6.1. Define the batch definition

---

A (bulk) processing batch first selects rows for processing and then processes each row:



**Figure 33: Select and process rows**


Before designing the batch you should decide:

*What operation should be performed on which data?*

The 'which data' determines your selection criteria, the 'what operation' determines the processing.

Note:

- The simplest version is a selection of rows on which you directly perform the DML.
- It may also be that the DML action triggers an update to a master record. In that case you would like to handle all the details for the same master in the same session/sub-process to avoid locking issues. In this second case, you also have to ask whether you want that is committed when all details are processed or that you want to commit per detail itself.
- A variation on this is that you want to perform two different actions with the same master. The second action is determined by the result of the first action.
- A variant of 1 and 2 together is a cursor which is executed per row from the selection.



**Figure 34: Determine the batch definition setup**

The batch template consists of several parts in one call. An example call is available in the package specification of the package SYS\_GEN\_PCK.

The different parts are:

- The batch module
- 0-n batch parameters
- 1-n batch groups

1-n batch units per group

#### 7.6.1.1. Define the batch module

The batch is the actual module as defined in the screen “Batch” (SYS1008F).

```

sys_gen_pck.batch_sources
( pi_file_location      => 'OZG_TMP'
, pi_module_name        => 'SVS0001S'
, pi_ind_count_processed => true
, pi_parameter_tab      => sys_gen_pck.batch_parameter_tabtype
                        ( sys_gen_pck.batch_parameter_rec
                        ( pi_name => . . .

```

Provide a valid database directory for the parameter pi\_file\_location. This is the directory the files will be created in. The parameter pi\_module\_name contains the code of the batch module as defined in the screen “Batch”. With the parameter pi\_ind\_count\_processed set to true a couple of system messages will be created to report when the batch request is completed about:

- the total amount of workunits
- the amount of successful processed units
- the amount of work units with an error

#### 7.6.1.2. Define the batch parameters

The batch parameters are used to influence the behavior of the batch based on the input provided by the user when creating the batch request.

Each batch parameter should be added to the call of BATCH\_SOURCES

```

sys_gen_pck.batch_parameter_rec
( pi_name      => 'P_MER_CODE'
, pi_table_name => 'VER#POLICIES_'
, pi_column_name => 'MER_CODE'
, pi_data_type  => 'VARCHAR2'

```

```
, pi_data_length    => 5
, pi_data_precision => 0
, pi_comment        => 'The code of the brand'
)
```

The parameter `pi_name` must have the same name/code as defined in the screen “Batch” in the field “Name in script”.

### 7.6.1.3. Define the processing unit(s)

The processing unit has two components, the “group” defines the selection and the “unit” defines the processing unit.

```
, pi_group_tab => sys_gen_pck.batch_group_tabtype
( sys_gen_pck.batch_group_rec
  ( pi_table_name    => 'VER#POLICIES_'
  , pi_alias         => 'POL'
  , pi_label         => 'Policies'
  , pi_identification => 'NUM'
  , pi_level         => 'BASE'
  , pi_alias_fu      => 'POL'
  , pi_unit_tab      => sys_gen_pck.batch_unit_tabtype
  )
)
```

The group implements the selection part of the batch. The provided table and column are used to create a basic query which can be adjusted later on. The alias (parameter `pi_alias`) is used to identify the group throughout the batch and should be unique within the batch. The parameter `pi_level` can have one of the two values “BASE” or “LOOKUP” and is used for the transaction level. The label (`pi_label`) is used in the messages created by the batch to report on the processed amount of work.

The parameter `pi_alias_fu` needs some explanation, sometimes the workload defined in either the group or the unit is not the actual workload to be reported, e.g. when the batch uses a grouping of data to be processed. A function will be provided to record the actual amount of data per group of unit when applicable. To use this option the alias of the parameter `pi_alias_fu` should be a different one than the alias of the group or unit.



**Note:** The group expects a unique single numeric value per processing unit, e.g. a record id, a policy number or a relation number (parameter `pi_identification`).

```
, pi_unit_tab => sys_gen_pck.batch_unit_tabtype
( sys_gen_pck.batch_unit_rec
  ( pi_table_name    => 'VER#POLICIES_'
  , pi_alias         => 'POL'
  , pi_label         => 'Policies'
  , pi_alias_fu      => 'POL'
  )
)
```

The unit implements the worker process. It can be the same unit as defined at the group or another unit when within the defined group a more detailed processing is needed. If a unit is based on another alias (`pi_alias`) a second query will be generated to transform the selected record from the group into a more detailed record structure for the unit.



**Note:** One batch can exist of one or more groups and each group exists of one or more units. Although one group with one unit is the most common type.



## 7.6.2. Implementation

---

When the sources are generated the actual implementation can be done. The `<MODULE>_CUST_PCK` custom package is the only source that needs to be modified for the implementation.

The custom package has several functions and procedures. For "`_xyz`" the alias you defined for your batch group or unit should be substituted when reading this.



**Note:** Don't add transaction code like rollback or commit in your custom implementation as well as a "when others" exception handler as this is dealt by the main package.

See Figure 32 for a schematic flow of the different functions and procedures and their place in the process

### 7.6.2.1. Function *get\_revision*

This function determines the revision of the batch as it is shown in the .out file produced by the batch request.

It is called once in the main batch request

### 7.6.2.2. Function *parameters\_ok*

In the function `parameters_ok` the script parameters can be validated.

Using batch request validation is preferred over implementing validation here as it prevents the batch request from being submitted. If any value is not correct a message can be written and the boolean value "false" is returned. This causes the batch to stop and the status "Error" is recorded.

It is called once in the main batch request

### 7.6.2.3. procedure *before\_processing*

The purpose of this procedure is to execute specific actions once when the batch is started. For example initialization or creating a master record to be referred to by details that are generated during batch processing.

It is called once in the main batch request

### 7.6.2.4. function *query\_xyz*

The `query_<alias>` function prepares the processing units.

The parameter `pi_volgnr` in the procedure `alg_batch_pck.ins_svh_bulk` determines the order in which the units are processed.

If more than one subprocess is started process (1) will handle row 1 and process 2 will handle row 2 etc.



**Note:** Implementing an 'DUP\_VAL\_ON\_INDEX' exception handler will not work as the inserts in the table will be done in bulk and the last set will be done post processing the function 'query\_xyz'. When, in the exceptional case you need to trap the 'DUP\_VAL\_ON\_INDEX' please add a call at the start of the function to 'ALG\_BATCH\_PCK.SET\_IGNORE\_DUPVAL'.

It is called once in the main batch request

#### **7.6.2.5. *procedure after\_processing***

The purpose of this procedure is to execute specific actions once when the batch is finished. For example cleaning up temporary data, generating a message based on the manual counts, etc.

It is called once in the main batch request

#### **7.6.2.6. *cursor a\_c\_xyz***

In the package specification a cursor can be defined. This will be the case if a Structure is provided with a different unit compared to the group.

The query\_xyz function queries the rows from the base usage and during processing a single row is presented to this cursor (v\_record\_id).

Using this cursor the selection from the lookup usage can be performed. Each row from the resulting set will be presented to the process\_xyz procedure. The order of the query result is the order of the rows processed by the process\_xyz procedure.

It is called once per record from the group selection in the subprocess batch request.

#### **7.6.2.7. *procedure update\_shg***

The procedure update\_shg is meant to customize recording of the number of records that was processed successfully or with errors using manual messages.

Using the procedure alg\_batch\_pck.toevoegen\_shg the message is initialized. Updating the number of processed records must be coded manually.

An update is chosen because otherwise too many records would be created causing trouble when purging batch requests.

Updating is done using an autonomous transaction and does not influence processing.

#### **7.6.2.8. *procedure before\_process\_xyz***

The purpose of this procedure is to execute specific actions once when the group is started. For example initialization of a package variable.

It is called once per group in the subprocess batch request

#### **7.6.2.9. *procedure after\_process\_xyz***

The purpose of this procedure is to execute specific actions once when the group is finished. For example cleaning up temporary data, generating a message based on the manual counts, etc.

It is called once per group in the subprocess batch request

#### **7.6.2.10. *procedure process\_success\_xyz***

This procedure can be used to write a message saying that processing was successful or to maintain a specific counter.

Sometimes an indicator needs to be updated when the transaction was successful. Such an action can be performed here too.

It is called once per record (unit) in the subprocess batch request

#### 7.6.2.11. *procedure process\_error\_xyz*

This procedure can be used to write a message saying that processing was not successful or to maintain a specific counter.

Transactions are not allowed. Recording or updating manual messages is allowed provided procedure `update_shg en alg_batch_pck.toevoegen_shg` are used. These messages are processed using an autonomous transaction.

It is called once per record in the subprocess batch request in case of an error.

#### 7.6.2.12. *procedure process\_xyz*

The procedure `process_<alias>` carries out the 'real' processing per processing unit.

In the `process_<alias>` procedure each row can be validated if it is suited for processing. If it is not, an error message can be written. In that case processing the row will be stopped.

It is called once per record (unit) in the subprocess batch request

### 7.6.3. Messages

---

Per record an system message can be created for informational purpose or to record an error. In case of an error the current record is skipped from being processed and the next record will be processed.

An example error message will look like

```
sys_message_handling_pck.give_error
( pi_msg_code           => 'SVS0001S004'
, pi_msg_default_text   => 'Record #1# does not comply to the specifications.'
, pi_msg_parmvalue_tab => sys_message_handling_pck.msg_parmvalue_tabtype
    ( sys_message_handling_pck.parmvalue
      ( pi_sequence_nr => 1
        , pi_value_number => pi_record_id
      )
      , sys_message_handling_pck.parmvalue
      ( pi_sequence_nr => 2
        , pi_value_char  => 'CHECK001A'
      )
    )
, pi_raise_exception    => true
, pi_table_id           => 123
, pi_record_id          => pi_record_id
);
```

Be sure to register the system message in the screen "System messages" (SYS1002F). Also note that each parameter value cannot exceed a length of 120 characters and the total length of a message with the parameters substituted cannot exceed a length of 2000 characters.

## 7.7. Generator: CSV Export Batch

The procedure `sys_gen_pck.export_csv_sources` creates a template for a script to write the result of a query into a CSV (comma separated value) file.

```
sys_gen_pck.export_csv_sources
( pi_file_location      => 'OZG_TMP'
, pi_module_name        => 'SVS0004R'
, pi_schema_owner       => 'SVS_OWNER'
, pi_ind_utf8           => 'Y'
, pi_table_name         => 'RBH#RELATIONS_'
, pi_alias              => 'REL'
, pi_label              => 'Relations'
, pi_item_tab           => sys_gen_pck.report_item_tabtype
```

With the parameter `pi_ind_utf8` set the output will use the UTF-8 character set. Otherwise the character set of the database will be used.

```

sys_gen_pck.report_item_tabtype
( sys_gen_pck.report_item_rec
  ( pi_name           => 'NUM'
    , pi_table_name    => 'RBH#RELATIONS_'
    , pi_column_name   => 'NUM'
    , pi_data_type     => 'NUMBER'
    , pi_data_length   => 10
    , pi_data_precision => 0
    , pi_prompt        => 'relation number'
  )
, sys_gen_pck.report_item_rec
  ( pi_name           => 'NAME'
    , pi_table_name    => 'RBH#RELATIONS_'

```

The report\_item\_rec function defines each column in the CSV report.

## 7.8. Generator: CSV Import Batch

The procedure sys\_gen\_pck.import\_csv\_sources creates a template to import and process a CSV file into the OHI Back Office database.

A maximum of twenty columns can be processed. The process\_row procedure processes row by row the CSV file.

## 7.9. Generator: XML Import batch


The procedure sys\_gen\_pck.import\_xml\_sources creates a template to import and process a XML file. It uses XQuery to process the data stored in an XMLTYPE datatype.

## 7.10. Other output scripts

It is possible to write your own scripts without using the template generator.

## 8. HTTP Links

HTTP Links allow users of the OHI Back Office GUI Application to view or process related data in an external application. For each HTTP link you can configure a HTTP request template to the target application and the OHI screens which will display the HTTP link.



**Figure 35: HTTP link buttons**

At runtime the HTTP link will open an extra browser window to send a HTTP request to the target application, substituting placeholders with runtime values derived from the current OHI screen.

Note that the target application must be an HTTP application!

Up to nine HTTP links can be defined per screen.

### 8.1. Configuration

Configuration of an HTTP link in OHI is done using two configuration screens, one for defining the URL and its parameters (HTTP-Link) and one for assigning a link to a menu button for an OHI screen (Module HTTP-Links).

#### 8.1.1. HTTP-Link


The HTTP-Link screen (Menu option: System / Management / General / HTTP-Link) is used to define the URL and an optional tooltip and or icon (see Figure x: HTTP Link definition screen).

To specify a link the following parameters must be supplied:

| Parameter   | Description                                                                                      | Mandatory |
|-------------|--------------------------------------------------------------------------------------------------|-----------|
| Description | The name of the link. This name will be used in the next screen to identify the link             | Yes       |
| Tooltip     | A short name for the link that will be shown when the user hovers with the mouse over the button | No        |
| Icon        | An alternative icon                                                                              | No        |
| URL         | The URL to link to. When using parameters some syntax rules apply.                               | Yes       |
| Active      | An indicator for activating or deactivating the link.                                            | Yes       |


If the Active indicator is not checked the link is disabled in any screen where it is used. If the Active indicator is checked it depends on the Active indicator for the particular screen where the link is used whether or not the link is enabled.

When using parameters some extra syntax rules are applicable for the URL. See the description for the next screen below for the correct formatting of the URL.



**Figure 36: Link definition screen**

It is recommended to specify a tooltip. If no tooltip is specified an ugly “N/A” appears when hovering over the button, instead of a useful description (See Figure 37), especially when no alternative icon is used. When more than one link is specified without custom icons or tooltips one needs to know by heart what the correct button is.



**Figure 37: without and with tooltip**

Adding an alternative icon for a link is little bit more laborious. It I described in the “Installation, Configuration and DBA Manual”.

### 8.1.2. Module HTTP-Links

In the previous screen the HTTP-link was defined, but the link was not attached to a screen. This attachment is done through the screen “Module HTTP-Links”

(Menu option: System / Management / General / Module HTTP-Links). The screen is shown in Figure 38

| Module | Description | Button | Description | Active                   |
|--------|-------------|--------|-------------|--------------------------|
|        |             |        |             | <input type="checkbox"/> |
|        |             |        |             | <input type="checkbox"/> |
|        |             |        |             | <input type="checkbox"/> |
|        |             |        |             | <input type="checkbox"/> |
|        |             |        |             | <input type="checkbox"/> |
|        |             |        |             | <input type="checkbox"/> |
|        |             |        |             | <input type="checkbox"/> |
|        |             |        |             | <input type="checkbox"/> |

| Variables       |                  |           |        |
|-----------------|------------------|-----------|--------|
| Module Variable | Request Variable | Parameter | Format |
|                 |                  |           |        |
|                 |                  |           |        |
|                 |                  |           |        |
|                 |                  |           |        |
|                 |                  |           |        |

**Figure 38: Linking HTTP-links to screens and defining variables**

In the upper block of the screen the actual linking between an HTTP-Link and a screen (module) is done. These parameters are described in the table below. There should be no surprises.


| Parameter   | Description                                                      | Mandatory? |
|-------------|------------------------------------------------------------------|------------|
| Module      | The code of the module.                                          | Yes        |
| Button      | A number from 1 to ??                                            | Yes        |
| Description | The name of the link as specified in the screen HTTP-Link        | Yes        |
| Active      | Indicator enabling or disabling the link <i>for the Module</i> . | Yes        |

The Lower block of the screen is the really interesting part. Here the possible parameters are defined that can be used in the HTTP request when clicking on the button for the link. Every row in the lower block specifies a single parameter for the selected link in the upper block:

| Parameter        | Description                                                                    | Mandatory? |
|------------------|--------------------------------------------------------------------------------|------------|
| Module Variable  | The Dutch name of the variable in the OHI screen                               | Yes        |
| Request Variable | The request variable as it occurs in the URL specified in the screen HTTP-Link | No         |
| Parameter        | The request parameter as it appears in the URL                                 | Yes        |
| Format           | An optional formatting step before the data is inserted in the URL.            | No         |


### 8.1.3. Example

Let's use an (admittedly unrealistic) example: suppose we set up an HTTP-Link as in Figure x. It is a link to a well known website and we will use it to search for videos that a relation registered in OHI has posted. Who knows, maybe he has posted videos of him or herself participating in dangerous sports?



**Figure 39: Example HTTP Link**

We will then attach the link to the Maintain Relation screen, which is module REL1001F. Also the family name and first name(s) have to be included in the URL. Figure 39 shows how to do it.



**Figure 40: Example set up for a link**

Note that when specifying the URL and the request variables the angular brackets (< and >) are not optional.

Now when entering a saving a relation with, say, last name Doe and first name John and clicking on the button that holds our link then the values will be substituted:

`http://www.youtube.com/results?search_query=<first_name>%20<last_name>`

becomes:

`http://www.youtube.com/results?search_query=John%20Doe`

The browser will link to this URL in a new page.



## 9. OHI Back Office Business Services

The OHI Back Office Business Services add integration facilities for a service oriented environment. The business services are part of a service layer for retrieving and updating core OHI Back Office data.

The 'Find' and 'Get' services are used to retrieve data from OHI Back Office. 'Write' services are used to store data in the OHI Back Office database.

OHI BO Business Services are implemented as PL/SQL services and made available through synchronous SOAP/HTTP web services.




Figure 41: OHI Business Services

### 9.1. Architecture

The OHI Back Office Business Services share the following characteristics:

- Segmentation into 'Find', 'Get', 'Write' and miscellaneous services to keep the complexity of each service within bounds.
- Each business service is implemented as a web service operation.
- Each web service is based on a WSDL which references versioned XSD files.
- Each web service is implemented as a SOAP 1.1/HTTP, document-style web service.
- Each business service is atomic and stateless ('fire and forget')
- Each 'Write' business service must be idempotent, which means that the response and effect must be the same for different calls with the same data.
- The actual work is carried by a PL/SQL 'service'. The web service acts as an interface between the caller and the PL/SQL service.

A more complete set of characteristics can be found in [Doc\[2\]](#).

### 9.2. Implementation

The starting point is a WSDL designed by OHI Back Office. The WSDL defines each operation with its inbound and outbound messages. The messages and underlying

XSD types are defined in versioned XSD files. Where appropriate, XSD types use enumerations to translate OHI domain values to meaningful values.

SVL web services consist of the following components:

- A Java web service (WAR file) based on a WSDL designed by OHI Back Office. For each WSDL operation, the Java web service maps the inbound and outbound objects to SQL types which are processed by;
- a PL/SQL web service package which contains the business logic to transform and process the;
- SQL types which hold the content of the inbound and outbound objects.

---

#### 9.2.1. Difference with C2B architecture

---

The C2B services were generated from data derived from Designer to call existing PL/SQL packages. Although this 'inside out approach' lent itself well for 100% code generation, the resulting web services were rigid and required application developers to transform objects to the format used internally by OHI and vice versa.

The SVL services are designed 'outside in' which means that every component can be derived to an XSD definition. This allows greater flexibility and contributes to a more user friendly XML content.

---

#### 9.2.2. The PL/SQL Service

---

The development of a business service starts with an XSD. Once the XSD for a web service is completed, the SQL type for holding element data are generated as well the Java classes to process XML content to object instances and vice versa.

The PL/SQL part of the web service is handled by a 'PL/SQL service' : a PL/SQL package which implements each business service as a packaged function, using SQL types for processing content.

### 9.3. Find, Get and Write Services

There are four types of service:

- Find services  
These are typically for retrieving a list of objects to select from: many objects, few details.
- Get services  
A 'get' service returns a single object with detailed information.
- Write services  
Write an object to the OHI Back Office database.
- Miscellaneous services  
Examples: a service to get the next free relation number or a service which acts as a 'service consumer' to an external web service.

With these different service types it should be possible to build a client application and keep the complexity of each service within bounds.

### 9.4. Service consumers

A small number of the OHI Back Office business services are called 'service consumers', which means that these services are used as a proxy for calling external services.

Examples: Vecozo service, procedure authorization.

## 9.5. Write Services

The current, second-generation of write services supports idempotent behavior, selective updates and processes time-valid data. The first service of this new breed is the WriteRelation service.

The existing first-generation 'write' services will be migrated to the new paradigm over time.

### 9.5.1. Idempotent behavior

---

'Write' services should have idempotent behavior to ensure that each subsequent call to a business service with the same data will return the same response and have the same effect as the first call.

Note that this requirement does not apply for 'Find' and 'Read' services, because the contents of the data base may have changed between subsequent service calls.

### 9.5.2. Selective updates

---

'Write' services are used both for inserting and updating data into the OHI Back Office data base. When updating, 'write' services support selective updates to allow the caller to send a partial message. The advantage is that the calling application only needs to know a subset of the data which can be processed by the business message. For example a self-service application only needs to have very little data to allow an end user to update his residential address.

In the example below, the name and phone number are set for relation 1864856800:

```
<v11:Person>
  <v11:relationNumber>1864856800</v11:relationNumber>
  <v11:name>Bakker</v11:name>
  <v11:phoneNumber>06-51227410</v11:phoneNumber>
</v11:Person>
```

If we want to change the name, we can simply pass the new name:

```
<v11:Person>
  <v11:relationNumber>1864856800</v11:relationNumber>
  <v11:name>Slager</v11:name>
</v11:Person>
```

We can also wipe the contents of a column, for example the phone number:

```
<v11:Person>
  <v11:relationNumber>1864856800</v11:relationNumber>
  <v11:phoneNumber></v11:phoneNumber>
</v11:Person>
```

#### 9.5.2.1. 'Zero' update

Leaving out a tag means that its related data is left untouched. This is the cornerstone for selective updates.

#### 9.5.2.2. Use *xsi:nil* to remove existing values

With empty tags you can wipe lists and simple string values. If you want to wipe values which are enumerations or other data types, you should use the nil attribute, like below:

```
<v11:startDate xsi:nil="true"/>
```

Note that the xsi namespace should refer to <http://www.w3.org/2001/XMLSchema-instance>.

### 9.5.2.3. Lists

Lists can have 0 or more elements which together are enclosed in a list-tag, like in the example below:

```
<v11:Person>
  <v11:relationNumber>1864856800</v11:relationNumber>
  <v11:bankAccountList>
    <v11:bankAccount>
      <v11:accountNumber>
        NL42RABO0111750768
      </v11:accountNumber>
      <v11:bankRelationNumber>
        1525725800
      </v11:bankRelationNumber>
      <v11:bankAccountType>IBANAccount</v11:bankAccountType>
      <v11:countryCode>NL</v11:countryCode>
      <v11:currencyCode>EUR</v11:currencyCode>
    </v11:bankAccount>
  </v11:bankAccountList>
</v11:Person>
```

To support selective updates, lists are optional. If you do not want to update a list of details, just omit the list and its surrounding list tag:

```
<v11:Person>
  <v11:relationNumber>1527308300</v11:relationNumber>
  <!--<v11:bankAccountList/> -->
</v11:Person>
```

Likewise , if you want to delete the list, use an empty list tag:

```
<v11:Person>
  <v11:relationNumber>1527308300</v11:relationNumber>
  <v11:bankAccountList/>
</v11:Person>
```



**Note:** if you add a list to the request you must include all elements. You cannot add a list with a single element just to update the single element. In that case all other elements will be deleted.

### 9.5.2.4. Time-valid lists

Time-valid lists are used to create and update data with a start and end date, such as addresses, marital statuses etc.

They share some characteristics with ordinary lists:

- Time valid lists are optional: the list related data in the OHI Back Office database are not updated if you omit the list tag altogether.
- All list-related data in the OHI Back Office are deleted if you specify an empty list tag.

The difference is that you can use time-valid lists to update the current situation without removing past data.

Consider the following example to register that Peter is no longer married since 1 January 2013:

```
<v11:maritalStatusList>
  <v11:maritalStatus>
    <v11:startDate>2013-01-01</v11:startDate>
  </v11:maritalStatus>
</v11:maritalStatusList>
```

```

        dissolved marriage / dissolved registered partnership
    </v11:maritalStatus>
</v11:maritalStatus>
</v11:maritalStatusList>

```

This information is processed as follows:

- The start date of 1 January 2013 is used as a reference date.
- Peter's previous marital status record (married) is ended by 31 December 2012
- Peter's marital status records starting after the reference date are deleted (if they exist)
- A new marital status record to indicate Peter's current status is created with a start date of 1 January 2013.

#### 9.5.2.5. *Segmented time-valid lists*

The mechanism described above is too coarse for processing time-valid information like addresses, since you may have different home and postal addresses at any point in time.

This is solved with segmented time-valid lists: this means that the list is processed once for every segment, for example 'address type'.

Consider the following example where John's home address is updated:

```

<v11:addressList>
  <v11:address>
    <v11:startDate>2010-06-04</v11:startDate>
    <v11:addressType>Home</v11:addressType>
    <v11:street>Haverstraat</v11:street>
    <v11:houseNumber>41</v11:houseNumber>
    <v11:postalCode>3511NB</v11:postalCode>
    <v11:countryCode>NL</v11:countryCode>
  </v11:address>
</v11:addressList>

```

This information is processed as follows:

- The start date of 4 June 2010 is used a reference date for John's home addresses
- John's previous home address is ended at 3 June 2010
- John's home addresses starting after the reference date are deleted.
- A new home address is registered starting 4 June 2010
- John's postal addresses remain untouched.

We can update John's home addresses and postal addresses in one go:

```

<v11:addressList>
  <v11:address>
    <v11:startDate>2010-06-04</v11:startDate>
    <v11:addressType>Home</v11:addressType>
    <v11:street>Haverstraat</v11:street>
    <v11:houseNumber>41</v11:houseNumber>
    <v11:postalCode>3511NB</v11:postalCode>
    <v11:countryCode>NL</v11:countryCode>
  </v11:address>
  <v11:address>
    <v11:startDate>2010-07-01</v11:startDate>
    <v11:addressType>Postal</v11:addressType>
    <v11:street>Postbus</v11:street>
  </v11:address>
</v11:addressList>

```

```

        <v11:houseNumber>306</v11:houseNumber>
        <v11:postalCode>3300AH</v11:postalCode>
        <v11:countryCode>NL</v11:countryCode>
    </v11:address>
</v11:addressList>

```

Note that an empty address list will delete all John's addresses:

```

<v11:addressList>
</v11:addressList>

```



**Note:** segmentation is not necessarily restricted to a single element (like address type in this case)



**Note:** consult the functional specification to find out whether a time-valid list is segmented and which elements are used for segmentation.

#### 9.5.2.6. XSD types for Write services.

When examining an XSD for a web service with 'Write' operations you will find that the complex types used by Write Services are prefixed with 'PX'.

You will also find that these complex types largely consist of optional elements. This is needed to support selective updates.

There is a downside to this optionality: if you leave out many elements when entering new data, your inbound XML will still validate correctly against the XSD.

However when sending the request, the OHI Back Office business rules come into play and raise exceptions if your data is incomplete or incorrect.

It would be too complex to document which business rules you may encounter.

Our advice for validating a client application using a 'Write' service would be to always include various tests with new data.

## 9.6. Error Handling

Two types of SOAP faults when running a web service operation:

- Functional SOAP fault: indicates an error which occurred in the PL/SQL service.  
In many cases the functional SOAP fault will contain CDM Rule Frame error messages rather than error messages created specifically for the business services.
- Technical SOAP fault: any other fault except a functional SOAP fault.

---

## 10. Custom Development Practices

By giving you an 'open database', OHI Back Office gives you great freedom to develop your own code.

With freedom comes responsibility.

As we explained in the 'Overview' chapter, OHI Back Office is an 'all in one' engine to process claims and policies for health care payers.

A badly written piece of custom code can slow down the core processes for which it is intended or even block the operation of other, unrelated processes.

What follows here is a minimum of tips to prevent these risks.

### 10.1. Create a custom schema

You should create a custom schema because you are not allowed to connect to the OHI Back Office schema, let alone create your own database objects in the OHI Back Office schema.

---

#### 10.1.1. How many schema's do you need?

You may have multiple custom applications which interface with OHI Back Office, for example a self-service portal, custom batch processing scripts, and an interface which processes CRM data into OHI Back Office.

Each of these applications may be created by a different team and have a different release schedule.

In that case, a custom schema per application makes it easier to manage these different applications and split the post-installation work and testing efforts whenever a new OHI Back Office release is installed.

### 10.2. Use an abstraction layer

We cannot stop progress, so OHI Back Office will keep evolving with every new release. This means many smaller or larger changes to the OHI Back Office data model and PL/SQL packages.

Adapting your custom code to the new release should be as little work as possible .

Using an abstraction layer for your custom code helps you to reduce the amount of code and more importantly, the number of references to the OHI Back Office data model and PL/SQL functions.

This is what your abstraction layer should do:

- Make your code DRY
- Encapsulate business logic with packaged procedures.
- Create custom views to query OHI Back Office data.
- Use the OHI Back Office TAPI's for DML operations.
- Call custom packaged functions from Dynamic PLSQL hooks

---

#### 10.2.1. Make your code DRY

DRY means Don't Repeat Yourself. It is all about replacing duplicate code with your own functions and function calls until you arrive at the minimum amount of code which can still be easily understood and maintained. This has nothing to do with OHI Back Office, it is just good programming practice.

### 10.2.2. Encapsulate business logic with packaged procedures

---

The purpose here is to reduce the amount of code which directly depends on OHI Back Office.

If you have large chunks of custom PL/SQL code, split each chunk in 'control' code (the part which evaluates parameters etc.) and functional code (the part which does the processing). Put the processing part in one or more packaged procedures, so that your controlling code does not do much more than call packaged procedures.

Now review your packaged procedures to separate business logic from DML logic (the code which refers directly to OHI Back Office database objects). Put the DML logic in packaged functions.

Caveat: when defining parameters for your custom packaged functions, do not refer to the OHI Back Office tables to keep the dependency of OHI Back Office code to a minimum.

### 10.2.3. Create custom views

---

Whenever the OHI Back Office data model changes, it is much less work to revise a small number of views than to repair many individual queries, because views create another abstraction level.

When defining these views it may be attractive to 'stack' views on top of each other and reach an even higher abstraction level. However, this may hurt the performance of your custom code.

As soon as you need to improve the performance of your custom development code, replace 'stacked' views with individual views based directly on the OHI Back Office tables.

### 10.2.4. Call custom packaged functions from Dynamic PLSQL hooks

---

Create your own custom packaged procedures to be called by the Dynamic PLSQL hooks in OHI Back Office.

## 10.3. Define your transactions

The simplest definition of a transaction is 'everything that happens between two commits'.

A better definition (Wikipedia) is 'A database transaction, by definition, must be atomic, consistent, isolated and durable (ACID)'. In order to comply with this definition you should design your transactions as the smallest unit of work can be committed or rolled back.

The notion of the smallest unit of work is important because the longer the duration of a transaction, the more tables and rows are locked which cannot be updated by other processes at the same time.

The notion of a 'unit' of work is important as well: a well-designed transaction ensures that each time the same actions are performed. If a transaction is defined as a limited set of operations it is easier to debug and reduce side-effects. The limited set of operations also makes it easier to predict the duration of the transaction.

General rules:

- Long sessions will keep tables and rows locked and will hinder other processes.
- Do not put transaction control statements in lower-level routines.
- If you anticipate to process hundreds of thousands of rows within a single transaction it may be wise to create multiple transactions.



### 10.3.1. Transactions and CDM RuleFrame

---

OHI Back Office uses CDM RuleFrame to enforce business rules, many of which are only evaluated when the transaction is closed or committed.

You may use

- `Api_algemeen_pck.start_api_transactie`  
Calls `qms_transaction.open_transaction` to open a CDM Rule Frame transaction.
- `Api_algemeen_pck.einde_api_transactie`  
Calls `qms_transaction_mgt.close_transaction` to close the CDM Rule Frame transaction.

Structuring your transaction is important to avoid confusing results when the rules on the Rule Stack are finally evaluated.

More information about CDM RuleFrame in 'Appendix D – What you should know about CDM RuleFrame'.

## 10.4. Locking

If your code does not explicitly lock database rows, the locks in your session will be implicit locks resulting from updates on individual rows. These locks will be released when you commit or roll back your transaction.

This strategy would be OK if the application does not have long running transactions.

Since OHI Back Office is batch oriented, your code should always take into account that:

- a long running process may have locked the same data that your code tries to update.
- another process may be waiting for you to release the locks you have (implicitly) set in your transaction.
- a worst case scenario may evolve if your code waits to lock a row while other processes are waiting to lock the rows already locked by your code.

The safest advice is to:

- do not use 'lock table' statements
- use 'select for update nowait' cursors if you intend to update data.

If one of the selected rows is already locked by another transaction, the 'select for update nowait' cursor will raise a 'resource\_busy' exception.

It is then up to you to process the 'resource\_busy' exception. By default your transaction will be rolled back and control will be handed to the calling program.

## 10.5. Use Named Parameters

When calling an OHI Back Office function or procedure, you can choose to make the call with 'positional' or 'named' parameters.

```
l_rel_no := api_en_relation_details.adjudicate_manually
           ( 1234567800
             , 'D'
             , 'Approved by management'
           );
```

Figure x: call with positional parameters

```
l_rel_no := api_en_relation_details.adjudicate_manually
           ( p_no           => 123467800
             , p_new_status => 'D'
```

```
, p_explanation => 'Approved by management'
);
```

Figure x: call with parameters

Using named parameters makes your code easier to understand and maintain. It also makes your code less dependent of a specific version of OHI Back Office because as long as no mandatory parameters are added to the OHI Back Office function, it will compile. On the other hand, if Oracle adds mandatory parameters, the compilation will raise a syntax error which tells you which function call failed to compile.

## 10.6. Profile your code

As a whole, OHI Back Office works best if there are no long running transactions. Your custom code may hinder other processes if it takes too long to run due to badly performing queries.

You should ensure that you use the database resources efficiently:

- Open SQLDeveloper
- Connect to a non-production OHI database with production-like volumes
- Copy each query to the workspace
- Select 'explain' to explain your query
- Iteratively refine your query

If you don't use SQLDeveloper, use EXPLAIN PLAN (See SQL Reference for details).

## 10.7. Close open cursors

When possible use cursor-for loops. Apart from requiring less code, cursor-for loops automatically close their cursors. This is important to avoid the 'ora-01000 maximum open cursors exceeded' exception.

If you explicitly open a cursor, for example to fetch a single row, you should close the cursor as soon as possible. If an exception is raised before the cursor is closed, the cursor remains open and must be explicitly closed (test with %ISOPEN).

## 10.8. Coding Standards

We did not include any naming or formatting conventions because we felt these would confuse the issues discussed.

---

## 11. Deprecated Interfacing options

The following interfacing options are still available but will be obsolete in a future release:

- API layer (PL/SQL Functional API)
- API views (if these still exist)
- Connect 2 Backoffice (C2B) web services

## 12. Appendix A - Business event framework datamodel

| ALG_EVENT_DEFINITIES                                  |                                                                                                                                                                 |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| This table holds the event definitions                |                                                                                                                                                                 |
| NAAM (Name)                                           | This is a logical name for the event type, for example: AZR_MODIFY_PARTY.                                                                                       |
| OMS (Description)                                     | For example: Export updates to parties to the XYZ system.                                                                                                       |
| DETECTOR                                              | A custom plug-in procedure which is called to detect events for this event definition. Example: azr_mod_prt_pck.detector.                                       |
| BEGIN_HANDLER                                         | A plug-in procedure that must be called once before processing events for this type, for example to create a .csv file to which all event data will be written. |
| HANDLER                                               | A plug-in procedure which is called for every event that must be processed. Example: my_event_pck.handler.                                                      |
| END_HANDLER                                           | A plug-in procedure which is called once after all events have been processed, for example to close a .csv file to which all event data were written.           |
| LAATSTE_DETECTIE_DATUM (last_detection_date)          | Used by the framework to record the last date when the detection mechanism was used.                                                                            |
| STATUS                                                | Updated by the framework to avoid multiple starts of the framework for this event definition. The status can be: 'K' (ready) or 'L' (running).                  |
| RUN_NR                                                | Managed by the framework. All events that were detected in a single run are given the same run number for later processing and reporting.                       |
| SCHONINGSINTERVAL_VERWERKT (Purge interval processed) | Defines when (successfully) processed events for this definition may be purged. The default interval is 7 days.                                                 |
| SCHONINGSINTERVAL_MISLUKT (Purge interval failed)     | Defines when failed events for this definition may be purged. The default interval is 27 days.                                                                  |
| IND_ACTIEF (Active indicator)                         | Indicates whether the event is currently active.                                                                                                                |

| ALG_EVENT_INIT_WIJZIGINGEN                                                         |                                                                          |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| This table holds the tables which are monitored by the event for triggered events. |                                                                          |
| EDE_ID                                                                             | Foreign key to ALG_EVENT_DEFINITIES.                                     |
| TAB_ID                                                                             | Foreign key to ALG_TABELLEN.                                             |
| IND_INSERT                                                                         | Indicates whether insert actions on the table should be signaled.        |
| DPS_ID_INSERT                                                                      | Foreign key to ALG_DYN_PLSQL_DEFINITIES to fine-tune the insert trigger. |
| IND_UPDATE                                                                         | Indicates whether update actions on the table should be signaled.        |
| DPS_ID_UPDATE                                                                      | Foreign key to ALG_DYN_PLSQL_DEFINITIES to fine-tune the update trigger. |
| IND_DELETE                                                                         | Indicates whether delete actions on the table should be signaled.        |
| DPS_ID_DELETE                                                                      | Foreign key to ALG_DYN_PLSQL_DEFINITIES to fine-tune the delete trigger. |

| ALG_EVENT_INIT_WIJZIGINGEN                                                         |                                                  |
|------------------------------------------------------------------------------------|--------------------------------------------------|
| This table holds the tables which are monitored by the event for triggered events. |                                                  |
| IND_ACTIEF (Active indicator)                                                      | Indicates whether the event is currently active. |

| ALG#EVENTS                                                 |                                                                                                                                                                                                                                                                                                                   |
|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| This table stores events with storage clause set to Table. |                                                                                                                                                                                                                                                                                                                   |
| EDE_ID                                                     | Foreign key to the ALG_EVENT_DEFINITIES table for the event definition that signaled this event.                                                                                                                                                                                                                  |
| EDE_RUN_NR                                                 | Set by the framework to group event occurrences. The highest run number is stored in the event definition.                                                                                                                                                                                                        |
| CODE                                                       | Code retrieved by the detection plug-in for use as a key to process the event. In most cases this will be the primary key that can be used to find the data with which the event is to be processed. To be compatible with storing the event to the queue this should be in format table_id##record_id##DML-type. |
| STATUS                                                     | Records the processing status of an event occurrence. Possible values: 'N' (new), 'O' (pending), 'V' (processed), 'M' (failed).                                                                                                                                                                                   |
| DATUM_ORIGINEEL (original date)                            | An optional column that can be used to determine the processing order.                                                                                                                                                                                                                                            |
| CREATIE_MOMENT (creation date)                             | This standard column is used for processing in the correct order if the DATUM_ORIGINEEL has not been set.                                                                                                                                                                                                         |

| ALG#EVENT_ERRORS                                        |                                                                                                                          |
|---------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| This table holds errors during the handling of an event |                                                                                                                          |
| EDE_ID                                                  | Refers to the event definition that detected this event.                                                                 |
| TAB_ID                                                  | Foreign key to ALG_TABELLEN, source table of the record                                                                  |
| RECORD_ID                                               | Refers to the record of the changed record. Together with TAB_ID this uniquely identifies the record in OHI Back Office. |
| DML_TYPE                                                | What DML action caused the event                                                                                         |
| EET_ID                                                  | Refers to the event in ALG#EVENTS table.                                                                                 |
| CODE                                                    | Code for event processing.                                                                                               |
| CREATIE_MOMENT (creation date)                          | Timestamp when the error occurred                                                                                        |
| FOUTCODE (Error code)                                   | The code of the error occurred.                                                                                          |
| FOUTMELDING (Error message)                             | The error message for the error that occurred.                                                                           |

| ALG_EDE_PAYLOAD_TP                         |                                                                                                                          |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| The object for storing events to the queue |                                                                                                                          |
| EDE_ID                                     | Refers to the event definition that detected this event.                                                                 |
| TAB_ID                                     | Foreign key to ALG_TABELLEN, source table of the record                                                                  |
| RECORD_ID                                  | Refers to the record of the changed record. Together with TAB_ID this uniquely identifies the record in OHI Back Office. |
| DML_TYPE                                   | What DML action caused the event                                                                                         |

### 13. Appendix B - Business event interface ALG\_EVENT\_INTERFACE\_PCK

| Procedures           |                                                                                                                                         | Parameters         |                                                      |                                                                                                              |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--------------------|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Name                 | Description                                                                                                                             | Name               | Type                                                 | Description                                                                                                  |
| Install              | Creates an event definition in the database. Also available as function returning alg_event_definities.id%type.                         | pi_name            | alg_event_definities.naam%type                       | The name of the event definition.                                                                            |
|                      |                                                                                                                                         | pi_description     | alg_event_definities.oms%type                        | The description of the event definition.                                                                     |
|                      |                                                                                                                                         | pi_event_type      | alg_event_definities.type_signalering% type          | Indicates how the event is signaled.<br>Allowable values:<br>D for Detected events<br>T for Triggered events |
|                      |                                                                                                                                         | pi_storage         | alg_event_definities.type_opslag%type                | Indicates how events are stored.<br>Allowable values:<br>T for Table<br>Q for Queued                         |
|                      |                                                                                                                                         | pi_handler         | alg_event_definities.handler%type                    | The (package) procedure for the handler of the event.                                                        |
|                      |                                                                                                                                         | pi_detector        | alg_event_definities.detector%type                   | The (package) procedure for the detector of the event.                                                       |
|                      |                                                                                                                                         | pi_begin_handler   | alg_event_definities.begin_handler% type             | The (package) procedure for the begin handler of the event.                                                  |
|                      |                                                                                                                                         | pi_end_handler     | alg_event_definities.end_handler%type                | The (package) procedure for the end handler of the event.                                                    |
|                      |                                                                                                                                         | pi_purge_processed | alg_event_definities.schoningsinterval_verwerkt%type | Determines after how many days successfully processed events can be deleted from the event table.            |
|                      |                                                                                                                                         | pi_purge_failed    | alg_event_definities.schoningsinterval_mislukt%type  | Determines after how many days failed events can be deleted from the event table.                            |
| deinstall            | Removes an event definition form the database. When events still exist for this definition an error is given.                           | pi_name            | alg_event_definities.naam%type                       | The name of the event definition to be removed from the database.                                            |
| deinstall            | Removes an event definition form the database. When events still exist for this definition an error is given.                           | pi_edc_id          | alg_event_definities.id%type                         | The ID of the event definition to be removed from the database.                                              |
| purge_all_events     | Removes all events for the given event definition from the database. Can be used prior to the deinstall procedure to remove all events. | pi_name            | alg_event_definities.naam%type                       | The name of the event for which all the event occurrences will be removed.                                   |
| purge_all_events     | Removes all events for the given event definition from the database. Can be used prior to the deinstall procedure to remove all events. | pi_edc_id          | alg_event_definities.id%type                         | The ID of the event definition for which all the event occurrences will be removed                           |
| reapply_failed_event | Reset events with the status 'Failed' from a                                                                                            | pi_name            | alg_event_definities.naam%type                       | the unique name of the event definition                                                                      |

| Procedures           |                                                                                                                                                                                                                                                                                                                                                                                                                   | Parameters      |                                |                                                                                                            |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|--------------------------------|------------------------------------------------------------------------------------------------------------|
| Name                 | Description                                                                                                                                                                                                                                                                                                                                                                                                       | Name            | Type                           | Description                                                                                                |
|                      | previous run.                                                                                                                                                                                                                                                                                                                                                                                                     | pi_code         | alg#events.code%type           | the identifying code of the event                                                                          |
| reapply_failed_event | Reset events with the status 'Failed' from a previous run.                                                                                                                                                                                                                                                                                                                                                        | pi_eide_id      | alg_event_definities.id%type   | the unique identifier of the event definition                                                              |
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                   | pi_code         | alg#events.code%type           | the identifying code of the event                                                                          |
| add_event            | This procedure must be called by the detector of an event to add an occurrence of the event to the event table or queue.<br>When the storage type of the event is set to Table, the event is only created in case there is no existing event with the given code for the event definition with a status N(ew).<br>When the storage type of the event is set to Queue, the event is always placed on the queue.    | pi_name         | alg_event_definities.naam%type | The name of the event definition.                                                                          |
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                   | pi_code         | alg#events.code%type           | The identifying code of the event. Must be in format:<br>Table_id##record_id##dml_type. E.g. 1234##876##U. |
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                   | pi_date         | alg#events.master_date%type    | Optional timestamp for ordering event handling.                                                            |
| add_event            | This procedure must be called by the detector of an event to add an occurrence of the event to the event table of queue.<br>When the storage type of the event is set to Table, the event is only created in case there is no existing event with the given code for the event definition with a status N(ew).<br>When the storage type of the event is set to Queue, the event is always placed on the queue.    | pi_eide_id      | alg_event_definities.id%type   | The ID of the event definition.                                                                            |
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                   | pi_code         | alg#events.code%type           | The identifying code of the event. Must be in format:<br>Table_id##record_id##dml_type. E.g. 1234##876##U. |
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                   | pi_date         | alg#events.master_date%type    | Optional timestamp for ordering event handling.                                                            |
| add_event            | This procedure must be called by the detector of an event to add an occurrence of the event to the event table or queue.<br>In case the storage type of the event is set to Table, the event is only created when there is no existing event with the given code for the event definition with a status N(ew).<br>In case the storage type of the event is set to Queue, the event is always placed on the queue. | pi_eide_payload | alg_eide_payload_tp            | The object type containing the data of the event.                                                          |
| type_payload_to_code | Function which converts a storage type Queue payload type to a storage type Table format. Returns alg#events.code in the format table_id##record_id##dml_type. E.g. 1234##876##U                                                                                                                                                                                                                                  | pi_eide_payload | alg_eide_payload_tp            | The object type containing the data of the event.                                                          |
| code_payload_to_type | Function which converts a storage type Queue payload type to a storage type Table format. Returns alg_eide_payload_tp.                                                                                                                                                                                                                                                                                            | pi_name         | alg_event_definities.naam%type | The name of the event definition.                                                                          |
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                   | pi_code         | alg#events.code%type           | The identifying code of the event. Must be in format:<br>Table_id##record_id##dml_type. E.g. 1234##876##U. |



| Procedures           |                                                                                                                       | Parameters |                              |                                                                                                               |
|----------------------|-----------------------------------------------------------------------------------------------------------------------|------------|------------------------------|---------------------------------------------------------------------------------------------------------------|
| Name                 | Description                                                                                                           | Name       | Type                         | Description                                                                                                   |
| code_payload_to_type | Function which converts a storage type Queue payload type to a storage type Table format. Returns alg_eде_payload_tp. | pi_eде_id  | alg_event_definities.id%type | The id of the event definition.                                                                               |
|                      |                                                                                                                       | pi_code    | alg#events.code%type         | The identifying code of the event. Must be in format:<br>Table_id##record_id##dml_type. E.g.<br>1234##876##U. |

## 14. Appendix C - Tracing

The application code of OHI Back Office has been instrumented to trace the PL/SQL code as it is executed. Both the CAPI packages, batch packages and underlying packages of the OHI Back Office Business Services have been instrumented.


By turning on tracing you get a detailed overview to help you analyze the program flow. This is useful if you want to debug or understand a problem.

You can also instrument your custom code with trace calls.

### 14.1. Activation

#### 14.1.1. Tracing a Batch Request

You can trace a batch request by activating the indicator “Debug” when creating the request.



#### 14.1.2. Tracing a Forms Session

You can trace a form by setting the indicator “Debug” in screen SYS1017F:



### 14.2. How to Access Trace Logs

The log information is written into two tables:

- **ALG#TRACE\_SESSION:** This table contains session information per debug session, like the session id, the user and module code in case of a forms session.
- **ALG#TRACE\_LOG:** This table contains all the data of a trace per session. It also records the PL/SQL object and the procedure stack of the call to the trace package (ALG\_TRACE\_LOG).

With the OHI Back Office parameter “DebugLines” the maximum amount of trace records per session can be set as a session can create a huge set or records.

Records in ALG#TRACE\_SESSION and ALG#TRACE\_LOG will be purged automatically after a certain threshold. This threshold can be set with the BackOffice parameter “RetentieTLG”.

### 14.3. Instrumentation of Custom Code

You can instrument your own code using the various procedures of the ALG\_TRACE\_PCK package:

| Procedure   | Description                                                                        |
|-------------|------------------------------------------------------------------------------------|
| Enable      | Activate a debug session                                                           |
| Disable     | De-activate the debug session                                                      |
| Enter       | Should be called at the start of a function or procedure. Helps following the flow |
| Leave       | Should be called at the end of a function or procedure.                            |
| Log         | Provide extra logging                                                              |
| Force_write | Force writing of debug information from memory to the table                        |



**Note:** Avoid the use of disable / enable in low level code.

---

## 15. Appendix D – What you should know about CDM RuleFrame

If you develop custom code to work with OHI Back Office you should know a few things about CDM RuleFrame:

- CDM RuleFrame was developed by Oracle Consulting around 1999.
- CDM RuleFrame uses Oracle Designer as its repository.
- OHI Back Office uses CDM RuleFrame to enforce business rules.
- In 2004-2005, the OHI Back Office team revised parts of CDM RuleFrame to solve performance issues.
- CDM RuleFrame has its own concept of a transaction to add functionality to the standard Oracle transaction.
- During the CDM RuleFrame transaction, rules are pushed to the 'Rule Stack': when a DML action is performed on a row in a table, the generated database trigger code calls the appropriate function in the table-specific TAPI package. This function puts those rules which cannot be evaluated immediately on Rule Stack for later evaluation.
- The rules that were pushed on the Rule Stack will be evaluated only when the CDM Rule Frame transaction is closed.
- You can avoid building a 'random' Rule Stack by explicitly defining your CDM Rule Frame transaction.
- You can start a CDM Rule Frame transaction in your custom code by calling `api_algemeen_pck.start_api_transactie`
- You can end a CDM Rule Frame transaction by calling `api_algemeen_pck.einde_api_transactie` or calling `COMMIT`

## 16. Appendix E – Modification Mechanism for Policies and Relations

OHI Back Office has a ‘modification mechanism’ to allow changes to policies and relations without hindering the core processes like claims processing.

OHI Back Office can be configured to allow direct DML on relations or to use the modification mechanism.

If the mechanism is used, the policy or relation that is to be updated is cloned, together with related child tables, for example addresses, discounts etc.

The cloned rows have negative ID's which are the negative value of the original (positive) ID. As the clone is being updated, the original rows are untouched, which allows the core processes to continue.

The cloning of a policy can be done with the `API_EN_POLICY_AND_DETAILS.MODIFY` function. The equivalent function for a relation is `API_EN_RELATION_DETAILS.MODIFY`.

The cloned policy or relation can be updated at will. However a delete on an already existing row in the original version cannot be deleted. If it is required to remove such record the column “`MODIFICATION_STATUS`” (“`mutatie_status`”) should be set with the capital letter “V”.

Once the user has completed the updates to the cloned policy or relation, the status of the clone is set to ‘READY’. The clone must then be approved manually or by a batch process (ZRG4021S).

Once the changed version has been approved, the clone data is merged with the original data and the clone is removed.

To merge the clone with the original policy use the function `API_EN_POLICY_AND_DETAILS.APPLY`.

The set of functions to manipulate a policy in the api `API_EN_POLICY_AND_DETAILS` are:

| Function             | Description                                                                           |
|----------------------|---------------------------------------------------------------------------------------|
| Modify               | Make a copy of a policy                                                               |
| Apply                | Merge the modified copy with the original                                             |
| Remodify             | In case of issues when applying the copy go back to the “Pending modification” status |
| Cancel               | Purge the copy policy                                                                 |
| Modification_pending | Check if there is already a copy of the policy                                        |

## 17. Appendix F – Dynamic PL/SQL Types

The following dynamic PL/SQL types are available in the given processed. Column bound checks are available on every functional table.

| Name                                                                    | Type           | Purpose                                                                                       |
|-------------------------------------------------------------------------|----------------|-----------------------------------------------------------------------------------------------|
| Adresveld (Address field)                                               | Check          | Validate the data of an address field against a address reference table                       |
| Adresveld bepaling ()                                                   | Text procedure | Determine address components based on e.g. the postal code in the OHI Back Office screens     |
| Back Office parameter ()                                                | Check          | Provide a validation on the values entered in the Back Office parameter values                |
| Betaalactie (Payment)                                                   | Text           | Provide a payment description used by the XML output for payments                             |
| Betalingsverkeerregel (Payment matching detail)                         | Text procedure | Determine the correct source (payment or collection) for this payment detail.                 |
| Commissieberekening (Commission calculation)                            | Text procedure | Calculate commission                                                                          |
| Commissieberekeningdatum (Commission calculation date)                  | Text procedure | Set the calculation date                                                                      |
| Commissieberekeningverzoek (Commission calculation request)             | Text procedure | Request a commission calculation                                                              |
| Commissieregelevaluatie (Commission rule evaluation)                    | Text procedure | Evaluate a commission rule                                                                    |
| Declaratieregel (Claimline)                                             | Check          | Validate a claimline                                                                          |
| Event (Event)                                                           | Check          | Provide a trigger condition for the triggered events in the Business event framework          |
| GBA-controle (Population register check)                                | Check          | Perform a check for a relation against a population register                                  |
| Incassoactie (Collection)                                               | Text           | Provide a payment description used by the XML output for collections                          |
| Kolomgebonden (Column bound)                                            | Check          | Perform a custom column bound check                                                           |
| Naamcomponent (Name component)                                          | Check          | Validate the data of a name component                                                         |
| Polis (Policy)                                                          | Check          | Perform a policy acceptance check                                                             |
| Poliscompleteerstap (Complete policy)                                   | Text procedure | Add additional data to a policy in the apply policy process (complete policy)                 |
| Restrictie (Restriction)                                                | Check          | Can be used to check if an entity flexfield is allowed on a subset of the data for the entity |
| Standaardantwoord op dekkingsvraag (Default answer to benefit question) | Text           | Provide a default answer for a benefit question                                               |
| XML (XML)                                                               | Text           | Add custom data on a record when performing an import of a XML file                           |

| Name                                            | Type  | Purpose |
|-------------------------------------------------|-------|---------|
| Zorgvoornemenperiode (Pre-authorization period) | Check |         |