



PRIMAVERA

**Connecting BPM 11g to P6
Release 8.4**

September 2014

Contents

Configuring Oracle BPM 11g to Work with P6	5
Pre-Integration Requirements for BPM 11g: Start Here.....	5
Integrating Oracle BPM 11g with P6.....	7
Modifying the P6 Environment for BPM 11g	7
Configuring P6 to Connect to Oracle BPM 11g	8
Verifying the Sample Workflow Configuration	9
Creating a Cluster Environment for BPM in WebLogic	10
Prerequisites for Creating a Cluster for BPM in WebLogic	10
Extending the WebLogic Domain to Create a New Cluster	10
Finalizing the Extended Schema for BPM.....	12
Testing the Connection for P6, BPM, and Web Services	12
Configuring WSDL Location and Service Endpoints.....	12
Deploying the SOA Composite.....	13
Deploy Client Application and Task UI Project	13
Assigning the TestConfig Role to Users	13
Troubleshooting and Known Issues for BPM 11g	14
Known Issues	14
Checking the P6 EPPM Web Services Logs	14
Configuring the Logging Level	14
Setting Logging On and Off	15
Oracle BPM 11g Logging.....	15
Troubleshooting Scenarios	15
Troubleshooting Connector Failures to Load Due to Configuration Issues.....	15
Troubleshooting P6 Workflows Portlet Failures To Load Data, Show Forms, Status Images, or Initiate a Process	15
BPM Workflows in P6	17
About Workflows	17
Working with Workflows in P6.....	17
Appendix	23
BPM 11g: Configuring SAML Web Service Clients for Identity Switching without Message Protection	23
Message Protection Policy	23
Setting the WSIdentityPermission	24
Creating the basic.credentials Key.....	24
Applying the New Policy	24
Configuring a Keystore if One Is Not Configured	25
For More Information	25
Where to Get Documentation	25

Where to Get Training..... 27

Where to Get Support 28

Legal Notices 30

Configuring Oracle BPM 11g to Work with P6

The Oracle Business Process Management (BPM) Suite provides an integrated environment for developing, administering, and using business applications centered around business processes. BPM supports BPM and Business Process Execution Language (BPEL) standards from modeling and implementation to run-time and monitoring.

P6 integrates with BPM 11g allowing you to initiate and manage workflows. You can use a sample project initiation workflow for P6 sample database that is available on OTN for 11g.

Looking toward the future, you can expand your investment in BPM to include workflows representing more stages of your application, program, project, or product development life cycle from design-time and implementation to run-time and application management.

The Oracle BPM Suite enables you to:

- ▶ Create and customize business processes, models, and standards using pre-defined components for web-based applications.
- ▶ Collaborate between process developers and process analysts.
- ▶ Expand business process management to include flexible, unstructured processes.
- ▶ Integrate your applications with Web Services.
- ▶ Add dynamic tasks and support approval routing using declarative patterns and rules-driven flow determination.

Unify different stages of your development life cycle by addressing end-to-end requirements for developing process-based applications. Oracle BPM 11g unifies the design, implementation, run time, and monitoring stages based on a Service-Oriented Architecture (SOA) infrastructure. This allows different personas to participate through all stages of the workflow life-cycle.

In This Section

Pre-Integration Requirements for BPM 11g: Start Here	5
--	---

Pre-Integration Requirements for BPM 11g: Start Here

Before continuing, ensure the following required conditions have been addressed:

Note: See the Tested Configurations document for information on supported versions.

- 1) Ensure you have installed Oracle Fusion Middleware SOA Suite and have an Oracle MDS Schema created (which is a pre-requisite for the Oracle Fusion Middleware SOA Suite).

- 2) On the domain where you will install P6 EPPM, configure WebLogic Middleware with Oracle Application Development Framework (Oracle ADF). This will ensure the P6 EPPM domain will have Oracle WSM Policy Manager and Oracle JRF modules, which you must have when integrating P6 EPPM with BPM. To download the Oracle ADF, refer to the following link: <http://www.oracle.com/technetwork/developer-tools/adf/downloads/index.html>

Note: If you installed the Oracle Fusion Middleware SOA Suite to the same WebLogic Middleware home where you installed P6 EPPM, then the Oracle ADF is already available and you can skip this step.

- 3) Download the Oracle BPM 11g Suite documentation from <http://www.oracle.com/technetwork/middleware/bpm/downloads/downloads-097443.html>.
- 4) See <http://www.oracle.com/technetwork/middleware/bpm/downloads/index-100737.html> to accept a license agreement and download a BPM package.
- 5) Install Oracle BPM 11g (11.1.1.7) PS5. See the BPM documentation at <http://www.oracle.com/technetwork/middleware/bpm/documentation/index.html> to guide you. If you will be designing and developing your own workflows in 11g, you will need JDeveloper with extensions or Oracle Business Process Composer for 11g.

Note: You can use BPM 11g (11.1.1.7) PS5 with P6 EPPM R8.4. Previous versions of 11g will not work with 8.4.

- 6) Install and configure P6 EPPM. This includes having completed any licensing requirements and downloading any documentation for P6 EPPM, including P6 and P6 EPPM Web Services.
 - a. Make sure you have a working configuration of P6. The term *P6* refers to the web application user interface for the main module in the P6 EPPM suite.
 - b. You must deploy the Oracle WSM Policy and JRF modules for P6 to work with BPM 11g. If you use the P6 EPPM Configuration Wizard, you can use it to deploy the Oracle WSM Policy and JRF modules. You will have to have a WebLogic domain to deploy the policy and module. You can also deploy the Oracle WSM Policy and JRF modules manually in WebLogic if you choose not to use the configuration wizard to do so.

Note: P6 EPPM Web Services and P6 (which includes Oracle WSM Policy manager and Oracle WSM JRF modules) can be on the same domain or separate domains.

- c. Make sure you have installed P6 EPPM Web Services and ensure its authentication mode matches BPM's authentication mode. For example, *Username Token Profile*, *SAML*, or *Cookies*.
- 7) Read the *P6 EPPM Media Pack* readme file to familiarize yourself with a few known issues relating to P6 and BPM.
- 8) Configure both BPM and P6 to work together. See ***Integrating Oracle BPM 11g with P6*** (on page 7) in this guide for steps.
- 9) To ensure the BPM functionality is available in P6, you must set up a username in BPM that matches an equivalent P6 username (only the username value must match; Passwords can be different between the environments).

You must assign the user in BPM the appropriate role to perform the functional requirements. Refer to **Testing the Connection for P6, BPM, and Web Services** (on page 12).

Integrating Oracle BPM 11g with P6

To integrate Oracle BPM 11g with P6, you must complete the following tasks in the specified order:

- 1) **Modifying the P6 Environment for BPM 11g** (on page 7).
- 2) **Configuring P6 to Connect to Oracle BPM 11g** (on page 8).

Modifying the P6 Environment for BPM 11g

You can use BPM 11g (11.1.1.7) with P6 EPPM R8.4. Previous versions of 11g will not work with R8.4.

To configure BPM 11g with P6 Release 8.4:

- 1) Create a new directory on the host where P6 is running. For example, **P6BPMConnector/P6** and **P6BPMConnector/BPM**.
- 2) In the P6 media pack `Tools\BPM Connector\11g` subfolder, locate the `prm-bpm-connector-11.1.1.X-v1.0.jar`
- 3) Copy the connector file listed above to the **P6BPMConnector/P6** folder you created. Determine the location of the BPM installation that you are using to integrate with P6. If you have multiple SOA Suite installations, ensure that you determine the location of the specific installation that you are integrating with P6.
- 4) Copy all the supporting jars from the BPM installation that you are using to integrate with P6 to the **P6BPMConnector/BPM** folder you created. Their default locations are listed:
 - ▶ `C:\oracle\Middleware\Oracle_SOA1\soa\modules\oracle.soa.fabric_11.1.1\`
`bpm-infra.jar`
 - ▶ `C:\oracle\Middleware\Oracle_SOA1\soa\modules\oracle.soa.workflow_11.1.1\`
`bpm-services.jar`
 - ▶ `C:\Oracle\Middleware\Oracle_SOA1\soa\modules\oracle.soa.fabric_11.1.1\`
`fabric-runtime.jar`
 - ▶ `C:\oracle\Middleware\oracle_common\modules\oracle.jmx_11.1.1\`
`jmxframework.jar`
 - ▶ `C:\oracle\Middleware\oracle_common\modules\oracle.jmx_11.1.1\`
`jmxspi.jar`
 - ▶ `C:\oracle\Middleware\oracle_common\bpm\modules\oracle.bpm.mgmt_11.1.1\`
`oracle.bpm.bpmn-em-tools.jar`
 - ▶ `C:\oracle\Middleware\oracle_common\soa\modules\oracle.soa.mgmt_11.1.1\`
`soa-infra-mgmt.jar`

- ▶ C:\Oracle\Middleware\wlserver_10.3\server\lib
wlclient.jar
- ▶ C:\Oracle\Middleware\oracle_common\webservices
wsclient_extended.jar
- ▶ C:\Oracle\Middleware\oracle_common\oui\lib
xml.jar
- ▶ C:\Oracle\Middleware\oracle_common\modules\oracle.xdk_11.1.0
xmlparserv2.jar

Note: The jars must be from the same BPM installation that will be integrated with P6.

5) Edit the weblogic.policy file:

- a. Locate the weblogic.policy file in one of the following locations:
In Windows: C:\WebLogic_Home\wlserver_10.3\server\lib
In Linux: /WebLogic_Home/wlserver_10.3/server/lib
- b. Add the following information in weblogic.policy file and restart the P6 application server.

```
grant codeBase "file:<full path to BPM support JAR directory> /*" {  
permission java.security.AllPermission;  
};
```

For example :

```
grant codeBase "file:C:/oracle/bpm111X/*" {  
permission java.security.AllPermission;  
};  
or  
grant codeBase "file:/home/oracle/bpm111X/*" {  
permission java.security.AllPermission;  
};
```

- c. Save and close the file.
- d. Restart the P6 application server.

Configuring P6 to Connect to Oracle BPM 11g

To connect P6 and BPM 11g:

- 1) Open the P6 Administrator application.
- 2) In the **Configurations** tab, expand your configuration.
- 3) Expand **Database/Instance[n]/BPM Settings**.
- 4) In the **Connector file location** field, enter the full path (including the file name) where you copied the connector files.

For example:

```
c:/oracle/bpm111x/eppmjars/prm-bpm-connector-11.1.1.x-v1.0.jar or  
/home/oracle/bpm111x/prm-bpm-connector-11.1.1.x-v1.0.jar
```


- 5) In the **BPM library path** field, enter the path of the directory where you copied all the 11g jars.

Note: If the above settings are incorrect or the BPM jar files are incomplete, you will be prompted with an error message when you try to configure the BPM. Verify that your settings and jar files are correct.

- 6) Right-click **BPM Configuration**, then select **Configure** to set options from the dialog box. If you receive an error message, check your values from the previous steps in this section.
- 7) To configure P6 to use BPM 11g, add the following settings:

Caution: Do not put a forward slash / at the end of the URL. For example, it should read only `http://host:port`, and not `http://host:port/`.

- a. In the **bpm.user** field, enter the BPM 11g user with administrative access to BPM.
- b. In the **bpm.password** field, enter the password for the user.
- c. In the **bpm.t3.url** field, enter the T3 URL for your Oracle SOA configuration. For example: `t3://host:port/soa-infra`
- d. In the **bpm.security.realm** field, enter the name of the security realm used by BPM. This is `jazn.com` by default.
- e. In the **bpm.soap.url** field, enter the URL for the SOAP services. Usually this URL takes the form of `http://host:port`.
- f. In the **bpm.workspace.url** field, enter an address in the form of `http://host:port` that indicates where the BPM Workspace application is hosted.

Note: The host can be an IP address or a host name such as a machine name. For WebSphere, see `http://publib.boulder.ibm.com/infocenter/wsdoc400/v6r0/index.jsp`.

- g. In the **bpm.partition** field, enter the name of the SOA partition containing the BPM composite applications you would like to use in P6. The default partition name is `default`.
- 8) Click **OK** and save changes. When the configuration is complete, you will see a **BPM properties have been configured** message.
- 9) Restart the P6 application server.

Verifying the Sample Workflow Configuration

The sample workflow provided uses Username Token Authentication and does not implement the message protection options of Nonce, Creation Timestamp, or SSL encryption. For the sample workflow to work, you must set the following settings to false or P6 EPPM Web Services will reject the messages sent from BPM.

To verify you configured the sample workflow correctly set the following to false:

- 1) Open the P6 Administrator application.
- 2) In the **Configurations** tab, expand your configuration.
- 3) Expand **Web Services/Security/Authentication**.
- 4) In the **Mode** field, select **Username Token Profile**.

- 5) Expand **Web Services/Security/Authentication/Username Token Profile/Nonce** and set **Require Nonce** to **false**.
- 6) Expand **Web Services/Security/Authentication/Username Token Profile/Created** and set **Require Created** to **false**.
- 7) Expand **Web Services/Security/Authentication/SAML Token Profile** and set **Require Signed SAML Token** to **false**.
- 8) Expand **Web Services/Security/Message Protection**:
 - a. Set **Require Timestamp** to **false**.
 - b. Set **Require Digital Signatures for Incoming Messages** to **false**.
 - c. Set **Require Encryption for Incoming Messages** to **false**.
 - d. Set **Encrypt Response** to **false**.

Creating a Cluster Environment for BPM in WebLogic

Follow the instructions in the following sections to create a cluster environment for BPM in WebLogic.

Prerequisites for Creating a Cluster for BPM in WebLogic

Before you create a cluster:

Note: See the Tested Configurations document for supported versions.

- 1) Install the **Oracle MDS (Metadata Services) schema** using the **Repository Creation Unit (RCU)** on a separate database instance.
- 2) Install **Oracle Fusion Middleware SOA Suite** on the Middleware Home for all nodes where you configured P6 EPPM.
- 3) Create a cluster for BPM 11g in WebLogic. Follow WebLogic's instructions to create a cluster. The following instructions will refer to the cluster as **BPMCLUSTER_domain**.

Extending the WebLogic Domain to Create a New Cluster

To extend the WebLogic Domain:

- 1) Stop the P6 EPPM servers:
 - ▶ If you started the servers using Node Manager (for example, start_Primavera.bat), run **stop_Primavera.bat** to stop all running servers.
 - ▶ If you started the servers using startWebLogic.cmd/startManagedWebLogic.cmd in Windows or startWebLogic.sh/startManagedWebLogic.sh in Unix, use the "stop" version for those files to stop the servers.
- 2) Run the WebLogic **Configuration Wizard**.
- 3) In the **Welcome** window:
 - a. Select **Extend an existing WebLogic domain**.
 - b. Click **Next**.
- 4) In the **Select a WebLogic Domain Directory** window:

- a. Expand **domains**.
 - b. Select the BPM Cluster domain (for example, BPMCLUSTER_domain), which you must extend with policy manager.
 - c. Click **Next**.
- 5) In the **Select Extension Source** window:
- a. Select **Extend my domain automatically to support the following added products:**.
 - b. Select **Oracle WSM Policy Manager - 11.1.1.0 [oracle_common]**. When you select this option, the wizard will automatically select **Oracle JRF - 11.1.1.0 [oracle_common]**.
 - c. Click **Next**.
- 6) In the **Configure JDBC Component Schema** window:
- a. Enter your MDS schema details. The MDS details are the DB configuration details where you installed the Oracle MDS schema.
 - b. Click **Next**.
- 7) In the **Test JDBC Component Schema** window:
- a. Select your schema.
 - b. Click **Test Connections**.
 - c. If the test is successful, click **Next**.
If the test fails, go back to the previous screen and ensure your credentials are correct.
- 8) In the **Select Optional Configuration** window:
- a. Select **Managed Servers, Clusters and Machines** and **Deployments and Services**.
 - b. Click **Next**.
- 9) In the **Configured Managed Servers** window, do not make changes and click **Next**.
- 10) In the **Configure Clusters** window, do not make changes and click **Next**.
- 11) In the **Assign Servers to Clusters** window, do not make changes and click **Next**.
- 12) In the **Configure Machines** window, do not make changes and click **Next**.
- 13) In the **Assign Servers to Machines** window, do not make changes and click **Next**.
- 14) In the **Target Deployments to Clusters or Servers** window:
- a. In the left pane, select **AdminServer**.
 1. In the right pane under **Applications**, select **wsm-pm**.
 2. In the right pane under **Library**, select all options.
 - b. In the left pane, select another server.
 1. In the right pane under **Applications**, select the application that corresponds to that server. For example, if you selected the P6 server, select **P6** under **Applications**.
 2. Clear all other options for that server.
 3. Repeat these steps for each server.
 - c. In the left pane, select **Cluster** and select all the applications that belong in that cluster from the right pane.
 - d. Click **Next**.
- 15) In the **Target Services to Clusters or Servers** window:
- a. In the left pane, select **AdminServer** and select all options in the right pane.

- b. In the left pane, select **Cluster** and clear all options in the right pane.
 - c. Click **Next**.
- 16) On the Configuration Summary screen:
- a. Verify the configuration summary.
 - b. Click Extend.
 - c. When the extension is complete, click **Done**.

Finalizing the Extended Schema for BPM

To finalize the extended schema for BPM:

- 1) Copy this extended domain to all node server machines that are part of the created cluster.
- 2) Set StartScriptEnabled to true:
 - a. Go to the Node Manager folder in the WebLogic home (for example, C:\Oracle\Middleware\wlserver_10.3\common\nodemanager)
 - b. Edit the **nodemanager.properties** file.
 - c. Set **StartScriptEnabled = true**.
 - d. Ensure that **StartScriptName=startWebLogic.cmd** or **StartScriptName=startWebLogic.sh** depending on your operating system.
- 3) Start the servers:
 - ▶ Run **start_Primavera.bat/ start_Primavera.sh** to start all the servers through node manager.
 - ▶ To start the servers manually, run **startWeblogic.cmd/startManagedWeblogic.cmd** for Windows or **startWeblogic.sh/startManagedWeblogic.sh** for Unix.

Testing the Connection for P6, BPM, and Web Services

This section includes steps to to deploy and configure the P6ConfigValidator workflow, which you can use to test a web services call.

Configuring WSDL Location and Service Endpoints

The configuration plan references the generic endpoint: p682ws:7011. The configuration plan also contains BPEL properties in the workflow to configure the target environment. In this workflow, these entries consist only of the P6 user name, password, and database instance to use when making the test Web Service call.

To prepare the configuration plan:

- 1) Unzip the files in the **P6_R83_Tools\BPM Connector\P6ConfigValidator_1.0_DemoPackaging.zip** folder from the Media Pack.
- 2) Edit the **P6ConfigValidator_cfgplan.xml** file.
- 3) Find the attribute **<replace />** and change the following values:

- a. Find **<property name="bpel.preference.p6userName">** and replace the P6 username value between the "**<replace>** **</replace>**" elements with a P6 username from your environment. Oracle recommends using a user assigned to the Admin Superuser Global security profile.
- b. Find **<property name="bpel.preference.p6password">** and replace the P6 password value between the "**<replace>** **</replace>**" elements with the password of the user from above.
- c. Find **<replace>localhost:7011</replace>** and replace the value between the "**<replace>** **</replace>**" elements with the hostname:port where you deployed P6 Web Services.
- 4) Save the changes made to the **P6ConfigValidator_cfgplan.xml** file and close the text editor.

Deploying the SOA Composite

To deploy the JAR for the SOA composite:

- 1) Login to Enterprise Manager on the WebLogic Server hosting SOA.
- 2) Expand **SOA, soa-infra, server_name**.
- 3) Right-click on the target soa-infra partition and select **SOA Deployment, Deploy to This Partition....**
- 4) Specify the location of the service archive file **sca_P6ConfigValidator_rev1.0.jar** and the edited configuration plan (**P6ConfigValidator_cfgplan.xml**) for this environment.
- 5) Click **Next** to confirm the remaining options for the target environment.
- 6) Deploy the JAR for the SOA composite.

Deploy Client Application and Task UI Project

To deploy the P6ConfigUI.ear as a standard application deployment to the same server where the SOA is running:

- 1) Login to Enterprise Manager.
- 2) Expand **WebLogic Domain, domain_name**.
- 3) Right-click on the server name and select **Application Deployment, Deploy**.
- 4) Specify the location of **P6ConfigUI.ear**.
- 5) (optional) Specify the location of the deployment plan if needed.
- 6) Click **Next** to confirm the remaining options for the target environment.
- 7) Deploy **P6ConfigUI.ear**.

Assigning the TestConfig Role to Users

To use this workflow, you need to assign a BPM role for the user to initiate the test and receive the confirmation the test was successful.

To assign the role:

- 1) Login to the BPM Workspace as a user with administrative rights.
- 2) Click **Administration** on the top right toolbar.
- 3) On the **Organization Roles** list, select **P6ConfigValidator.TestConfig**.

- 4) On the **Details** pane, make one or more BPM users or user groups a member of the **TestConfig** role. The BPM users or user groups assigned to the TestConfig role must match a P6 username for the workflow to be visible from P6.
- 5) Click **Apply** to save these changes.

Troubleshooting and Known Issues for BPM 11g

Use the BPM and P6 EPPM Web Services log viewers to troubleshoot problems if they arise and check for known issues with BPM 11g.

Note: As a general rule when troubleshooting workflow failures, first check the BPM diagnostics to determine at what point in the process the workflow failed. If the failure is related to retrieving data from P6, then you should check the P6 EPPM Web Services logs. Also be sure to check the P6 Help and other documentation for both P6 and BPM.

Known Issues

When integrating P6 and BPM, you can use only English as the language. While both P6 and BPM both support localization, the API for integrating these two applications supports only English.

Checking the P6 EPPM Web Services Logs

The Oracle Primavera Prime API uses the Java Logging API to handle log messages. Message levels that the API logs range from FINEST to SEVERE, in which FINEST logs the most messages and SEVERE logs the least messages. Additionally, there is a level ALL, which logs all messages; however, this setting could potentially impact performance.

Configuring the Logging Level

You configure the logging level by specifying and then editing your own declared logging configuration file (see <http://download.oracle.com/javase/>) by adding or modifying the following lines:

```
com.primavera.integration.level = <level>
com.primavera.ws.level = <level>
```

Where <level> is one of the following values: FINEST, FINER, FINE, CONFIG, INFO, WARNING, SEVERE, ALL, OFF. For example, to set the logging level to ALL, use the following:

```
com.primavera.integration.level = ALL
```

```
com.primavera.ws.level = ALL
```

Setting Logging On and Off

By default the API logging is turned off. You can turn logging on by uncommenting the following line in the cxf.xml that is supplied in the default Oracle Primavera Prime API server deployment:

```
<!-- <cxf:logging /> -->
```

After removing the comment markers, the line would appear as follows:

```
<cxf:logging />
```

Note: You can find the cxf.xml here:
p6ws.war\WEB-INF\classes\cxf.xml

Oracle BPM 11g Logging

Refer to the following file to access BPM messages:

```
<WebLogic domain of Fusion  
middleware>/servers/AdminServer/logs/AdminServer.log
```

In a typical BPM 11g installation on Linux, the WebLogic domain for Fusion Middleware is:

```
<WebLogic domain>/user_projects/domains/domain1
```

Troubleshooting Scenarios

Outside of the scope of general issues with BPM or P6 EPPM, the P6 BPM Integration can potentially yield two types of issues:

- 1) connector configuration issues
- 2) data implementation issues rooted in either P6 or the BPM server

Troubleshooting Connector Failures to Load Due to Configuration Issues

- 1) In the P6 Administrator application, set the **Log/Console Logger/Severity Level** to *debug* or *info*.
- 2) Check the P6 log for BPM related messages. The log file is `P6WebAccess.html` and its location is specified in `BREBootStrap.xml` located in your P6 EPPM home folder. These messages should indicate the cause of the connector failing to load.

Troubleshooting P6 Workflows Portlet Failures To Load Data, Show Forms, Status Images, or Initiate a Process

These type of errors could have their root cause in either the P6 application or the BPM server.

- 1) In P6 Administrator application, set the **Log/Console Logger/Severity Level** to *debug* or *info*.

- 2) Check the P6 log for BPM related messages. The log file is `P6WebAccess.html` and its location is specified in `BREBootStrap.xml` located in your P6 EPPM home folder. These messages should indicate why the BPM code failed to process normally.
- 3) Check the BPM logs in these cases to make sure that the cause of the failure is not due to the BPM server.

BPM Workflows in P6

The following sections detail information about workflows and how to work with them.

In This Section

About Workflows	17
Working with Workflows in P6	17

About Workflows

A workflow is an automated business process that routes information and tasks between participants according to a defined set of procedures or rules designed to coordinate a specific business goal. Workflows are primarily characterized by their level of procedural automation involving one or more dynamic related series of processes, and their combination of human and machine-based tasks involving interaction with software and systems.

The following industry segments, marked by relatively high office labor costs and transaction volume, have demonstrated successful workflow implementations:

- ▶ Insurance
- ▶ Banking
- ▶ Legal
- ▶ General & Administrative
- ▶ Design
- ▶ Engineering
- ▶ Manufacturing

Business process modeling and workflow automation allow transactions to be conducted electronically without the need for manual intervention such as conducting certain validations or re-keying data. When workflow IT systems are processing repetitive, mundane, and often error-prone work, talented staff resources become available to handle activities that add real value to the enterprise.

Working with Workflows in P6

You can use workflows to route business processes such as project initiation requests through your organization to gather information and visibility before a go/no go decision is made. Template data, routing designators, and approval rules can be set for each stage of a workflow. To illustrate these options, pretend we have a workflow involving five key approval managers. You can define the workflow such that all five must approve and even specify a particular sequence, if any. A much more relaxed approval rule would require only one out of the five to approve. The following are just some example of how you can use workflows.

Workflows are defined, deployed, and configured in BPM where your workflow designer defines the workflow tasks involved and assigns them to specific users, roles, or groups. Then, in P6, a business need kicks off an instance of the workflow and its required tasks are automatically routed to their users, roles, or groups.

When a specific user or any user assigned to a role or group logs into P6, the **Workflows** portlet on their dashboard will display their relevant tasks at this stage of the workflow, as authenticated by BPM. As a workflow participant, you can select a task in the workflow instance and claim ownership for it. This means you will be responsible for performing the task. The application refreshes itself to show only the actions permitted for this stage of the workflow for you (the currently logged in user).

Oracle Primavera P6 - Content of Personal Workspace

Content | Layout | Access

General

Portfolio Views **Add**

Project Performance

Workflow

☐ Document Reviews

☒ **Workflows** **1**

Show workflows initiated in the past days *Applies to My Workflows tab only*

Resources

Personal Information

☒ My Projects

☐ My Workgroups

☐ My Activities

☐ My Risks

☐ My Issues

☒ Communication Center

☐ My Documents

☒ My Calendar

Custom Portlets **Add**

Contract Management

Default Save Save and Close Cancel

Oracle Primavera P6 - Personal Workspace

Personal Workspace | Construction | Energy | Corporate | IT | Manufacturing | Product R&D | Strategic Programs | Workflow

Expand All Collapse All Customize

Workflows **2**

Action Required (6) My Workflows

ID	Process	Name	Initiator	Status	Initiated Date
301	ChangeControl	RegisterChange1	Jack Smith	In Progress	01-Apr-11
303	ProjectInitiate	RequestProject	Jack Smith	In Progress	01-Apr-11
304	StageGate	TEMPStageGatePicker	Jack Smith	In Progress	01-Apr-11
305	ChangeControl	RegisterChange1	Jack Smith	In Progress	01-Apr-11
306	ProjectInitiate	RequestProject	Jack Smith	In Progress	01-Apr-11
307	ProjectInitiate				

RequestTemplate - ... **4**

ChangeControl

ChangeProcess

ProjectInitiate

StageGate

OK Cancel


My Workflows **3**

Action Required (6) My Workflows

Show: Role All Status In Progress

ID	Process	Name	Initiator	Status	Initiated Date	Days Pending
301/0	ChangeControl	RegisterChange1	Jack Smith	In Progress	01-Apr-11	0
302/0	ChangeProcess		Jack Smith	In Progress	01-Apr-11	0
303/0	ProjectInitiate		Jack Smith	In Progress	01-Apr-11	0
304/0	StageGate		Jack Smith	In Progress	01-Apr-11	0
305/0	ChangeControl		Jack Smith	In Progress	01-Apr-11	0
306/0	ProjectInitiate		Jack Smith	In Progress	01-Apr-11	0

Table 1 of 2: Key Workflow Screen Elements

Item	Description
①	Setup and Configuration: After your administrator sets up BPM, configure a dashboard to display the Workflows portlet.
②	Action Required Tab: This tab shows the tasks that are important to you (the currently logged in user).
③	My Workflows Tab: This tab enables you to view all workflows according to role and status filters you can set.
④	Initiate a Workflow: Click  Initiate a Workflow to start a new instance of a workflow based on a predesigned template.

ORACLE Business Process Workspace

1

Tasks | **Activity Guides** | **Process Tracking** | **Standard Dashboards**

Applications

- ChangeControl
- RequestProject
- RequestProject
- StageGate

My Tasks | **Initiated Tasks** | **Administrative Tasks**

Actions | Assignee: Me & My Group | State: Assigned | Search

Application: Request a Primavera Project

Initiator: Admin

Workflow Diagram:

```

graph LR
    Start((Start)) --> GetInitialData[Get Initial Data]
    GetInitialData --> InitialRequest[Initial Request]
    InitialRequest --> Outcome1{Outcome}
    Outcome1 -- Submit --> CreateProject[Create Project]
    CreateProject --> SetProjectCodes1[Set Project Codes]
    SetProjectCodes1 --> Outcome2{Outcome}
    Outcome2 --> EditRequest[Edit Project Request]
    EditRequest --> Outcome3{Outcome}
    Outcome3 --> CheckBudget[Check Budget]
    CheckBudget --> OverThreshold{Over Threshold}
    OverThreshold --> GetDataPO[Get Data for PO Review]
    GetDataPO --> ProjectOfficeReview[Project/Office Review]
    ProjectOfficeReview --> SetProjectCodes2[Set Project Codes]
    SetProjectCodes2 --> Outcome4{Outcome}
    Outcome4 --> ResourceManagerReview{Resource Manager Review Required?}
    ResourceManagerReview -- yes --> ResourceManagerReview2[Resource Manager Review]
    ResourceManagerReview2 --> Outcome5{Outcome}
    Outcome5 --> Outcome1
    Outcome4 -- no --> Outcome1
    OverThreshold -- Rejected --> Cancel((Cancel))
    OverThreshold -- Under Threshold --> Outcome1
  
```

2

Workflows

Action Required (1) | My Workflows

Category	Activity	Initiator	Stage	Status	Due Date
Request a Project	InitialRequest	Kevin	Stage1	ASSIGNED	

Workflows

Action Required (1) | My Workflows


Show: Role All | Status All

Name	ID	Initiator	Status	Stage
RequestProject	20002	Kevin	In Progress	InitialRequest
RequestProject	20001	Kevin	Approved	

3

Date	Action	User	Stage
01-Mar-13 02:07 PM	Instance created.		RequestProject
01-Mar-13 02:07 PM	Instance entered activity.		Start
01-Mar-13 02:07 PM	Instance completed activity.		Start
01-Mar-13 02:07 PM	Instance entered activity.		Get Initial Data
01-Mar-13 02:07 PM	Instance entered activity.		Start
01-Mar-13 02:07 PM	Instance completed activity.		Start
01-Mar-13 02:07 PM	Instance entered activity.		Prep Globals
01-Mar-13 02:07 PM	Instance completed activity.		Prep Globals
01-Mar-13 02:07 PM	Instance entered activity.		Get EPS List
01-Mar-13 02:07 PM	Instance completed activity.		Get EPS List
01-Mar-13 02:07 PM	Instance entered activity.		Set EPS List

Table 2 of 2: Key Workflow Screen Elements

Item	Description
1	<p>BPM Workspace: Use the BPM Workspace to update the progress of tasks, initiate a change, request a project, and retrieve project information. You are also able to apply a bulk action to multiple work items.</p> <p>Note: If using BPM 11g (which always uses secure sign-on or SSO authentication), you will see the form in a new window. If SSO authentication is not configured with BPM, you must log into BPM in the resulting window, close that window, and then return to P6 and click  View Form again. This procedure is required whenever your BPM session expires.</p>
2	<p>Sample Workflow: A basic workflow image with tasks for a business user, two project offices, and a project manager.</p>
3	<p>Workflow History: View a chronological sequence of all the previous actions, users, and stages in the current workflow.</p>

Appendix

In This Section

BPM 11g: Configuring SAML Web Service Clients for Identity Switching without Message Protection	23
---	----

BPM 11g: Configuring SAML Web Service Clients for Identity Switching without Message Protection

Oracle Web Services Manager (WSM) includes **wss11_saml_token_identity_switch_with_message_protection_client_policy**, which enables identity switching. Identity switching means that the policy propagates a different identity than the one based on the authenticated Subject.

The Service-Oriented Architecture (SOA) application requires you to specify which user identity to use in client-side Web service policies, and then dynamically switches the user associated with the SAML token in the outbound Web service request. Instead of using the user name from the Subject, this policy allows you to set a new user name when sending the SAML Web service request.

The **wss11_saml_token_identity_switch_with_message_protection_client_policy** creates the SAML token based on the user ID set via the property **javax.xml.ws.security.auth.username**.

The initial identity switching policy requires message encryption, which requires the server-side policy to be the same. You will not want this policy when working in P6. To change the policy, you need to create a new client-side policy based on the existing identity switching policy (this is done through Enterprise Manager (EM), using the "create like" option). Within the new policy definition, you can remove the existing assertion (SAML 1.1 SAML with Certificates) and replace it with a new assertion based on an appropriate template, which in this case is WS-Security SAML Token Client.

Message Protection Policy

You can configure policies in the **Web Services Policies, Edit Policy** section of EM. You can also copy the custom SAML Identity Policy. To do this, copy the `oracle_wss11_saml_token_identity_switch_with_message_protection_client_policy.txt` file located here:
http://download.oracle.com/docs/cd/E20686_01/English/Technical_Documentation/Oracle_BPM/oracle_wss11_saml_token_identity_switch_with_message_protection_client_policy.txt.

Setting the WSIIdentityPermission

The Web service client (for example, the SOA reference binding component) where you attached the **wss11_saml_token_identity_switch_with_message_protection_client_policy** must have the **oracle.wsm.security.WSIIdentityPermission**.

To use Fusion Middleware Control and add the **oracle.wsm.security.WSIIdentityPermission** to the SOA reference binding component as a System Grant, perform the following steps:

- 1) In the **Navigator** pane, expand **WebLogic Domain** to show the domain where you need to configure the application. Select the domain.
- 2) Using **Fusion Middleware Control**, click **WebLogic Domain, Security, System Policies**. System policies are the system-wide policies applied to all applications deployed to the current WebLogic Domain.
- 3) From the **System Policies** page, select the arrow icon in the **Permission** field to search the system security grants.
- 4) Select one of the codebase permissions to use as a starting point and click **Create Like**.
- 5) In the **Grant Details** section of the page, enter **file:\${common.components.home}/modules/oracle.wsm.agent.common_11.1.1/wsm-agent-core.jar** in the **Codebase** field.
- 6) In the **Permissions** section of the page, select the starting point permission class and click **Edit**.
- 7) In the **Permission Class** field, enter **oracle.wsm.security.WSIIdentityPermission**. The resource name is the composite name for SOA and the application name for a J2EE client. The action is always **assert**.

Creating the basic.credentials Key

You also need to add the basic.credentials key to the csf store via EM. You might need to create a default keystore if you have not done that already.

- 1) Right-click **Domain** then select **Security, Credentials**.
- 2) Create a **basic.credentials** key.

Applying the New Policy

- 1) Before applying the new policy, you need to import into JDeveloper. Copy the new custom policy to your JDev store directory (either use the attached policy from this document or export your custom policy from EM). The location of the store could appear as follows:
USER_HOME\AppData\Roaming\JDeveloper\system11.1.1.4.37.59.23\DefaultDomain\oracle\store\gmds\owsm\policies
- 2) Apply this new client policy to your service reference in your composite app via EM.

With this policy in place you can leverage the javax.xml.ws.security.auth.username inbound service property. If you are hardcoding, set the value without quotes. The value is set to jcooper; however, you can also extract the username from the payload of execData variable.

You do not have to import the policy to JDev, you can deploy the composite without a client-side policy, and then set the client policy through EM.

EM has a feature for setting the client-side policies that shows you compatible client-side policies based on the service you are calling.

References

http://download.oracle.com/docs/cd/E17904_01/web.1111/b32511/setup_config.htm#WSSEC3585

Configuring a Keystore if One Is Not Configured

- 1) Right-click your WebLogic domain and select **Security Provider Configuration**.
- 2) In the **Keystore Section**, select **Configure**.
- 3) Provide credentials.

For More Information

Where to Get Documentation

Complete documentation libraries for P6 EPPM releases are available on the Oracle Technology Network (OTN) at:

<http://www.oracle.com/technetwork/documentation/primavera-093289.html>

From this location you can either view libraries online or download them to have local copies. We recommend viewing them from OTN to ensure you always access the latest versions, including critical corrections and enhancements.

P6 EPPM is configured to access its help systems on OTN. However, you can also install local versions when you install the software.

The documentation assumes a standard setup of the product, with full access rights to all features and functions.

The following table describes the core documents available for P6 EPPM and lists the recommended readers by role. P6 EPPM roles are described in the *Planning Your P6 EPPM Implementation* guide.


Title	Description
<i>What's New in P6 EPPM</i>	Highlights the new and enhanced features included in this release. You can also use the <i>P6 EPPM Cumulative Feature Overview Tool</i> to identify the features that have been added since a specific release level. All users should read this guide.

Title	Description
<i>Planning Your P6 EPPM Implementation</i>	Explains planning your implementation, provides an installation process overview, frequently asked questions, client and server requirements, and security information. The P6 EPPM network administrator/database administrator and P6 administrator should read this guide.
<i>P6 EPPM Installation and Configuration Guide</i>	Explains how to install and configure the P6 EPPM using the P6 EPPM Installation and Configuration wizards. The P6 EPPM network administrator/database administrator and P6 administrator should read this guide.
<i>P6 EPPM Installation and Manual Configuration Guide</i>	Explains how to install and configure the P6 EPPM using the P6 EPPM Installation wizards, and how to manually configure individual components. The P6 EPPM network administrator/database administrator and P6 administrator should read this guide.
<i>P6 EPPM Post Installation Administrator's Guide</i>	Describes how to get started using P6 EPPM applications after you have installed and configured them. Complete the tasks in this guide before letting your users work with these applications. These tasks include information about configuring your users and security settings and privileges, configuring your P6 Administrator application Administrator settings, and finalizing your P6 Integration API and P6 EPPM Web Services settings. The P6 EPPM network administrator/database administrator and P6 administrator should read this guide.
<i>Tested Configurations</i>	Lists the configurations that have been tested and verified to work with P6 EPPM. The network administrator/database administrator and P6 EPPM administrator should read this document.
<i>P6 User's Guide</i>	Explains how to plan, set up, and manage projects in a multiuser environment. If you are new to P6, start with this guide to learn how to use the software effectively to plan and manage projects. When you need more detail, refer to the P6 Help. The program manager, project manager, resource/cost manager, team leader, and all P6 users should read this guide.
<i>P6 Help</i>	Explains how to use P6 to administer, plan, set up, and manage projects, portfolios, workflows, timesheets, documents, and reports in a multiuser environment. Describes how to analyze performance and ROI, and analyze budgets. If you are new to P6, use this Help to learn how to use the software effectively.

Title	Description
	The operations executive, P6 EPPM and P6 administrator, program manager, project manager, resource/cost manager, team leader, and all users should read this Help.
<i>P6 Data Dictionary</i>	Defines fields used in P6. All P6 users should refer to this guide if they need a field definition.
<i>P6 Team Member Web Help</i>	Describes how to use P6 Team Member Web to provide status on activities. P6 Team Member Web users should read this Help.
<i>P6 EPPM Web Services Programmer's Guide</i>	Describes how to invoke, use, and troubleshoot the available services and operations within supported environments. When you need specific information about the services and operations available, refer to the P6 EPPM Web Services Reference Manual. Anyone who wants to develop applications which interact with P6 should read this guide.
<i>P6 EPPM Web Services Reference Manual</i>	Describes all services and operations available in P6 EPPM Web Services. Anyone who wants to develop applications which interact with P6 should read this guide.
<i>P3 to P6 EPPM Migration Guide</i>	Provides best practices for migrating your P3 data to P6 EPPM, and details how P3 functionality maps to P6 EPPM functionality. All administrators should read this guide if your organization is moving from P3 to P6.

Distributing Information to the Team

You can copy the online documentation to a network drive for access by project participants. Team members can then view or print those portions that specifically relate to their roles in the organization.

Throughout this documentation, the Security Guidance icon  helps you to quickly identify security-related content to consider during the installation and configuration process.

Where to Get Training

To access comprehensive training for all Primavera products, go to:

<http://education.oracle.com>

Oracle Learning Library

The Oracle Learning Library (OLL) provides online learning content covering Primavera products. Content includes whitepapers, videos, tutorials, articles, demos, step-by-step instructions to accomplish specific tasks, and self-paced interactive learning modules.

To access the learning library's Primavera content, go to:

<http://www.oracle.com/oll/primavera>

Where to Get Support

If you have a question about using Oracle products that you or your network administrator cannot resolve with information in the documentation or help, click <http://support.oracle.com/>. This page provides the latest information on contacting Oracle Global Customer Support, knowledge articles, and the support renewals process. For more information about working with Support, visit <https://support.oracle.com/epmos/faces/DocumentDisplay?id=888813.2> to view **Support Tools & Tips**.

The following knowledge articles are a good place to start your research because they link to the most frequently referenced articles about P6 EPPM

- ▶ Primavera Product Master Notes [ID 1489367.1]
- ▶ Master Note For Primavera P6 Common Application Questions Or Issues [ID 1292929.1]

P6 EPPM integrates with different Oracle applications; when you create a Service Request, be sure to open the request with the proper Support team. To ensure you reach the proper Support team, enter the correct product information when you create the Service Request. Each product has its own support line.

- ▶ Use the **Primavera P6 EPPM** support line when you are having installation, configuration, or connection issues related to P6 EPPM.
- ▶ Use one of the following support lines when you are having installation or configuration issues that do not relate to P6 EPPM.
 - ▶ Oracle WebLogic Server
 - ▶ Oracle Database Server
 - ▶ BI Publisher
 - ▶ BPM
 - ▶ Oracle Webcenter Content Core Capabilities (formerly Universal Content Management)
 - ▶ Oracle Enterprise Manager
 - ▶ Oracle Access Manager
 - ▶ Oracle AutoVue

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/us/support/contact-068555.html> or visit <http://www.oracle.com/us/corporate/accessibility/support/index.html> if you are hearing impaired.

Using Primavera's Support Resource Centers

Primavera's Support Resource Center provides links to important support and product information. Primavera's Product Information Centers (PICs) organize documents found on My Oracle Support (MOS), providing quick access to product and version specific information such as important knowledge documents, Release Value Propositions, and Oracle University training. PICs also offer documentation on Lifetime Management, from planning to installs, upgrades, and maintenance.

Visit <https://support.oracle.com/epmos/faces/DocumentDisplay?id=1486951.1> to access links to all of the current PICs.

PICs also provide access to:

- ▶ **Communities** which are moderated by Oracle providing a place for collaboration among industry peers to share best practices.
- ▶ **News** from our development and strategy groups.
- ▶ **Education** via a list of available Primavera product trainings through Oracle University. The Oracle Advisor Webcast program brings interactive expertise straight to the desktop using Oracle Web Conferencing technology. This capability brings you and Oracle experts together to access information about support services, products, technologies, best practices, and more.

Legal Notices

Oracle Primavera Connecting BPM 11g to P6

Copyright © 1999, 2014, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software or hardware and documentation may provide access to or information on content, products and services from third-parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.