



PRIMAVERA

**Gateway Installation and Configuration Guide
Release 15.1**

March 2015

Contents

Overview	5
Downloading Primavera Gateway	5
Installation Prerequisites.....	7
Installing the Oracle Database	7
Installing Supported JDK	8
Installing WebLogic	8
Installing Oracle Fusion Middleware Infrastructure (WebLogic 12c Only)	8
Running the Repository Creation Utility (RCU).....	9
Installing the Primavera Application Database	10
Installing the P6 Adapter.....	10
Downloading Third-Party Providers.....	11
Execute a Manual Script Before Installation.....	11
Installing Primavera Gateway	13
Installing Primavera Gateway Using the Wizard	13
Installing Primavera Gateway Using the Save Response File.....	18
Installing the Gateway Database Using the Install Utility	18
Starting and Stopping the Primavera Gateway Domain.....	19
(Optional) Changing the Default Node Manager Port Number	20
Creating Users and Associating them with a Role	20
Using the Gateway Configuration Utilities.....	21
Adding User-Defined Fields (UDFs) and Codes to P6 EPPM.....	22
Adding P6 User-Defined Fields and Codes to Providers	23
Adding, Updating, or Customizing Gateway Metadata	24
Adding or Removing Providers	25
Adding or Removing Customizations	26
Supporting Java Customization on a Managed Server	28
Configuring Deployment Targets.....	28
Configuring the P6 Deployment Target.....	28
Enabling Encryption Between Primavera Gateway and P6 Adapter	29
Configuring Provider Deployment Targets	30
Updating the Existing Domain with Server Group Information (WebLogic 12c)	30
Uninstalling Primavera Gateway	33
For More Information	35
Where to Get Documentation	35
Where to Get Training.....	38
Where to Get Support	39
Documentation Accessibility.....	40

Legal Notices 41

Overview

The *Gateway Installation and Configuration Guide* describes how to:

- ▶ Download and install the Primavera Gateway application using the installation wizard.
Depending on WebLogic version, the installation wizard provides the following options:
 - ▶ On WebLogic 12c, you can install Primavera Gateway on an Admin server or a Managed server with OWSM. However, to use Primavera Gateway APIs, you must install Primavera Gateway on a Managed server only.
 - ▶ On WebLogic 11g, you can install Primavera Gateway on an Admin server only.

Note: To install Primavera Gateway on WebLogic 11g with OWSM enabled, refer to the *Primavera Gateway Manual Deployment Guide*.

- ▶ Set up and configure the WebLogic domain for Primavera Gateway
- ▶ Create Primavera Gateway users and add them to the Primavera Gateway user groups
- ▶ Configure Primavera Gateway components

This guide is intended for IT professionals who are installing and configuring the server environment for Primavera Gateway and who are supporting Primavera Gateway users.

For the full list of system requirements and versions, see the *Primavera Gateway Tested Configurations* document.

In This Section

Downloading Primavera Gateway 5

Downloading Primavera Gateway

To download Primavera Gateway:

- 1) Go to the Oracle Software Delivery Cloud.
- 2) Download Primavera Gateway and extract the file content to the following folders:
 - ▶ Disk1
 - ▶ gatewayapiclient
 - ▶ GatewayUtility
 - ▶ script
- 3) Go to the location where you extracted the contents and run the following:
If you are installing on a Microsoft Windows system, double-click and run **setup.exe** from the following directory:
 - ▶ Windows 64-bit: Double-click **setup.exe** file from the **win64\Disk1\install** directory

If you are installing on a Linux or Solaris system, execute **./runInstaller.sh** from the following directories:



Give execute permission to run the installer using the syntax: **chmod 755 <file name>**

- ▶ Linux 64-bit: Execute **./runInstaller.sh** file from the **linux64/Disk1/install** directory
- ▶ Solaris 64-bit: Execute **./runInstaller.sh** file from the **solaris64/Disk1/install** directory

Installation Prerequisites

Review the following prerequisites before installing and configuring Primavera Gateway.

Notes:

-  Oracle recommends using strong passwords. Strong passwords in Primavera Gateway are defined as passwords containing between 8 and 20 characters and at least one numeric and one alpha character. To further strengthen the password, use a mixture of upper and lower case letters.
-  For security reasons, Oracle strongly recommends that you replace the default database users' passwords immediately after a manual database installation or an upgrade. Do not use special characters in the database name, for example: { } [] : ; < > , . ? ! @ # \$ % ^ & * () - _ | / \ ~ ` _

In This Section

Installing the Oracle Database	7
Installing Supported JDK.....	8
Installing WebLogic.....	8
Running the Repository Creation Utility (RCU).....	9
Installing the Primavera Application Database	10
Installing the P6 Adapter	10
Downloading Third-Party Providers.....	11
Execute a Manual Script Before Installation	11

Installing the Oracle Database

You must install the Oracle database server before you can install the Primavera Gateway database. Your Oracle account representative is always your best source for licensing details. For supported versions of the database, see the *Tested Configurations* document.

Notes:

- You must install Oracle Multimedia, along with these supporting components: Oracle JVM, Oracle XML DB (XDB), and XML Developer's Kit (XDK). Unless you specify otherwise, all these components automatically get installed with the latest versions of the supported Oracle database. If you chose not to install these components, you will need to install them before you install Primavera Gateway. See the *Oracle Multimedia's User's Guide* on the Oracle Technology Network (OTN) for information on how to install these components.
- Oracle Text is a required component of Oracle Database.
- You must use UTF8 encoding to support Primavera Gateway's localized user interface.

Installing Supported JDK

Install and configure Oracle JDK as follows:

- 1) Download the supported version of Oracle JDK from Oracle website. For supported versions of Java, see the *Tested Configurations* document.
- 2) Set the JAVA_HOME and Path environment variables as follows:
 - ▶ On Windows, set the **JAVA_HOME** and **Path** environment variables to the installed Java location.
 - ▶ On Linux and Solaris, export **JAVA_HOME** variable to installed java location, and update the **PATH** variable with the **Java_Home/bin** path.
- 3) Ensure java -version command shows the correct java version in the console.

Installing WebLogic

You will need to install WebLogic to deploy Primavera Gateway. For supported versions, see the *Tested Configurations* document. Also, consult WebLogic's documentation for installation instructions.

Note: On Windows, Oracle recommends you install the application server to a folder with a short name.

Installing Oracle Fusion Middleware Infrastructure (WebLogic 12c Only)

You must run Oracle Fusion Middleware's **fmw_infra_<version>.jar** executable only if you are installing Primavera Gateway on a Managed server.

Notes:

- Do **not** install Oracle Fusion Middleware if you are installing Primavera Gateway on an Admin server.
- Rename the derby.jar file to prevent the derby server from startup when Primavera Gateway is restarted.

Oracle Fusion Middleware installs specific files that WebLogic 12c needs to work with Primavera Gateway. This file is part of Application Development Runtime. See the *Tested Configurations* document for supported versions.

These files ensure that the correct templates are used when creating or extending a WebLogic domain. It will also download the Repository Creation Utility (RCU), which you will run later.

Note: Specify the WebLogic home as the Oracle Home for this installation.

Now proceed to run the RCU. For more details, see ***Running the Repository Creation Utility (RCU)*** (on page 9).

Running the Repository Creation Utility (RCU)

Oracle Web Services Manager (OWSM) authentication is required to support external REST service authentication in Primavera Gateway. To install the schemas needed to support OWSM authentication, you will need to run the Repository Creation Utility (RCU).

To run the RCU:

- ▶ For Windows installations, run **rcu.bat**.
- ▶ For Linux and Solaris installations, run **./rcu.sh**

Run the RCU as follows:

- 1) Go to the location where RCU was installed after you ran the **fmw_infra_<version>.jar**. For example, C:\oracle\Middleware\Oracle_Home\oracle_common\bin.

Note: Edit the **RCU.bat (.sh)** file located under <Weblogic-home>/oracle_common/bin folder to ensure that the ORACLE_HOME is set to the Middleware path (Not database). For example,

```
SET
ORACLE_HOME=ORACLE_HOME=C:\Oracle\Middleware\Oracle_Home
```

- 2) On the **Welcome** screen, select **Next**.

Note: Select **Next** on each screen to advance to the next step.

- ▶ On the **Create Repository** screen, select **Create Repository** and **System Load and Product Load**.
- 1) On the **Database Connection Details** screen, enter the following details:
 - ▶ **Database Type:** Select Oracle Database.
 - ▶ **Host Name:** The host name or the server IP address for the Primavera Gateway database.
 - ▶ **Port:** A unique port number for the Gateway database schema. Port number **1521** displays by default.
 - ▶ **Service Name:** The global database name. For example, orcl.us.oracle.com.

- ▶ **Username:** The user name with DBA privileges who can install a schema.
 - ▶ **Password:** The password for user name provided above.
 - ▶ **Role:** Role of the user who will be creating the MDS schema. Select **SYSDBA**.
- 2) On the **Select Components** screen, select a new prefix. Make a note of the prefix you choose. This information is required when you run the Gateway install wizard.
- In the **Components** section, select the following:
- **Metadata Services**
 - **Audit Services**
 - **Audit Services Append**
 - **Audit Services Viewer**
 - **Oracle Platform Security Services**
 - **ServiceTable**
- 3) On the **Schema Passwords** screen, select the **One password for all components** password method for handling your passwords. Make note of the password you use.
- 4) On the **Map Tablespace** screen, select the defaults. Make notes of your selections.
- 5) On the **Summary** screen, review your selected installation options and select **Create**.
- 6) When the wizard is finished, click **Close**.

Installing the Primavera Application Database

Gateway supports integration with the following Primavera applications:

- ▶ P6 Enterprise Project Portfolio Management (P6 EPPM)

Note: When you run Primavera Gateway, and connect to a P6 EPPM database, information about your P6 EPPM installation is needed when you install the P6 Adapter.

- ▶ Oracle Primavera Prime
- ▶ Primavera Unifier
- ▶ Oracle Instantis EnterpriseTrack

To connect with any of the above applications using Gateway, you will need to install the relevant product and database. For detailed installation instructions, go to <http://www.oracle.com/technetwork/apps-tech/primavera/documentation/index.html>.

Installing the P6 Adapter

If you want to integrate with P6 EPPM, Primavera Gateway requires you to install the P6 Adapter. See the *Installing and Configuring the P6 Adapter* document in the P6 EPPM documentation library for more information about deploying and configuring the P6 Adapter.

Downloading Third-Party Providers

If you want to integrate with any third party enterprise application, download the necessary third-party provider files that needs to be installed in Primavera Gateway to a separate folder location. You will need to specify this folder location in the **Select Third-Party Providers** screen when you install Primavera Gateway using the installation wizard.

Execute a Manual Script Before Installation

Before running the install wizard, execute a manual script:

- 1) From the command line, execute:

sqlplus <sysdba_username>/<sysdba_password>@<SID> as sysdba

Where:

<sysdba_username> is a sysdba user name (sys by default)

<sysdba_password> is a sysdba password

<SID> is a SID of the Oracle database instance

For example, sqlplus sys/myPassword@ORCL as sysdba

Note: The command will be different if you are connecting from the host other than the host where the database is installed, or connecting to the database using a service name.

- 2) At the SQL prompt, execute:

SQL>@<path>\manual_script_before_install.sql

Where, <path> is an absolute path to the directory where the script is located.

For example,

On Windows: If the installer is located in c:\installer\win64, the command to execute the script will be

@C:\install\win64\script\manual_script_before_install.sql

On Linux: If the installer is located in /home/user/installer/linux64, the command to execute the script will be

@/home/user/installer/linux64/script/manual_script_before_install.sql

On Solaris: If the installer is located in /home/user/installer/solaris64, the command to execute the script will be

@/home/user/installer/solaris64/script/manual_script_before_install.sql

This script grants sys.DBMS_REPUTIL privileges to the system user which will be validated during database installation.

Installing Primavera Gateway

This chapter describes the how to install Primavera Gateway using the:

- ▶ Install using the installation wizard
- ▶ Install using a save response file
- ▶ Configure the Gateway database using the configuration utilities
- ▶ Create Gateway users and associating them with a role
- ▶ Configure providers added to Gateway
- ▶ Configure provider deployment targets
- ▶ Un-install Primavera Gateway

In This Section

Installing Primavera Gateway Using the Wizard	13
Installing Primavera Gateway Using the Save Response File	18
Installing the Gateway Database Using the Install Utility	18
Starting and Stopping the Primavera Gateway Domain	19
(Optional) Changing the Default Node Manager Port Number	20
Creating Users and Associating them with a Role	20
Using the Gateway Configuration Utilities	21
Configuring Deployment Targets	28
Updating the Existing Domain with Server Group Information (WebLogic 12c)	30

Installing Primavera Gateway Using the Wizard

The Gateway installation wizard can be used for the following purposes:

- ▶ Installing and configuring Primavera Gateway
- ▶ Installing Primavera Gateway with an existing Gateway database

If you have already installed Primavera Gateway, you can use the installation wizard for:

- ▶ Creating another new Gateway database
- ▶ Re-installing Gateway without any configuration
- ▶ Re-installing Gateway, configuring, and connecting to an existing database
- ▶ Re-installing Gateway, creating a new database, and configuring and connecting to the new database

The installation wizard installs and configures the following:

- ▶ Primavera Gateway database
- ▶ WebLogic domain in which Primavera Gateway is to be deployed
- ▶ Providers

For Linux and Solaris 64-bit Installations:

- 1) Give execute permission to run the installer using the syntax: **chmod 755 runinstaller.sh**
- 2) Execute **./runInstaller.sh** from the **linux64/Disk1/install** directory.

For Microsoft Windows 64-bit Installations: Double-click **setup.exe** file from the **win64/Disk1/install** directory

- 1) On the **Welcome** screen, select **Next**.

Note: Select **Next** on each screen to advance to the next step.

- 2) On the **Specify Installation Location** screen, enter the following information:

Primavera Home: Enter the path and directory or select **Browse** to select the directory and path for installing Primavera Gateway.

For Windows installations, the default Primavera home installation location is **C:\PrimaveraGateway**.

For Linux installations, the default Primavera home installation location is **/home/<User ID>/PrimaveraGateway**.

For Solaris installations, the default Primavera home installation location is **/home/<User ID>/PrimaveraGateway**.

- 3) On the **Specify Database Installation Type** screen select any of the following database installation options:

- ▶ **Install New Database:** Select this option to install a new Primavera Gateway database. If the database already exists, then upon selecting this option, you will have to specify a new schema owner.
- ▶ **Use Existing Database:** Select this option to install the Primavera Gateway application, and continue using the current Gateway database. However, if the existing Gateway database is the previous version, then it will be upgraded to the current version.

- 4) On the **Specify Database Connection Details** screen, enter the following information for the Gateway database:

- ▶ **Database Host Address:** Enter the host name or the server IP address for the Primavera Gateway database.
- ▶ **Database Host Port:** Enter a unique port number for the Gateway database schema. Port number **1521** displays by default.
- ▶ **Database Name:** Enter the database name to connect with the Gateway database. By default, **orcl**. Select **Service** to deploy Gateway in a Managed server.
 - **SID:** Select this option to connect to the database using the system identifier.
 - **Service:** Select this option to connect to the database using a service name.

If you chose the **Install New Database** option in the **Specify Database Installation Type** screen, the following additional fields display:

- ▶ **Schema Owner:** Enter the name of the Primavera Gateway database schema owner.
- ▶ **Schema Password:** Enter a case-sensitive password for the schema owner.
- ▶ **Confirm Password:** Re-enter the case-sensitive password.

Note: You will need the schema owner and password to connect to the database.

- ▶ **DBA User Name:** Enter the user name of the Oracle database administrator.
- ▶ **DBA Password:** Enter the password of the Oracle database administrator.
- ▶ Select the **Test Connection** button to check for database connectivity. If the test is successful, the following message displays: *Connection is successful*. If the test is not successful, check the port number specified, schema user ID and case-sensitive password combination, SID or Service value, and the database host address.

If you chose the **Use Existing Database** option in the **Specify Database Installation Type** screen, then enter the **Schema Password**, and the **DBA Password** fields.

- 5) On the **Select Installation Type** screen, select any of the following installation options:
 - ▶ **Install and Configure Primavera Gateway:** Select this installation option to install the Primavera Gateway application, configure the WebLogic domain for Gateway, and create and connect to the Gateway database. This option is selected by default for all new installations. Proceed to the **Specify Middleware Location** screen.
 - ▶ **Install the Gateway Application:** Select this installation option to only install the Primavera Gateway application. It will not create the WebLogic domain, and will not create or connect to the Gateway database. Proceed to the **Installation Summary** screen.
 - ▶ **Install Primavera Gateway Database:** Select this installation option to only create or upgrade the Gateway database. It will not install the Gateway application or the WebLogic domain for Gateway. Proceed to the **Installation Summary** screen.
- 6) On the **Specify Middleware Location** screen, enter the following information regarding the WebLogic installation:
 - ▶ **Oracle Middleware Home:** Enter or select **Browse** to navigate the path and locate the Middleware folder.
 - ▶ **WebLogic Server Directory:** Enter or select **Browse** to navigate the path and locate the WebLogic server directory. For example, C:\<WebLogic_Home>\wlserver.
 - ▶ **Domain Location:** Enter or select **Browse** to navigate and locate the WebLogic domain folder. For example, C:\<WL_Server_Home>\wl1213\user_projects\domains.
 - ▶ **Apply Patch:** Select this option to install a patch. This option is enabled only if a patch is required, and has not been applied.
- 7) On the **New Domain Details** screen, enter the following information to create the WebLogic domain for Primavera Gateway:
 - ▶ **Administrator User Name:** Enter a name for the WebLogic domain administrator.
 - ▶ **Administrator User Password:** Enter an alphanumeric password of at least 8 characters for the WebLogic domain administrator. Passwords may contain the following special characters: underscore (_), dollar (\$), or pound (#).

Note: Make a note of the domain administrator's user name and password.

- ▶ **Confirm Password:** Re-enter the case-sensitive password.

- ▶ **Domain Name:** Enter a new WebLogic domain name for Primavera Gateway. For example, PrimaveraGateway. The installer will create a sub-folder with this domain name under the domain location folder provided on the previous screen.
 - ▶ **Administrator Server Port:** Enter a unique port number for the new domain.
 - ▶ **Managed Server Deployment:** Select this option to deploy Primavera Gateway in a Managed server. Also specify a database service name in the **Database Connection Details** screen.
 - **Managed Server Port:** Enter a unique port number for the Managed server.
 - **Node Manager Port:** The port number **5556** displays by default. For more details see the topic, *(Optional) Changing the Default Node Manager Port Number* (on page 20).
- 8) In the **Gateway Administrator Details** screen, create a user profile for a Primavera Gateway administrator as follows:
- ▶ **Gateway Administrator User Name:** Enter a name for the Primavera Gateway administrator. The admin user, **GatewayAdmin**, displays by default.
 - ▶ **Gateway Administrator Password:** Enter an alphanumeric password of at least 8 characters for the Primavera Gateway administrator.
 - ▶ **Confirm Password:** Re-enter the case-sensitive password.
- 9) On the **Specify Java Development Kit Location** screen, enter the following information:
- ▶ **Java Home Directory:** Enter or select **Browse** to locate the JAVA_HOME location that will be used by the WebLogic domain. The JAVA_HOME location displays by default. Java 1.7.0_75 or later is required.
 - **Note:** Refer to the *Tested Configurations* document for supported versions of JDK.
-
- 10) On the **MDS Database Details** screen, enter the MDS database connection information that was specified on running the RCU:
- ▶ **Database Host Address:** Enter the host name or the server IP address for the MDS database.
 - ▶ **Database Host Port:** Enter a unique port number for the MDS database schema.
 - ▶ **Database Service Name:** Enter the service name to connect to the MDS database.
 - ▶ **MDS Schema Prefix:** Enter the prefix that was used for the MDS schema in the RCU.
 - ▶ **MDS Schema Password:** Enter the password for the MDS schema.
- 11) On the **Select Primavera Providers** screen, the following Primavera providers will be installed by default:
- ▶ EnterpriseTrack
 - ▶ P6
 - ▶ Prime
 - ▶ Unifier
- Select the **Restore Providers** button to restore all primavera providers in the displayed list.
- Select the **Remove Provider** button to remove a selected provider from the displayed list.
- 12) On the **Select Third Party Providers** screen, select the providers you wish to install.

- ▶ **Primavera's Sample Provider:** Select this option to install the Primavera sample provider packaged with Gateway. This option is selected by default.
 - ▶ **Third-Party Providers:** Select this option to add or delete alternative third-party providers.
 - Select the **Add Provider** button to navigate and locate the home directory for each third-party provider. Ensure that the **lib** sub-folder includes the provider's jar file, the **data** sub-folder includes the metadata xml files. The optional **supplement** sub-folder can contain any additional files. Folder names are case-sensitive.
 - Select the **Delete Provider** button to delete a selected third-party provider from the displayed list.
- 13) On the **Select Help Package** screen, select any of the following options for installing the Primavera Gateway Online Help.
- ▶ **Install Online Version of Help:** Select this option if you want to use the default URL which connects to the Oracle Technology Network (OTN) site. OTN houses Oracle's most up-to-date documentation. If Primavera Gateway functionality changes, the help documentation on OTN will show those changes.
 - ▶ **Install Local Version of Help:** Select this option to use the local help (**gatewayhelp.war** file) installed on a server. However, if any updates are made to the Primavera Gateway help on OTN, these will not be available if you are using the .war file.
- 14) The **Installation Summary** screen displays all the components selected for installation in the previous steps. Review all the selected installation options. Select **Save** if you want to save the installation summary details in an .ini file. This is also a Saved Response file.
- Select **Back** or select the appropriate window in the left pane to change your install options. Select **Install** to begin installing Primavera Gateway.

Note: Save the stored .ini file as a backup of your current installation and configuration choices in a secure location.

- 15) The **Installation Progress** window displays a success message on successful completion.
- If you chose **Install and Configure Primavera Gateway** (1st option) in the **Select Installation Type** screen, the **Configuration Progress** screen displays after Primavera Gateway is successfully installed.
- If you chose **Install Primavera Gateway** (2nd option) in the **Select Installation Type** screen, the **Installation Complete** screen displays.
- If you chose **Install Primavera Gateway Database** (3rd option) in the **Select Installation Type** screen, the **Configuration Progress** screen displays.

Note: Copy all properties files in the **wlst** folder to a save location if you want to replicate the installation using the silent installer later. These files must be copied before the installation completes.

- 16) The **Configuration Progress** screen displays the progression of the installation and configuration tasks.
- 17) On the **Installation Complete** screen, select **Finish** to complete Primavera Gateway installation and close the wizard. Log in to Primavera Gateway with the Gateway Admin user profile created during installation.

Installing Primavera Gateway Using the Save Response File

Use this method to clone Primavera Gateway installations across servers. To proceed with this installation method, you need the Save Response File which captures the options selected during installation. The Save Response file is created when you click **Save** on the **Installation Summary** screen of the installation wizard.

To install Primavera Gateway in the silent mode using the save response file created from the wizard installation:

- 1) Locate the **Save Response File** that was created using the Primavera Gateway installation wizard.
- 2) Replace `<SECURE VALUE>` for password with the actual password.
- 3) Copy all properties files to the **wlst** folder, overwriting existing properties files.
- 4) Run the installer in the silent mode as follows:

For Windows installations, execute:

```
setup.exe -silent -responseFile c:\<path to>\<YourResponseFile.ini>
```

For Linux and Solaris installations, execute:

```
./runInstaller -silent -responseFile /<path to>/<YourResponseFile.ini>
```

Note: The path to the .ini file must be the absolute path.

The output displays in the command console. Upon completion, the following success message displays: *The installation of Primavera Gateway completed successfully.*

- 5) Logs and errors from the installation are located in the following default locations:
For Windows installations, the default location is: C:\Program Files\Oracle\Inventory\logs
For Linux and Solaris installations, the default location is: <user home directory>/oraInventory/logs

Installing the Gateway Database Using the Install Utility

If you chose to only installed the Gateway application using the wizard, you can:

- ▶ Re-run the installation wizard, and select the **Install Primavera Gateway Database** option
For more details, *Installing Primavera Gateway Using the Wizard* (on page 13).
or
- ▶ Run the **Gateway-DBInstallation** utility from the `<INSTALLER_FOLDER>\GatewayUtility\` folder or the `<Primavera_Gateway_Home>\pd\snaphots\dbsetup-dist` folder

To install the Gateway database using the **Gateway-DBInstallation**:

- 1) Navigate to the `<Primavera_Gateway_Home>\pd\snaphots\dbsetup-dist` folder.
- 2) If you are installing on a non-Microsoft Windows system, type the following command:
chmod 755 Gateway-DBInstallation.sh
- 3) Run the following command:
 - ▶ For Windows installations, run **Gateway-DBInstallation.bat**
 - ▶ For Linux and Solaris installations, run **./Gateway-DBInstallation.sh**

4) Enter the following database connection details:

- ▶ **DBA User Name:** Enter the name of the database administrator.
- ▶ **DBA Password:** Enter the password for the database administrator.
- ▶ **Database Host:** Enter the host name of the Oracle database on which you will be updating the Primavera Gateway database.
- ▶ **Database Host Port:** Enter the port number of the Oracle database.
- ▶ **Database Name:** Enter the Gateway database name and select any of the following methods to connect to the database.
 - **SID:** Enter the SID of the Oracle database.
 - **Service:** Enter the service name of the Oracle database.
- ▶ **Schema Owner:** Enter the name of the schema owner. The owner **pdiuser** displays by default.
- ▶ **Schema Password:** Enter the password for the schema owner.
- ▶ **Provider data folder:** Select **Add** to include all the source and destination data paths which contain XMLs with the metadata to load to the Gateway database.

For example, to install the Sample database and P6 data. In that provider data folder, include the P6provider\data folder, the sampleprovider\data folder and the sampleprovider\data\p6 folder to create the Gateway database. Otherwise, the error message: *No field mapping data found*, displays.

Note: The data folder of at least two providers must be selected, in addition to the **pdi/data** folder to complete the installation successfully.

- ▶ Select **Test Connection**. Modify the applicable fields if the connection fails and repeat as necessary.
- ▶ Select **Run** to install the Gateway database.

Starting and Stopping the Primavera Gateway Domain

Starting the Primavera Gateway Domain on an Admin Server

For Windows installations, From the **Start** menu, select **Oracle, Primavera Gateway**, and then **Start Primavera Gateway**. This invokes the **startGatewayWLDomain.cmd** file.

For Linux and Solaris installations, enter `cd <Primavera Gateway_Home>/WLST`, and then run `./startGatewayWLDomain.sh`

-
- **Notes:**
 - You may need to set permissions on the **startGatewayWLDomain.sh** file. If so, enter the following command:
`chmod 755 startGatewayWLDomain.sh.`
 - You must use the
`<PrimaveraGateway_home>WLST\startGatewayWLDomain.*`
 scripts to start the Primavera Gateway domain because these scripts contain the specific memory and timezone settings required by Primavera Gateway.
-

Stopping the Primavera Gateway Domain on an Admin Server

For Windows installations, from the **Start** menu, select **Oracle, Primavera Gateway**, and then **Stop Primavera Gateway**. This invokes the `stopGatewayWLDomain.cmd` file.

For Linux and Solaris installations, enter `cd <Primavera Gateway_Home>/WLST`, and then run `./stopGatewayWLDomain.sh`

Note: You may need to set permissions on the `stopGatewayWLDomain.sh` file. If so, enter the following command:
`chmod 755 stopGatewayWLDomain.sh.`

Starting the Primavera Gateway Domain on a Managed Server

For Windows installations, from the **Start** menu, select **Oracle, Primavera Gateway**, and then **Start Primavera Gateway**. This invokes the `gatewayQuickStart.cmd` file.

For Linux and Solaris installations, enter `cd <Primavera Gateway_Home>/WLST`, and then run `./gatewayQuickStart.sh`

Note: You may need to set permissions on the `startGatewayWLDomain.sh` file. If so, enter the following command:
`chmod 755 gatewayQuickStart.sh.`

Stopping the Primavera Gateway Domain on a Managed Server

For Windows installations, from the **Start** menu, select **Oracle, Primavera Gateway**, and then **Stop Primavera Gateway**. This invokes the `stopPrimavera.cmd` file.

For Linux and Solaris installations, enter `cd <Primavera Gateway_Home>/WLST`, and then run `./stopPrimavera.sh`

Note: You may need to set permissions on the `stopGatewayWLDomain.sh` file. If so, enter the following command:
`chmod 755 stopPrimavera.sh.`

(Optional) Changing the Default Node Manager Port Number

To specify an alternative Node Manager port number from the default, 5556:

- 1) Stop Gateway and the Node Manager.
- 2) Modify `ListenPort` in `<Gateway_Domain>\config\config.xml`.
- 3) Modify `ListenPort` in `<Gateway_Domain>\nodemanager\nodemanager.properties`.
- 4) Modify `nodeManagerPort` in `<Gateway_Home>\wlst\primavera.properties`.
- 5) Start Gateway.

Creating Users and Associating them with a Role

Create roles for PDI authentication as follows:

- 1) Ensure the Primavera Gateway domain is running.

- 2) Log in to the WebLogic Administration Server Console for the Gateway domain:
 - a. In a browser, open the following location:
http://<hostname>:<port>/console
 Where, hostname and port is the hostname and port of your Primavera Gateway domain.
 The default port is **7001**.
 - b. Enter the administrator user name and password.
- 3) Select **Lock & Edit**.
- 4) Select **Security Realms**.
- 5) Select **myrealm**.
- 6) Select the **Roles and Policies**, tab.
- 7) Select **Global Roles**, and **Roles**
 - a. Enter the role: PrimaveraGatewayAdmin
 - b. Set **Group** = PrimaveraGatewayAdmin
 - c. Select **Add Conditions**, and then select **Group** for "Predicate List".
 - d. Select **Next**.
 - e. Enter the group name. Group names must be identical to the created role. For example, PrimaveraGatewayAdmin.
 - f. Select **Add**, then **Finish**.
 - g. Select **Save**.

Repeat Step 7 and create the roles, PrimaveraGatewayDeveloper and PrimaveraGatewayUser.

 - ▶ For the PrimaveraGatewayDeveloper role, set **Group** = PrimaveraGatewayDeveloper
 - ▶ For the PrimaveraGatewayUser role, set **Group** = PrimaveraGatewayUser
- 8) Select **Activate Changes**.

Using the DefaultAuthenticator

- 1) Go to **Users and Groups** tab and create the following groups:
 - ▶ PrimaveraGatewayAdmin
 - ▶ PrimaveraGatewayDeveloper
 - ▶ PrimaveraGatewayUser
- 2) Create users and assign them to the groups listed above.

Using the Gateway Configuration Utilities

The following configuration utilities are provided in Primavera Gateway. Run each utility for the purpose described below:

- ▶ **Gateway-P6Setup**: Run this utility to add User Defined Fields (UDFs) and codes to P6 EPPM.

Access the Gateway-P6Setup utility from the
<Primavera_Gateway_Home>\pd\snaphots\dbsetup-dist folder or the
<INSTALLER_FOLDER>\GatewayUtility folder.

- ▶ **Gateway-Configuration:** Run this utility to manage metadata, and add or remove providers and customizations.

The following configuration options are available:

- ▶ Manage Gateway metadata
- ▶ Manage providers
- ▶ Manage customizations

Access the Gateway-Configuration utility from the

<Primavera_Gateway_Home>\pd\snaphots\dbsetup-dist folder or the **<INSTALLER_FOLDER>\GatewayUtility** folder.

Note: Before executing the utilities on Windows, Linux, or Solaris, ensure the following:

- The **bin** folder of the supported Java JDK is included in the PATH.
 - If there are other JDK bin folders in the PATH, then the supported Java JDK should be listed first.
-

Adding User-Defined Fields (UDFs) and Codes to P6 EPPM

You have the option to add User-Defined Fields (UDFs) and codes to P6 EPPM and to prepare the P6 EPPM database for synchronizing the data. Use this procedure to also add UDFs and codes from Oracle Primavera Prime, Primavera Unifier, to P6 EPPM.

For example, if your application has UDFs or codes that P6 EPPM does not have, you can add these UDFs or codes using an XML file that you edit and then point to it in the Gateway Configuration utility. The XML file needs to conform to the DataConfiguration.xsd schema. For more information on the DataConfiguration.xsd schema, see the *Primavera Gateway Developer's Guide*.

To add your application UDFs or codes to P6 EPPM:

- 1) Ensure that your **JAVA_HOME** variable is pointing to a supported JDK folder.

Note: Ensure the following:

- The **bin** folder of the supported Java JDK is included in the PATH.
 - If there are other JDK bin folders in the PATH, it should be listed first.
-

- 2) Navigate to the **<Primavera_Gateway_Home>/pd\snaphots/dbsetup-dist** folder.
- 3) If you are installing on a non-Microsoft Windows system, type the following command to give execute permission for the utility:
chmod 755 Gateway-P6Setup.sh
- 4) Run the following command:
 - ▶ For Windows installation, run **Gateway-P6Setup.bat**
 - ▶ For Linux and Solaris installations, run **./Gateway-P6Setup.sh**
- 5) Enter the following information in the **Primavera P6 Data Setup Utility** dialog box:
 - a. In the **P6 Admin User Name** field, enter the user name of a user who has admin privileges on the P6 deployment.

- b. In the **P6 Admin Password** field, enter the password of the admin user.
- c. In the **P6 Adapter Endpoint URL** field, enter the address of the **SyncServiceV1 wsdl** file that is served by the P6 adapter you deployed as a prerequisite. This address would follow the format:
`<protocol>://<hostname>:<port number>/p6adapter/services/SyncServiceV1?wsdl`
- d. In the **P6 database instance ID**, enter the system ID (SID) for the P6 database instance.
- e. In the **P6 Data XML File Path**, enter or select **Browse** to specify the path to the XML file that you modified with the UDFs or codes which you want to add to P6 EPPM.
 For a P6 EPPM with Sample provider integration, ensure you have installed the Sample provider, and now select the **SampleP6DataSetup.xml** in the
`<Primavera_Gateway_Home>\sample\sampleprovider\data\p6data` folder. The path you enter must be the absolute path to the file.
 For a P6 EPPM with Oracle Primavera Prime integration, select the
PrimeP6DataSetup.xml file in the
`<Primavera_Gateway_Home>\primeprovider\data\p6data` folder. The path you enter must be the absolute path to the file.
 For a P6 EPPM with Primavera Unifier integration, locate the **UnifierP6DataSetup.xml** file for the Unifier provider. The path you enter must be the absolute path to the file.
 For a P6 EPPM with any third-party enterprise application integration, select the relevant
`<third-party provider P6datasetup>XML` file from the **data** folder. The path you enter must be the absolute path to the file.
- f. Select **Run**. The UDFs or codes will be imported into the P6 EPPM deployment you selected.
- g. Select **Finish** to close the utility.

Adding P6 User-Defined Fields and Codes to Providers

To have additional P6 UDFs and codes available for synchronization and field mapping templates for a selected provider, the UDFs and codes must be included in the:

- ▶ metadata.xml
- ▶ P6ExtraMetaData.xml
- ▶ PDIEExtraMetaData.xml

Adding P6 UDFs and Codes to the Sample Provider

Add UDFs or codes in the P6ExtraMetaData and PDIEExtraMetaData files in the
`<Primavera_Gateway_Home>\sample\sampleprovider\data\p6` folder.

Adding P6 UDFs and Codes to the Prime Provider

Add UDFs or codes in the P6ExtraMetaData and PDIEExtraMetaData file in the
`<Primavera_Gateway_Home>\primeprovider\data` folder.

Adding P6 UDFs and Codes to the Unifier Provider

Add UDFs or codes in the PDIEExtraMetaData.xml file in the
`<Primavera_Gateway_Home>\unifierprovider\data` folder.

Adding P6 UDFs and Codes for Third-party Providers

For all third-party providers, add UDFs or codes in the P6ExtraMetaData.xml and PDIExtraMetaData.xml files located under the **data** folder of the third-party provider.

Note: Ensure that **P6data** folder is listed before the third-party provider folders. Otherwise the third-party provider fails to load.

Adding, Updating, or Customizing Gateway Metadata

After modifying the P6ExtraMetaData and PDIExtraMetaData files, run the **Gateway-Configuration** utility to add your application's UDFs or Codes in the Gateway metadata. The utility is located in the following location:

- ▶ On Windows, go to **C:\<Primavera_Gateway_Home>\pdi\snapshots\dbsetup-dist**
 - ▶ On Linux and Solaris, go to **C:/<Primavera_Gateway_Home>/pdi/snapshots/dbsetup-dist**
- 1) Navigate to the **<Primavera_Gateway_Home>/pdi/snapshots/dbsetup-dist** folder.
 - 2) If you are installing on a non-Microsoft Windows system, type the following command to give execute permission for the utility:
chmod 755 Gateway-Configuration.sh
 - 3) Run the following command:
 - ▶ For Windows installations, run **Gateway-Configuration.bat**
 - ▶ For Linux and Solaris installations, run **./Gateway-Configuration.sh**
 - 4) In the **Primavera Gateway Configuration Utility** dialog box, enter the following information:
 - a. Select **Manage Metadata**, and select **Next**.
 - b. Select any of the following options to manage Gateway metadata and select **Next**.
 - **Replace Gateway Metadata**
 - **Update Gateway Metadata**
 - **Customize Gateway Metadata**

Note: The **Customize Gateway Metadata** option only updates the Gateway database with metadata.

- 5) Based on the **Manage Metadata** option selected in the previous step, enter the following database connection details:
 - a. In the **DBA User Name** field, enter the user name of the oracle database administrator.
 - b. In the **DBA Password** field, enter the password of the oracle database administrator.
 - c. In the **Database Host** field, enter the host name of the Oracle database on which you will be updating the Primavera Gateway database.
 - d. In the **Database Host Port** field, enter the port number of the Oracle database.
 - e. In the **Database Name** field, enter the Gateway database name and select any of the following methods to connect to the database.
 - In the **SID** field, enter the SID of the Oracle database.
 - In the **Service** field, enter the service name of the Oracle database.
 - f. In the **Schema Owner** field, enter the schema owner name.
 - g. In the **Schema Password** field, enter the password for the schema owner.

- h. In the **Provider data folder** field, verify the path name for the following, as applicable:
 - If you are using the Sample provider, then verify that this field contains the default Sample directory that contains all the Sample XML metadata/mapping templates.
 - If you chose to install additional providers, then verify that this field contains the home directory for each provider. The XML files in the associated **data** subdirectory must include all the required data to load metadata and mapping templates.

For more information about these files, see the *Gateway Developer's Guide*.

To add providers, select **Add** and locate the **data** folder for each provider you wish to add.

To remove providers, select a provider and select **Remove**.

- i. In the **Gateway Data Folder** field, verify the path name to the PDI data folder. For example, C:/PrimaveraGateway/pdi/data.
- j. If you chose to **Customize Gateway Metadata**, then specify the XML file in the **Customization XML** field. Enter the path name or select **Browse** and locate the Customization.xml file for the specific provider.

Note: This field displays only when you select the Customize Gateway Metadata option.

- k. Select **Test Connection**. If the connection fails, modify the applicable fields and repeat as necessary.
- l. Select **Run** to run the configuration utility.

Adding or Removing Providers

To add or remove providers, including Primavera providers, to Primavera Gateway:

- 1) Stop the Gateway domain before adding or removing providers or customizations.
- 2) Ensure the following:
 - ▶ The **bin** folder of the supported Java JDK is included in the PATH.
 - ▶ If there are other JDK bin folders in the PATH, they should be listed first.
- 3) Navigate to the <Primavera_Gateway_Home>/pdi/snapshots/dbsetup-dist folder.
- 4) If you are installing on a non-Microsoft Windows system, type the following command:
chmod 755 Gateway-Configuration.sh
- 5) Run the following command:
 - ▶ For Windows installations, run **Gateway-Configuration.bat**
 - ▶ For Linux and Solaris installations, run **./Gateway-Configuration.sh**.
- 6) In the **Primavera Gateway Configuration Utility** dialog box, enter the following information:
 - a. Select **Manage Providers**, and click **Next**.
Selecting this option updates the pdi.ear file and the Gateway database with custom metadata from the XML files.
 - b. In the **Select Gateway ear file (pdi.ear) location**, enter or click **Browse** to locate the .ear file.

- c. In the **Gateway domain location** field, enter or click **Browse** to specify the Gateway domain.
 - d. In the **Installed Gateway Providers** field, review the list of providers displayed and perform any of the following actions:
 - To add a provider, click **Add Provider Location**, and navigate to the location of the provider.
 - To remove a provider listed in the Gateway user interface, select the provider and click **Remove**.
 - To delete a provider from the database and the pdi.ear file, select the **Delete** option and click **Remove**.
- 7) Enter the following database connection details:
- a. In the **DBA User Name** field, enter the name of the database administrator.
 - b. In the **DBA Password** field, enter the password for the database administrator.
 - c. In the **Database Host** field, enter the host name of the Oracle database on which you will be updating the Primavera Gateway database.
 - d. In the **Database Host Port** field, enter or verify the port number of the Oracle database.
 - e. In the **Database Name** field, enter the Gateway database name and select any of the following methods to connect to the database.
 - In the **SID** field, enter the SID of the Oracle database.
 - In the **Service** field, enter the service name of the Oracle database.
 - f. In the **Schema Owner** field, enter the database user name to be used for the Primavera Gateway database. (This name should match the **Schema Owner** name when you installed Primavera Gateway.)
 - g. In the **Schema Password** field, enter the database password to be used for the Primavera Gateway database.
 - h. Select **Test Connection**. Modify the applicable fields if the connection fails and repeat as necessary.
 - i. Click **Update**. The status field displays a success message.
 - j. Click **Finish** to exit the configuration utility.

Note: Redeploy pdi.ear to ensure the changes are reflected in Primavera Gateway.

Adding or Removing Customizations

Use this procedure if a customization includes XML files, jar files, and other files such as Java customization. If you have installed Gateway on a managed server, see **Supporting Java Customization on a Managed Server** (on page 28) for more details.

Note: If a customization does not include any jar files, and uses Groovy customization, then upload the XML file from the Gateway user interface.

To add or remove customization files in Gateway:

- 1) Stop the Gateway domain before adding or removing providers or customizations.

- 2) Ensure the following:
 - ▶ The **bin** folder of the supported Java JDK is included in the PATH.
 - ▶ If there are other JDK bin folders in the PATH, it should be listed first.
- 3) Navigate to the **<Primavera_Gateway_Home>/pdi/snapshots/dbsetup-dist** folder.
- 4) If you are installing on a non-Microsoft Windows system, type the following command for execute privileges:
chmod 755 Gateway-Configuration.sh
- 5) Run the following command:
 - ▶ For Windows installations, run **Gateway-Configuration.bat**
 - ▶ For Linux and Solaris installations, run **./Gateway-Configuration.sh**
- 6) In the **Primavera Gateway Configuration Utility** dialog box, enter the following information:
 - a. Select **Manage Customizations**, and select **Next**.
Selecting this option updates the pdi.ear file and the Gateway database with custom metadata from the customization XML files.
 - b. In the **Select Gateway ear file (pdi.ear) location**, enter or select **Browse** to locate the .ear file.
 - c. In the **Installed Gateway Customizations** field, review the list of customization files displayed in the dialog box, and perform any of the following actions:
 - To add a customization, select **Add Customization**, and navigate to the folder location of the customization file.
 - To remove a customization from the list, select a specific customization, and select **Remove**.
 - To delete a customization from the database and the pdi.ear file, select the **Delete** option and select **Remove**.
- 7) Enter the following database connection details:
 - ▶ **DBA User Name**: Enter the name of the database administrator.
 - ▶ **DBA Password**: Enter the password for the database administrator.
 - ▶ **Database Host**: Enter the host name of the Oracle database on which you will be updating the Primavera Gateway database.
 - ▶ **Database Host Port**: Enter the port number of the Oracle database.
 - ▶ **Database Name**: Enter the Gateway database name and select any of the following methods to connect to the database.
 - **SID**: Enter the SID of the Oracle database.
 - **Service**: Enter the service name of the Oracle database.
 - ▶ **Schema Owner**: Enter the name of Gateway schema owner. (This name should match the name that was entered when you installed Primavera Gateway.)
 - ▶ **Schema Password**: Enter the password for the schema owner.
 - ▶ Select **Test Connection**. Modify the applicable fields if the connection fails and repeat as necessary.
 - ▶ Select **Update**. The status field displays a success message.
 - ▶ Select **Finish** to exit the configuration utility.

Supporting Java Customization on a Managed Server

If you have installed Gateway on a **managed server**, complete the following steps to ensure Java customization is supported:

- 1) Log in to the WebLogic Administration console for Gateway.
- 2) Select **pdi.ear** in **Deployments** tab and stop the deployment.
- 3) Select **Lock & Edit** in the left pane and select **pdi.ear** in **Deployments** tab.
- 4) Select **Update** to update **pdi.ear** for the managed server.
- 5) Save the changes from the left pane (Activate Changes)
- 6) Restart **pdi.ear** deployment.

Configuring Deployment Targets

For each provider installed in Primavera Gateway, you must specify a deployment target in the Gateway user interface.

Configuring the P6 Deployment Target

To configure the P6 deployment target:

- 1) Using a browser, enter the Primavera Gateway URL.
<hostname>:<port number>/pdi
Where, <hostname> and <port number> should match those of your Primavera Gateway domain.
- 2) Log in to Primavera Gateway with Gateway Administration credentials.

Note: You must be assigned the PrimaveraGatewayAdmin role.

- 3) In Primavera Gateway, select the **Configuration** tab, **Deployments**.
A list of providers added at installation display.
- 4) In the **Provider Name** column, select **P6 Provider** and select the **Edit** button.
- 5) On the **Edit Deployment General** page, complete the fields as applicable.

Note: Select **Next** on each wizard dialog box to advance to the next step.

- 6) On the **Deployment Configuration** page, enter the following information:
 - a. In the **User Name** field, enter a user name of a user who has admin privileges on the P6 deployment.
 - b. In the **Password** field, enter the password of the admin user.
 - c. In the **Endpoint** field, enter the address of the sync service that is served by your P6 adapter that you deployed as a prerequisite. This address would follow this format:
<protocol>://<hostname>:<port number>/p6adapter/services/SyncServiceV1
 - d. If encryption is to be enabled, select **Enable Encryption** and enter the following information:
 1. In the **Keystore File** field, select **Browse...** and locate the keystore file.

2. in the **Keystore Password** field, enter the keystore password.
3. In the **Certificate Alias** field enter a certificate alias.

Note: The information you enter here must be consistent with the information used when deploying the P6 Adapter.

- e. In the **P6 Currency** field, enter the base currency for your P6 deployment.
If necessary, log into P6 to obtain the base currency used by your P6 deployment.
- f. Select **Save**.

Enabling Encryption Between Primavera Gateway and P6 Adapter

To ensure all requests and responses between Primavera Gateway and P6 Adapter are encrypted:

1) Create a Keystore file:

- a. Create a folder, for example, C:\keystore.
- b. Create a keystore with the private key. For example, by using the Java keytool genkey command. From the command line, execute:

```
keytool -genkey -alias <alias_name> -keyalg RSA -sigalg SHA1withRSA
-keypass <keyPassword> -storepass <storePassword> -keystore <keystore
file location>
```

Where:

<alias> is the key alias

<keyPassword> is the password of the private key

<storePassword> is the password of the keystore

For example:

```
keytool -genkey -alias myAlias -keyalg RSA -sigalg SHA1withRSA
-keypass myPassword -storepass myPassword -keystore
c:\keystore\keystore.jks
```

- c. Enter information for each of the following questions:
 - What is your first and last name?
Enter the Gateway host name.
 - What is the name of your organization?
 - What is the name of your city or locality?
 - What is the name of your State or Province?
 - What is the two-letter country code for this unit? For example, US.
 - Is CN=<Gateway host name>, OU=<organization unit name>, O=<organization name>, L=<location>, ST=<state code>, C=<country code> correct? Enter Y or N.

Note: If P6Adapter is deployed on other than a Gateway machine, then copy the keystore folder with keystore.jks to the P6Adapter machine.

- 2) In the Gateway user interface, select the **Configuration** tab and enter deployment information for P6.

- 3) In P6 EPPM administration application, enter the keystore information that was entered in the Keystore file. The values must be identical.
- 4) In the P6 EPPM administration application, modify the message protection node setting as follows:
 - ▶ **Require Timestamp:** True
 - ▶ **Require Digital Signature for Incoming Messages:** True
 - ▶ **Require Encryption for Incoming Messages:** True
 - ▶ **KeyStore Type:** JKS
 - ▶ **File Location:** c:\keystore\keystore.jks
 - ▶ **KeyStore Password:** <password for the keystore file provided in keytool command>
 - ▶ **Private Key Alias:** <alias name provided in keytool command>
 - ▶ **Private Key Password:** <private key password for the keystore file provided in the keytool command>
 - ▶ **Encrypt Response:** True
- 5) After encryption is set, restart the P6 adapter domain in WebLogic.

Configuring Provider Deployment Targets

To configure provider deployments, including Primavera providers:

- 1) Using a browser, enter the Primavera Gateway URL.
<hostname>:<port number>/pdi
Where, the <hostname> and <port number> should match those of your Primavera Gateway domain.
- 2) Log into Primavera Gateway with Gateway Administration credentials.

Note: You must be assigned the PrimaveraGatewayAdmin role.

- 3) In Primavera Gateway, select the **Configuration** tab, **Deployments**.
A list of providers added at installation display.
- 4) In the **Provider Name** column, select the provider and select the **Edit** button.
 - a. In the **Edit Deployment General** and **Edit Deployment Configuration** pages, complete the applicable fields for your provider deployment.
 - b. Select **Save**.

Updating the Existing Domain with Server Group Information (WebLogic 12c)

If you have installed Primavera Gateway on a Managed server with OWSM, you will need to update the existing Gateway domain with server group information as follows:

- 1) Go to <WebLogic_Server_Path>/common/bin directory
- 2) Depending on the operating system, run the following script:
 - On Windows: Run config.cmd
 - On Linux or Solaris: Run config.sh

- 3) On the **Update Domain** screen:
 - ▶ Select **Update an existing domain**.
 - ▶ In the **Domain Location** field, enter or select Browse... and locate the Gateway domain to be updated.

Note: Select **Next** to advance to the next step.

- 4) On the **Advanced Configuration** screen, select **Managed Servers, Clusters and Coherence**.
- 5) On the **Managed Servers** screen, select **Managed Server** from the list and expand the drop-down list in the **Server Groups** column. Select the following options:
 - ▶ **JRF-MAN-SVR**
 - ▶ **WSM-CACHE-SVR**
 - ▶ **WSMPM-MAN-SVR**
- 6) On the **Configuration Summary** screen, select **Update**.

Uninstalling Primavera Gateway

Uninstall Primavera Gateway as follows:

- 1) Invoke the Uninstall wizard as follows:
 - ▶ For Windows, from the **Start** menu, select **Programs, Oracle-Primavera Gateway, Uninstall Primavera Gateway**.
 - ▶ For Linux and Solaris, execute the following commands:
cd <GatewayHome>/oui/bin
./runInstaller -deinstall
- 2) On the **Welcome** screen, click **Next**.
- 3) On the **Deinstall Oracle Home** screen, click **Deinstall**.
- 4) On the **Deinstallation Progress** screen select any of the following buttons to confirm the uninstall:
 - ▶ Click **Yes** to uninstall Primavera Gateway.
 - ▶ Click **No** to uninstall Primavera Gateway without deleting the Oracle Home directory.
- 5) On the **Deinstallation Complete** screen, click **Finish** to exit the wizard.
- 6) For Windows, from the **Start** menu, select **Programs, Oracle WebLogic**, and then **User Projects** and delete the Gateway domain that was created at installation.
- 7) Delete the Gateway domain folder from the **<WebLogic_HOME>/user_projects/domains** directory.
- 8) (For Managed server only) Run the RCU utility to drop the repository.
- 9) Log in to the Oracle database and drop the Gateway schema user that was created at installation.
- 10) Delete the Primavera Gateway home folder that was created at installation.

For More Information

In This Section

Where to Get Documentation	35
Where to Get Training	38
Where to Get Support	39
Documentation Accessibility	40

Where to Get Documentation

Complete documentation libraries for Primavera Gateway releases are available on the Oracle Technology Network (OTN) at:

<http://www.oracle.com/technetwork/documentation/default-1923957.html>

From this location you can either view libraries online or download them to have local copies. We recommend viewing them from OTN to ensure you always access the latest versions, including critical corrections and enhancements.

Primavera Gateway is configured to access its help system on OTN. However, you can also install a local version when you install the software.

The documentation assumes a standard setup of the product, with full access rights to all features and functions.

The following table describes the core documents available for Primavera Gateway and lists the recommended readers by role.

Title	Description
<i>Gateway Help</i>	Describes how to work with Primavera Gateway and provides information to help users accomplish tasks. All users should read the Help.
<i>Gateway Developer's Guide</i>	Provides information on how third-party systems such as enterprise resource management (ERP) and enterprise asset management (EAM) systems can create their own providers in order to integrate with Primavera products. Developers of third-party providers that integrate with Primavera products via Primavera Gateway should read this book.


Title	Description
<i>Gateway Customization Guide</i>	<p>Provides information on how to customize an existing third-party integration.</p> <p>Developers interested in customizing existing third-party providers that integrate with Primavera products via Primavera Gateway should read this book.</p>
<i>Gateway Provider Reference Guide</i>	<p>Provides a list of the business objects available for each supported provider.</p> <p>Developers of third-party providers that integrate with Primavera products via Primavera Gateway should read this book.</p>
<i>EBS Provider Reference Guide</i>	<p>Provides a list of the business objects available for the EBS provider.</p> <p>Developers of third-party providers that integrate with Primavera products via Primavera Gateway should read this book.</p>
<i>VCP Provider Reference Guide</i>	<p>Provides a list of the business objects available for the VCP provider.</p> <p>Developers of third-party providers that integrate with Primavera products via Primavera Gateway should read this book.</p>
<i>Manual Deployment Guide</i>	<p>Provides information on how to manually install and configure Primavera Gateway.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator for the third-party or ERP system should read this guide.</p>
<i>Gateway Installation and Configuration Guide</i>	<p>Provides information on how to install and configure Primavera Gateway. Primavera Gateway is a product that facilitates integrations with Primavera products and third-party systems such as enterprise resource management (ERP) and enterprise asset management (EAM) systems.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator for the third-party or ERP system should read this guide.</p>
<i>Gateway Upgrade Guide</i>	<p>Provides a sequence of procedures that must be completed to upgrade to a new version of Primavera Gateway.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator for the third-party or ERP system should read this guide.</p>

Title	Description
<i>Gateway Performance and Sizing Guide</i>	<p>Provides hardware and software requirements for deploying Primavera Gateway.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator for the third-party or ERP system should read this guide.</p>
<i>Gateway Security Guide</i>	<p>Provides guidelines on establishing a highly secure environment for all Primavera Gateway environments.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator for the third-party or ERP system should read this guide.</p>
<i>Gateway API Programmer's Guide</i>	<p>Provides instructions on how to access and use Primavera Gateway REST APIs.</p> <p>The Primavera Gateway network administrator/database administrator and Primavera Gateway users having the Gateway Developer role should read this guide.</p>
<i>Connecting with Instantis EnterpriseTrack</i>	<p>Provides instructions on how to setup the integration environment for Oracle Instantis EnterpriseTrack in Primavera Gateway.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator for the third-party system should read this guide.</p>
<i>Connecting Prime and P6 EPPM</i>	<p>Provides instructions on how to setup the integration environment between Oracle Primavera Prime and P6 Enterprise Project Portfolio Management in Primavera Gateway.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator for the third-party system should read this guide.</p>
<i>Connecting Unifier and P6 EPPM</i>	<p>Provides instructions on how to setup the integration environment between Oracle Primavera Unifier and P6 Enterprise Project Portfolio Management in Primavera Gateway.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator for the third-party system should read this guide.</p>
<i>Migrating P6 Data Between Distinct Environments</i>	<p>Provides instructions on how to setup the integration environment between distinct P6 deployments to transfer P6 data in Primavera Gateway.</p> <p>The Primavera Gateway network administrator/database administrator and the administrator should read this guide.</p>

Title	Description
<i>Connecting E-Business Suite</i>	Provides instructions on how to setup the integration environments for Oracle E-Business Suite with P6 Enterprise Project Portfolio Management and Instantis EnterpriseTrack in Primavera Gateway. The Primavera Gateway network administrator/database administrator and the administrator for the third-party system should read this guide.
<i>Connecting Value Chain Planning and P6 EPPM</i>	Provides instructions on how to setup the integration environment between Oracle Value Chain Planning and P6 Enterprise Project Portfolio Management in Primavera Gateway. The Primavera Gateway network administrator/database administrator and the administrator for the third-party system should read this guide.
<i>Configuring Gateway for Single Sign On</i>	Provides instructions on how to configure Oracle Access Manager (OAM) and then enable Single Sign On for Primavera Gateway. The Primavera Gateway network administrator/database administrator should read this guide.
<i>Gateway Licensing Information User Manual</i>	Lists licensing information of all third-party software that is used or associated with the Oracle software program.
<i>Tested Configurations</i>	Lists the configurations that have been tested and verified to work with Primavera Gateway. The Primavera Gateway network administrator/database administrator and the administrator for the third-party or ERP system should read this guide.

Distributing Information to the Team

You can copy the online documentation to a network drive for access by project participants. Each team member can then view or print those portions that specifically relate to his or her role in the organization.

Throughout this documentation, the Security Guidance icon  helps you to quickly identify security-related content to consider during the installation and configuration process.

Where to Get Training

To access comprehensive training for all Primavera products, go to:

<http://education.oracle.com>

Oracle Learning Library

The Oracle Learning Library (OLL) provides online learning content covering Primavera products. Content includes videos, tutorials, articles, demos, step-by-step instructions to accomplish specific tasks, and self-paced interactive learning modules.

To access the learning library's Primavera content, go to:

<http://www.oracle.com/goto/oll>

Where to Get Support

If you have a question about using Oracle products that you or your network administrator cannot resolve with information in the documentation or help, click <http://support.oracle.com/>. This page provides the latest information on contacting Oracle Global Customer Support, knowledge articles, and the support renewals process. For more information about working with Support, visit <https://support.oracle.com/epmos/faces/DocumentDisplay?id=888813.2> to view Support Tools & Tips.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/us/support/contact-068555.html> or visit <http://www.oracle.com/us/corporate/accessibility/support/index.html> if you are hearing impaired.

Using Primavera's Support Resource Centers

Primavera's Support Resource Center provides links to important support and product information. Primavera's Product Information Centers (PICs) organize documents found on My Oracle Support (MOS), providing quick access to product and version specific information such as important knowledge documents, Release Value Propositions, and Oracle University training. PICs also offer documentation on Lifetime Management, from planning to installs, upgrades, and maintenance.

Visit <https://support.oracle.com/epmos/faces/DocumentDisplay?id=1486951.1> to access links to all of the current PICs.

PICs also provide access to:

- ▶ **Communities** are moderated by Oracle providing a place for collaboration among industry peers to share best practices.
- ▶ **News** from our development and strategy groups.
- ▶ **Education** contains a list of available Primavera product trainings through Oracle University. The Oracle Advisor Webcast program brings interactive expertise straight to the desktop using Oracle Web Conferencing technology. This capability brings you and Oracle experts together to access information about support services, products, technologies, best practices, and more.

For more information about working with Support, visit <https://support.oracle.com/epmos/faces/DocumentDisplay?id=888813.2>.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Legal Notices

Oracle Primavera Prime Gateway Installation and Configuration Guide

Copyright © 2013, 2015, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software or hardware and documentation may provide access to or information on content, products and services from third-parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.