

**Oracle® Retail Analytic Parameter Calculator for
Regular Price Optimization**

Installation Guide

13.2.2

E20547-01

January 2011

Copyright © 2011, Oracle and/or its affiliates. All rights reserved.

Primary Author: Anirudha Accanoor

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Licensing Note: This media pack includes a Restricted Use license for Oracle Retail Predictive Application Server (RPAS) - Enterprise Engine to support Oracle® Retail Analytic Parameter Calculator for Regular Price Optimization only.

Value-Added Reseller (VAR) Language

Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

(i) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.

(ii) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.

(iii) the software component known as **Access Via**™ licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.

(iv) the software component known as **Adobe Flex**™ licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

Contents

Send Us Your Comments	vii
Preface	ix
Audience	ix
Documentation Accessibility	ix
Related Documentation	x
Customer Support	x
Review Patch Documentation	x
Oracle Retail Documentation on the Oracle Technology Network	xi
Conventions	xi
 1 Introduction	
Hardware and Software Requirements	1-2
Supported Oracle Retail Products	1-3
Additional Documentation	1-3
Road Map for Installing APC-RPO	1-3
 2 Installing APC-RPO on UNIX Environments	
Preparation	2-1
Environment Variable Setup Script	2-1
Additional Environment Variables	2-2
Downloading and Extracting the APC-RPO Media Pack	2-3
Installing Analytic Parameter Calculator for Regular Price Optimization	2-3
Post Installation Tasks	2-12
Configuration Files for the RPAS Fusion Client	2-13
Configuring the RPAS Fusion Client for APC-RPO	2-14
 A Appendix: Installation Order	
Enterprise Installation Order	A-1

Send Us Your Comments

Oracle Retail Analytic Parameter Calculator for Regular Price Optimization
Installation Guide, 13.2.2

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

Note: Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the Online Documentation available on the Oracle Technology Network Web site. It contains the most current Documentation Library plus all documents revised or released recently.

Send your comments to us using the electronic mail address: #
retail-doc_us@oracle.com.

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at <http://www.oracle.com>.

Preface

Oracle Retail Installation Guides contain the requirements and procedures that are necessary for the retailer to install Oracle Retail products.

This document provides detailed instructions on how you can install the Analytic Parameter Calculator for Regular Price Optimization application (apcrpo domain). This document does not describe how to create the actual configuration.

Audience

This Installation Guide is for the following audiences:

- System administrators and operations personnel
- Database administrators
- System analysts and programmers
- Integrators and implementation staff personnel

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/support/contact.html> or visit <http://www.oracle.com/accessibility/support.html> if you are hearing impaired.

Related Documentation

For more information, see the following documents in the Oracle Retail Analytic Parameter Calculator for Regular Price Optimization 13.2.2 documentation set:

- *Oracle Retail Analytic Parameter Calculator for Regular Price Optimization Release Notes*
- *Oracle Retail Analytic Parameter Calculator for Regular Price Optimization User Guide for the RPAS Classic Client*
- *Oracle Retail Analytic Parameter Calculator for Regular Price Optimization User Guide for the RPAS Fusion Client*
- *Oracle Retail Analytic Parameter Calculator for Regular Price Optimization Implementation Guide*

For more information on RPAS, see the Oracle Retail Predictive Application Server 13.2.2 documentation set.

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:
<https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

Review Patch Documentation

When you install the application for the first time, you install either a base release (for example, 13.1) or a later patch release (for example, 13.1.2). If you are installing the base release, additional patch, and bundled hot fix releases, read the documentation for all releases that have occurred since the base release before you begin installation. Documentation for patch and bundled hot fix releases can contain critical information related to the base release, as well as information about code changes since the base release.

Oracle Retail Documentation on the Oracle Technology Network

Documentation is packaged with each Oracle Retail product release. Oracle Retail product documentation is also available on the following Web site:

http://www.oracle.com/technology/documentation/oracle_retail.html

(Data Model documents are not available through Oracle Technology Network. These documents are packaged with released code, or you can obtain them through My Oracle Support.)

Documentation should be available on this Web site within a month after a product release.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Introduction

This document provides instructions on installing Oracle Retail Analytic Parameter Calculator for Regular Price Optimization (APC-RPO). It provides detailed instructions on how to install the Analytic Parameter Calculator for Regular Price Optimization application. This document does not describe how to create the actual configuration.

Supplemental installation guides are referenced in this document. The *RPAS Installation Guide* and *RPAS Configuration Tools User Guide* must be obtained prior to beginning the installation process. Read these documents in their entirety before beginning the installation.

This chapter provides the hardware and software requirements for APC-RPO. It also provides information on the supported Oracle Retail products and the road map to install the APC-RPO application. It includes the following:

- [Hardware and Software Requirements](#)
- [Supported Oracle Retail Products](#)
- [Additional Documentation](#)
- [Road Map for Installing APC-RPO](#)

Hardware and Software Requirements

The following table provides information about the current release.

Table 1–1 Hardware and Software Requirements

Requirement	Details
Supported RPAS Version	13.2.2
Supported OS, Server and Compilers	<ul style="list-style-type: none"> ■ Oracle Solaris 10 (SPARC): GCC 4.2.3 (32 bit) ■ AIX 5.3 (POWER) - TL12 SP1: GCC 4.1.1 (32 bit) ■ AIX 6.1 (POWER) -TL4: GCC 4.3.3 (32 bit) ■ HP-UX 11.31 (Itanium): ACC 6.20 (64 bit) ■ Oracle Linux 5, Update 3 (5.3): GCC 4.1.2 (64 bit) ■ Red Hat Enterprise Linux 5.3: GCC 4.1.2 (64 bit) <p>Notes:</p> <p>After the 13.2.2 release, the following components will no longer be supported:</p> <ul style="list-style-type: none"> ■ 32 bit compilation on Solaris 10, AIX 5.3, and AIX 6.1 platforms. All custom extensions must be recompiled in the 64 bit mode on these platforms. Customers must also migrate to 64 bit Java on these platforms. ■ GCC compiler on Solaris 10. The Oracle Solaris Studio 12.2 compiler is in development as a replacement for the GCC compiler. Customers on Solaris 10 who have custom extensions must recompile their extensions using this compiler.
Supported OS, Client	<ul style="list-style-type: none"> ■ Microsoft Windows XP ■ Microsoft Windows Vista
Required 3rd Party Software	<ul style="list-style-type: none"> ■ Oracle Java Runtime Environment (JRE) 1.6 ■ Oracle Java Runtime Environment (JRE) 1.5 <ul style="list-style-type: none"> - For AIX, the JRE version must be the 32-bit version of # Java 1.5 SR1 or higher. <p>Notes:</p> <ul style="list-style-type: none"> ■ After the 13.2.2 release, JRE 1.5 will no longer be supported. Only JRE 1.6 will remain supported. ■ When installing Java, avoid enabling AutoUpdate because it may update the Java version without prompting. ■ If using APC-RPO on the RPAS Fusion Client and if the Fusion Client is installed on a WebLogic server that resides on the same system as the RPAS server, you must use Java 1.6
For ODI Enabled Integration of the Fashion Planning Bundle (Optional)	Oracle Data Integrator 10.1.3.5

Supported Oracle Retail Products

The following Oracle Retail products are supported:

Table 1–2 Supported Oracle Retail Products

Product	Version
Oracle Retail Regular Price Optimization (RPO)	13.2.2

Additional Documentation

See the following additional documentation for installing, managing, and using the RPAS Fusion Client and APC-RPO:

- Additional RPAS Documentation:
 - *Oracle Retail Predictive Application Server Installation Guide*
 - *Oracle Retail Predictive Application Server Administration Guide for the Fusion Client*
 - *Oracle Retail Predictive Application Server User Guide for the Fusion Client*
- Additional APC-RPO Documentation :
 - *Oracle Retail Analytic Parameter Calculator for Regular Price Optimization User Guide for the RPAS Fusion Client*

Road Map for Installing APC-RPO

This guide explains how you can install and set up the APC-RPO application. In order to install APC-RPO for production, you must perform the following tasks in a sequence:

Task	Description
<i>Pre-installation Tasks</i>	
1.	Install and set up the RPAS Infrastructure. For more information, refer to the <i>Oracle Retail Predictive Application Server Installation Guide</i> .
2.	Install and set up the RPAS Client. RPAS Release 13.2.2 includes the RPAS Classic Client and RPAS Fusion Client. For more information, refer to the <i>Oracle Retail Predictive Application Server Installation Guide</i> .
3.	Review and meet the hardware and software requirements for APC-RPO. For more information, see Hardware and Software Requirements .
<i>Installation Task</i>	
4.	Access the APC-RPO installation software and install the application. For more information, see Chapter 2, "Installing APC-RPO on UNIX Environments" .

Note: The APC-RPO installation software enables you to install the taskflow and online help files for the RPAS Fusion Client. In order to install the taskflow files, the RPAS Fusion Client must already be installed.

Installing APC-RPO on UNIX Environments

The installation of the server-side RPAS components on UNIX operating systems is accomplished using Java-based installation programs that are included with the installation package.

The Analytic Parameter Calculator for Regular Price Optimization (APC-RPO) Installer automates the following:

- Installation of the APC-RPO mock install configuration.
- Installation of the APC-RPO configuration for the RPAS Fusion Client. For more information on installing the RPAS Fusion Client, refer to the *Oracle Retail Predictive Application Server Installation Guide*.
- Creation of a sample APC-RPO domain.

This document assumes that the RPAS installer process (from the *RPAS Installation Guide*) has been completed prior to using the APC-RPO installer.

Preparation

The RPAS server components required prior to this installation process are available from Oracle's E-Delivery web site, <http://edelivery.oracle.com>, and My Oracle Support, <https://support.oracle.com>.

Environment Variable Setup Script

Before running the solution installer, source your `retaillogin.ksh` script. The script is located in the root of the base directory where RPAS was installed unless the default was overwritten when specifying directory paths.

Source the script from inside the directory where the script is located:

```
././retaillogin.ksh
```

Or, include the full path after the period ".":

```
./<base_directory>/retaillogin.ksh
```

Notes:

- The preceding period and space (" ") must be included at the beginning of the command when executing the script.
 - Include this path and script in the .profile in your home directory (~/.profile) if you want to have this environment setup script run during login.
-

This script sets up the environment variables, such as `RPAS_HOME` and `RIDE_HOME`, which are required for RPAS to run properly.

Additional Environment Variables

In addition to the execution of `retaillogin.ksh`, export the following environment variables prior to starting the installer.

All Platforms:

```
export#RPAS_JAVA_CLASSPATH="$RPAS_HOME/applib/aaijni.jar:#  
$RPAS_HOME/applib/aaiAPCRPO.jar:$RPAS_JAVA_CLASSPATH"
```

Note: The following commands are an example based on common Java installation structures. To ensure you are adding the correct path, use the Unix `find` command to locate `libjvm.so` (find `$JAVA_HOME` -name `libjvm.so`) and adjust the below paths as appropriate.

For Linux:

```
export#PATH=$JAVA_HOME/bin:$JAVA_HOME/jre/lib/amd64/server:$PATH  
export#LD_LIBRARY_PATH=$JAVA_HOME/jre/lib/amd64/server:$LD_LIBRARY_PATH
```

For Solaris:

```
export#LD_LIBRARY_PATH="$JAVA_HOME/bin:$JAVA_HOME/lib/sparc/client:#  
$LD_LIBRARY_PATH"  
export#PATH="$JAVA_HOME/bin:$JAVA_HOME/lib/sparc/client:$PATH"
```

For AIX:

```
export#LIBPATH="$JAVA_HOME/bin:$JAVA_HOME/bin/classic:$LIBPATH"  
export#PATH="$JAVA_HOME/bin:$JAVA_HOME/bin/classic:$PATH"
```

For HP-UX:

```
export#SHLIB_PATH="$JAVA_HOME/bin:$JAVA_HOME/lib/IA64W/server:$SHLIB_PATH"  
export#PATH="$JAVA_HOME/bin:$JAVA_HOME/lib/IA64W/server:$PATH"
```

Downloading and Extracting the APC-RPO Media Pack

The following procedure provides information about downloading and extracting the APC-RPO media pack and its contents:

1. Create a directory to store the APC-RPO media pack on the target server. This directory is referred to as [APC-RPO Installation]. It is the location where the APC-RPO installation routine is run.
2. Download and extract the media pack to this location. Once extracted, two directories appear, CDROM and DOCS.

The CDROM folder contains the sizeopt.zip file. This file contains the APC-RPO solution.

The DOCS folder contains the APC-RPO documentation.

Installing Analytic Parameter Calculator for Regular Price Optimization

The following procedure provides information about installing APC-RPO:

1. Extract the APC-RPO installer from the [APC-RPO Installation] directory.

```
cd#CDROM
unzip#apcrpo.zip
```

2. From the [APC-RPO Installation]/CDROM directory, run the following commands to run the APC-RPO installer:

```
cd#apcrpo
./install.sh
```

Note: The command must be executed with the preceding period and forward slash (./).


If you are running this process on an X-Windows emulator (such as Exceed), graphical user interface to the Installer appears. If you are running in console mode through a terminal emulator, the text interface to the installer appears.

In both cases, the requested information is identical. In the GUI, you may be shown a check box to signal whether you want a component installed; in text mode, you are prompted for a response of **true** or **false**.

Note: In text mode, the default value appears in square brackets []. To use the default value and continue, press **Enter**. If you want to use a different value, enter the new value. When prompted to create a directory, respond with **y** or **yes** and press **Enter**.

3. The Analytic Parameter Calculator for Regular Price Optimization installer screen appears and displays the components that are installed during installation process and the required components.

Figure 2–1 Analytic Parameter Calculator for Regular Price Optimization Installer Screen



Click **Next** to continue.


4. The Choose Components to Install screen appears.

Select the following options:

- **APCRPO** – Select this option to install the APC-RPO application with the domain.
- **RPAS Fusion Client configuration** – Select this option to install the RPAS Fusion Client configuration for APC-RPO. For more information on the configuration files included for the RPAS Fusion Client, see [Configuration Files for the RPAS Fusion Client](#).

Note: If you do not want to install the RPAS Fusion Client configuration, clear this check box and skip steps 8 and 9.

Figure 2–2 Choose Components to Install Screen



Click **Next** to continue.

5. The Base Paths for Solution screen appears.

Enter the relevant information in the following fields:

- **Dir to store solution** - Enter the directory path where your solution should be stored.
- **Dir to store created domains** - Enter the directory path where you the domain should be stored.
- **Path to retaillogin.ksh script** - Enter the path and file name to the retaillogin.ksh script created during RPAS installation.

Figure 2–3 Base Paths for Solution Screen

Base Paths for Solution


Dir to store solution	<input type="text" value="/u00/rpas/mock/configurations/apcrp"/>	Select Folder
Dir to store created domains	<input type="text" value="/u00/rpas/mock/domains"/>	Select Folder
Path to retaillogin.ksh script	<input type="text" value="/u00/rpas/mock/retaillogin.ksh"/>	Select File

Cancel Back Next Install

Click **Next** to continue.

6. The Domain installation paths screen appears. Enter the path to the APC-RPO domain to be created.


Figure 2-4 *Install Tasks Screen*



Click **Next** to continue.

7. The Install Tasks screen appears.
 - If you want to create the APC-RPO domain, select the **Create APCRPO Domain** check box, which is selected by default.
 - If you want to install all required components to support the APC-RPO domain, but not create the actual APC-RPO domain, clear the check box.

Figure 2–5 Fusion Location Information Screen



Click **Next** to continue.

8. The Fusion Location Information screen appears.

- Enter the number of servers running the RPAS Fusion Client where you want to install the APC-RPO configuration. In case the RPAS Fusion Client is running on a single server, enter 1. In case you have a clustered installation, you can enter up to four servers.
- Enter the host name and port number of the RPAS server.

Note: The Fusion Location Information screens appear when you select the RPAS Fusion Client configuration check box on the [Choose Components to Install Screen](#).

If you are not installing the RPAS Fusion Client configuration, proceed to step 10.

Figure 2–6 Fusion Location Information Screen

The screenshot shows a window titled "Analytic Parameter Calculator for Regular Price Optimiza...". Inside the window, there is a section titled "Fusion Location Information". Below this title, there are three input fields with labels: "Enter the number of RPAS Fusion Client servers to install these configurations on: (1-4)", "Enter the RPAS server hostname:", and "Enter the RPAS server port:". The first field contains the value "1", the second field contains "localhost", and the third field contains "55555". At the bottom of the window, there are four buttons: "Cancel", "Back", "Next", and "Install". The "Next" button is highlighted with a yellow border.

Click **Next** to continue.

9. Based on the number of servers you entered, the Fusion Location Information screen appears with the following set of fields for each server configuration:
 - **Hostname or IP** – Enter the host name or IP address of the server where the RPAS Fusion Client is installed.
 - **Configuration Directory** – Enter the location of the config directory available at the location where the RPAS Fusion Client is installed.
 - **Login username** – Enter the user name to log on to the server where the RPAS Fusion Client is installed.
 - **Login password** – Enter the password associated with the user name.
 - **Login username alias** – Specify an alias name for the administrative user. Specifying an alias name for the administrative user enhances the security for the application. When left blank, the alias name defaults to the administrative user name.

Figure 2–7 *Installation Progress Screen*


Click **Next** to continue.

Note: As part of the Oracle Software Security Assurance, sensitive information such as user credentials for the RPAS Fusion Client are encrypted and stored in a secure location in the application installation directory. This location is called the Oracle Wallet.

When the installation starts, the administrative user credentials will be retrieved from the Oracle Wallet based on the alias name specified in this screen.

10. The Installation Progress screen appears. Once you are ready to begin installation, click **Install**.

Figure 2–8 Installation Progress Screen



This screen also displays the progress of the installation routine. Select **Show Details** to view the log output as the installation is performed. If you do not select to view the details, a graphical representation of the installation steps appears. As each step is completed, the color changes to show you the progress.

You can toggle between detailed mode at any time during or after the installation.

11. When the installation has finished, the Finished message appears. Click **OK** to close the dialog box.
12. To view the installation details, select the **Show Details** button. The screen displays two tabs, the Output tab and the Error tab. It is recommended that you review these tabs for any issues that may have occurred during the installation process.

If you want to view the log again at a later date, a text copy is saved in the directory [APC-RPO Installation]. The log file is named based on the product and timestamp, followed by the .log extension.

Created as part of this process is the `make_domain.apcrpo` file located in [Solution Install Dir] entered previously. This file contains all of the required parameters needed to support the domain installation. If necessary, this file may be modified if the default parameters are not appropriate for your particular environment.

Note: The domain install process may also include post-installation data loading scripts specific to the APC-RPO configuration. These scripts, if present, may also be modified.

For additional information on installing RPAS domains manually, see the *RPAS Installation Guide*.

13. Click **Exit** to close the installer.

Post Installation Tasks

After you have installed APC-RPO, perform the following post installation tasks.

- Before starting the DomainDaemon, you must first source the solution's `environment.ksh` script. This loads all environment variables required by RPAS to interact with your solution's workbooks. To do this, either in shell or with an addition to your `.profile`, add `.` [Solution Install Dir]/bin/environment.ksh.
- If you have re-installed APC-RPO, you must edit a help file to use the APC-RPO online help in the RPAS Fusion Client.

Manually edit the `rgbu_planning_home/Help/ohwconfig.xml` file by removing the following duplicate line:

```
<helpSet#xmlns=" "#id="<shortProductName>"#  
location="<shortProductName>/<shortProductName>-help.hs"/>##
```

If this duplicate line is not removed, a "500 Page Not Found" error occurs when attempting to access the online help in the RPAS Fusion Client.

Configuration Files for the RPAS Fusion Client

This section describes the optional installation method that involves setting up the RPAS Fusion Client configuration and online help for the APC-RPO configuration. If you chose to install the Fusion Client configuration files using the APC-RPO installer, you can skip this section.

Note: Before proceeding, ensure that you have appropriate access privileges on the server running the RPAS Fusion Client.

Along with the files to install the APC-RPO solution and domain, the APC-RPO installation media pack also includes the RPAS Fusion Client configuration and online help files that you must install if you want to use APC-RPO on the RPAS Fusion Client.

These files are available at the following location within the [APC-RPO Installation] directory:

```
[APC-RPO#Installation]/apcrpo/fusion
<server-name>{RPASServerName}</server-name>
```

During the APC-RPO installation, these files are automatically copied over to the configuration directory where the RPAS Fusion Client is installed. The installation also ensures that the following RPAS Fusion Client configuration files are updated to reflect the APC-RPO installation:

- `ProfileList.xml` - Located in the [RPAS#Fusion#Client#Installation]/#config/rpas directory. This XML file includes the domain configuration available for use with the RPAS Fusion Client.
- `ohwconfig.xml` - Located in the [RPAS#Fusion#Client#Installation]/config/Help#directory. This XML file includes the online help configuration for the RPAS Fusion Client.

If you do not install the Fusion Client configuration files during the APC-RPO installation, you can choose to do one of the following tasks:

- Run the APC-RPO installer again, and select to install only the RPAS Fusion Client configuration.
- Run the RPAS Fusion Client installer again, and specify the APC-RPO domain configuration. For more information on the RPAS Fusion Client installation, refer to the *Oracle Retail Predictive Application Server Installation Guide*.
- Configure the RPAS Fusion Client for APC-RPO manually. For more information, see [Configuring the RPAS Fusion Client for APC-RPO](#).

Configuring the RPAS Fusion Client for APC-RPO

This section describes the optional configuration method that involves manually setting up the RPAS Fusion Client with the APC-RPO configuration. If you chose to install the Fusion Client configuration files using the APC-RPO installer, you can skip this section.

Note: Before proceeding, ensure that you have appropriate access privileges on the server running the RPAS Fusion Client.

To set up an additional domain connection:

1. Once you have the APC-RPO domain set up, navigate to the following location in the RPAS Fusion Client installation directory:

```
<RPAS_Fusion_Client_Installation>/config/rpas/
```

2. In a text editor, edit the ProfileList.xml file, and append a connection specification for your domain in the following syntax:

```
<connection-spec#name="{DomainConnectionName}">
#<server-name>{RPASServerName}</server-name>
#####<daemon-port>{Port#Number}</daemon-port>##
#####<domain>
#####<domain-name>{DomainName}</domain-name>
#####<domain-path>{Location#where#the#domain#is#installed}</domain-path>
#####</domain>
</connection-spec>
```

Note: In the example above, placeholders have been used as values for the parameters. Ensure that you replace the placeholders with the relevant values.

Where,

- `connection-spec#name` – Name for the connection specification. This matches the name for the taskflow configuration and resource files. Each must have a unique name.
- `server-name` – The host where the RPAS server is installed and the DomainDaemon process is running.
- `daemon-port` – The port specified when starting the DomainDaemon.
- `domain-name` – The name that is displayed to the user on the login screen.
- `domain-path` – Location where the domain is installed.

Note: Multiple domains on the same server can use the same configuration.

3. Save and close the ProfileList.xml file.
4. In the <RPAS_Fusion_Client_Installation>/config directory, create a new folder and specify the domainConnectionName or connection-spec name as the folder name.

5. Navigate to the fusionClient directory located within the directory where the domain is installed. This folder contains the following files that define the taskflow configuration:

- taskflowBundle.properties
- taskflow.xml

When you created the domain using the rpasInstall script, these files were generated based on the taskflow configuration you set up in the RPAS Configuration Tools. For more information on the taskflow configuration, refer to the *RPAS Configuration Tools User Guide*.

6. Copy the two files to the domain name folder you created in step 4.
7. Rename the Taskflow.xml file to include the domain name. The new file name must now read as Taskflow_<domainConnectionName>.xml. Where <domainConnectionName> is the domain connection name or connection-spec name.
8. Create a resources subfolder within this location and move the taskflowBundle.properties file to the resources subfolder.
9. In the resources subfolder, rename the taskflowBundle.properties file to include the domain name. The new file name must now read as <domainConnectionName>Bundle.properties. Where <domainConnectionName> is the domain connection name or connection-spec name.
10. For the changes to take effect, restart the RPAS and WebLogic servers.

Appendix: Installation Order

This section provides a guideline for the order in which the Oracle Retail applications should be installed. If a retailer has chosen to use only some of the applications, the order is still valid, less the applications not being installed.

Note: The installation order is not meant to imply integration between products.

Enterprise Installation Order

1. Oracle Retail Merchandising System (RMS), Oracle Retail Trade Management (RTM), Oracle Retail Sales Audit (ReSA), Optional: Oracle Retail Fiscal Management (ORFM)

Note: ORFM is an optional application for RMS if you are implementing Brazil localization.

2. Oracle Retail Service Layer (RSL)
3. Oracle Retail Extract, Transform, Load (RETL)
4. Oracle Retail Active Retail Intelligence (ARI)
5. Oracle Retail Warehouse Management System (RWMS)
6. Oracle Retail Allocation
7. Oracle Retail Invoice Matching (ReIM)
8. Oracle Retail Price Management (RPM)

Note: During installation of RPM, you are asked for the RIBforRPM provider URL. Since RIB is installed after RPM, make a note of the URL you enter. If you need to change the RIBforRPM provider URL after you install RIB, you can do so by editing the `remote_service_locator_info_ribserver.xml` file.

9. Oracle Retail Central Office (ORCO)
10. Oracle Retail Returns Management (ORRM)
11. Oracle Retail Back Office (ORBO) or Back Office with Labels and Tags (ORLAT)

12. Oracle Retail Store Inventory Management (SIM)

Note: During installation of SIM, you are asked for the RIB provider URL. Since RIB is installed after SIM, make a note of the URL you enter. If you need to change the RIB provider URL after you install RIB, you can do so by editing the `remote_service_locator_info_ribserver.xml` file.

- 13. Oracle Retail Predictive Application Server (RPAS)**
- 14. Oracle Retail Demand Forecasting (RDF)**
- 15. Oracle Retail Category Management (CM)**
- 16. Oracle Retail Replenishment Optimization (RO)**
- 17. Oracle Retail Analytic Parameter Calculator Replenishment Optimization # (APC RO)**
- 18. Oracle Retail Regular Price Optimization (RPO)**
- 19. Oracle Retail Merchandise Financial Planning (MFP)**
- 20. Oracle Retail Size Profile Optimization (SPO)**
- 21. Oracle Retail Assortment Planning (AP)**
- 22. Oracle Retail Item Planning (IP)**
- 23. Oracle Retail Item Planning Configured for COE (IP COE)**
- 24. Oracle Retail Advanced Inventory Planning (AIP)**
- 25. Oracle Retail Integration Bus (RIB)**
- 26. Oracle Retail Point-of-Service (ORPOS)**
- 27. Oracle Retail Markdown Optimization (MDO)**
- 28. Oracle Retail Clearance Optimization Engine (COE)**
- 29. Oracle Retail Analytic Parameter Calculator for Markdown Optimization (APC-MDO)**
- 30. Oracle Retail Analytic Parameter Calculator for Regular Price Optimization (APC-RPO)**
- 31. Oracle Retail Promotion Intelligence and Promotion Planning and Optimization (PI-PPO)**
- 32. Oracle Retail Workspace (ORW)**