

# **Oracle Health Insurance Back Office**

## **JET Application Installation & Configuration Manual**

Version 1.1

Part number: F13010-01

December 11, 2018

Copyright © 2018, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

#### **U.S. GOVERNMENT RIGHTS**

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are “commercial computer software” or “commercial technical data” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Where an Oracle offering includes third party content or software, we may be required to include related notices. For information on third party notices and the software and related documentation in connection with which they need to be included, please contact the attorney from the Development and Strategic Initiatives Legal Group that supports the development team for the Oracle offering. Contact information can be found on the Attorney Contact Chart.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your beta trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Software License and Service Agreement, which has been executed and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

## CHANGE HISTORY

Release	Version	Changes
10.18.1.3.0	0.1	<ul style="list-style-type: none"><li>• Creation</li></ul>
10.18.1.3.0	0.2	<ul style="list-style-type: none"><li>• Revision 07-09-2018</li><li>• Add 'Back Office' to 'Prerequisites'</li><li>• Revised 'Deploy HSL and PSL services'</li></ul>
10.18.1.3.0	0.3	<ul style="list-style-type: none"><li>• Revised PSL installation</li></ul>
10.18.1.3.0	0.4	<ul style="list-style-type: none"><li>• Revised architecture diagram</li><li>• Minor textual changes</li><li>• Revised note about hsl.tokenvalidation.rotor</li></ul>
10.18.1.3.0	1.0	<ul style="list-style-type: none"><li>• Reviewed. Slightly adjusted and updated to version 1.0.</li></ul>
10.18.2.0.0	1.1	<ul style="list-style-type: none"><li>• Republished with new part nr.</li></ul>

## RELATED DOCUMENTS

A reference in the text (**doc[x]**) is a reference to another document about a subject that is related to this document.

Below is a list of related documents:

<b>Doc[1]</b>	OHI Back Office HTTP Service Layer Installation & Configuration Manual (CTA13681)
---------------	---

---

# Contents

1	Introduction.....	6
2	Architectural overview .....	7
2.1	ZRGOHIJET Application.....	7
2.2	HSL and PSL services .....	8
3	Prerequisites .....	9
3.1	Weblogic Server (WLS) Preparation .....	9
3.2	Database Preparation.....	9
3.2.1	Create a HSL database account.....	9
3.2.2	Create a PSL database account.....	9
3.3	OHI Back Office.....	9
3.3.1	OHI Back Office Parameters.....	9
3.3.2	Module Authorization .....	10
3.4	Deploy HSL and PSL services.....	11
3.4.1	Create WLS data source for HSL database account .....	11
3.4.2	Create WLS data source for PSL database account.....	11
3.4.3	Configure hsl.properties .....	11
3.4.4	Configure psl.properties.....	11
3.4.5	Deploy HSL_JUP.....	11
3.4.6	Deploy HSL_AUN.....	12
3.4.7	Deploy HSL_AUZ.....	12
3.4.8	Deploy PSL_ACL.....	12
3.5	Deployment Activation.....	12
4	Installation of ZRGOHIJET Application.....	13
4.1	ZRGOHIJET Deployment.....	13
4.2	Post Installation.....	15
4.3	Updating the ZRGOHIJET Application.....	15
4.4	Deployment validation .....	16
5	Appendix A – Samples for HSL and PSL Properties Files .....	17
5.1	HSL Properties File Sample.....	17
5.2	PSL Properties File Sample .....	17

---

# 1 Introduction

The OHI Back Office JET Application provides web modules for OHI Back Office users.

OHI Back Office web modules are designed from the ground up as productivity tools for power users.

Whereas most of the Forms modules help to navigate through the OHI Back Office data to support multiple potential different processes, the web modules are designed to support a specific process.

The first web module is 'ZRG3097J' (Achterafcontrole). This module is used by claims examiners to re-check the validity of pre-selected claims lines. Advanced filters help the claim examiner to mark claims lines within a selected set for further investigation, keep track of the examination process and comment on individual claims lines.

All web modules and their supporting components are packaged as a single WAR file: ZRGOHIJET.war.

The ZRGOHIJET application is deployed to Oracle WebLogic Application Server (WLS).

In order to use the ZRGOHIJET application, the following HSL services must also be deployed:

- HSL\_AUN - Authentication of OHI Back Office users
- HSL\_AUZ - Authorization of OHI Back Office users
- HSL\_JUP - Returns the location of HSL services used by ZRGOHIJET modules.


In order to use the ZRG3097J module the following services must be deployed:

- PSL\_ACL - Private HTTP service to support the claims examination process.

This document describes how to install the ZRGOHIJET application and its related services.

## 2 Architectural overview

The diagram below shows the components of the OHI BO JET Application:



### 2.1 ZRGOHIJET Application



The ZRGOHIJET application was built using Oracle's "JET" toolkit for building modern web applications.

Among others, Oracle JET contains UI components, data binding support to synchronize between the front end application and a database back end, and has mobile support.

You can find more information on

<http://www.oracle.com/webfolder/technetwork/jet/index.html>


The ZRGOHIJET application is installed through a single WAR file. The web application calls HSL and PSL services to interact with the OHI Back Office database.

## 2.2 HSL and PSL services

The following HSL and PSL services are used to interact with the OHI Back Office database:

- HSL\_JUP  
Retrieve the OHI Back Office parameter values for 'JavaScript user interface' as a list of properties.
- HSL\_AUN  
Log on to the OHI Back Office database using the credentials entered by the user. If successful, return an OAUTH2 access token and a list of 'claims', i.e. a list of modules which may be accessed by the user.
- HSL\_AUZ  
Verify that the access token provided by the user is valid for the required service operation.
- PSL\_ACL  
REST service providing functionality for ZRG3097J

The architecture of each of the HSL and PSL services is shown below:



For more information about HSL services, see **Doc[1]**.



## 3 Prerequisites

The following prerequisites apply before you can deploy the OHI Back Office JET Application.

### 3.1 Weblogic Server (WLS) Preparation

Follow the instructions in **Doc[1]** to prepare WebLogic Server.

Ensure that the following steps are completed:

- Create HSL properties file
- Create PSL properties file
- Add `-Dhsl.properties=<hsl_properties>` to Server Start parameter in WLS. Where `<hsl_properties>` refers to the location of the HSL properties file.
- Add `-Dpsl.properties=<psl_properties>` to Server Start parameter in WLS. Where `<psl_properties>` refers to the location of the PSL properties file. (see Appendix G in **Doc[1]**).

### 3.2 Database Preparation

Install the database components for OHI Back Office:

Verify that the following database packages are valid in the OHI Back Office object owner schema (in a normal situation no invalid plsql packages should exist within the object owner schema):

- HSL\_JUP\_SP\_PCK  
Interface for the HSL\_JUP service
- HSL\_AUN\_SP\_PCK  
Interface for the HSL\_AUN service
- HSL\_AUZ\_SP\_PCK  
Interface for the HSL\_AUZ service
- PSL\_ACL\_SP\_PCK  
Interface for the PSL\_ACL service

#### 3.2.1 Create a HSL database account

---

Create a database account to call the HSL services, eg. 'hsl\_user'.  
See **Doc[1]** for more information.

#### 3.2.2 Create a PSL database account

---

Create a database account to call the PSL\_ACL service, eg. 'psl\_user'.  
See **Doc[1]** for more information.

### 3.3 OHI Back Office

#### 3.3.1 OHI Back Office Parameters

---

The ZRGOHIJET application calls HSL\_AUN and HSL\_AUZ for authentication and authorization of its users. It uses PSL\_ACL as a back end to access OHI Back Office

data.

Before it can do so, it needs to locate a Base URL where these services can be found. This is where HSL\_JUP comes in. This service, running at the same WLS domain as ZRGOHIJET itself, will connect to the OHI Back Office database and retrieve the OHI Back Office parameters of group 'Javascript user interface' to retrieve the backend url and log level.

To set the Back Office parameters:

- Open the Forms GUI and select 'Systeem > Algemeen > Back Office parameter waarden'.
- Select group 'Javascript user interface' and engage Execute Query.
- Set 'Backend URL' to the Base URL of the HSL\_AUN, HSL\_AUZ and PSL\_ACL services that you will use.  
The format is `https://server:port`  
Example: `https://localhost:8888`
- Optionally, set the log level.

BDDEV1813 Oracle Health Insurance Back Office

Bestand Bewerken Venster Help

ORACLE

Back Office parameterwaarden

Nr	Parameter	Groep	Type Groep	S?	Datatype
1	Backend URL	JavaScript user interface	Webservice	<input type="checkbox"/>	Alfanumeriek
2	Log level	JavaScript user interface	Webservice	<input type="checkbox"/>	Alfanumeriek
				<input type="checkbox"/>	
				<input type="checkbox"/>	
				<input type="checkbox"/>	
				<input type="checkbox"/>	
				<input type="checkbox"/>	
				<input type="checkbox"/>	
				<input type="checkbox"/>	
				<input type="checkbox"/>	

Help text: In een JavaScript applicatie dient bekend te zijn wat de URL is van de HTTP API's, zodat deze benaderd kunnen worden.

Parameterwaarden

Waarde	Datum ingang	Datum einde

### 3.3.2 Module Authorization

Do not forget to set up module authorization for the ZRGOHIJET modules:

- ZRG3097J

To access module authorization: Systeem > Beheer > Autorisatie > Moduleautorisatie.

## 3.4 Deploy HSL and PSL services

The instructions below are complementary to the general instructions for deploying HSL and PSL services given in **Doc[1]**.

### 3.4.1 Create WLS data source for HSL database account

---

Create a data source for connecting to the HSL user in the OHI Back Office database.

### 3.4.2 Create WLS data source for PSL database account

---

Create a data source for connecting to the PSL user in the OHI Back Office database.

### 3.4.3 Configure hsl.properties

---

The `hsl.tokenvalidation.rotor` property is used by:

- HSL\_AUN (authenticate OHI Back Office user and issue access token); and
- HSL\_AUZ (authenticate access token and verify authorization)

Ensure that this value is set. Refer to Appendix F in **Doc[1]** for more information.

### 3.4.4 Configure psl.properties

---

Before deploying any PSL modules, ensure that the following properties are set:

```
psl.authorization=TOKEN
psl.usercontext.control=TOKEN
psl.usercontext.token.type=JWT
psl.usercontext.claim=prn
psl.tokenvalidation.authentication=Basic BASE64_USERNAME_PASSWORD
psl.tokenvalidation.url=https://server:port/HSL_AUZ/auz/v1/authorization/verify
psl.tokenvalidation.method=post
psl.tokenvalidation.bodyparam={ "method" : "#method#", "token" : "#jwt#" ,
"resource" : "#path#" }
```

#### Notes

- The tokenvalidation URL must match the Base URI of the HSL\_AUZ service.
- The value for `psl.tokenvalidation.authentication` is a base64 encoded username:password string prepended with 'Basic'.  
The username:password combination must refer to a valid Weblogic user which has access to the HSL\_AUZ service.  
You may use <https://www.base64encode.org/> to generate the base64 encoded string.

See Appendix E in **Doc[1]** for more information about authentication and authorization and an actual example of a base64 encoded string.

### 3.4.5 Deploy HSL\_JUP

---

Before deploying HSL\_JUP, create entries for HSL\_JUP in the HSL properties file: data source, log configuration, allowed origins, usercontext etc.

Ensure that the following properties are set:

```
hsl.jup.authorization=NONE
# anyone can call HSL_JUP to retrieve the OHI BO params for the Javascript UI
```

#### Notes:

- The data source (`hsl.jup.jndiname`) is used to retrieve Back Office Parameters for the ZRGOHIJET Application. The 'Backend Url' parameter should point at the base URL for the PSL\_ACL, HSL\_AUN and HSL\_AUZ services.

Deploy HSL\_JUP with 'Custom Roles and Policies'.

### 3.4.6 Deploy HSL\_AUN

---

Before deploying HSL\_AUN, create entries for HSL\_AUN in the HSL properties file: data source, log configuration, allowed origins etc.

Ensure that the following properties are set:

```
hsl.aun.authorization=NONE
# anyone can call HSL_AUN and provide user/pass to login to the database
```

Deploy HSL\_AUN with 'Custom Roles and Policies'.

### 3.4.7 Deploy HSL\_AUZ

---

Before deploying HSL\_AUZ, create entries for HSL\_AUZ in the HSL properties file: data source, log configuration, allowed origins etc.

Ensure that the following properties are set:

```
hsl.auz.authorization=BASIC
# any weblogic user can call HSL_AUZ to verify token for token bearer.
# deploy with 'custom roles and policies' to fine-tune access through WLS
```

Deploy with 'Default Descriptors' if any weblogic user may call this service.

Deploy HSL\_AUZ with 'Custom Roles and Policies' if you want to fine-tune access through WLS.

### 3.4.8 Deploy PSL\_ACL

---

Before deploying PSL\_ACL, create entries for PSL\_ACL in the PSL properties file: data source, log configuration, allowed origins etc.

Deploy PSL\_ACL with 'Custom Roles and Policies'.

## 3.5 Deployment Activation

New deployments are not initially active.

Either start the new deployments through the WLS console or restart the managed server(s) to which the new application is/are deployed.

## 4 Installation of ZRGOHIJET Application

The OHI Back Office web modules are packaged in a single archive named 'ZRGOHIJET.war'. This WAR file must be deployed to WLS.

### 4.1 ZRGOHIJET Deployment











Make sure that you deploy ZRGOHIJET.war on the same Managed Server as HSL\_JUP.war. Both applications must be accessible through the same Managed Server and port number.

Deploy ZRGOHIJET.war using default settings.

Although the procedure is similar to deploying HSL and PSL services you may find it useful to look at the step-by-step instructions below.

Select 'Deployments' from the WLS console:

[Customize this table](#)

Deployments								
<a href="#">Install</a> <a href="#">Update</a> <a href="#">Delete</a>			Showing 1 to 10 of 11 <a href="#">Previous</a>   <a href="#">Next</a>					
<input type="checkbox"/>	Name ↕	State	Health	Type	Targets	Scope	Domain Partitions	Deployment Order
<input type="checkbox"/>	 HSL_AUN (v4.10)	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 HSL_AUZ (v4.9)	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 HSL_C2B (v4.21)	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 HSL_DOS (v4.1)	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 HSL_JUP (v4.2)	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 HSL_POL (v4.37)	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 HSL_REL (v4.24)	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 OHIJET_prototype	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 PSL_ACL (v4.2)	Active	✓ OK	Web Application	MS_SVLB0SPC31	Global		100
<input type="checkbox"/>	 state-management-provider-memory-rar	Active	✓ OK	Resource Adapter	MS_SVLB0SPC31, MS_SVLB0SPC32	Global		100
<a href="#">Install</a> <a href="#">Update</a> <a href="#">Delete</a>			Showing 1 to 10 of 11 <a href="#">Previous</a>   <a href="#">Next</a>					

Select 'Install' to create a new deployment.

Select 'ZRGOHIJET.war'

**Install Application Assistant**

Back Next Finish Cancel

**Locate deployment to install and prepare for deployment**

Select the file path that represents the application root directory, archive file, exploded archive directory, or application module descriptor that you want to install. You can also enter the path of the application directory or file in the Path field.

**Note:** Only valid file paths are displayed below. If you cannot find your deployment files, Upload your file(s) and/or confirm that your application contains the required deployment descriptors.

**Path:** /ol:/env/Base/DTT/ST1/ohiBase/java/ZRGOHIJET.war

**Recently Used Paths:**

- /home/llibcorv/ozq\_rcs
- /ohi/env/Base/DTT/ST1/ohiBase/java
- /ohi/env/Case/DTT/ST2/ohiCase/java
- /home/btrezina/ozq\_rcs

**Current Location:** s1c10ary.us.oracle.com / chi / envBase / DT1ST1 / ohBase / java

- ☐ PSH10053.jar
- ☐ PSH\_UTIL.jar
- ☒ HSL\_AUN.war
- ☒ HSL\_AUZ.war
- ☒ HSL\_CAB.war
- ☒ HSL\_CLA.war
- ☒ HSL\_POL.war
- ☒ HSL\_REL.war
- ☐ SIC\_ATLASSIAN\_ORACLE\_ID.jar
- ☐ SIC\_OOZWEBSERVICES.ear
- ☐ SIC\_OOZWEBSERVICES.ear
- ☐ SIC\_OOZWEBSERVICE\_END.ear
- ☐ SIC\_OOZWEBSERVICE\_ENS.ear
- ☐ SVL1001C.jar
- ☐ SVL1002C.jar
- ☐ SVL1003C.jar
- ☐ SVL1004C.jar
- ☐ SVL1005C.jar
- ☐ SVL1006C.jar
- ☐ SVL1007C.jar
- ☐ SVL1008C.jar
- ☐ SVL1009C.jar
- ☐ SVL1010C.jar
- ☐ SVLEOWS.ear
- ☐ VER\_VECCOZO\_PRT.jar
- ☒ ZRGOHIJET.war

Back Next Finish Cancel

Select to install the deployment as an application

Home > Summary of Deployments

**Install Application Assistant**

Back Next Finish Cancel

**Choose installation type and scope**

Select if the deployment should be installed as an application or library. Also decide the scope of this deployment.

The application and its components will be targeted to the same locations. This is the most common usage.

☒ **Install this deployment as an application**

Application libraries are deployments that are available for other deployments to share. Libraries should be available on all of the targets running their referencing applications.

☐ **Install this deployment as a library**

Select a scope in which you want to install the deployment.

**Scope:** Global ▾

Back Next Finish Cancel

Target the application at the managed server to which HSL\_JUP is deployed:

**Install Application Assistant**

Back Next Finish Cancel

**Select deployment targets**

Select the servers and/or clusters to which you want to deploy this application. (You can reconfigure deployment targets later).

**Available targets for ZRG0HIJET :**

Servers
<input type="checkbox"/> AS_SVL12212
<input checked="" type="checkbox"/> MS_SVLBTTST1
<input type="checkbox"/> MS_SVLBTTST2

Back Next Finish Cancel

Finish the deployment using 'DD Only' (use the application's deployment descriptors):

**Install Application Assistant**

Back Next Finish Cancel

**Optional Settings**

You can modify these settings or accept the defaults.  
\* Indicates required fields

**General**

What do you want to name this deployment?

\* Name: ZRG0HIJET

Archive Version: v4.1

Deployment Plan Version:

**Security**

What security model do you want to use with this application?

☒ DD Only: Use only roles and policies that are defined in the deployment descriptors.

☐ Custom Roles: Use roles that are defined in the Administration Console; use policies that are defined in the deployment descriptor.

☐ Custom Roles and Policies: Use only roles and policies that are defined in the Administration Console.

☐ Advanced: Use a custom model that you have configured on the realm's configuration page.

**Source Accessibility**

How should the source files be made accessible?

☒ Use the defaults defined by the deployment's targets

Recommended selection.

☐ Copy this application onto every target for me

During deployment, the files will be copied automatically to the Managed Servers to which the application is targeted.

☐ I will make the deployment accessible from the following location

Location: /home/lileberw/ozg\_rcs/ZRG0HIJET.war

Provide the location from where all targets will access this application's files. This is often a shared directory. You must ensure the application files exist in this location and that each target can reach the location.

The application is now deployed.

## 4.2 Post Installation

When the application is initially deployed, it needs to be activated.

Either activate the deployment through WLS console or restart the managed server(s) to which the application is deployed.

## 4.3 Updating the ZRG0HIJET Application

In time, more modules will be added to the ZRG0HIJET application.

When deploying a newer version of the ZRG0HIJET application, select 'Update' to update the application (ensure that the new ZRG0HIJET.war is copied to the existing location).

Alternatively, select 'Delete' to delete the existing ZRGOHIJET application and create a new deployment as described above.

## 4.4 Deployment validation

When validating the deployment, all components must be correctly installed and deployed.


Before you continue:

- verify that you have completed all steps in 'Prerequisites'.
- verify that you have deployed and started the ZRGOHIJET.war application as described in this chapter.


To verify the deployment, browse

<https://server:port/ohibo>

Example:



When you have successfully logged on with your OHI username and password, the screen should look like this:





## 5 Appendix A – Samples for HSL and PSL Properties Files

### 5.1 HSL Properties File Sample

The sample below may help you put together a PSL properties for testing.

Note:

- You will have to set your own values for the values shown in *italics*
- Do NOT set the log level to FINEST in production mode as this considerably slows down the service execution. Use ERROR instead.

```
# HSL properties sample for testing.
#
hsl.aun.authorization=NONE
hsl.aun.jndiname=HSL_BDSPC31
hsl.aun.logfile=/home/oracle/hsl.aun.log
hsl.aun.loglevel=FINEST
hsl.aun.usercontext=MANAGER
#
hsl.auz.authorization=BASIC
hsl.auz.jndiname=HSL_BDSPC31
hsl.auz.logfile=/home/oracle/hsl.auz.log
hsl.auz.loglevel=FINEST
hsl.auz.usercontext=MANAGER
#
hsl.jup.authorization=NONE
#hsl.jup.jndiname=HSL_BDSPC31
hsl.jup.jndiname=HSL_BDDEV1814
hsl.jup.logfile=/home/oracle/hsl.jup.log
hsl.jup.loglevel=FINEST
hsl.jup.usercontext=MANAGER
#
hsl.tokenvalidation.rotor=testing
```

### 5.2 PSL Properties File Sample

The sample below may help you put together a PSL properties for testing.

Note:

- You will have to set your own values for the values shown in *italics*
- Do NOT set the log level to FINEST in production mode. Use ERROR instead.
- The value for psl.tokenvalidation.authentication is a base64 encoded string. The username:password combination must refer to a valid Weblogic user which has access to the HSL\_AUZ service. You may use <https://www.base64encode.org/> to generate the base64 encoded string.

```
# PSL properties sample for testing.
#
psl.tokenvalidation.authentication=Basic cmVzdHVzZXI6b3B1bnpvcmc5OQ==
psl.tokenvalidation.url=https://ol6ohi.ohi.oracle.com:7094/HSL_AUZ/auz/v1/authorization/verify
psl.tokenvalidation.method=post
psl.tokenvalidation.bodyparam={ "method" : "#method#", "token" : "#jwt#" , "resource" : "#path#" }
psl.authorization=TOKEN
psl.usercontext.control=TOKEN
psl.usercontext.token.type=JWT
psl.usercontext.claim=prn
#
psl.acl.jndiname=HSL_BDSPC31
psl.acl.loglevel=FINEST
psl.acl.logfile=/home/oracle/psl.acl.log
```