

**Oracle® Agile Product Lifecycle
Management for Process**

Reporting User Guide

Release 6.2.4.x

F57999-01

May 2022

Copyright © 2022, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface	ix
Audience.....	ix
Variability of Installations.....	ix
Documentation Accessibility	ix
Related Documents	x
Conventions.....	x
 1 Introducing Reporting	
Reporting Options	1-1
 2 Using Queued Search Reporting	
Getting Started with Queued Search Reporting	2-1
Accessing Reporting	2-1
Using the Reporting Page	2-1
Search Field Definitions	2-1
Saving Search Criteria	2-2
Running a Report	2-4
Generating a Report	2-5
Viewing Queued Reports	2-6
Report Status	2-6
Custom Layouts	2-7
Defining a Custom Layout	2-7
Creating a New Layout	2-10
Marking a Layout as Default	2-11
Modifying a Layout	2-12
Using the Aggregated Feature	2-13
Deleting a Layout.....	2-13
 3 Using Ready Reports	
Overview	3-1
Usage Examples	3-1
Business Objects	3-2
ADMN	3-2
Component Catalog	3-2
DRL	3-2

eQ.....	3-2
GSM.....	3-2
NPD	3-3
NSM.....	3-3
PQM.....	3-3
PQS	3-3
SCRM	3-3
UGM	3-3
WFA	3-3
Assigning Roles	3-4
Accessing Ready Reports	3-4
Ready Reports Listing Page	3-5
Ready Report Details Page	3-6
Ready Report Creator Page	3-6
Summary Information Section	3-7
Search Information Section	3-7
Search Criteria Section	3-8
Additional Notes about Search Criteria	3-8
Search Results	3-9
Using Contextual Variables	3-9
Using Ready Reports in Agile PLM for Process Applications.....	3-11
Local Browser Bookmarks	3-11
Sharing with the Entire User Base	3-12
Security and Access	3-13
Security	3-13
Visibility	3-13
Site Access	3-13
Ready Report Veto Plugin	3-14
Specification Veto Plugin	3-14
Technical Documentation	3-14
Available Reference Implementations	3-14
Adjusting Report Views	3-14
Terminology	3-14
Configuration Files	3-14
Report Views Structure	3-15
Model	3-15
MandatoryProperty	3-15
SearchableProperties	3-15
DisplayColumns	3-16
ColumnInfo	3-16
Example: Adding Business Unit to Packaging Search Results	3-16
Adding New Report Views	3-18

A Ready Reports Contextual Variables

Contextual Variables	A-1
DRL	A-1
EQ	A-1

GSM.....	A-2
NPD.....	A-7
NSM.....	A-8
PQM.....	A-9
PQS	A-11
SCRM.....	A-12
UGM	A-14

B Ready Reports Models

ADMN	B-1
Custom Section	B-1
View: ExtendedSectionAttributeTemplateView	B-1
Model: Custom Sections.....	B-1
Extended Attribute	B-2
View: ExtendedAttributeView.....	B-2
Model: Extended Attributes.....	B-2
Component Catalog	B-2
Component Catalog Term.....	B-2
View: FICTermView	B-2
Model: Component Catalog Items	B-2
DRL	B-3
DRL Document	B-3
View: DocumentSearchView.....	B-3
Model: DRL Documents.....	B-3
EQ	B-4
Material EQ Request.....	B-4
View: EQMaterialRequestView	B-4
Model: Material eQuestionnaires.....	B-4
Packaging EQ Request.....	B-5
View: EQPackagingRequestView	B-5
Model: Packaging eQuestionnaires.....	B-5
Printed Packaging EQ Request--Deprecated	B-6
View: EQPrintedPackagingRequestView.....	B-6
Model: Printed Packaging eQuestionnaires	B-6
Product EQ Request	B-7
View: EQProductRequestView	B-7
Model: Product eQuestionnaires.....	B-7
Trade EQ Request	B-8
View: EQTradeRequestView.....	B-8
Model: Trade eQuestionnaires	B-8
GSM	B-9
Delivered Material Packing Specification	B-9
View: SpecSummaryView.....	B-9
Model: Delivered Material Packing Specifications	B-9
Equipment Specification	B-11
View: SpecSummaryView.....	B-11
Model: Equipment Specifications.....	B-11

Formulation Specification.....	B-13
View: SpecSummaryView.....	B-13
Model: Formulation Specifications.....	B-13
Global Succession Request	B-15
View: SuccessionRequestView	B-15
Model: Global Succession Requests.....	B-15
GSM Activity.....	B-16
View: SpecSummaryView.....	B-16
Model: GSM Activities.....	B-16
Labeling Specification	B-17
View: SpecSummaryView.....	B-17
Model: Labeling Specifications	B-17
LIO Profile	B-19
View: SpecSummaryView.....	B-19
Model: LIO Profiles.....	B-19
Master Specification	B-20
View: SpecSummaryView.....	B-20
Model: Master Specifications	B-20
Material Specification	B-21
View: SpecSummaryView.....	B-21
Model: Material Specifications.....	B-21
Menu Item Specification.....	B-25
View: SpecSummaryView.....	B-25
Model: Menu Item Specifications.....	B-25
Nutrient Profile	B-28
View: SpecSummaryView.....	B-28
Model: Nutrient Profiles	B-28
Packaging Specification.....	B-31
View: SpecSummaryView.....	B-31
Model: Packaging Specifications.....	B-31
Packing Config Specification.....	B-33
View: SpecSummaryView.....	B-33
Model: Packing Configuration Specifications	B-33
Printed Packaging Specification--Deprecated	B-35
View: SpecSummaryView.....	B-35
Model: Printed Packaging Specifications	B-35
Product Specification	B-37
View: SpecSummaryView.....	B-37
Model: Product Specifications.....	B-37
Testing Protocol	B-40
View: SpecSummaryView.....	B-40
Model: Testing Protocols.....	B-40
Trade Specification	B-42
View: SpecSummaryView.....	B-42
Model: Trade Specifications	B-42
NPD.....	B-45
Innovations/Sales Pipeline	B-45

View: NPDIdeaView	B-45
Model: Ideas.....	B-45
Project	B-45
View: ProjectView	B-45
Model: Projects	B-45
Strategic Brief	B-46
View: StrategicBriefView.....	B-46
Model: Strategic Briefs	B-46
NSM	B-47
Nutrient Analysis	B-47
View: NutrientAnalysisMainView	B-47
Model: Nutrient Analysis.....	B-47
Nutrient Composite	B-48
View: NutrientCompositeView	B-48
Model: Nutrient Composites.....	B-48
PQM	B-48
Action.....	B-48
View: PQMActionView.....	B-48
Model: PQM Actions.....	B-48
Audit.....	B-50
View: PQMAuditView	B-50
Model: PQM Audits.....	B-50
Issue	B-52
View: PQMIssueView	B-52
Model: PQM Issues.....	B-52
PQS	B-54
Lot Sample	B-54
View: LotSampleView.....	B-54
Model: Samples	B-54
Session	B-55
View: SessionView	B-55
Model: Sessions	B-55
Scorecard.....	B-55
View: ScorecardView	B-55
Model: Scorecards	B-55
SCRM	B-56
Company	B-56
View: CompanyMainSearchViewSingleSelectAlias.....	B-56
Model: Companies	B-56
Company/Facility SDM	B-57
View: ManagedDocumentMultiSelect.....	B-57
Model: Supporting Docs - Company/Facility	B-57
Facility	B-58
View: FacilityMainSearchViewSingleSelect.....	B-58
Model: Facilities	B-58
Contact	B-59
View: ContactProfileView	B-59

Model: Contact Profiles	B-59
Non-Spec Sourcing Approval	B-60
View: SourcingApprovalNonSpecView	B-60
Model: Non-Spec Sourcing Approvals	B-60
Spec Related Sourcing Approval	B-61
View: SourcingApprovalView	B-61
Model: Spec-Related Sourcing Approvals	B-61
Non-Spec Sourcing Approval SDM	B-62
View: ManagedDocumentMultiSelect	B-62
Model: Supporting Docs - Non-Spec SAC	B-62
Spec Sourcing Approval SDM	B-64
View: ManagedDocumentMultiSelect	B-64
Model: Supporting Docs - Spec-Related SAC	B-64
UGM	B-65
Group	B-65
View: GroupView	B-65
Model: Group Profiles	B-65
User	B-66
View: UserView	B-66
Model: User Profiles	B-66
WFA	B-67
GSM Workflow Process Template	B-67
View: WorkflowProcessTemplateView	B-67
Model: GSM Workflows	B-67
PQM Workflow Process Template	B-67
View: WorkflowProcessTemplateView	B-67
Model: PQM Workflows	B-67
SCRM Workflow Process Template	B-67
View: WorkflowProcessTemplateView	B-67
Model: SCRM Workflows	B-67

C Best Practices

When to use Searching, Reporting, or Printing	C-1
Searching vs Reporting vs Printing Scenarios	C-1
Reporting Tools Details	C-2
Notes	C-2

Preface

The *Agile Product Lifecycle Management for Process Reporting User Guide* explains how to use the Reporting (RPT) application, in conjunction with Ready Reports, Printing and Custom Reports, to provide reporting capability for data in the Global Specification Management (GSM), eQuestionnaire (eQ), Product Quality Management (PQM), User Group Management (UGM), New Product Development (NPD), and Supply Chain Relationship Management (SCRM) applications, as well as custom data.

This Preface contains these topics:

- [Audience](#)
- [Variability of Installations](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Conventions](#)

Audience

This guide is intended for end users who are responsible for creating and managing information in and/or reporting on information in Agile Product Lifecycle Management (PLM) for Process. Information about administering the system resides in the *Agile Product Lifecycle Management for Process Administrator User Guide*.

Variability of Installations

Descriptions and illustrations of the Agile PLM for Process user interface included in this manual may not match your installation. The user interface of Agile PLM for Process applications and the features included can vary greatly depending on such variables as:

- Which applications your organization has purchased and installed
- Configuration settings that may turn features off or on
- Customization specific to your organization
- Security settings as they apply to the system and your user account

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

For more information, see the following documents in the Oracle Agile PLM for Process documentation set:

- *Agile Product Lifecycle Management for Process Getting Started Guide*
- *Agile Product Lifecycle Management for Process Global Specification Management User Guide*
- *Agile Product Lifecycle Management for Process Supply Chain Relationship Management User Guide*
- *Agile Product Lifecycle Management for Process eQuestionnaire User Guide*
- *Agile Product Lifecycle Management for Process Product Quality Management User Guide*
- *Agile Product Lifecycle Management for Process User Group Management User Guide*
- *Agile Product Lifecycle Management for Process New Product Development User Guide*
- *Agile Product Lifecycle Management for Process Security Configuration Guide*
- *Agile Product Lifecycle Management for Process Configuration Guide*
- *Agile Product Lifecycle Management for Process Release Notes*.
- *Agile Product Lifecycle Management for Process Reporting Guide* (reporting pack) for custom report configuration
- *Agile Product Lifecycle Management for Process Navigation Configuration Guide*

These and other documentation are posted on Oracle Technology Network (OTN) at this location:

<https://www.oracle.com/technical-resources/documentation/agile.html#plmprocess>

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Introducing Reporting

This chapter provides an overview of Oracle Agile Product Lifecycle Management (PLM) for Process Reporting and includes the following topic:

- [Reporting Options](#)

Reporting Options

Oracle Agile Product Lifecycle Management for Process offers several ways to access and report on data.

- **Queued Reporting**—Queued Reporting is a method of accessing data through an object model-based queued searches tool that allows users to define their own search criteria and result definitions. This allows for queued searches reporting against much of the data in Global Specification Management (GSM), Product Quality Management (PQM), and Supply Chain Relationship Management (SCRM). One of the main use cases for queued searches is to overcome the 500 search result limit of EQT searches. See [Chapter 2, "Using Queued Search Reporting"](#) for more information on this option.
- **Ready Reports**—Ready Reports are saved entity query tool (EQT) searches that are available for business objects in Agile PLM for Process. Ready reports allow users to quickly access data they need in the context they need it. This contextual access can also be used to access data across Agile PLM for Process modules. For example, a user can find all companies that could potentially source a material directly from the GSM material specification. Since ready reports has its own administration interface, reports can be created and managed by business users. No technical report writing skills are necessary.

Reports can be saved as local browser bookmarks or individually shared with other users. Reports can even be shared to the entire user community by adding new navigation items throughout Agile PLM for Process applications. Refer to the *Agile Product Lifecycle Management for Process Navigation Configuration Guide* for more information. This method is described in [Chapter 3, "Using Ready Reports"](#).

- **Custom Reports**—You can also configure custom reports for the Agile Product Lifecycle Management (PLM) for Process Reporting module. All reports will use a reporting service like Oracle BI Publisher or SQL Server Reporting Services. However, PLM for Process allows you to execute these reports in different ways. Depending on your usability needs, environment requirements and security requirements around parameters, either choice is valid.

Custom Report Configuration—This approach allows you to execute the report from within PLM for Process. You can use the PLM for Process custom report UI interface and the report can be returned to the user in PDF format. While this involves more complexity during the configuration of the report, this keeps the user within the PLM for Process application and security filtering can be applied to report parameters.

For example, if a specification is required as a parameter, PLM for Process UI tools can be used to filter the user's available choices using core application security rules like GSM BU Security. You would also use this approach when you don't want to set up user access in the reporting application. More information around configuring this approach can be found in the Custom Report Configuration Section of the *Agile Product Lifecycle Management for Process Reporting Guide*.

BI Publisher Integration—This approach allows the user to execute reports within a reporting application. We recommend Oracle BI Publisher and offer out of the box reports that can be leveraged. If the user has appropriate roles in BI publisher they can customize the report layouts as well as create new reports based on the provided data models. More information around configuring this approach can be found in the BI Publisher Integration section of the *Agile Product Lifecycle Management for Process Reporting Guide*.

- **Printing**—PLM for Process also allows specification print views directly from GSM. The appearance of these print outs is configurable. See the *Agile Product Lifecycle Management for Process Print Extensibility Overview Guide* for more information.

Refer to [Appendix C, "Best Practices"](#) for more information on common scenarios that might help you determine which reporting method best suits your needs.

Using Queued Search Reporting

This chapter describes the capabilities and applied uses of the Reporting product. It includes the following topics:

- [Getting Started with Queued Search Reporting](#)
- [Custom Layouts](#)

Getting Started with Queued Search Reporting

The Reporting application enables you to create queued search reports, create reporting layouts, and run customized, third-party reports.

Accessing Reporting

To access Reporting, select **RPT** from the Applications menu.

Using the Reporting Page



[Figure 2–1](#) shows the basic Reporting search page, which consists of fields that are defined below.

Figure 2–1 Reporting page, Queued Searches

The screenshot displays the 'Queued Searching' interface. At the top, there is a 'Search Source' dropdown menu set to 'Material Specifications'. Below this is a section for 'Search Criteria' with a 'Load' button, a 'Save' button, and a 'Custom Layout' dropdown menu set to 'STANDARD'. The 'Search Criteria' section includes two dropdown menus: 'Spec Name' and 'Contains', followed by a text input field. Below these fields is a link for 'Additional Search Criteria...'. At the bottom right of the search criteria section are three buttons: 'Reset', 'Search', and 'Generate Report'.

Search Field Definitions

- Object name—Displays a drop-down list of object types that are the information the report will be performed on.
- Key field list—Displays a drop-down list of criteria based on the selected object type.
- Operator—Displays a drop-down list of operators based on the criteria that you choose in the key field list. Examples include Equals, Not Equals, Contains, and Starts With.

- **Search term**—Further define your report by entering specific text or numbers related to the first two report fields. If this field is preceded by an add data icon, click the icon to view a dialog box with available choices.
- () **more criteria**—Enables you to display another row of search criteria fields. This acts as an "and" function, which narrows your search results.
- () **less criteria**—Removes a row of search criteria fields. Displays once the more criteria option has been selected.
- **Show Per Page**—Sets the number of search results to display at one time.

The Reporting search page includes the following buttons and links:


- **Load**—Loads a saved search.
- **Save**—Saves search criteria in a reusable library. Use this option if you use certain search criteria often.
- **Recent Items**—Displays a list of recent search items.
- **Additional Search Criteria**—Displays a dialog box where you can specify extended attributes or custom sections as search criteria. The available choices are defined by the object you selected in the Object name field. Refer to the *Oracle Agile Product Lifecycle Management for Process Getting Started Guide* for more information about searching for custom data.
- **Reset**—Clears all search criteria fields and results.
- **Search**—Displays your search results. The number of search results returned is limited to 500 entries. If your report generates more than 500 matches, the report must be generated and queued up. See "[Viewing Queued Reports](#)" on page 2-6 for more information.
- **Generate Report**—Generates your report results.
- **Custom Layout**—Defines the report layout. Custom layouts are explained in greater detail on page 2-7.
- **Export**—Writes the search results to an Excel file and displays a dialog box for downloading or viewing the exported file.

Saving Search Criteria

Once you have entered your search criteria, you can save those criteria for later use. This feature can be a great help when search criteria become very complex.

To save search criteria:

1. Enter your search criteria.
2. Click **Save**. A Save Search Criteria As dialog box displays, as shown in [Figure 2-2](#).

Figure 2–2 The Save Search Criteria As dialog box

3. Type a descriptive name for the search criteria to save and click **Save**.

After you have saved one or more searches, you can easily retrieve saved search criteria.

Note: Only the search criteria is saved; the contents of the report and the custom layout are not saved.

To retrieve a saved search:

1. On any search form, click **Load** and then select **Load Saved Search** from the drop-down list. A dialog box displays, showing a list of all of the searches that you have saved, as shown in Figure 2–3.

Figure 2–3 Saved searches dialog box

2. Click the linked name of the saved search to load the criteria. Reporting closes the dialog box and loads the saved search criteria into the main search page.

Running a Report

You can create queued search reports based on the following Global Specification Management (GSM) specifications/objects:

- . Material Specifications
- . Menu Item Specifications
- . Packaging Material Specifications
- . Printed Packaging Specifications (Deprecated)
- . Product Specifications
- . Trade Specifications
- . Packing Configuration Specifications
- . Delivered Material Packing Specifications
- . Equipment Specifications
- . Formulation Specifications
- . Labeling Specifications
- . Master Specifications
- . Nutrient Profiles
- . Activities
- . LIO Profiles
- . Component Catalog
- . Global Successions
- . Smart Issue Requests
- . Testing Protocols

You can also create queued search reports based on the following Supply Chain Relationship Management (SCRM) entities:

- . Facilities
- . Companies
- . Spec Related Sourcing Approvals
- . Non-Spec Related Sourcing Approvals
- . Supplier Document Management
- . SAC Document Management
- . Non-Spec SAC Document Management

Queued search reports can also be based on the following eQuestionnaires (eQ) types:

- . Material Questionnaires
- . Packaging Questionnaires
- . Printed Packaging Questionnaires (Deprecated)
- . Product Questionnaires
- . Trade Questionnaires

As well as the following Product Quality Management (PQM) objects:

- PQM Actions
- PQM Audits
- PQM Issues

and Nutrition Surveillance Management (NSM) objects:

- Nutrient Analyses
- Nutrient Composites

You can create queued search reports based on the following ADMN's Custom Data:

- Custom Sections
- Extended Attributes

As well as New Product Development's (NPD) objects:

- Innovations/Sales Pipelines
- Projects
- Strategic Briefs

Document Repository's (DRL) DRL Documents,

and User Group Management's (UGM):

- Users
- Groups

Report attributes vary depending on the business entity as well. For example, to run a report for a facility, the report attributes are fields within a facility profile, including (but not limited to):

- Facility name
- Company name
- Sourcing taxonomy


Specify which attributes to include on a report using Custom Layout feature, as described on "[Custom Layouts](#)" on page 2-7.

To perform a report, select **RPT > Queued Searches > Queued Searching** from the left navigation panel. The Reporting search page displays. Select a business entity from the **Object** name drop-down list, then specify search criteria values in the search fields. Click **Search**. The search results table displays all data objects matching the search criteria, in ascending order by default.

Generating a Report

Click **Generate Report** to submit reports to the report generation queue. The **Generate Report** button is found on the Reporting page, as seen in [Figure 2-1](#) on page 2-1. When a report request in the queue is processed, it will be created or saved in Excel format so that you can click the presented link to download, open, or save it. The report can also be saved in a comma delimited format.

After you click **Generate Report**, a dialog box is displayed, as shown in [Figure 2-4](#). Fill in the **Report Name** (required) and **Description** fields, then click **Save**.


Figure 2–4 Generate Report dialog box


The dialog box titled "Generate Report" has a "Save" button and a "Cancel" button in the top right corner. It contains two text input fields. The first field is labeled "Report Name:" and contains the text "Spec name contains BBQ". The second field is labeled "Description:" and contains the text "BBQ specs for the Business Unit of North America". Both fields have a small upward-pointing arrow icon on the right side.



When you click **Save**, the report is added to a queue for processing offline.

Viewing Queued Reports

To view reports that have been queued, click **RPT > Queued Searches > Search Queue** from left navigation panel. The Reports Queue page, shown in [Figure 2–5](#), displays report details. The Status column displays the status of the report as indicated by a red, amber, or green bar.

Figure 2–5 Reports Queue page


The Reports Queue page has a header bar with a database icon and the title "Reports Queue". Below the header is a table titled "Report Details". The table has six columns: Name, Description, Date Submitted, Start Date, Date Completed, and Status. There is one row of data. The Status column contains a yellow bar and a red 'X' icon. Below the table is a legend with three colored squares: red for "Submitted", yellow for "In Progress", and green for "Completed".

Name	Description	Date Submitted	Start Date	Date Completed	Status
facilities contain west	Our facilities in western region	Jun 11, 2014 8:19:59 PM	Jun 11, 2014 8:20:21 PM		 

Submitted In Progress Completed

Report Status

The **Status** column displays one of the following statuses:

Red status means that the report request has been submitted but the report is not yet being generated.

Amber status means that the report is currently being generated.

Green status means that the report is ready. When the status turns green, the name of the report becomes a link. Clicking the link gives you the option to either view the report or save it. When the report is ready, the person who generated the report receives an email notification.

Reports that are run in the Reporting application are not limited in size like search results and can sometimes be very large. Reports are run in order of submission to the reporting queue.

Custom Layouts

As previously mentioned, the setting you provide for custom layouts determines which fields are displayed on the report. Select a layout based on the purpose of the report. Access the User Customized Layout page by either:

- Clicking the add data icon next to the Custom Layout drop-down on the Reporting search page. Refer to [Figure 2–1](#), on page 2-1 for more information.

Or

- Select **RPT > Queued Searches > Custom Layouts** from the left navigation panel.

Defining a Custom Layout

As [Figure 2–6](#) shows, the User Customized Layout page displays all the object types on which queued searches can be created. Select an object type, and then click the edit icon to display all the defined layouts for that object type. [Figure 2–7](#) shows all the custom layouts for the Facilities object type. In this example, “Summary View” is the default layout that will be displayed when you run a report on Facilities.

Figure 2–6 User Customized Layouts page




Custom Layouts



User Customized Layouts







Search Type
 Activities
 Company
 Component Catalog
 Custom Sections
 Delivered Material Packing Specifications
 DRL Documents
 Equipment Specifications
 Extended Attributes
 Facility
 Formulation Specifications
 Global Successions
 Groups
 Innovations/Sales Pipelines
 Labeling Specifications
 LIO Profiles
 Master Specifications
 Material Questionnaires
 Material Specifications
 Menu Item Specifications
 Non-Spec Related Sourcing Approval
 Non-Spec SAC Document Management
 Nutrient Analysis
 Nutrient Composite
 Nutrient Profile
 Packaging Material Specifications
 Packaging Questionnaires
 Packing Configuration Specifications
 PQM Actions
 PQM Audits
 PQM Issues
 Printed Packaging Questionnaires
 Printed Packaging Specification
 Product Questionnaires
 Product Specifications
 Projects
 SAC Document Management
 Smart Issue Requests
 Spec Related Sourcing Approval
 Strategic Briefs
 Supplier Document Management
Testing Protocols
Trade Questionnaires
Trade Specifications
Users



Figure 2–7 Available layouts for Facility object type; “Summary View” is the default layout



Custom Layouts

▼
 User Customized Layouts

	Search Type		
	Facility		
	Material Specifications		
	Menu Item Specifications		
	Packaging Material Specifications		
	Product Specifications		
	Supplier Document Management		
	Trade Specifications		

	Default	Name	Created
	<input type="radio"/>	-- STANDARD --	
	<input type="radio"/>	Sourcing Category Report	Jun 17, 2014 1:58:51 PM
	<input checked="" type="radio"/>	Summary View	Jun 17, 2014 2:00:21 PM

Add New

Creating a New Layout

Click **Add New** to create a new layout. Next, type the name of the layout in the **Layout Name** field (required). Remove the fields not required from the Columns section. For details, refer to "Modifying a Layout" on page 2-12.

Figure 2–8 shows the new layout page for Facility.

Figure 2–8 Facility page

(Facility)
Custom Layout

Summary

Layout Name:

Date Created: Mar 20, 2015

Customization Of: Facility

Columns

	Column Name	Caption	Aggregated		
	Facility #		No		
	Facility Name		No		
	Company Name		No		
	City		No		
	State/Province		No		
	Country Name		No		

Add New **Sort Order**

Marking a Layout as Default

Each object type has a default, out-of-the box layout called "--STANDARD--". These standard layouts will be used if you do not create custom layouts for the object types.

Figure 2–9 Marking a default layout

Custom Layouts

▼ User Customized Layouts

Search Type

Facility

Material Specifications

Menu Item Specifications

Packaging Material Specifications

Product Specifications

Supplier Document Management

Trade Specifications

	Default	Name	Created
	<input checked="" type="radio"/>	-- STANDARD --	
	<input type="radio"/>	Rollup BUs	Jun 17, 2014 2:03:57 PM

Add New

On the Reporting page, the default custom layout is marked with an asterisk, as shown in Figure 2–10.

Figure 2–10 Custom Layout with asterisk

Queued Searching

Search Source: Facilities

▼ Search Criteria ▼ Load Save Custom Layout *Summart view + Recent Items

--- ▼

[Additional Search Criteria...](#)

Reset Search Generate Report

Modifying a Layout

You can modify only the user-defined report layouts.

To modify a custom layout:

1. In the User Customized Layouts section, click the linked field name of the layout that you want to modify. RPT displays the layout page for the selected item. The Columns section displays all the columns that are in the current layout.

Figure 2–11 Modifying a layout for Facility, Summary View

(Facility)
Custom Layout

Summary

Layout Name: Summary View

Date Created: Mar 20, 2015

Customization Of: Facility

Columns


	Column Name	Caption	Aggregated		
	Facility #		No		
	Facility Name		No		
	Company Name		No		
	City		No		
	State/Province		No		
	Country Name		No		

Add New Sort Order

2. To edit a column, click the edit icon in the left most column next to the column name.

To customize the column name, provide a name in the **Caption** field.

To change the position of the columns, click **Sort Order**. In the Sort Order dialog box to assign sort priority and direction, and then click **Done**.

Figure 2–12 Sort Order dialog


	Column Name	Sort Priority	Direction
1	Facility #	- ▼	Ascending ▼
2	Facility Name	- ▼	Ascending ▼
3	Company Name	- ▼	Ascending ▼
4	City	- ▼	Ascending ▼
5	State/Province	- ▼	Ascending ▼
6	Country Name	- ▼	Ascending ▼

3. To remove a column, click the edit icon in the leftmost column next to the column name. If the column is removable, the delete icon displays in the rightmost column. Clicking the delete icon removes the column from the layout.
4. Click **Save**.

To add new fields to a layout:

1. Click **Add New** at the bottom of the page. A dialog box displays all the fields that you can add to the layout.
2. Select one or more fields.
3. Click **Done**.
4. Click **Save**.

Using the Aggregated Feature

As seen above in [Figure 2–11](#), the layout page contains the Aggregated column. For some columns you can use the aggregated feature to combine multiple data results in a reporting cell separated by a comma “,”, semi-colon “;” or a new line. By default, the feature is set to “No”.

Deleting a Layout

You can delete only the user-defined report layouts.

To delete a layout:

1. Click **RPT > Queued Searches > Custom Layouts** from the left hand navigation panel. The User Customized Layouts page is displayed.
2. Select a business object. Custom layouts for the business object are displayed at the bottom of the page, as shown in [Figure 2–13](#).

Figure 2–13 User Customized Layout page



Custom Layouts

▼ User Customized Layouts

Search Type	
Facility	
	Material Specifications
	Menu Item Specifications
	Packaging Material Specifications
	Product Specifications
	Supplier Document Management
	Trade Specifications

	Default	Name	Created	
	<input type="radio"/>	-- STANDARD --		
	<input type="radio"/>	Sourcing Category Report	Jun 17, 2014 1:58:51 PM	
	<input checked="" type="radio"/>	Summary View	Jun 17, 2014 2:00:21 PM	

Add New

3. Click the edit icon in the left most column next to the layout you want to delete. A delete icon displays in the right most column. In Figure 2–13 above, the Sourcing Category Report row is in edit mode.
4. Click the delete icon to delete the layout. The Reporting application displays a dialog box prompting you to confirm the deletion.
5. Click **OK** to delete the layout.

Using Ready Reports

This chapter describes how to use the Ready Reports feature in Agile PLM for Process and includes the following topics:

- Overview
- Assigning Roles
- Assigning Roles
- Accessing Ready Reports
- Ready Reports Listing Page
- Ready Report Details Page
- Ready Report Creator Page
- Using Contextual Variables
- Using Ready Reports in Agile PLM for Process Applications
- Security and Access
- Adjusting Report Views

Overview

Ready Reports allow users to quickly access data they need in the context they need it. Ready reports are saved entity query tool (EQT) searches that are available for business objects in Agile PLM for Process. Since ready reports has its own administration interface, reports can be created and managed by business users. No technical report writing skills are necessary.

Reports can be saved as local browser bookmarks or individually shared with other users. Reports can even be shared to the entire user community by adding new navigation items throughout Agile PLM for Process applications. Refer to the *Agile Product Lifecycle Management for Process Navigation Configuration Guide* for more information.

Usage Examples

The possibilities around how you use ready reports are virtually endless. Here are a few common use cases that can be accomplished with ready reports.

1. Find all finished goods with the allergen of X, created in the last 90 days.
2. Show me all packaging specifications that will be effective in the next 20 days.
3. Find all completed recalls performed in the last year.
4. Show all supplier documents associated to this material specification.

5. Find all facility audits that are due in the next 120 days.
6. Find all companies that could potentially source this material.
7. Show me all raw materials that are currently owned by Employee X.
8. Find all NPD projects in stage 2, 3 or 4 slotted for plant X.
9. Find all PQS sessions performed in the last 10 days at this location.

Business Objects

Ready reports are available for the following business objects:

ADMN

- . Custom section
- . Extended attribute

Component Catalog

- . Component Catalog term

DRL

- . DRL document

eQ

- . Material eQuestionnaire
- . Packaging eQuestionnaire
- . Printed packaging eQuestionnaire (Deprecated)
- . Product eQuestionnaire
- . Trade eQuestionnaire

GSM

- . Delivered material packing specification
- . Equipment specification
- . Formulation specification
- . Global succession request
- . GSM activity
- . Labeling specification
- . LIO profile
- . Master specification
- . Material specification
- . Menu Item specification
- . Nutrient profile
- . Packaging specification
- . Packing configuration specification
- . Printed packaging specification (Deprecated)

- . Product specification
- . Testing protocol
- . Trade specification

NPD

- . Innovations/sales pipeline
- . Project
- . Strategic brief

NSM

- . Nutrient analysis
- . Nutrient composite

PQM

- . Action
- . Audit
- . Issue

PQS

- . Lot sample
- . Session
- . Scorecard

SCRM

- . Company
- . Company/facility SDM
- . Facility
- . Non specification-related sourcing approval
- . Non specification-related sourcing approval SDM
- . Specification-related sourcing approval
- . Specification-related sourcing approval SDM
- . Contact profile

UGM

- . Group
- . User

WFA

- . GSM workflow process template
- . PQM workflow process template
- . SCRM workflow process template

Assigning Roles

Two roles exist for ready reports. The user must have one of these roles to access the ready reports administration application. Roles can be added using the UGM application.

[READY_REPORT_ADMIN]—This role allows a user to access the ready reports administration application. This user can create ready reports as well as edit reports they originated.

[READY_REPORT_SUPER_ADMIN]—This role allows everything READY_REPORT_ADMIN allows however this role allows the user to adjust the Max Results field. Editing the Max Results field could greatly affect performance so this role should be reserved for a more technical administrator.

Accessing Ready Reports

Once a ready report is installed, the administrator accesses them by clicking **Ready Reports** in the top menu bar or in the left navigation panel of the application.

Figure 3–1 Ready Reports option, top menu bar
























Figure 3–2 Ready Reports option, left navigation panel



Choosing these options shows the Ready Reports listing page, which lists saved ready reports and is used to create new reports, shown below.

Ready Reports Listing Page

Figure 3-3 Ready Reports listing page

Ready Reports			
	Report ID #	Report Name	
11	 1293	Supplier Documents - Expire Next Month	
12	 1291	Material Questionnaires - Returned This Week	
13	 1290	Supplier Documents - Expire in 2 weeks	
14	 1289	Project - Prototypes Project Blue	
15	 1288	Project - Created Yesterday	
16	 1287	Project - Prototypes Sunny Days	
17	 1286	Supplier Documents	
18	 1285	Prototypes Assigned to this Project	
19	 1282	Approved formulations where this material is used	
20	 1281	Where Used-Trade Spec	

10 ▼ ◀ 1... 1 2 3 4 ...4 ▶

- To preview a report, click the view details icon.
- To edit a report, click anywhere in the corresponding row. The Ready Reports Details page is displayed, as shown below.
- To delete a report, click the delete icon. You will be prompted to confirm the deletion; click **OK** to delete the report, or **Cancel** to cancel.
- To create a new report, click the create new icon or select **New** from the action menu. The Ready Reports Creator Page is displayed. Its use is described on "[Ready Report Creator Page](#)" on page 3-6.

Ready Report Details Page

This page displays when the administrator selects a report from the Ready Reports listing page. The report opens in edit mode.

Figure 3–4 Ready Report details page

The screenshot shows the 'Ready Report' interface for a report titled 'Supplier Documents - Expire in 30 days (1227)'. The interface is divided into three main sections: Summary Information, Search Information, and Search Criteria.

- Summary Information:** This section contains fields for Report Name (Supplier Documents - Expire in 30 days), Originator (Jones, Sarah), Report ID (1227), Report URL (http://slc05dhj.us.oracle.com/ReadyReports/ReadyReports.aspx?pkid=1108018f0103-c39e-4999-98e8-017b011520ae), Max Results (500), and Hide Criteria (unchecked).
- Search Information:** This section contains fields for Target Object (Company) and Report View (CompanyMainSearchViewSingleSelectAlias).
- Search Criteria:** This section contains a field for Company Name (Company Name), a dropdown for Contains, and a text input field for the search criteria. There are also buttons for Reset and Preview, and a link for Additional Search Criteria...

Ready Report Creator Page

This page displays when the user creates a ready report by selecting the **New** menu option or the create new icon. This page allows users to build a ready report. Results can be previewed by clicking **Preview**.

Note: If the report is using active object, the Preview button will not display search results. Instead a message is displayed indicating search results are not available.

Figure 3–5 Ready Report Creator page

The screenshot shows the 'Ready Report Creator' interface. At the top, there is a header with a magnifying glass icon, the text '(4308)', and 'Ready Report'. Below this are three main sections:

- Summary Information:** Contains fields for 'Report Name' (a text input), 'Originator' (displayed as 'Jones, Sarah'), 'Report ID' (displayed as '4308'), 'Report URL' (displayed as 'Not Currently Available'), 'Max Results' (a text input with '500' and a note '(Max Results over 500 require a performance evaluation)'), and 'Hide Criteria' (a checkbox).
- Search Information:** Contains 'Target Object' (a dropdown menu with 'Company' selected) and 'Report View' (a dropdown menu with 'CompanyMainSearchViewSingleSelectAlias' selected).
- Search Criteria:** Includes a 'Customize' link, a search criterion 'Company Name' with a dropdown, an operator 'Contains' with a dropdown, and a text input field. Below this is a link 'Additional Search Criteria...', and at the bottom right are 'Reset' and 'Preview' buttons.

The ready report page is comprised of the Summary Information section, Search Information section, and Search Criteria section.

Summary Information Section

This section defines the ready report. Key fields include:

Report Name—Name associated with the ready report. This will be used as the title for the popup where the ready report is displayed. This is a required field.

Originator—System-assigned user who created the report. Only the originator can view and edit this report in the ready reports administration application.

Report ID—System-assigned ID.

Report URL—The actual URL to be used to access the ready report. This could be used on its own or included as part of a navigation extension. For more information on the navigation extensions, please refer to the *Agile Product Lifecycle Management for Process Navigation Configuration Guide*.

Note: When active object contextual variables are included in criteria, this URL has to be accessed using a navigation extension.

Max Results—Maximum number of search results returned. This field is visible to users with the [READY_REPORT_SUPER_ADMIN] role. Note: Use caution when adjusting this field beyond 500 items; doing so could have large performance implications.

Hide Criteria—If checked, search criteria are hidden in consumed ready reports. This allows you to lock down a ready report criteria set. When it is essential that end users are not allowed to adjust the ready report results, then it should be hidden.

Search Information Section

This section contains two fields that define the search:

Target Object—Target object defines the object the search will be performed against. This could be any of the objects defined in ["Overview"](#) on page 3-1.

Report View—Defines the fields that can be used in the search criteria as well as the search result columns. Views and available fields are detailed in the section ["Adjusting Report Views"](#) on page 3-14.

Search Criteria Section

The search criteria define the actual data that will be used to determine the report results. Criteria available will depend on the report view that is selected. There are two types of criteria that can be added as search criteria:

- **Manual Criteria**—The ready report itself declares the search item. The search item is manually saved by the ready report administrator. For example, Classification equals “Critical”. Critical was manually placed by the ready report administrator and will always be “Critical” no matter where the ready report is executed from. See below for more information on using the search criteria tool.
- **Contextual Criteria**—When using contextual criteria, the object the user is on when executing the ready report will decide the search item. For example, assume the user is on a material specification with the classification of “Active Ingredient.” When the user executes the ready report from that material specification, the criteria will be Classification equals “Active Ingredient.” If the user was on a material specification with a classification of “Critical,” then the criteria would use “Critical” as the search item. Some contextual fields could contain multiple selections like preferred cross reference. If the field contains multiple selections the contextual value may remain blank. See the ["Using Contextual Variables"](#) on page 3-9 for more information about the available contextual variables.

To find an object using the search page, set search criteria as you normally would, click **Search**, and view returned results.

The search page includes the following buttons:

Reset—Clears all search criteria fields and results.

Preview—Previews your search results including the Search Results section in a pop-up window. If the search includes an active object contextual variable, clicking this button returns an error message.

The more criteria icon displays to the right of the search term field. When clicked, more criteria creates another row of the main three search fields. You can use additional rows to enter additional search parameters. For example, you can search for all specification names that contain “Milk” that are in the “Approved” status.

This less criteria icon appears when additional search rows are added using the more criteria icon.

Additional buttons appear to the right of the search term field if contextual variables are available, as described in ["Using Contextual Variables"](#) on page 3-9.

Additional Notes about Search Criteria

1. At this time “blind” searches, where search criteria are empty, are not allowed. While the system allows you to save a blind search, when the search is run, an error is returned stating no search criteria were defined.
2. When searching using only additional search criteria, you must include a wildcard search in the main search criteria section. For example, Spec Name Contains %, then the additional search criteria for the extended attribute, breakdown item, or custom section.

3. The maximum number of criteria rows is 10, unless you are using relative dates. Relative dates count as 2 rows, so the maximum number of relative date fields without other criteria would be 5. If other criteria are defined, the number of date fields will vary. For example, if you have 8 other fields defined, you would only be able to use one relative date.

Search Results

The search results show the actual data that will be returned from the search that was created. Search result columns are determined by the report view. If the search includes an active object contextual variable, an error message is returned instead of results.

After completing the fields above, click **Save** or **Save & Close** to save the report.

Using Contextual Variables

Ready reports allow you to use contextual variables. This means a ready report can use the user's context, location in the application, or date as search criteria. For example, a user can be on a material specification and run a ready report that finds all formulation specifications that use that material specification as an input that they are the owner of that are effective in the next 30 days.

Note: Contextual Variables that pull data from objects in other applications will not work for PQM object reports when PQM is configured to use a different database than the rest of the PLM for Process applications. PQM could also be set up to use a 3rd party applications instead of GSM, SCRM and NPD. Contextual variables that pull data from those areas that are configured to use third party applications will not work.

Figure 3–6 Sample consumed ready report, delivered material specification

Delivered Material - Current Workflow Owner - Active Object
Ready Report

Search Criteria Load Save

Current Workflow Owner Equals + Steve Smith

Reset Search

Spec #	Spec Name	Status	Category	Supersedes
5077481-001	Corrugated Case Pack with Poly Liner	Developmental	Cardboard and Paper » Primary » * No Category Available	
5077514-001	Wax Lined Boxes	Draft	Multi Material » Primary » * No Category Available	
5077516-001	Shipping Carton	Draft	Cardboard and Paper » Primary » * No Category Available	

There are three categories of contextual variables available:

- **Object**—Allows you to use values from fields on an active object as input to the search criteria. For example, “Show me all supplier documents associated to this material.” From a material or packaging specification the ready report can find all specification-related sourcing approval documents associated to the active specification the user is on.
- **User**—Allows you to use the current user running the report as input to the search criteria. For example, you can use the active user as a variable. This allows you to create reports like “Show me all trade specifications that I own” or “Show me all material specifications that I created.”

- **Date**—Allows you to use date variables as search criteria. For example, to say the “Next 30 days” the system assumes today's date and adds 30 days to today's date for search criteria. Options available are:

Last (Today - X) for the last X days

Next (Today + X) for the next X days

Between (Today +/- X) for a date range, for example, Today + or - 20 days

This allows you to create reports like “Show me all company supplier documents that expire in the next 30 days.”

You can add contextual variables in your search criteria by selecting one of the following icons:

- Click the active object icon to add the current active object as the search term
- Click the active user icon to add the current active user
- Click the relative date icon to add the current relative date.

The clear icon appears once you add the active object, active user, or relative date.

Not all criteria support contextual variables. For a full listing of supported variables see [Appendix A, "Ready Reports Contextual Variables"](#).

Note: When using active object variables, ready reports can only be executed from contextual locations. This means they have to be added as navigation items and cannot be used as personal bookmarks or standalone URLs. This is because the context actually drives the report criteria; if executed from a bookmark the system has no context to pull criteria from.


To test your ready report with active object contextual variables without adding it to the navigation, the following URL can be used once your report is saved.

`http://<URL>/ReadyReports/readyreports.aspx?pkid=<READYREPORTPKID>&ao=<ACTIVEOBJECTPKID>`

READYREPORTPKID—This pkid can be found in the browser's address bar when you have the ready report open in **Ready Report Administration**. See [Figure 3–7](#) below.

ACTIVEOBJECTPKID—This pkid can be found in the browser's address bar when you have the specification/object open. Note that not all objects will have the pkid in the browser's address bar. For these objects a navigation item has to be added to test the report.

Figure 3–7 URL for testing ready reports containing contextual variables



Using Ready Reports in Agile PLM for Process Applications

Reports can be saved as local browser bookmarks or individually shared with other users. Reports can even be shared to the entire user community by adding new navigation items throughout Agile PLM for Process applications.

Local Browser Bookmarks


The fastest and easiest way for a user to use a ready report would be to save the report as a local browser bookmark. This allows users to create relevant groupings of objects. For example, you can create a report that finds all formulations tied to a specific NPD project. Now the user will have one click access to every formulation they are currently working on within that project.

Note: By nature of design, reports containing active objects cannot be bookmarked.

Once you have a ready report created, follow these steps to bookmark your report:

1. Open the Ready Reports Administration application.
2. Locate the ready report you would like to bookmark in the ready report listing.
3. Select view details icon.
4. Your ready report opens in a new browser window and from there you can add this page to your favorites by clicking **Add to favorites** in your browser, as [Figure 3–8](#) shows below.

Figure 3–8 Adding a favorite to your browser



Or

1. Open the Ready Reports Administration application.
2. From the Ready Reports Details page, click the favorites icon to the right of the Report URL field.

A ready report can be shared with other users just by sharing the system-generated URL.

1. Open the Ready Reports Administration application.
2. Open the ready report you would like to share.
3. Copy the Report URL.
4. Paste the URL in email or instant message to share with other users.

Note: By nature of design, reports containing active object contextual variables cannot be shared via URL link.

Sharing with the Entire User Base

Reports can even be shared with the entire user community by adding new navigation items throughout Agile PLM for Process applications. Navigation items can have their own security rules so based on your configuration only the users you want to share the link with will see the link. Navigation items can be added to any application and context can be very specific. For example, you can provide a report that allows users to see all expired supplier documents. It can be linked only to a material specification and seen by users in the group “Supplier Managers”. The figures below show how navigation items might be added for NPD.

Note that reports containing active objects can be shared using this method.

Figure 3–9 Icon from NPD





Figure 3–10 Report run from NPD



Refer to the *Agile Product Lifecycle Management for Process Navigation Configuration Guide* for more information.

Security and Access

Security

All ready reports support GSM and SCRM business unit (BU) security. See the *Agile Product Lifecycle Management for Process Security Configuration Guide* for more information.

Visibility

All ready reports respect BU and workflow visibility.

Site Access

Individual site access controls which ready reports administrators and end users have access to. For example, if users only have site access to SCRM but they are a ready report administrator, they will only see target objects related to the SCRM application. All other application objects are hidden from their view.

The same goes for end users. If the end users only have site access for GSM, they will not be able to execute a ready report that uses an SCRM target object. If attempted, the users see a No Permissions error. Site access is assigned in UGM. Refer to the *Agile Product Lifecycle for Process Administrator User Guide* for more information.

Note: Users with the NPD_PARTNER role will not be able to execute any NPD ready report, regardless of site access. Access to DRL is role-based so, users must have one of the following roles to access DRL: [DRL_CREATOR], [DRL_EDITOR], or [DRL_VIEWER].

Ready Report Veto Plugin

If the out of the box security filters do not cover your specific use cases, the specification veto plugin can be used. For example, a user may have site access to GSM, but you do not want them to access a ready report that returns formulation specifications. A veto plugin can be deployed that checks the UGM user group and exact target object restricting the user's access.

Specification Veto Plugin

The ready reports framework uses a veto handler to extend security logic. Custom security rules can be evaluated when determining the ability to execute a ready report. The specification veto plugin is an extension point available to all ready reports. The custom class evaluates the current ready report and returns a true or false giving access to the results of the report or not.

Technical Documentation Refer to the PluginExtensions document, located in the [ProdikaHome]\Installer\ReferenceImplementations\PluginExtensions\Documentation folder for more details.

Available Reference Implementations This plugin is an example of a ready report veto handler. In this example, if the users' last name is Janjua or ready report model is based on material specification, they will not be able to see a report.

The reference implementation file can be found in:

[ProdikaHome]\Installer\ReferenceImplementations\ReadyReport\ReadyReportVetoHandlerPluginDemo.cs

Adjusting Report Views

Report Views can be extended. A report view allows you to customize the result columns returned for a ready report. There is a limit of 20 columns that can be returned as search results. To perform this extension, you will need to have access to the configuration files and permissions to reset IIS.

The choices of result columns are limited to what is included in the models listing found in [Appendix B, "Ready Reports Models"](#).

WARNING: When the ready reports application is upgraded, you will need to apply these configuration changes again. Comments are recommended so you can easily see which views were added.

Terminology

Here are some general terms that are used.

Models—Models define which criteria and search result columns are available.

Views—Views define which criteria and result columns are actually shown to the user.

Mandatory Property—A property used in a view that filters data returned based on security, visibility or configuration rules.

Configuration Files

New report views should be added to the ExtensionViews.xml file located inside the config\Extensions folder by completing the following steps:

1. Back up the ExtensionViews.xml file.

2. Make adjustments to the ExtensionViews.xml file.
3. Reset IIS and review your new report view within the ready reports UI.

Report Views Structure

The report view node structure looks like this:

```
< ReportViewName >
<AllowedModels>
<Model>
  <MandatoryProperty>
  <SearchableProperties>
  <DisplayColumns>
    <ColumnInfo>
  </DisplayColumns>
</Model>
</AllowedModels>
</ReportViewName>
```

Model

This represents the search model being used in the view. The name will generally tell you what target object you are running your report against. For example, most target objects in GSM are named: “Main [Type] Specification”. A specific example, the packaging specification search page, uses the following view:

```
<Model active="true" name="Main Packaging Specification" alias="lblType1009"
orderByColumns="-" captionColumn="0" primaryKeyColumnName="SpecID">
```

MandatoryProperty

This represents the filters being applied to the search view. These should not be edited.

SearchableProperties

This node is generally used to exclude certain search criteria based on configurations.

DisplayColumns

This node represents the actual result columns that are displayed to the user. Here is where columns can be removed or added.

The example below shows the result columns for the main packaging specification search in GSM.

```
DisplayColumns
  <ColumnInfo width="79" dataField="SpecNumber"
    dataFieldCaption="lblSpecNumber"/>
  <ColumnInfo width="256" dataField="SpecName" dataFieldCaption="lblSpecName"/>
  <ColumnInfo width="87" dataField="CurrentStatus"
    dataFieldCaption="lblSpecSummaryStatus"
    dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.WorkflowSta
      tusDataColumnTransformerFactory,EQTService"/>
  <ColumnInfo width="225" dataField="Taxonomy" dataFieldCaption="lblTaxonomy"/>
  <ColumnInfo width="102" dataField="Supercedes" dataFieldCaption="lblSupercedes"
    dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.SpecSuperce
      desDataTransformerFactory,PlatformExtensions"/>
  <ColumnInfo width="100" dataField="ctxSysEquiv"
    dataFieldCaption="lblContextSensitiveSysEquivCtlEquivalent"
    dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.GSMContextS
      ensitiveEquivalentDataTransformerFactory,PlatformExtensions"
    enableHandler="Class:Xeno.Prodika.EQTService.SearchablePropertyHandlers.Feature
      PropertyItemEnabledResolverFactory,EQTService$GSM.EQT.CrossReferences.Enabled"/
  >
</DisplayColumns>
```

ColumnInfo

The ColumnInfo node represents the actual result column. It has the following available attributes:

dataField—The actual id for the data to be returned. Please refer to the included Available Views and Models Index for the ids that can be used.

dataFieldCaption—The translatable label that will be used as the column header. Please refer to the included Available Views and Models Index for the data field captions that can be used.

Width—This is the column width designated in pixels. Make sure when you remove or add a column the new total width remains at 849 pixels. For example, if you were to add a column that was 150 pixels in width that would bring the total to 999. You must remove width from the other existing columns so that it once again equals 849 pixels.

dataTransformer—This is code that transforms the data returned in a recognizable string to the user.

isAggregatable—Used to display results that have more than one value. If set to true, the results will be combined into a single row, otherwise, one row will be returned for each value. For example, multiple Business Units can be added to a specification so the report will return multiple values for a single column.

aggregationDelimiter—Character used to divide the aggregated results.

Note: Columns that are added will be sortable. However, these columns will only be sorting the string of text returned. So if you are returning a date or number in your column, sorting will not appear to be functioning correctly.

Example: Adding Business Unit to Packaging Search Results

1. Find the “Main Packaging Specification” search view inside ExtensionViews.xml.
2. Find the <DisplayColumns node>.

```
<DisplayColumns>
    <ColumnInfo width="79" dataField="SpecNumber"
dataFieldCaption="lblSpecNumber"/>
    <ColumnInfo width="256" dataField="SpecName"
dataFieldCaption="lblSpecName"/>
    <ColumnInfo width="87" dataField="CurrentStatus"
dataFieldCaption="lblSpecSummaryStatus"
dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.Workflo
wStatusDataColumnTransformerFactory,EQTService"/>
    <ColumnInfo width="225" dataField="Taxonomy"
dataFieldCaption="lblTaxonomy"/>
    <ColumnInfo width="102" dataField="Supercedes"
dataFieldCaption="lblSupercedes"
dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.SpecSup
ercedesDataTransformerFactory,PlatformExtensions"/>
    <ColumnInfo width="100" dataField="ctxSysEquiv"
dataFieldCaption="lblContextSensitiveSysEquivCtlEquivalent"
dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.GSMCont
extSensitiveEquivalentDataTransformerFactory,PlatformExtensions"
enableHandler="Class:Xeno.Prodika.EQTService.SearchablePropertyHandlers.Fea
turePropertyItemEnabledResolverFactory,EQTService$GSM.EQT.CrossReferences.E
nabled"/>
</DisplayColumns>
```

3. Add a new Column node after the Equivalent column (ctxSysEquiv) using the Approved Business Unit dataField id, FieldCaption label, and appropriate width. Since the Approved Business Unit column can contain multiple values, the aggregation and dataTransformer attributes have been defined.

```
    <ColumnInfo width="125" dataField="ApprovedForUseBUDisplayName"
dataFieldCaption="lblBusinessUnit"
dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessU
nitDataColumnTransformerFactory,EQTService" isAggregatable="true"
aggregationDelimiter=", " />
<DisplayColumns>
    <ColumnInfo width="79" dataField="SpecNumber"
dataFieldCaption="lblSpecNumber"/>
    <ColumnInfo width="256" dataField="SpecName"
dataFieldCaption="lblSpecName"/>
    <ColumnInfo width="87" dataField="CurrentStatus"
dataFieldCaption="lblSpecSummaryStatus"
dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.Workflo
wStatusDataColumnTransformerFactory,EQTService"/>
    <ColumnInfo width="225" dataField="Taxonomy"
dataFieldCaption="lblTaxonomy"/>
    <ColumnInfo width="102" dataField="Supercedes"
dataFieldCaption="lblSupercedes"
dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.SpecSup
ercedesDataTransformerFactory,PlatformExtensions"/>
    <ColumnInfo width="100" dataField="ctxSysEquiv"
dataFieldCaption="lblContextSensitiveSysEquivCtlEquivalent"
dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.GSMCont
extSensitiveEquivalentDataTransformerFactory,PlatformExtensions"
enableHandler="Class:Xeno.Prodika.EQTService.SearchablePropertyHandlers.Fea
turePropertyItemEnabledResolverFactory,EQTService$GSM.EQT.CrossReferences.E
nabled"/>
    <ColumnInfo width="125" dataField="ApprovedForUseBUDisplayName"
```

```
dataFieldCaption="lblBusinessUnit"
dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService" isAggregatable="true"
aggregationDelimiter=", " />
</DisplayColumns>
```

4. To support 1024x768 resolutions, make sure your total width matches what it was before your addition. In this example the total width was 849 pixels. So you will need to remove 125 pixels of width from pre-existing column(s), like specification name.

```
<ColumnInfo width="131" dataField="SpecName" dataFieldCaption="lblSpecName"/>
```

5. Reset IIS.
6. Go to a Ready Report and select the **Packaging Specification** target object and verify the new column appears.

Adding New Report Views

New report views can be added by copying an existing view and changing the view name and corresponding attributes. This allows you to offer multiple report views per target object.

The report view node structure looks like the following. [ReportViewName] will appear in the report view drop down for the target object specified in the <Model> node.

```
<ReportViewName>
<AllowedModels>
<Model>
  <MandatoryProperty>
  <SearchableProperties>
  <DisplayColumns>
    <ColumnInfo>
  </DisplayColumns>
</Model>
</AllowedModels>
</ReportViewName>
```

Ready Reports Contextual Variables

This appendix contains a list of contextual variables that are supported in search criteria for ready reports for various applications. Refer to the ReadyReports.xml configuration file for further details.

Contextual Variables

DRL

Search Model	Available Variables
DRL Document	Catalogs
	Classification
	Document Date
	Effective Date
	Expiration Date
	Originator
	Status

EQ

Search Model	Available Variables
All EQ models contain these variables:	Additional Administrators (Users)
	Additional Administrators (Groups)
	Company Name
	Date Received
	Date Sent
	Due Date
	Primary Owner
	Status

GSM

Search Model	Available Variables
All models except Global Succession, Activity specification, and LIO profile contain these variables:	Associated Specs (Name and Number)
	Category
	Created
	Current Workflow: Owner or Group
	Effective
	Last Edit
	Originator
	Short Name
	Status
	Workflow

Search Model	Available Variables
Delivered Material Packing Specification	Inactive

Search Model	Available Variables
Equipment Specification	Inactive

Search Model	Available Variables
Formulation Specification	Facility
	Inactive
	Input Item
	Input Item (plus alternates)
	NPD Project
	Output Item

Search Model	Available Variables
Labeling Specification	Inactive

Search Model	Available Variables
Master Specification	Inactive

Search Model	Available Variables
Material Specification	Known to Contain: Additives, Allergens, Intolerances May Contain: Additives, Allergens, Intolerances Does Not Contain: Additives, Allergens, Intolerances BD Component Term or Alias BD Component Term Classification Country of Origin Inactive Material Type Output Type Receiving Facilities Source Facility

Search Model	Available Variables
Menu Item Specification	Known to Contain: Additives, Allergens, Intolerances May Contain: Additives, Allergens, Intolerances Does Not Contain: Additives, Allergens, Intolerances Actual Label Claims Inactive Menu Item Build Menu Item Class Potential Label Claims Standard

Search Model	Available Variables
Nutrient Profile	none

Search Model	Available Variables
--------------	---------------------

Packaging Specification	Inactive
	Item Type
	Receiving Facilities
	Source Facility

Search Model	Available Variables
Packing Configuration Specification	Inactive

Search Model	Available Variables
Printed Packaging Specification (Deprecated)	Inactive
	Receiving Facilities
	Source Facility

Search Model	Available Variables
Product Specification	Known to Contain: Additives, Allergens, Intolerances
	May Contain: Additives, Allergens, Intolerances
	Does Not Contain: Additives, Allergens, Intolerances
	BD Component Term or Alias
	BD Component Term
	Inactive
	Receiving Facilities
	Source Facility

Search Model	Available Variables
---------------------	----------------------------

Trade Specification	Known to Contain: Additives, Allergens, Intolerances
	May Contain: Additives, Allergens, Intolerances
	Does Not Contain: Additives, Allergens, Intolerances
	Actual Label Claims
	Brand
	BD Component Term or Alias
	BD Component Term
	GTIN/UPC/EAN
	Material Specification
	Packaging Materials
	Potential Label Claims
	UDEX Classification

Search Model	Available Variables
Global Succession	Created By
	New Specification: Name and Number
	Specification to Supersede: Name and Number

Search Model	Available Variables
GSM Activity	Activity Type
	Current Workflow: Owner or Group
	Effective
	Inactive
	Last Edit
	Originator
	Primary Item Specification: Name and Number
	Related Items Specification: Name and Number
	Status

Search Model	Available Variables
LIO Profile	Associated Formulation: Name and Number
	Associated Output: Name and Number
	Created
	Last Edit
	Nutrient Profile: Name and Number
	Originator

NPD

Search Model	Available Variables
Innovation/Sales Pipeline	Administrators
	Internal Project #
	Request Date
	Status

Search Model	Available Variables
Project	Brands
	Channels
	Consumer Value Perception
	Demographics
	Enabling Technology
	Gate Keeper(s)
	Global Categories
	Internal Project #
	Lead Countries
	Origination Date
	Priority
	Project Owner
	Project Type
	Readers (groups)
	Readers (users)
	Risk
	Stage
	Status
	Strategic Brief
	Team Leader(s)
	Team Member(s)

Search Model	Available Variables
Strategic Brief	Brands
	Channels
	Gate Keeper(s)
	Global Categories
	Key Sponsor(s)
	Lead Countries
	Origination Date
	Status
	Team Member(s)

NSM

Search Model	Available Variables
Nutrient Analysis	Creator
	Date of Analysis
	Date of Last Update
	Date Received from Lab
	Date Sent to Lab
	GTIN/UPC
	Sample Type
	Source Facility
	Specification

Search Model	Available Variables
Nutrient Composite	Date of Composite
	Date of Last Update
	Originator
	Specification

PQM

Search Model	Available Variables
Action	Action Type
	Affected Items (By Equivalent)
	Affected Items (By Rev)
	Affected Items (Rev. Indep.)
	Associated Project
	Company
	Customer
	Facility
	Last Edit
	Origination Date
	Originator
	Product Lines
	Related Actions
	Related Audits
	Related Issues
	Status
	Workflow

Search Model	Available Variables
Audit	Actual Audit Date
	Affected Items (By Equivalent)
	Affected Items (By Rev)
	Affected Items (Rev. Indep.)
	Audit Result
	Audit Type
	Company
	Customer
	Facility
	Last Edit
	Origination Date
	Originator
	Planned Audit Date
	Product Lines
	Related Actions
	Related Issues
	Status
	Workflow

Search Model	Available Variables
Issue	Affected Items (By Equivalent)
	Affected Items (By Rev)
	Affected Items (Rev. Indep.)
	Company
	Customer
	Expected Resolution Date
	Facility
	Issue Type
	Last Edit
	Occurrence Date
	Origination Date
	Originator
	Product Lines
	Related Actions
	Related Audits
	Resolution
	Severity
	Status
	Workflow

PQS

Search Model	Available Variables
Lot Sample	Date Created
	Date Received
	GTIN/UPC/EAN
	Internal Alias
	Location
	Receiving Facility
	Sample Production Date
	Scheduled Evaluation Date
	Source Facility
	Source Facility (country)
	Spec Name
	Spec #

Search Model	Available Variables
Scorecard	Date of Scoring
	Originator
	Sample Details
	Sample #
	Scored By
	Spec Name

Search Model	Available Variables
Session	Evaluation Date
	Location
	Sample Details
	Session Leader
	Users

SCRM

Search Model	Available Variables
Company	Alt. Supply Capability
	City Name
	Country
	Postal Code
	Sourcing (select spec)
	Sourcing (spec number)

Search Model	Available Variables
Facility	City Name
	Company
	Company Name
	Country
	Postal Code
	SAC Supplier Item #
	Sourcing (select spec)
	Sourcing (spec number)

Search Model	Available Variables
Contact	Associated Company
	Associated Facility
	Company Name
	Country
	Last SP Login Date
	Last Updated

Search Model	Available Variables
Non Spec Sourcing Approval	Class
	Company
	QA Assigned
	SC Assigned
	Sourcing Facility
	Sourcing Type
	Status

Search Model	Available Variables
Spec-Related Sourcing Approval	Class
	Company
	Protocol
	QA Assigned
	Receiving Facility
	SC Assigned
	Sourcing Facility
	Sourcing Type
	Specification
	Specification Taxonomy
	Status

Search Model	Available Variables
Company/Facility SDM	Company
	Document Type

Due/Renewal Date
Effective Date
Expiration Date
Facility
Originator
Status

Search Model	Available Variables
Non-Spec Sourcing Approval SDM	Company
	Document Type
	Due/Renewal Date
	Effective Date
	Expiration Date
	Facility
	Originator
	Status

Search Model	Available Variables
Spec Sourcing Approval SDM	Company
	Document Type
	Due/Renewal Date
	Effective Date
	Expiration Date
	Facility
	Originator
	Sourcing (select spec)
	Sourcing (spec number)
	Sourcing (taxonomy)
	Status

UGM

Search Model	Available Variables
Group	Last Updated

Search Model	Available Variables
User	Country
	Facility
	Last Updated
	User Name

Ready Reports Models

This appendix details the fields that can be displayed in the search results grid used for ready reports. It is sorted by application and business object.

ADMN

Custom Section

View: ExtendedSectionAttributeTemplateView

Model: Custom Sections

Data Field	Data Field Caption	Notes
CategoryTabDisplay	lblCategoryTab	
ColumnName	lblColumnName	isAggregatable="true"
CreatedDate	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
ExtendedAttributeStatus	lblStatus	
ExtendedAttributeTemplateName	lblSectionName	
ID	lblSectionID	
LastEditDate	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$1020"
RowName	lblRowName	isAggregatable="true"
SecurityClassDisplay	lblSecurityClassification	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"

Extended Attribute

View: ExtendedAttributeView

Model: Extended Attributes

Data Field	Data Field Caption	Notes
CategoryTabDisplay	lblCategoryTab	
ExtAttrTypeDisplayValue	lblAttributeType	
ExtendedAttributeGroup	lblGroup	
ExtendedAttributeID	lblExtendedAttributeTypeID	
ExtendedAttributeName	lblAttributeName	
ExtendedAttributeStatus	lblAttributeStatus	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUserService.MostRecentlyUsedItemObjectEnabledResolverFactory\$2281"
SegmentName	lblSegmentNameProperty	sAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"

Component Catalog

Component Catalog Term

View: FICTermView

Model: Component Catalog Items

Data Field	Data Field Caption	Notes
CreateByUserName	lblCreatedBy	
FICTermAliasPKID2	lblTermOrAlias	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.FICTermAliasDataColumnTransformerFactory,EQTService"
FICTermNumber	lblTermNumber	
FICTermID	lblTermID	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUserService.MostRecentlyUsedItemObjectEnabledResolverFactory\$6900"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
StatusName	lblStatus	

DRL

DRL Document

View: DocumentSearchView

Model: DRL Documents

Data Field	Data Field Caption	Notes
AttachmentTitleDisplay	lblAttachmentTitle	isAggregatable="true"
BusinessUnit	lblBusinessUnit	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService" isAggregatable="true" aggregationDelimiter=","
ClassificationDisplay	lblExactMatchClassification	isAggregatable="true"
DocumentDate	lblDocumentDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
DocumentNumberIssue	lblDocumentID	
EffectiveDate	lblEffectiveDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
ExpirationDate	lblExpirationDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$7502"
Originator	lblOriginator	
StatusName	lblStatus	
Title	lblDocumentTitle	
VisibilityDisplay	lblExactMatchVisibility	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"

EQ

Material EQ Request

View: EQMaterialRequestView

Model: Material eQuestionnaires

Data Field	Data Field Caption	Notes
AddlAdminGroupsDisplay	lblAddlAdminGroups	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.CurrentWorkflowGroupDataColumnTransformerFactory,ReadyReportsLib"
AddlAdminUsersDisplay	lblAddlAdminUsers	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
eQImportedIntoGSMDisplay	lblEQImportedIntoGSM	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.EQImportIntoGSMDataColumnTransformerFactory,eQWebUI"
ImportMaterialSpecDisplay	lblImportSpec	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.SpecNameDataColumnTransformerFactory,ReadyReportsLib"
IsSupplierInitiatedDisplay	lblSupplierInitiated	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$1004EQ"
QuestionnaireApprovedUseOwner	lblPrimaryOwner	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
QuestionnaireCompany	lblEQCompany	
QuestionnaireDateReceived	lblEQDateRcvd	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
QuestionnaireDateSent	lblEQDateSent	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
QuestionnaireDueDate	lblEQDueDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
QuestionnaireEmail	lblEQEmail	
QuestionnaireNumber	lblEQNumber	
QuestionnaireStatusDisplay	lblEQStatus	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.EQStatusDataColumnTransformerFactory,eQWebUI"
QuestionnaireTitle	lblEQTitle	

SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
-------------	------------------------	---

Packaging EQ Request

View: EQPackagingRequestView

Model: Packaging eQuestionnaires

Data Field	Data Field Caption	Notes
AddlAdminGroupsDisplay	lblAddlAdminGroups	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.CurrentWorkflowGroupDataColumnTransformerFactory,ReadyReportsLib"
AddlAdminUsersDisplay	lblAddlAdminUsers	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
eQImportedIntoGSMDisplay	lblEQImportedIntoGSM	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.EQImportIntoGSMDataColumnTransformerFactory,eQWebUI"
ImportPackagingSpecDisplay	lblImportSpec	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.SpecNameDataColumnTransformerFactory,ReadyReportsLib"
IsSupplierInitiatedDisplay	lblSupplierInitiated	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$1009EQ"
QuestionnaireApprovedUseOwner	lblPrimaryOwner	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
QuestionnaireCompany	lblEQCompany	
QuestionnaireDateReceived	lblEQDateRcvd	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
QuestionnaireDateSent	lblEQDateSent	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
QuestionnaireDueDate	lblEQDueDate	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTService"
QuestionnaireEmail	lblEQEmail	
QuestionnaireNumber	lblEQNumber	
QuestionnaireStatusDisplay	lblEQStatus	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.EQStatusDataColumnTransformerFactory,eQWebUI"

Data Field	Data Field Caption	Notes
QuestionnaireTitle	lblEQTitle	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"

Printed Packaging EQ Request--Deprecated

View: EQPrintedPackagingRequestView

Model: Printed Packaging eQuestionnaires

Data Field	Data Field Caption	Notes
AddlAdminGroupsDisplay	lblAddlAdminGroups	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.CurrentWorkflowGroupDataColumnTransformerFactory,ReadyReportsLib"
AddlAdminUsersDisplay	lblAddlAdminUsers	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
eQImportedIntoGSMDisplay	lblEQImportedIntoGSM	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.EQImportIntoGSMDataColumnTransformerFactory,eQWebUI"
ImportPrintedPackagingSpecDisplay	lblImportSpec	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.SpecNameDataColumnTransformerFactory,ReadyReportsLib"
IsSupplierInitiatedDisplay	lblSupplierInitiated	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$2121EQ"
QuestionnaireApprovedUseOwner	lblPrimaryOwner	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
QuestionnaireCompany	lblEQCompany	
QuestionnaireDateReceived	lblEQDateRcvd	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTSservice"
QuestionnaireDateSent	lblEQDateSent	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTSservice"
QuestionnaireDueDate	lblEQDueDate	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateFormatValueDelegateFactory,EQTSservice"
QuestionnaireEmail	lblEQEmail	
QuestionnaireNumber	lblEQNumber	

Data Field	Data Field Caption	Notes
QuestionnaireStatusDisplay	lblEQStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.EQStatusDataColu mnTransformerFactory,eQWebUI"
QuestionnaireTitle	lblEQTitle	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="", " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"

Product EQ Request

View: EQProductRequestView

Model: Product eQuestionnaires

Data Field	Data Field Caption	Notes
AddlAdminGroupsDisplay	lblAddlAdminGroups	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib"
AddlAdminUsersDisplay	lblAddlAdminUsers	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
eQImportedIntoGSMDisplay	lblEQImportedIntoGSM	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.EQImportIntoGSM DataColumnTransformerFactory,eQWebUI"
ImportProductSpec	lblImportSpec	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.DataColumnTransformers.Spec NameDataColumnTransformerFactory,ReadyR eportsLib"
IsSupplierInitiatedDisplay	lblSupplierInitiated	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$6501EQ"
QuestionnaireApprovedUseOwner	lblPrimaryOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
QuestionnaireCompany	lblEQCompany	
QuestionnaireDateReceived	lblEQDateRcvd	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateFormat ValueDelegateFactory,EQTService"
QuestionnaireDateSent	lblEQDateSent	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateFormat ValueDelegateFactory,EQTService"
QuestionnaireDueDate	lblEQDueDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateFormat ValueDelegateFactory,EQTService"

Data Field	Data Field Caption	Notes
QuestionnaireEmail	lblEQEmail	
QuestionnaireNumber	lblEQNumber	
QuestionnaireStatusDisplay	lblEQStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.EQStatusDataColu mnTransformerFactory,eQWebUI"
QuestionnaireTitle	lblEQTitle	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"

Trade EQ Request

View: EQTradeRequestView

Model: Trade eQuestionnaires

Data Field	Data Field Caption	Notes
AddlAdminGroupsDisplay	lblAddlAdminGroups	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib"
AddlAdminUsersDisplay	lblAddlAdminGroups	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
eQImportedIntoGSMDisplay	lblEQImportedIntoGSM	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.EQImportIntoGSM DataColumnTransformerFactory,eQWebUI"
ImportTradeSpecDisplay	lblImportSpec	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.DataColumnTransformers.Spec NameDataColumnTransformerFactory,ReadyR eportsLib"
IsSupplierInitiatedDisplay	lblSupplierInitiated	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$2147EQ"
QuestionnaireApprovedUseOwner	lblPrimaryOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
QuestionnaireCompany	lblEQCompany	
QuestionnaireDateReceived	lblEQDateRcvd	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateFormat ValueDelegateFactory,EQTService"
QuestionnaireDateSent	lblEQDateSent	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateFormat ValueDelegateFactory,EQTService"

Data Field	Data Field Caption	Notes
QuestionnaireDueDate	lblEQDueDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateFormat ValueDelegateFactory,EQTService"
QuestionnaireEmail	lblEQEmail	
QuestionnaireNumber	lblEQNumber	
QuestionnaireStatusDisplay	lblEQStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.EQStatusDataColu mnTransformerFactory,eQWebUI"
QuestionnaireTitle	lblEQTitle	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="", " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"

GSM

Delivered Material Packing Specification

View: SpecSummaryView

Model: Delivered Material Packing Specifications

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.BusinessUnitDataC olumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1010 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1010 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1010 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1010 display"

Data Field	Data Field Caption	Notes
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.TaxonomyAliasDataCol umnTransformerFactory,EQTService\$Foodserv iceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.CountryDataColum nTransformerFactory,EQTService" isAggregatable="true"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Description	lblDescription	
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$1010"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SupercedesLangAware	lblSupercedes	
Taxonomy	lblTaxonomy	

Data Field	Data Field Caption	Notes
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$1010" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
WorkflowName	lblWorkflow	

Equipment Specification

View: SpecSummaryView

Model: Equipment Specifications

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTSservice"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2280 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2280 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2280 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2280 display"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSservice.DataTransformers.TaxonomyAliasDataColumnTransformerFactory,EQTSservice\$FoodserviceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.CountryDataColumnTransformerFactory,EQTSservice" isAggregatable="true"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTSservice"

Data Field	Data Field Caption	Notes
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTS Service.DataTransformers.GSMContextSensitiveEquivalentDataTransformerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTS ervice.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTS ervice\$GSM.EQT.CrossReferences.Enabled"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQTS Service.DataTransformers.WorkflowStatusDataColumnTransformerFactory,EQTS ervice"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflowGroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQTS Service.DataTransformers.UserNameDataColumnTransformerFactory,FICS ervice" isAggregatable="true"
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTS ervice"
ERPSysNameAndID	lblERPSysNameAndID	dataTransformer="Singleton:Xeno.Prodika.EQTS Service.DataTransformers.LegacySystemEquivalentDataColumnTransformerFactory,EQTS ervice" isAggregatable="true"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTS ervice"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTS ervice"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUS ervice.MostRecentlyUsedItemObjectEnabledResolverFactory\$2280"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQTS Service.DataTransformers.UserNameDataColumnTransformerFactory,FICS ervice"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SupersedesLangAware	lblSupersedes	
SystemNameDisplayName	lblSystemName	isAggregatable="true"
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"

Data Field	Data Field Caption	Notes
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$2280" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
WorkflowName	lblWorkflow	

Formulation Specification

View: SpecSummaryView

Model: Formulation Specifications

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTSservice"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$5816 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$5816 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$5816 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$5816 display"
BOMItemAnnotationDisplay	lblBOMItemAnnotation	isAggregatable="true"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSservice.DataTransformers.TaxonomyAliasDataColumnTransformerFactory,EQTSservice\$FoodserviceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.CountryDataColumnTransformerFactory,EQTSservice" isAggregatable="true"

Data Field	Data Field Caption	Notes
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.GSMContextSensit iveEquivalentDataTransormerFactory,Platform Extensions" enableHandler="Class:Xeno.Prodika.EQT Servi ce.SearchablePropertyHandlers.FeatureProperty ItemEnabledResolverFactory,EQTService\$GS M.EQT.CrossReferences.Enabled"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Description	lblDescription	
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
FacilityDisplayName	lblFacility	dataTransformer="Singleton:EQTModels.Busin essUnitSecurity.BUSecuredFacilityNameDataC olumnTransformerFactory,EQTModels"
FormulationType	lblFormulationType	
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$5816"
NPDProjectNameDisplay	lblNPDProjectName	
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="", " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	

Data Field	Data Field Caption	Notes
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
StepInstrKeywordsDisplay	lblStepInstructionsKeywords	isAggregatable="true"
StepName	lblStepName	isAggregatable="true"
SupersedesLangAware	lblSupersedes	
SystemEquivalentDisplay	lblSysEquivCtEquivalent	isAggregatable="true"
SystemNameDisplayName	lblSystemName	isAggregatable="true"
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$5816" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
WorkflowName	lblWorkflow	

Global Succession Request

View: SuccessionRequestView

Model: Global Succession Requests

Data Field	Data Field Caption	Notes
CreatedDate	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTSERVICE.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTSERVICE"
CreatorName	lblCreatedBy	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUSERVICE.MostRecentlyUsedItemObjectEnabledResolverFactory\$5806"
NewSpecificationName	lblNewSpecName	
NewSpecificationNumber	lblNewSpecNumber	
ParentSpecType	lblParentType	dataFormatter="Singleton:Xeno.Prodika.EQTSERVICE.FormatValueDelegates.DataObjectNameFormatValueDelegateFactory,EQTSERVICE"
RequestNumber	lblRequestNumber	
SpecToSupersedeSpecName	lblSupersedeSpecName	
SpecToSupersedeSpecNumber	lblSupersedeSpecNumber	
SuccessionSpecType	lblSuccessionType	dataFormatter="Singleton:Xeno.Prodika.EQTSERVICE.FormatValueDelegates.DataObjectNameFormatValueDelegateFactory,EQTSERVICE"

GSM Activity

View: SpecSummaryView

Model: GSM Activities

Data Field	Data Field Caption	Notes
ActPrimarySpecNameDisplay	lblActivityPrimarySpecName	
ActPrimarySpecNumberDisplay	lblActivityPrimarySpecNumber	
ActRelatedSpecNameDisplay	lblActivityRelatedSpecName	isAggregatable="true"
ActRelatedSpecNumberDisplay	lblActivityRelatedSpecNumber	isAggregatable="true"
ActivityWorkflowName	lblActivityType	
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.BusinessUnitDataC olumnTransformerFactory,EQTService"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSe rvice.DataTransformers.TaxonomyAliasDataCol umnTransformerFactory,EQTService\$Foodserv iceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.CountryDataColum nTransformerFactory,EQTService" isAggregatable="true"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$2283"
OriginatorName	lblSpecSummaryOriginator	
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"

Data Field	Data Field Caption	Notes
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
SpecialNotes	lblActivitySpecialNotes	
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$2283" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
WorkflowName	lblWorkflow	

Labeling Specification

View: SpecSummaryView

Model: Labeling Specifications

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTSERVICE.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTSERVICE"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$1006 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$1006 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$1006 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	sAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$1006 display"

Data Field	Data Field Caption	Notes
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.TaxonomyAliasDataCol umnTransformerFactory,EQTService\$Foodserv iceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.CountryDataColum nTransformerFactory,EQTService" isAggregatable="true"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Description	lblDescription	
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$1006"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SystemNameDisplayName	lblSystemName	isAggregatable="true"
SupersedesLangAware	lblSupersedes	

Data Field	Data Field Caption	Notes
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$1006" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
WorkflowName	lblWorkflow	

LIO Profile

View: SpecSummaryView

Model: LIO Profiles

Data Field	Data Field Caption	Notes
AssociatedFormulationEquiv	lblAssocFormulationEquivalent	isAggregatable="true"
AssociatedFormulationName	lblAssocFormulationName	
AssociatedFormulationNumber	lblAssocFormulationNum	
AssociatedNPName	lblAssocNPName	
AssociatedNPNumber	lblAssocNPNum	
AssociatedOutputEquiv	lblAssocOutputEquivalent	isAggregatable="true"
AssociatedOutputName	lblAssocOutputName	
AssociatedOutputNumber	lblAssocOutputNum	
Description	lblDescription	
LastSavedDate	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTSERVICE.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTSERVICE"
LIONumber	lblProfileNumber	
LIOProfileCreatedDate	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTSERVICE.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTSERVICE"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUSERVICE.MostRecentlyUsedItemObjectEnabledResolverFactory\$5506"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQTSERVICE.DataTransformers.UserNameDataColumnTransformerFactory,FICSERVICE"
ProfileName	lblProfileName	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUSER"
StatusName	lblStatus	

Master Specification

View: SpecSummaryView

Model: Master Specifications

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.BusinessUnitDataC olumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1005 display"
AssociatedSpecERPIDDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1005 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1005 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1005 display"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSe rvice.DataTransformers.TaxonomyAliasDataCol umnTransformerFactory,EQTService\$Foodserv iceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.CountryDataColum nTransformerFactory,EQTService" isAggregatable="true"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
CurrentStatus	lblSpecStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Description	lblDescription	

Data Field	Data Field Caption	Notes
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$1005"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter=", " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SupercedesLangAware	lblSupercedes	
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common. Controls.Thumbnail.EQTEnableHandler,WebC ommon\$1005" dataFormatter="Singleton:Xeno.Web.UI.Comm on.Controls.Thumbnail.EQTDataFormatter,We bCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
WorkflowName	lblWorkflow	

Material Specification

View: SpecSummaryView

Model: Material Specifications

Data Field	Data Field Caption	Notes
AdditivesContainedDisplay	lblctlComplianceAdditives	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$Additives"

Data Field	Data Field Caption	Notes
AdditivesNotContDisplay	lblComplianceAdditivesNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AdditivesMayContDisplay	lblComplianceAdditivesMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AllergensContainedDisplay	lblctlComplianceAllergens	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
AllergensNotContDisplay	lblComplianceAllergensNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
AllergensMayContDisplay	lblComplianceAllergensMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$1004 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$1004 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$1004 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$1004 display"
ClassificationDisplayName	lblClassification	isAggregatable="true"
CombinedIngredientStatement	lblIngredientStateCtlCombinedState	

Data Field	Data Field Caption	Notes
CompliesWithDisplay	lblctlComplianceCompliesWith	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$CompliesWith"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.TaxonomyAliasDataCol umnTransformerFactory,EQTService\$Foodserv iceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.CountryDataColum nTransformerFactory,EQTService" isAggregatable="true"
CountryOfOriginDisplay	lblCountryOfOrigin	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.CountryDataColum nTransformerFactory,EQTService"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.GSMContextSensit iveEquivalentDataTransormerFactory,Platform Extensions" enableHandler="Class:Xeno.Prodika.EQTServi ce.SearchablePropertyHandlers.FeatureProperty ItemEnabledResolverFactory,EQTService\$GS M.EQT.CrossReferences.Enabled"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Description	lblDescription	
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
IngredientStatement	lblIngredientStatement	
IntolerancesContainedDisplay	lblctlComplianceIntolerances	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$Intolerances"

Data Field	Data Field Caption	Notes
IntolerancesNotContDisplay	lblComplianceIntolerancesNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Intolerances"
IntolerancesMayContDisplay	lblComplianceIntolerancesMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Intolerances"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTSERVICE.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
MaterialTypeExDisplay	lblType	lblType dataTransformer="Singleton:Xeno.Prodika.EQTSERVICE.DataTransformers.MaterialTypeExDataTransformerFactory,PlatformExtensions"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUSERVICE.MostRecentlyUsedItemObjectEnabledResolverFactory\$1004"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQTSERVICE.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
ParentFrmSpecERPIDDdisplay	lblParentFormulationSpecERPID	isAggregatable="true"
ParentFrmSpecNameDisplay	lblParentFormulationSpecName	isAggregatable="true"
ParentFrmSpecNumDisplay	lblParentFormulationSpecNum	isAggregatable="true"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SourcingFacilityDisplayName	lblSourceFacility	isAggregatable="true" dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels"
SourcingNumberSpec	lblSourcingNumber	isAggregatable="true"
specCostBookValue	lblUSDPer100g	dataTransformer="Singleton:Xeno.Prodika.GSMLib.EQTDisplayColumnCellTransformers.FormulationCostBookValueDataTransformerFactory,GSMLib"
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SupercedesLangAware	lblSupercedes	
SupplierPartNumberDisplayName	lblSupplierItemNumber	isAggregatable="true"
SystemNameDisplayName	lblSystemName	isAggregatable="true"
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"

Data Field	Data Field Caption	Notes
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$1004" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
TradeSpecERPIDDdisplay	lblTradeSpecERPID	isAggregatable="true"
TradeSpecNameDisplay	lblTradeSpecName	isAggregatable="true"
TradeSpecNumDisplay	lblTradeSpecNum	isAggregatable="true"
VendorHasApprovedDisplayName	lblVendorHasApproved	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.VendorHasApprovedDataColumnTransformerFactory,ReadyReportsLib" isAggregatable="true"
WorkflowName	lblWorkflow	

Menu Item Specification

View: SpecSummaryView

Model: Menu Item Specifications

Data Field	Data Field Caption	Notes
ActualClaimsDisplayName	lblActualLabelClaims	isAggregatable="true"
AdditivesContainedDisplay	lblctlComplianceAdditives	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AdditivesNotContDisplay	lblComplianceAdditivesNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AdditivesMayContDisplay	lblComplianceAdditivesMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AllergensContainedDisplay	lblctlComplianceAllergens	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
AllergensNotContDisplay	lblComplianceAllergensNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"

Data Field	Data Field Caption	Notes
AllergensMayContDisplay	lblComplianceAllergensMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$6500 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$6500 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$6500 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$6500 display"
BusinessUnit	lblBusinessUnit	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService" isAggregatable="true"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSservice.DataTransformers.TaxonomyAliasDataColumnTransformerFactory,EQTService\$FoodserviceConcept" isAggregatable="true"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.GSMContextSensitiveEquivalentDataTransormerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTSservice.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$GSM.EQT.CrossReferences.Enabled"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.WorkflowStatusDataColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.CurrentWorkflowGroupDataColumnTransformerFactory,ReadyReportsLib" isAggregatable="true"

Data Field	Data Field Caption	Notes
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQTS Service.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
IngredientStatement	lblIngredientStatement	
IntolerancesContainedDisplay	lblctlComplianceIntolerances	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$Intolerances"
IntolerancesNotContDisplay	lblComplianceIntolerancesNotContai ned	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$Intolerances"
IntolerancesMayContDisplay	lblComplianceIntolerancesMayContai n	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$Intolerances"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MenuItemClassName	lblMenuItemClass	isAggregatable="true"
MenuItemStandardDisplay	lblStandard	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$6500"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
PotentialClaimsDisplayName	lblPotentialLabelClaims	isAggregatable="true"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter=", " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
CompliesWithDisplay	lblctlComplianceCompliesWith	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$CompliesWith"

Data Field	Data Field Caption	Notes
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SupercedesLangAware	lblSupercedes	
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"
SystemNameDisplayName	lblSystemName	isAggregatable="true"
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$6500" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
WorkflowName	lblWorkflow	

Nutrient Profile

View: SpecSummaryView

Model: Nutrient Profiles

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$5750 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$5750 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$5750 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$5750 display"
CaloriesDisplay	lblCaloriesPerHundredGram	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerHundredGramDataTransformerFactory,PlatformExtensions\$lblCalories"

Data Field	Data Field Caption	Notes
CaloriesPerServingDisplay	lblCaloriesPerServing	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.NutrientItemPerServing DataTransformerFactory,PlatformExtensions\$lb lCalories"
CarbohydratesDisplay	lblCarbsPerHundredGram	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.NutrientItemPerHundre dGramDataTransformerFactory,PlatformExtens ions\$lblCarbohydrates"
CarbsPerServingDisplay	lblCarbsPerServing	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.NutrientItemPerServing DataTransformerFactory,PlatformExtensions\$lb lCarbohydrates"
CholesterolDisplay	lblCholesterolPerHundredGram	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.NutrientItemPerHundre dGramDataTransformerFactory,PlatformExtens ions\$lblCholesterol"
CholesterolPerServingDisplay	lblCholesterolPerServing	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.NutrientItemPerServing DataTransformerFactory,PlatformExtensions\$lb lCholesterol"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSer vice.DataTransformers.TaxonomyAliasDataCol umnTransformerFactory,EQTService\$Foodserv iceConcept" isAggregatable="true"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
IngredientStatement	lblIngredientStatement	
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUSer vice.MostRecentlyUsedItemObjectEnabledResol verFactory\$5750"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
Owner	lblOwner	
ParentSpecName	lblParentSpecName	isAggregatable="true"

Data Field	Data Field Caption	Notes
ParentSpecNum	lblParentSpecNum	isAggregatable="true"
ProteinDisplay	lblProteinPerHundredGram	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerHundredGramDataTransformerFactory,PlatformExtensions\$lblProtein"
ProteinPerServingDisplay	lblProteinPerServing	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerServingDataTransformerFactory,PlatformExtensions\$lblProtein"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SodiumDisplay	lblSodiumPerHundredGram	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerHundredGramDataTransformerFactory,PlatformExtensions\$lblSodium"
SodiumPerServingDisplay	lblSodiumPerServing	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerServingDataTransformerFactory,PlatformExtensions\$lblSodium"
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SupercedesLangAware	lblSupercedes	
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$5750" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
TotalFatDisplay	lblTotalFatPerHundredGram	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerHundredGramDataTransformerFactory,PlatformExtensions\$lblTotalFat"
TotalFatPerServingDisplay	lblTotalFatPerServing	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerServingDataTransformerFactory,PlatformExtensions\$lblTotalFat"
TotalSugarDisplay	lblTotalSugarPerHundredGram	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerHundredGramDataTransformerFactory,PlatformExtensions\$lblTotalSugar"
TotalSugarPerServingDisplay	lblTotalSugarPerServing	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.NutrientItemPerServingDataTransformerFactory,PlatformExtensions\$lblTotalSugar"
WorkflowName	lblWorkflow	

Packaging Specification

View: SpecSummaryView

Model: Packaging Specifications

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.BusinessUnitDataC olumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1009 display"
AssociatedSpecERPIDDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1009 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1009 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib. EQTSearchablePropertyHandlers.AssocSpecCo nfigPropertyItemEnabledResolverFactory,GSM Lib\$1009 display"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSe rvice.DataTransformers.TaxonomyAliasDataCol umnTransformerFactory,EQTService\$Foodserv iceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.CountryDataColum nTransformerFactory,EQTService" isAggregatable="true"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.GSMContextSensit iveEquivalentDataTransformerFactory,Platform Extensions" enableHandler="Class:Xeno.Prodika.EQTServi ce.SearchablePropertyHandlers.FeatureProperty ItemEnabledResolverFactory,EQTService\$GS M.EQT.CrossReferences.Enabled"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"

Data Field	Data Field Caption	Notes
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.CurrentWorkflowGroupDataColumnTransformerFactory,ReadyReportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService" isAggregatable="true"
Description	lblDescription	
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
ItemType	lblItemType	
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$1009"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SourcingFacilityDisplayName	lblSourceFacility	isAggregatable="true" dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels"
SourcingNumberSpec	lblSourcingNumber	isAggregatable="true"
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SpecStatus	lblSpecSummaryStatus	
SupercedesLangAware	lblSupercedes	
SupplierPartNumberDisplayName	lblSupplierItemNumber	isAggregatable="true"
SystemNameDisplayName	lblSystemName	isAggregatable="true"
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"
Taxonomy	lblTaxonomy	

Data Field	Data Field Caption	Notes
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$1009" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
VendorHasApprovedDisplayName	lblVendorHasApproved	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.VendorHasApprovedDataColumnTransformerFactory,ReadyReportsLib" isAggregatable="true"
WorkflowName	lblWorkflow	

Packing Config Specification

View: SpecSummaryView

Model: Packing Configuration Specifications

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2076 display"
AssociatedSpecERPIDDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2076 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2076 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2076 display"
ConceptDisplay	lblConcept	ataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.TaxonomyAliasDataColumnTransformerFactory,EQTService\$FoodserviceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.CountryDataColumnTransformerFactory,EQTService" isAggregatable="true"

Data Field	Data Field Caption	Notes
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.GSMContextSensit iveEquivalentDataTransormerFactory,Platform Extensions" enableHandler="Class:Xeno.Prodika.EQT Servi ce.SearchablePropertyHandlers.FeatureProperty ItemEnabledResolverFactory,EQTService\$GS M.EQT.CrossReferences.Enabled"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Description	lblDescription	
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$2076"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SupercedesLangAware	lblSupercedes	
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"

Data Field	Data Field Caption	Notes
SystemNameDisplayName	lblSystemName	isAggregatable="true"
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$2076" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
WorkflowName	lblWorkflow	

Printed Packaging Specification--Deprecated

View: SpecSummaryView

Model: Printed Packaging Specifications

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTSservice"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2121 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2121 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2121 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2121 display"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSservice.DataTransformers.TaxonomyAliasDataColumnTransformerFactory,EQTSservice\$FoodserviceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.CountryDataColumnTransformerFactory,EQTSservice" isAggregatable="true"

Data Field	Data Field Caption	Notes
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.GSMContextSensit iveEquivalentDataTransormerFactory,Platform Extensions" enableHandler="Class:Xeno.Prodika.EQT Servi ce.SearchablePropertyHandlers.FeatureProperty ItemEnabledResolverFactory,EQTService\$GS M.EQT.CrossReferences.Enabled"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.WorkflowStatusDa taColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Inactive	lblSpecSummaryInactive	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$2121"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SourcingFacilityDisplayName	lblSourceFacility	isAggregatable="true" dataTransformer="Singleton:EQTModels.Busin essUnitSecurity.BUSecuredFacilityNameDataC olumnTransformerFactory,EQTModels"
SourcingNumberSpec	lblSourcingNumber	isAggregatable="true"
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	

Data Field	Data Field Caption	Notes
SupercedesLangAware	lblSupercedes	
SupplierPartNumberDisplayName	lblSupplierItemNumber	isAggregatable="true"
SystemNameDisplayName	lblSystemName	isAggregatable="true"
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$2121" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
VendorHasApprovedDisplayName	lblVendorHasApproved	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.VendorHasApprovedDataColumnTransformerFactory,ReadyReportsLib" isAggregatable="true"
WorkflowName	lblWorkflow	

Product Specification

View: SpecSummaryView

Model: Product Specifications

Data Field	Data Field Caption	Notes
AdditivesContainedDisplay	lblctlComplianceAdditives	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AdditivesNotContDisplay	lblComplianceAdditivesNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AdditivesMayContDisplay	lblComplianceAdditivesMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AllergensContainedDisplay	lblctlComplianceAllergens	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
AllergensNotContDisplay	lblComplianceAllergensNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"

Data Field	Data Field Caption	Notes
AllergensMayContDisplay	lblComplianceAllergensMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$6501 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$6501 display"
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$6501 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$6501 display"
BusinessUnit	lblBusinessUnit	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService" isAggregatable="true" aggregationDelimiter=",",
CompliesWithDisplay	lblctlComplianceCompliesWith	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$CompliesWith"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSservice.DataTransformers.TaxonomyAliasDataColumnTransformerFactory,EQTService\$FoodserviceConcept" isAggregatable="true"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.GSMContextSensitiveEquivalentDataTransormerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTSservice.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$GSM.EQT.CrossReferences.Enabled"

Data Field	Data Field Caption	Notes
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQTS Service.DataTransformers.WorkflowStatusData ColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.Transformers.CurrentWorkflow GroupDataColumnTransformerFactory,ReadyR eportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQ TS Service.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
ERPSysNameAndID	lblERPSysNameAndID	dataTransformer="Singleton:Xeno.Prodika.EQ TS Service.DataTransformers.LegacySystemEqui valentDataColumnTransformerFactory,EQTSe rvice" isAggregatable="true"
IngredientStatement	lblIngredientStatement	
IntolerancesContainedDisplay	lblctlComplianceIntolerances	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$Intolerances"
IntolerancesNotContDisplay	lblComplianceIntolerancesNotContai ned	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$Intolerances"
IntolerancesMayContDisplay	lblComplianceIntolerancesMayContai n	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$Intolerances"
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$6501"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TS Service.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
ProductClassificationName	lblClassification	isAggregatable="true"
ProductStandardDisplay	lblStandard	
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"

Data Field	Data Field Caption	Notes
ShortName	lblSpecShortName	
SourcingFacilityDisplayName	lblSourceFacility	isAggregatable="true" dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels"
SourcingNumberSpec	lblSourcingNumber	isAggregatable="true"
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SupercedesLangAware	lblSupercedes	
SupplierPartNumberDisplayName	lblSupplierItemNumber	isAggregatable="true"
SystemNameDisplayName	lblSystemName	isAggregatable="true"
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"
Taxonomy	lblTaxonomy	
Thumbnail	lblThumbnail	enableHandler="Class:Xeno.Web.UI.Common.Controls.Thumbnail.EQTEnableHandler,WebCommon\$6501" dataFormatter="Singleton:Xeno.Web.UI.Common.Controls.Thumbnail.EQTDataFormatter,WebCommon" hideHeader="true" disableExport="true" sortingEnabled="false"
VendorHasApprovedDisplayName	lblVendorHasApproved	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.VendorHasApprovedDataColumnTransformerFactory,ReadyReportsLib" isAggregatable="true"
WorkflowName	lblWorkflow	

Testing Protocol

View: SpecSummaryView

Model: Testing Protocols

Data Field	Data Field Caption	Notes
Id	lblTestingProtocolID	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$2078"
TestingProtocolCreated	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTSservice"
TestingProtocolDescription	lblDescription	
TestingProtocolLastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTSservice"
TestingProtocolName	lblProtocolName	
TestingProtocolOriginator	lblOriginator	

Data Field	Data Field Caption	Notes
TestingProtocolScope	lblScope	
TestingProtocolStatus	lblStatus	

Trade Specification

View: SpecSummaryView

Model: Trade Specifications

Data Field	Data Field Caption	Notes
ActualClaimsDisplayName	lblActualLabelClaims	isAggregatable="true"
AdditivesContainedDisplay	lblctlComplianceAdditives	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AdditivesNotContDisplay	lblComplianceAdditivesNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AdditivesMayContDisplay	lblComplianceAdditivesMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Additives"
AllergensContainedDisplay	lblctlComplianceAllergens	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
AllergensNotContDisplay	lblComplianceAllergensNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
AllergensMayContDisplay	lblComplianceAllergensMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Allergens"
ApprovedForUseBUDisplayName	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService"
AssociatedSpecAssocDisplay	lblAssociatedSpecAssociation	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2147 display"
AssociatedSpecERPIDDisplayName	lblAssociatedSpecERPID	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSMLib\$2147 display"

Data Field	Data Field Caption	Notes
AssociatedSpecNameDisplay	lblAssociatedSpecName	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSM Lib\$2147 display"
AssociatedSpecNumberDisplay	lblAssociatedSpecNumber	isAggregatable="true" enableHandler="Class:Xeno.Prodika.GSMLib.EQTSearchablePropertyHandlers.AssocSpecConfigPropertyItemEnabledResolverFactory,GSM Lib\$2147 display"
Brand	lblBrand	
CompliesWithDisplay	lblctlComplianceCompliesWith	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReports Lib\$CompliesWith"
ConceptDisplay	lblConcept	dataTransformer="Class:Xeno.Prodika.EQTSservice.DataTransformers.TaxonomyAliasDataColumnTransformerFactory,EQTService\$FoodserviceConcept" isAggregatable="true"
CountriesWhereUsedDisplayName	lblCountriesWhereUsed	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.CountryDataColumnTransformerFactory,EQTService" isAggregatable="true"
CountryOfOriginDisplay	lblCountryOfOrigin	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.CountryDataColumnTransformerFactory,EQTService"
Created	lblCreated	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.GSMContextSensitiveEquivalentDataTransformerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTSservice.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$GSM.EQT.CrossReferences.Enabled"
CurrentStatus	lblSpecSummaryStatus	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.WorkflowStatusDataColumnTransformerFactory,EQTService"
CurrentWorkflowGroup	lblCurrentWorkFlowGroup	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.Transformers.CurrentWorkflowGroupDataColumnTransformerFactory,ReadyReportsLib" isAggregatable="true"
CurrentWorkflowOwner	lblCurrentWorkFlowOwner	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.UserNameDataColumnTransformerFactory,FICService" isAggregatable="true"
Effective	lblSpecSummaryEffective	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
GtinUpcNumber	lblGTINUPC	
IngredientStatement	lblNutrientProfileIngredientStatement	

Data Field	Data Field Caption	Notes
IntolerancesContainedDisplay	lblctlComplianceIntolerances	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Intolerances"
IntolerancesNotContDisplay	lblComplianceIntolerancesNotContained	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Intolerances"
IntolerancesMayContDisplay	lblComplianceIntolerancesMayContain	isAggregatable="true" dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$Intolerances"
ItemType	lblItemType	
LastEdit	lblLastEdited	dataFormatter="Singleton:Xeno.Prodika.EQTServive.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServive.MostRecentlyUsedItemObjectEnabledResolverFactory\$2147"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
PotentialClaimsDisplayName	lblPotentialLabelClaims	isAggregatable="true"
RichTextDocKeywordsDisplay	lblRichTextDocKeywords	isAggregatable="true"
SDMAAttachmentDisplay	lblAttachmentName	isAggregatable="true"
SegmentName	SegmentName lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
ShortName	lblSpecShortName	
SourcingNumberSpec	lblSourcingNumber	isAggregatable="true"
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	
SpecStatus	lblSpecSummaryStatus	
SupercedesLangAware	lblSupercedes	
SystemEquivalentDisplay	lblSysEquivCtlEquivalent	isAggregatable="true"
SystemNameDisplayName	lblSystemName	isAggregatable="true"
Taxonomy	lblTaxonomy	
UDEXClassificationDisplayName	lblUDEXClassification	
WorkflowName	lblWorkflow	

NPD

Innovations/Sales Pipeline

View: NPDIdeaView

Model: Ideas

Data Field	Data Field Caption	Notes
AdminsCaption	lblAdmins	
BusinessUnitsDisplayName	lblBusinessUnit	isAggregatable="true"
InternalProjectNumber	lblInternalProjectNumber	
MRUWeight	lblMRUWeight	lblMRUWeight enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$3410"
RequestDate	lblRequestDate	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
StatusName	lblStatus	
Title	lblTitle	

Project

View: ProjectView

Model: Projects

Data Field	Data Field Caption	Notes
BrandDisplayName	lblBrands	
BusinessUnitsDisplayName	lblExactMatchBU	
Description	lblDescription	
DevelopmentStageTitle	lblDevelopmentStageTitle	
InternalProjectNumber	lblInternalProjectNumber	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$3202"
OriginationDate	lblOriginationDate	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"

Data Field	Data Field Caption	Notes
Private	lblPrivate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.DataFormatters.BooleanTypeFormatVal ueDelegateFactory,PlatformExtensions"
ProjectNumber	lblProjectNumber	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
StatusName	lblStatus	
StrategicBriefTitle	lblStrategicBriefTitle	
TeamLeadersCaption	lblTeamLeaders	
Title	lblTitle	

Strategic Brief

View: StrategicBriefView

Model: Strategic Briefs

Data Field	Data Field Caption	Notes
BrandDisplayName	lblBrands	isAggregatable="true"
BusinessUnitsDisplayName	lblBusinessUnit	isAggregatable="true"
ChannelDisplayName	lblChannels	isAggregatable="true"
CountriesDisplayName	lblLeadCountries	isAggregatable="true"
GlobalCategoriesDisplayName	lblGlobalCategories	isAggregatable="true"
KeySponsorsDisplayName	lblKeySponsors	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService" isAggregatable="true"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$3211"
OriginationDate	lblOriginationDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
StatusName	lblStatus	
StrategicBriefNumber	lblStrategicBriefNumber	
Title	lblTitle	

NSM

Nutrient Analysis

View: NutrientAnalysisMainView

Model: Nutrient Analysis

Data Field	Data Field Caption	Notes
analysisDate_View	lblDateOfAnalysis	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
AnalysisNumber	lblAnalysisNumber	
ApprovedForUseBU	lblApprovedUsageBU	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.BusinessUnitDataC olumnTransformerFactory,EQTService"
Composites	lblComposites	dataTransformer="Singleton:Xeno.Prodika.NS MLib.EQT.NSMCompositeNumberTransforme rFactory,NSMLib" isAggregatable="true" aggregationDelimiter=", "
Description	lblDescription	
GTINUPC	lblGTINUPC	
LastUpdated	lblLastUpdated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$6152"
ReceivedFromLab	lblReceivedFromLab	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
SampleNumber	lblSampleNumber	
SampleType	lblSampleType	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter=", " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
SentToLab	lblSentToLab	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
SourceFacilityDisplay	lblSourceFacility	dataTransformer="Singleton:EQTModels.Busin essUnitSecurity.BUSecuredFacilityNameDataC olumnTransformerFactory,EQTModels"
SpecName	lblSpecName	

Nutrient Composite

View: NutrientCompositeView

Model: Nutrient Composites

Data Field	Data Field Caption	Notes
ApprovedForUseBU	lblApprovedUsageBU	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.BusinessUnitDataC olumnTransformerFactory,EQTService"
CompositeDate_View	lblDateOfComposite	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
CompositeNumber	lblCompositeNumber	
LastUpdated	lblLastUpdated	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$6150"
OriginatorDisplay	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels\$UGMUser"
SpecName	lblSpecName	
Title	lblTitle	

PQM

Action

View: PQMActionView

Model: PQM Actions

Data Field	Data Field Caption	Notes
AffectedItemsEquvDisplay	lblAffectedItemsEquivalent	isAggregatable="true"
AffectedItemsNonRevDisplay	lblAffectedItemsRevisionIndependent	isAggregatable="true" aggregationDelimiter=","
AffectedItemsWithRevDisplay	lblAffectedItemsWithRevision	isAggregatable="true" aggregationDelimiter=","
AssociatedProjectDisplay	lblAssociatedProject	

Data Field	Data Field Caption	Notes
CompanyDisplay	lblCompany	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredCompanyNameDataColumnTransformerFactory,EQTModels" isAggregatable="true"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.PQMContextSensitiveEquivalentDataTransormerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTService.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$PQM.EQT.CrossReferences.Enabled"
CustomerDisplay	lblCustomer	dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$PQMCustomers" isAggregatable="true" enableHandler="Class:EQTModels.Common.HideToSupplierFeaturePropertyItemEnabledResolverFactory,EQTModels\$!PQM.Customers.HiddenToSupplier.Enabled"
FacilityDisplay	lblFacility	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels" isAggregatable="true" aggregationDelimiter=","
ItemNumber	lblActionNumber	
LastEditedDate	lblLastEditDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$7003"
Originated	lblOriginationDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
Originator	lblOriginator	dataTransformer="Singleton:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.UserSupplierNameDataColumnTransformerFactory,ReadyReportsLib"
ProductLinesDisplay	lblProductLines	dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$PQMProductLines" isAggregatable="true" enableHandler="Class:EQTModels.Common.HideToSupplierFeaturePropertyItemEnabledResolverFactory,EQTModels\$!PQM.ProductLines.HiddenToSupplier.Enabled"
PQMActionType	lblPQMActionType	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.KeyValLookupItemDataColumnTransformerFactory,EQTService\$PQMActionTypes"
PQMDescription	lblPQMDescription	
PQMStatus	lblStatus	
PQMTitle	lblProblemStatement	

Data Field	Data Field Caption	Notes
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels"

Audit

View: PQMAuditView

Model: PQM Audits

Data Field	Data Field Caption	Notes
ActualAuditDate	lblActualAuditDate	dataFormatter="Singleton:Xeno.Prodika.EQTS er vice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
AffectedItemsEquvDisplay	lblAffectedItemsEquivalent	isAggregatable="true"
AffectedItemsNonRevDisplay	lblAffectedItemsRevisionIndependent	dataTransformer="Class:Xeno.Prodika.Services.PQM.DataTransformers.AffectedItemSpecNumberNoRevDataColumnTransformerFactory,PQMLib\$7004"
AffectedItemsWithRevDisplay	lblAffectedItemsWithRevision	dataTransformer="Singleton:Xeno.Prodika.Services.PQM.DataTransformers.AffectedItemSpecNumberWithRevDataColumnTransformerFactory,PQMLib"
AuditResult	lblAuditResult	dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$PQMAuditResults"
CompanyDisplay	lblCompany	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredCompanyNameDataColumnTransformerFactory,EQTModels" isAggregatable="true"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.PQMContextSensitiveEquivalentDataTransormerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTS er vice.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$PQM.EQT.CrossReferences.Enabled"
CustomerDisplay	lblCustomer	dataTransformer="Class:Oracle.PLM4P.ReadyReports.Lib.DataColumnTransformers.LookupDataColumnTransformerFactory,ReadyReportsLib\$PQMCustomers" isAggregatable="true" enableHandler="Class:EQTModels.Common.HideToSupplierFeaturePropertyItemEnabledResolverFactory,EQTModels\$!PQM.Customers.HiddenToSupplier.Enabled"
FacilityDisplay	lblFacility	dataTransformer="Singleton:Xeno.Prodika.Services.PQM.DataTransformers.PQMItemBUSecuredFacilityNameDataColumnTransformerFactory,PQMLib"

Data Field	Data Field Caption	Notes
ItemNumber	lblAuditNumber	
LastEditedDate	lblLastEditDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$7004"
Originated	lblOriginationDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Originator	lblOriginator	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.DataColumnTransformers.User SupplierNameDataColumnTransformerFactory, ReadyReportsLib"
PlannedAuditDate	lblPlannedAuditDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
PQMAuditType	lblPQMAuditType	dataTransformer="Class:Xeno.Prodika.EQTser vice.DataTransformers.KeyValLookupItemDat aColumnTransformerFactory,EQTService\$PQ MAuditTypes"
PQMDescription	lblPQMDescription	
PQMStatus	lblStatus	
PQMTitle	lblProblemStatement	
ProductLinesDisplay	lblProductLines	dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$PQMProductLines" isAggregatable="true" enableHandler="Class:EQTModels.Common.H ideToSupplierFeaturePropertyItemEnabledReso lverFactory,EQTModels\$!PQM.ProductLines.H iddenToSupplier.Enabled"
RelatedActionsDisplay	lblRelatedActions	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.DataColumnTransformers.PQM NameDataColumnTransformerFactory,ReadyR eportsLib"
RelatedIssuesDisplay	lblRelatedIssues	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.DataColumnTransformers.PQM NameDataColumnTransformerFactory,ReadyR eportsLib"
SegmentName	SegmentName lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="", " enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels"

Issue

View: PQMIssueView

Model: PQM Issues

Data Field	Data Field Caption	Notes
AffectedItemsEquvDisplay	lblAffectedItemsEquivalent	isAggregatable="true"
AffectedItemsNonRevDisplay	lblAffectedItemsRevisionIndependent	isAggregatable="true" aggregationDelimiter=", "
AffectedItemsWithRevDisplay	lblAffectedItemsWithRevision	isAggregatable="true" aggregationDelimiter=", "
CompanyDisplay	lblCompany	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredCompanyNameDataColumnTransformerFactory,EQTModels" isAggregatable="true"
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTS ervice.DataTransformers.PQMContextSensitiveEquivalentDataTransormerFactory,Platform Extensions" enableHandler="Class:Xeno.Prodika.EQTServi ce.SearchablePropertyHandlers.FeatureProperty ItemEnabledResolverFactory,EQTSservice\$PQ M.EQT.CrossReferences.Enabled"
CustomerDisplay	lblCustomer	dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$PQMCustomers" isAggregatable="true" enableHandler="Class:EQTModels.Common.H ideToSupplierFeaturePropertyItemEnabledReso lverFactory,EQTModels\$!PQM.Customers.Hid denToSupplier.Enabled"
Disposition	lblDisposition	dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$PQMIssueDispositions"
ExpectedResolutionDate	lblExpectedResolutionDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTSservice"
FacilityDisplay	lblFacility	dataTransformer="Singleton:EQTModels.Busin essUnitSecurity.BUSecuredFacilityNameDataC olumnTransformerFactory,EQTModels" isAggregatable="true" aggregationDelimiter=", "
ItemNumber	lblIssueNumber	
LastEditedDate	lblLastEditDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTSservice"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$7002"

Data Field	Data Field Caption	Notes
OccurrenceDate	lblOccurrenceDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Originated	lblOriginationDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
Originator	lblOriginator	dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.DataColumnTransformers.User SupplierNameDataColumnTransformerFactory, ReadyReportsLib"
PQMDescription	lblPQMDescription	
PQMIssueType	lblPQMIssueType	dataTransformer="Class:Xeno.Prodika.EQTSe rvice.DataTransformers.KeyValLookupItemDat aColumnTransformerFactory,EQTService\$PQ MIssueTypes"
PQMStatus	lblStatus	
PQMTitle	lblProblemStatement	
ProductLinesDisplay	lblProductLines	dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$PQMProductLines" isAggregatable="true" enableHandler="Class:EQTModels.Common.H ideToSupplierFeaturePropertyItemEnabledReso lverFactory,EQTModels\$!PQM.ProductLines.H iddenToSupplier.Enabled"
RelatedActionsDisplay	lblRelatedActions	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.DataColumnTransformers.PQM NameDataColumnTransformerFactory,ReadyR eportsLib"
RelatedAuditsDisplay	lblRelatedAudits	isAggregatable="true" dataTransformer="Singleton:Oracle.PLM4P.Re adyReports.Lib.DataColumnTransformers.PQM NameDataColumnTransformerFactory,ReadyR eportsLib"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.S egmentPropertyItemWithUserTypeEnabledRes olverFactory,EQTModels"
Severity	lblSeverity	dataTransformer="Class:Oracle.PLM4P.Ready Reports.Lib.DataColumnTransformers.Lookup DataColumnTransformerFactory,ReadyReports Lib\$PQMIssueSeverities"

PQS

Lot Sample

View: LotSampleView

Model: Samples

Data Field	Data Field Caption	Notes
CreationDate	lblCreationDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateFormat ValueDelegateFactory,EQTService"
GTINUPCEAN	lblGTINUPCEAN	
InternalAlias	lblInternalAlias	
InternalSampleID	lblSampleNumber	
LogReceivingNumber	lblLogReceivingNumber	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$5270"
ProductionDate	lblManufactureDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
ReceivingDate	lblDateRcvd	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
ReceivingFacilityNameDisplay	lblReceivingFac	
SampleLocation	lblLocation	
SampleNotes	lblNotes	
SampleNumber	lblCodeDate	
SampleTypeDisplay	lblSampleType	
SessionLocationDisplay	lblSrcFacilityCountry	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.CountryDataColum nTransformerFactory,EQTService"
SourceFacilityName	lblSourceFacility	
SpecName	lblSpecName	
SpecNameNumber	lblSpecNameNumber	
SpecNumber	lblSpecNumber	
TestScheduledDate	blScheduledEvaluationDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
UseThroughDate	lblUseThroughDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService"
WayBill	lblWayBill	

Session

View: SessionView

Model: Sessions

Data Field	Data Field Caption	Notes
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5271"
SessionEvaluationDate	lblEvaluationDate	dataFormatter="Singleton:Xeno.Prodika.EQTSERVICE.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTSERVICE"
SessionLeaderDisplay	lblSessionLeader	
SessionLocationDisplay	lblLocation	
SessionName	lblSessionName	
SessionNumber	lblSessionNumber	

Scorecard

View: ScorecardView

Model: Scorecards

Data Field	Data Field Caption	Notes
OriginatorDisplay	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQTSERVICE.DataTransformers.UserNameDataColumnTransformerFactory,FICSERVICE"
Sample	lblSample	
SampleNumberDisplay	lblSample	
Score	lblScore	
ScorecardNumber	lblScorecardNumber	
ScoredByName	lblScoredBy	
ScoredDate	lblScoredDate	dataFormatter="Singleton:Xeno.Prodika.EQTSERVICE.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTSERVICE"
SpecName	lblSpecName	
SpecSumSpecName	lblSpecName	

SCRM

Company

View: CompanyMainSearchViewSingleSelectAlias

Model: Companies

Data Field	Data Field Caption	Notes
AltSpecSupplyCapDisplayName	lblAltSpecSupplyCap	isAggregatable="true"
ApprovedForUseBUDisplayName	lblApprovedUsageBU	isAggregatable="true"
City	lblCityName	
CompanyName	lblCompanyName	
CompanyNumber	lblCompanyNumber	
CompanyStatusDisplayName	lblCompanyStatus	
CompanyCountryDisplayName	lblCountry	
ContactProfileLastName	lblContactProfileLastName	
ContactProfileFirstName	lblContactProfileFirstName	
ContactProfileUserName	lblContactProfileUserName	
CountryName	lblCountryName	
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.SCRMContextSensitiveEquivalentDataTransformerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTService.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$SCRM.EQT.CrossReferences.Enabled"
EquivalentDisplay	lblSystemEquivalent	isAggregatable="true"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5002"
PostalCode	lblPostalCode	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels"
SpecAttributesDisplayName	lblSpecialAttributes	isAggregatable="true"
StateProvince	lblStateProvince	

Company/Facility SDM

View: ManagedDocumentMultiSelect

Model: Supporting Docs - Company/Facility

Data Field	Data Field Caption	Notes
DocParentStOrProvName	lblStateProvince	
DocTypeNameDisplay	lblDocumentType	enableHandler="Class:Xeno.Prodika.Config.SDMFeatureEnabledResolverFactory,PlatformExtensions\$DocumentType 5001,5002"
DocumentBusinessUnitDisplay	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTS TService.DataTransformers.BusinessUnitDataC olumnTransformerFactory,EQTSservice">
DocCompanyStatusDisplay	lblParentStatus	
DocumentDescription	lblDescription	
DocumentEffectiveDateDisplay	lblEffectiveDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTSservice" enableHandler="Class:Xeno.Prodika.Config.SD MFeatureEnabledResolverFactory,PlatformExte nsions\$EffectiveDate 5001,5002"
DocumentExpirationDateDisplay	lblExpirationDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTSservice" enableHandler="Class:Xeno.Prodika.Config.SD MFeatureEnabledResolverFactory,PlatformExte nsions\$ExpirationDate 5001,5002"
DocumentParentCityName	lblCity	
DocumentParentCountryName	lblCountryName	
DocumentParentName	lblCompanyFacility	
DocumentParentPostalCode	lblPostalCode	
DocumentRequiredDateDisplay	lblRequiredDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTSservice" enableHandler="Class:Xeno.Prodika.Config.SD MFeatureEnabledResolverFactory,PlatformExte nsions\$DueDate 5001,5002"
ManagedDocStatusDisplay	lblStatus	enableHandler="Class:Xeno.Prodika.Config.SD MFeatureEnabledResolverFactory,PlatformExte nsions\$Status 5001,5002"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$2231_5001,2231_5002"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.UserNameDataCol umnTransformerFactory,FICService"

Data Field	Data Field Caption	Notes
ParentFacility	lblCompany	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityCompanyNameDataColumnTransformerFactory,EQTModels"
ParentFacility	lblFacility	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels"

Facility

View: FacilityMainSearchViewSingleSelect

Model: Facilities

Data Field	Data Field Caption	Notes
AltSpecSupplyCapDisplayName	lblAltSpecSupplyCap	
ApprovedForUseBUDisplayName	lblApprovedUsageBU	isAggregatable="true"
City	lblCityName	
CompanyName	lblCompanyName	
ContactProfileFirstName	lblContactProfileFirstName	
ContactProfileLastName	lblContactProfileLastName	
CountryName	lblCountryName	
ctxSysEquiv	lblPreferredEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.SCRMContextSensitiveEquivalentDataTransformerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTService.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$SCRM.EQT.CrossReferences.Enabled"
FacilityName	lblFacilityName	
FacilityNumber	lblFacilityNumber	
FacilityStatusDisplayName	lblFacilityStatus	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5001"
PostalCode	lblPostalCode	
SpecAttributesDisplayName	lblSpecialAttributes	isAggregatable="true"
SpecEquivSourcedDisplay	lblSpecEquivSourced	isAggregatable="true"
SpecNumSourcedDisplay	lblSpecNumSourced	isAggregatable="true"
StateProvince	lblStateProvince	
SystemEquivalent	lblSystemEquivalent	isAggregatable="true"

Data Field	Data Field Caption	Notes
UsedInFacilityPKIDDisplay	lblUsedIn	dataTransformer="Singleton:EQTModels.BussUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels" isAggregatable="true"
VendorMaterialNumberDisplay	lblFacilitySACIngNum	isAggregatable="true"

Contact

View: ContactProfileView

Model: Contact Profiles

Data Field	Data Field Caption	Notes
AssociatedCompanyDisplay	lblAssociatedCompany	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.SupplierAssociatedCompanyNamesDataTransformerFactory,PlatformExtensions"
AssociatedFacilityDisplay	lblAssociatedFacility	dataTransformer="Singleton:Xeno.Prodika.EQTSservice.DataTransformers.SupplierAssociatedFacilityNamesDataTransformerFactory,PlatformExtensions"
CompanyName	lblCompanyName	
CompanyTelephone	lblCompanyTelephone	
Email	lblEmailAddress	
FirstName	lblFirstName	
JobTitle	lblJobTitle	
LastLoginDateDisplay	lblLastLoginDate	dataFormatter="Singleton:Xeno.Prodika.EQTSservice.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService"
LastName	lblLastName	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5351"
Name	lblLoginName	
RepTelephone	lblRepTelephone	
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels\$UGMUser"
UserStatus	lblUserStatus	

Non-Spec Sourcing Approval

View: SourcingApprovalNonSpecView

Model: Non-Spec Sourcing Approvals

Data Field	Data Field Caption	Notes
CompanyName	lblCompanyName	
Description	lblDescription	
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5019"
QAAssignedDisplay	lblQAAssigned	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
SACDescription	lblNotes	
SACStatus	lblStatus	
SCAssignedDisplay	lblSCAssigned	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService" isAggregatable="true"
SegmentName	lblSegmentNameProperty	
SourcingClass	lblClass	
SourcingFacilityPKID	lblSourcingFacility	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels"
SourcingNumber	lblSourcingNumber	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels"
SourcingTypeDisplay	lblType	isAggregatable="true" aggregationDelimiter="," dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.SourcingTypeDataTransformerFactory,PlatformExtensions"
UsedInFacilityPKIDDisplay	lblReceivingFac	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels" isAggregatable="true" aggregationDelimiter=","

Spec Related Sourcing Approval

View: SourcingApprovalView

Model: Spec-Related Sourcing Approvals

Data Field	Data Field Caption	Notes
ApprovedForUseBUDisplay	lblApprovedUsageBU	isAggregatable="true"
ApprovedForUseCptDisplay	lblApprovedUsageConcept	dataTransformer="Class:Xeno.Prodika.EQTService.DataTransformers.TaxonomyAliasDataColumnTransformerFactory,EQTService\$FoodserviceConcept" isAggregatable="true"
AssignedReferenceDisplay	lblAssignedReference	
CompanyName	lblCompanyName	
ctxSysEquivDisplay	lblSpecEquivalent	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.ContextSensitiveSACEquivalentDataTransformerFactory,PlatformExtensions" enableHandler="Class:Xeno.Prodika.EQTService.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$GSM.EQT.CrossReferences.Enabled"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5012"
QAAssignedDisplay	lblQAAssigned	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
SACDescription	lblNotes	
SACStatus	lblStatus	
SCAssignedDisplay	lblSCAssigned	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService" isAggregatable="true"
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter="," enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels"
SourcingClass	lblClass	
SourcingFacilityPKID	lblSourcingFacility	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels"
SourcingNumber	lblSourcingNumber	
SourcingTypeDisplay	lblType	isAggregatable="true" aggregationDelimiter="," dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.SourcingTypeDataTransformerFactory,PlatformExtensions"
SpecName	lblSpecName	
SpecNumber	lblSpecNumber	

Data Field	Data Field Caption	Notes
SpecTaxonomyDisplay	lblSpecificationTaxonomy	
SupplierPartNumber	lblSupplierItemNumber	
UsedInFacilityPKIDDisplay	lblReceivingFac	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels" isAggregatable="true" aggregationDelimiter=","

Non-Spec Sourcing Approval SDM

View: ManagedDocumentMultiSelect

Model: Supporting Docs - Non-Spec SAC

Data Field	Data Field Caption	Notes
DocParentStOrProvName	lblStateProvince	
DocTypeNameDisplay	lblDocumentType	enableHandler="Class:Xeno.Prodika.Config.SDMFeatureEnabledResolverFactory,PlatformExtensions\$DocumentType 5019"
DocumentBusinessUnitDisplay	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService">
DocumentEffectiveDateDisplay	lblEffectiveDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService" enableHandler="Class:Xeno.Prodika.Config.SDMFeatureEnabledResolverFactory,PlatformExtensions\$EffectiveDate 5019"
DocumentExpirationDateDisplay	lblExpirationDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService" enableHandler="Class:Xeno.Prodika.Config.SDMFeatureEnabledResolverFactory,PlatformExtensions\$ExpirationDate 5019"
DocumentRequiredDateDisplay	lblRequiredDate	dataFormatter="Singleton:Xeno.Prodika.EQTService.FormatValueDelegates.ShortDateCharMonthFormatValueDelegateFactory,EQTService" enableHandler="Class:Xeno.Prodika.Config.SDMFeatureEnabledResolverFactory,PlatformExtensions\$DueDate 5019"
DocCompanyStatusDisplay	lblParentStatus	
DocumentDescription	lblDescription	
DocumentParentCityName	lblCity	
DocumentParentCountryName	lblCountryName	
DocumentParentName	lblCompanyFacility	
DocumentParentPostalCode	lblPostalCode	

Data Field	Data Field Caption	Notes
ManagedDocStatus	lblStatus	enableHandler="Class:Xeno.Prodika.Config.SDMFeatureEnabledResolverFactory,PlatformExtensions\$Status\$5019"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$2231_5019"
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
ParentCompany	lblCompany	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityCompanyNameDataColumnTransformerFactory,EQTModels"
ParentFacility	lblFacility	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels"

Spec Sourcing Approval SDM

View: ManagedDocumentMultiSelect

Model: Supporting Docs - Spec-Related SAC

Data Field	Data Field Caption	Notes
DocParentStOrProvName	lblStateProvince	
DocTypeNameDisplay	lblDocumentType	enableHandler="Class:Xeno.Prodika.Config.SDMFeatureEnabledResolverFactory,PlatformExtensions\$DocumentType 5012"
DocumentBusinessUnitDisplay	lblBusinessUnit	isAggregatable="true" dataTransformer="Singleton:Xeno.Prodika.EQTS ervice.DataTransformers.BusinessUnitDataC olumnTransformerFactory,EQTService">"
DocCompanyStatusDisplay	lblParentStatus	
DocumentDescription	lblDescription	
DocumentEffectiveDateDisplay	lblEffectiveDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService" enableHandler="Class:Xeno.Prodika.Config.SDM FeatureEnabledResolverFactory,PlatformExt ensions\$EffectiveDate 5012"
DocumentExpirationDateDisplay	lblExpirationDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService" enableHandler="Class:Xeno.Prodika.Config.SDM FeatureEnabledResolverFactory,PlatformExt ensions\$ExpirationDate 5012"
DocumentParentCityName	lblCity	
DocumentParentCountryName	lblCountryName	
DocumentParentName	lblCompanyFacility	
DocumentParentPostalCode	lblPostalCode	
DocumentRequiredDateDisplay	lblRequiredDate	dataFormatter="Singleton:Xeno.Prodika.EQTS ervice.FormatValueDelegates.ShortDateCharM onthFormatValueDelegateFactory,EQTService" enableHandler="Class:Xeno.Prodika.Config.SDM FeatureEnabledResolverFactory,PlatformExt ensions\$DueDate 5012"
ManagedDocSpecSourcedTaxAlias	lblSpecSourcedTax	dataTransformer="Singleton:Xeno.Prodika.EQ TService.DataTransformers.SpecSummaryTaxo monyAliasDataColumnTransformerFactory,EQ TService"
ManagedDocStatus	lblStatus	enableHandler="Class:Xeno.Prodika.Config.SDM FeatureEnabledResolverFactory,PlatformExt ensions\$Status 5012"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUServ ice.MostRecentlyUsedItemObjectEnabledResol verFactory\$2231_5012"

Data Field	Data Field Caption	Notes
Originator	lblOriginator	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.UserNameDataColumnTransformerFactory,FICService"
ParentCompany	lblCompany	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredParentCompanyNameDataColumnTransformerFactory,EQTModels"
ParentFacility	lblFacility	dataTransformer="Singleton:EQTModels.BusinessUnitSecurity.BUSecuredFacilityNameDataColumnTransformerFactory,EQTModels"
SpecEquivSourced	lblSpecEquivSourced	
SpecNamePlusNum	lblSpecName	
SpecNumSourced	lblSpecNumSourced	

UGM

Group

View: GroupView

Model: Group Profiles

Data Field	Data Field Caption	Notes
CanonicalName	lblGroupCanonicalNameProperty	
Description	lblGroupDescriptionProperty	
LastUpdatedLookupKey	lblLastUpdated	dataTransformer="Singleton:Xeno.Prodika.Services.PrincipalManagementService.EQT.DataTransformers.LastUpdatedDCTransformerForGroupFactory,PrincipalManagementService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$2055"
Name	lblGroupNameProperty	
GroupStatusDisplay	lblStatus	dataFormatter=?Singleton:Oracle.PLM4P.ReadyReports.Lib.DataFormatters.StatusIntValueFormatterFactory,ReadyReportsLib"
RoleNameDisplay	lblGroupRoleNameProperty	isAggregatable="true"
TagNameDisplay	lblGroupWorkflowTags	isAggregatable="true"
UserNameDisplay	lblGroupUserNameProperty	isAggregatable="true"

User

View: UserView

Model: User Profiles

Data Field	Data Field Caption	Notes
AddressState	lblAddressStateProperty	
AffiliateName	lblAffiliateNameProperty	enableHandler="Class:Xeno.Prodika.EQTService.SearchablePropertyHandlers.FeaturePropertyItemEnabledResolverFactory,EQTService\$Common.EQT.UserView.AffiliateName.Enabled"
CountryNameDisplay	lblUserCountryNameProperty	
EmailAddress	lblUserEmailProperty	
FacilityName	lblUserFacilityNameProperty	
FirstName	lblFirstNameProperty	
GroupNameDisplay	lblUserGroupNameProperty	isAggregatable="true" aggregationDelimiter=", "
GSMBUDisplay	lblUserGSMBusinessUnits	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService" isAggregatable="true" aggregationDelimiter=", "
LastName	lblLastNameProperty	
LastUpdatedLookupKey	lblLastUpdated	dataTransformer="Singleton:Xeno.Prodika.Services.PrincipalManagementService.EQT.DataTransformers.LastUpdatedDCTransformerForUserFactory,PrincipalManagementService"
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$2053"
ProperUserName	lblUserFullName	
RoleNameDisplay	lblUserRoleNameProperty	isAggregatable="true" aggregationDelimiter=", "
SCRMBUDisplay	lblUserSCRMBusinessUnits	dataTransformer="Singleton:Xeno.Prodika.EQTService.DataTransformers.BusinessUnitDataColumnTransformerFactory,EQTService" isAggregatable="true" aggregationDelimiter=", "
SegmentName	lblSegmentNameProperty	isAggregatable="true" aggregationDelimiter=", " enableHandler="Class:EQTModels.Common.SegmentPropertyItemWithUserTypeEnabledResolverFactory,EQTModels"
Status	lblUserStatusProperty	
UserName	lblUserLoginName	

WFA

GSM Workflow Process Template

View: WorkflowProcessTemplateView

Model: GSM Workflows

Data Field	Data Field Caption	Notes
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5756_GSM"
ProcessTemplateDescription	lblDescription	
ProcessTemplateName	lblName	

PQM Workflow Process Template

View: WorkflowProcessTemplateView

Model: PQM Workflows

Data Field	Data Field Caption	Notes
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5756_PQM"
ProcessTemplateDescription	lblDescription	
ProcessTemplateName	lblName	

SCRM Workflow Process Template

View: WorkflowProcessTemplateView

Model: SCRM Workflows

Data Field	Data Field Caption	Notes
MRUWeight	lblMRUWeight	enableHandler="Class:Xeno.Prodika.MRUService.MostRecentlyUsedItemObjectEnabledResolverFactory\$5756_SCRM"
ProcessTemplateDescription	lblDescription	
ProcessTemplateName	lblName	

Best Practices

This appendix contains guidelines for using various reporting methods based on common tasks.

When to use Searching, Reporting, or Printing

Data Inquiry	Resolution
I want would like to search on all of my recently viewed items.	App Searches
I need to see all trade specifications in my business unit, and when I use searching in the application I only get 500 to return.	Queued Searches
When I am on a NPD project, I would like to have one-click access to all of the associated packaging specifications and their suppliers.	Ready Reports
A supplier needs to see all quality issues associated with their company through Supplier Portal.	Custom Report (Reporting UI)
I would like to review all incoming product issues, with the ability to drill down in a report to investigate and isolate related issues.	Custom Report – Direct Access
Once a quarter, purchasing would like to see all approved specifications by specification type with category and approved supplier.	Custom Report – Scheduled w/ email delivery
Supplier needs to view a specification they are approved to supply.	Printing – Supplier Portal

Searching vs Reporting vs Printing Scenarios

Scenario	Recommendation	Skills Needed
I would like to change specification printouts to emphasize certain data by bolding some items and changing font colors on others.	Update Print Template	XML
I would like to create a specification printout viewable by the public that includes a Nutrition Facts Panel.	Create a new BI Publisher report with a PDF output	SQL, BI Publisher knowledge
I would like to create a quality report for plant personnel, but I need to restrict the information on the report based on their PLM for Process access.	Create a BI Publisher report utilizing the Reporting UI	SQL, BI Publisher knowledge

Scenario	Recommendation	Skills Needed
I really like the reports in the eQ report packs, but I would like to change the chart types and add our company logo.	Use the same data model and copy and modify the existing report	BI Publisher knowledge
I would like for our purchasing group to see all formulations currently in development that are using this material.	Create a ready report	Ready Report

Reporting Tools Details

	Max Results	Custom Layout	Layout Editor	Data Options	Skills Required	Security
EQT Searches	500	Simple ²	No	Active Links & Export	XML ³	App
Ready Reports	500 ¹	Simple ²	No	Active Links & Export	XML ³	App
Queued Searching	Unlimited ⁵	Simple ²	Yes	Active Links & Export	None	App
Custom Reports (BI Publisher/SSRS)	Unlimited ⁵	Complex	Yes	Highly Interactive	None ⁴	Role Based, Custom
Printing	NA	Complex	No	Static	XSL-FO, XML, and C# ⁶	App

Notes

1. Max Results over 500 require a performance evaluation.
2. Additional columns only.
3. For adding new columns only.
4. SQL required to develop new data models.
5. Restricted by hardware configuration and/or limitation.
6. For custom handlers only.