

Name restart-domain – restarts the DAS of the specified domain

Synopsis restart-domain [--terse={false|true}] [--echo ={false|true}]
[--host *host*] [--port *admin-port*]
[--user *admin-user*] [--passwordfile *file-name*]

Description Use the restart-domain command to restart the Domain Administration Server (DAS) of the specified domain. The domain is specified through a combination of the --host option and the --port option. The domain must already be started.

The restart-domain command does not exit until the command has verified that the domain has been stopped and restarted.

A domain might be started with the verbose option of the start-domain(1) command set to true. In this situation, after the domain is restarted, messages continue to be displayed in the console window that was opened when the domain was originally started.

This command can be run in the remote mode only.

Options -t --terse

Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

-e --echo

Setting to true will echo the command line statement on to the standard output. Default is false.

-H --host

The machine name where the domain administration server is running. The default value is localhost.

-p --port

The HTTP port or HTTPS port for administration. This port is the port in the URL that you specify in your web browser to manage the domain, for example, `http://localhost:4848`.

The default port number for administration is 4848.

-u --user

The user name of the authorized administrative user of the domain administration server.

If you have authenticated to a domain by using the `asadmin login` command, you need not specify the --user option for subsequent operations on the domain.

--passwordfile

Specifies the name, including the full path, of a file that contains the password entries in a specific format.

The password is defined in the following form:

```
AS_ADMIN_PASSWORD=password
```

password is the actual administrator password for the domain.

Operands None.

Examples EXAMPLE 1 Using the restart-domain Command

This example shows the command for restarting a domain that is running on localhost and listens for administration requests on HTTP port 4848.

```
asadmin> restart-domain
Successfully restarted the domain
Command restart-domain executed successfully.
```

Exit Status 0 command executed successfully
 1 error in executing the command

See Also delete-domain(1), list-domains(1), start-domain(1), stop-domain(1)

