



GlassFish Server Open Source Edition 3.1 Quick Start Guide

Oracle Corporation
500 Oracle Parkway
Redwood City, CA 94065
U.S.A.

Part No: 821-2455-12
July 2011

Copyright © 2010, 2011, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Quick Start for Basic Features

GlassFish Server Open Source Edition provides a server for the development and deployment of Java Platform, Enterprise Edition (Java EE platform) applications and web technologies based on Java technology. GlassFish Server 3.1 provides the following:

- A lightweight and extensible core based on OSGi Alliance standards
- A web container
- An easy-to-use Administration Console for configuration and management
- Update Tool connectivity for updates and add-on components
- Support for high availability clustering and load balancing

The following topics are addressed here:

- [“About This Quick Start Guide” on page 3](#)
- [“Default Paths and File Names” on page 4](#)
- [“Default Administration Values” on page 5](#)
- [“Starting and Stopping the Default Domain” on page 6](#)
- [“Starting and Stopping the Database Server” on page 6](#)
- [“Starting the Administration Console” on page 7](#)
- [“Deploying and Undeploying Applications” on page 8](#)
- [“High Availability Clustering and Load Balancing” on page 13](#)
- [“Updating and Extending an Existing Installation” on page 14](#)
- [“Removing GlassFish Server 3.1 Software” on page 15](#)
- [“For More Information” on page 16](#)

About This Quick Start Guide

GlassFish Server Open Source Edition 3.1 Quick Start Guide demonstrates key features of the GlassFish Server product and enables you to quickly learn the basics. Step-by-step procedures introduce you to product features and enable you to use them immediately.

This guide assumes that you have already obtained and installed the GlassFish Server 3.1 software. For more information about installing GlassFish Server 3.1, see the *GlassFish Server Open Source Edition 3.1 Installation Guide*.

Instructions and examples in this guide that apply to all supported operating systems use the forward slash character (/) as path separators in all file names and commands. Ensure that you use the correct character for the system on which GlassFish Server is installed. For example:

- **UNIX, Linux, or Mac OS X systems:** *as-install/bin/asadmin*
- **Windows systems:** *as-install\bin\asadmin*

This guide provides basic information only. For comprehensive information about GlassFish Server and other entities mentioned in this guide, see [“For More Information” on page 16](#).

To review additional details about this release before you begin using the software, see the *GlassFish Server Open Source Edition 3.1-3.1.1 Release Notes*. The *Release Notes* provide important information about the GlassFish Server 3.1 release, including details about new features, information about known issues and possible workarounds, and tips for installing and working with GlassFish Server 3.1 software.

Default Paths and File Names

The following table describes the default paths and file names that are used in this book.

TABLE 1 Default Paths and File Names

Placeholder	Description	Default Value
<i>as-install</i>	Represents the base installation directory for GlassFish Server. In configuration files, <i>as-install</i> is represented as follows: <code>\${com.sun.aas.installRoot}</code>	Installations on the Oracle Solaris operating system, Linux operating system, and Mac OS operating system: <i>user's-home-directory/glassfish3/glassfish</i> Windows, all installations: <i>SystemDrive:\glassfish3\glassfish</i>
<i>as-install-parent</i>	Represents the parent of the base installation directory for GlassFish Server.	Installations on the Oracle Solaris operating system, Linux operating system, and Mac operating system: <i>user's-home-directory/glassfish3</i> Windows, all installations: <i>SystemDrive:\glassfish3</i>
<i>domain-root-dir</i>	Represents the directory in which a domain is created by default.	<i>as-install/domains/</i>

TABLE 1 Default Paths and File Names (Continued)

Placeholder	Description	Default Value
<i>domain-dir</i>	Represents the directory in which a domain's configuration is stored. In configuration files, <i>domain-dir</i> is represented as follows: \${com.sun.aas.instanceRoot}	<i>domain-root-dir/domain-name</i>

Default Administration Values

The following table lists default administration values for GlassFish Server. See [“Default Paths and File Names” on page 4](#) for more information about the *as-install* and *domain-dir* placeholders.

TABLE 2 Default Administration Values

Item	Default Value or Location
Domain name	domain1
Master password	changeit
asadmin(1M) command-line utility	<i>as-install</i> /bin
Configuration files	<i>domain-dir</i> /config
Log files	<i>domain-dir</i> /logs
Administration server port	4848
HTTP port	8080
HTTPS port	8181
Pure JMX clients port	8686
Message Queue port	7676
IIOP port	3700
IIOP/SSL port	3820
IIOP/SSL port with mutual authentication	3920

Starting and Stopping the Default Domain

When you install GlassFish Server, a default domain named `domain1` is created. The following procedures describe how to start and stop `domain1` when it is the only domain. For information about starting and stopping a domain when there are multiple domains, see Chapter 3, “Administering Domains,” in *GlassFish Server Open Source Edition 3.1 Administration Guide*.

▼ To Start the Default Domain

Before You Begin GlassFish Server software must be installed before you start the domain.

- **Run the `asadmin start-domain` command without an operand:**

`as-install/bin/asadmin start-domain`

The command starts the default domain, `domain1`.

▼ To Stop the Default Domain

- **Run the `asadmin stop-domain` command without an operand:**

`as-install/bin/asadmin stop-domain`

The command stops the default domain, `domain1`.

Tip – To determine whether a domain is running, use the `asadmin list-domains` command:

`as-install/bin/asadmin list-domains`

Starting and Stopping the Database Server

A database server is not started by default when you start the GlassFish Server domain. If your applications require a database back end, you must start and stop the database server manually.

The following procedures describe how to start and stop the Java DB server that is bundled with GlassFish Server. For information about starting and stopping other database servers, see the documentation for your specific product.

For the list of database products supported in this release, see the *GlassFish Server Open Source Edition 3.1-3.1.1 Release Notes*.

For more information about database connectivity, see Chapter 11, “Administering Database Connectivity,” in *GlassFish Server Open Source Edition 3.1 Administration Guide*.

▼ To Start the Java DB Server

Before You Begin At least one GlassFish Server domain must be started before you start the database server.

- **Run the `asadmin start-database` command.**

The general form for the command is as follows:

```
as-install/bin/asadmin start-database --dbhome directory-path
```

For example, to start the Java DB server from its default location:

```
as-install/bin/asadmin start-database --dbhome as-install-parent/javadb
```

▼ To Stop the Java DB Server

- **Run the `asadmin stop-database` command:**

```
as-install/bin/asadmin stop-database
```

Starting the Administration Console

The GlassFish Server Administration Console provides a browser interface for configuring, administering, and monitoring GlassFish Server.

▼ To Start the Administration Console

Before You Begin At least one GlassFish Server domain must be started.

- 1 **Type the URL in your browser.**

The default URL for the Administration Console on the local host is as follows:

```
http://localhost:4848
```

- 2 **If prompted, log in to the Administration Console.**

You will be prompted to log in if you chose to require an administration password at the time GlassFish Server was installed.

See Also For more information, see the Administration Console online help.

Deploying and Undeploying Applications

The process of configuring and enabling applications to run within the GlassFish Server framework is referred to as *deployment*.

This section explains how to deploy, list, and undeploy applications. The procedures in this section use the `hello.war` sample application. The following topics are addressed here:

- “To Obtain the Sample Application” on page 8
- “Deploying and Undeploying the Sample Application From the Command Line” on page 8
- “Deploying and Undeploying Applications by Using the Administration Console” on page 10
- “Deploying and Undeploying the Sample Application Automatically” on page 11

▼ To Obtain the Sample Application

- 1 Download a copy of the `hello.war` sample application from <http://glassfish.java.net/downloads/quickstart/hello.war>.
- 2 Save the `hello.war` file in the directory of your choice.

This directory is referred to as *sample-dir*.

Deploying and Undeploying the Sample Application From the Command Line

GlassFish Server provides `asadmin` subcommands for performing the following deployment-related tasks:

- “To Deploy the Sample Application From the Command Line” on page 8
- “To List Deployed Applications From the Command Line” on page 9
- “To Undeploy the Sample Application From the Command Line” on page 9

▼ To Deploy the Sample Application From the Command Line

Before You Begin

The sample application must be available before you start this task. To download the sample, see “To Obtain the Sample Application” on page 8. At least one GlassFish Server domain must be started before you deploy the sample application.

- 1 Run the `asadmin deploy` command.

The general form for the command is as follows:

`as-install/bin/asadmin deploy war-name`

To deploy the `hello.war` sample, the command is as follows:

```
as-install/bin/asadmin deploy sample-dir/hello.war
```

2 Access the `hello` application by typing the following URL in your browser:

`http://localhost:8080/hello`

The application's start page is displayed, and you are prompted to type your name.

Hi, my name is Duke. What's yours?

3 Type your name and click Submit.

The application displays a customized response, giving you a personal Hello.

See Also For more information about the `deploy` subcommand, see `deploy(1)`.

For more information about deploying applications from the command line, see *GlassFish Server Open Source Edition 3.1 Application Deployment Guide*.

▼ To List Deployed Applications From the Command Line

- **Run the `asadmin list-applications` command:**

```
as-install/bin/asadmin list-applications
```

▼ To Undeploy the Sample Application From the Command Line

- **Run the `asadmin undeploy` command.**

The general form for the command is as follows:

```
as-install/bin/asadmin undeploy war-name
```

For *war-name*, use the literal `hello`, not the full `hello.war` name.

For the `hello.war` example, the command is as follows:

```
as-install/bin/asadmin undeploy hello
```

See Also For more information about the `undeploy` subcommand, see `undeploy(1)`.

Deploying and Undeploying Applications by Using the Administration Console

The graphical Administration Console of GlassFish Server enables you to perform the following deployment-related tasks:

- [“To Deploy the Sample Application by Using the Administration Console” on page 10](#)
- [“To View Deployed Applications in the Administration Console” on page 11](#)
- [“To Undeploy the Sample Application by Using the Administration Console” on page 11](#)

▼ To Deploy the Sample Application by Using the Administration Console

Before You Begin

The sample application must be available before you start this task. To download the sample, see [“To Obtain the Sample Application” on page 8](#). At least one GlassFish Server domain must be started before you deploy the sample application.

- 1 Launch the Administration Console by typing the following URL in your browser:**
`http://localhost:4848`
- 2 Click the Applications node in the tree on the left.**
The Applications page is displayed.
- 3 Click the Deploy button.**
The Deploy Applications or Modules page is displayed.
- 4 Select Packaged File to be Uploaded to the Server, and click Browse.**
- 5 Navigate to the location in which you saved the `hello.war` sample, select the file, and click Open.**
You are returned to the Deploy Applications or Modules page.
- 6 Specify a description in the Description field, for example:**
`hello`
- 7 Accept the other default settings, and click OK.**
You are returned to the Applications page.
- 8 Select the check box next to the `hello` application and click the Launch link to run the application.**
The default URL for the application is as follows:
`http://localhost:8080/hello/`

See Also For more information, see the Administration Console online help.

▼ To View Deployed Applications in the Administration Console

- 1 Launch the Administration Console by typing the following URL in your browser:
`http://localhost:4848`
- 2 Click the Applications node in the tree on the left.
Expand the node to list deployed applications. Deployed applications are also listed in the table on the Applications page.

▼ To Undeploy the Sample Application by Using the Administration Console

- 1 Launch the Administration Console by typing the following URL in your browser:
`http://localhost:4848`
- 2 Click the Applications node in the tree on the left.
The Applications page is displayed.
- 3 Select the check box next to the `hello` sample application.
- 4 Remove or disable the application.
 - To remove the application, click the Undeploy button.
 - To disable the application, click the Disable button.

See Also For more information, see the Administration Console online help.

Deploying and Undeploying the Sample Application Automatically

GlassFish Server enables you to performing the following deployment-related tasks automatically:

- [“To Deploy the Sample Application Automatically” on page 12](#)
- [“To Undeploy the Sample Application Automatically” on page 12](#)

▼ To Deploy the Sample Application Automatically

You can deploy applications automatically by placing them in the *as-install/domains/domain-name/autodeploy* directory, where *domain-name* is the name of the domain for which you want to configure automatic deployment. For this example, use the default domain, *domain1*:

```
as-install/domains/domain1/autodeploy
```

Before You Begin The sample application must be available before you start this task. To download the sample, see [“To Obtain the Sample Application” on page 8](#).

● Copy the application WAR file to the *as-install/domains/domain-name/autodeploy* directory.

- On UNIX, Linux, and Mac OS X systems, type this command:

```
cp sample-dir/hello.war as-install/domains/domain-name/autodeploy
```

- On Windows systems, type this command:

```
copy sample-dir\hello.war as-install\domains\domain-name\autodeploy
```

GlassFish Server automatically discovers and deploys the application. The default URL for the application is as follows:

```
http://localhost:8080/hello/
```

▼ To Undeploy the Sample Application Automatically

- 1 Change to the domain's *autodeploy* directory.

```
cd as-install/domains/domain-name/autodeploy
```

- 2 Delete the sample application's WAR file to undeploy and remove the application.

- On UNIX, Linux, and Mac OS X systems, type this command:

```
rm hello.war
```

- On Windows systems, type this command:

```
del hello.war
```

High Availability Clustering and Load Balancing

GlassFish Server enables multiple GlassFish Server instances to be clustered to provide high availability through failure protection, scalability, and load balancing. The subsections that follow provide an overview of high availability clustering and load balancing for GlassFish Server.

Clusters of GlassFish Server Instances

A *cluster* is a collection of GlassFish Server instances that work together as one logical entity. A cluster provides a runtime environment for one or more Java Platform, Enterprise Edition (Java EE) applications. A cluster provides high availability through failure protection, scalability, and load balancing.

A GlassFish Server *instance* is a single Virtual Machine for the Java platform (Java Virtual Machine or JVM machine) on a single node in which GlassFish Server is running. A node defines the host where the GlassFish Server instance resides. The JVM machine must be compatible with the Java Platform, Enterprise Edition (Java EE).

GlassFish Server instances form the basis of an application deployment. An instance is a building block in the clustering, load balancing, and session persistence features of GlassFish Server. Each instance belongs to a single domain and has its own directory structure, configuration, and deployed applications. Every instance contains a reference to a node that defines the host where the instance resides.

For more information, see the following documentation:

- Chapter 3, “Administering GlassFish Server Nodes,” in *GlassFish Server Open Source Edition 3.1 High Availability Administration Guide*
- Chapter 4, “Administering GlassFish Server Clusters,” in *GlassFish Server Open Source Edition 3.1 High Availability Administration Guide*
- Chapter 5, “Administering GlassFish Server Instances,” in *GlassFish Server Open Source Edition 3.1 High Availability Administration Guide*

Session Persistence and Failover

Storing session state data enables the session state to be recovered after the failover of an instance in a cluster. Recovering the session state enables the session to continue without loss of information. GlassFish Server supports in-memory session replication on other servers in the cluster for maintaining HTTP session and stateful session bean data.

For more information, see Chapter 9, “Configuring High Availability Session Persistence and Failover,” in *GlassFish Server Open Source Edition 3.1 High Availability Administration Guide*.

Load Balancing for Clustered Configurations

GlassFish Server supports web server and hardware-based load balancing for clustered configurations. A load balancer is deployed with a cluster, and provides the following features:

- Allows an application or service to be scaled horizontally across multiple physical (or logical) hosts yet still present the user with a single URL
- Insulates the user from host failures or server crashes when used with session persistence
- Enhances security by hiding the internal network from the user

GlassFish Server Open Source Edition is compatible with the Apache HTTP server `mod_jk` module for load balancing.

GlassFish Server load balancing configurations can vary widely depending on the needs of your enterprise. For complete information about configuring load balancing in GlassFish Server, see the following documentation:

- Chapter 7, “Configuring HTTP Load Balancing,” in *GlassFish Server Open Source Edition 3.1 High Availability Administration Guide*
- Chapter 11, “RMI-IIOP Load Balancing and Failover,” in *GlassFish Server Open Source Edition 3.1 High Availability Administration Guide*

Updating and Extending an Existing Installation

GlassFish Server provides an administrative tool called Update Tool that enables you to install updates and add-on components to your existing GlassFish Server installation. Update Tool can be accessed as a standalone graphical tool from the command line or as a browser-based graphical tool from the Administration Console. For more information about Update Tool, see “Update Tool” in *GlassFish Server Open Source Edition 3.1 Administration Guide*.

▼ To Access the Graphical Update Tool From the Command Line

- **Run the `updatetool` command:**

`as-install-parent/bin/updatetool`

If Update Tool is not installed, you will be prompted to install it. Install the tool if desired, then use the `updatetool` command to start the tool. Extensive online help is available from the tool's Help menu.

See Also A command-line interface is also available for Update Tool. The command-line interface uses the `pkg` command and enables you to perform most of the tasks provided by the graphical

version. For more information about the `pkg` command, see Chapter 10, “Extending and Updating GlassFish Server,” in *GlassFish Server Open Source Edition 3.1 Administration Guide*.

▼ To Access Update Tool by Using the Administration Console

Before You Begin At least one GlassFish Server domain must be started before you launch the Administration Console.

- 1 **Launch the Administration Console by typing the following URL in your browser:**
`http://localhost:4848`
- 2 **Click the Update Tool node in the tree on the left.**

See Also For more information, see the Administration Console online help.

Removing GlassFish Server 3.1 Software

Before removing the GlassFish Server software, stop the following processes:

- All domains and other related processes
- Command prompts that use the installation directory or its subdirectories
- The Update Tool notifier process if present
- Any applications that use files that are part of the Java Platform, Standard Edition (Java SE)

For more information about performing these tasks, see Chapter 2, “Uninstalling GlassFish Server 3.1,” in *GlassFish Server Open Source Edition 3.1 Installation Guide*.

▼ To Remove GlassFish Server Software on UNIX, Linux, and Mac OS X Systems

- 1 **Change to the *as-install-parent* directory, which contains the uninstallation program.**
- 2 **If necessary, grant execute permissions to the uninstallation program file.**
`chmod +x ./uninstall.sh`
- 3 **Run the uninstallation program.**
`./uninstall.sh`

- 4 Examine the contents of the remaining installation directories and remove any files or directories that you do not want, including hidden directories prefixed with a dot.

▼ To Remove GlassFish Server Software on Windows Systems

- 1 Change to the *as-install-parent* directory, which contains the uninstallation program.
`uninstall.exe`
- 2 Run the uninstallation program.
- 3 Examine the contents of the remaining installation directories and remove any files or directories that you do not want, including hidden directories prefixed with a dot.

For More Information

Additional resources are available to help you learn more about GlassFish Server 3.1 and related technologies.

The following resources are described here:

- “Product Documentation” on page 16
- “GlassFish Communities” on page 17
- “Tutorials” on page 17
- “Java EE 6 Samples” on page 17

Product Documentation

Comprehensive product documentation is available and includes the following.

- *GlassFish Server Open Source Edition 3.1-3.1.1 Release Notes*: Latest details about new features, known issues, and tips for installing and working with GlassFish Server software.
- All-in-one documentation archive (available for download from the [GlassFish Server Open Source Edition - 3.1 Final](http://glassfish.java.net/downloads/3.1-final.html) (<http://glassfish.java.net/downloads/3.1-final.html>) page): Collection of guides that document GlassFish Server features and functions.
- [GlassFish Server Screencasts](http://wikis.sun.com/display/GlassFish/Screencasts+and+Other+Videos) (<http://wikis.sun.com/display/GlassFish/Screencasts+and+Other+Videos>): Collection of video recordings that demonstrate various features and provide examples for working with GlassFish Server and related technologies.
- [GlassFish Server FAQs](http://wikis.sun.com/display/GlassFish/GlassFishFAQIndex) (<http://wikis.sun.com/display/GlassFish/GlassFishFAQIndex>): Frequently asked questions covering a variety of GlassFish Server topics.

GlassFish Communities

The following resources will help you connect with other users, learn more about GlassFish Server, and get help if needed.

- **GlassFish Forum** (<http://www.java.net/forums/glassfish/glassfish>): Public online discussion forum that provides community support and tips for working with GlassFish Server.
- **GlassFish Wiki** (<http://wikis.sun.com/display/GlassFish>): Community site that provides a wide range of information related to GlassFish Server.
- **GlassFish Documentation Project** (<http://glassfish.java.net/docs/project.html>): Documentation community site that provides details about GlassFish Server documentation and how you can participate.
- **GlassFish Quality Community** (<http://glassfish.java.net/quality/portal>): Quality community site focused on testing and improving GlassFish Server.

Tutorials

The following tutorials provide working examples and detailed instructions for creating enterprise applications for the Java EE 6 platform.

- ***Your First Cup: An Introduction to the Java EE Platform***: Provides a short tutorial for beginning Java EE programmers that shows how to develop a simple enterprise application from scratch. The sample application consists of four main components: a JAX-RS RESTful web service, an enterprise bean, a Java Persistence API entity, and a web application created with JavaServer Faces Facelets technology.
- ***The Java EE 6 Tutorial***: Provides a beginner's guide to developing enterprise applications for GlassFish Server. The tutorial includes working examples and instructions for creating applications with Java EE 6 technologies, including Java Servlets, JavaServer Faces, Facelets, RESTful Web Services, Enterprise JavaBeans, Java Persistence API, Contexts and Dependency Injection for the Java EE platform, and more. The document is also available through Update Tool.

Java EE 6 Samples

The sample applications demonstrate Java EE 6 technologies. The samples are available through Update Tool and also as part of the Java EE 6 SDK distributions. The SDK distributions are available from the **Java EE downloads page** (<http://www.oracle.com/technetwork/java/javae/downloads/index.html>).

