

# asadmin commands list

## [8.1 EE CLI Commands -- Dev Page](#)

[\[a\]](#), [\[b\]](#), [\[c\]](#), [\[d\]](#), [\[e\]](#), [\[f\]](#), [\[g\]](#), [\[h\]](#), [\[i\]](#), [\[j\]](#), [\[k\]](#), [\[l\]](#), [\[m\]](#), [\[n\]](#), [\[o\]](#), [\[p\]](#), [\[q\]](#), [\[r\]](#), [\[s\]](#), [\[t\]](#), [\[u\]](#), [\[v\]](#), [\[w\]](#), [\[x\]](#), [\[y\]](#), [\[z\]](#), [\[Usage Text\]](#)

### A

[add-resources](#)

[apply-http-lb-changes](#)

[apply-repository-zip](#)

[top](#)

### B

[backup-domain](#)

[top](#)

### C

[change-admin-password](#)

[change-master-password](#)

[clear-ha-store](#)

[clear-status](#)

[configure-ha-cluster](#)

[configure-ha-persistence](#)

[configure-http-lb-config](#)

[configure-lb-weight](#)

[configure-webservice-management](#)

[copy-config](#)

[create-admin-object](#)

[create-admin-object-amx](#)

[create-application-ref](#)

[create-audit-module](#)

[create-auth-realm](#)

[create-cluster](#)

[create-connector-connection-pool](#)

[create-connector-resource](#)

[create-connector-resource-amx](#)

[create-connector-security-map](#)

[create-custom-resource](#)

[create-custom-resource-amx](#)

[create-domain](#)

[create-file-user](#)  
[create-ha-store](#)  
[create-http-health-checker](#)  
[create-http-lb](#)  
[create-http-lb-config](#)  
[create-http-lb-ref](#)  
[create-http-listener](#)  
[create-iiop-listener](#)  
[create-instance](#)  
[create-javamail-resource](#)  
[create-javamail-resource-amx](#)  
[create-jdbc-connection-pool](#)  
[create-jdbc-resource](#)  
[create-jdbc-resource-amx](#)  
[create-jms-host](#)  
[create-jms-resource](#)  
[create-jmsdest](#)  
[create-jndi-resource](#)  
[create-jndi-resource-amx](#)  
[create-jvm-options](#)  
[create-lifecycle-module](#)  
[create-management-rule](#)  
[create-mbean](#)  
[create-message-security-provider](#)  
[create-node-agent](#)  
[create-node-agent-config](#)  
[create-password-alias](#)  
[create-persistence-resource](#)  
[create-profiler](#)  
[create-repository-zip](#)  
[create-resource-adapter-config](#)  
[create-resource-adapter-config-amx](#)  
[create-resource-ref](#)  
[create-service](#)  
[create-ssl](#)  
[create-system-properties](#)  
[create-threadpool](#)  
[create-transformation-rule](#)  
[create-virtual-server](#)  
[top](#)

## D

[delete-admin-object](#)

[delete-admin-object-amx](#)

[delete-application-ref](#)

[delete-audit-module](#)

[delete-auth-realm](#)

[delete-cluster](#)

[delete-config](#)

[delete-connector-connection-pool](#)

[delete-connector-resource](#)

[delete-connector-resource-amx](#)

[delete-connector-security-map](#)

[delete-custom-resource](#)

[delete-custom-resource-amx](#)

[delete-domain](#)

[delete-file-user](#)

[delete-http-health-checker](#)

[delete-http-lb](#)

[delete-http-lb-config](#)

[delete-http-lb-ref](#)

[delete-http-listener](#)

[delete-iiop-listener](#)

[delete-instance](#)

[delete-javamail-resource](#)

[delete-javamail-resource-amx](#)

[delete-jdbc-connection-pool](#)

[delete-jdbc-resource](#)

[delete-jdbc-resource-amx](#)

[delete-jms-host](#)

[delete-jms-resource](#)

[delete-jmsdest](#)

[delete-jndi-resource](#)

[delete-jndi-resource-amx](#)

[delete-jvm-options](#)

[delete-lifecycle-module](#)

[delete-management-rule](#)

[delete-mbean](#)

[delete-message-security-provider](#)

[delete-node-agent](#)

[delete-node-agent-config](#)

[delete-password-alias](#)

[delete-persistence-resource](#)  
[delete-profiler](#)  
[delete-resource-adapter-config](#)  
[delete-resource-adapter-config-amx](#)  
[delete-resource-ref](#)  
[delete-ssl](#)  
[delete-system-property](#)  
[delete-threadpool](#)  
[delete-transformation-rule](#)  
[delete-virtual-server](#)  
[deploy](#)  
[deploydir](#)  
[disable](#)  
[disable-http-lb-application](#)  
[disable-http-lb-server](#)  
[display-error-distribution](#)  
[display-error-statistics](#)  
[display-log-records](#)  
[top](#)

## **E**

[enable](#)  
[enable-http-lb-application](#)  
[enable-http-lb-server](#)  
[export](#)  
[export-http-lb-config](#)  
[top](#)

## **F**

[flush-jmsdest](#)  
[freeze-transaction-service](#)  
[top](#)

## **G**

[generate-diagnostic-report](#)  
[generate-jvm-report](#)  
[get](#)  
[get-client-stubs](#)  
[get-hadb-info](#)  
[get-health](#)  
[top](#)

## I

[is-hadb-installed](#)

[top](#)

## J

[jms-ping](#)

[top](#)

## L

[list](#)

[list-admin-objects](#)

[list-admin-objects-amx](#)

[list-application-refs](#)

[list-audit-modules](#)

[list-auth-realms](#)

[list-backups](#)

[list-clusters](#)

[list-components](#)

[list-configs](#)

[list-connector-connection-pools](#)

[list-connector-resources](#)

[list-connector-resources-amx](#)

[list-connector-security-maps](#)

[list-custom-resources](#)

[list-custom-resources-amx](#)

[list-domains](#)

[list-file-groups](#)

[list-file-users](#)

[list-http-lb-configs](#)

[list-http-lbs](#)

[list-http-listeners](#)

[list-iiop-listeners](#)

[list-instances](#)

[list-javamail-resources](#)

[list-javamail-resources-amx](#)

[list-jdbc-connection-pools](#)

[list-jdbc-resources](#)

[list-jdbc-resources-amx](#)

[list-jms-hosts](#)

[list-jms-resources](#)

[list-jmsdest](#)  
[list-jndi-entries](#)  
[list-jndi-resources](#)  
[list-jndi-resources-amx](#)  
[list-lifecycle-modules](#)  
[list-management-rules](#)  
[list-mbeans](#)  
[list-message-security-providers](#)  
[list-node-agents](#)  
[list-password-aliases](#)  
[list-persistence-resources](#)  
[list-registry-locations](#)  
[list-resource-adapter-configs](#)  
[list-resource-adapter-configs-amx](#)  
[list-resource-refs](#)  
[list-status](#)  
[list-sub-components](#)  
[list-system-properties](#)  
[list-threadpools](#)  
[list-timers](#)  
[list-transformation-rules](#)  
[list-virtual-servers](#)  
[login](#)  
[top](#)

## **M**

[migrate-timers](#)  
[multimode](#)  
[top](#)

## **P**

[ping-connection-pool](#)  
[ping-hadb-agent](#)  
[publish-to-registry](#)  
[top](#)

## **R**

[reconfig](#)  
[recover-transactions](#)  
[remove-ha-cluster](#)  
[restart-hadb](#)

[restore-domain](#)  
[rollback-transaction](#)  
[top](#)

## S

[set](#)  
[set-hadb-info](#)  
[show-component-status](#)  
[start-appserv](#)  
[start-callflow-monitoring](#)  
[start-cluster](#)  
[start-database](#)  
[start-domain](#)  
[start-hadb](#)  
[start-instance](#)  
[start-node-agent](#)  
[stop-appserv](#)  
[stop-callflow-monitoring](#)  
[stop-cluster](#)  
[stop-database](#)  
[stop-domain](#)  
[stop-hadb](#)  
[stop-instance](#)  
[stop-node-agent](#)  
[top](#)

## U

[undeploy](#)  
[unfreeze-transaction-service](#)  
[unpublish-from-registry](#)  
[unset](#)  
[update-connector-security-map](#)  
[update-file-user](#)  
[update-password-alias](#)  
[top](#)

## V

[verify-domain-xml](#)  
[version](#)  
[top](#)

## Usage Text

add-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] xmlfilepath

apply-http-lb-changes [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] lb\_name

apply-repository-zip [--host localhost] [--port 4848] [--user admin\_user] [--passwordfile file\_name] [--terse=false] [--echo=false] [--interactive=true] [--secure=true] [--target server\_name|nodeagent\_name] [--rootdir server\_root\_path|nodeagent\_root\_path] [zip-file]

backup-domain [--domaindir domain\_directory] [--description description] [--echo=false] [--terse=false] [--verbose=false] [domain\_name]

change-admin-password [--terse=false] [--echo=false] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user]

change-master-password [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--savemasterpassword=false] [--agentdir nodeagent\_dir | --domaindir domain\_dir] [nodeagent\_name|domain\_name]

clear-ha-store [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password][--haadminpasswordfile file\_name] [--hosts hadb-host-list] [--storeuser username] [--storepassword password] [--dbsystempassword dbpassword] databaseName

clear-status [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] target

configure-ha-cluster [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--devicesize devicesize] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] --hosts hadb-host-list [--autohadb=false] [--portbase port-number] [--property (name=value)[:name=value]\*] clusterName



configure-ha-persistence [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--type persistence-type] [--frequency frequency] [--scope scope] [--store jdbc-resource-jndi-name] [--property (name=value)[:name=value]\*] clusterName

configure-http-lb-config [--user DAS\_user] [--passwordfile file\_name] [--host DAS\_host(Default localhost)] [--port DAS\_port(Default 4849)] [--terse=false] [--echo=false] [--interactive=true] [--responsetimeout=60] [--httpsrouting=false] [--reloadinterval=60] [--monitor=false] [--routecookie=true] [--healthcheckerurl url] [--healthcheckerinterval=30] [--healthcheckertimeout timeout] --target target [--lbxmlfile xml\_file\_name] [--lbpolicy lbpolicy] [--lbpolicymodule lbpolicymodule] lb\_config\_name

configure-lb-weight --cluster cluster\_name [instance-name=weight[:instance-name=weight]\*]

configure-webservice-management [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] [--monitoring=OFF] [--maxhistorysize=25] webservice\_name

copy-config [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--systemproperties (name=value)[:name=value]\*] source\_config\_name new\_config\_name

create-admin-object [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] --restype aorestype --raname resource\_adapter\_name [--enabled=true] [--description text] [--property (name=value)[:name=value]\*] [--target target(Default server)] jndi\_name

create-admin-object-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] --restype aorestype --raname resource\_adapter\_name [--enabled=true] [--description text] [--property (name=value)[:name=value]\*] [--target target(Default server)] jndi\_name

create-application-ref [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] [--enabled=true] [--virtualservers virtual\_servers] reference\_name

create-audit-module [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] --classname classme [--property (name=value)[:name=value]\*] [--target target(Default server)]

audit\_module\_name

create-auth-realm [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --classname realm\_class [--property (name=value)[:name=value]\*] [--target target(Default server)]  
auth\_realm\_name

create-cluster [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--config config\_name] [--systemproperties (name=value)[:name=value]\*] [--hosts hadb-host-list] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--devicesize devicesize] [--haproperty (name=value)[:name=value]\*] [--autohadb=false] [--portbase port-number] cluster\_name

create-connector-connection-pool [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--steadypoolsize 8] [--maxpoolsize 32] [--maxwait 60000] [--poolresize 2] [--idletimeout 300] [--failconnection=false] --rname resource\_adapter\_name --connectiondefinition connection\_definition\_name [--transactionsupport transaction\_support] [--isconnectvalidatereq=false] [--description text] [--property (name=value)[:name=value]\*] poolname

create-connector-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --poolname connector\_connection\_pool\_name [--enabled=true] [--description description] [--target target(Default server)] jndi\_name

create-connector-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --poolname connector\_connection\_pool\_name [--enabled=true] [--description description] [--target target(Default server)] jndi\_name

create-connector-security-map [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --poolname connector\_connection\_pool\_name --principals principal-name[,principal-name]\* | --usergroups user-group[,user-group]\* --mappedusername user-name mapname

create-custom-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --restype resource\_type --factoryclass classname [--enabled=true] [--description text] [--property

(name=value)[:name=value]\*) [--target target(Default server)] jndi\_name

create-custom-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --restype resource\_type --factoryclass classname [--enabled=true] [--description text] [--property (name=value)[:name=value]\*) [--target target(Default server)] jndi\_name

create-domain [--terse=false] [--echo=false] [--interactive=true] [--domaindir domain\_directory] [--template domain\_template] --adminport port\_number --adminuser admin [--passwordfile filename ] [--instanceport port\_number] [--savemasterpassword=false] [--domainproperties (name=value)[:name=value]\*) [--savelogin=false] domain\_name

create-file-user [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--groups user\_groups[:user\_groups]\*) [--authrealmname authrealm\_name] [--target target(Default server)] username

create-ha-store [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--hosts hadb-host-list] [--storeuser username] [--storepassword password] [--dbssystempassword dbpassword] databaseName

create-http-health-checker [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--url url] [--interval 30] [--timeout 10] [--config config\_name] target

create-http-lb [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] --config lb\_config\_name [--autoapplyenabled=false] --devicehost device\_host\_or\_ip --deviceport device\_port [--sslproxyhost proxy\_host] [--sslproxyport proxy\_port] [--property (name=value)[:name=value]\*) load\_balancer\_name

create-http-lb-config [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--responsetimeout 60] [--httpsrouting=false] [--reloadinterval=60] [--monitor=false] [--routecookie=true] --target target | config\_name

create-http-lb-ref [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--lbpolicy

policy] [--lbpolicymodule path-to-module] [--healthcheckerurl url] [--healthcheckerinterval interval-in-seconds] [--healthcheckertimeout timeout-in-seconds] [--lbenableallapplications] [--lbenableallinstances] --config config\_name target

create-http-listener [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --listeneraddress address --listenerport listener\_port --defaultvs virtual\_server [--servername server\_name] [--acceptorthreads acceptor\_threads] [--xpowered=true] [--redirectport redirect\_port] [--securityenabled=false] [--enabled=true] [--target target(Default server)] listener\_id

create-iiop-listener [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --listeneraddress address [--iiopport iiopport] [--securityenabled=false] [--enabled=true] [--property (name=value)[:name=value]\*] [--target target(Default server)] listenerid

create-instance [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--config config\_name | --cluster cluster\_name] --nodeagent nodeagent\_name(implicitly\_created) [--systemproperties (name=value)[:name=value]\*] instance\_name

create-javamail-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --mailhost hostname --mailuser username --fromaddress address [--storeprotocol imap] [--storeprotocolclass com.sun.mail.imap.IMAPStore] [--transprotocol smtp] [--transprotocolclass com.sun.mail.smtp.SMTPTransport] [--debug=false] [--enabled=true] [--description text] [--property (name=value)[:name=value]\*] [--target target(Default server)] jndi\_name

create-javamail-resource-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --mailhost hostname --mailuser username --fromaddress address [--storeprotocol imap] [--storeprotocolclass com.sun.mail.imap.IMAPStore] [--transprotocol smtp] [--transprotocolclass com.sun.mail.smtp.SMTPTransport] [--debug=false] [--enabled=true] [--description text] [--property (name=value)[:name=value]\*] [--target target(Default server)] jndi\_name

create-jdbc-connection-pool [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --datasourceclassname classname [--restype res\_type] [--steadypoolsize 8] [--maxpoolsize 32] [--maxwait 60000] [--poolresize 2] [--idletimeout 300] [--isolationlevel

isolation\_level] [--isolationguaranteed] [--isconnectvalidatereq=false] [--validationmethod auto-commit] [--validationtable tablename] [--failconnection=false] [--allownoncomponentcallers=false] [--nontransactionalconnections=false] [--description text] [--property (name=value)[:name=value]\*] jdbc\_connection\_pool\_id

create-jdbc-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --connectionpoolid id [--enabled=true] [--description text] [--target target(Default server)] jndi\_name

create-jdbc-resource-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --connectionpoolid id [--enabled=true] [--description text] [--target target(Default server)] jndi\_name

create-jms-host [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] [--mqhost host\_name] [--mqport 7676] [--mquser admin] [--mqpassword admin] [--property (name=value)[:name=value]\*] jmshostname

create-jms-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --restype resource\_type [--enabled=true] [--description text] [--property (name=value) [:name=value]\*] [--target target(Default server)] jndi\_name

create-jmsdest [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --desttype|T topic|queue [--target target (Default server)] [--property (name=value)[:name=value]\*] destname

create-jndi-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --jndilookupname lookupname --restype resource\_type --factoryclass classname [--enabled=true] [--description text] [--property (name=value)[:name=value]\*] [--target target(Default server)] jndi\_name

create-jndi-resource-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --jndilookupname lookupname --restype resource\_type --factoryclass classname [--enabled=true] [--description text] [--property (name=value)[:name=value]\*] [--target target(Default server)] jndi\_name

create-jvm-options [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--profiler=false] [--target target(Default server)] (jvm\_option\_name[=jvm\_option\_value])[:jvm\_option\_name[=jvm\_option\_value]]\*

create-lifecycle-module [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --classname classname [--classpath classpath] [--loadorder load\_order] [--failurefatal=false] [--enabled=true] [--description description] [--target target(Default server)] [--property (name=value)[:name=value]\*] modulename

create-management-rule [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--ruleenabled=true] [--ruledescription description] [--action action-mbean-name] --eventtype log|timer|trace|monitor|cluster|lifecycle|notification [--eventloglevel FINEST|FINER|FINE|CONFIG|INFO|WARNING|SEVERE|OFF] [--recordevent=true] [--eventdescription description] [--eventproperties (property=value[:property=value]\*)] [--target target] rule-name

create-mbean [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--name name] [--objectname object-name] [--target=server] [--attributes name=value[:name=value]\*] implementation-class-name

create-message-security-provider [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] --classname provider\_class [--layer message\_layer=SOAP] [--providertype provider\_type] [--requestauthsource request\_auth\_source] [--requestauthrecipient request\_auth\_recipient] [--responseauthsource response\_auth\_source] [--responseauthrecipient response\_auth\_recipient] [--isdefaultprovider] [--property (name=value)[:name=value]\*] provider\_name

create-node-agent [--terse=false] [--echo=false] [--interactive=true] [--host DAS\_host(Default localhost)] [--port DAS\_port(Default 4849)] [--user DAS\_user] [--passwordfile file\_name] [--agentdir nodeagent\_path] [--agentport port\_number] [--savemasterpassword=false] [--secure=true] [--agentproperties (name=value)[:name=value]\*] [nodeagent\_name]

create-node-agent-config [--terse=false] [--echo=false] [--interactive=true] [--host

localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] nodeagent\_name

create-password-alias [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] aliasname

create-persistence-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--jdbcjndiname jdbc\_jndiname | --connectionpoolid id] [--factoryclass classname] [--enabled=true] [--description text] [--property (name=value)[:name=value]\*] [--target target(Default server)] jndi\_name

create-profiler [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--classpath classpath] [--nativelibpath native\_library\_path] [--enabled=true] [--property (name=value)[:name=value]\*] [--target target(Default server)] profiler\_name

create-repository-zip [--host localhost] [--port 4848] [--user admin\_user] [--passwordfile file\_name] [--terse=false] [--echo=false] [--interactive=true] [--secure=true] [server\_name | nodeagent\_name]

create-resource-adapter-config [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--threadpools threadpoolids] [--property name=value[:name=value]\*] raname

create-resource-adapter-config-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--threadpools threadpoolids] [--property name=value[:name=value]\*] raname

create-resource-ref [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] [--enabled=true] reference\_name

asadmin create-service [--terse=false] [--echo=false] --passwordfile password-file [--name service-name] [--type daslnode-agent] [--serviceproperties (name=value)+] domain-dir\node-agent-dir

create-ssl [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --type [http-listener|iiop-listener|iiop-service] --certname cert\_name [--ssl2enabled=false] [--

ssl2ciphers ssl2ciphers] [--ssl3enabled=true] [--ssl3tlsciphers ssl3tlsciphers] [--  
tlseenabled=true] [--tlsrollbackenabled=true] [--clientauthenabled=false] [--target  
target(Default server)] [listener\_id]

create-system-properties [--terse=false] [--echo=false] [--interactive=true] [--host  
localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name]  
[--target target(Default server)] (name=value)[:name=value]\*

create-threadpool [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--  
port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--  
maxthreadpoolsize max\_thread\_pool\_size] [--minthreadpoolsize min\_thread\_pool\_size]  
[--idletimeout idle\_thread\_timeout\_in\_seconds] [--workqueues number\_work\_queues] [--  
target target(Default server)] threadpool\_id

create-transformation-rule [--terse=false] [--echo=false] [--interactive=true] [--host  
localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile  
file\_name] --webservice name webservice\_name [--enabled=true] [--applyto=request] --  
rulefilelocation rule\_file\_location transformation-rule-name

create-virtual-server [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--  
port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --hosts  
hosts [--httplisteners httplisteners] [--defaultwebmodule default\_web\_module] [--state on]  
[--logfile logfile] [--property (name=value)[:name=value]\*] [--target target(Default  
server)] virtual\_server\_id

delete-admin-object [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--  
port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target  
target(Default server)] jndi\_name

delete-admin-object-amx [--terse=false] [--echo=false] [--interactive=true] [--host  
localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile  
file\_name] [--target target(Default server)] jndi\_name

delete-application-ref [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--  
-port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--  
cascade=truelfalse] [--target target(Default server)] application\_reference\_name

delete-audit-module [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--  
port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target  
target(Default server)] audit\_module\_name



delete-auth-realm [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] auth\_realm\_name

delete-cluster [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--autohadboverride true|false] cluster\_name

delete-config [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] config\_name

delete-connector-connection-pool [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--cascade=false] poolname

delete-connector-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] connector\_resource\_name

delete-connector-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] connector\_resource\_name

delete-connector-security-map [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --poolname poolname mapname

delete-custom-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jndi\_name

delete-custom-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jndi\_name

delete-domain [--terse=false] [--echo=false] [--domaindir domain\_directory] domain\_name

delete-file-user [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--authrealmname authrealm\_name] [--target target(Default server)] username

delete-http-health-checker [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--config config\_name] target

delete-http-lb [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] load\_balancer\_name

delete-http-lb-config [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] config\_name

delete-http-lb-ref [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] --config config\_name target

delete-http-listener [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] httplistener\_id

delete-iiop-listener [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] listenerid

delete-instance [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] instance\_name

delete-javamail-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jndi\_name

delete-javamail-resource-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jndi\_name

delete-jdbc-connection-pool [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--cascade=false] jdbc\_connection\_pool\_id

delete-jdbc-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target

target(Default server)] jdbc\_resource\_name

delete-jdbc-resource-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jdbc\_resource\_name

delete-jms-host [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jmshostname

delete-jms-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jndi\_name

delete-jmsdest [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --desttype|-T topic|queue [--target target(Default server)] destname

delete-jndi-resource [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jndi\_name

delete-jndi-resource-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] jndi\_name

delete-jvm-options [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--profiler=false] [--target target(Default server)] (jvm\_option\_name[=jvm\_option\_value]) [:jvm\_option\_name[=jvm\_option\_name]]\*

delete-lifecycle-module [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] modulename

delete-management-rule [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target] rule-name

delete-mbean [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target=server]

name

delete-message-security-provider [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --layer message\_layer [--target target(Default server)] provider\_name

delete-node-agent [--terse=false] [--echo=false] [--interactive=true] [--agentdir nodeagent\_path] nodeagent\_name

delete-node-agent-config [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] nodeagent\_name

delete-password-alias [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] aliasname

delete-persistence-resource [--target target(Default server)] jndi\_name

delete-profiler [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)]

delete-resource-adapter-config [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] raname

delete-resource-adapter-config-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] raname

delete-resource-ref [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] reference\_name

delete-ssl [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --type [http-listener|iiop-listener|iiop-service] [--target target(Default server)] [listener\_id]

delete-system-property [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--target

target(Default server)] property\_name

delete-threadpool [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] threadpool\_id

delete-transformation-rule [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --webservicename webservice\_name transformation-rule-name

delete-virtual-server [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] virtual\_server\_id

deploy [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--virtualservers virtual\_servers] [--contextroot context\_root] [--force=true] [--precompilejsp=false] [--verify=false] [--name component\_name] [--upload=true] [--retrieve local\_dirpath] [--dbvendorname dbvendorname] [--createtables=truelfalse | --dropandcreatetables=truelfalse] [--uniquetablenames=truelfalse] [--deploymentplan deployment\_plan] [--enabled=true] [--generatermistubs=false] [--availabilityenabled=false] [--libraries jar\_file[(pathseparator)jar\_file]\*] [--target target(Default server)] filepath

deploydir [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--virtualservers virtual\_servers] [--contextroot contextroot] [--force=true] [--verify=false] [--precompilejsp=false] [--name component-name] [--uniquetablenames=truelfalse] [--dbvendorname dbvendorname] [--createtables=false | --dropandcreatetables=false] [--generatermistubs=false] [--availabilityenabled=false] [--libraries jar\_file[(pathseparator)jar\_file]\*] [--target target(Default server)] dirpath

disable [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] component\_name

disable-http-lb-application [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--timeout 30] --name application\_name target

disable-http-lb-server [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [-

-port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--timeout 30] target

display-error-distribution [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] timestamp

display-error-statistics [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)]

display-log-records [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--errorlevel SEVERE|WARNING] [--target target(Default server)] --timestamp timestamp module-id[:module-id]\*

enable [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target (Default server)] component\_name

enable-http-lb-application [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] --name application\_name target

enable-http-lb-server [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] target

export [name=value [name=value]\*]

export-http-lb-config [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] --config config\_name [file\_name]

flush-jmsdest [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --desttype|-T topic|queue [--target target(Default server)] destname

freeze-transaction-service [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)]

generate-report [--terse=false] [--echo=false] [--interactive=true] [--local=false] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --outputfile zip\_file\_name[--file filename] [--bugids bugids] [--logstartdate start-date] [--logenddate end-date] [--targetdir local\_dir\_path] target

generate-jvm-report [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--type=summary|memory|class|thread] [target (Default server)]

get [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--monitor=false] [--interval monitoringinterval] [--iterations counter] (dotted-attribute-name)+

get-client-stubs [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] --appname application\_name local\_directory\_path

get-hadb-info [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--hosts hadb-host-list] clusterName

get-health (target=cluster\_name)

is-hadb-installed [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name]

jms-ping [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name]

list [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--monitor=false] [dotted-parent-element-name]+

list-admin-objects [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-admin-objects-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-application-refs [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-audit-modules [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-auth-realms [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-backups [--domaindir domain\_directory] [--terse=false] [--echo=false] [--verbose=false] [domain\_name]

list-clusters [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target(Default domain)]

list-components [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile filename] [--type application|ejb|web|connector|webservice] [target (Default server)]

list-configs [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target(Default domain)]

list-connector-connection-pools [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name]

list-connector-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-connector-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-connector-security-map [--terse=false] [--echo=false] [--interactive=true] [--host



localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--securitymap mapname] [--verbose=false] pool-name

list-custom-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-custom-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-domains [--terse=false] [--echo=false] [--domaindir domain\_directory]

list-file-groups [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--name username] [--authrealmname authrealm\_name] [target(Default server)]

list-file-users [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--authrealmname authrealm\_name] [target(Default server)]

list-http-lb-configs [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target]

list-http-lbs [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name]

list-http-listeners [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-iiop-listeners [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-instances [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target(Default domain)]

list-javamail-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name]

[target(Default server)]

list-javamail-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-jdbc-connection-pools [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name]

list-jdbc-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target (Default server)]

list-jdbc-resources-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target (Default server)]

list-jms-hosts [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-jms-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--restype resource\_type] [target (Default server)]

list-jmsdest [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--desttype|T topic|queue] [target (Default server)]

list-jndi-entries [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--context context-name] [target(Default server)]

list-jndi-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-jndi-resources-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-lifecycle-modules [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-management-rules [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target=server]

list-mbeans [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target=server]

list-message-security-providers [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--layer message\_layer] [target(Default server)]

list-node-agents [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target (Default domain)]

list-password-aliases [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name]

list-persistence-resources [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-registry-locations [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name]

list-resource-adapter-configs [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--verbose=false] [--rname connector\_module\_name]

list-resource-adapter-configs-amx [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--verbose=false] [--rname connector\_module\_name]

list-resource-refs [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-status [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target]

list-sub-components [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--type ejb|servlets] [--appname appname] modulename

list-system-properties [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-threadpools [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

list-timers [--host localhost] [--port 4848] [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] target

list-transformation-rules [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--webserviceName webservice\_name]

list-virtual-servers [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [target(Default server)]

asadmin login [--terse=false] [--echo=false] [--host localhost] [--port 4848|4849] [--secure | s]

migrate-timers [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--destination destination\_name] server\_name

multimode [--file filename] [--printprompt] [--encoding encode]

ping-connection-pool [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] poolname

ping-hadb-agent [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--hosts hadb-host-list] clusterName

publish-to-registry [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] --registryjndinames comma-separated-list --webservicename webservice\_name [--lbhost lb\_host] [--lbport lb\_port] [--lbsslport lb\_ssl\_port] [--organization organization\_name] [--categories comma-separated-list] [--description description]

reconfig

recover-transactions [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--txlogdir transaction\_log\_dir and --destination destination\_server\_name] server\_name

remove-ha-cluster [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--hosts hadb-host-list] databaseName

restart-hadb [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--hosts hadb-host-list] databaseName

restore-domain [--domaindir domain\_directory] [--filename backup\_filename] [--description description] [--terse=false] [--echo=false] [--verbose=false] [domain\_name]

rollback-transaction [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] transaction\_id

set [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] (dotted-attribute-name=value)+

set-hadb-info [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--hosts

hadb-host-list] clusterName name=value:name=value\*

show-component-status [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)] component\_name

start-appserv [--terse=false] [--echo=false] [--interactive=true] [--user admin\_user] [--passwordfile file\_name] [--domaindir domain\_directory]

start-callflow-monitoring [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--filtertype (type=value):type=value]\*] instance-name

start-cluster [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--autohadboverride true|false] cluster\_name

start-database [--dbhost 0.0.0.0] [--dbport 1527] [--dbhome db\_directory] [--echo=false] [--terse=false]

start-domain [--terse=false] [--echo=false] [--interactive=true] [--user admin\_user] [--passwordfile file\_name] [--domaindir domain\_directory] [--verbose=false] [--debug=false] [domain\_name]

start-hadb [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--hosts hadb-host-list] databaseName

start-instance [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] instance\_name

start-node-agent [--terse=false] [--echo=false] [--interactive=true] [--user admin\_user] [--passwordfile file\_name] [--agentdir nodeagent\_path] [--startinstances=true] [--verbose=false] [nodeagent\_name]

stop-appserv [--terse=false] [--echo=false] [--domaindir domain\_directory]

stop-callflow-monitoring [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] instance-name

stop-cluster [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--autohadboverride true|false] cluster\_name

stop-database [--dbhost 0.0.0.0] [--dbport 1527]

stop-domain [--terse=false] [--echo=false] [--domaindir domain\_directory] [domain\_name]

stop-hadb [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] [--haagentport port\_number] [--haadminpassword password] [--haadminpasswordfile file\_name] [--hosts hadb-host-list] databaseName

stop-instance [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4849] [--secure|-s=true] [--user admin\_user] [--passwordfile file\_name] instance\_name

stop-node-agent [--terse=false] [--echo=false] [--interactive=true] [--secure=true] [--agentdir nodeagent\_path] [nodeagent\_name]

undeploy [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] [--droptables=true|false] [--cascade=false] [--target target(Default server)] component\_name

unfreeze-transaction-service [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] [--target target(Default server)]

unpublish-from-registry [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] --registryjndinames comma-separated-list --webservicename webservice\_name

unset name [name]\*

update-connector-security-map [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure|-s] [--user admin\_user] [--passwordfile file\_name] --poolname connector\_connection\_pool\_name [--addprincipals principal-name[,principal-name]\*] [--addusergroups user-group[,user-group]\*] [--removeprincipals principal-name[,principal-name]\*] [--removeusergroups user-group[,user-group]\*] [--

mappedusername user-name] mapname

update-file-user [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--groups user\_groups[:user\_groups]\*] [--authrealmname authrealm\_name] [--target target(Default server)] username

update-password-alias [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] aliasname

verify-domain-xml [--terse=false] [--echo=false] [--verbose=false] [--domaindir domain\_directory] [domain\_name]

version [--terse=false] [--echo=false] [--interactive=true] [--host localhost] [--port 4848|4849] [--secure | -s] [--user admin\_user] [--passwordfile file\_name] [--verbose=false]

[top](#)