

Name delete-message-security-provider – enables administrators to delete a message security provider

Synopsis delete-message-security-provider
[--help]
--layer *message_layer*
provider_name

Description The delete-message-security-provider subcommand enables administrators to delete a message security provider.

In terms of what happens when this subcommand is run, the provider-config sub-element for the given message layer (message-security-config element of domain.xml is deleted. The domain.xml file specifies parameters and properties to the Enterprise Server). The options specified in the list below apply to attributes within the message-security-config and provider-config sub-elements of the domain.xml file.

If the message-layer (message-security-config attribute) does not exist, it is created, and then the provider-config is created under it.

This command is supported in remote mode only.

Options If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.

--help
Displays the help text for the subcommand.

--target
Do not specify this option. This option is retained for compatibility with other releases. If you specify this option, a syntax error does not occur. Instead, the subcommand runs successfully and the option is silently ignored.

--layer
The message-layer from which the provider has to be deleted. The default value is HttpServlet.

Operands *provider_name*
The name of the provider used to reference the provider-config element.

Examples **EXAMPLE 1** Deleting a message security provider

The following example shows how to delete a message security provider for a client.

```
asadmin> delete-message-security-provider  
--layer SOAP mySecurityProvider
```

Exit Status 0 command executed successfully
1 error in executing the command

See Also [create-message-security-provider\(1\)](#), [list-message-security-providers\(1\)](#)
[asadmin\(1M\)](#)

