

**Name** delete-custom-resource – removes a custom resource

**Synopsis** delete-custom-resource [--help] [--target *target*] *jndi-name*

**Description** The delete-custom-resource subcommand removes a custom resource.

This subcommand is supported in remote mode only.

**Options** --help

-?

Displays the help text for the subcommand.

--target

This option helps specify the location of the custom resources that you are deleting. Valid targets are server, domain, cluster, and instance. The default is server.

**Note** – Resources are always created for a domain as a whole but are only active for targets for which a <resource-ref> has been created using the --target option when the resource was created. This means that deleting a resource only deletes the <resource-ref> element for the specified --target, and does not delete the resource from the domain as a whole unless domain is specified as the --target for the deletion.

*server*

Deletes the resource for the default server instance. This is the default value.

*domain*

Deletes the resource for the domain.

*cluster\_name*

Deletes the resource for every server instance in the cluster.

*instance\_name*

Deletes the resource for a particular server instance.

**Operands** *jndi-name*

The JNDI name of this resource.

**Examples** **EXAMPLE 1** Deleting a Custom Resource

This example deletes a custom resource named mycustomresource.

```
asadmin> delete-custom-resource mycustomresource
```

Command delete-custom-resource executed successfully.

**Exit Status** 0 subcommand executed successfully

1 error in executing the subcommand

**See Also** [create-custom-resource\(1\)](#), [list-custom-resources\(1\)](#)

[asadmin\(1M\)](#)