

**Name** delete-admin-object – removes the administered object with the specified JNDI name.

**Synopsis** delete-admin-object [--help] [--target *target*] *jndi\_name*

**Description** The delete-admin-object subcommand removes an administered object with the specified JNDI name.

This subcommand is supported in remote mote only.

**Options** --help

-?

Displays the help text for the subcommand.

--target

This is the name of the targets for which the administered object is to be deleted. Valid values are:

**Note** – Resources are always created for a domain as a whole but are only active for targets for which a <resource-ref> has been created using the --target option when the resource was created. This means that deleting a resource only deletes the <resource-ref> element for the specified --target, and does not delete the resource from the domain as a whole unless domain is specified as the --target for the deletion.

*server*

Deletes the administered object for the default server instance *server* and is the default value.

*configuration\_name*

Deletes the administered object for the specified configuration.

*cluster\_name*

Deletes the administered object for the specified cluster.

*instance\_name*

Deletes the administered object for a particular server instance.

**Operands** *jndi\_name*

JNDI name of the administered object to be deleted.

**Examples** EXAMPLE 1 Deleting an Administered Object

This example deletes the administered object named `.jms/samplequeue`.

```
asadmin> delete-admin-object jms/samplequeue
```

```
Command delete-admin-object executed successfully
```

**Exit Status** 0 subcommand executed successfully

1 error in executing the subcommand

**See Also** `create-admin-object(1)`, `list-admin-objects(1)`  
`asadmin(1M)`