

-
- Name** create-protocol-finder – adds a new protocol finder
- Synopsis** create-protocol-finder [--help]
 --protocol *protocol-name*
 --targetprotocol *target-protocol-name*
 --classname *class-name*
 [--target *server*]
protocol-finder-name
- Description** The create-protocol-finder subcommand creates a protocol finder for a protocol. This subcommand is supported in remote mode only.
- Options**
- help
 -?
 Displays the help text for the subcommand.
 - protocol
 The name of the associated protocol.
 - targetprotocol
 The name of the target protocol.
 - classname
 The fully qualified name of the Java class that implements the protocol finder.
 - target
 Creates the protocol finder only on the specified target. Valid values are as follows:
 - server
 Creates the protocol finder on the default server instance. This is the default value.
 - configuration-name*
 Creates the protocol finder in the specified configuration.
 - cluster-name*
 Creates the protocol finder on all server instances in the specified cluster.
 - standalone-instance-name*
 Creates the protocol finder on the specified standalone server instance.
- Operands** *protocol-finder-name*
 The name of the protocol finder.
- Exit Status**
- 0 command executed successfully
 - 1 error in executing the command
- See Also** [delete-protocol-finder\(1\)](#), [list-protocol-finders\(1\)](#)
[asadmin\(1M\)](#)