

- 
- Name** delete-http – removes HTTP parameters from a protocol
- Synopsis** delete-http [--help]  
 [--target *target*]  
*protocol-name*
- Description** The delete-http subcommand removes the specified HTTP parameter set from a protocol. This subcommand is supported in remote mode only.
- Options** --help  
 -?  
 Displays the help text for the subcommand.
- target  
 Deletes the HTTP parameter set only from the specified target. Valid values are as follows:
- server*  
 Deletes the HTTP parameter set from the default server instance. This is the default value.
- configuration-name*  
 Deletes the HTTP parameter set from the specified configuration.
- cluster-name*  
 Deletes the HTTP parameter set from all server instances in the specified cluster.
- standalone-instance-name*  
 Deletes the HTTP parameter set from the specified standalone server instance.
- Operands** *protocol-name*  
 The name of the protocol from which to delete the HTTP parameter set.
- Examples** **EXAMPLE 1** Deleting an HTTP Parameter Set  
 The following command deletes the HTTP parameter set from a protocol named http-1:
- ```
asadmin> delete-http http-1
```
- Command delete-http executed successfully.
- Exit Status** 0            command executed successfully  
 1            error in executing the command
- See Also** [create-http\(1\)](#)  
[asadmin\(1M\)](#)