

---

<b>Name</b>	list-virtual-servers – lists the existing virtual servers
<b>Synopsis</b>	<code>list-virtual-servers [--help] [target]</code>
<b>Description</b>	The <code>list-virtual-servers</code> subcommand lists the existing virtual servers. This subcommand is supported in remote mode only.
<b>Options</b>	<code>--help</code> <code>-?</code> Displays the help text for the subcommand.
<b>Operands</b>	<i>target</i> Restricts the listing to virtual servers for a specified target. Valid values are as follows:  <i>server</i> Lists the virtual servers for the default server instance. This is the default value.  <i>configuration-name</i> Lists the virtual servers for the specified configuration.  <i>cluster-name</i> Lists the virtual servers for all server instances in the specified cluster.  <i>instance-name</i> Lists the virtual servers for the specified server instance.
<b>Examples</b>	<b>EXAMPLE 1</b> Listing Virtual Servers The following command lists all the virtual servers for the server instance:  <pre>asadmin&gt; list-virtual-servers server __asadmin Command list-virtual-servers executed successfully.</pre>
<b>Exit Status</b>	0        command executed successfully 1        error in executing the command
<b>See Also</b>	<a href="#">create-virtual-server(1)</a> , <a href="#">delete-virtual-server(1)</a>  <a href="#">asadmin(1M)</a>