

Name list-jms-resources – lists the JMS resources

Synopsis list-jms-resources [--help]
[--restype *type*]
[*target*]

Description The list-jms-resources subcommand lists the existing Java Message Service (JMS) resources (destination and connection factory resources).

This subcommand is supported in remote mode only. Remote asadmin subcommands require a running domain administration server (DAS).

Options --help

-?

Displays the help text for the subcommand.

--restype

The JMS resource type can be javax.jms.Topic, javax.jms.Queue, javax.jms.ConnectionFactory, javax.jms.TopicConnectionFactory, or javax.jms.QueueConnectionFactory.

Operands *target*

Restricts the listing to resources for a specified target. Valid values are as follows:

server

Lists the resources for the default server instance. This is the default value.

domain

Lists the resources for the domain.

cluster-name

Lists the resources for every server instance in the specified cluster.

instance-name

Lists the resources for the specified server instance.

Examples EXAMPLE 1 Listing all JMS resources

The following subcommand lists all JMS resources.

```
asadmin> list-jms-resources
jms/Queue
jms/ConnectionFactory
jms/DurableConnectionFactory
jms/Topic
Command list-jms-resources executed successfully.
```

EXAMPLE 2 Listing JMS resources of a specified type

The following subcommand lists all javax.jms.ConnectionFactory resources.

EXAMPLE 2 Listing JMS resources of a specified type *(Continued)*

```
asadmin> list-jms-resources --restype javax.jms.ConnectionFactory  
jms/ConnectionFactory  
jms/DurableConnectionFactory  
Command list-jms-resources executed successfully.
```

Exit Status	0	subcommand executed successfully
	1	error in executing the subcommand

See Also [create-jms-resource\(1\)](#), [delete-jms-resource\(1\)](#)

[asadmin\(1M\)](#)

