

**Name** list-jmsdest – lists the existing JMS physical destinations

**Synopsis** list-jmsdest [--help]  
[--desttype *type*]  
[*target*]

**Description** The list-jmsdest subcommand lists the Java Message Service (JMS) physical destinations.

This subcommand is supported in remote mode only. Remote asadmin subcommands require a running domain administration server (DAS).

**Options** --help  
-?

Displays the help text for the subcommand.

--desttype

The type of JMS destination to be listed. Valid values are `topic` and `queue`.

**Operands** *target*

Restricts the listing to physical destinations for a specified target. Valid values are as follows:

*server*

Lists the physical destinations for the default server instance. This is the default value.

*configuration-name*

Lists the physical destinations in the specified configuration.

*cluster-name*

Lists the physical destinations for every server instance in the specified cluster.

*instance-name*

Lists the physical destinations for the specified server instance.

**Examples** EXAMPLE 1 Listing all physical destinations

The following subcommand lists all the physical destinations.

```
asadmin> list-jmsdest
PhysicalQueue
PhysicalTopic
Command list-jmsdest executed successfully.
```

EXAMPLE 2 Listing all physical destinations of a specified type

The following subcommand lists all physical topics.

```
asadmin> list-jmsdest --desttype topic
PhysicalTopic
Command list-jmsdest executed successfully.
```

**Exit Status** 0            subcommand executed successfully  
              1            error in executing the subcommand

**See Also** `create-jmsdest(1)`, `delete-jmsdest(1)`, `flush-jmsdest(1)`  
[asadmin\(1M\)](#)

