

Name flush-jmsdest – purges messages in a JMS destination.

Synopsis flush-jmsdest [--help]
--desttype {topic|queue}
[--target *target*]
destname

Description The `flush-jmsdest` subcommand purges the messages from a physical destination in the server's Java Message Service (JMS) configuration.

This subcommand is supported in remote mode only. Remote `asadmin` subcommands require a running domain administration server (DAS).

Options --help

-?

Displays the help text for the subcommand.

--desttype

This option indicates the type of physical destination from which you want to purge messages. The supported destination types are `topic` and `queue`.

--target

Purges messages from the physical destination only for the specified target. Valid values are as follows:

server

Purges messages from the physical destination for the default server instance. This is the default value.

configuration-name

Purges messages from the physical destination in the specified configuration.

cluster-name

Purges messages from the physical destination for every server instance in the specified cluster.

instance-name

Purges messages from the physical destination for the specified server instance.

Operands *dest_name*

The unique identifier of the JMS destination to be purged.

Examples EXAMPLE 1 Purging messages from a physical destination

The following subcommand purges messages from the queue named `PhysicalQueue`.

```
asadmin> flush-jmsdest --desttype queue PhysicalQueue
```

Command `flush-jmsdest` executed successfully.

Exit Status 0 subcommand executed successfully
 1 error in executing the subcommand

See Also [create-jmsdest\(1\)](#), [list-jmsdest\(1\)](#), [delete-jmsdest\(1\)](#)
[asadmin\(1M\)](#)

