

Name delete-jmsdest – removes a JMS physical destination

Synopsis delete-jmsdest [--help]
--desttype *type*
[--target *target*]
dest_name

Description The `delete-jmsdest` subcommand removes the specified Java Message Service (JMS) physical destination.

This subcommand is supported in remote mode only. Remote `asadmin` subcommands require a running domain administration server (DAS).

Options --help

-?

Displays the help text for the subcommand.

--desttype

The type of the JMS destination. Valid values are `topic` and `queue`.

--target

Deletes the physical destination only from the specified target. Although the `delete-jmsdest` subcommand is related to resources, a physical destination is deleted using the JMS Service (JMS Broker), which is part of the configuration. A JMS Broker is configured in the `config` section of `domain.xml`. Valid values are as follows:

server

Deletes the physical destination from the default server instance. This is the default value.

configuration-name

Deletes the physical destination from the specified configuration.

cluster-name

Deletes the physical destination from every server instance in the specified cluster.

instance-name

Deletes the physical destination from the specified server instance.

Operands *dest_name*

The unique identifier of the JMS destination to be deleted.

Examples EXAMPLE 1 Deleting a physical destination

The following subcommand deletes the queue named `PhysicalQueue`.

```
asadmin> delete-jmsdest --desttype queue PhysicalQueue
```

Command `delete-jmsdest` executed successfully.

Exit Status 0 subcommand executed successfully
 1 error in executing the subcommand

See Also `create-jmsdest(1)`, `list-jmsdest(1)`, `flush-jmsdest(1)`
[asadmin\(1M\)](#)

