

Name delete-jms-resource – removes a JMS resource

Synopsis delete-jms-resource [--help]
[--target *target*]
jndi_name

Description The delete-jms-resource subcommand removes the specified Java Message Service (JMS) resource. Ensure that you remove all references to this resource before executing this subcommand.

This subcommand is supported in remote mode only. Remote asadmin subcommands require a running domain administration server (DAS).

Options --help

-?

Displays the help text for the subcommand.

--target

Deletes the JMS resource only from the specified target. Valid values are as follows:

Note – Resources are always created for a domain as a whole but are only active for targets for which a <resource-ref> has been created using the --target option when the resource was created. This means that deleting a resource only deletes the <resource-ref> element for the specified --target, and does not delete the resource from the domain as a whole unless domain is specified as the --target for the deletion.

server

Deletes the JMS resource from the default server instance. This is the default value.

domain

Deletes the JMS resource from the domain.

cluster-name

Deletes the JMS resource from every server instance in the specified cluster.

instance-name

Deletes the JMS resource from the specified server instance.

Operands *jndi_name*

The JNDI name of the JMS resource to be deleted.

Examples EXAMPLE 1 Deleting a JMS destination resource

The following subcommand deletes the JMS destination resource named jms/MyQueue.

```
asadmin> delete-jms-resource jms/MyQueue
```

```
Administered object jms/MyQueue deleted.
```

```
Command delete-jms-resource executed successfully.
```

Exit Status 0 subcommand executed successfully
 1 error in executing the subcommand

See Also [create-jms-resource\(1\)](#), [list-jms-resources\(1\)](#)
[asadmin\(1M\)](#)

