

## Group Management Service Configuration in Glassfish V3.1

### 1. Introduction

#### 1.1. Project/Component Working Name:

Group Management Service (GMS-Shoal project)

#### 1.2. Name(s) and e-mail address of Document Author(s)/ Supplier:

Sheetal Vartak : sheetal.vartak@oracle.com

Joe Fialli : joe.fialli@oracle.com

#### 1.3. Date of This Document:

02/25/2011 - Joe: align with what got implemented.

06/21/2010 = Joe, simplify by replacing GMS\_TCPSTARTPORT and GMS\_TCPENDPORT with GMS\_LISTENER\_PORT.

06/18/2010 - Joe add content where TBD is in section 4.7

06/17/2010 - Joe, corrections made during implementation phase for GMS\_LISTENER\_PORT and GMS\_TCPENDPORT in section 4.5. Moved these

from group-management-service property to cluster property.

06/01/2010 - Joe, Add documentation for the gms configuration.

05/26/2010 - Joe, Update with feedback from April 29th admin meeting.

04/06/2010 - Sheetal, Initial version

### 2. Project Summary

#### 2.1. Project Description:

GMS configuration

#### 2.2. Risks and Assumptions:

No risks. But there is a plan to change certain property names to make them easier to understand. So there needs to be backward compatibility in place.

### 3. Problem Summary

#### 3.1. Problem Area:

Shoal GMS requires configuration information to join a dynamic cluster. This information is configured in DAS domain.xml under cluster and group-management-service elements. The information is read and used to join the group in gf v3.1 module cluster/gms-adapter.

#### 3.2. Justification:

The main theme for Glassfish 3.1 is Clustering and HA. GMS being an important piece of this theme needs to be configured correctly. Hence the need for support of the GMS configuration through domain.xml.

#### 4. Technical Description:

##### 4.1. Details:

The work mainly comprises of bringing 3.1 to 2.1.1 parity. All the GMS related attributes/properties that were supported in GF 2.1.X domain.xml will be brought over to 3.1. There are some attributes whose names need to be changed just so that the names reveal the real reason behind the attribute and are not confusing to understand. For this, backward compatibility will need to be preserved. Some properties that were introduced in 2.1.1 need to be promoted to attributes. A few new attributes will need to be introduced due to support for Grizzly as the underlying transport layer.

##### 4.2. Bug/RFE Number(s):

None so far.

##### 4.3. In Scope:

Everything explained in 4.1.

##### 4.4. Out of Scope:

Despite specifying v3.1 cluster property **gms-virtual-multicast-uris**, the functionality that implements this is not in scope for gf v3.1.

<intentionally added page break here so next section is at top of page>

#### 4.5. Interfaces:

The Config API will need to be modified in order to incorporate the new GMS config changes.

GMS configuration in GF 2.1.1 structure in domain.xml

Below is an extraction of relevant GMS configuration related xml document fragments from a GF v2.1.1 domain.xml.

The example configures a glasfish cluster named *dev-cluster*.

Relevant GMS elements, attributes and properties are in **bold**.

```
<cluster name="dev-cluster"
  config-ref="dev-cluster-config"
  heartbeat-enabled="true",
  heartbeat-address="<legal multicast address>"
  heartbeat-port="integer larger 2000">

  <property name="gms-bind-interface-address"
    value=${GMS_DEV-CLUSTER_BIND_INTERFACE_ADDR}/>
  <property name="gms-initial-host-list"
    value="tcp://ipAddr1:port,tcp://ipAddr2:port,..."/>
  <property name="gms-member-type"
    value=${GMS_DEV-CLUSTER_MEMBER_TYPE}/>
</cluster>

<config name="dev-cluster-config"
  dynamic-reconfiguration-enabled="true">
  ...
  <group-management-service
    fd-protocol-max-tries="3"
    fd-protocol-timeout-in-millis="2000"
    merge-protocol-max-interval-in-millis="10000"
    merge-protocol-min-interval-in-millis="5000"
    ping-protocol-timeout-in-millis="5000"
    vs-protocol-timeout-in-millis="1500">

    <property name="failure-detection-tcp-retransmit-timeout"
      value="3000"/>
  </group-management-service>
</config>
```

cluster element notes:

In Glassfish v2.1.1 asadmin create-cluster created the above cluster element in domain.xml, The creation command ensured that cluster.heartbeat-address attribute value was unique for each cluster listed in the domain.xml. heartbeat-address has to be a valid multicast address.

See link

<http://wiki.glassfish.java.net/Wiki.jsppage=FaqsHowtoConfigureGMSPropertiesInDomainXML> on how to configure properties gms-bind-interface-address and failure-detection-tcp-retransmit-timeout introduced in gf v2.x. See <http://appserver.sfbay.sun.com/Wiki.jsp?page=GMSHowTo> for documentation on how to configure MEMBER\_TYPE added in glassfish v2.x timeframe.

- New gf v3.1 structure in domain.xml

Below is an example illustrating all possible elements/attributes and properties existing in glassfish v3.1 domain.xml for configuring GMS.

```
<cluster
  name="dev-cluster"
  config-ref="dev-cluster-config"
  gms-enabled="true"
  gms-multicast-address="229.9.1.1"
  gms-multicast-port="2299"
  gms-bind-interface-address=
    "${GMS-BIND-INTERFACE-ADDRESS-dev-cluster}"
  <property name="GMS_LISTENER_PORT"
    value="${GMS_LISTENER_PORT-dev-cluster}"/>
  <property name="gms-list-virtual-multicast-uri"
    value="tcp://ipAddr1:port,tcp://ipAddr2:port,..."/>
  <property name="GMS_MEMBER_TYPE"
    value="${GMS-MEMBER-TYPE-dev-cluster}"/>
</cluster>

<config name="dev-cluster-config"
  dynamic-reconfiguration-enabled="true"/>
...
<group-management-service group-discovery-timeout-in-millis="5000">
  <failure-detection
    max-missed-heartbeats="3"
    heartbeat-frequency-in-millis="2000"
    verify-failure-waittime-in-millis="1500"
    verify-failure-connect-timeout-in-millis="10000"/>
</group-management-service>
```

```

</config>

// If possible, would prefer to advise setting system-property for DAS in
// domain.xml servers.server[@name="server"]. Here is what that
// looks like in v3 today.
<server name="server" config-ref="server-config">
  <resource-ref ref="jdbc/__TimerPool" />
  <resource-ref ref="jdbc/__default" />
  <system-property name="GMS_LISTENER_PORT-dev-cluster"
value="9090" />
</server>

// in gf v2, we set system-property on "server-config" with other
// system property.
<server config-ref="server-config" name="server">
  <!-- deleted non-essential info to this issue -->
  <system-property
    name="GMS_LISTENER_PORT-dev-cluster"
    value="9090" />
  <system-property
    name="GMS-BIND-INTERFACE-ADDRESS-dev-cluster"
    value="129.148.71.168" />
</server>

// setting gms system properties for a clustered instance.
<server config-ref="devtest-cluster-config" name="instance1">
  <!-- deleted non-essential info to this issue -->

  <!-- optional GMS system properties -->
  <system-property
    name="GMS_LISTENER_PORT-dev-cluster"
    value="9121" />
  <!-- following optional GMS system property specifies that a
  -- clustered instance does not participate in HA when ha is
  -- enabled.
  -->
  <system-property
    name="{GMS-MEMBER-TYPE-dev-cluster}"
    value="SPECTATOR" />
</server>

```

Summary of xml element/attribute/property changes from gf v2.x to gf 3.1 domain.xml.

Below are the mapping transformations that gms gf v3.1 upgrade

will perform to upgrade a gf v2 domain.xml to gf v3.1 format.

**cluster** element changes:

- Renamed 3 attributes under *cluster* :
  - From: **heartbeat-enabled**      To: **gms-enabled**
  - From: **heartbeat-address**      To: **gms-multicast-address**
  - From: **heartbeat-port**      To: **gms-multicast-port**
- Promoted gf v2.1 cluster property **gms-bind-interface-address** to an attribute of cluster in v3.1.
- Renamed gf v2.1 cluster property **gms-initial-host-list** to **gms-list-virtual-multicast-uri**.

**group-management-service** element changes:

- Rename an attribute of group-management-service element:
  - From: **ping-protocol-timeout-in-millis**
  - To: **group-discovery-timeout-in-millis**
- Add a new element under the *group-management-service* element called *failure-detection*. Move a number of attributes of gf v2.x group-management-service element to be attributes of gf 3.1 group-management-service.failure-detection element.
  - From: **fd-protocol-timeout-in-millis**
  - To: **failure-detection.heartbeat-frequency-in-millis**
  - From: **fd-protocol-max-tries**
  - To: **failure-detection.max-missed-heartbeats**
  - From: **fd-protocol-timeout-in-millis**
  - To: **failure-detection.verify-failure-waittime-in-millis**
- Promote gf v2.x group-managment-service property **failure-detection-tcp-retransmit-timeout** to gf v3 group-management-service.failure-detection attribute **verify-failure-connect-timeout-in-milis**
- Remove attributes **merge-protocol-max-interval-in-millis** and **merge-protocol-min-interval-in-millis** from gf v3.1 element **group-management-service** since they were never used in gf v2.x and will not have any meaning in gf v3.1.

Need to specify a symbolic value that can be replaced per instance for cluster properties *gms-bind-interface-address* and *gms-member-type*. The symbolic token value is set per clustered server instance via *system-property*.

- backward compatibility for the property name changes

The server mbeans are auto-generated. So some amount of work needs to be manually done to make sure that the *domain.xml* is backward compatible.

\*\*\*\*\*

GMS configuration attribute/property documentation:

For each GMS configuration attribute/property below, document whether it is required or optional, whether there exist a default value, the valid values for the attribute/property, relationship to other attributes/properties.

TBD: finish documentation below.

- **cluster** attributes

### **gms-enabled**

Its default value is **true**.

If *gms-enabled* is set to **false**, gms is completely disabled for this glassfish cluster. No GMS injected services are available. No HA is available.

When **gms-enabled** is set to **false**, no other gms configuration parameters are processed.

### **gms-multicast-address**

This attribute is optional.

Either this attribute or cluster property

**gms-list-virtual-multicast-uri** must be set when **gms-enabled** is set to **true**.

When cluster property *gms-list-virtual-multicast-uri* is not set to a null or empty string value, its default value is "229.9.1.1".

Implementation enforced constraints: this value should differ from all other cluster *gms-multicast-address* specified in a *domain.xml*.

### **gms-multicast-port="2299"**

This attribute defaults to the value 2299.

### **gms-bind-interface-address="<local network interface IP address>"**

On a multi-home machine (possessing 2 or more network interfaces), this attribute allows one to configure which network interface is used for GMS. This attribute is optional. It does not have a default value. This value should be a IP address of a local network interface IP address.

Multicast must be enabled for this interface UNLESS **gms-list-virtual-multicast-uri** is set. GMS Implementation must validate that this is a valid local network interface IP address.

Options to handle invalid value:

1. fail fast - Consider a SEVERE error and do not allow application server to start. Diagnostic output instructs user on how to configure properly. Plan on using this approach.
2. print a WARNING that the value is invalid and default to using the default algorithm to select which Network Interface is used. Did this in glassfish v2.x. It is too much of a surprise that this is only a WARNING when it was set incorrectly.

- **cluster** properties

name = **GMS\_LISTENER\_PORT**

value = "\${GMS\_LISTENER\_PORT-\${CLUSTERNAME}}"

Specify a unique GMS port. When multiple glassfish instances are started on one machine, this value must be unique across the glassfish instances. This property is only necessary to force GMS to use a specific port. Typically, GMS selects a free port from a default range (9100 to 9200). To configure the range, set GMS\_TCPSTARTPORT and GMS\_TCPSTOPPORT as a cluster properties.

### **gms-list-virtual-multicast-uri**

value="tcp://ipAddr1:port,tcp://ipAddr2:port,..."

The property is optional. It is required to be set when gms-multicast-address is not set. This property is not scheduled to be implemented. When this property is set, **GMS\_LISTENER\_PORT** must be same value as port listed in this list for ipAddrX above. Additionally, on a multihome machine, there may be a need to set **cluster** attribute **gms-bind-interface-address** to ipAddrX.

### **gms-member-type**

value="\${GMS-cluster-name-MEMBER\_TYPE}"

Allow any com.sun.enterprise.management.grizzly.GrizzlyConfigConstants properties to be configured in cluster.property. These values enable tuning of the transport. The same GrizzlyConfigConstant occurring in both cluster and group-management-service, the cluster one takes precedence.

\*\*\*\*\*

- **group-management-service** attributes  
**group-discovery-timeout-in-millis**

When a GMS client is first joining its group, this is time that it waits for a response back from the Master of the gms group. The default is 5 seconds. After this time is expired, then the instance will make itself the master of the group. Typically, the DAS is started before all other instances in the cluster and it is the defacto Master of GMS group. When the DAS is stopped while the clustered instances are still running, then all remaining gms group members run the same algorithm to select a successor to previous Master of gms group.

- **group-management-service.failure-detection** attributes  
**max-missed-heartbeats**="3"  
**heartbeat-frequency-in-millis**="2000"  
**verify-failure-waittime-in-millis**="1500"  
**verify-failure-connect-timeout-in-millis**="10000"

The existing documentation for GF v2.x group-management-service attributes at GlassfishWiki GMS FAQ is sufficient for the above properties. One just needs to map between the GF v2.x names for these attributes/properties to the GF v3.1 attribute names.

### **group-management-service** properties

Allow any com.sun.enterprise.mgmt.transport.grizzly.GrizzlyConfigConstants properties to be configured here. These values enable tuning of the transport.

\*\*\*\*\*

#### Logging

Enable ShoalLogger logging in Glassfish 3.1 using following commands:

```
// for clustered instances  
asadmin set-log-levels --target clusterName ShoalLogger:CONFIG
```

```
// for DAS.  
asadmin set-log-levels ShoalLogger:CONFIG
```

\*\*\*\*\*

#### 4.6. Doc Impact:

Documentation is needed.

Here was a gf v2 FAQ discussing various group-management-service attributes. The same basic discussion applies (with appropriate mapping of names from gf v2 to new gf v3.1 names by reader) Link: [gfv2.1 group management service attributes](#).

#### 4.7. Admin/Config Impact:

Admin CLI

Replace deprecated heartbeatport and heartbeataddress with multicastport and multicastaddress.

Example:

```
asadmin create-cluster --multicastport 2050 --multicastaddress 230.9.1.1 someName
```

TBD: Complete admin GUI for GMS.

Admin gui/cli related changes :

- expose new attributes and attribute name changes
- property-modified-to-attribute change
- add ability to provide generic cluster properties in glassfish v3.1 admin GUI. In GF v2.1, this capability was not provided and only could introduce cluster properties via asadmin CLI set command. In GF v2.1, there was a capability to add generic properties for group-management-service and these will still be needed in GF v3.1.

#### 4.8. HA Impact:

The config changes will only affect how GMS is started.

#### 4.9. I18N/L10N Impact:

No.

#### 4.10. Packaging & Delivery:

No impact.

#### 4.11. Security Impact:

No impact.

#### 4.12. Compatibility Impact

If older attribute/property names are used, then the class/interface needs to provide a solution to deal with backward compatibility.

// List any requirements on upgrade tool and migration tool.

#### 4.13. Dependencies:

### 5. Reference Documents:

// List of related documents, if any (BugID's, RFP's, papers).  
// Explain how/where to obtain the documents, and what each  
// contains, not just their titles.

ShoalGMSPropertiesInGlassfish\_v2\_DomainXML

<http://appserver.sfbay.sun.com/Wiki.jsp?page=SetGMSIpAddressInAppServer>

### 6. Schedule:

#### 6.1. Projected Availability:

// Dates in appropriate precision (quarters, years)