

Name create-audit-module– adds an audit module

Synopsis create-audit-module --classname *classname*
[--help]

[--property (name=value)[:name=value]*]
audit_module_name

Description This subcommand adds the named audit module for the plug-in module that implements the audit capabilities. Audit modules collect and store information on incoming requests (servlets, EJB components) and outgoing responses. This subcommand is supported in remote mode only.

Options --classname

The name of the Java class that implements this audit module. If not specified, defaults to `com.sun.enterprise.security.Audit`.

--help

Displays the help text for the subcommand.

--property

Optional attributes name/value pairs of provider implementation specific attributes.

The only valid property is `auditOn`, which can be specified as `true` or `false`. If `true`, causes the loading of the audit module and ensures that it is called by the Enterprise Server's audit library at audit points.

--target

Do not specify this option. This option is retained for compatibility with other releases. If you specify this option, a syntax error does not occur. Instead, the subcommand runs successfully and the option is silently ignored.

Operands *audit_module_name*

The name of this audit module.

Examples EXAMPLE 1 Creating an audit module

```
asadmin> create-audit-module
--classname com.sun.appserv.auditmodule
--property defaultuser=admin:Password=admin sampleAuditModule
Command create-audit-module executed successfully
```

Exit Status 0 command executed successfully

1 error in executing the command

See Also `delete-audit-module(1)`, `list-audit-modules(1)`

[asadmin\(1M\)](#)