

Name	delete-config – deletes an existing named configuration
Synopsis	<code>delete-config [--help] configuration-name</code>
Description	<p>The <code>delete-config</code> subcommand deletes an existing named configuration from the configuration of the domain administration server (DAS) in the <code>domain.xml</code> file. You can delete a configuration only if no server instances or clusters refer to the configuration. A standalone configuration is automatically deleted when the sever instance or cluster that refers to it is deleted. You cannot delete the <code>default-config</code> configuration that is copied to create standalone configurations.</p> <p>This subcommand is supported in remote mode only.</p>
Options	<p><code>--help</code> <code>-?</code> Displays the help text for the subcommand.</p>
Operands	<p><i>configuration-name</i> The name of the configuration that you are deleting.</p>
Examples	<p>EXAMPLE 1 Deleting a Named Configuration</p> <p>This example deletes the named configuration <code>pmdconfig</code>.</p> <pre>asadmin> delete-config pmdconfig</pre> <p>Command <code>delete-config</code> executed successfully.</p>
Exit Status	<p>0 command executed successfully</p> <p>1 error in executing the command</p>
See Also	<p><code>copy-config(1M)</code>, <code>list-configs(1M)</code></p> <p>asadmin(1M)</p> <p>configuration(5ASC)</p>