

Name	list-configs – lists named configurations
Synopsis	list-configs [--help] [<i>target</i>]
Description	<p>The <code>list-configs</code> subcommand lists named configurations in the configuration of the domain administration server (DAS) in the <code>domain.xml</code> file. The list can be filtered by cluster or instance.</p> <p>This subcommand is supported in remote mode only.</p>
Options	<p>--help -?</p> <p>Displays the help text for the subcommand.</p>
Operands	<p><i>target</i></p> <p>Filters the list of configurations. Valid values are as follows:</p> <p><i>domain</i> Lists all named configurations in the current domain.</p> <p><i>cluster-name</i> Lists the named configuration that defines the configuration of instances in the specified cluster.</p> <p><i>instance-name</i> Lists the named configuration that defines the configuration of the specified instance.</p>
Examples	<p>EXAMPLE 1 Listing All Named Configurations in a Domain</p> <p>This example lists all named configurations in the current domain.</p> <pre>asadmin> list-configs server-config default-config pmdclust-config pmdsharedconfig pmdcpinst-config ymlclust-config il1-config il2-config</pre> <p>Command <code>list-configs</code> executed successfully.</p>
Exit Status	<p>0 command executed successfully</p> <p>1 error in executing the command</p>
See Also	<p>copy-config(1), delete-config(1)</p> <p>asadmin(1M)</p> <p>configuration(5ASC)</p>