Name delete-node-config – deletes a node that is not enabled for communication over SSH

Synopsis delete-node-config [--help] node-name

Description The delete-node-config subcommand deletes a node that is not enabled for communication over secure shell (SSH) from the domain. This subcommand does not require secure shell (SSH) to be configured.

> This subcommand can delete only a node that is not enabled for communication over SSH. A node that is enabled for communication over SSH must be deleted by using the delete-node-ssh(1) subcommand. To determine whether a node is enabled for communication over SSH, use the list-nodes(1) subcommand.

> No GlassFish Server instances must reside on the node that is being deleted. Otherwise, the subcommand fails. Before running this subcommand, delete any instances that reside on the node by using, for example, the delete-instance(1) subcommand or the delete-local-instance(1) subcommand.

This subcommand is supported in remote mode only.

Options --help

- ?

Displays the help text for the subcommand.

Operands *node-name*

The name of the node to delete. The node must not be enabled for communication over SSH. Otherwise, an error occurs.

Examples EXAMPLE 1 Deleting a Node That Is Not Enabled for Communication Over SSH

This example deletes the node s jo3, which is not enabled for communication over SSH.

```
asadmin> delete-node-config sj03
```

Command delete-node-config executed successfully.

Exit Status 0

command executed successfully

error in executing the command

```
See Also create-node-config(1), delete-node-ssh(1), delete-instance(1),
delete-local-instance(1), install-node(1), list-nodes(1), uninstall-node(1),
update-node-config(1), update-node-ssh(1)
```

asadmin(1M)