

Name delete-lifecycle-module – removes the lifecycle module

Synopsis delete-lifecycle-module [--help] [--target *target*] *module_name*

Description The `delete-lifecycle-module` subcommand removes a lifecycle module. A lifecycle module provides a means of running a short or long duration Java-based task at a specific stage in the server life cycle. This subcommand is supported in remote mode only.

Options --help

-?

Displays the help text for the subcommand.

--target

Indicates the location where the lifecycle module is to be deleted. Valid values are

- `server-` Specifies the default server instance as the target for deleting the lifecycle module. `server` is the name of the default server instance and is the default value for this option.
- `cluster_name-` Specifies a particular cluster as the target for deleting the lifecycle module.
- `instance_name-` Specifies a particular server instance as the target for deleting the lifecycle module.
- `configuration_name-` Specifies a particular configuration as the target for deleting the lifecycle module.

Operands *module_name*

This operand is a unique identifier for the deployed server lifecycle event listener module.

Examples EXAMPLE 1 Deleting a Lifecycle Module

The following example deletes a lifecycle module named `customSetup`.

```
asadmin> delete-lifecycle-module customSetup
Command delete-lifecycle-module executed successfully
```

Exit Status 0 command executed successfully

1 error in executing the command

See Also `create-lifecycle-module(1)`, `list-lifecycle-modules(1)`

`asadmin(1M)`