

Name list-applications – lists deployed applications

Synopsis list-applications [--help]
[--long={false|true}] [--resources] [--subcomponents]
[--type *type*] [*target*]

Description The `list-applications` subcommand lists deployed Java EE applications and the type of each application that is listed.

If the `--type` option is not specified, all applications are listed. If the type option is specified, you must specify a type. The possible types are listed in the Options section of this help page.

If multiple versions of a module or application are deployed, this subcommand lists all versions. To list which version is enabled, set the `--long` option to `true`. For more information about module and application versions, see the “Module and Application Versions” in *Sun GlassFish Enterprise Server v3 Preview Application Deployment Guide*.

This subcommand is supported in remote mode only.

Options --help

-?

Displays the help text for the subcommand.

--long

If `true`, displays whether each module or application listed is enabled. The default is `false`.

--resources

Lists the application-scoped resources for each application. If the `--subcomponents` option is also used, lists the application-scoped resources for each component within the application.

--subcomponents

Lists the subcomponents of each application. The subcomponents listed depend on the application type. For example, for a Java EE application (EAR file), modules are listed. For a web application, servlets and JSP pages are listed. For an EJB module, EJB subcomponents are listed.

--type

Specifies the type of the applications that are to be listed. The options are as follows:

- application
- appclient
- connector
- ejb
- web
- webservice

If no type is specified, all applications are listed.

Operands --target

This is the name of the target upon which the subcommand operates. The valid values are as follows:

server

Lists the applications for the default server instance *server* and is the default value.

domain_name

Lists the applications for the named domain.

cluster_name

Lists the applications for every server instance in the cluster.

instance_name

Lists the applications for a particular server instance.

Examples EXAMPLE 1 Listing the Web Applications

```
asadmin> list-applications --type web
hellojsp <web>
Command list-applications executed successfully
```

Exit Status 0 subcommand executed successfully
1 error in executing the subcommand

See Also [list-components\(1\)](#), [list-sub-components\(1\)](#), [show-component-status\(1\)](#)

[asadmin\(1M\)](#)

Sun GlassFish Enterprise Server v3 Preview Application Deployment Guide

