

Name `disable` – disables the component

Synopsis `disable [--help] [--target target_name] component_name`

Description The `disable` subcommand immediately disables the specified deployed component. If the component has not been deployed, an error message is returned.

This subcommand is supported in remote mode only.

Options `--help`

`--?`

Displays the help text for the subcommand.

`--target`

This option specifies the target on which you are disabling the component. Valid values are:

`server`

Disables the component on the default server instance `server` and is the default value.

domain_name

Disables the component on the named domain.

cluster_name

Disables the component on every server instance in the cluster.

instance_name

Disables the component on a particular server instance.

Operands *component_name*

name of the component to be disabled.

The name can include an optional version identifier, which follows the name and is separated from the name by a colon (:). The version identifier must begin with a letter or number. It can contain alphanumeric characters plus underscore (_), dash (-), and period (.) characters. To disable multiple versions, you can use an asterisk (*) as a wildcard character. For more information about module and application versions, see the “Module and Application Versions” in *Sun GlassFish Enterprise Server v3 Preview Application Deployment Guide*.

Examples **EXAMPLE 1** Disabling a Component

This example disables the deployed component `sampleApp`.

```
asadmin> disable sampleApp
```

```
Command disable executed successfully
```

Exit Status 0 subcommand executed successfully
 1 error in executing the subcommand

See Also [deploy\(1\)](#), [undeploy\(1\)](#), [enable\(1\)](#)

[asadmin\(1M\)](#)

Sun GlassFish Enterprise Server v3 Preview Application Deployment Guide

