# **AppsAccess**

# **Training Guide**

Software Version 6.5.5



© 2006 Logical Apps

All rights reserved. Printed in USA.

#### Restricted Rights Legend

This software and associated documentation contain proprietary information of Logical Apps. It is provided under a license agreement containing restrictions on use and disclosure and it is also protected by copyright law. Reverse engineering of this software is prohibited.

The information contained in this document is subject to change without notice. Logical Apps does not warrant that this document is error free. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Logical Apps.

Logical Apps provides on-site support as well as remote phone and web support to ensure quick and effective product implementation. To request support, to suggest product enhancements, or to comment on Logical Apps software or documentation, send email to support@logicalapps.com, or contact us at the address or phone number given below.

AppsAccess, AppsAudit, AppsControl, AppsExtend, AppsForm, AppsFlow, AppsRules, and Rapid Compliance are trademarks of Logical Apps. All trademarks and registered trademarks are the property of their respective owners.

Document AA002-655C 4/12/2006

Logical Apps 15420 Laguna Canyon, Suite 150 Irvine, CA 92618 949.453.9101

# **Contents**

About AppsAcce	SS	1
Conflict Matrix Fo	orms	3
Starting AppsAcco	258	3
Finding Conflict F	Rules	4
Making Selections	in AppsAccess	5
Defining Conflic	t Rules	7
Creating Conflict	Rules Manually	7
Creating Global S	ubscribers	
Operating Uni	its	
Submenus		11
Data Groups .		12
Users		12
Finishing the S	Subscriber Configuration	13
Uploading Conflic	et Rules from a Spreadsheet	

Generating and Reviewing Conflicts	17
Generating User Conflicts	17
Reviewing User Conflicts	18
Updating Status for User Conflicts	20
Mass Updating User Conflicts	21
Resolving Conflicts	23
Manual Conflict Resolution	23
Cleanup Procedures	24
Managing Cleanup	25
Automated Conflict Resolution	25
Activating Responsibilities	26
Responding to Notifications	28
Reports and Concurrent Requests	29
Running Reports or Requests	29
Conflicts Summary Report	31
Responsibilities with Conflicts Report	32
User Conflicts Report	33
Conflict Matrix Report	34
Application Conflict Report	35
User Exclusions Report	36
Extract Conflict Rules	36
Load Conflict Rules	37
Archive User Conflict Data	37
Reset User Conflicts	37
Analyze Responsibility Conflicts	37
Generate User Conflicts	37
Cache WF User Roles	38
Support	39

# **About AppsAccess**

AppsAccess detects segregation-of-duties conflicts within an organization, either preventing them from occurring or uncovering them so that they can be properly managed. Designed for use with Oracle Applications, AppsAccess identifies conflicts at both the responsibility and function levels.

AppsAccess users create "conflict rules," each of which specifies two responsibilities or functions that should not both be assigned to an individual person. Users may create rules one at a time in a form called the Conflict Matrix, or upload already-created rules from an Excel spreadsheet and adapt them as needed.

Each conflict rule applies one of three "control types" — Prevent, Allow with Rules, or Approval Required. These determine the action to be taken when an Oracle Applications user is assigned duties that violate a conflict rule:

- A Prevent rule denies access to conflicting responsibilities or functions. When a user is assigned responsibilities that trigger a Prevent rule, AppsAccess sets their end dates to match their start dates, thus ensuring there is no period during which the user has access to conflicting elements.
- An Allow with Rules conflict rule permits access to conflicting responsibilities or functions providing that additional rules, written in Logical Apps AppsForm, mitigate the conflict by modifying Oracle Applications forms.
- An Approval Required rule designates a reviewer who can either accept a conflict (that is, allow an Oracle Applications user to work at responsibilities or functions that are known to be in conflict) or reject it.

Once conflict rules are defined, an AppsAccess user "generates conflicts" — causes AppsAccess to evaluate current Oracle Applications users and note those who are in violation of conflict rules. AppsAccess then lists the conflicts generated by each rule in a form called User Conflicts. It treats these conflicts in either of two ways:


• A user may have been assigned responsibilities or functions before a rule was created to define them as conflicting. If so, the User Conflict form displays appropriate status for the conflict: "Prevent" or "Allow with Rules" if the conflict was generated by a rule of either type, or "Pending" if it was generated by an Approval Required rule. Only the Pending status can be updated: a reviewer may approve or reject the conflict, either by itself (in a User Conflict Actions form) or along with others (in a Mass Update User Conflict form).


Decisions made in these forms, however, do not take effect; instead, they are logged to AppsAccess reports. Administrators would then use information from the reports to undertake "cleanup" — to make adjustments in Oracle Applications such as end-dating responsibilities assigned to users affected by conflicts, or excluding a function from a responsibility in which it conflicts with another function.

A user may have been assigned responsibilities or functions after a rule was created to define them as conflicting. In this case, AppsAccess automatically applies end dates if the control type is Prevent. If it is Allow with Rules, AppsAccess automatically removes end dates if at least one AppsForm rule has been associated with the conflict rule (but applies end dates if not).

If the control type is Approval Required, the responsibility assignment does not take effect immediately, and AppsAccess posts a notification of the conflict to the designated reviewer's Oracle Applications home site. Similarly, when a new user is created, his assignments are analyzed for conflicts, and notifications are transmitted to designated reviewers.

The reviewer's response to this notification updates responsibility end dates for the affected user: For an approval, the end dates are removed, permitting indefinite access to the conflicting elements. For a rejection, the end dates are made to match the start dates, preventing any access. Moreover, the user's status is updated in the AppsAccess User Conflicts form.





Three AppsAccess reports provide information for the resolution of conflicts: The Conflict Summary Report shows the number of conflicts generated for each responsibility and so helps in establishing resolution priorities. The Responsibilities with Conflicts Report lists the conflicts within each responsibility. The User Conflicts Report presents data generated when conflicts are approved or rejected in the User Conflict Actions form.

Two remaining reports are useful for auditing: The Conflict Matrix report lists conflict rules and, for each rule, displays the values that define it. The Application Conflict Report provides status information about each user affected by each rule.

#### **Conflict Matrix Forms**

AppsAccess separates the authority to create conflict rules from the authority to approve or reject conflicts generated by those rules. To do so, it provides two copies of the Conflict Matrix form:

- In a copy of the Conflict Matrix labeled Define Conflict Rules, users can create rules, generate conflicts, and review them. This copy of the Conflict Matrix, however, blocks access to the forms in which conflicts are approved or rejected.
- In a copy of the Conflict Matrix labeled User Conflict Approval, users can view conflict rules and review conflicts. They can select options that open the User Conflict Actions and Mass Update User Conflicts forms, and then use those forms to approve or reject conflicts. In this copy of the Conflict Matrix, however, users cannot create conflict rules.


#### **Starting AppsAccess**

To start AppsAccess:

- 1 Select the Logical Apps AppsRules responsibility from the Application list. (Ensure first that the AppsRules responsibility is available to you.)
- **2** In the Logical Apps Navigator, select either of two AppsAccess options:
  - Click on AppsAccess Define Conflict Rules to open the copy of the Conflict Matrix in which rules are created but conflicts cannot be approved or rejected.
  - Click on AppsAccess User Conflict Approval to open the copy of the Conflict Matrix that permits the approval or rejection of conflicts but does not allow the creation of conflict rules.
- **3** Click on the Open button in the Logical Apps Navigator.

### **Finding Conflict Rules**

When you open either copy of the Conflict Matrix, a Find Conflict Rules form appears.



You can use this form to load existing conflict rules into the Conflict Matrix. To search for all rules, simply click on the Find button. Or to search for a selection of rules, complete the following steps.

- **1** Fill any combination of the following boxes.
  - Conflict Rule Name: From the list, select a rule to search for it. An entry in this field causes AppsAccess to return only the single rule that matches the rule name. Or leave the field blank to search among all rules; doing so may return any number of rules (depending on the remaining filter selections.)
  - Application: From the list, select an Oracle application to find rules involving that application (as either of two applications to which conflicting responsibilities or functions may belong). Or leave the box blank to see rules involving any application.
  - Entity Type: Select Function or Responsibility to find rules defining conflicts in one entity or the other, or leave the box blank to see rules for both types.
  - Entity: From the list, select a function or a responsibility to search for rules involving that entity (as either of the two conflicting entities). Or leave the box blank to search for rules involving any function or responsibility. The values you can select depend on your selection in the Entity Type box.
  - Reviewer: From the list, select a workflow role to find rules for which that role is the designated conflict reviewer. Or leave the box blank to see rules for which anyone is a designated reviewer.
  - Approval Group: From the list, select the name of an approval group (as configured in Logical Apps AppsFlow) to find rules for which that group is the designated conflict reviewer. Or leave the box blank to see rules for which any (or no) group is a designated reviewer.
  - End-Dated Conflicts: Select Y (for yes) to find rules for which conflicts are end-dated or N (for no) to find rules for which conflicts are not end-dated. Or leave the box blank to search for both types of rule.


- Conflicts Exist: Select Y (for yes) to find rules for which conflicts exist or N
  (for no) to find rules for which no conflicts exist. Or leave the box blank to
  search for both types of rule.
- Same OU: Select Y (for yes) to find rules that apply within operating units or N (for no) to search for rules that apply across operating units. Or leave the box blank to find both types of rule.
- Same SOB: Select Y (for yes) to find rules that apply within sets of books or N (for no) to search for rules that apply across sets of books. Or leave the box blank to find both types of rule.
- Control Type: Select any combination of check boxes for control types —
   Approval, Prevent, or Allow with Rules to search for rules of those types.

   Select all three check boxes, or clear all three of them, to search for rules of all types.
- **2** Click on the Find button. (Or, to discard the filtering selection you have made and start over, click on the Clear button.)


After being used, the Find Conflict Rules form remains open in the background. To bring it to the foreground and use it again, click on it (drag any other forms, such as the Conflict Matrix, out of the way). If you close it, you can reopen it: Click on View in the menu bar, then Find in the View menu. Or, click on the Find icon, located second from the left in the tool bar. (It looks like a flashlight.)

#### **Making Selections in AppsAccess**

When you click in a list of values box to enter data, AppsAccess presents a list icon to the right of the box. It looks like an ellipsis:



When you click on this icon, AppsAccess opens a window in which you can produce a filterable list of values that may be entered in the box:



To use this window:

- 1 Click in the Find box and type a string of characters for which AppsAccess should search. You can use the percent sign (%) to stand for any string of characters. For example, the string AKD would return all entries that begin with those letters, while the string %AKD would return all entries in which those letters appear in any position. The percent sign alone would return all possible entries.
- **2** Click on the Find button. AppsAccess returns a list of the items that match your search criteria.
- **3** Scroll through the list and click on the item you want.
- **4** Click on the OK button.

# **Defining Conflict Rules**

The AppsAccess Conflict Matrix enables you to create new conflict rules; as an alternative, you can upload already-created rules from an Excel spreadsheet. In the Conflict Matrix, you can also view existing rules as well as generate user conflicts that the rules define.

As you create (or upload) rules, you may consider limiting their number (or at least the number that are active), so that the number of conflicts they generate is not overwhelming. A typical strategy is to start with a set of rules that define what you determine to be the most important conflicts, then clean up those conflicts before moving on to another set of rules. See "Managing Cleanup" on page 25.

Outside of the Conflict Matrix, you can complete other tasks related to conflict-rule definition. One is to create "global subscribers" — to identify data groups, submenus, operating units, or users who are exempt from conflict rules. Another is to configure workflow roles; you must assign one to each conflict rule to server as a reviewer of conflicts generated by rules. These are created and maintained in LogicalApps AppsFlow; for instructions on configuring them, refer to the *AppsFlow User's Guide*.

#### **Creating Conflict Rules Manually**

In broad terms, creating a conflict rule involves specifying two conflicting "entities," either responsibilities or functions; noting the applications to which those entities belong; and selecting a control type, a reviewer, and a few other parameters. You can

Entity Conflict Rule Name Entity Type Application Conflicting Application Conflicting Entity Exist Conflict Rule 1 Responsi... V Oracle Purchasing Purchasing Super Ut Oracle Public Sector Payables Manager Conflict Rule 6 Function Oracle Purchasing Purchase Orders Oracle Purchasing Receipts Conflict Rule 11 ▼ Oracle Public Sector Suppliers Oracle Purchasing Control Type Approval Required ✓ Same OU ☑ Same SOB Reviewer System Administrator Approval Group Start Date 03-JUN-05 08:57:54 End Date Reason Business Risk 3 Generate User Conflicts Global Subscribers

complete all these tasks in the copy of the Conflict Matrix that opens when you select the AppsAccess — Define Conflict Rules option in the Logical Apps Navigator:

To create a conflict rule in the Conflict Matrix:

- 1 Activate a row in the grid on the Conflict Matrix. Use any of these methods:
  - If the Conflict Matrix grid contains any empty rows, click in the first one.
  - Click on the New button, which is first on the left in the tool bar.
  - Click on File in the menu bar, then on New in the File menu.
  - Open the Find Conflict Rules form and click on its New button.
- **2** Type a name for the rule in the Conflict Rule Name field.
- **3** In the Entity Type list box, select *Responsibility* or *Function*.
- **4** Select the "base" entity the first of the two entities your rule is to define as conflicting. Use either of two methods:
  - In the Entity list of values, select a responsibility or function. (The list contains only one type or the other, depending on your choice in the Entity Type list box.) AppsAccess then fills the Application field with the name of the application to which the entity belongs.
  - In the Application list of values, select an application. AppsAccess limits values in the Entity field to those belonging to the application you selected (and of the type you chose in the Entity Type list box). Select the one you want.
- **5** Select the conflicting entity the second of the two entities your rule is to define as conflicting. Use either of the methods you could use to select a base entity, but this time in the Conflicting Application and Conflicting Entity lists of values.
- **6** In the Control Type list box, select the control type you want to apply to the rule Prevent, Allow with Rules, or Approval Required. (See page 1 for definitions of these control types.)
- 7 In the Reviewer list of values, select the person (workflow role) who is to review individual conflicts generated by the rule. Although the review of conflicts applies

- only to a rule of the Approval Required control type, you must select a reviewer even if you are configuring an Allow with Rules or Prevent rule.
- **8** In the Approval Group list of values, select an approval group with authority to review individual conflicts generated by the rule. If you enter a value in this optional field, AppsAccess ignores the value entered in the mandatory Reviewer field. If you omit a value here, AppsAccess uses the value in the Reviewer field.
- **9** Select the Same OU check box if you want the rule to apply only within individual operating units. Select the Same SOB check box if you want the rule to apply only within individual sets of books. Clear the appropriate check box if you want the rule to apply across operating units or sets of books.
- **10** In the Reason box, type an explanation of the business risk addressed by this conflict rule. (This reason appears in the LA AppsAccess Conflict Matrix Report.)
- 11 In the Start Date field, select a date on which the rule takes effect. In the End Date field, select a date on which the rule expires. (Assigning the current date, or an earlier one, as an end date inactivates the rule; you can edit the rule to delete the end date later, when you are ready to use the rule.)

By default, Start Date is set to the date on which you create the rule and End Date is blank, so that the rule takes effect immediately and remains in effect indefinitely. To change these values, select a date in the pop-up calendar that appears when you click on either list-of-values icon. Or type a date in the format configured for your instance of Oracle Applications.

If you selected the Prevent or Approval Required control type (in step 6), you need only save the rule. If you selected the Allow with Rules control type, you must link this rule with one or more AppsForm rules. To do so, complete these steps:

1 In the Conflict Matrix, click on the AppsForm Rules button (which becomes active only when you select the Allow with Rules control type.) An AppsForm Rules form appears:



- **2** From the AppsForm Rule list of values, select a rule that addresses the conflict.
- **3** In the Comment box, explain briefly why the AppsForm rule is being attached to this conflict rule.
- 4 Allow AppsAccess to complete the Creation Date and Active fields.

  The Creation Date field defaults to the date and time you establish a link between the AppsForm and AppsAccess rules the system date at the moment you select the AppsForm rule. (It appears after you refresh the AppsForm Rules form.)

The Active check box is selected by default if the AppsForm rule is active. You can choose only among active rules, so the check box is always selected initially. If you inactivate a rule in AppsForm, however, the check box is cleared here automatically.

- You may want the conflict rule to invoke more than one AppsForm rule. If so, repeat steps 2–4 for each AppsForm rule you want to invoke.
- **6** Close the AppsForm Rule form: click on the × symbol in its upper right corner.

Once you've completed all configuration steps, save the conflict rule: Click on File in the menu bar, then on Save in the File menu. Or click on the Save icon, located fourth from the left in the toolbar.

#### **Creating Global Subscribers**


You can specify submenus, functions, data groups, operating units, and users who are exempt from conflict rules. Such exclusions can ensure that query-only access to Oracle Applications features does not trigger conflict rules, even when standard access to the same features would. Or they may avoid the generation of conflicts that need not be tracked (such as for support personnel, who might have super-user access, but who do not actually carry out the conflicting responsibilities or functions).

Items designated for exclusion (or, in one case, inclusion) are called global subscribers. To select them, click on the Global Subscribers button in the Define Conflict Rules copy of the Conflict Matrix. (The button is disabled in the User Conflict Approval copy.) Then, in a Global Subscribers form, click on the tab for a subscriber type.

#### **Operating Units**

You can select operating units either to be included in, or excluded from, conflict-rule processing. These selections apply to operating units assigned to users, responsibilities, applications, or sites through use of the MO: Operating Unit profile option in the system administrator responsibility. The option may be set simultaneously at any or all of these levels, and the active setting is the one at the most narrowly focused level (first user, then responsibility, then application, then site).

1 In the Global Subscribers form, click on the Include/Exclude Operating Units tab:



**2** Select operating units in the list-of-values fields under either of the Include and Exclude headings. It is permissible to have entries in both lists simultaneously.

- **3** Select or clear the Active check boxes next to the entries:
  - If Active check boxes are selected under the Include heading, the corresponding operating units are eligible for conflict-rule processing and all others are excluded.
  - If Active check boxes are selected under the Exclude heading, the corresponding operating units are excluded from conflict-rule processing, and all others are included.


Do not select Active check boxes simultaneously under both the Include and Exclude headings. Otherwise you will be unable to save the subscriber configuration.

#### **Submenus**

A submenu under one menu may provide query-only access to functions, even though the same submenu under another menu provides write access to the same functions. A conflict rule that includes such a function would trigger conflicts for all instances of the function — rightly when a user has write access, but falsely for query-only access.

To exclude just the query-only functions from conflict-rule processing, create submenu subscribers:

1 In the Global Subscribers form, click on the Exclude Sub-Menus/Functions tab:



2 Make selections in the Menu Name, Sub-Menu Name, and (optionally) Function Name list boxes. (The last of these and other fields come into view as you scroll the form to the right.) AppsAccess supplies corresponding values in the User Menu Name, User Sub Menu Name, and User Function Name fields.

This exclusion feature recognizes only direct parent-child relationships:


- To exclude a submenu, specify that submenu and its immediate parent menu; use the Sub-Menu Name and Menu Name fields (respectively). To exclude a submenu is to exclude all functions available from that submenu.
- To exclude a single function, specify that function and its immediate parent submenu; use the Function Name and Menu Name fields (respectively). Note that you would include the submenu name in the *Menu Name field* and would leave the Sub-Menu Name field blank.

3 Select the Active check box to exempt the query-only instance of the function or functions from conflict rules, while leaving write-enabled instances subject to conflict rules. Or, clear the check box to deactivate the exemption.

#### **Data Groups**

Version 6.5.5 of AppsAccess includes the capability to evaluate conflict rules against data groups. To eliminate false conflicts that can occur when custom responsibilities are assigned to query-only data groups, you can exempt data groups from conflict-rule processing:

1 In the Global Subscribers form, click on the Exclude Data Groups tab:




- 2 In the Data Group lists of values, select the group that is to receive the exclusion.
  - If a description was written when the group was created, it appears by default in the Description box. If no description was written, the box remains blank. The Description box does not accept direct input.
- 3 The Active check box is selected by default. Leave it selected for the exclusion to take effect. Clear it (click on it so that no check mark appears) to reserve an exclusion for the group, but not have it take effect at present.

#### **Users**

You can exclude individual users from conflict-rule processing:

1 In the Global Subscribers form, click on the Exclude Users tab:



- **2** In the User Name list of values, select the ID of the user who is to receive the exclusion.
  - If a description of the user was written when the user ID was created, it appears by default in the Description box. If no description was written when the user ID was created, the box remains blank. The Description box does not accept direct input.
- **3** The Active check box is selected by default. Leave it selected for the user exclusion to take effect. Clear it (click on it so that no check mark appears) if you want to reserve a user exclusion for the user, but not have it take effect at present.

#### **Finishing the Subscriber Configuration**

When you finish working in the Global Subscriber forms, save the subscribers you've created: Click on File in the Oracle Applications menu bar, then on Save in the File menu. (Once you've created and saved a subscriber, you cannot delete it, although you can deactivate it by clearing its Active check box.) Then close the Global Subscriber forms: Click on the × symbol in the upper right corner.

You can print a report that lists all global subscribers; see page 36.

### **Uploading Conflict Rules from a Spreadsheet**

Rather than create rules one at a time in the Conflict Matrix, you can select rules in a Microsoft Excel spreadsheet, edit them in the spreadsheet to contain values appropriate for your site, and then upload them all at once. Before you start, be sure you know the name of the ODBC driver that enables you to connect to your Oracle system.

To prepare the spreadsheet for uploading:

**1** Open the AppsAccess LA\_SOD spreadsheet.

Conflict Name	Entity Type	Application	User Function Name	Conflicting Application	Conflicting Function Display Name	Control Type	Approver	F
Requisitions*Purchase Orders	Function	Oracle Purchasing	Requisitions	Oracle Purchasing	Purchase Orders	Approval Required	SYSADMIN	Buyers should not process their own process contols.
Requisition Summary Purchase Orders	Function	Oracle Purchasing	Requisition Summ	Oracle Purchasing	Purchase Orders	Approval Required	SYSADMIN	Buyers should not process their own process contols.
Requisitions*PO Summary: Create New PO	Function	Oracle Purchasing	Requisitions	Oracle Purchasing	PO Summary: Create New PO	Approval Required	SYSADMIN	Buyers should not process their own process contols.
Requisitions*Releases	Function	Oracle Purchasing	Requisitions	Oracle Purchasing	Releases	Prevent	SYSADMIN	Buyers should not process their own process contols.
Requisition Summary PO Summary: Create	P Function	Oracle Purchasing	Requisition Summ	Oracle Purchasing	PO Summary: Create New PO	Prevent	SYSADMIN	Buyers should not process their own process contols.
Requisition Summary Releases	Function	Oracle Purchasing	Requisition Summ	Oracle Purchasing	Releases	Prevent	SYSADMIN	Buyers should not process their own process contols.
Requisitions AutoCreate Documents	Function	Oracle Purchasing	Requisitions	Oracle Purchasing	AutoCreate Documents	Prevent	SYSADMIN	Buyers should not process their own process contols.
Requisition Summary AutoCreate Documen	Function	Oracle Purchasing	Requisition Summ	Oracle Purchasing	AutoCreate Documents	Allow with Rules	SYSADMIN	Buyers should not process their own process contols.
PO Summary: Create New PO*Receipts	Function	Oracle Purchasing	PO Summary: Cre	Oracle Purchasing	Receipts	Allow with Rules	SYSADMIN	Receiving personnel should never ha orders or to change receiving contro have the ability to do any receiving or
Releases*Receipts	Function	Oracle Purchasing	Releases	Oracle Purchasing	Receipts	Allow with Rules	SYSADMIN	Receiving personnel should never ha orders or to change receiving contro have the ability to do any receiving or
AutoCreate Documents*Receipts	Function	Oracle Purchasing	AutoCreate Docu	Oracle Purchasing	Receipts	Allow with Rules	SYSADMIN	Receiving personnel should never hat orders or to change receiving control have the ability to do any receiving or

- **2** In the upper left corner of the Access Load Values sheet, provide the ODBC driver name, connect string, Apps user name, and Apps password.
- **3** Click on the Update Data button. The spreadsheet is populated with up to 65,536 rows of rule data. (Owing to Excel limitations, this is the maximum number possible.)
- **4** Review the rules and select those you want to upload: In the Load column, select the value *Y* for rules you want and *N* for rules you don't want.
- **5** Edit the Control Type, Reviewer, and Reason values as appropriate for the rules you are uploading. You cannot change the values in other columns.
  - In particular, SYSADMIN is the default conflict reviewer for all rules in the spreadsheet. For each rule, change this value to an appropriate person (role).
- **6** On the Tools menu, click Create CSV for AppsAccess. In response to prompts, enter a file name and location. Click OK to save the file.



#### Note

The Create CSV for AppsAccess option appears in the Excel Tools menu only if the macro security level for Excel is set to low. To effect this setting, click on Tools in the Excel menu bar, then on Options in the Tools menu. In the Options window, click on the Security tab. In the Security panel, click on the Macro Security button. A Security window opens; in its Security Level panel, click on the Low radio button. Then close the Security and Options windows — click on the OK button in each.

To upload the file you've prepared:

- **1** As an admin user, upload the CSV file to your UTL directory on the database server.
- **2** Open the Navigator in the Logical Apps responsibility. Click on View in the menu bar, then on Requests in the View menu.
- **3** A Find Requests form opens. Click on its Submit a New Request button. In the Submit a New Request dialog, click on Single Request and then on the OK button.
- **4** A Submit Request form opens. In its Name list of values box, select LA AppsAccess Load Conflict Rules.
- **5** A Parameters form appears. In it, supply the following values:
  - Load: From the list, select Yes to load the data. (The value No would validate the data without loading it.)
  - Flat Filename: Enter the name you created for the CSV file.
  - Flat File Path: Enter the location you established for the file.
  - Log Details: From the list, select Yes to created a detailed log or No to create a more cursory log. Typically, you would select Yes only to troubleshoot a problem with an upload operation.

14

- **6** In the Submit Request form, click on the Submit button. At the next prompt, make a note of the request number, then click on No to return to the Find Requests form.
- **7** To view the log, click on the Specific Requests button. Type the ID number for your request in the Request ID field, and click on the Find button.
- **8** A Requests form shows the status of your request. When it informs you that the request is completed (you may have to click on the Refresh Data button), click on the View Output button. A log file similar to the following one appears:

++
Logical Apps Custom: Version : UNKNOWN - Development
Copyright © 1979, 1999, Oracle Corporation. All rights reserved.
LAA_LOAD_CONFLICT module: LA AppsAccess Load Conflict Rules
++
Current system time is 25-JAN-2006 11:27:52
++
**Starts**25-JAN-2006 11:27:52
**Ends**25-JAN-2006 11:33:28
++
Start of log messages from FND_FILE
++
After Inserting Into Interim Table
Total of 333 Records Inserted Into Interim Table Out of 333 Records 1 Records Have Error
Out of 333 Records i Records have Effor
Enter Bank Transaction Codes*Enter Bank Transaction   Invalid Conflict
Function/Responsibility Name
++
End of log messages from FND_FILE
+

# **Generating and Reviewing Conflicts**

Once conflict rules are defined and saved, the next step is to generate conflicts — to have AppsAccess search through users' work assignments for violations of the rules. For each rule, you can then open a User Conflicts form to view a list of the conflicts the rule has generated, together with the user affected by each conflict and its status.

For conflicts generated by Prevent or Allow with Rules conflict rules, the status is set to Prevent or Allow with Rules, respectively, and stays that way. For Approval Required conflicts, the reviewer designated in the conflict rule sets the status of conflicts — approves or rejects them — individually in a User Conflict Actions form or many-at-once in a Mass Update User Conflicts form.

However, the assignment of status in either of the User Conflict Actions or Mass Update User Conflicts forms does nothing more than add information to reports. It neither grants, denies, nor prevents access to conflicting responsibilities or functions. The actual implementation of conflict rules is carried out through a combination of manual and automated processes, which are discussed in detail in Chapter 4.

#### **Generating User Conflicts**


When you generate user conflicts, AppsAccess evaluates all conflict rules that have been saved and produces a "snapshot" — a set of conflicts existing at the current moment, as distinct from other sets of conflicts generated at past moments. With each new snapshot, AppsAccess saves the previous snapshot to an archive table.

Thus rules may be added or edited, but the existing snapshot reflects the way rules were configured the last time conflicts were generated, and will continue to do so until the Generate User Conflicts process is run again. So you should generate user conflicts whenever conflict rules change.

Before generating conflicts, you may choose to run an Analyze Responsibility Conflicts concurrent request. It can speed up conflict generation if rules have changed. See "Managing Cleanup" on page 25 and "Analyze Responsibility Conflicts" on page 37.

For the first of two methods to generate user conflicts, complete these steps:

- 1 Open the Define Conflict Rules copy of the Conflict Matrix. (See page 3.) It is unimportant whether the Conflict Matrix displays any conflict rules.
- **2** Click on the Generate User Conflicts button (located at the lower left of the Conflict Matrix form).
- A message informs you that a generate-user-conflicts request has been submitted. Make a note of the request ID, and click on the OK button to clear the message.




The Generate User Conflicts button is active in the Define Conflict Rules copy of the Conflict Matrix, but not in the User Conflict Approval copy. However, you can generate conflicts no matter which Conflict Matrix form is open (or even when only the Logical Apps Navigator is open). To do so, use the Requests option on the View menu to launch the LA AppsAccess Generate User Conflicts concurrent request. (See "Reports and Concurrent Requests" on page 29.)

#### **Reviewing User Conflicts**


To view the conflicts you've generated, refresh the Conflict Matrix — reload the rules in which you are interested, even if they were already loaded in the Conflict Matrix when you initiated the generate-user-conflicts request. To review user conflicts:

1 Click in the Find Conflict Rules form to make it active. Use it to locate the rules you want and load them into either copy of the Conflict Matrix. (See pages 4 –5.)

**2** When users' work assignments violate a rule, AppsAccess places a check mark in a Conflicts Exist box for that rule. The check box is located to the right of the Conflict Matrix row in which the rule is defined:



3 Select one of the check-marked rules. (Click on the row in which it is defined; note that a rectangle to its left turns blue.) Then click on the User Conflicts button. The following User Conflicts form presents a list of all users who possess both of the responsibilities or functions that the rule defines as being in conflict.




- 4 Note each user's status, which depends on the control type defined for the rule:
  - If the control type is Approval Required, each user's status begins at Pending. This status can be updated (see below).
  - If the control type is Allow with Rules, each user's status is Allow with Rules. This status cannot be updated.
  - If the control type is Prevent, each user's status is Prevent. This status cannot be updated.

### **Updating Status for User Conflicts**

If you opened the User Conflicts form from the User Conflict Approval copy of the Conflict Matrix, you can open another form in which you can approve or reject conflicts one at a time. To do so, you must be a reviewer designated in the rule that generated the conflict; otherwise you can view, but not update, approval status.

- 1 In the User Conflicts form, select a conflict to update. (That is, click on the row in which it is defined. The row is selected when a rectangle to its left turns blue.)
- **2** Click on the Action/Action History button. The User Conflict Actions form opens:



- **3** If the form lists more than one conflict user, select the one you want (once again, click on its row so that the rectangle to the left turns blue).
- **4** In the Action Type list, select Approved, Rejected, or Pending.

Approving a user conflict means that you know it exists and decide to allow it for the user. Rejecting a user conflict means that you decline to allow the user access to conflicting responsibilities or functions. Pending is the default status assigned by AppsAccess, indicating that a decision is yet to be made.



#### Note

Approvals and rejections made in this form are logged to AppsAccess reports, but do not take effect. Also, if an on-line approval notification is pending for a conflict, its status here can be updated only indirectly, through a response to the notification. For more on both issues, see Chapter 4, "Resolving Conflicts."

- **5** Specify dates during which this status is to remain in effect.
  - Start Date defaults to the date on which you are taking action. Accept the default or modify it to specify a future date on which you want the action to take effect.
  - End Date is blank by default. Insert a date on which you want the status to expire, or leave the box blank to allow the status to remain in effect indefinitely. An end date earlier than the start date prompts AppsAccess to present an error message.
  - In either case, select a date in the pop-up calendar that appears when you click on the list-of-values icon. Or type a date in the format configured for your instance of Oracle Applications.
- **6** In the Comments box, type a comment explaining why this conflict should be approved or rejected.

7 Click on the Done button. A dialog box prompts you to save your work; click Yes to preserve the action you selected or No to discard it. The User Conflict Actions form closes and the focus returns to the User Conflicts form, where the action you took is now displayed in the Status box.

#### **Mass Updating User Conflicts**

You can define sets of conflicts and review them all at once, rather than one at a time. You can approve or reject the conflicts in any combination, and give a reason for your decisions.

1 In the User Conflict Approval copy of the Conflict Matrix form, click on the Mass Update button. The following Mass Update User Conflicts form appears:



- 2 The Mass Update form can display only conflicts generated by rules for which you are a designated approver. To see all such conflicts, enter no filtering parameters in the six fields at the top of the form (and skip to step 3). Or, to specify conflicts you want to update, select values for any combination of the following filtering parameters:
  - Username: Select a user ID to produce a list of conflicts affecting that user.
  - Conflict Rule Name: Select a rule name to produce a list of conflicts generated by a particular rule.
  - Application: Select an application name to produce a list of conflicts generated by rules for which this is the base application.
  - Conflicting Application: Select an application name to produce a list of conflicts generated by rules for which this is the conflicting application.
  - Responsibility: Select a responsibility name to produce a list of conflicts generated by rules for which this is the base responsibility.

• Conflicting Responsibility: Select a responsibility name to produce a list of conflicts generated by rules for which this is the conflicting responsibility.



#### Note

If you attempt to search for conflicts that have already been approved or rejected, the search produces no results.

**3** Click the Find button. (To arrange results in alphabetical order by user name, select the Order Conflicts by Username check box first.) The grid displays Pending conflicts that conform to your search parameters.

Each row in the grid displays information about a conflict: the name of the affected user and the names of the conflict itself, its base responsibility, and its conflicting responsibility. Another row near the bottom of the form displays more information about the conflict currently selected in the grid: the names of its base application, conflicting application, base function, and conflicting function. (For a responsibility conflict, the function fields actually repeat the names of the base and conflicting responsibilities, since functions don't apply for such a rule.)


- **4** Review the conflicts and use any of these methods to approve or reject them:
  - Click in the Approve or Reject check box to the right of each conflict entry.
  - Click on the Select All Approval button to approve all the conflicts.
  - Click on the Select All Reject button to reject all the conflicts.
  - If you change your mind, click the De-Select All Approval or De-Select All Reject button to rescind either the approvals or the rejections you have made.



#### Note

Approvals and rejections made in this form are logged to AppsAccess reports, but do not take effect. Also, if an on-line approval notification is pending for a conflict, its status here can be updated only indirectly, through a response to the notification. For more on both issues, see Chapter 4, "Resolving Conflicts."

**5** Click the Action button and, in a Mass Update Action dialog, type a reason for your updates. Then click the OK button.



**6** A message informs you that the updates have been saved. Click its OK button.

When you finish updating status for a set of conflicts, you can load another set and update their status. You can click the Clear button to remove entries currently displayed in the grid, but this is not necessary; if you specify new search parameters and click the Find button, the newly specified conflicts replace the old set in the grid.

To close the Mass Update User Conflicts form, click on its Done button.

# **Resolving Conflicts**

Although a conflict is defined, and may be approved or rejected, in AppsAccess, it is not resolved until actions are taken outside of AppsAccess. These actions may include:

- Adjusting the end dates for responsibilities assigned to a user affected by a conflict. For an approved conflict, end dates may be set in the future (or removed) so that access to a responsibility is extended. For a rejected conflict, end dates are set to the present moment so that access to a responsibility is cut off.
- Excluding one or more conflicting functions from a responsibility or from menus, or removing a submenu containing conflicting functions from menus.
- Adding a user affected by an Allow-with-Rules conflict as a subscriber to the AppsForm rule associated with the conflict rule. For instructions on adding subscribers to AppsForm rules, see the AppsForm User's Guide.

The process for effecting these resolutions depends on whether a user has been assigned duties before or after an AppsAccess rule is created to define them as conflicting.

#### **Manual Conflict Resolution**

The first time conflicts are generated, and afterwards whenever conflict-rule definitions change, you are likely to uncover users who have been granted access to responsibilities or functions before conflict rules defined them as conflicting. AppsAccess uncovers these conflicts, but does not resolve them. Instead, you must eliminate these conflicts manually, a process known as "cleanup."

#### **Cleanup Procedures**

To uncover these conflicts, you would generate user conflicts and then review them, either in the User Conflicts form or in the User Conflicts report. The course of action for each conflict depends on its control type:

- For an Allow with Rules conflict, the user's access to conflicting entities should be permitted to continue.
- For a Prevent conflict, the user's access to one or both conflicting entities would have to be terminated.
- An Approval Required conflict could be approved or rejected. In either case, the
  reviewer should, for auditing purposes, assign status to the conflict in the User
  Conflict Actions form or the Mass Update User Conflicts form.

To allow or approve a conflict, you need do nothing in Oracle Applications.

To prevent or reject a conflict, you have four options. The first resolves a function- or responsibility-based conflict. The remaining three are appropriate for function-based conflicts — particularly those involving two functions within a single responsibility:

- In the Oracle Applications Users form, set the end date for at least one responsibility involved in the conflict to the current date.
- Exclude one of two conflicting functions from the responsibility through which the user has access to that function.
- Remove the function from menus through which the user has access to it, or remove a submenu containing a conflicting function from the user's menus.
- Exclude those menus from the responsibility that provides the user with access to the function.

See Oracle documentation for procedures on excluding functions or menus from responsibilities, or removing functions from menus. To facilitate mapping functions to menus, AppsAccess has a feature that defines the paths to menus on which functions reside:

- **1** In the User Conflicts form, select the row for a function conflict you want to resolve.
- **2** Click on Tools in the menu bar, and either Where Used or Conflict Where Used in the Tools menu:
  - If you selected Where Used, a Menu Path window shows the menus in which the "base entity," as defined in the AppsAccess conflict rule, resides.
  - If you selected Conflict Where Used, the Menu Path window shows the menus in which the "conflicting entity" resides. In this example, that entity is the Receipts function:

```
Menu Path - From Responsibility/Purchasing Super User) To Function (Receipts)

Receiving - PO_RECEIVING_GUI

Receipts - Receipts

- AZN_PR_PROCUREMENT

- Receipts
```

#### **Managing Cleanup**

The number of conflicts found by AppsAccess is typically quite large, numbering in the millions at some sites. This can affect the performance of the Generate User Conflicts process, but perhaps more importantly may result in a complex cleanup process. You can, however, take steps to manage the process effectively:

- As noted earlier, you may choose to identify a set of rules that are of the most immediate importance, generate conflicts only for them, and clean up those conflicts before implementing another set of rules. You may create only as many rules as you intend to run at a given moment, or you may create (or upload) all the rules you anticipate needing, but inactivate those you are not ready to run at a given moment. To inactivate a rule, load it in the Conflict Matrix and insert the current date in the End Date field. When you are ready to use the rule, reactivate it by editing it again to delete its end date.
- When you change conflict-rule definitions, run the Analyze Responsibility Conflicts concurrent request before generating a new conflict snapshot. It speeds the process of generating conflicts by reducing function conflicts to the responsibility level (and so permitting them to be matched to users who are assigned responsibilities).
- Some users may account for disproportionately large numbers of conflicts. You can exempt them temporarily from conflict-rule processing by configuring them as global subscribers (see page 12), and then generate and clean up conflicts associated with other, "ordinary" users. Once that's done, you can deactivate the global subscriber status for the "high intensity" users (all or some of them) and clean up their conflicts, continuing until all users are accounted for. You may anticipate in advance that some users (for example, those with superuser responsibilities) will be high-intensity. Or you may discover others when you generate conflicts, and at that point exempt them and generate a new conflict snapshot.
- You may identify a number of operating units (say, three) that are in most immediate need of cleanup, execute conflict rules only for them, clean up the resulting conflicts, and then move on to other operating units. You can focus on one or a set of operating units by, once again, creating global subscribers (see page 10), either by selecting operating units to be included in rule analysis, or by excluding all other operating units from rule processing.


#### **Automated Conflict Resolution**

Whenever a new user is created or an existing user is assigned new responsibilities, AppsAccess evaluates the assignment for violations of existing conflict rules, and then presents an option to "submit" or cancel it. If the assignment is submitted, AppsAccess denies access for a Prevent conflict, grants access for an Allow with Rules conflict, or sends on-line notifications to reviewers for an Approval Required conflict. A reviewer approves or rejects the last of these simply by responding to the notification.

#### **Activating Responsibilities**

The process begins in the Oracle Applications Users form, as a new user is created or an existing user receives new responsibility or function assignments. (See Oracle documentation for information on accessing the Users form and configuring users.)

- 1 With the User form open, a system administrator selects a user and, in the grid accessible from the Responsibilities tab, assigns responsibilities. Both the start and end dates for these responsibilities are set by default to the current date, and cannot be modified directly. The administrator saves the new assignments.
- 2 The administrator clicks on Actions in the menu bar, then on Assign Responsibilities in the Actions menu. An Activate Responsibilities form opens; it presents a copy of the responsibilities listed in the Users form, but allows the administrator to change the end dates.






#### Note

If the Assign Responsibilities option is inactive, use a Mass Associate feature, available in AppsForm or AppsFlow, to associate a function called AppsAccess Activate Responsibilities with either the responsibility or the menu from which you gain access to the Users form. For information on using the Mass Associate feature, see the user's guide for AppsForm or AppsFlow.

**3** The administrator removes end dates (or alters them to a future date) for a selection of responsibilities, and so provisionally grants access to them. He then clicks the Initiate Conflict Analysis button.

- 4 An Initiate Conflict Analysis form provides data about responsibilities for which the administrator changed end dates, noting those for which no conflict exists and listing all conflicts in which the responsibilities are involved. For each conflict, a Status field displays a message:
  - For a Prevent conflict, end dates will not be removed.
  - For an Allow with Rule conflict, end dates will be removed, provided that the conflict rule is associated with an AppsForm rule.
  - For an Approval Required conflict, an approval flow will be launched.



- **5** The administrator may, at this point, take either of two actions:
  - Click on the Cancel button to avoid assigning conflicting responsibilities. The Activate Responsibilities form would reappear; the administrator would click on its Cancel button, and then on the No button in a prompt to save changes. He can then reselect the Assign Responsibilities option in the Actions menu and try granting access to a different selection of responsibilities.
  - Click on the Submit button to accept the selection of responsibilities, even if it contains conflicts. AppsAccess then grants access to responsibilities with no conflicts. For responsibilities with Allow with Rules conflicts, it grants access if the conflict rule is associated with an AppsForm rule, but denies access if not. For responsibilities with Prevent conflicts, it denies access.

In these cases, "granting access" means setting end dates in the Users form to match those selected in the Activate Responsibilities form — or removing them if they have been removed in Activate Responsibilities. "Denying access" means setting end dates in the Users form to the current date.

For responsibilities involved in Approval Required conflicts, AppsAccess sends notifications to approvers. The end dates in the Users form remain temporarily set at the current date. Whether that value is made permanent or reset depends upon the approvers' responses to the notifications.

However, AppsAccess takes the most restrictive possible action when responsibilities are involved in multiple conflicts. For example, when a responsibility assignment violates both a Prevent and an Approval Required rule, access is denied and no notification is sent to approvers. The "pecking order" is Prevent, Approval Required, Allow with Rules, no conflict.

#### **Responding to Notifications**

For an Approval Required conflict, the approval workflow forwards a notification to the reviewer defined in the conflict rule. To respond to such a request:

1 Go to the Oracle E-Business Suite Home site and find the approval notification:



**2** Click on the notification to open it:



- Review information about the assignment of responsibilities that either are in conflict with one another or contain conflicting functions. Optionally, type a comment explaining the decision you are about to make.
- **4** Click one of the following buttons:
  - Approve: The user is given access to the responsibilities. When they were
    provisionally assigned, their end dates were removed or set to a future date in
    the Activate Responsibilities form. Approval of this notification resets the end
    dates in the Users form to match the setting in the Activate Responsibilities
    form. (This takes effect, however, only when the Oracle Workflow background process has run.)
  - Reject: The user is denied access to the responsibilities End dates in the Users form are set permanently to the dates that were current when the responsibilities where provisionally assigned.
  - Reassign: You reassign the conflict to another reviewer. The originally assigned end dates remain, but an approval by the other reviewer will remove them.
- **5** Click on the Return to Portal link.

The decision you make automatically updates the AppsAccess User Conflicts form.


# **Reports and Concurrent Requests**

AppsAccess provides a set of reports that presents not only the results of analysis for use in locating and resolving conflicts, but also, for auditing purposes, data about rule configuration and user exclusions. Reports are available in text and PDF formats. AppsAccess also accepts "concurrent requests" — it runs utility programs that archive data, prepare export files or load import files, reset values, and generate user conflicts.

### **Running Reports or Requests**

To run any of the reports or concurrent request programs:


**1** With the Logical Apps Navigator open, click on View in the Oracle Applications menu bar, then on Requests in the View menu. The Find Requests form appears:



**2** Click the Submit a New Request button. At the prompt, select Single Request and click OK. The Submit Request form appears:



- **3** In the Name list of values, select the name of the report or request you want to run. Click on the OK button.
- 4 If a report or request takes parameters, a Parameters form appears. To filter entries in a report or items subject to a request, select values for any number of parameters. Or, to include all possible entries or items, leave the parameters blank. Parameters vary from one report or request to another. (See the description of each report or request for a discussion of its parameters.) Click on the OK button.
- 5 In the Submit Request form, click on the Submit button. At the next prompt, make a note of the request number; then click on Yes to run another report or request, or no to return to the Find Requests form.
- **6** To see the results of a report, or check on the progress of a report or request, click on the My Requests in Progress radio button and then on the Find button. Or click on the Specific Requests radio button, type your request number in the Request ID field, and click on the Find button.
- A Requests form shows the status of your request. Click the View Output button to see results. (From this form, you can also click the Submit a New Request button to begin the process of generating another report or request.)



### **Conflicts Summary Report**

The Conflicts Summary Report shows the number of conflicts per application — the total and the number at each of the approved, rejected, pending, and prevent statuses. For each application, the report groups conflicts by responsibility. However, there are two ways in which a responsibility may be considered to be associated with an application: the first is a direct association, with a given responsibility linked to only one application. The second way is through the following linkage: an application is associated with a function, which is associated with a menu, which is granted to a responsibility. To ensure a correct count of both function- and responsibility-based conflicts for each application, the report bases its calculations on the second association. As a result, the report may show responsibilities within an application that are not directly linked to the application.

Moreover, a given conflict is counted in each of the applications (base and conflicting) it affects. A rule, for example, may define a conflict between two functions, each associated with a distinct application. If the rule were to generate 10 conflicts, the report would show 10 conflicts in each of the applications, for a total of 20.

As you generate the report, you can select these parameters:

- Run Date: Select a date to view summary values for conflicts generated up to that date. This parameter is required.
- Application: Select an application to view summary values for conflicts associated with that application. Or, leave the parameter blank to view summary values for conflicts associated with all applications.

The Conflicts Summary Report looks like this:

Ap	psAccess Coni	flicts Summar	У			
Instance: visdb					Page: 2 of 19	
Conc. Req. Id: 2720724					Date: 17-JUN-05 10:45 A	M
Snapshot Date: 16-JUN-05 01:02 PM						
Application Name Advanced Supply Chain	Planning					
Application name Advanced Supply chain						
Responsibility Name	Approved	Rejected	Pending	Prevent	Total	
Advanced Planning and Scheduling (Process	0	0	9	0	9	
Operations)	U		,	O	,	
Facility Operations, Vision Operations	0	0	62	50	112	
(USA)	Ü	·	02	30	112	
Maintenance Manager, Progress S&L	0	0	34	29	63	
Manufacturing Manager	0	0	160	132	292	
Manufacturing and Distribution Manager	0	0	257	210	467	
Manufacturing and Distribution Manager	0	0	50	36	86	
Vision Corporation Japan		ū	50	30	00	
Manufacturing and Distribution Manager	0	0	85	65	150	
Vision Services Japan		ŭ	03		230	
Manufacturing and Distribution Manager, Sao	0	0	130	110	240	
Paulo (BR)		ū	130	110	240	
Manufacturing and Distribution Manager,	0	0	38	3.0	68	
Vision Project Manufacturing USD	Ü	·	30	30	00	
Manufacturing and Distribution Manager,	0	0	72	58	130	
Vision Project Mfg		, and the second			130	
Manufacturing and Distribution Project	0	0	34	29	63	
User, Progress S&L		ŭ			03	
OPM All	0	0	14	12	26	
Project Manufacturing Manager	0	0	47	38	85	
Shop Floor Manager, Vision Operations	0	0	10	8	18	
shop frost manager, vision operacions	o o	0	10	Ü	10	
Totals	0	0	1002	807	1809	
TOTALS	U	0	1002	007	1003	

#### **Responsibilities with Conflicts Report**

The Responsibilities with Conflicts Report lists responsibilities for which conflicts exist, and identifies the components of each conflict as well as the rule that defines it. As you generate the report, you can select the following parameters:

- Application Name: Select an application to view responsibilities that have conflicts associated with the application. Or leave the parameter blank to view responsibilities that have conflicts associated with all applications.
- Responsibility: Select a responsibility to view only conflicts for that responsibility. Or leave the parameter blank to view conflicts for all responsibilities.
- Function: Select a function to view only conflicts involving that function. Or leave the parameter blank to view conflicts involving all functions. You can select a function only if you have first selected an application.
- Control Type: Select a control type Approval Required, Allowed with Rules, or Prevent — to view only conflicts of that type. Or accept the default value, All, to view conflicts of all types.
- Conflict Within Same Responsibility: Select *Y* (for yes) to view information on conflicts between functions within a responsibility, or *N* (for no) to view information on conflicts between entities across responsibilities. Or leave this parameter blank to view information on conflicts of both types.


The Responsibilities with Conflicts Report looks like this:

		AppsAccess Responsibilit		Report Run Date	: 17-JUN-2005 11:28:29
Instance : visdb				Page :	2 Of 3553
esponsibility	Function	Conflicting Responsibility	Conflicting Function	Control Type	Conflict Hale Dame
Purchasing Super User	Purchase Orders	Cost Management	Requisitions	Approval Required	EA PO/REQ
Purchasing Buyer	Purchase Orders	Cost Management	Requisitions	Approval Required	DA PO/REQ
iProcurement Super User	Purchase Orders	Cost Management	Requisitions	Approval Esquired	DA PO/REQ
Public Sector Purchasing Super User	Purchase Orders	Cost Management	Requisitions	Approval Required	DA PO/REG
Public Sector Purchasing Buyer	Purchase Orders	Cost Management	Requisitions	Approval Required	DA PO/REQ
Procurement Process, Operations	Purchase Orders	Cost Management	Requisitions	Approval Required	DA PO/RBQ
Purchasing, Vision Operations (UEA)	Purchase Orders	Cost Management	Requisitions	Approval Required	DA PO/REQ
All Procurement Operations	Purchase Orders	Cost Management	Requisitions	Approval Required	DA PO/HRQ
Buyer, Vision Operations (USA)	Purchase Orders	Cost Management	Requisitions	Approval Required	DA PO/REQ
Procurement Manager	Purchase Orders	Cost Management	Requisitions	Approval Esquired	DA PO/HRQ
Procure to Pay	Purchase Orders	Cost Management	Requisitions	Approval Required	DA PO/REQ
Purchasing, Vision Horway	Purchase Orders	Cost Management	Requisitions	Approval Esquired	DA PO/REQ
Purchasing Super User	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Required	DA PO/RRQ
Purchasing Buyer	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Esquired	EA 90/890
Procurement Super User	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Esquired	EA 90/890
Aublic Sector Purchasing Super User	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Required	DA PO/REQ
Public Sector Purchasing Buyer	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Required	DA PO/HRQ
Procurement Process, Operations	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Required	DA PO/REQ
Purchasing, Vision Operations	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Esquired	DA PO/REG
All Procurement Operations	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Esquired	DA PO/RRQ
Buyer, Vision Operations (USA)	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Esquired	DA PO/REG
Procurement Manager	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Esquired	DA PO/REQ
Procure to Pay	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Required	DA PO/REQ
Purchasing, Vision Norway	Purchase Orders	Cost Management GUI (No Update)	Requisitions	Approval Esquired	DA PO/REQ
Aurohasing Super User	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Required	DA PO/REQ
Purchasing Buyer	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Esquired	LA PO/RRQ
iProcurement Super User	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Required	EA PO/890
Public Sector Purchasing Super Joer	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Required	DA PO/REG
Public Sector Purchasing Buyer	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Esquired	DA PO/HRQ
Procurement Process, Operations	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Esquired	DA PO/HRQ
Purchasing, Vision Operations (UEA)	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Esquired	DA PO/REQ
All Procurement Operations	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Esquired	EA PO/889
Buyer, Vision Operations (USA)	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Required	DA PO/HRQ
rocurement Manager	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Esquired	EA PO/889
rocure to Pay	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Required	DA PO/HRQ
Aurchasing, Vision Norway	Purchase Orders	Cost Management GUI (No View)	Requisitions	Approval Esquired	DA PO/SSQ
Ost Management	Purchase Orders	Purchasing Super User	Requisitions	Approval Required	DA PO/HRQ
Cost Management GUI (No Update)	Purchase Orders	Purchasing Super User	Requisitions	Approval Required	DA PO/REQ
Cost Management GUI (No View)	Purchase Orders	Purchasing Super User	Requisitions	Approval Required	EA PO/890

#### **User Conflicts Report**

The User Conflicts Report presents information on the resolution of conflicts for individual users. It collects data generated when conflicts are resolved in the User Conflict Actions form. A system administrator would use information from the report to implement conflict-resolution decisions. As you generate the report, you can select the following parameters:

- Snapshot Run Date: Select a date to view summary values for conflicts generated up to that date. This parameter is required.
- Conflict Rule Name: Select a rule to view information on the resolution of conflicts generated by that rule. Or leave the parameter blank to see information on the resolution of conflicts generated by all rules.
- Control Type: Select a control type Approval Required, Allowed with Rules, or Prevent — to view only information on the resolution of conflicts generated by that type of rule. Or accept the default value, All, to see information on the resolution of conflicts generated by all types of rule.
- User Name: Select a user ID to view only information on the resolution of conflicts concerning that user. Or leave the parameter blank to see information on the resolution of conflicts concerning all users.






### **Conflict Matrix Report**

The Conflict Matrix Report lists conflict rules and, for each rule, displays the values that define it. As you generate the report, you can select the following parameters:

- Conflict Rule Name: Select a conflict rule to view information only about that rule. Or leave this parameter blank to see information about all rules.
- Entity Type: Select Function or Responsibility to view rules that find conflicts in one entity or the other, or Both to see both types of rule.
- Application Name: Select an application to view rules that involve that application, or leave the parameter blank to view rules that involve any application.
- Control Type: Select a control type Approval Required, Allowed with Rules, or Prevent — to view only information on conflict rules involving that type. Or accept the default, All, to see information on conflict rules involving all types.
- Conflicts Exist: Select Y (for yes) to list rules for which conflicts exist or N (for no) to list rules for which conflicts do not exist. Or leave the parameter blank to list both types of rule.
- End Dated Conflict: Select Y (for yes) to list rules for which conflicts are enddated or N (for no) to list rules for which conflicts are not end-dated. Or leave the parameter blank to list both types of rule.
- Same OU: Select Y (for yes) to list rules that apply within operating units or N (for no) to list rules that apply across operating units. Or leave the parameter blank to list both types of rule.
- Same SOB: Select Y (for yes) to list rules that apply within sets of books or N (for no) to list rules that apply across sets of books. Or leave the parameter blank to list both types of rule.

The Conflict Matrix Report looks like this:



## **Application Conflict Report**

The Application Conflict Report lists conflict rules and, for each, provides status information about each user affected by the rule — whether the conflict has been accepted or rejected or remains pending, and the start and end dates that apply to an approval decision. As you generate the report, you can select the following parameters:

- Snapshot Run Date: Select a date to view summary values for conflicts generated up to that date. This parameter is required.
- Application Name: Select an application to view information about rules that
  involve that application, or leave the parameter blank to view rules that involve
  any application.
- Conflict Rule Name: Select a conflict rule to view information only about that rule. Or leave this parameter blank to see information about all rules.
- Entity Type: Select Function or Responsibility to view information about rules
  that find conflicts in one entity or the other, or Both to see information about
  both types of rules.
- Control Type: Select a control type Approval Required, Allowed with Rules, or Prevent — to view only information on conflict rules involving that type. Or accept the default, All, to see information on conflict rules involving all types.
- Approval Status: Select Approved, Pending, or Rejected to see information about conflicts at one of these statuses, or retain the default value, All, to see information about conflicts at all statuses.

The Application Conflict Report looks like this:




#### **User Exclusions Report**

The User Exclusions Report lists all of the persons who have been granted exemptions for conflict-rule processing. Typically these are people, such as support personnel, who might require substantial super-user access, but who do not actually carry out the responsibilities or functions that are in conflict. Such users would therefore generate many user conflicts even though the conflicts need not be tracked. The User Exclusions report does not take any parameters, and looks like this:



#### **Extract Conflict Rules**

The Extract Conflict Rules concurrent request generates a CSV (text) file that contains a record of each active conflict rule — each rule that is not end-dated. The file can then be used for uploading conflict rules into another Oracle Applications instance. The Extract Conflict Rules request takes no parameters, and it produces output looks like the following:



Save the output as a CSV file in order to upload it to another instance.

#### **Load Conflict Rules**

The Load Conflict Rules concurrent request uploads conflict-rule definitions from a CSV file. That file is generated either by the Extract Conflict Rules concurrent request or from a spreadsheet provided by Logical Apps. For a detailed procedure for using the Load Conflict Rules concurrent request, see page 13.

#### **Archive User Conflict Data**

The Archive User Conflict Data concurrent request archives records of older conflicts to a history table. This request takes, as its only parameter, a date in the format configured for your instance of Oracle Applications; the request archives conflicts generated before that date.

#### **Reset User Conflicts**

The Reset User Conflicts concurrent request in effect rescinds the assignment of conflicting responsibilities to a user. Ordinarily, such a conflict would be approved (and end dates for the responsibilities would be removed) or rejected (and end dates retained). Until then, however, the user has no access to the responsibilities and the assignment cannot be changed. If the approval decision is never made (if, for example, the designated reviewer leaves the company), the Reset User Conflicts request can be run so that the user's assignments are returned to their original state, and the assignment can be made again (with the conflict rule rewritten to designate another reviewer). The request takes, as its only parameter, the user ID of the user whose conflicts are to be reset.

### **Analyze Responsibility Conflicts**

The Analyze Responsibility Conflicts concurrent request runs conflict rules in order to reduce conflicts to the responsibility level. That is, before function conflicts can be recognized as applying to users, they must be recognized as existing in the responsibilities that are assigned to users. The Analyze Responsibility Conflicts request performs this step; running this request therefore speeds the process of generating user conflicts. This request takes no parameters.

#### **Generate User Conflicts**

The Generate User Conflicts concurrent request analyzes the assignments of responsibilities to users and determines which assignments violate conflict rules. Running this concurrent request is equivalent to clicking the Generate User Conflicts button in the Conflict Matrix form (see page 17). This request takes no parameters.

#### **Cache WF User Roles**

The Cache WF User Roles request refreshes a table called laa\_wf\_user\_roles, which holds workflow-role data used only by AppsAccess. Typically you need not run this request, because equivalent processing occurs each time user conflicts are generated, either through use of the Generate User Conflicts button (see page 17) or the Generate User Conflicts concurrent request (see above). You may, however, choose to run it when a reviewer is updated in an AppsAccess rule or when there is an update to workflow roles used as AppsAccess reviewers

# Support

From on-site support to remote phone and web support, the Logical Apps team of experienced professionals provides the help and information you need to ensure quick and effective implementation. The Logical Apps team includes a Technical Support Representative, an Account Manager, and a Logical Apps staff consisting of consultants and support specialists.

#### **Feedback**

Thank you for using Logical Apps AppsAccess. We value your comments and feedback. Mail your comments to the following address, or call us directly at (949) 453-9101.

Logical Apps Attn: Documentation Management 15420 Laguna Canyon Road Suite 150 Irvine, CA 92618 U.S.A.

Or send email to support@Logical Apps.com.