

AppsRules Suite

Installation Guide

Software Version 6.5

© 2005 Logical Apps

All rights reserved. Printed in USA.

Restricted Rights Legend

This software and associated documentation contain proprietary information of Logical Apps. It is provided under a license agreement containing restrictions on use and disclosure and it is also protected by copyright law. Reverse engineering of this software is prohibited.

The information contained in this document is subject to change without notice. If you find problems in the documentation, report them to support@logicalapps.com. Logical Apps does not warrant that this document is error free. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Logical Apps.

AppsAccess, AppsAudit, AppsControl, AppsExtend, AppsForm, AppsFlow, and AppsRules are trademarks of Logical Apps. All trademarks and registered trademarks are the property of their respective owners.

Document Version AR011-650C

10/14/05

Submit product enhancement requests through email at support@logicalapps.com. The majority of our product enhancements come from client requests.

Logical Apps
15420 Laguna Canyon, Suite 150
Irvine, CA 92618
949.453.9101

Contents

AppsRules Suite Installation Overview.....	1
Preparatory Procedures	2
Installing AppsRules Suite	5
Creating a User and Tablespace	5
Installing Database Server Components.....	6
Installing Forms Server Components	11
CUSTOM.pll Modifications	14
Configuring the Remote Compilation.....	16
Bouncing the Servers	18
Postinstallation Tasks	19
AppsFlow	19
AppsAudit	20
AppsAccess and AppsControl	22
AppsAccess Concurrent Program	24
Special Cases	24

Validation27
 Installation History32

AppsRules Suite Installation Overview

The AppsRules Suite is a set of five integrated applications that work with Oracle Applications to define business processes, enhance security, and safeguard data integrity:

- AppsForm modifies the security, navigation, field, and data properties of Oracle Applications forms.
- AppsFlow works with Oracle Applications Workflows to define and implement business processes.
- AppsAudit tracks changes to the values of fields in database tables and displays reports that present information about changes to each field.
- AppsControl applies change control to Oracle Applications fields — it can monitor change, require a reason for a change, or require approval for a change.
- AppsAccess defines and detects segregation-of-duties conflicts, either preventing them from occurring or uncovering them so that they can be properly managed.

These applications are installed on the database and forms servers on which Oracle Applications run. The installation process implements the following architecture:

- Database Schema: Installation requires the identification of a schema for use by Logical Apps applications. Logical Apps recommends strongly the creation of a new schema named XXLAAPPS. However, a user who has already established a schema for third-party products may choose to use that schema instead.

- **Tablespace:** Logical Apps recommends creating a tablespace for indexes used by Logical Apps database objects. (An already established tablespace may be used.)
- **Database Objects:** AppsRules makes use of database tables, packages, sequences, and workflows, which are placed in the `XXLAAPPS` (or user-specified) schema. All Logical Apps table names begin with the prefix `LA`.
- **Application Server Objects:** AppsRules uses custom forms, which are installed on the application server. Custom forms are located in the `$XXLAAPPS_TOP/forms/US` directory.
- **Program Executables:** AppsRules uses program executables to report on, migrate, and compile business rules. The following objects are installed on the concurrent manager server (typically the database server): reports, programs, and Java files. Custom programs are located in the `$XXLAAPPS_TOP/forms/US` directory; some executable programs may also reside in the `$XXLAAPPS_TOP/bin` directory.

Logical Apps provides two comprehensive Installer programs that place AppsRules applications on the database and forms servers. (In addition, they install AppsCore, a rules engine that provides functionality to the applications.) Each Installer may be run in either of two modes:

- **GUI:** The Installer presents a series of windows that prompt you to provide information necessary for the installation. Each window also provides access to a help file. As you progress through the windows, you can return to windows you had completed earlier in order to review or change the entries in them. (The Installer retains any entry you don't change, even if you return to a step earlier than the one in which such an entry was made.) GUI mode is the default.
- **Console:** The Installer presents a series of command prompts in a UNIX console, in response to which you provide information necessary for the installation. Console mode prompts for the same information as GUI mode, but does not enable you to return to earlier prompts and does not provide help screens.

To run each Installer program, you would type its name — `ladbinstall.bin` or `lafrminstall.bin` — at the UNIX command prompt. The name alone launches the GUI mode; the name along with the argument `-i console` launches the console mode.

Preparatory Procedures

Before installing AppsRules, ensure that the following requirements have been met:

- Grant the following APPS schema objects the select privilege to the `XXLAAPPS` schema:
 - `FND_FILE` — Package Spec and Body
 - `FND_PROFILE` — Package Spec and Body
- Confirm that Java is in your path. Type the following at the UNIX command prompt:
`which java`

- Verify that you use Java version 1.3 or higher. Type the following at the UNIX command prompt:

```
java -version
```

If more than one copy of Java exists on your system, verify the version on the copy in the opt directory (for example, /usr/opt1.3/bin/java).

- Ensure that the Oracle Advanced Security product is installed. (Logical Apps uses DBMS_Obfuscation for encrypting the password.) Type the following at the UNIX command prompt:

```
adapters
```

Look for Oracle Security Server Authentication Adapter among the return values.

- Each of your database server, forms server, and concurrent manager server may run on its own host machine. If so, complete the following tasks to confirm that the host machines communicate properly:
 - Send a file via FTP from the database server to the concurrent manager server, and from the concurrent manager server to the forms server.
 - Perform a remote execution of the shell file, by any of the following methods: Enable rsh (remote shell), enable ssh (secured shell), have a common mount point, manual.

Installing AppsRules Suite

In broad terms, the AppsRules Suite installation process involves four steps:

- 1** Create a tablespace for Logical Apps indexes, and a custom database user/schema. Logical Apps recommends strongly that the user/schema be named `XXLAAPPS`.
- 2** Run the Installer program to place Logical Apps tables, packages, sequences, and workflows on the database server. All Logical Apps table names begin with the prefix `LA`, and all tables reside in the `XXLAAPPS` schema. The database server installation must precede the forms server installation.
- 3** Run the Installer program to place Logical Apps forms on the forms server. All custom forms are located in the `$XXLAAPPS_TOP/forms/US` directory.
- 4** Configure a remote compilation feature, which makes libraries resident on the concurrent server available to the forms server.

Creating a User and Tablespace

To begin the installation process, download the file `LOGICALAPPS.zip` to a temporary directory on your local system from the FTP site provided by Logical Apps. From it, extract the two files — `ladbinstall.bin` and `lafrminstall.bin` — you will run for database and forms installation.

Next, create the Logical Apps tablespace and database user/schema. The latter must be granted the connect and resource privileges in the Oracle Applications database. Logical Apps recommends using the name `XXLAAPPS` for the new user, and creating all Logical Apps database objects in the `XXLAAPPS` schema.

The following is a sample SQL script that can be used to create the user:

```
CREATE USER XXLAAPPS
IDENTIFIED BY XXLAAPPS
DEFAULT TABLESPACE &DEF_TSPACE
TEMPORARY TABLESPACE &TMP_TSPACE
QUOTA UNLIMITED ON &DEF_TSPACE
QUOTA 0K ON SYSTEM;

GRANT CONNECT TO XXLAAPPS;
GRANT RESOURCE TO XXLAAPPS;
```

Allocate a minimum of 80 megabytes of space, 40 on the tmp directory and 40 on the file system from which the installer is to be launched.

Installing Database Server Components

To install database server components of AppsRules, run the file `ladbininstall.bin`:


- 1 Transfer the `ladbininstall.bin` file to the database server, via FTP in binary mode. Use the `applmgr` account.
- 2 Use `applmgr` to log in to the database server. Ensure that the user (login ID) has write and read privileges on `$APPL_TOP`.
- 3 Execute the environment file, if it is not included in the profile:
`$. $APPL_TOP/$APPLFENV`
- 4 Set the execute permission on `ladbininstall`:
`$. chmod +x ladbininstall.bin`
- 5 Execute `ladbininstall.bin`. Use the file name alone to run the Installer in GUI mode; add the argument `-i console` to run the Installer in console mode.

As noted earlier, the Installer's GUI and console modes prompt for the same information. If you choose GUI mode (as shown in the following procedure for using the installer), you can perform these operations in each of the windows:


- Review a brief description of the information you need to provide.
- Click on the Help button to open a window that provides a more expansive description of the information you need to provide. (After you review this information, click on the Close button to exit the Help window.)
- Type installation information in the labeled text boxes (or accept default values).
- When you complete one window, click on the Next button to move from it to the next window.
- Click the Previous button if you wish to return to a window you completed earlier.
- Note that the titles of the windows you are to complete appear in a column along the left of each window. Those yet to be completed are shown in grey; windows that have been completed are shown in black.

To complete the database server installation:

- 1 Enter your customer name and license key as they were provided to you by Logical Apps. The fields are case-sensitive. When you click Next, a message displays the applications you are licensed to install; click the OK button to clear the message.



- 2 Specify a staging directory — a temporary location for source files:



The Installer suggests a default directory; its name is a timestamp for the moment you perform the installation, with *DB* (for database). If you wish to select another directory, click the Choose button and, in a Select a Folder window, navigate to the directory you want. If you specify a nonexistent directory, the Installer creates that directory. If you navigate away from the default directory and want to return

to it, click on the Restore Default Folder button. Make a note of the directory name; you'll need it later, when you configure remote compilation.

- 3 Verify the default values for the host name, SID (service identifier) and network port of the Oracle Applications database server, which the Installer takes from the shell environment. If the defaults are not correct, enter correct values.

The screenshot shows the 'LogicalApps Database Install' window with the 'Database Host' tab selected. The left sidebar lists the installation steps: License Key, Staging, Database Host (selected), Database Schema, Application TOP, Environment, Input Summary, Installing..., and Installation. The main area contains instructions: 'Specify the database host name, service SID, and TNS port of the database in which Logical Apps applications are to be installed.' Below this are three input fields: 'Database Host Name' with the value 'mammoth.whq.logicalapps.com', 'SID' with the value 'visdb', and 'Port' with the value '1521'. At the bottom, there are buttons for 'Cancel', 'Help', 'Previous', and 'Next', and a footer that reads 'InstallAnywhere by Zero G'.


- 4 Supply log-on values for the Logical Apps and Oracle Applications (APPS) schemas:

The screenshot shows the 'LogicalApps Database Install' window with the 'Database Schema' tab selected. The left sidebar is the same as in the previous screenshot, with 'Database Schema' now selected. The main area contains instructions: 'Supply credentials for the Logical Apps schema and APPS schema. It is strongly recommended that you use the name XXLAAPPS for the Logical Apps schema.' Below this are four input fields: 'LogicalApps Schema' with the value 'XXLAAPPS', 'Password' (empty), 'Oracle APPS Schema Password' (empty), and 'Index Table Space' (empty). At the bottom, there are buttons for 'Cancel', 'Help', 'Previous', and 'Next', and a footer that reads 'InstallAnywhere by Zero G'.

As noted earlier, Logical Apps recommends strongly the creation of a dedicated schema called XXLAAPPS, and the Installer provides this value by default. If you follow the recommendation, accept the default; otherwise, replace it with the name of the schema you will use for Logical Apps database objects. Also enter

the passwords for the Logical Apps and Oracle APPS schemas, and the name of the tablespace for indexes used by Logical Apps database objects.

- 5 Establish the Logical Apps TOP — the high-level directory for the storage of AppsRules files. Specify a directory that is the parent of the Logical Apps TOP and an application short name that is appended to the parent directory to form the Logical Apps TOP directory.



By default, the Installer selects the Oracle Applications TOP as the parent directory and XXLAAPPS as the application short name. These values are recommended, but you can change them. (To select another parent directory, click on the Choose button and, in a Select a Folder window, navigate to the directory you want. If you enter the name of a nonexistent directory, the Installer creates that directory. To return to the default directory, click the Restore Default button.)


If you have selected an application short name that is already in use, the Installer displays a warning message when you click the Next button:



To respond to this warning:


- Click Enter Again to return to the Application TOP form and set a new value.
- Click Continue to accept the duplicate application short name. Doing so, however, would cause AppsRules and another application to share the name, with the risk that files for one application or the other might be overwritten.
- Click Abort to abandon the AppsRules installation.

- 6 Specify paths to files that contain environment variables for the Oracle Applications shell. (The installation appends Logical Apps-specific entries to these files.)



Accept the defaults, or click a Choose button and, in a Select a Folder window, navigate to a directory you want. If you enter the name of a nonexistent directory, the Installer creates that directory. To return to the default directory, click the Restore Default button.

- 7 Review your selections in the Input Summary form:



If you determine that any of the entries is inappropriate, you can click on the Previous button until you reach the form in which you selected the entry, and

change it. (The Installer retains any entries you don't change, even if you pass by them as you return to an earlier step in the installation process.)

- 8** Note that in the Input Summary form, the label for the button at the lower right has changed from *Next* to *Install*. When you are satisfied with the selections you have made in preceding forms, click on the Install button to complete the database server installation.

The Installer displays error messages (if any are warranted) upon completing the installation of each Logical Apps application, and displays an overall status upon completing the installation of all products. If the overall status is Success, the installation has finished with no errors.

If errors occur, they or the overall status may be classified as Warning, Nonfatal, or Fatal, depending on severity. The Installer recovers (restores the system to its state prior to the installation) for Fatal errors, but not for Warning or Nonfatal errors. For details about errors and the installation process, navigate to the directory from which the Installer ran and review two log files: LADB_LOG_*timestamp*.log and LADB_ERROR_*timestamp*.log, where *timestamp* is the date and time at which the Installer ran.

Installing Forms Server Components

To install forms server components of AppsRules, run the file lafrminstall.bin:

- 1** If the database and forms servers run on the same host, re-source the environment by opening a new shell.
- 2** Transfer the lafrminstall.bin file to the forms server, via FTP in binary mode. Use the applmgr account.
- 3** Use applmgr to log in to the forms server. Ensure that the user (login ID) has write and read privileges on \$APPL_TOP.
- 4** Execute the environment file, if it is not included in the profile:

```
$..$APPL_TOP/$APPLFENV
```
- 5** Set the execute permission on lafrminstall:

```
$.chmod +x lafrminstall.bin
```
- 6** Execute lafrminstall.bin. Use the file name alone to run the Installer in GUI mode; add the argument *-i console* to run the Installer in console mode.

Most windows (or console prompts) for the forms installation are identical to those for the database installation. If you select GUI mode, each window enables you to perform the same operations as you could in the database-server Installer (see page 6).

To complete the forms server installation:

- 1** In the License Key window, once again enter the customer name and license key provided to you by Logical Apps. These are the same as the values you entered for the database-server installation. Once again, when you click the Next button a messages displays the applications you are licensed to install; click the OK button to clear the message.

- 2 In the Staging form, once again select a directory for the temporary placement of source files. The Installer once again suggests a default — its name this time a time-stamp for the moment you perform the installation, along with *FRM* (for forms).

If you wish to select another directory, click on the Choose button. In a Select a Folder window, navigate to the directory you want. If you specify a nonexistent directory, the Installer creates that directory. If you navigate away from the default directory and want to return to it, click on the Restore Default Folder button.

- 3 In the Database Host form, select the database host name used where the database installation has been run, and the appropriate SID and port values.
- 4 The Database Schema window is changed slightly from its corresponding window in the database-server Installer program. There is no longer an Index Table Space field (as that field would be inapplicable to forms installation), but where the database-server Installer requested only a password for the Oracle Applications schema, the forms-server Installer asks for a name as well:

For the Apps Schema field, accept the default value, APPS. (This needs to match the database-server value, which is hard-coded.) For each of the remaining fields, enter the same value as you entered for the database installation.

Once again, Logical Apps recommends strongly the creation of a dedicated schema called XXLAAPPS, and the Installer provides this value by default. If you follow the recommendation, accept the default; otherwise replace it with the name of the schema you will use for Logical Apps database objects. Also enter the passwords for the Logical Apps and Oracle APPS schemas.


- 5 In the Application TOP form, establish the Logical Apps TOP for the forms server — the highest-level directory for the storage of AppsRule files. Specify a directory that is to serve as the parent of the Logical Apps TOP, and an application short name that is appended to the parent directory to form the Logical Apps TOP directory.

The Installer defaults to the forms-server-specific Oracle Applications TOP as the parent directory and XXLAAPPS as the application short name. These values are recommended.

Ensure, however, that the application short name for the forms server is the same as the one you selected for the database server. If you wish to select another parent directory, click on the Choose button and, in a Select a Folder window, navigate to the directory you want. If you enter the name of a nonexistent directory, the Installer creates that directory. To return to the default directory, click the Restore Default button.

The forms-server Installer, like its database-server counterpart, presents a warning if you select an application short name that is already in use and it presents the same response options:

- Click Enter Again to return to the Application TOP form and set a new value.
 - Click Continue to accept the duplicate application short name. Doing so, however, would cause AppsRules and another application to share the name, with the risk that files for one application or the other might be overwritten.
 - Click Abort to abandon the AppsRules installation.
- 6** In the Environment form, specify paths to files that contain environment variables for the Oracle Applications shell. (The installation appends Logical Apps-specific entries to these files.) Accept the defaults, or click a Choose button and, in a Select a Folder window, navigate to a directory you want. If you enter the name of a nonexistent directory, the Installer creates that directory. To return to the default directory, click the Restore Default button. In any case select values that are appropriate for the forms server.
- 7** When you complete the Environment form, the forms server Installer presents a CUSTOM.pll form:



Forms server installation requires that an existing CUSTOM.pll file be modified so that it can link to an LACUSTOM.pll file. If you select Yes, the Installer backs up your existing CUSTOM.pll, and then overwrites the original with a modified copy that contains the necessary links to LACUSTOM.pll. (The backup copy has a time-stamp appended to the .pll file extension.) If your existing CUSTOM.pll contained any customization, a Yes selection in this form would require you to copy your customizations manually from the backup file to the Logical Apps-provided CUSTOM.pll.

If you select No, the Installer retains your existing CUSTOM.pll. In this case, you need to edit the file to insert links to LACUSTOM.pll (see below).

- 8 In the Input Summary form, review the selections you have made. If you determine that any of the entries is inappropriate, you can click on the Previous button until you reach the form in which you selected the entry, and change it. (The Installer retains any entries you don't change, even if you pass by them as you return to an earlier step in the installation process.)
- 9 When you are satisfied with the selections you have made in preceding forms, click on the Install button in the Input Summary form to complete the forms server installation.

The Installer displays error messages (if any are warranted) upon completing the installation of each Logical Apps application, and displays an overall status upon completing the installation of all products. If the overall status is Success, the installation has finished with no errors.

If errors occur, they or the overall status may be classified as Warning, Nonfatal, or Fatal, depending on severity. The Installer recovers (restores the system to its state prior to the installation) for Fatal errors, but not for Warning or Nonfatal errors. For details about errors and the installation process, navigate to the directory from which the Installer ran and review two log files: LAFRM_LOG_ *timestamp*.log and LAFRM_ERROR_ *timestamp*.log, where *timestamp* is the date and time at which the Installer ran.

CUSTOM.pll Modifications

If you chose (in step 7) not to overwrite your CUSTOM.pll file, edit the CUSTOM.pll file. (If you selected Yes in step 7, ignore this section and skip ahead to “Configuring the Remote Compilation.”)

- 1 In place of the existing code for *Procedure Event(event_name varchar2)*, substitute the following:

```
PROCEDURE event(event_name varchar2) is

    form_name          varchar2(30) := name_in('system.current_form');
    block_name          varchar2(30) := name_in('system.cursor_block');
    field_name          varchar2(30) := name_in('system.current_item');
    function_name       varchar2(30);
    parameters          varchar2(2000);
```

```

begin
  if (event_name = 'ZOOM') then
    la_enhncmtmgr_pkg.la_zooms(form_name,block_name,function_name,
      parameters);
    if function_name is not NULL
    then
      if parameters is null then
        fnd_function.execute(function_name,'Y','N');
      elsif 'ZOOMSPECIAL' = substr(parameters,1,11) then
        lacustom.event('ZOOMSPECIAL'); -----new code 081903
      else
        parameters := lazoom.zoom_event(parameters);
        fnd_function.execute(function_name,'Y','N',parameters);
      end if;
    end if;
  -----WNF
  elsif (event_name='WHEN-NEW-FORM-INSTANCE') then
    lacustom.event('WNF');
  -----WNB
  elsif (event_name = 'WHEN-NEW-BLOCK-INSTANCE') then
    lacustom.event('WNB');
  -----WNI
  elsif (event_name = 'WHEN-NEW-ITEM-INSTANCE') then
    lacustom.event('WNI');
  -----WNR
  elsif (event_name = 'WHEN-NEW-RECORD-INSTANCE') then
    lacustom.event('WNR');
  -----WNV
  elsif (event_name = 'WHEN-VALIDATE-RECORD') then
    lacustom.event('WVR');
  -----
  elsif (substr(event_name,1,7) = 'SPECIAL') then
    execute_menu(event_name);
  -----
  else lacustom.event(event_name);  --put other events here
  end if;
end event;

```

- 2** In place of the code for *Function zoom_available*, substitute the following:

```

FUNCTION zoom_available return boolean is
  v_enabled    varchar2(20);

begin  --x
  v_enabled := lazoom.zoom_enabled;
  IF v_enabled = 'TRUE' THEN
    return TRUE;
  else
    return FALSE;
  end if;
RETURN NULL;
end zoom_available;

```

- 3** Attach the following libraries. (Remove the path when attaching the libraries.)

- LACUSTOM.pll
- LABRSQL.pll

- 4** Compile the file and ensure there are no compilation errors.

Configuring the Remote Compilation

To finish the installation, you must configure a remote compilation feature, which makes libraries resident on the concurrent sever available to the forms server.

- 1 Log on to the database server.
- 2 If you don't already know it, determine the full path to the Java executable. At the command prompt, type:

```
which java
```

- 3 Navigate to the staging directory (which you selected in step 2 of the database server installation process).

- 4 Grant the execute permission on a file called laconfig.sh:

```
chmod +x AppsCore/db/scripts/laconfig.sh
```

- 5 Run the laconfig.sh file:

```
AppsCore/db/scripts/laconfig.sh arg1 arg2
```

- In place of *arg1*, insert the full path of the Logical Apps TOP directory, followed by “/bin.” Note that the path to the Logical Apps TOP directory typically contains more than the values you selected in step 5 of the database server installation process. To determine the path to this directory, use the echo command, specifying the application short name you selected in step 5 of the database server installation, followed by “_TOP.” For example:

```
echo $XXLAAPPS_TOP
```

As an example of a correct value for *arg1*, the path to the Logical Apps TOP configured on page 9 might be:

```
/oracle/bin/ebiz115/appl/XXLAAPPS/11.5.0/bin
```

- In place of *arg2* insert the full path of the staging directory (which you selected in step 2 of the database server installation process), followed by “/AppsCore.” For example, the correct value for the staging directory configured on page 7 might be:

```
/export/home/oracle/rkstage/DB_27Jun2005_134434/AppsCore
```

Running the laconfig.sh file produces a series of command-line prompts. Respond to them as follows:

- 1 Enter the full path of the Java executable.
- 2 The following prompt appears:

```
Choose your Configuration from below:
```

1. Single-Tier (all tiers on a single node)
2. Multi-node (a separate node for each server)
3. Two Node (one database/concurrent proc. node, one forms/web node)
4. Two Node (one forms/concurrent proc. node, one database node)
5. Exit Program

Enter 1 if all of the database, forms, and concurrent servers reside on a single machine; enter 2 if each resides on its own machine; enter 3 if the database and concurrent servers reside on one machine, and the forms server on another; enter 4 if the forms and concurrent servers reside on one machine, and the database server on another.

3 The following prompt appears:

```
Environment File is 'filename'
Does this environment file set Oracle Home (Y/N)
```

Select *Y* for yes or *N* for no as appropriate. If you select *N*, the system prompts you for the name of the file that does set the Oracle Home; enter the file name.

4 If you selected option 2, 3, or 4 in step 2, the following prompt appears:

```
Choose the execution method from below:
1) Secured Shell - ssh
2) Remote execution - rexec
3) Manual
```

Enter the number corresponding to the protocol you will use for communication among the machines on which your servers reside.

5 If you selected option 2, 3, or 4 in step 2, the following prompt appears:

```
Enter the Number of Form Servers:
```

Enter the number of form servers you have.

6 The following set of prompts appears once for each of the form servers you enumerated in step 5 (with the *x* replaced by a form server number):

```
Enter the Form Server Number x Host Name:
Enter the Login ID:
Enter the Password:
Enter the full path of Logical Apps binaries on the FORM
Server:
```

For each set of prompts, enter the host name, the login ID for the owner of APPL_TOP, that owner's password, and the appropriate path. You can get the last of these values by logging on to the form server and typing the following command:

```
echo @XXLAAPPS_TOP_bin
```

Once you have finished executing the laconfig.sh file, verify that the following files exist and make sure both the Java path and Classpath are set correctly:

- Database server (under \$XXLAAPPS_TOP/bin): LAGENLIB.prog, LAMIGRATE.prog, LAIMPORT.prog
- Forms server: LAFORMSGEN.prog

Finally, if you want to enable migration (the ability to port AppsRules configurations from one instance to another) with password security:

- 1** Navigate to \\System Administration Responsibility\\Profile\\System.
- 2** Query for the LAAPPS: Enable Migration Security profile option.
- 3** Set the value to Yes at site level. (This can be controlled further at the responsibility and user levels.)

Bouncing the Servers

When you finish configuring the remote compilation feature, bounce both the form server and the concurrent manager server.

Postinstallation Tasks

Once the installation is complete, you must perform additional tasks specific to the applications you've installed.

AppsFlow

To use AppsFlow, run the Synchronize WF LOCAL Tables concurrent program:

- 1** Log on to the System Administrator responsibility in Oracle Applications.
- 2** Click on View in the Oracle Applications menu bar, then on Requests in the View menu. The Find Requests form appears.
- 3** Click the Submit a New Request button. At the prompt, select Single Request and click OK. The Submit Request form appears.
- 4** In the Name list of values, select Synchronize WF LOCAL Tables. Click on the OK button.
- 5** A Parameters form appears. Enter the following values (as shown at the top of the next page), then click on the OK button:
 - Orig System: ALL
 - Parallel Processes: 1
 - Logging Mode: LOGGING
 - Temporary Tablespace: Choose an appropriate temporary tablespace.
- 6** In the Submit Request form, click on the Submit button.

Submit Request

Run this Request...

Name: **Synchronize WF LOCAL tables**

Parameters: **American English**

Orig System: **ALL** All Orig Systems

Parallel Processes: **1**

Logging Mode: **LOGGING** Logging Activated

Temporary Tablespace:

OK Cancel Clear Help

AppsAudit

To use AppsAudit, complete three tasks. First, set the AuditTrail:Activate profile option to Yes:


- 1 Log on to the System Administrator responsibility in Oracle Applications.
- 2 In the Navigator, select Profile, then System.
- 3 In the Find System Profile Values form, select AuditTrail:Activate in the Profile list of values. Then click on the Find button.
- 4 Ensure that the AuditTrail:Activate option is set to Yes at the Site level:

Profile	Site	Application	Responsibility	User
AuditTrail:Activate	Yes			

Second, add the LACSVREPORT style to the printer you will use for AppsAudit:

- 1 In the System Administrator responsibility, select Install, then Printer, then Register.
- 2 A Printers form appears. In its Printer list of values, select the printer you wish to use with AppsAudit. Note the value that appears in the Type field when you select the printer, and then click on the Printer Types button.
- 3 A Printer Types form appears. In its Type field, query for the Type you noted in step 2. (Press the F11 key; enter the Type value in the Type field; press Ctrl+F11.)


- 4 In the Style list of values, select LACSVREPORT. (The software automatically supplies an associated value under Driver Name.)



- 5 Click on File in the menu bar, then on Save in the File menu.

Third, modify the report style:

- 1 Still in the System Administrator responsibility, select Concurrent, then Program, then Define.
- 2 A Concurrent Programs form appears. In its Program field, query for Logical Apps AppsAudit Report. (Press the F11 key; enter *Logical Apps AppsAudit Report* in the Program field; press Ctrl+F11.)
- 3 The Style field displays the value Landwide. Change this to Landscape.




- 4 Click on File in the menu bar, then on Save in the File menu.

AppsAccess and AppsControl

To use AppsAccess you must import two xml files, and to use AppsControl you must import three xml files. To do so, you use a migration utility, which the Installer programs set up automatically as a part of the installation process.


First, ensure that the migration utility is configured correctly:

- 1 Log on to the Logical Apps responsibility in Oracle Applications. In that responsibility, select AppsRules.
- 2 Once the AppsRules form is open, click on Logical Apps Utilities in the menu bar, then on Migration Setup in the Utilities menu.
- 3 A Migration Utility form appears. Ensure that the Setup Host Names tab is selected:



Host Name	Description
newport.whq.logicalapps.com	Dev
cypress.whq.logicalapps.com	QA

- 4 Confirm that the database server host name (the one selected in step 3 of the database server installation process) is displayed in the Host Name column. The Installer program should have inserted this value during installation.
- 5 Click on the Setup Instances tab:



Host Name	Instance	Port Number	User Name	Password
newport.whq.logicalapps.com	visdev	1525	apps	
cypress.whq.logicalapps.com	visdb	1521	apps	

Connect String

- 6 Ensure that appropriate values are displayed in the Host Name, Instance (SID), Port Number, User Name, and Password columns. (The first three values are

those specified in step 3 of the database server installation process, and the last two are those specified in step 4.) Again, the Installer should have inserted these values automatically.

- 7** Having confirmed these values (or, if necessary, entered them), close the Migration Utility form.

The five xml files are located in subdirectories of the staging directory you selected in step 2 of the database server installation process. For AppsAccess the files are located in *StagingDirectory*/AppsAccess/db/scripts, and include the following:


- laa_apps_access_rule.xml
- laa_apps_access_flow.xml

For AppsControl the files are located in *StagingDirectory*/AppsControl/db/scripts, and include the following:

- appscontrol_notification.xml
- appscontrol_approval.xml
- appscontrol_reject.xml

For each application, the files must be imported in the order shown. Complete the following procedure once for each of the files:

- 1** With AppsRules open, click on Logical Apps in the menu bar, then on Import from File in the Utilities menu. An Import from File form appears:



- 2** In the directory box, type the path to the folder that contains the import file.
- 3** In the File Name box, type the name of the file you want to import.
- 4** Select a value for Debug Level. Ordinarily, select Low; select High instead if you need to uncover the cause of a failed import.
- 5** Click on the Import button. A concurrent request message displays the ID number of the concurrent request under which the import operation is carried out. Click on the OK button to clear the message.

AppsAccess Concurrent Program

If you are upgrading AppsAccess from an earlier version, the name of one of its concurrent programs may not have been updated correctly. To correct the program name:

- 1 Log on to the System Administrator responsibility in Oracle Applications.
- 2 In the Navigator, select Concurrent, then Program, then Define. The Concurrent Programs form opens.
- 3 Query for the Conflict Data Purge program: Press F11, type the phrase *LA AppsAccess Conflict Data Purge* in the Program field, and press Ctrl+F11.

- 4 In both the Program and Description fields, type the following new value for the name of the program: *LA AppsAccess Archive User Conflict Data*. Do not change any other values.
- 5 Save the change: Click on File in the menu bar, and then Save in the File menu. Then close the Concurrent Programs form (click on the × symbol).

If you are performing a new installation of AppsAccess, this issue does not arise; the program is named correctly, and you need not take any corrective action.

Special Cases

If the database server and concurrent manager server are on different hosts, make the following changes to the TKprof script (LTKPROF.prog), which is located in the Logical Apps binary directory on the concurrent manager server. (The changed lines are shown in boldface.) The value <db_login> is the database server name, and the value <db_hostname> is the user name to log on to the database server.

```
#!/bin/sh
oracle_login=$1
tempfile=$$latkprof.txt
temptrc=$$latkprof.trc
echo Temp file $tempfile
echo tkprof directory "$5"
pwd
tkfiles=`ssh <db_login>@<db_hostname> ls $5`
for i in $tkfiles
do
echo processing $i
scp <db_login>@<db_hostname>:$i /tmp/$temptrc
tkprof /tmp/$temptrc /tmp/$tempfile explain=$1
cat /tmp/$tempfile
rm /tmp/$tempfile
rm /tmp/$temptrc
done
```

If you have multiple APPS schemas, the LA_ENHNCMTMGR_PKG must be created as a synonym under each of these schemas. To perform this operation, run the following command:

```
create synonym LA_ENHNCMTMGR_PKG for apps.LA_ENHNCMTMGR_PKG
```


If this is not set, the following error message appears when a user attempts to log on to a read-only or MRC (multiple reporting currency) responsibility:

```
la_enhncmtmgr_pkg not declared
```


Validation

As a part of the installation process, the Installer programs complete several “behind-the-scenes” tasks. Open Oracle Applications forms to confirm that these tasks have been completed. (As you perform these validation steps, you may be instructed to “query for” a value. If so, press the F11 key, type the specified value in a specified field, and press Ctrl+F11.)

- 1 Log on to the System Administrator responsibility in Oracle Applications.
- 2 Select Application, then Register.
- 3 In the Application field, query for Logical Apps Custom. The form should contain the following values:



Application	Short Name	Basepath	Description
Logical Apps Custom	XXLAAPPS	XXLAAPPS_TOP	Logical Apps Custom Application

- 4 Switch to the Application Developer responsibility. (Select File in the menu bar, then Switch Responsibility in the File menu; then select Application Developer in the Responsibilities form.) In the Application Developer Navigator, double-click on Application, then Form. In the Form field, query on LABIZ. The form should contain the following values:

Form	Application	User Form Name	Description
LABIZ	Logical Apps Custom	AppsRules	Logical Apps AppsRules

- 5 Switch back to the System Administrator responsibility. In its Navigator, select Security, then Responsibility, then Request. In the Request Groups form, query for the Logical Apps Request Group. The form should contain the following values:

Group: LogicalApps Request Group

Application: Logical Apps Custom

Code: LOGAPPSRG

Description: Request Group for LogicalApps Applications

Requests

Type	Name	Application
Application	Logical Apps Custom	Logical Apps Custom

Description: Logical Apps Custom Application

- 6 Still in the System Administrator responsibility, select Application, then Menu in the Navigator. In the Menus form, query for LAAR_NAVIGATE and confirm the values shown in the following illustration. (Note that the illustration is a composite, showing entries that would appear if you were to use the scroll bar in the Menus form.)

Seq	Prompt	Submenu	Function	Description	Grant
10	AppsRules		Appsrules	LogicalApps AppsRules	☒
20			AppsExtend	LogicalApps AppsExtend	☒
30			AppsExtend Value Form	AppsExtend Value form function	☒
40			AppsFlow Constraints	AppsFlow Constraints form functi	☒
50			AppsMigrate	AppsRules Migration form functio	☒
60			AppsRules Libraries	AppsRules Libraries form function	☒
70			AppsWatch	AppsWatch form function	☒
80			Appsrules Audit	AppsRules Audit form function	☒
85			Flexfield Values	FND Flexfields	☒
90	Requests: Run		LogicalApps Reports	LogicalApps SRS	☒
110			AppsFlow	AppsFlow form function	☒
120	Find Processes		Find Processes	Find Workflow Processes Functio	☒
130	Find Notification		Find Notifications	Find Workflow Notifications Func	☒
150			AppsAudit	AppsAudit form function	☒
160			AppsAudit Online	AppsAudit Online form function	☒
170			AppsAudit Report	AppsAudit Report form function	☒
205	AppsAccess - De		AppsAccess Define Con	AppsAccess - Define Conflict Rule	☒
210	AppsAccess - Us		AppsAccess User Confl	AppsAccess - User Conflict Approv	☒
215			AppsAccess Global Sub	AppsAccess - Global Subscribers	☒
220			AppsAccess Activate Re	AppsAccess - Activate Responsibi	☒
225			AppsAccess Function W	AppsAccess - Function Where Use	☒
410	AppsControl		AppsControl Wizard	Logical Apps AppsControl Wizard	☒
420			AppsControl Change Re	Logical Apps AppsControl Reasor	☒
911			Mass Associate Function	Mass Associate Function	☒
999	Install History		Logical Apps Installatio	Logical Apps Products Installatio	☒

If you are upgrading from an earlier version, the menu may contain an obsolete item and may lack two new items. Check that entries appear at sequence numbers 205 and 210, and contain the following values. If not, create the entries manually.

- Sequence 205: Prompt is “AppsAccess - Define Conflict Rules”; Submenu is blank; Function is “AppsAccess Define Conflict Rules”; Description is “AppsAccess - Define Conflict Rules”; Grant box is checked.
- Sequence 210: Prompt is “AppsAccess - User Conflict Approval”; Submenu is blank; Function is “AppsAccess User Conflict Approval”; Description is “AppsAccess - User Conflict Approval”; Grant box is checked.

Also, delete an entry with the value “AppsAccess” in the Prompt and Function columns, if one exists.

- 7 In the System Administrator Navigator, select Security, then Responsibility, then Define. In the Responsibilities form, query for Logical Apps. (This is the responsibility you would assign to Oracle Applications User so that they can use Logical Apps applications.)

Switch to the Logical Apps responsibility and, in the Logical Apps Navigator, select AppsRules. Then do the following:


- 1 Select Tools in the menu bar, then Logical Apps Configuration in the Tools menu.
- 2 An AppsRules Configurations form appears. Confirm that a value displayed in the UTL Path field:

- 3 The UTL Path field value should match the name of one of the directories set for UTL PATH in your environment. To confirm that it does, run the following SQL query to generate a list of those directories:


```
select value from gv$parameter where name='utl_file_dir'
```

Finally, confirm that appropriate values have been set for AppsRules libraries:

- 1 With AppsRules open, click on Logical Apps Utilities in the menu bar, then on AppsRules Libraries in the Logical Apps Utilities menu.
- 2 With a Logical Apps Libraries form open, click on Tools in the menu bar, then on Value Sets in the Tools menu.
- 3 In the Name field of the Find Value Set form, enter the value *LA%* and click on the Find button.



- 4 Select (one at a time) the LAAC_CATEGORY, LAAR_LIBRARY_MODULES, and LAAR_LIBRARY_THEME entries. For each, confirm that a Segment Values form displays the value *ALL* in the Values field of the Values, Effective tab. For example:



Installation History

You can review information about the installation of files for your AppsRules implementation. To do so:

- 1 Log on to the Logical Apps responsibility.
- 2 In the Navigator, select Install History. The Installation History form appears:

Install Datetime	Release	Component	Host Name	Install Status	Product	User Name	Schema	Staging Dir
07-JUL-2005 10:06:01	6.5.3	FRM	vail	SUCCESS	AppsCore	oracle	XXLAAPPS	/home/oracle/dtstage/FRM
07-JUL-2005 10:06:01	6.5.3	FRM	vail	SUCCESS	AppsForm	oracle	XXLAAPPS	/home/oracle/dtstage/FRM
07-JUL-2005 10:06:01	6.5.3	FRM	vail	SUCCESS	AppsAudit	oracle	XXLAAPPS	/home/oracle/dtstage/FRM
07-JUL-2005 10:06:01	6.5.3	FRM	vail	SUCCESS	AppsControl	oracle	XXLAAPPS	/home/oracle/dtstage/FRM
07-JUL-2005 10:06:01	6.5.3	FRM	vail	SUCCESS	AppsAccess	oracle	XXLAAPPS	/home/oracle/dtstage/FRM
07-JUL-2005 10:06:01	6.5.3	FRM	vail	SUCCESS	AppsFlow	oracle	XXLAAPPS	/home/oracle/dtstage/FRM
07-JUL-2005 09:59:57	6.5.3	DB	vail	SUCCESS	AppsCore	oracle	XXLAAPPS	/home/oracle/dtstage/DB_0
07-JUL-2005 09:59:57	6.5.3	DB	vail	SUCCESS	AppsForm	oracle	XXLAAPPS	/home/oracle/dtstage/DB_0
07-JUL-2005 09:59:57	6.5.3	DB	vail	SUCCESS	AppsAudit	oracle	XXLAAPPS	/home/oracle/dtstage/DB_0
07-JUL-2005 09:59:57	6.5.3	DB	vail	SUCCESS	AppsFlow	oracle	XXLAAPPS	/home/oracle/dtstage/DB_0

Installed Files...

Each row provides information about the installation of a LogicalApps program element — for example, the top row in this illustration shows that the AppsCore element for version 6.5.3 of the forms server was successfully installed. Because there are several elements for each of the forms and database servers, a single installation of AppsRules fills multiple rows in the grid — for example, all of the rows in this illustration pertain to an installation performed on the seventh of July.


- 3 To view a list of the files installed for a given element, click on the row for that element and then on the Installed Files button. The following form appears:

Product	Filename	Revision	Install Status
AppsCore	CUSTOM.pll	1.0	Success
AppsCore	LAADDFUNC.fmb	1.0	Success
AppsCore	LAAEELM.fmb	1.0	Success
AppsCore	LAAFACCOBJ.fmb	1.0	Success
AppsCore	LAAFCONST.fmb	1.0	Success
AppsCore	LAAFLOW.fmb	1.0	Success
AppsCore	LAAPEN.fmb	1.0	Success
AppsCore	LAAPPSAUDIT.fmb	1.0	Success
AppsCore	LAAPPSAUDITREPORT.fmb	1.0	Success
AppsCore	LAAUDIT.fmb	1.0	Success

Close

Click on the Close button to clear this form.

- 4 Finally, to review information about all currently installed files (regardless of whether they were added in the most recent installation), click on the Current File Versions tab:



File Name	Revision	Install Time	Product	Release	Component	Install Status
CUSTOM.pll	1.0	07 JUL 2005 10:06:01	AppsCore	6.5.3	FRM	Success
CustomException.java	1.0	07 JUL 2005 09:59:57	AppsCore	6.5.3	DB	Success
EntityName.java	1.0	07 JUL 2005 09:59:57	AppsCore	6.5.3	DB	Success
IOUtil.java	1.0	07 JUL 2005 09:59:57	AppsCore	6.5.3	DB	Success
Insert.java	1.0	07 JUL 2005 09:59:57	AppsCore	6.5.3	DB	Success
LAAACCESS.fmb	1.3	07 JUL 2005 10:06:01	AppsAccess	6.5.3	FRM	Success
LAACONACC.rdf	1.0	07 JUL 2005 09:59:57	AppsAccess	6.5.3	DB	Success
LAACONACC_T.rdf	1.0	07 JUL 2005 09:59:57	AppsAccess	6.5.3	DB	Success
LAACONACR.rdf	1.0	07 JUL 2005 09:59:57	AppsAccess	6.5.3	DB	Success
LAACONACR_T.rdf	1.0	07 JUL 2005 09:59:57	AppsAccess	6.5.3	DB	Success
LAACONRS.rdf	1.0	07 JUL 2005 09:59:57	AppsAccess	6.5.3	DB	Success
LAACONRS.T.rdf	1.0	07 JUL 2005 09:59:57	AppsAccess	6.5.3	DB	Success

- 5 To close the Installation History form, click on its × symbol.

