

Mapping and Simple Transformation Document

Related Mapping (copy from related mapping)

Mapping Name
RDM PO Receipt Create

Mapping Participants	
Application	RDM
Type	POReceiptDesc.dtd

XML Tag Name	Included Mapping	Cardinality of included mapping	Table Name	Column Name	Data Type	Length	Permissible values and descriptions	Keys (pk)	Required? (yes/no)
dc_dest_id			TRANSSHIPMENT_SETUP	DC_DEST_ID	VARCHAR2	10			
appt_nbr			RECEIPT_TO_UPLOAD	APPT_NBR	NUMBER	9	Unique identifier for receiving a group of items		YES
po_nbr			RECEIPT_TO_UPLOAD	PO_NBR	VARCHAR2	10	Unique Purchase Order identifier		YES
document_type			PO	DOCUMENT_TYPE	VARCHAR2	1	Used to indicate the PO type. Values are 'T' or 'P'.		
item_id			RECEIPT_TO_UPLOAD	ITEM_ID	VARCHAR2	25	Uniquely identifies the item. May consist of some combination of SKU, style, color, size, etc.		YES
unit_qty			RECEIPT_TO_UPLOAD	UNIT_QTY	NUMBER	12,4	Number of individual units		YES
receipt_xactn_type			RECEIPT_TO_UPLOAD	RECEIPT_XACTN_TYPE	CHAR	1	Transaction Type; Values R= receipt which indicates items received. A: Receipt Adjustment T: Transshipment X: Transshipment adjustment		YES
receipt_date			RECEIPT_TO_UPLOAD	RECEIPT_DATE	DATE		The date on which a receipt took place.		
receipt_nbr			RECEIPT_TO_UPLOAD	RECEIPT_NBR	NUMBER	9	A value which uniquely identifies a receipt transaction.		YES
asn_nbr			RECEIPT_TO_UPLOAD	ASN_NBR	VARCHAR2	30	Advance ship notice number		

Mapping and Simple Transformation Document

Related Mapping (copy from related mapping)

Mapping Name
RDM PO Receipt Create

Mapping Participants	
Application	RDM
Type	POReceiptDesc.dtd

XML Tag Name	Included Mapping	Cardinality of included mapping	Table Name	Column Name	Data Type	Length	Permissible values and descriptions	Keys (pk)	Required? (yes/no)
dest_id			RECEIPT_TO_UPLOAD	DEST_ID	VARCHAR2	10	A number which uniquely identifies a destination to which the DC delivers goods		
container_id			RECEIPT_TO_UPLOAD	CONTAINER_ID	VARCHAR2	20	Unique identifier for a container. A container is a generic thing that can hold merchandise or other containers. This could be carton, pallet, tote, trolley, laundry basket, etc.		
distro_nbr			RECEIPT_TO_UPLOAD	DISTRO_NBR	VARCHAR2	10			
distro_doc_type			RECEIPT_TO_UPLOAD	DISTRO_DOC_TYPE	VARCHAR2	1	Valid values are A,D,T,C,V		
to_disposition			RECEIPT_TO_UPLOAD	TO_DISPOSITION	VARCHAR2	6	Valid values are Unavailable, Trouble, Distributed, Available		
from_disposition			RECEIPT_TO_UPLOAD	FROM_DISPOSITION	VARCHAR2	6	Always NULL for Add		
to_wip			RECEIPT_TO_UPLOAD	TO_WIP	VARCHAR2	6	Work in Process Code		
from_wip			RECEIPT_TO_UPLOAD	FROM_WIP	VARCHAR2	6	Work in Process Code		
to_trouble			RECEIPT_TO_UPLOAD	TO_TROUBLE	VARCHAR2	2	Value describing a trouble condition		
from_trouble			RECEIPT_TO_UPLOAD	FROM_TROUBLE	VARCHAR2	2	Value describing a trouble condition		
user_id			RECEIPT_TO_UPLOAD	USER_ID	VARCHAR2	10	Unique identifier for a user		