

Retek® Price Management™ 10.1.5

Installation Guide

Corporate Headquarters:

Retek Inc.
Retek on the Mall
950 Nicollet Mall
Minneapolis, MN 55403
USA
888.61.RETEK (toll free US)
Switchboard:
+1 612 587 5000
Fax:
+1 612 587 5100

European Headquarters:

Retek
110 Wigmore Street
London
W1U 3RW
United Kingdom
Switchboard:
+44 (0)20 7563 4600
Sales Enquiries:
+44 (0)20 7563 46 46
Fax:
+44 (0)20 7563 46 10

The software described in this documentation is furnished under a license agreement, is the confidential information of Retek Inc., and may be used only in accordance with the terms of the agreement.

No part of this documentation may be reproduced or transmitted in any form or by any means without the express written permission of Retek Inc., Retek on the Mall, 950 Nicollet Mall, Minneapolis, MN 55403, and the copyright notice may not be removed without the consent of Retek Inc.

Information in this documentation is subject to change without notice.

Retek provides product documentation in a read-only-format to ensure content integrity. Retek Customer Support cannot support documentation that has been changed without Retek authorization.

The functionality described herein applies to this version, as reflected on the title page of this document, and to no other versions of software, including without limitation subsequent releases of the same software component. The functionality described herein will change from time to time with the release of new versions of software and Retek reserves the right to make such modifications at its absolute discretion.

Retek® Price Management™ is a trademark of Retek Inc.

Retek and the Retek logo are registered trademarks of Retek Inc.

This unpublished work is protected by confidentiality agreement, and by trade secret, copyright, and other laws. In the event of publication, the following notice shall apply:

©2005 Retek Inc. All rights reserved.

All other product names mentioned are trademarks or registered trademarks of their respective owners and should be treated as such.

Printed in the United States of America.

Customer Support

Customer Support hours

Customer Support is available 7x24x365 via email, phone, and Web access.

Depending on the Support option chosen by a particular client (Standard, Plus, or Premium), the times that certain services are delivered may be restricted. Severity 1 (Critical) issues are addressed on a 7x24 basis and receive continuous attention until resolved, for all clients on active maintenance. Retek customers on active maintenance agreements may contact a global Customer Support representative in accordance with contract terms in one of the following ways.

Contact Method	Contact Information
----------------	---------------------

E-mail	support@retex.com
--------	-------------------

Internet (ROCS)	rocs.retek.com Retek's secure client Web site to update and view issues
-----------------	---

Phone	+1 612 587 5800
-------	-----------------

Toll free alternatives are also available in various regions of the world:

Australia	+1 800 555 923 (AU-Telstra) or +1 800 000 562 (AU-Optus)
France	0800 90 91 66
Hong Kong	800 96 4262
Korea	00 308 13 1342
United Kingdom	0800 917 2863
United States	+1 800 61 RETEK or 800 617 3835

Mail	Retek Customer Support Retek on the Mall 950 Nicollet Mall Minneapolis, MN 55403
------	---

When contacting Customer Support, please provide:

- Product version and program/module name.
- Functional and technical description of the problem (include business impact).
- Detailed step-by-step instructions to recreate.
- Exact error message received.
- Screen shots of each step you take.
- WebEx recording of recreation (when applicable).

Contents

Chapter 1 – Database server installation instructions.....	1
Mount CD-ROM on the Database Server	1
Update DDL.....	2
Update packages, stored procedures and functions	2
Chapter 2 – Application Server installation instructions.....	3
UNIX (Sun Solaris/HPUX/AIX)	3
Copy and unpack install files from CDROM	3
Deploy the RPM War File into the Default OC4J Application	3
Start/Stop/Load the default OC4J application	3
Edit the file db.properties	4
Reload the default OC4J application	5
Chapter 3 – Applying source code	7

Chapter 1 – Database server installation instructions

Before you apply the RPM 10.1.5 patch:

- Check that RMS 10.1.12 is installed.
- Check that RPM 10.1.4 is installed.
- Review the enclosed RPM 10.1.5 Patch Release Notes (rpm-1015-rn.pdf).
- Review each of the enclosed SIR documents.

Before copying over any files:

- Note whether customizations have been made to the module. If so, then the customizations must be reapplied over the new version of the module (or the fix may need to be applied to the custom version of the code). Please refer to Chapter 2.
- Copy the original files to a different directory before copying over them in case they need to be referred to at a later date.



Note: Normally OC4J is installed in an existing Oracle 9iAS (9IAS_ORACLE_HOME) location. However, OC4J can be installed and run outside 9IAS_ORACLE_HOME. For this reason, ORACLE_HOME refers to the location where OC4J will be installed.



Note: JDK 1.3.x is a requirement for both OC4J and RPM

Mount CD-ROM on the Database Server

1. Mount the CD-ROM on your Database Server.
2. Copy the rpm1015dbpatch.tar.z file from the CD /dbserverunix directory to a newly created staging directory on your UNIX server.
3. Log in to UNIX.
4. Change directories to the staging directory.



Note: The tar file must have a .Z extension.

5. If the tar file has a “z” in lowercase, change it by typing:

```
mv rpm1015dbpatch.tar.z rpm1015dbpatch.tar.Z
```
6. Uncompress the tar file by entering:

```
uncompress rpm1015dbpatch.tar.Z
```
7. Untar the tar file by entering:

```
tar xvf rpm1015dbpatch.tar
```

Update DDL

1. Change directories to <staging area>/dbcs.
2. Review and understand the scripts before running them.
3. If you have customized any objects, make modifications.
4. Log in to SQLPLUS as the rmsdev10 user.
5. Enter the following command:

```
SQL> @patch1015dbcs.sql
```
6. View the spool file patch1015dbcs.log when finished to verify that no errors were found.

Update packages, stored procedures and functions

1. On the server, change directories to <staging area>/db_objects.
2. Log in to SQLPLUS as rmsdev10.
3. Enter the following command to update packages, procedures, and functions:

```
SQL> @patch1015rpm.sql
```
4. Exit SQLPlus.
5. View the spool file patch1015rpm.log when finished to verify that no errors were found.

Chapter 2 – Application Server installation instructions

UNIX (Sun Solaris/HPUX/AIX)

Copy and unpack install files from CDROM

1. Mount the CD-ROM on your UNIX Application Server.
2. Change directories to /appserverunix.
3. Copy the rpm1015apppatch.tar file from the CD /appserverunix directory to a newly created staging directory on your UNIX Application server.
4. Log in to UNIX.
5. Change directories to the staging directory.
6. Untar the tar file by entering:

```
tar xvf rpm1015apppatch.tar
```

Deploy the RPM War File into the Default OC4J Application



Note: J2EE_HOME refers to \$ORACLE_HOME/j2ee/home.



Note: The variable <product> refers to the name of the rpm.war file

1. Back up the following objects currently deployed in \$J2EE_HOME/applications:
 - rpm.war
 - rpm/



Note: This is the directory that was created when deploying the rpm.war file just backed up

2. Copy the new rpm.war file from <staging directory>/ to \$J2EE_HOME/applications.

Start/Stop/Load the default OC4J application

1. First to stop the default OC4J container if you haven't done so already, issue the following command in \$J2EE_HOME:

```
> java -jar admin.jar ormi://<server_name>/ <admin_id>  
<admin_password> -shutdown -force
```



Note: <server_name> is the name of the server or it's IP address. <admin_id> and <admin_password> are the administration username and password supplied during the OC4J install.



Example: java -jar admin.jar ormi:/retekdev10/ admin admin -shutdown -force

2. To start the default OC4J container, issue the following command in \$J2EE_HOME:

```
> java -jar oc4j.jar &
```

“Oracle9iAS (1.0.2.2.1) Containers for J2EE initialized” (or similar) is displayed at the command line after successful startup.

Edit the file db.properties

1. Change directories to \$J2EE_HOME/applications/rpm/WEB-INF/classes/com/retek/rpm/util/conf.
2. Edit db.properties; the values to be changed are:

```
rms.url=jdbc:oracle:thin:@<database server>:<port>:<database sid>  
rms.user=<rms schema owner>  
rms.password=<rms schema password>
```

Where:

- Database server = machine name of server where the database resides
- port = Oracle database port
- database sid = Oracle database sid name
- rms schema owner = name of the RMS 10.1.x database schema
- rms schema password = RMS 10.1.x database schema password



Example: rms.url=jdbc:oracle:thin:@retekdev10:1521:rms109i
rms.user=rms10
rms.password=retex
rmsmaxconn=15
rms.driver=oracle.jdbc.driver.OracleDriver

```
# Set to disable rfx in the batch. Will use SQL instead  
disablerfx=true
```

```
# Set to the rfx executable  
rfxpath=C:\\dev\\rpm\\rfxFake.bat
```



Note: disablerfx and rfxpath in the db.properties file should not be changed.

Reload the default OC4J application



Note: OC4J must be reloaded in order for the changes made to db.properties to take effect.

1. To stop the default OC4J container, issue the following command in \$J2EE_HOME:

```
> java -jar admin.jar ormi://<server_name>/ <admin_id>  
<admin_password> -shutdown -force
```



Note: <server_name> is the name of the server or its IP address. <admin_id> and <admin_password> are the administration username and password supplied during the OC4J install.



Example: java -jar admin.jar ormi:/retekdev10/ admin admin -shutdown -force

2. To start the default OC4J container, issue the following command in \$J2EE_HOME:

```
java -jar $J2EE_HOME/oc4j.jar &
```

“Oracle9iAS (1.0.2.2.1) Containers for J2EE initialized” (or similar) is displayed at the command line after successful startup.

3. Load the new OC4J application by entering the following URL in a browser:

<http://<server>:<port>/<product>>

- server = name or IP address of the web server OC4J is running on
- port = port number set in default-web-site.xml above
- product = value of root in the web-app element of default-web-site.xml above



Example: <http://server:8388/rpm>

Chapter 3 – Applying source code

If customizations have been made to RPM, the 10.1.5 source code can be compiled and applied to the application. Compile the .java source code included on this CD, then, place the generated .class files into the appropriate directory locations.

Before applying the patch source files over existing code:

- Note whether customizations have been made to the module. If so, then the customizations must be reapplied to the new version of the module (or the fix may need to be applied to the custom version of the code).

Back up the existing RPM class files before copying over the 10.1.5 class files in order to refer to them at a later date if necessary.